
IPython Documentation

Выпуск 8.14.0.dev

The IPython Development Team

мая 04, 2023

1	Обзор	3
2	What's new in IPython	9
3	Installation	351
4	Руководство	357
5	Конфигурирование и донастройка	437
6	Developer's guide for third party tools and libraries	537
7	Guide for IPython core Developers	549
8	The IPython API	555
9	Директива IPython Sphinx	787
10	Об IPython	801
	Содержание модулей Python	811
	Алфавитный указатель	813

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

One of Python’s most useful features is its interactive interpreter. It allows for very fast testing of ideas without the overhead of creating test files as is typical in most programming languages. However, the interpreter supplied with the standard Python distribution is somewhat limited for extended interactive use.

The goal of IPython is to create a comprehensive environment for interactive and exploratory computing. To support this goal, IPython has three main components:

- An enhanced interactive Python shell.
- A decoupled *two-process communication model*, which allows for multiple clients to connect to a computation kernel, most notably the web-based notebook provided with [Jupyter](#).
- An architecture for interactive parallel computing now part of the `ipyparallel` package.

All of IPython is open source (released under the revised BSD license).

1.1 Улучшенная интерактивная оболочка Python

IPython’s interactive shell (`ipython`), has the following goals, amongst others:

1. Provide an interactive shell superior to Python’s default. IPython has many features for tab-completion, object introspection, system shell access, command history retrieval across sessions, and its own special command system for adding functionality when working interactively. It tries to be a very efficient environment both for Python code development and for exploration of problems using Python objects (in situations like data analysis).
2. Serve as an embeddable, ready to use interpreter for your own programs. An interactive IPython shell can be started with a single call from inside another program, providing access to the current namespace. This can be very useful both for debugging purposes and for situations where a blend of batch-processing and interactive exploration are needed.

3. Offer a flexible framework which can be used as the base environment for working with other systems, with Python as the underlying bridge language. Specifically scientific environments like Mathematica, IDL and Matlab inspired its design, but similar ideas can be useful in many fields.
4. Allow interactive testing of threaded graphical toolkits. IPython has support for interactive, non-blocking control of GTK, Qt, WX, GLUT, and OS X applications via special threading flags. The normal Python shell can only do this for Tkinter applications.

1.1.1 Основные возможности интерактивной оболочки

- Dynamic object introspection. One can access docstrings, function definition prototypes, source code, source files and other details of any object accessible to the interpreter with a single keystroke (`?`, and using `??` provides additional detail).
- Searching through modules and namespaces with `*` wildcards, both when using the `?` system and via the `%psearch` command.
- Completion in the local namespace, by typing `TAB` at the prompt. This works for keywords, modules, methods, variables and files in the current directory. This is supported via the `prompt_toolkit` library. Custom completers can be implemented easily for different purposes (system commands, magic arguments etc.)
- Numbered input/output prompts with command history (persistent across sessions and tied to each profile), full searching in this history and caching of all input and output.
- User-extensible „magic“ commands. A set of commands prefixed with `%` or `%%` is available for controlling IPython itself and provides directory control, namespace information and many aliases to common system shell commands.
- Alias facility for defining your own system aliases.
- Complete system shell access. Lines starting with `!` are passed directly to the system shell, and using `!!` or `var = !cmd` captures shell output into python variables for further use.
- The ability to expand python variables when calling the system shell. In a shell command, any python variable prefixed with `$` is expanded. A double `$$` allows passing a literal `$` to the shell (for access to shell and environment variables like `PATH`).
- Filesystem navigation, via a magic `%cd` command, along with a persistent bookmark system (using `%bookmark`) for fast access to frequently visited directories.
- A lightweight persistence framework via the `%store` command, which allows you to save arbitrary Python variables. These get restored when you run the `%store -r` command.
- Automatic indentation and highlighting of code as you type (through the `prompt_toolkit` library).
- Macro system for quickly re-executing multiple lines of previous input with a single name via the `%macro` command. Macros can be stored persistently via `%store` and edited via `%edit`.
- Session logging (you can then later use these logs as code in your programs). Logs can optionally timestamp all input, and also store session output (marked as comments, so the log remains valid Python source code).
- Session restoring: logs can be replayed to restore a previous session to the state where you left it.
- Verbose and colored exception traceback printouts. Easier to parse visually, and in verbose mode they produce a lot of useful debugging information (basically a terminal version of the `cgitb` module).
- Auto-parentheses via the `%autocall` command: callable objects can be executed without parentheses: `sin 3` is automatically converted to `sin(3)`

- Auto-quoting: using `,` or `;` as the first character forces auto-quoting of the rest of the line: `, my_function a b` becomes automatically `my_function("a","b")`, while `;my_function a b` becomes `my_function("a b")`.
- Extensible input syntax. You can define filters that pre-process user input to simplify input in special situations. This allows for example pasting multi-line code fragments which start with `>>>` or `...` such as those from other python sessions or the standard Python documentation.
- Flexible *configuration system*. It uses a configuration file which allows permanent setting of all command-line options, module loading, code and file execution. The system allows recursive file inclusion, so you can have a base file with defaults and layers which load other customizations for particular projects.
- Embeddable. You can call IPython as a python shell inside your own python programs. This can be used both for debugging code or for providing interactive abilities to your programs with knowledge about the local namespaces (very useful in debugging and data analysis situations).
- Easy debugger access. You can set IPython to call up an enhanced version of the Python debugger (pdb) every time there is an uncaught exception. This drops you inside the code which triggered the exception with all the data live and it is possible to navigate the stack to rapidly isolate the source of a bug. The `%run` magic command (with the `-d` option) can run any script under pdb's control, automatically setting initial breakpoints for you. This version of pdb has IPython-specific improvements, including tab-completion and traceback coloring support. For even easier debugger access, try `%debug` after seeing an exception.
- Profiler support. You can run single statements (similar to `profile.run()`) or complete programs under the profiler's control. While this is possible with standard cProfile or profile modules, IPython wraps this functionality with magic commands (see `%prun` and `%run -p`) convenient for rapid interactive work.
- Simple timing information. You can use the `%timeit` command to get the execution time of a Python statement or expression. This machinery is intelligent enough to do more repetitions for commands that finish very quickly in order to get a better estimate of their running time.

```
In [1]: %timeit 1+1
10000000 loops, best of 3: 25.5 ns per loop

In [2]: %timeit [math.sin(x) for x in range(5000)]
1000 loops, best of 3: 719 µs per loop
```

To get the timing information for more than one expression, use the `%timeit` cell magic command.

- Doctest support. The special `%doctest_mode` command toggles a mode to use doctest-compatible prompts, so you can use IPython sessions as doctest code. By default, IPython also allows you to paste existing doctests, and strips out the leading `>>>` and `...` prompts in them.

1.2 Несвязанная двухпроцессная модель

IPython has abstracted and extended the notion of a traditional *Read-Evaluate-Print Loop* (REPL) environment by decoupling the *evaluation* into its own process. We call this process a **kernel**: it receives execution instructions from clients and communicates the results back to them.

This decoupling allows us to have several clients connected to the same kernel, and even allows clients and kernels to live on different machines. With the exclusion of the traditional single process terminal-based IPython (what you start if you run `ipython` without any subcommands), all other IPython machinery uses this two-process model. Most of this is now part of the **Jupyter** project, which includes `jupyter console`, `jupyter qtconsole`, and `jupyter notebook`.

As an example, this means that when you start `jupyter qtconsole`, you're really starting two processes, a kernel and a Qt-based client which can send commands to and receive results from that kernel. If there is already a kernel running that you want to connect to, you can pass the `--existing` flag which will skip initiating a new kernel and connect to the most recent kernel, instead. To connect to a specific kernel once you have several kernels running, use the `%connect_info` magic to get the unique connection file, which will be something like `--existing kernel-19732.json` but with different numbers which correspond to the Process ID of the kernel.

You can read more about using `jupyter qtconsole`, and `jupyter notebook`. There is also a [message spec](#) which documents the protocol for communication between kernels and clients.

См.также:

[Frontend/Kernel Model example notebook](#)

1.3 Интерактивные параллельные вычисления

This functionality is optional and now part of the `ipyparallel` project.

1.3.1 Переносимость и требования к Python

Version 7.0+ supports Python 3.4 and higher. Versions 6.x support Python 3.3 and higher. Versions 2.0 to 5.x work with Python 2.7.x releases and Python 3.3 and higher. Version 1.0 additionally worked with Python 2.6 and 3.2. Version 0.12 was the first version to fully support Python 3.

IPython is known to work on the following operating systems:

- Linux
- Most other Unix-like OSs (AIX, Solaris, BSD, etc.)
- Mac OS X
- Windows (CygWin, XP, Vista, etc.)

See [here](#) for instructions on how to install IPython.

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

What's new in IPython

Development version in-progress features:

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

2.1 Development version

This document describes in-flight development work.

Предупреждение: Please do not edit this file by hand (doing so will likely cause merge conflicts for other Pull Requests). Instead, create a new file in the `docs/source/whatsnew/pr` folder

Released, 2019

Need to be updated:

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

2.1.1 Antigravity feature

Example new antigravity feature. Try `import antigravity` in a Python 3 console.

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

2.1.2 Incompatible change switch to perl

Document which filename start with `incompat-` will be gathers in their own incompatibility section.

Starting with IPython 42, only perl code execution is allowed. See [PR #42](#)

2.1.3 Backwards incompatible changes

This section documents the changes that have been made in various versions of IPython. Users should consult these pages to learn about new features, bug fixes and backwards incompatibilities. Developers should summarize the development work they do here in a user friendly format.

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

2.2 8.x Series

2.2.1 IPython 8.13

As usual for the end of the month, minor release of IPython. This release is significant in that it not only has a number of bugfixes, but also drop support for Python 3.8 as per NEP 29 ([PR #14023](#)).

All the critical bugfixes have been backported onto the 8.12.1 release (see below). In addition to that went into 8.12.1 you'll find:

- Pretty representation for `Counter` has been fixed to match the Python one and be in decreasing order. [PR #14032](#)
- Module completion is better when jedi is disabled [PR #14029](#).
- Improvement of `%bash` magic that would get stuck [PR #14019](#)

We hope you enjoy this release and will maybe see you at JupyterCon in less than two weeks.

As usual you can find the full list of PRs on GitHub under [the 8.12.1 milestone](#).

Thanks to the D.E. Shaw group for the request and sponsoring the work.

2.2.2 IPython 8.12.1

This is the twin release of IPython 8.13 that contain only critical UI and bug fixes. The next minor version of IPython has dropped support for Python 3.8 – as per NEP 29 and this IPython 8.12.x will now only receive bugfixes.

- [PR #14004](#) Fix a bug introduced in IPython 8.12 that crash when inspecting some docstrings.
- [PR #14010](#) Fix fast traceback code that was not working in some case.
- [PR #14014](#) Fix `%page` magic broken in some case.
- [PR #14026](#), [PR #14027](#) Tweak default shortcut with respect to autosuggestions.
- [PR #14033](#) add back the ability to use `.get()` on `OInfo` object for backward compatibility with `h5py` (this will be re-deprecated later, and `h5py` will also get a fix).

As usual you can find the full list of PRs on GitHub under [the 8.12.1 milestone](#).

Thanks to the D.E. Shaw group for the request and sponsoring the work.

2.2.3 IPython 8.12

Hopefully slightly early release for IPython 8.12. Last Thursday of the month, even if I guess it's likely already Friday somewhere in the pacific ocean.

A number of PRs and bug fixes this month with close to 20 PRs merged !

The IPython repo reached [PR #14000](#) !! Actually the PR that create those exact release note is [PR #14000](#). Ok, more issues and PR is not always better, and I'd love to have more time to close issues and Pull Requests.

Let's note that in less than 2 month JupyterCon is back, in Paris please visit jupytercon.com, and looking forward to see you there.

Packagers should take note that `typing_extension` is now a mandatory dependency for Python versions <3.10.

Let's note also that according to [NEP29](#), It is soon time to stop support for Python 3.8 that will be release more than 3 and 1/2 years ago:

On Apr 14, 2023 drop support for Python 3.8 (initially released on Oct 14, 2019)

Thus I am likely to stop advertising support for Python 3.8 in the next release at the end of April.

Here are some miscellaneous updates of interest:

- [PR #13957](#) brings updates to the Qt integration, particularly for Qt6.
- [PR #13960](#) fixes the %debug magic command to give access to the local scope.
- [PR #13964](#) fixes some crashes with the new fast traceback code. Note that there are still some issues with the fast traceback code, and I a, likely to fix and tweak behavior.
- [PR #13973](#) We are slowly migrating IPython internals to use proper type objects/dataclasses instead of dictionaries to allow static typing checks. These are technically public API and could lead to breakage, so please let us know if that's the case and I'll mitigate.
- [PR #13990](#), [PR #13991](#), [PR #13994](#) all improve keybinding and shortcut configurability.

As usual you can find the full list of PRs on GitHub under [the 8.12 milestone](#).

We want to thank the D.E. Shaw group for requesting and sponsoring the work on the following big feature. We had productive discussions on how to best expose this feature

Dynamic documentation dispatch

We are experimenting with dynamic documentation dispatch for object attribute. See [#13860](#). The goal is to allow object to define documentation for their attributes, properties, even when those are dynamically defined with `__getattr__`.

In particular when those objects are base types it can be useful to show the documentation

```
In [1]: class User:
...:
...:     __custom_documentations__ = {
...:         "first": "The first name of the user.",
...:         "last": "The last name of the user.",
...:     }
...:
...:     first:str
...:     last:str
...:
...:     def __init__(self, first, last):
...:         self.first = first
...:         self.last = last
...:
...:     @property
...:     def full(self):
...:         """`self.first` and `self.last` joined by a space."""
...:         return self.first + " " + self.last
...:
...:     user = Person('Jane', 'Doe')
```

(continues on next page)

(продолжение с предыдущей страницы)

```
In [2]: user.first?
Type:          str
String form:    Jane
Length:        4
Docstring:      the first name of a the person object, a str
Class docstring:
....

In [3]: user.last?
Type:          str
String form:    Doe
Length:        3
Docstring:      the last name, also a str
...
```

We can see here the symmetry with IPython looking for the docstring on the properties:

```
In [4]: user.full?
HERE
Type:      property
String form: <property object at 0x102bb15d0>
Docstring: first and last join by a space
```

Note that while in the above example we use a static dictionary, libraries may decide to use a custom object that define `__getitem__`, we caution against using objects that would trigger computation to show documentation, but it is sometime preferable for highly dynamic code that for example export an API as object.

2.2.4 IPython 8.11

Back on almost regular monthly schedule for IPython with end-of-month really-late-Friday release to make sure some bugs are properly fixed. Small addition of with a few new features, bugfix and UX improvements.

This is a non-exhaustive list, but among other you will find:

Faster Traceback Highlighting

Resurrection of pre-IPython-8 traceback highlighting code.

Really long and complicated files were slow to highlight in traceback with IPython 8 despite upstream improvement that make many case better. Therefore starting with IPython 8.11 when one of the highlighted file is more than 10 000 line long by default, we'll fallback to a faster path that does not have all the features of highlighting failing AST nodes.

This can be configured by setting the value of `IPython.code.ultratb.FAST_THRESHOLD` to an arbitrary low or large value.

Autoreload verbosity

We introduce more descriptive names for the `%autoreload` parameter:

- `%autoreload now` (also `%autoreload`) - perform autoreload immediately.
- `%autoreload off` (also `%autoreload 0`) - turn off autoreload.
- `%autoreload explicit` (also `%autoreload 1`) - turn on autoreload only for modules whitelisted by `%import` statements.
- `%autoreload all` (also `%autoreload 2`) - turn on autoreload for all modules except those blacklisted by `%import` statements.
- `%autoreload complete` (also `%autoreload 3`) - all the features of `all` but also adding new objects from the imported modules (see `IPython/extensions/tests/test_autoreload.py::test_autoload_newly_added_objects`).

The original designations (e.g. «2») still work, and these new ones are case-insensitive.

Additionally, the option `--print` or `-p` can be added to the line to print the names of modules being reloaded. Similarly, `--log` or `-l` will output the names to the logger at INFO level. Both can be used simultaneously.

The parsing logic for `%import` is now improved such that modules can be whitelisted and blacklisted in the same line, e.g. it's now possible to call `%import os, -math` to include `os` for `%autoreload explicit` and exclude `math` for modes `all` and `complete`.

Terminal shortcuts customization

Previously modifying shortcuts was only possible by hooking into startup files and practically limited to adding new shortcuts or removing all shortcuts bound to a specific key. This release enables users to override existing terminal shortcuts, disable them or add new keybindings.

For example, to set the `right` to accept a single character of auto-suggestion you could use:

```
my_shortcuts = [
    {
        "command": "IPython:auto_suggest.accept_character",
        "new_keys": ["right"]
    }
]
%config TerminalInteractiveShell.shortcuts = my_shortcuts
```

You can learn more in [TerminalInteractiveShell.shortcuts](#) configuration reference.

Miscellaneous

- `%gui` should now support PySide6. [PR #13864](#)
- Cli shortcuts can now be configured [PR #13928](#), see above. (note that there might be an issue with `prompt_toolkit 3.0.37` and shortcut configuration).
- Capture output should now respect `;` semicolon to suppress output. [PR #13940](#)
- Base64 encoded images (in jupyter frontend), will not have trailing newlines. [PR #13941](#)

As usual you can find the full list of PRs on GitHub under [the 8.11 milestone](#).

Thanks to the [D. E. Shaw group](#) for sponsoring work on IPython and related libraries.

2.2.5 IPython 8.10

Out of schedule release of IPython with minor fixes to patch a potential CVE-2023-24816. This is a really low severity CVE that you most likely are not affected by unless:

- You are on windows.
- You have a custom build of Python without `_ctypes`
- You `cd` or start IPython or Jupyter in untrusted directory which names may be valid shell commands.

You can read more on [the advisory](#).

In addition to fixing this CVE we also fix a couple of outstanding bugs and issues.

As usual you can find the full list of PRs on GitHub under [the 8.10 milestone](#).

In Particular:

- bump minimum numpy to `>=1.21` version following NEP29. [PR #13930](#)
- fix for compatibility with MyPy 1.0. [PR #13933](#)
- fix nbgrader stalling when IPython's `showtraceback` function is monkeypatched. [PR #13934](#)

As this release also contains those minimal changes in addition to fixing the CVE I decided to bump the minor version anyway.

This will not affect the normal release schedule, so IPython 8.11 is due in about 2 weeks.

2.2.6 IPython 8.9.0

Second release of IPython in 2023, last Friday of the month, we are back on track. This is a small release with a few bug-fixes, and improvements, mostly with respect to terminal shortcuts.

The biggest improvement for 8.9 is a drastic amelioration of the auto-suggestions sponsored by D.E. Shaw and implemented by the more and more active contributor [@krassowski](#) <<https://github.com/krassowski>>.

- `right` accepts a single character from suggestion
- `ctrl+right` accepts a semantic token (macos default shortcuts take precedence and need to be disabled to make this work)
- `backspace` deletes a character and resumes hinting autosuggestions
- `ctrl-left` accepts suggestion and moves cursor left one character.
- `backspace` deletes a character and resumes hinting autosuggestions
- `down` moves to suggestion to later in history when no lines are present below the cursors.
- `up` moves to suggestion from earlier in history when no lines are present above the cursor.

This is best described by the Gif posted by [@krassowski](#) <<https://github.com/krassowski>>, and in the PR itself [PR #13888](#).

Please report any feedback in order for us to improve the user experience. In particular we are also working on making the shortcuts configurable.

If you are interested in better terminal shortcuts, I also invite you to participate in issue [13879](#).

As we follow [NEP29](#), next version of IPython will officially stop supporting numpy 1.20, and will stop supporting Python 3.8 after April release.

As usual you can find the full list of PRs on GitHub under [the 8.9 milestone](#).

Thanks to the [D. E. Shaw group](#) for sponsoring work on IPython and related libraries.

2.2.7 IPython 8.8.0

First release of IPython in 2023 as there was no release at the end of December.

This is an unusually big release (relatively speaking) with more than 15 Pull Requests merged.

Of particular interest are:

- [PR #13852](#) that replaces the greedy completer and improves completion, in particular for dictionary keys.
- [PR #13858](#) that adds `py.typed` to `setup.cfg` to make sure it is bundled in wheels.
- [PR #13869](#) that implements tab completions for IPython options in the shell when using `argcomplete` <<https://github.com/kislyuk/argcomplete>>. I believe this also needs a recent version of Traitlets.
- [PR #13865](#) makes the `Inspector` class of `InteractiveShell` configurable.
- [PR #13880](#) that removes minor-version entrypoints as the minor version entry points that would be included in the wheel would be the one of the Python version that was used to build the `whl` file.

In no particular order, the rest of the changes update the test suite to be compatible with Pygments 2.14, various docfixes, testing on more recent python versions and various updates.

As usual you can find the full list of PRs on GitHub under [the 8.8 milestone](#).

Many thanks to @krassowski for the many PRs and @jasongrout for reviewing and merging contributions.

Thanks to the [D. E. Shaw group](#) for sponsoring work on IPython and related libraries.

2.2.8 IPython 8.7.0

Small release of IPython with a couple of bug fixes and new features for this month. Next month is the end of year, it is unclear if there will be a release close to the new year's eve, or if the next release will be at the end of January.

Here are a few of the relevant fixes, as usual you can find the full list of PRs on GitHub under [the 8.7 milestone](#).

- [PR #13834](#) bump the minimum prompt toolkit to 3.0.11.
- IPython shipped with the `py.typed` marker now, and we are progressively adding more types. [PR #13831](#)
- [PR #13817](#) add configuration of code blacks formatting.

Thanks to the [D. E. Shaw group](#) for sponsoring work on IPython and related libraries.

2.2.9 IPython 8.6.0

Back to a more regular release schedule (at least I try), as Friday is already over by more than 24h hours. This is a slightly bigger release with a few new features that contain no less than 25 PRs.

We'll notably found a couple of non negligible changes:

The `install_ext` and related functions have been removed after being deprecated for years. You can use `pip` to install extensions. `pip` did not exist when `install_ext` was introduced. You can still load local extensions without installing them. Just set your `sys.path` for example. [PR #13744](#)

IPython now has extra entry points that use the major *and* *minor* version of python. For some of you this means that you can do a quick `ipython3.10` to launch IPython from the Python 3.10 interpreter, while still using Python 3.11 as your main Python. [PR #13743](#)

The completer matcher API has been improved. See [PR #13745](#). This should improve the type inference and improve dict keys completions in many use case. Thanks [@krassowski](#) for all the work, and the D.E. Shaw group for sponsoring it.

The color of error nodes in tracebacks can now be customized. See [PR #13756](#). This is a private attribute until someone finds the time to properly add a configuration option. Note that with Python 3.11 that also shows the relevant nodes in traceback, it would be good to leverage this information (plus the «did you mean» info added on attribute errors). But that's likely work I won't have time to do before long, so contributions welcome.

As we follow NEP 29, we removed support for numpy 1.19 [PR #13760](#).

The `open()` function present in the user namespace by default will now refuse to open the file descriptors 0,1,2 (stdin, out, err), to avoid crashing IPython. This mostly occurs in teaching context when incorrect values get passed around.

The `?`, `??`, and corresponding `pinfo`, `pinfo2` magics can now find objects inside arrays. That is to say, the following now works:

```
>>> def my_func(*arg, **kwargs):pass
>>> container = [my_func]
>>> container[0]?
```

If `container` define a custom `getitem`, this `__will__` trigger the custom method. So don't put side effects in your `getitem`s. Thanks to the D.E. Shaw group for the request and sponsoring the work.

As usual you can find the full list of PRs on GitHub under [the 8.6 milestone](#).

Thanks to all hacktoberfest contributors, please contribute to [closember.org](#).

Thanks to the [D. E. Shaw group](#) for sponsoring work on IPython and related libraries.

2.2.10 IPython 8.5.0

First release since a couple of month due to various reasons and timing preventing me for sticking to the usual monthly release the last Friday of each month. This is of non negligible size as it has more than two dozen PRs with various fixes an bug fixes.

Many thanks to everybody who contributed PRs for your patience in review and merges.

Here is a non-exhaustive list of changes that have been implemented for IPython 8.5.0. As usual you can find the full list of issues and PRs tagged with [the 8.5 milestone](#).

- Added a shortcut for accepting auto suggestion. The `End` key shortcut for accepting auto-suggestion. This binding works in Vi mode too, provided `TerminalInteractiveShell.emacs_bindings_in_vi_insert_mode` is set to be `True` [PR #13566](#).
- No popup in window for latex generation when generating latex (e.g. via `_latex_repr_`) no popup window is shown under Windows. [PR #13679](#)
- Fixed error raised when attempting to tab-complete an input string with consecutive periods or forward slashes (such as `«file:///var/log/...»`). [PR #13675](#)
- Relative filenames in Latex rendering: The `latex_to_png_dvipng` command internally generates input and output file arguments to `latex` and `dvipis`. These arguments are now generated as relative files to the current working directory instead of absolute file paths. This solves a problem where the current working directory contains characters that are not handled properly by `latex` and `dvips`. There are no changes to the user API. [PR #13680](#)
- Stripping decorators bug: Fixed bug which meant that ipython code blocks in restructured text documents executed with the ipython-sphinx extension skipped any lines of code containing python decorators. [PR #13612](#)
- Allow some modules with frozen dataclasses to be reloaded. [PR #13732](#)
- Fix paste magic on wayland. [PR #13671](#)
- show maxlen in deque's repr. [PR #13648](#)

Restore line numbers for Input

Line number information in tracebacks from input are restored. Line numbers from input were removed during the transition to v8 enhanced traceback reporting.

So, instead of:

```
-----
ZeroDivisionError                                Traceback (most recent call last)
Input In [3], in <cell line: 1>()
----> 1 myfunc(2)

Input In [2], in myfunc(z)
      1 def myfunc(z):
----> 2     foo.boo(z-1)

File ~/code/python/ipython/foo.py:3, in boo(x)
      2 def boo(x):
----> 3     return 1/(1-x)

ZeroDivisionError: division by zero
```

The error traceback now looks like:

```
-----
ZeroDivisionError                                Traceback (most recent call last)
Cell In [3], line 1
----> 1 myfunc(2)

Cell In [2], line 2, in myfunc(z)
      1 def myfunc(z):
```

(continues on next page)

(продолжение с предыдущей страницы)

```

----> 2     foo.boo(z-1)

File ~/code/python/ipython/foo.py:3, in boo(x)
      2 def boo(x):
----> 3     return 1/(1-x)

ZeroDivisionError: division by zero

```

or, with `xmode=Plain`:

```

Traceback (most recent call last):
  Cell In [12], line 1
      myfunc(2)
  Cell In [6], line 2 in myfunc
      foo.boo(z-1)
  File ~/code/python/ipython/foo.py:3 in boo
      return 1/(1-x)
ZeroDivisionError: division by zero

```

[PR #13560](#)

New setting to silence warning if working inside a virtual environment

Previously, when starting IPython in a virtual environment without IPython installed (so IPython from the global environment is used), the following warning was printed:

Attempting to work in a virtualenv. If you encounter problems, please install IPython inside the virtualenv.

This warning can be permanently silenced by setting `c.InteractiveShell.warn_venv` to `False` (the default is `True`).

[PR #13706](#)

Thanks to the [D. E. Shaw group](#) for sponsoring work on IPython and related libraries.

2.2.11 IPython 8.4.0

As for 7.34, this version contains a single fix: fix uncaught `BdbQuit` exceptions on `ipdb` exit [PR #13668](#), and a single typo fix in documentation: [PR #13682](#)

Thanks to the [D. E. Shaw group](#) for sponsoring work on IPython and related libraries.

2.2.12 IPython 8.3.0

- [PR #13625](#), using `?`, `??`, `*?` will not call `set_next_input` as most frontend allow proper multiline editing and it was causing issues for many users of multi-cell frontends. This has been backported to 7.33
- [PR #13600](#), `pre_run_*`-hooks will now have a `cell_id` attribute on the info object when frontend provides it. This has been backported to 7.33
- [PR #13624](#), fixed `End` key being broken after accepting an auto-suggestion.
- [PR #13657](#) fixed an issue where history from different sessions would be mixed.

2.2.13 IPython 8.2.0

IPython 8.2 mostly bring bugfixes to IPython.

- Auto-suggestion can now be elected with the `end` key. [PR #13566](#)
- Some traceback issues with `assert etb is not None` have been fixed. [PR #13588](#)
- History is now pulled from the sqitel database and not from in-memory. In particular when using the `%paste` magic, the content of the pasted text will be part of the history and not the verbatim text `%paste` anymore. [PR #13592](#)
- Fix `Ctrl-\` exit cleanup [PR #13603](#)
- Fixes to `ultratb` ipdb support when used outside of IPython. [PR #13498](#)

I am still trying to fix and investigate [#13598](#), which seems to be random, and would appreciate help if you find a reproducible minimal case. I've tried to make various changes to the codebase to mitigate it, but a proper fix will be difficult without understanding the cause.

All the issues on pull-requests for this release can be found in the [8.2 milestone](#). . And some documentation only PR can be found as part of the [7.33 milestone](#) (currently not released).

Thanks to the [D. E. Shaw group](#) for sponsoring work on IPython and related libraries.

2.2.14 IPython 8.1.1

Fix an issue with `virtualenv` and Python 3.8 introduced in 8.1

Revert [PR #13537](#) (fix an issue with symlinks in `virtualenv`) that raises an error in Python 3.8, and fixed in a different way in [PR #13559](#).

2.2.15 IPython 8.1.0

IPython 8.1 is the first minor release after 8.0 and fixes a number of bugs and updates a few behaviors that were problematic with the 8.0 as with many new major release.

Note that beyond the changes listed here, IPython 8.1.0 also contains all the features listed in [IPython 7.32](#).

- Misc and multiple fixes around quotation auto-closing. It is now disabled by default. Run with `TerminalInteractiveShell.auto_match=True` to re-enabled
- Require `pygments>=2.4.0` [PR #13459](#), this was implicit in the code, but is now explicit in `setup.cfg/setup.py`
- Docs improvement of `core.magic_arguments` examples. [PR #13433](#)

- Multi-line edit executes too early with `await`. [PR #13424](#)
- `black` is back as an optional dependency, and autoformatting disabled by default until some fixes are implemented (`black` improperly reformat magics). [PR #13471](#) Additionally the ability to use `yapf` as a code reformatter has been added [PR #13528](#) . You can use `TerminalInteractiveShell.autoformatter="black"`, `TerminalInteractiveShell.autoformatter="yapf"` to re-enable auto formatting with `black`, or switch to `yapf`.
- Fix an issue where `display` was not defined.
- Auto suggestions are now configurable. Currently only `AutoSuggestFromHistory` (default) and `None`. new provider contribution welcomed. [PR #13475](#)
- multiple packaging/testing improvement to simplify downstream packaging (`xfail` with reasons, try to not access network...).
- Update deprecation. `InteractiveShell.magic` internal method has been deprecated for many years but did not emit a warning until now.
- internal `appended_to_syspath` context manager has been deprecated.
- fix an issue with symlinks in `virtualenv` [PR #13537](#) (Reverted in 8.1.1)
- Fix an issue with vim mode, where cursor would not be reset on exit [PR #13472](#)
- `ipython` directive now remove only known pseudo-decorators [PR #13532](#)
- `IPython/lib/security` which used to be used for jupyter notebook has been removed.
- Fix an issue where `async with` would execute on new lines. [PR #13436](#)

We want to remind users that IPython is part of the Jupyter organisations, and thus governed by a Code of Conduct. Some of the behavior we have seen on GitHub is not acceptable. Abuse and non-respectful comments on discussion will not be tolerated.

Many thanks to all the contributors to this release, many of the above fixed issues and new features were done by first time contributors, showing there is still plenty of easy contribution possible in IPython . You can find all individual contributions to this milestone [on github](#).

Thanks as well to the [D. E. Shaw group](#) for sponsoring work on IPython and related libraries. In particular the Lazy autoloading of magics that you will find described in the 7.32 release notes.

2.2.16 IPython 8.0.1 (CVE-2022-21699)

IPython 8.0.1, 7.31.1 and 5.11 are security releases that change some default values in order to prevent potential Execution with Unnecessary Privileges.

Almost all version of IPython looks for configuration and profiles in current working directory. Since IPython was developed before pip and environments existed it was used a convenient way to load code/packages in a project dependant way.

In 2022, it is not necessary anymore, and can lead to confusing behavior where for example cloning a repository and starting IPython or loading a notebook from any Jupyter-Compatible interface that has `ipython` set as a kernel can lead to code execution.

I did not find any standard way for packaged to advertise CVEs they fix, I'm thus trying to add a `__patched_cves__` attribute to the IPython module that list the CVEs that should have been fixed. This attribute is informational only as if a executable has a flaw, this value can always be changed by an attacker.

```
In [1]: import IPython

In [2]: IPython.__patched_cves__
Out[2]: {'CVE-2022-21699'}

In [3]: 'CVE-2022-21699' in IPython.__patched_cves__
Out[3]: True
```

Thus starting with this version:

- The current working directory is not searched anymore for profiles or configurations files.
- Added a `__patched_cves__` attribute (set of strings) to IPython module that contain the list of fixed CVE. This is informational only.

Further details can be read on the [GitHub Advisory](#)

2.2.17 IPython 8.0

IPython 8.0 is bringing a large number of new features and improvements to both the user of the terminal and of the kernel via Jupyter. The removal of compatibility with an older version of Python is also the opportunity to do a couple of performance improvements in particular with respect to startup time. The 8.x branch started diverging from its predecessor around IPython 7.12 (January 2020).

This release contains 250+ pull requests, in addition to many of the features and backports that have made it to the 7.x branch. Please see the [8.0 milestone](#) for the full list of pull requests.

Please feel free to send pull requests to update those notes after release, I have likely forgotten a few things reviewing 250+ PRs.

2.2.18 Dependencies changes/downstream packaging

Most of our building steps have been changed to be (mostly) declarative and follow PEP 517. We are trying to completely remove `setup.py` (PR #13238) and are looking for help to do so.

- minimum supported `traitlets` version is now 5+
- we now require `stack_data`
- minimal Python is now 3.8
- `nose` is not a testing requirement anymore
- `pytest` replaces `nose`.
- `iptest`/`iptest3` cli entrypoints do not exist anymore.
- the minimum officially supported `numpy` version has been bumped, but this should not have much effect on packaging.

2.2.19 Deprecation and removal

We removed almost all features, arguments, functions, and modules that were marked as deprecated between IPython 1.0 and 5.0. As a reminder, 5.0 was released in 2016, and 1.0 in 2013. Last release of the 5 branch was 5.10.0, in May 2020. The few remaining deprecated features we left have better deprecation warnings or have been turned into explicit errors for better error messages.

I will use this occasion to add the following requests to anyone emitting a deprecation warning:

- Please add at least `stacklevel=2` so that the warning is emitted into the caller context, and not the callee one.
- Please add **since which version** something is deprecated.

As a side note, it is much easier to conditionally compare version numbers rather than using `try/except` when functionality changes with a version.

I won't list all the removed features here, but modules like `IPython.kernel`, which was just a shim module around `ipykernel` for the past 8 years, have been removed, and so many other similar things that pre-date the name **Jupyter** itself.

We no longer need to add `IPython.extensions` to the `PYTHONPATH` because that is being handled by `load_extension`.

We are also removing `Cythonmagic`, `sympyprinting` and `rmagic` as they are now in other packages and no longer need to be inside IPython.

2.2.20 Documentation

The majority of our docstrings have now been reformatted and automatically fixed by the experimental [Vélin](#) project to conform to `numpydoc`.

2.2.21 Type annotations

While IPython itself is highly dynamic and can't be completely typed, many of the functions now have type annotations, and part of the codebase is now checked by `mypy`.

2.2.22 Featured changes

Here is a features list of changes in IPython 8.0. This is of course non-exhaustive. Please note as well that many features have been added in the 7.x branch as well (and hence why you want to read the 7.x what's new notes), in particular features contributed by QuantStack (with respect to debugger protocol and Xeus Python), as well as many debugger features that I was pleased to implement as part of my work at QuanSight and sponsored by DE Shaw.

Traceback improvements

Previously, error tracebacks for errors happening in code cells were showing a hash, the one used for compiling the Python AST:

```
In [1]: def foo():
...:     return 3 / 0
...:

In [2]: foo()

-----
ZeroDivisionError                                Traceback (most recent call last)
<ipython-input-2-c19b6d9633cf> in <module>
----> 1 foo()

<ipython-input-1-1595a74c32d5> in foo()
      1 def foo():
----> 2     return 3 / 0
      3

ZeroDivisionError: division by zero
```

The error traceback is now correctly formatted, showing the cell number in which the error happened:

```
In [1]: def foo():
...:     return 3 / 0
...:

Input In [2]: foo()

-----
ZeroDivisionError                                Traceback (most recent call last)
input In [2], in <module>
----> 1 foo()

Input In [1], in foo()
      1 def foo():
----> 2     return 3 / 0

ZeroDivisionError: division by zero
```

The `stack_data` package has been integrated, which provides smarter information in the traceback; in particular it will highlight the AST node where an error occurs which can help to quickly narrow down errors.

For example in the following snippet:

```
def foo(i):
    x = [[0]]
    return x[0][i][0]

def bar():
    return foo(0) + foo(
        1
    ) + foo(2)
```

calling `bar()` would raise an `IndexError` on the return line of `foo`, and IPython 8.0 is capable of telling you where the index error occurs:

```

IndexError
Input In [2], in <module>
----> 1 bar()
      ~~~~~

Input In [1], in bar()
      6 def bar():
----> 7     return foo(0) + foo(
           ~~~~~

      8         1
           ~~~~~
      9     ) + foo(2)
           ~~~~~

Input In [1], in foo(i)
      1 def foo(i):
      2     x = [[0]]
----> 3     return x[0][i][0]
           ~~~~~

```

The corresponding locations marked here with `~` will show up highlighted in the terminal and notebooks.

Finally, a colon `::` and line number is appended after a filename in traceback:

```

ZeroDivisionError                                Traceback (most recent call last)
File ~/error.py:4, in <module>
      1 def f():
      2     1/0
----> 4 f()

File ~/error.py:2, in f()
      1 def f():
----> 2     1/0

```

Many terminals and editors have integrations enabling you to directly jump to the relevant file/line when this syntax is used, so this small addition may have a high impact on productivity.

Autosuggestions

Autosuggestion is a very useful feature available in `fish`, `zsh`, and `prompt-toolkit`.

`Ptpython` allows users to enable this feature in `ptpython/config.py`.

This feature allows users to accept autosuggestions with `ctrl e`, `ctrl f`, or right arrow as described below.

1. Start `ipython`



```
In [1]:
```

2. Run `print("hello")`

```
In [1]: print("hello")
hello

In [2]: █
```

3. start typing `print` again to see the autosuggestion

```
In [1]: print("hello")
hello

In [2]: p█rint("hello")
```

4. Press `ctrl-f`, or `ctrl-e`, or `right-arrow` to accept the suggestion

```
In [1]: print("hello")
hello

In [2]: print█("hello")█
```

You can also complete word by word:

1. Run `def say_hello(): print("hello")`

```
In [1]: def say_hello(): print("hello")

In [2]: |
```

2. Start typing the first letter if `def` to see the autosuggestion

```
In [2]: d|ef say_hello(): print("hello")
```

3. Press `alt-f` (or `escape` followed by `f`), to accept the first word of the suggestion

```
In [2]: def |say_hello(): print("hello")
```

Importantly, this feature does not interfere with tab completion:

1. After running `def say_hello(): print("hello")`, press d

```
In [2]: d|def say_hello(): print("hello")
```

2. Press Tab to start tab completion

```
In [2]: d|
      def      dict      %debug      %dirs
      del      dir()     %%debug     %doctest_mode
      delattr() divmod()  %dhist
```

- 3A. Press Tab again to select the first option

```
In [2]: def|
      def      dict      %debug      %dirs
      del      dir()     %%debug     %doctest_mode
      delattr() divmod()  %dhist
      keyword
```

- 3B. Press `alt f` (escape, f) to accept to accept the first word of the suggestion

```
In [2]: def |say_hello(): print("hello")
```

- 3C. Press `ctrl-f` or `ctrl-e` to accept the entire suggestion

```
In [2]: def say_hello(): print("hello")
```

Currently, autosuggestions are only shown in the emacs or vi insert editing modes:

- The `ctrl e`, `ctrl f`, and `alt f` shortcuts work by default in emacs mode.
- To use these shortcuts in vi insert mode, you will have to create [custom keybindings](#) in your `config.py`.

Show pinfo information in ipdb using «?» and «??»

In IPDB, it is now possible to show the information about an object using «?» and «??», in much the same way that it can be done when using the IPython prompt:

```
ipdb> partial?
Init signature: partial(self, /, *args, **kwargs)
Docstring:
partial(func, *args, **keywords) - new function with partial application
of the given arguments and keywords.
File:      ~/.pyenv/versions/3.8.6/lib/python3.8/functools.py
Type:      type
Subclasses:
```

Previously, `pinfo` or `pinfo2` command had to be used for this purpose.

Autoreload 3 feature

Example: When an IPython session is run with the „autoreload“ extension loaded, you will now have the option „3“ to select, which means the following:

1. replicate all functionality from option 2
2. autoloader all new funcs/classes/enums/globals from the module when they are added
3. autoloader all newly imported funcs/classes/enums/globals from external modules

Try `%autoreload 3` in an IPython session after running `%load_ext autoreload`.

For more information please see the following unit test : `extensions/tests/test_autoreload.py:test_autoload_newly_added_objects`

Auto formatting with black in the CLI

This feature was present in 7.x, but disabled by default.

In 8.0, input was automatically reformatted with Black when black was installed. This feature has been reverted for the time being. You can re-enable it by setting `TerminalInteractiveShell.autoformatter` to "black"

History Range Glob feature

Previously, when using `%history`, users could specify either a range of sessions and lines, for example:

```
~8/1-~6/5  # see history from the first line of 8 sessions ago,  
           # to the fifth line of 6 sessions ago.``
```

Or users could specify a glob pattern:

```
-g <pattern> # glob ALL history for the specified pattern.
```

However users could *not* specify both.

If a user *did* specify both a range and a glob pattern, then the glob pattern would be used (globbing *all* history) *and the range would be ignored*.

With this enhancement, if a user specifies both a range and a glob pattern, then the glob pattern will be applied to the specified range of history.

Don't start a multi-line cell with sunken parenthesis

From now on, IPython will not ask for the next line of input when given a single line with more closing than opening brackets. For example, this means that if you (mis)type `]]` instead of `[]`, a `SyntaxError` will show up, instead of the `...:` prompt continuation.

IPython shell for ipdb interact

The `ipdb interact` starts an IPython shell instead of Python's built-in `code.interact()`.

Automatic Vi prompt stripping

When pasting code into IPython, it will strip the leading prompt characters if there are any. For example, you can paste the following code into the console - it will still work, even though each line is prefixed with prompts (In, Out):

```
In [1]: 2 * 2 == 4
Out[1]: True

In [2]: print("This still works as pasted")
```

Previously, this was not the case for the Vi-mode prompts:

```
In [1]: [ins] In [13]: 2 * 2 == 4
...: Out[13]: True
...:
File "<ipython-input-1-727bb88eaf33>", line 1
[ins] In [13]: 2 * 2 == 4
             ^
SyntaxError: invalid syntax
```

This is now fixed, and Vi prompt prefixes - `[ins]` and `[nav]` - are skipped just as the normal `In` would be.

IPython shell can be started in the Vi mode using `ipython --TerminalInteractiveShell.editing_mode=vi`. You should be able to change mode dynamically with `%config TerminalInteractiveShell.editing_mode='vi'`

Empty History Ranges

A number of magics that take history ranges can now be used with an empty range. These magics are:

- `%save`
- `%load`
- `%pastebin`
- `%pycat`

Using them this way will make them take the history of the current session up to the point of the magic call (such that the magic itself will not be included).

Therefore it is now possible to save the whole history to a file using `%save <filename>`, load and edit it using `%load` (makes for a nice usage when followed with `F2`), send it to dpaste.org using `%pastebin`, or view the whole thing syntax-highlighted with a single `%pycat`.

Windows timing implementation: Switch to `process_time`

Timing on Windows, for example with `%%time`, was changed from being based on `time.perf_counter` (which counted time even when the process was sleeping) to being based on `time.process_time` instead (which only counts CPU time). This brings it closer to the behavior on Linux. See [PR #12984](#).

Miscellaneous

- Non-text formatters are not disabled in the terminal, which should simplify writing extensions displaying images or other mimetypes in supporting terminals. [PR #12315](#)
- It is now possible to automatically insert matching brackets in Terminal IPython using the `TerminalInteractiveShell.auto_match=True` option. [PR #12586](#)
- We are thinking of deprecating the current `%%javascript` magic in favor of a better replacement. See [PR #13376](#).
- `~` is now expanded when part of a path in most magics [PR #13385](#)
- `%%timeit` magic now adds a comma every thousands to make reading a long number easier [PR #13379](#)
- "info" messages can now be customised to hide some fields [PR #13343](#)
- `collections.UserList` now pretty-prints [PR #13320](#)
- The debugger now has a persistent history, which should make it less annoying to retype commands [PR #13246](#)
- `!pip !conda !cd` or `!ls` are likely doing the wrong thing. We now warn users if they use one of those commands. [PR #12954](#)
- Make `%precision` work for `numpy.float64` type [PR #12902](#)

Re-added support for XDG config directories

XDG support through the years comes and goes. There is a tension between having an identical location for configuration in all platforms versus having simple instructions. After initial failures a couple of years ago, IPython was modified to automatically migrate XDG config files back into `~/.ipython`. That migration code has now been removed. IPython now checks the XDG locations, so if you `_manually_` move your config files to your preferred location, IPython will not move them back.

2.2.23 Preparing for Python 3.10


To prepare for Python 3.10, we have started working on removing reliance and any dependency that is not compatible with Python 3.10. This includes migrating our test suite to `pytest` and starting to remove `nose`. This also means that the `iptest` command is now gone and all testing is via `pytest`.

This was in large part thanks to the NumFOCUS Small Developer grant, which enabled us to allocate \$4000 to hire [Nikita Kniazev \(@Kojoley\)](#), who did a fantastic job at updating our code base, migrating to `pytest`, pushing our coverage, and fixing a large number of bugs. I highly recommend contacting them if you need help with C++ and Python projects.

You can find all relevant issues and PRs with [the SDG 2021 tag](#)

2.2.24 Removing support for older Python versions

We are removing support for Python up through 3.7, allowing internal code to use the more efficient `pathlib` and to make better use of type annotations.



We had about 34 PRs only to update some logic to update some functions from managing strings to using Pathlib.

The completer has also seen significant updates and now makes use of newer Jedi APIs, offering faster and more reliable tab completion.

2.2.25 Misc Statistics

Here are some numbers:

```
7.x: 296 files, 12561 blank lines, 20282 comments, 35142 line of code.
8.0: 252 files, 12053 blank lines, 19232 comments, 34505 line of code.
```

```
$ git diff --stat 7.x...master | tail -1
340 files changed, 13399 insertions(+), 12421 deletions(-)
```

We have commits from 162 authors, who contributed 1916 commits in 23 month, excluding merges (to not bias toward maintainers pushing buttons):

```
$ git shortlog -s --no-merges 7.x...master | sort -nr
535 Matthias Bussonnier
86 Nikita Kniazev
69 Blazej Michalik
49 Samuel Gaist
27 Itamar Turner-Trauring
18 Spas Kalaydzhisyki
```

(continues on next page)

(продолжение с предыдущей страницы)

```
17 Thomas Kluyver
17 Quentin Peter
17 James Morris
17 Artur Svistunov
15 Bart Skowron
14 Alex Hall
13 rushabh-v
13 Terry Davis
13 Benjamin Ragan-Kelley
 8 martinRenou
 8 farisachugthai
 7 dswij
 7 Gal B
 7 Corentin Cadiou
 6 yuji96
 6 Martin Skarzynski
 6 Justin Palmer
 6 Daniel Goldfarb
 6 Ben Greiner
 5 Sammy Al Hashemi
 5 Paul Ivanov
 5 Inception95
 5 Eyenpi
 5 Douglas Blank
 5 Coco Mishra
 5 Bibo Hao
 5 André A. Gomes
 5 Ahmed Fasih
 4 takuya fujiwara
 4 palewire
 4 Thomas A Caswell
 4 Talley Lambert
 4 Scott Sanderson
 4 Ram Rachum
 4 Nick Muoh
 4 Nathan Goldbaum
 4 Mithil Poojary
 4 Michael T
 4 Jakub Klus
 4 Ian Castleden
 4 Eli Rykoff
 4 Ashwin Vishnu
 3
 3 sleeping
 3 Sylvain Corlay
 3 Peter Corke
 3 Paul Bissex
 3 Matthew Feickert
 3 Fernando Perez
 3 Eric Wieser
 3 Daniel Mietchen
 3 Aditya Sathe
```

(continues on next page)

(продолжение с предыдущей страницы)

```
3 007vedant
2 rchiodo
2 nicolaslazo
2 luttik
2 gorogoroumaru
2 foobarbyte
2 bar-hen
2 Theo Ouzhinski
2 Strawkage
2 Samreen Zarroug
2 Pete Blois
2 Meysam Azad
2 Matthieu Ancellin
2 Mark Schmitz
2 Maor Kleinberger
2 MRCWirtz
2 Lumir Balhar
2 Julien Rabinow
2 Juan Luis Cano Rodríguez
2 Joyce Er
2 Jakub
2 Faris A Chugthai
2 Ethan Madden
2 Dimitri Papadopoulos
2 Diego Fernandez
2 Daniel Shimon
2 Coco Bennett
2 Carlos Cordoba
2 Boyuan Liu
2 BaoGiang HoangVu
2 Augusto
2 Arthur Svistunov
2 Arthur Moreira
2 Ali Nabipour
2 Adam Hackbarth
1 richard
1 linar-jether
1 lbennett
1 juacrumar
1 gpotter2
1 digitalvirtuoso
1 dalthviz
1 Yonatan Goldschmidt
1 Tomasz Kłloczko
1 Tobias Bengfort
1 Timur Kushukov
1 Thomas
1 Snir Broshi
1 Shao Yang Hong
1 Sanjana-03
1 Romulo Filho
1 Rodolfo Carvalho
```

(continues on next page)

(продолжение с предыдущей страницы)

```
1 Richard Shadrach
1 Reilly Tucker Siemens
1 Rakesh Roshan
1 Piers Titus van der Torren
1 PhanatosZou
1 Pavel Safronov
1 Paulo S. Costa
1 Paul McCarthy
1 NotWearingPants
1 Naelson Douglas
1 Michael Tiemann
1 Matt Wozniski
1 Markus Wageringel
1 Marcus Wirtz
1 Marcio Mazza
1 Lumír 'Frenzy' Balhar
1 Lightyagami1
1 Leon Anavi
1 LeafyLi
1 LOuisJOshua
1 Kyle Cutler
1 Krzysztof Cybulski
1 Kevin Kirsche
1 KIU Shueng Chuan
1 Jonathan Slenders
1 Jay Qi
1 Jake VanderPlas
1 Iwan Briquemont
1 Hussaina Begum Nandyala
1 Gordon Ball
1 Gabriel Simonetto
1 Frank Tobia
1 Erik
1 Elliott Sales de Andrade
1 Daniel Hahler
1 Dan Green-Leipciger
1 Dan Green
1 Damian Yurzola
1 Coon, Ethan T
1 Carol Willing
1 Brian Lee
1 Brendan Gerrity
1 Blake Griffin
1 Bastian Ebeling
1 Bartosz Telenczuk
1 Ankitsingh6299
1 Andrew Port
1 Andrew J. Hesford
1 Albert Zhang
1 Adam Johnson
```

This does not, of course, represent non-code contributions, for which we are also grateful.

2.2.26 API Changes using Frappuccino

This is an experimental exhaustive API difference using [Frappuccino](#)

The following items are new in IPython 8.0

```
+ IPython.core.async_helpers.get_asyncio_loop()
+ IPython.core.completer.Dict
+ IPython.core.completer.Pattern
+ IPython.core.completer.Sequence
+ IPython.core.completer.__skip_doctest__
+ IPython.core.debugger.Pdb.precmd(self, line)
+ IPython.core.debugger.__skip_doctest__
+ IPython.core.display.__getattr__(name)
+ IPython.core.display.warn
+ IPython.core.display_functions
+ IPython.core.display_functions.DisplayHandle
+ IPython.core.display_functions.DisplayHandle.display(self, obj, **kwargs)
+ IPython.core.display_functions.DisplayHandle.update(self, obj, **kwargs)
+ IPython.core.display_functions.__all__
+ IPython.core.display_functions.__builtins__
+ IPython.core.display_functions.__cached__
+ IPython.core.display_functions.__doc__
+ IPython.core.display_functions.__file__
+ IPython.core.display_functions.__loader__
+ IPython.core.display_functions.__name__
+ IPython.core.display_functions.__package__
+ IPython.core.display_functions.__spec__
+ IPython.core.display_functions.b2a_hex
+ IPython.core.display_functions.clear_output(wait=False)
+ IPython.core.display_functions.display(*objs, include='None', exclude='None', metadata=
↳ 'None', transient='None', display_id='None', raw=False, clear=False, **kwargs)
+ IPython.core.display_functions.publish_display_data(data, metadata='None', source='
↳ <deprecated>', *, transient='None', **kwargs)
+ IPython.core.display_functions.update_display(obj, *, display_id, **kwargs)
+ IPython.core.extensions.BUILTINS_EXTS
+ IPython.core.inputtransformer2.has_sunken_brackets(tokens)
+ IPython.core.interactiveshell.Callable
+ IPython.core.interactiveshell.__annotations__
+ IPython.core.ultratb.List
+ IPython.core.ultratb.Tuple
+ IPython.lib.pretty.CallExpression
+ IPython.lib.pretty.CallExpression.factory(name)
+ IPython.lib.pretty.RawStringLiteral
+ IPython.lib.pretty.RawText
+ IPython.terminal.debugger.TerminalPdb.do_interact(self, arg)
+ IPython.terminal.embed.Set
```

The following items have been removed (or moved to superclass):

```
- IPython.core.application.BaseIPythonApplication.initialize_subcommand
- IPython.core.completer.Sentinel
- IPython.core.completer.skip_doctest
- IPython.core.debugger.Tracer
```

(continues on next page)

(продолжение с предыдущей страницы)

```

- IPython.core.display.DisplayHandle
- IPython.core.display.DisplayHandle.display
- IPython.core.display.DisplayHandle.update
- IPython.core.display.b2a_hex
- IPython.core.display.clear_output
- IPython.core.display.display
- IPython.core.display.publish_display_data
- IPython.core.display.update_display
- IPython.core.excolors.Deprec
- IPython.core.excolors.ExceptionColors
- IPython.core.history.warn
- IPython.core.hooks.late_startup_hook
- IPython.core.hooks.pre_run_code_hook
- IPython.core.hooks.shutdown_hook
- IPython.core.interactiveshell.InteractiveShell.init_deprecation_warnings
- IPython.core.interactiveshell.InteractiveShell.init_readline
- IPython.core.interactiveshell.InteractiveShell.write
- IPython.core.interactiveshell.InteractiveShell.write_err
- IPython.core.interactiveshell.get_default_colors
- IPython.core.interactiveshell.removed_co_newlocals
- IPython.core.magics.execution.ExecutionMagics.profile_missing_notice
- IPython.core.magics.script.PIPE
- IPython.core.prefilter.PrefilterManager.init_transformers
- IPython.core.release.classifiers
- IPython.core.release.description
- IPython.core.release.keywords
- IPython.core.release.long_description
- IPython.core.release.name
- IPython.core.release.platforms
- IPython.core.release.url
- IPython.core.ultratb.VerboseTB.format_records
- IPython.core.ultratb.find_recursion
- IPython.core.ultratb.findsource
- IPython.core.ultratb.fix_frame_records_filenames
- IPython.core.ultratb.inspect_error
- IPython.core.ultratb.is_recursion_error
- IPython.core.ultratb.with_patch_inspect
- IPython.external.__all__
- IPython.external.__builtins__
- IPython.external.__cached__
- IPython.external.__doc__
- IPython.external.__file__
- IPython.external.__loader__
- IPython.external.__name__
- IPython.external.__package__
- IPython.external.__path__
- IPython.external.__spec__
- IPython.kernel.KernelConnectionInfo
- IPython.kernel.__builtins__
- IPython.kernel.__cached__
- IPython.kernel.__warningregistry__
- IPython.kernel.pkg

```

(continues on next page)

(продолжение с предыдущей страницы)

```

- IPython.kernel.protocol_version
- IPython.kernel.protocol_version_info
- IPython.kernel.src
- IPython.kernel.version_info
- IPython.kernel.warn
- IPython.lib.backgroundjobs
- IPython.lib.backgroundjobs.BackgroundJobBase
- IPython.lib.backgroundjobs.BackgroundJobBase.run
- IPython.lib.backgroundjobs.BackgroundJobBase.traceback
- IPython.lib.backgroundjobs.BackgroundJobExpr
- IPython.lib.backgroundjobs.BackgroundJobExpr.call
- IPython.lib.backgroundjobs.BackgroundJobFunc
- IPython.lib.backgroundjobs.BackgroundJobFunc.call
- IPython.lib.backgroundjobs.BackgroundJobManager
- IPython.lib.backgroundjobs.BackgroundJobManager.flush
- IPython.lib.backgroundjobs.BackgroundJobManager.new
- IPython.lib.backgroundjobs.BackgroundJobManager.remove
- IPython.lib.backgroundjobs.BackgroundJobManager.result
- IPython.lib.backgroundjobs.BackgroundJobManager.status
- IPython.lib.backgroundjobs.BackgroundJobManager.traceback
- IPython.lib.backgroundjobs.__builtins__
- IPython.lib.backgroundjobs.__cached__
- IPython.lib.backgroundjobs.__doc__
- IPython.lib.backgroundjobs.__file__
- IPython.lib.backgroundjobs.__loader__
- IPython.lib.backgroundjobs.__name__
- IPython.lib.backgroundjobs.__package__
- IPython.lib.backgroundjobs.__spec__
- IPython.lib.kernel.__builtins__
- IPython.lib.kernel.__cached__
- IPython.lib.kernel.__doc__
- IPython.lib.kernel.__file__
- IPython.lib.kernel.__loader__
- IPython.lib.kernel.__name__
- IPython.lib.kernel.__package__
- IPython.lib.kernel.__spec__
- IPython.lib.kernel.__warningregistry__
- IPython.paths.fs_encoding
- IPython.terminal.debugger.DEFAULT_BUFFER
- IPython.terminal.debugger.cursor_in_leading_ws
- IPython.terminal.debugger.emacs_insert_mode
- IPython.terminal.debugger.has_selection
- IPython.terminal.debugger.vi_insert_mode
- IPython.terminal.interactiveshell.DISPLAY_BANNER_DEPRECATED
- IPython.terminal.ipapp.TerminalIPythonApp.parse_command_line
- IPython.testing.test
- IPython.utils.contexts.NoOpContext
- IPython.utils.io.IOStream
- IPython.utils.io.IOStream.close
- IPython.utils.io.IOStream.write
- IPython.utils.io.IOStream.writelines
- IPython.utils.io.__warningregistry__

```

(continues on next page)

(продолжение с предыдущей страницы)

```

- IPython.utils.io.atomic_writing
- IPython.utils.io.stderr
- IPython.utils.io.stdin
- IPython.utils.io.stdout
- IPython.utils.io.unicode_std_stream
- IPython.utils.path.get_ipython_cache_dir
- IPython.utils.path.get_ipython_dir
- IPython.utils.path.get_ipython_module_path
- IPython.utils.path.get_ipython_package_dir
- IPython.utils.path.locate_profile
- IPython.utils.path.unquote_filename
- IPython.utils.py3compat.PY2
- IPython.utils.py3compat.PY3
- IPython.utils.py3compat.buffer_to_bytes
- IPython.utils.py3compat.builtin_mod_name
- IPython.utils.py3compat.cast_bytes
- IPython.utils.py3compat.getcwd
- IPython.utils.py3compat.isidentifier
- IPython.utils.py3compat.u_format

```

The following signatures differ between 7.x and 8.0:

```

- IPython.core.completer.IPCompleter.unicode_name_matches(self, text)
+ IPython.core.completer.IPCompleter.unicode_name_matches(text)

- IPython.core.completer.match_dict_keys(keys, prefix, delims)
+ IPython.core.completer.match_dict_keys(keys, prefix, delims, extra_prefix='None')

- IPython.core.interactiveshell.InteractiveShell.object_inspect_mime(self, oname, detail_
↪ level=0)
+ IPython.core.interactiveshell.InteractiveShell.object_inspect_mime(self, oname, detail_
↪ level=0, omit_sections='()')

- IPython.core.interactiveshell.InteractiveShell.set_hook(self, name, hook, priority=50,
↪ str_key='None', re_key='None', _warn_deprecated=True)
+ IPython.core.interactiveshell.InteractiveShell.set_hook(self, name, hook, priority=50,
↪ str_key='None', re_key='None')

- IPython.core.oinspect.Inspector.info(self, obj, oname='', formatter='None', info='None
↪ ', detail_level=0)
+ IPython.core.oinspect.Inspector.info(self, obj, oname='', info='None', detail_level=0)

- IPython.core.oinspect.Inspector.pinfo(self, obj, oname='', formatter='None', info='None
↪ ', detail_level=0, enable_html_pager=True)
+ IPython.core.oinspect.Inspector.pinfo(self, obj, oname='', formatter='None', info='None
↪ ', detail_level=0, enable_html_pager=True, omit_sections='()')

- IPython.core.profiledir.ProfileDir.copy_config_file(self, config_file, path='None',
↪ overwrite=False)
+ IPython.core.profiledir.ProfileDir.copy_config_file(self, config_file, path,
↪ overwrite=False)

```

(continues on next page)

(продолжение с предыдущей страницы)

```

- IPython.core.ultratb.VerboseTB.format_record(self, frame, file, lnum, func, lines, ↵
↪ index)
+ IPython.core.ultratb.VerboseTB.format_record(self, frame_info)

- IPython.terminal.embed.InteractiveShellEmbed.mainloop(self, local_ns='None', module=
↪ 'None', stack_depth=0, display_banner='None', global_ns='None', compile_flags='None')
+ IPython.terminal.embed.InteractiveShellEmbed.mainloop(self, local_ns='None', module=
↪ 'None', stack_depth=0, compile_flags='None')

- IPython.terminal.embed.embed(**kwargs)
+ IPython.terminal.embed.embed(*, header='', compile_flags='None', **kwargs)

- IPython.terminal.interactiveshell.TerminalInteractiveShell.interact(self, display_
↪ banner='<object object at 0xfffff>')
+ IPython.terminal.interactiveshell.TerminalInteractiveShell.interact(self)

- IPython.terminal.interactiveshell.TerminalInteractiveShell.mainloop(self, display_
↪ banner='<object object at 0xfffff>')
+ IPython.terminal.interactiveshell.TerminalInteractiveShell.mainloop(self)

- IPython.utils.path.get_py_filename(name, force_win32='None')
+ IPython.utils.path.get_py_filename(name)

```

The following are new attributes (that might be inherited):

```

+ IPython.core.completer.IPCompleter.unicode_names
+ IPython.core.debugger.InterruptiblePdb.precmd
+ IPython.core.debugger.Pdb.precmd
+ IPython.core.ultratb.AutoFormattedTB.has_colors
+ IPython.core.ultratb.ColorTB.has_colors
+ IPython.core.ultratb.FormattedTB.has_colors
+ IPython.core.ultratb.ListTB.has_colors
+ IPython.core.ultratb.SyntaxTB.has_colors
+ IPython.core.ultratb.TBTools.has_colors
+ IPython.core.ultratb.VerboseTB.has_colors
+ IPython.terminal.debugger.TerminalPdb.do_interact
+ IPython.terminal.debugger.TerminalPdb.precmd

```

The following attribute/methods have been removed:

```

- IPython.core.application.BaseIPythonApplication.deprecated_subcommands
- IPython.core.ultratb.AutoFormattedTB.format_records
- IPython.core.ultratb.ColorTB.format_records
- IPython.core.ultratb.FormattedTB.format_records
- IPython.terminal.embed.InteractiveShellEmbed.init_deprecation_warnings
- IPython.terminal.embed.InteractiveShellEmbed.init_readline
- IPython.terminal.embed.InteractiveShellEmbed.write
- IPython.terminal.embed.InteractiveShellEmbed.write_err
- IPython.terminal.interactiveshell.TerminalInteractiveShell.init_deprecation_warnings
- IPython.terminal.interactiveshell.TerminalInteractiveShell.init_readline
- IPython.terminal.interactiveshell.TerminalInteractiveShell.write
- IPython.terminal.interactiveshell.TerminalInteractiveShell.write_err

```

(continues on next page)

(продолжение с предыдущей страницы)

```
- IPython.terminal.ipapp.LocateIPythonApp.deprecated_subcommands
- IPython.terminal.ipapp.LocateIPythonApp.initialize_subcommand
- IPython.terminal.ipapp.TerminalIPythonApp.deprecated_subcommands
- IPython.terminal.ipapp.TerminalIPythonApp.initialize_subcommand
```

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

2.3 Issues closed in the 8.x development cycle

GitHub stats for 2022/01/05 - 2022/01/12 (tag: 8.0.0rc1)

These lists are automatically generated, and may be incomplete or contain duplicates.

We closed 26 issues and merged 307 pull requests. The full list can be seen [on GitHub](#)

The following 99 authors contributed 372 commits.

- 007vedant
- Adam Hackbarth
- Aditya Sathe
- Ahmed Fasih
- Albert Zhang
- Alex Hall
- Andrew Port
- Ankitsingh6299
- Arthur Moreira
- Ashwin Vishnu
- Augusto
- BaoGiang HoangVu
- bar-hen
- Bart Skowron
- Bartosz Telenczuk
- Bastian Ebeling
- Benjamin Ragan-Kelley

- Blazej Michalik
- blois
- Boyuan Liu
- Brendan Gerrity
- Carol Willing
- Coco Bennett
- Coco Mishra
- Corentin Cadiou
- Daniel Goldfarb
- Daniel Mietchen
- Daniel Shimon
- digitalvirtuoso
- Dimitri Papadopoulos
- dswij
- Eric Wieser
- Erik
- Ethan Madden
- Faris A Chugthai
- farisachugthai
- Gal B
- gorogoroumaru
- Hussaina Begum Nandyala
- Inception95
- Iwan Briquemont
- Jake VanderPlas
- Jakub Klus
- James Morris
- Jay Qi
- Jeroen Bédorf
- Joyce Er
- juacrumar
- Juan Luis Cano Rodríguez
- Julien Rabinow
- Justin Palmer
- Krzysztof Cybulski
- L0uisJ0shua

- lbennett
- LeafyLi
- Lightyagami1
- Lumir Balhar
- Mark Schmitz
- Martin Skarzynski
- martinRenou
- Matt Wozniski
- Matthias Bussonnier
- Meysam Azad
- Michael T
- Michael Tiemann
- Naelson Douglas
- Nathan Goldbaum
- Nick Muoh
- nicolaslazo
- Nikita Kniazev
- NotWearingPants
- Paul Ivanov
- Paulo S. Costa
- Pete Blois
- Peter Corke
- PhanatosZou
- Piers Titus van der Torren
- Rakesh Roshan
- Ram Rachum
- rchiodo
- Reilly Tucker Siemens
- Romulo Filho
- rushabh-v
- Sammy Al Hashemi
- Samreen Zarroug
- Samuel Gaist
- Sanjana-03
- Scott Sanderson
- skalaydzhyski

- sleeping
- Snir Broshi
- Spas Kalaydzhisyki
- Sylvain Corlay
- Terry Davis
- Timur Kushukov
- Tobias Bengfort
- Tomasz Kłoczko
- Yonatan Goldschmidt
-

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

2.4 7.x Series

2.4.1 IPython 7.34

This version contains a single fix: fix uncaught BdbQuit exceptions on ipdb exit [PR #13668](#)

2.4.2 IPython 7.33

- Allow IPython hooks to receive current cell ids when frontend support it. See [PR #13600](#)
- ? does not trigger the insertion of a new cell anymore as most frontend allow proper multiline edition. [PR #13625](#)

2.4.3 IPython 7.32

Autoload magic lazily

The ability to configure magics to be lazily loaded has been added to IPython. See the `ipython --help-all` section on `MagicsManager.lazy_magic`. One can now use:

```
c.MagicsManager.lazy_magics = {
    "my_magic": "slow.to.import",
    "my_other_magic": "also.slow",
}
```

And on first use of `%my_magic`, or corresponding cell magic, or other line magic, the corresponding `load_ext` will be called just before trying to invoke the magic.

Misc

- Update sphinxify for Docrepr 0.2.0 [PR #13503](#).
- Set `co_name` for cells run line by line (to fix debugging with Python 3.10) [PR #13535](#)

Many thanks to all the contributors to this release. You can find all individual contributions to this milestone [on github](#).

Thanks as well to the [D. E. Shaw group](#) for sponsoring work on IPython and related libraries.

2.4.4 IPython 7.31

IPython 7.31 brings a couple of backports and fixes from the 8.0 branches, it is likely one of the last releases of the 7.x series, as 8.0 will probably be released between this release and what would have been 7.32.

Please test 8.0 beta/rc releases in addition to this release.

This Releases:

- Backport some fixes for Python 3.10 ([PR #13412](#))
- use full-alpha transparency on dvipng rendered LaTeX ([PR #13372](#))

Many thanks to all the contributors to this release. You can find all individual contributions to this milestone [on github](#).

Thanks as well to the [D. E. Shaw group](#) for sponsoring work on IPython and related libraries.

2.4.5 IPython 7.30

IPython 7.30 fixes a couple of bugs introduced in previous releases (in particular with respect to path handling), and introduces a few features and improvements:

Notably we will highlight [PR #13267](#) «Document that `%run` can execute notebooks and ipy scripts.», which is the first commit of Fernando Pérez since mid 2016 (IPython 5.1). If you are new to IPython, Fernando created IPython in 2001. The other most recent contribution of Fernando to IPython itself was May 2018, by reviewing and merging PRs. I want to note that Fernando is still active but mostly as a mentor and leader of the whole Jupyter organisation, but we're still happy to see him contribute code !

[PR #13290](#) «Use sphinxify (if available) in `object_inspect_mime` path» should allow richer Repr of docstrings when using jupyterlab inspector.

[PR #13311](#) make the debugger use `ThreadPoolExecutor` for debugger cmdloop. This should fix some issues/infinite loop, but let us know if you come across any regressions. In particular this fixes issues with [kmaork/madbg](#), a remote debugger for IPython.

Note that this is likely the ante-penultimate release of IPython 7.x as a stable branch, as I hope to release IPython 8.0 as well as IPython 7.31 next month/early 2022.

IPython 8.0 will drop support for Python 3.7, removed nose as a dependency, and 7.x will only get critical bug fixes with 8.x becoming the new stable. This will not be possible without [NumFOCUS Small Development Grants](#) Which allowed us to hire [Nikita Kniazev](#) who provide Python and C++ help and contracting work.

Many thanks to all the contributors to this release. You can find all individual contributions to this milestone [on github](#).

Thanks as well to the [D. E. Shaw group](#) for sponsoring work on IPython and related libraries.

2.4.6 IPython 7.29

IPython 7.29 brings a couple of new functionalities to IPython and a number of bugfixes. It is one of the largest recent release, relatively speaking, with close to 15 Pull Requests.

- fix an issue where base64 was returned instead of bytes when showing figures [PR #13162](#)
- fix compatibility with PyQt6, PySide 6 [PR #13172](#). This may be of interest if you are running on Apple Silicon as only qt6.2+ is natively compatible.
- fix matplotlib qtagg eventloop [PR #13179](#)
- Multiple docs fixes, typos, ... etc.
- Debugger will now exit by default on SigInt [PR #13218](#), this will be useful in notebook/lab if you forgot to exit the debugger. «Interrupt Kernel» will now exist the debugger.

It give Pdb the ability to skip code in decorators. If functions contain a special value names `__debuggerskip__ = True|False`, the function will not be stepped into, and Pdb will step into lower frames only if the value is set to `False`. The exact behavior is still likely to have corner cases and will be refined in subsequent releases. Feedback welcome. See the debugger module documentation for more info. Thanks to the [D. E. Shaw group](#) for funding this feature.

The main branch of IPython is receiving a number of changes as we received a [NumFOCUS SDG](#) (\$4800), to help us finish replacing `nose` by `pytest`, and make IPython future proof with an 8.0 release.

Many thanks to all the contributors to this release. You can find all individual contributions to this milestone [on github](#).

Thanks as well to the [D. E. Shaw group](#) for sponsoring work on IPython and related libraries.

2.4.7 IPython 7.28

IPython 7.28 is again a minor release that mostly bring bugfixes, and couple of improvement. Many thanks to MrMino, who again did all the work this month, and made a number of documentation improvements.

Here is a non-exhaustive list of changes,

Fixes:

- `async with` doesn't allow newlines [PR #13090](#)
- Dynamically changing to vi mode via `%config magic`) [PR #13091](#)

Virtualenv handling fixes:

- `init_virtualenv` now uses Pathlib [PR #12548](#)
- Fix Improper path comparison of virtualenv directories [PR #13140](#)
- Fix virtual environment user warning for lower case pathes [PR #13094](#)
- Adapt to all sorts of drive names for cygwin [PR #13153](#)

New Features:

- enable autoplay in embed YouTube player [PR #13133](#)

Documentation:

- Fix formatting for the core.interactiveshell documentation [PR #13118](#)
- Fix broken ipyparallel's refs [PR #13138](#)
- Improve formatting of %time documentation [PR #13125](#)
- Reword the YouTubeVideo autoplay WN [PR #13147](#)

Highlighted features

YouTubeVideo autoplay and the ability to add extra attributes to IFrame

You can add any extra attributes to the `<iframe>` tag using the new `extras` argument in the `IFrame` class. For example:

```
In [1]: from IPython.display import IFrame

In [2]: IFrame(src="src", width=300, height=300, extras=['loading="eager"'])
```

The above cells will result in the following HTML code being displayed in a notebook:

```
<iframe
  width="300"
  height="300"
  src="src"
  frameborder="0"
  allowfullscreen
  loading="eager"
></iframe>
```

Related to the above, the `YouTubeVideo` class now takes an `allow_autoplay` flag, which sets up the `iframe` of the embedded YouTube video such that it allows autoplay.

Примечание: Whether this works depends on the autoplay policy of the browser rendering the HTML allowing it. It also could get blocked by some browser extensions.

Try it out!

```
In [1]: from IPython.display import YouTubeVideo

In [2]: YouTubeVideo("dQw4w9WgXcQ", allow_autoplay=True)
```

Thanks

Many thanks to all the contributors to this release. You can find all individual contributions to this milestone on [github](#).

Thanks as well to the [D. E. Shaw group](#) for sponsoring work on IPython and related libraries.

2.4.8 IPython 7.27

IPython 7.27 is a minor release that fixes a couple of issues and compatibility.

- Add support for GTK4 [PR #131011](#)
- Add support for Qt6 [PR #13085](#)
- Fix an issue with pip magic on windows [PR #13093](#)

Thanks

Many thanks to all the contributors to this release. You can find all individual contributions to this milestone on [github](#).

Thanks as well to the [D. E. Shaw group](#) for sponsoring work on IPython and related libraries.

2.4.9 IPython 7.26

IPython 7.26 is a minor release that fixes a couple of issues, updates in API and Copyright/Licenses issues around various part of the codebase.

We'll highlight [this issue <https://github.com/ipython/ipython/issues/13039>](https://github.com/ipython/ipython/issues/13039) pointing out we were including and refereeing to code from Stack Overflow which was CC-BY-SA, hence incompatible with the BSD license of IPython. This lead us to a rewriting of the corresponding logic which in our case was done in a more efficient way (in our case we were searching string prefixes instead of full strings).

You will notice also a number of documentation improvements and cleanup.

Of particular interest are the following Pull-requests:

- The IPython directive now uses Sphinx logging for warnings. [PR #13030](#).
- Add expiry days option to pastebin magic and change http protocol to https. [PR #13056](#)
- Make IPython.utils.timing work with jupyterlite [PR #13050](#).

Pastebin magic expiry days option

The Pastebin magic now has `-e` option to determine the number of days for paste expiration. For example the paste that created with `%pastebin -e 20 1` magic will be available for next 20 days.

Thanks

Many thanks to all the contributors to this release and in particular MrMino who is doing most of the work those days. You can find all individual contributions to this milestone [on github](#).

Thanks as well to the [D. E. Shaw group](#) for sponsoring work on IPython and related libraries.

2.4.10 IPython 7.25

IPython 7.25 is a minor release that contains a single bugfix, which is highly recommended for all users of ipdb, ipython debugger `%debug` magic and similar.

Issuing commands like `where` from within the debugger would reset the local variables changes made by the user. It is interesting to look at the root cause of the issue as accessing an attribute (`frame.f_locals`) would trigger this side effects.

Thanks in particular to the patience from the reporters at D.E. Shaw for their initial bug report that was due to a similar coding oversight in an extension, and who took time to debug and narrow down the problem.

Thanks

Many thanks to all the contributors to this release you can find all individual contributions to this milestone [on github](#).

Thanks as well to the [D. E. Shaw group](#) for sponsoring work on IPython and related libraries.

2.4.11 IPython 7.24

Third release of IPython for 2021, mostly containing bug fixes. A couple of not typical updates:

Misc

- Fix an issue where `%recall` would both succeeded and print an error message it failed. [PR #12952](#)
- Drop support for NumPy 1.16 – practically has no effect beyond indicating in package metadata that we do not support it. [PR #12937](#)

Debugger improvements

The debugger (and `%debug` magic) have been improved and can skip or hide frames originating from files that are not writable to the user, as these are less likely to be the source of errors, or be part of system files this can be a useful addition when debugging long errors.

In addition to the global `skip_hidden True|False` command, the debugger has gained finer grained control of predicates as to whether to a frame should be considered hidden. So far 3 predicates are available :

- `tbbhide`: frames containing the local variable `__tracebackhide__` set to `True`.
- `readonly`: frames originating from readonly files, set to `False`.
- `ipython_internal`: frames that are likely to be from IPython internal code, set to `True`.

You can toggle individual predicates during a session with

```
ipdb> skip_predicates readonly True
```

Read-only files will now be considered hidden frames.

You can call `skip_predicates` without arguments to see the states of current predicates:

```
ipdb> skip_predicates
current predicates:
  tbhide : True
  readonly : False
  ipython_internal : True
```

If all predicates are set to `False`, `skip_hidden` will practically have no effect. We attempt to warn you when all predicates are `False`.

Note that the `readonly` predicate may increase disk access as we check for file access permission for all frames on many command invocation, but is usually cached by operating systems. Let us know if you encounter any issues.

As the IPython debugger does not use the traitlets infrastructure for configuration, by editing your `.pdbrc` files and appending commands you would like to be executed just before entering the interactive prompt. For example:

```
# file : ~/.pdbrc
skip_predicates readonly True
skip_predicates tbhide False
```

Will hide read only frames by default and show frames marked with `__tracebackhide__`.

Thanks

Many thanks to all the contributors to this release you can find all individual contributions to this milestone [on github](#).

Thanks as well to the [D. E. Shaw group](#) for sponsoring work on IPython and related libraries, in particular above mentioned improvements to the debugger.

2.4.12 IPython 7.23 and 7.23.1

Third release of IPython for 2021, mostly containing bug fixes. A couple of not typical updates:

- We moved to GitHub actions away from Travis-CI, the transition may not be 100% complete (not testing on nightly anymore), but as we ran out of Travis-Ci hours on the IPython organisation that was a necessary step. [PR #12900](#).
- We have a new dependency: `matplotlib-inline`, which try to extract matplotlib inline backend specific behavior. It is available on PyPI and conda-forge thus should not be a problem to upgrade to this version. If you are a package maintainer that might be an extra dependency to package first. [PR #12817](#) (IPython 7.23.1 fix a typo that made this change fail)

In the addition/new feature category, `display()` now have a `clear=True` option to clear the display if any further outputs arrives, allowing users to avoid having to use `clear_output()` directly. [PR #12823](#).

In bug fixes category, this release fix an issue when printing tracebacks containing Unicode characters [PR #12758](#).

In code cleanup category [PR #12932](#) remove usage of some deprecated functionality for compatibility with Python 3.10.

Thanks

Many thanks to all the contributors to this release you can find all individual contributions to this milestone [on github](#). In particular MrMino for responding to almost all new issues, and triaging many of the old ones, as well as takluyver, minrk, willinge for reacting quickly when we ran out of CI Hours.

Thanks as well to organisations, QuantStack (martinRenou and SylvainCorlay) for extracting matplotlib inline backend into its own package, and the [D. E. Shaw group](#) for sponsoring work on IPython and related libraries.

2.4.13 IPython 7.22

Second release of IPython for 2021, mostly containing bug fixes. Here is a quick rundown of the few changes.

- Fix some `sys.excepthook` shenanigan when embedding with qt, recommended if you – for example – use `napari`. [PR #12842](#).
- Fix bug when using the new `ipdb %context` magic [PR #12844](#)
- Couples of deprecation cleanup [PR #12868](#)
- Update for new `dpaste.com` api if you use the `%pastbin` magic. [PR #12712](#)
- Remove support for numpy before 1.16. [PR #12836](#)

Thanks

We have a new team member that you should see more often on the IPython repository, Błażej Michalik (@MrMino) have been doing regular contributions to IPython, and spent time replying to many issues and guiding new users to the codebase; they now have triage permissions to the IPython repository and we'll work toward giving them more permission in the future.

Many thanks to all the contributors to this release you can find all individual contributions to this milestone [on github](#).

Thanks as well to organisations, QuantStack for working on debugger compatibility for `Xeus_python`, and the [D. E. Shaw group](#) for sponsoring work on IPython and related libraries.

2.4.14 IPython 7.21

IPython 7.21 is the first release we have back on schedule of one release every month; it contains a number of minor fixes and improvements, notably, the new context command for `ipdb`

New «context» command in ipdb

It is now possible to change the number of lines shown in the backtrace information in ipdb using «context» command. [PR #12826](#)

(thanks @MrMino, there are other improvement from them on master).

Other notable changes in IPython 7.21

- Fix some issues on new osx-arm64 [PR #12804](#), [PR #12807](#).
- Compatibility with Xeus-Python for debugger protocol, [PR #12809](#)
- Misc docs fixes for compatibility and uniformity with Numpydoc. [PR #12824](#)

Thanks

Many thanks to all the contributors to this release you can find all individual contribution to this milestone [on github](#).

2.4.15 IPython 7.20

IPython 7.20 is the accumulation of 3 month of work on IPython, spacing between IPython release have been increased from the usual once a month for various reason.

- Mainly as I'm too busy and the effectively sole maintainer, and
- Second because not much changes happened before mid December.

The main driver for this release was the new version of Jedi 0.18 breaking API; which was taken care of in the master branch early in 2020 but not in 7.x as I though that by now 8.0 would be out.

The inclusion of a resolver in pip did not help and actually made things worse. If usually I would have simply pinned Jedi to <0.18; this is not a solution anymore as now pip is free to install Jedi 0.18, and downgrade IPython.

I'll do my best to keep the regular release, but as the 8.0-dev branch and 7.x are starting to diverge this is becoming difficult in particular with my limited time, so if you have any cycles to spare I'll appreciate your help to respond to issues and pushing 8.0 forward.

Here are thus some of the changes for IPython 7.20.

- Support for PyQt5 >= 5.11 [PR #12715](#)
- `%reset` remove imports more aggressively [PR #12718](#)
- fix the `%conda` magic [PR #12739](#)
- compatibility with Jedi 0.18, and bump minimum Jedi version. [PR #12793](#)

2.4.16 IPython 7.19

IPython 7.19 accumulative two month of works, bug fixes and improvements, there was exceptionally no release last month.

- Fix to restore the ability to specify more than one extension using command line flags when using traitlets 5.0 [PR #12543](#)
- Docs docs formatting that make the install commands work on zsh [PR #12587](#)
- Always display the last frame in tracebacks even if hidden with `__tracebackhide__` [PR #12601](#)
- Avoid an issue where a callback can be registered multiple times. [PR #12625](#)
- Avoid an issue in debugger mode where frames changes could be lost. [PR #12627](#)
- Never hide the frames that invoke a debugger, even if marked as hidden by `__tracebackhide__` [PR #12631](#)
- Fix calling the debugger in a recursive manner [PR #12659](#)

A number of code changes have landed on master and we are getting close to enough new features and codebase improvement that a 8.0 start to make sens. For downstream packages, please start working on migrating downstream testing away from iptest and using pytest, as nose will not work on Python 3.10 and we will likely start removing it as a dependency for testing.

2.4.17 IPython 7.18

IPython 7.18 is a minor release that mostly contains bugfixes.

- CRLF is now handled by magics my default; solving some issues due to copy pasting on windows. [PR #12475](#)
- Requiring pexpect `>=4.3` as we are Python 3.7+ only and earlier version of pexpect will be incompatible. [PR #12510](#)
- Minimum jedi version is now 0.16. [PR #12488](#)

2.4.18 IPython 7.17

IPython 7.17 brings a couple of new improvements to API and a couple of user facing changes to make the terminal experience more user friendly.

[PR #12407](#) introduces the ability to pass extra argument to the IPython debugger class; this is to help a new project from [kmaork](https://github.com/kmaork/madbg) (<https://github.com/kmaork/madbg>) to feature a fully remote debugger.

[PR #12410](#) finally remove support for 3.6, while the codebase is still technically compatible; IPython will not install on Python 3.6.

lots of work on the debugger and hidden frames from [@impact27](#) in [PR #12437](#), [PR #12445](#), [PR #12460](#) and in particular [PR #12453](#) which make the debug magic more robust at handling spaces.

Biggest API addition is code transformation which is done before code execution; IPython allows a number of hooks to catch non-valid Python syntax (magic, prompt stripping... etc). Transformers are usually called many time; typically:

- When trying to figure out whether the code is complete and valid (should we insert a new line or execute ?)
- During actual code execution pass before giving the code to Python's `exec`.

This lead to issues when transformer might have had side effects; or do external queries. Starting with IPython 7.17 you can expect your transformer to be called less time.

Input transformers are now called only once in the execution path of `InteractiveShell`, allowing to register transformer that potentially have side effects (note that this is not recommended). Internal methods `should_run_async`, and `run_cell_async` now take a recommended optional `transformed_cell`, and `preprocessing_exc_tuple` parameters that will become mandatory at some point in the future; that is to say cells need to be explicitly transformed to be valid Python syntax ahead of trying to run them. [PR #12440](#);

`input_transformers` can now also have an attribute `has_side_effects` set to `True`, when this attribute is present; this will prevent the transformers from being ran when IPython is trying to guess whether the user input is complete. Note that this may means you will need to explicitly execute in some case where your transformations are now not ran; but will not affect users with no custom extensions.

API Changes

Change of API and exposed objects automatically detected using [frappuccino](#)

The following items are new since 7.16.0:

```
+ IPython.core.interactiveshell.InteractiveShell.get_local_scope(self, stack_
↳ depth)
```

The following signatures differ since 7.16.0:

```
- IPython.core.interactiveshell.InteractiveShell.run_cell_async(self, raw_cell,
↳ store_history=False, silent=False, shell_futures=True)
+ IPython.core.interactiveshell.InteractiveShell.run_cell_async(self, raw_cell,
↳ store_history=False, silent=False, shell_futures=True, *, transformed_
↳ cell=None, preprocessing_exc_tuple=None)

- IPython.core.interactiveshell.InteractiveShell.should_run_async(self, raw_
↳ cell)
+ IPython.core.interactiveshell.InteractiveShell.should_run_async(self, raw_
↳ cell, *, transformed_cell=None, preprocessing_exc_tuple=None)

- IPython.terminal.debugger.TerminalPdb.pt_init(self)
+ IPython.terminal.debugger.TerminalPdb.pt_init(self, pt_session_options=None)
```

This method was added:

```
+ IPython.core.interactiveshell.InteractiveShell.get_local_scope
```

Which is now also present on subclasses:

```
+ IPython.terminal.embed.InteractiveShellEmbed.get_local_scope
+ IPython.terminal.interactiveshell.TerminalInteractiveShell.get_local_scope
```

2.4.19 IPython 7.16.1, 7.16.2

IPython 7.16.1 was release immediately after 7.16.0 to fix a conda packaging issue. The source is identical to 7.16.0 but the file permissions in the tar are different.

IPython 7.16.2 pins jedi dependency to «<=0.17.2» which should prevent some issues for users still on python 3.6. This may not be sufficient as pip may still allow to downgrade IPython.

Compatibility with Jedi > 0.17.2 was not added as this would have meant bumping the minimal version to >0.16.

2.4.20 IPython 7.16

The default traceback mode will now skip frames that are marked with `__tracebackhide__ = True` and show how many traceback frames have been skipped. This can be toggled by using `%xmode` with the `--show` or `--hide` attribute. It will have no effect on non verbose traceback modes.

The ipython debugger also now understands `__tracebackhide__` as well and will skip hidden frames when displaying. Movement up and down the stack will skip the hidden frames and will show how many frames were hidden. Internal IPython frames are also now hidden by default. The behavior can be changed with the `skip_hidden` while in the debugger, command and accepts «yes», «no», «true» and «false» case insensitive parameters.

Misc Noticeable changes:

- Exceptions are now (re)raised when running notebooks via the `%run`, helping to catch issues in workflows and pipelines. [PR #12301](#)
- Fix inputhook for qt 5.15.0 [PR #12355](#)
- Fix wx inputhook [PR #12375](#)
- Add handling for malformed pathext env var (Windows) [PR #12367](#)
- use \$SHELL in `system_piped` [PR #12360](#) for uniform behavior with ipykernel.

Reproducible Build

IPython 7.15 reproducible build did not work, so we try again this month [PR #12358](#).

API Changes

Change of API and exposed objects automatically detected using `frappuccino` (still in beta):

The following items are new and mostly related to understanding `__tracebackhide__`:

```
+ IPython.core.debugger.Pdb.do_down(self, arg)
+ IPython.core.debugger.Pdb.do_skip_hidden(self, arg)
+ IPython.core.debugger.Pdb.do_up(self, arg)
+ IPython.core.debugger.Pdb.hidden_frames(self, stack)
+ IPython.core.debugger.Pdb.stop_here(self, frame)
```

The following items have been removed:

```
- IPython.core.debugger.Pdb.new_do_down
- IPython.core.debugger.Pdb.new_do_up
```

Those were implementation details.

2.4.21 IPython 7.15

IPython 7.15 brings a number of bug fixes and user facing improvements.

Misc Noticeable changes:

- Long completion name have better elision in terminal [PR #12284](#)
- I've started to test on Python 3.9 [PR #12307](#) and fix some errors.
- Hi DPI scaling of figures when using qt eventloop [PR #12314](#)
- Document the ability to have systemwide configuration for IPython. [PR #12328](#)
- Fix issues with input autoformatting [PR #12336](#)
- `IPython.core.debugger.Pdb` is now interruptible ([PR #12168](#), in 7.14 but forgotten in release notes)
- Video HTML attributes ([PR #12212](#), in 7.14 but forgotten in release notes)

Reproducible Build

Starting with IPython 7.15, I am attempting to provide reproducible builds, that is to say you should be able from the source tree to generate an sdist and wheel that are identical byte for byte with the publish version on PyPI.

I've only tested on a couple of machines so far and the process is relatively straightforward, so this mean that IPython not only have a deterministic build process, but also I have either removed, or put under control all effects of the build environments on the final artifact. I encourage you to attempt the build process on your machine as documented in *Guide for IPython core Developers* and let me know if you do not obtain an identical artifact.

While reproducible builds is critical to check that the supply chain of (open source) software has not been compromised, it can also help to speedup many of the build processes in large environment (conda, apt...) by allowing better caching of intermediate build steps.

Learn more on <https://reproducible-builds.org/>. [Reflections on trusting trust](#) is also one of the cornerstone and recommended reads on this subject.

Примечание: The build commit from which the sdist is generated is also [signed](#), so you should be able to check it has not been compromised, and the git repository is a [merkle-tree](#), you can check the consistency with `git-fsck` which you likely want to enable by default.

NEP29: Last version to support Python 3.6

IPython 7.15 will be the Last IPython version to officially support Python 3.6, as stated by [NumPy Enhancement Proposal 29](#). Starting with next minor version of IPython I may stop testing on Python 3.6 and may stop publishing release artifacts that install on Python 3.6

Highlighted features

Highlighted features are not new, but seem to not be widely known, this section will help you discover in more narrative form what you can do with IPython.

Increase Tab Completion Menu Height

In terminal IPython it is possible to increase the height of the tab-completion menu. To do so set the value of `TerminalInteractiveShell.space_for_menu`, this will reserve more space at the bottom of the screen for various kind of menus in IPython including tab completion and searching in history.

Autoformat Code in the terminal

If you have a preferred code formatter, you can configure IPython to reformat your code. Set the value of `TerminalInteractiveShell.autoformatter` to for example 'black' and IPython will auto format your code when possible.

2.4.22 IPython 7.14

IPython 7.14 is a minor release that fix a couple of bugs and prepare compatibility with new or future versions of some libraries.

Important changes:

- Fix compatibility with Sphinx 3+ [PR #12235](#)
- Remove deprecated matplotlib parameter usage, compatibility with matplotlib 3.3+ [:122250](#)

Misc Changes

- set .py extension when editing current buffer in vi/emacs. [PR #12167](#)
- support for unicode identifiers in `?/??` [PR #12208](#)
- add extra options to the Video Rich objects [PR #12212](#)
- add pretty-printing to SimpleNamespace [PR #12230](#)

IPython.core.debugger.Pdb is now interruptible

A `KeyboardInterrupt` will now interrupt IPython's extended debugger, in order to make Jupyter able to interrupt it. (PR #12168)

Video HTML attributes

Add an option to `IPython.display.Video` to change the attributes of the HTML display of the video (PR #12212)

Pending deprecated imports

Many object present in `IPython.core.display` are there for internal use only, and should already been imported from `IPython.display` by users and external libraries. Trying to import those from `IPython.core.display` is still possible but will trigger a deprecation warning in later versions of IPython and will become errors in the future.

This will simplify compatibility with other Python kernels (like Xeus-Python), and simplify code base.

2.4.23 IPython 7.13

IPython 7.13 is the final release of the 7.x branch since master is diverging toward an 8.0. Exiting new features have already been merged in 8.0 and will not be available on the 7.x branch. All the changes below have been backported from the master branch.

- Fix inability to run PDB when inside an event loop PR #12141
- Fix ability to interrupt some processes on windows PR #12137
- Fix debugger shortcuts PR #12132
- improve tab completion when inside a string by removing irrelevant elements PR #12128
- Fix display of filename tab completion when the path is long PR #12122
- Many removal of Python 2 specific code path PR #12110
- displaying wav files do not require NumPy anymore, and is 5x to 30x faster PR #12113

See the list of all closed issues and pull request on [github](#).

2.4.24 IPython 7.12

IPython 7.12 is a minor update that mostly brings code cleanup, removal of longtime deprecated function and a couple update to documentation cleanup as well.

Notable changes are the following:

- Exit non-zero when ipython is given a file path to run that doesn't exist PR #12074
- Test PR on ARM64 with Travis-CI PR #12073
- Update CI to work with latest Pytest PR #12086
- Add infrastructure to run ipykernel eventloop via trio PR #12097
- Support git blame ignore revs PR #12091
- Start multi-line `__repr__` s on their own line PR #12099

2.4.25 IPython 7.11.1

A couple of deprecated functions (no-op) have been reintroduces in `py3compat` as Cython was still relying on them, and will be removed in a couple of versions.

2.4.26 IPython 7.11

IPython 7.11 received a couple of compatibility fixes and code cleanup.

A number of function in the `py3compat` have been removed; a number of types in the IPython code base are now non-ambiguous and now always `unicode` instead of `Union[Unicode,bytes]`; many of the relevant code path have thus been simplified/cleaned and types annotation added.

IPython support several verbosity level from exceptions. `xmode plain` now support chained exceptions. [PR #11999](#)

We are starting to remove `shell=True` in some usages of subprocess. While not directly a security issue (as IPython is made to run arbitrary code anyway) it is not good practice and we'd like to show the example. [#12023](#). This discussion was started by [@mschwager](#) thanks to a new auditing tool they are working on with duo-labs ([dlint](#)).

Work around some bugs in Python 3.9 tokenizer [PR #12057](#)

IPython will now print its version after a crash. [PR #11986](#)

This is likely the last release from the 7.x series that will see new feature. The master branch will soon accept large code changes and thrilling new features; the 7.x branch will only start to accept critical bug fixes, and update dependencies.

2.4.27 IPython 7.10.2

IPython 7.10.2 fix a couple of extra incompatibility between IPython, ipdb, asyncio and Prompt Toolkit 3.

2.4.28 IPython 7.10.1

IPython 7.10.1 fix a couple of incompatibilities with Prompt toolkit 3 (please update Prompt toolkit to 3.0.2 at least), and fixes some interaction with headless IPython.

2.4.29 IPython 7.10.0

IPython 7.10 is the first double digit minor release in the last decade, and first since the release of IPython 1.0, previous double digit minor release was in August 2009.

We've been trying to give you regular release on the last Friday of every month for a guaranty of rapid access to bug fixes and new features.

Unlike the previous first few releases that have seen only a couple of code changes, 7.10 bring a number of changes, new features and bugfixes.

Stop Support for Python 3.5 – Adopt NEP 29

IPython has decided to follow the informational [NEP 29](#) which layout a clear policy as to which version of (C)Python and NumPy are supported.

We thus dropped support for Python 3.5, and cleaned up a number of code path that were Python-version dependant. If you are on 3.5 or earlier pip should automatically give you the latest compatible version of IPython so you do not need to pin to a given version.

Support for Prompt Toolkit 3.0

Prompt Toolkit 3.0 was release a week before IPython 7.10 and introduces a few breaking changes. We believe IPython 7.10 should be compatible with both Prompt Toolkit 2.x and 3.x, though it has not been extensively tested with 3.x so please report any issues.

Prompt Rendering Performance improvements

Pull Request [PR #11933](#) introduced an optimisation in the prompt rendering logic that should decrease the resource usage of IPython when using the `_default_` configuration but could potentially introduce a regression of functionalities if you are using a custom prompt.

We know assume if you haven't changed the default keybindings that the prompt **will not change** during the duration of your input – which is for example not true when using vi insert mode that switches between `[ins]` and `[nor]` for the current mode.

If you are experiencing any issue let us know.

Code autoformatting

The IPython terminal can now auto format your code just before entering a new line or executing a command. To do so use the `--TerminalInteractiveShell.autoformatter` option and set it to `'black'`; if black is installed IPython will use black to format your code when possible.

IPython cannot always properly format your code; in particular it will auto formatting with *black* will only work if:

- Your code does not contains magics or special python syntax.
- There is no code after your cursor.

The Black API is also still in motion; so this may not work with all versions of black.

It should be possible to register custom formatter, though the API is till in flux.

Arbitrary Mimetypes Handing in Terminal (Aka inline images in terminal)

When using IPython terminal it is now possible to register function to handle arbitrary mimetypes. While rendering non-text based representation was possible in many jupyter frontend; it was not possible in terminal IPython, as usually terminal are limited to displaying text. As many terminal these days provide escape sequences to display non-text; bringing this loved feature to IPython CLI made a lot of sens. This functionality will not only allow inline images; but allow opening of external program; for example `mplayer` to «display» sound files.

So far only the hooks necessary for this are in place, but no default mime renderers added; so inline images will only be available via extensions. We will progressively enable these features by default in the next few releases, and contribution is welcomed.

We welcome any feedback on the API. See [Mime Renderer Extensions](#) for more informations.

This is originally based on work from in [PR #10610](#) from @stephanh42 started over two years ago, and still a lot need to be done.

MISC

- Completions can define their own ordering [PR #11855](#)
- Enable Plotting in the same cell than the one that import matplotlib [PR #11916](#)
- Allow to store and restore multiple variables at once [PR #11930](#)

You can see [all pull-requests](#) for this release.

API Changes

Change of API and exposed objects automatically detected using [frappuccino](#) (still in beta):

The following items are new in IPython 7.10:

```
+ IPython.terminal.shortcuts.reformat_text_before_cursor(buffer, document, shell)
+ IPython.terminal.interactiveshell.PTK3
+ IPython.terminal.interactiveshell.black_reformat_handler(text_before_cursor)
+ IPython.terminal.prompts.RichPromptDisplayHook.write_format_data(self, format_dict, md_
↪dict='None')
```

The following items have been removed in 7.10:

```
- IPython.lib.pretty.DICT_IS_ORDERED
```

The following signatures differ between versions:

```
- IPython.extensions.storemagic.restore_aliases(ip)
+ IPython.extensions.storemagic.restore_aliases(ip, alias='None')
```

Special Thanks

- @stephanh42 who started the work on inline images in terminal 2 years ago
- @augustogoulart who spent a lot of time triaging issues and responding to users.
- @con-f-use who is my (@Carreau) first sponsor on GitHub, as a reminder if you like IPython, Jupyter and many other library of the SciPy stack you can donate to [numfocus.org](#) non profit

2.4.30 IPython 7.9.0

IPython 7.9 is a small release with a couple of improvement and bug fixes.

- Xterm terminal title should be restored on exit [PR #11910](#)
- special variables `_`, `__``, `___` are not set anymore when cache size is 0 or less. [PR #11877](#)
- Autoreload should have regained some speed by using a new heuristic logic to find all objects needing reload. This should avoid large objects traversal like pandas dataframes. [PR #11876](#)
- Get ready for Python 4. [PR #11874](#)

- `%env` Magic now has heuristic to hide potentially sensitive values [PR #11896](#)

This is a small release despite a number of Pull Request Pending that need to be reviewed/worked on. Many of the core developers have been busy outside of IPython/Jupyter and we thanks all contributor for their patience; we'll work on these as soon as we have time.

2.4.31 IPython 7.8.0

IPython 7.8.0 contain a few bugfix and 2 new APIs:

- Enable changing the font color for LaTeX rendering [PR #11840](#)
- and Re-Expose some PDB API (see below)

Expose Pdb API

Expose the built-in `pdb.Pdb` API. `Pdb` constructor arguments are generically exposed, regardless of python version. Newly exposed arguments:

- `skip` - Python 3.1+
- `nosiginnt` - Python 3.2+
- `readrc` - Python 3.6+

Try it out:

```
from IPython.terminal.debugger import TerminalPdb
pdb = TerminalPdb(skip=["skipthismodule"])
```

See [PR #11840](#)

2.4.32 IPython 7.7.0

IPython 7.7.0 contain multiple bug fixes and documentation updates; Here are a few of the outstanding issue fixed:

- Fix a bug introduced in 7.6 where the `%matplotlib` magic would fail on previously acceptable arguments [PR #11814](#).
- Fix the manage location on freebsd [PR #11808](#).
- Fix error message about aliases after `%reset` call in ipykernel [PR #11806](#)
- Fix Duplication completions in emacs [PR #11803](#)

We are planning to adopt [NEP29](#) (still currently in draft) which may make this minor version of IPython the last one to support Python 3.5 and will make the code base more aggressive toward removing compatibility with older versions of Python.

GitHub now support to give only «Triage» permissions to users; if you'd like to help close stale issues and labels issues please reach to us with your GitHub Username and we'll add you to the triage team. It is a great way to start contributing and a path toward getting commit rights.

2.4.33 IPython 7.6.1

IPython 7.6.1 contain a critical bugfix in the `%timeit` magic, which would crash on some inputs as a side effect of [PR #11716](#). See [PR #11812](#)

2.4.34 IPython 7.6.0

IPython 7.6.0 contains a couple of bug fixes and number of small features additions as well as some compatibility with the current development version of Python 3.8.

- Add a `-l` option to `%psearch` to list the available search types. [PR #11672](#)
- Support `PathLike` for `DisplayObject` and `Image`. [PR #11764](#)
- Configurability of timeout in the test suite for slow platforms. [PR #11756](#)
- Accept any casing for matplotlib backend. [PR #121748](#)
- Properly skip test that requires numpy to be installed [PR #11723](#)
- More support for Python 3.8 and positional only arguments (pep570) [PR #11720](#)
- Unicode names for the completion are loaded lazily on first use which should decrease startup time. [PR #11693](#)
- Autoreload now update the types of reloaded objects; this for example allow pickling of reloaded objects. [PR #11644](#)
- Fix a bug where `%%time` magic would suppress cell output. [PR #11716](#)

Prepare migration to pytest (instead of nose) for testing

Most of the work between 7.5 and 7.6 was to prepare the migration from our testing framework to pytest. Most of the test suite should now work by simply issuing `pytest` from the root of the repository.

The migration to pytest is just at its beginning. Many of our test still rely on IPython-specific plugins for nose using pytest (doctest using IPython syntax is one example of this where test appear as «passing», while no code has been ran). Many test also need to be updated like `yield-test` to be properly parametrized tests.

Migration to pytest allowed me to discover a number of issues in our test suite; which was hiding a number of subtle issues – or not actually running some of the tests in our test suite – I have thus corrected many of those; like improperly closed resources; or used of deprecated features. I also made use of the `pytest --durations=...` to find some of our slowest test and speed them up (our test suite can now be up to 10% faster). Pytest as also a variety of plugins and flags which will make the code quality of IPython and the testing experience better.

Misc

We skipped the release of 7.6 at the end of May, but will attempt to get back on schedule. We are starting to think about making introducing backward incompatible change and start the 8.0 series.

Special Thanks to Gabriel (@gpotter2 on GitHub), who among other took care many of the remaining task for 7.4 and 7.5, like updating the website.

2.4.35 IPython 7.5.0

IPython 7.5.0 consist mostly of bug-fixes, and documentation updates, with one minor new feature. The Audio display element can now be assigned an element id when displayed in browser. See [PR #11670](#)

The major outstanding bug fix correct a change of behavior that was introduce in 7.4.0 where some cell magics would not be able to access or modify global scope when using the `@needs_local_scope` decorator. This was typically encountered with the `%%time` and `%%timeit` magics. See [#11659](#) and [PR #11698](#).

2.4.36 IPython 7.4.0

Unicode name completions

Previously, we provided completion for a unicode name with its relative symbol. With this, now IPython provides complete suggestions to unicode name symbols.

As on the PR, if user types `\LAT<tab>`, IPython provides a list of possible completions. In this case, it would be something like:

```
'LATIN CAPITAL LETTER A',
'LATIN CAPITAL LETTER B',
'LATIN CAPITAL LETTER C',
'LATIN CAPITAL LETTER D',
....
```

This help to type unicode character that do not have short latex aliases, and have long unicode names. for example , `\GREEK CAPITAL LETTER HETA`.

This feature was contributed by Luciana Marques [PR #11583](#).

Make audio normalization optional

Added „normalize“ argument to `IPython.display.Audio`. This argument applies when audio data is given as an array of samples. The default of `normalize=True` preserves prior behavior of normalizing the audio to the maximum possible range. Setting to `False` disables normalization.

Miscellaneous

- Fix improper acceptance of `return` outside of functions. [PR #11641](#).
- Fixed PyQt 5.11 backwards incompatibility causing sip import failure. [PR #11613](#).
- Fix Bug where `type?` would crash IPython. [PR #1608](#).
- Allow to apply `@needs_local_scope` to cell magics for convenience. [PR #11542](#).

2.4.37 IPython 7.3.0

IPython 7.3.0 bring several bug fixes and small improvements that you will described bellow.

The biggest change to this release is the implementation of the `%conda` and `%pip` magics, that will attempt to install packages in the **current environment**. You may still need to restart your interpreter or kernel for the change to be taken into account, but it should simplify installation of packages into remote environment. Installing using pip/conda from the command line is still the prefer method.

The `%pip` magic was already present, but was only printing a warning; now it will actually forward commands to pip.

Misc bug fixes and improvements:

- Compatibility with Python 3.8.
- Do not expand shell variable in execution magics, and added the `no_var_expand` decorator for magic requiring a similar functionality [PR #11516](#)
- Add `%pip` and `%conda` magic [PR #11524](#)
- Re-initialize posix aliases after a `%reset` [PR #11528](#)
- Allow the IPython command line to run `*.ipynb` files [PR #11529](#)

2.4.38 IPython 7.2.0

IPython 7.2.0 brings minor bugfixes, improvements, and new configuration options:

- Fix a bug preventing PySide2 GUI integration from working [PR #11464](#)
- Run CI on Mac OS ! [PR #11471](#)
- Fix IPython «Demo» mode. [PR #11498](#)
- Fix `%run` magic with path in name [PR #11499](#)
- Fix: add CWD to sys.path *after* stdlib [PR #11502](#)
- Better rendering of signatures, especially long ones. [PR #11505](#)
- Re-enable jedi by default if it's installed [PR #11506](#)
- Add New `minimal` exception reporting mode (useful for educational purpose). See [PR #11509](#)

Added ability to show subclasses when using `pinfo` and other utilities

When using `?/??` on a class, IPython will now list the first 10 subclasses.

Special Thanks to Chris Mentzel of the Moore Foundation for this feature. Chris is one of the people who played a critical role in IPython/Jupyter getting funding.

We are grateful for all the help Chris has given us over the years, and we're now proud to have code contributed by Chris in IPython.

OSMagics.cd_force_quiet configuration option

You can set this option to force the %cd magic to behave as if -q was passed:

```
In [1]: cd /
/

In [2]: %config OSMagics.cd_force_quiet = True

In [3]: cd /tmp

In [4]:
```

See [PR #11491](#)

In vi editing mode, whether the prompt includes the current vi mode can now be configured

Set the `TerminalInteractiveShell.prompt_includes_vi_mode` to a boolean value (default: True) to control this feature. See [PR #11492](#)

2.4.39 IPython 7.1.0

IPython 7.1.0 is the first minor release after 7.0.0 and mostly brings fixes to new features, internal refactoring, and fixes for regressions that happened during the 6.x->7.x transition. It also brings **Compatibility with Python 3.7.1**, as we're unwillingly relying on a bug in CPython.

New Core Dev:

- We welcome Jonathan Slenders to the committers. Jonathan has done a fantastic work on `prompt_toolkit`, and we'd like to recognise his impact by giving him commit rights. [#11397](#)

Notable Changes

- Major update of «latex to unicode» tab completion map (see below)

Notable New Features:

- Restore functionality and documentation of the **sphinx directive**, which is now stricter (fail on error by default), has new configuration options, has a brand new documentation page *Директива IPython Sphinx* (which needs some cleanup). It is also now *tested* so we hope to have less regressions. [PR #11402](#)
- `IPython.display.Video` now supports `width` and `height` arguments, allowing a custom width and height to be set instead of using the video's width and height. [PR #11353](#)
- Warn when using `HTML('<iframe>')` instead of `IFrame` [PR #11350](#)
- Allow Dynamic switching of editing mode between vi/emacs and show normal/input mode in prompt when using vi. [PR #11390](#). Use `%config TerminalInteractiveShell.editing_mode = 'vi'` or `%config TerminalInteractiveShell.editing_mode = 'emacs'` to dynamically switch between modes.

Notable Fixes:

- Fix entering of **multi-line blocks in terminal** IPython, and various crashes in the new input transformation machinery [PR #11354](#), [PR #11356](#), [PR #11358](#). These also fix a **Compatibility bug with Python 3.7.1**.
- Fix moving through generator stack in ipdb [PR #11266](#)

- %Magic command arguments now support quoting. [PR #11330](#)
- Re-add `rprint` and `rprinte` aliases. [PR #11331](#)
- Remove implicit dependency on `ipython_genutils` [PR #11317](#)
- Make `nonlocal` raise `SyntaxError` instead of silently failing in `async` mode. [PR #11382](#)
- Fix mishandling of magics and `= !` assignment just after a `dedent` in nested code blocks [PR #11418](#)
- Fix instructions for custom shortcuts [PR #11426](#)

Notable Internals improvements:

- Use of `os.scandir` (Python 3 only) to speed up some file system operations. [PR #11365](#)
- use `perf_counter` instead of `clock` for more precise timing results with `%time` [PR #11376](#)

Many thanks to all the contributors and in particular to `bartskowron` and `tonyfast` who handled some pretty complicated bugs in the input machinery. We had a number of first time contributors and maybe hacktoberfest participants that made significant contributions and helped us free some time to focus on more complicated bugs.

You can see all the closed issues and Merged PR, new features and fixes [here](#).

Unicode Completion update

In IPython 7.1 the Unicode completion map has been updated and synchronized with the Julia language.

Added and removed character characters:

`\jmath ()`, `\underleftrightharrow` (U+034D, combining) have been added, while `\textasciicaron` have been removed

Some sequences have seen their prefix removed:

- 6 characters `\text...<tab>` should now be inputted with `\...<tab>` directly,
- 45 characters `\Elz...<tab>` should now be inputted with `\...<tab>` directly,
- 65 characters `\B...<tab>` should now be inputted with `\...<tab>` directly,
- 450 characters `\m...<tab>` should now be inputted with `\...<tab>` directly,

Some sequences have seen their prefix shortened:

- 5 characters `\mitBbb...<tab>` should now be inputted with `\bbi...<tab>` directly,
- 52 characters `\mit...<tab>` should now be inputted with `\i...<tab>` directly,
- 216 characters `\mbfit...<tab>` should now be inputted with `\bi...<tab>` directly,
- 222 characters `\mbf...<tab>` should now be inputted with `\b...<tab>` directly,

A couple of characters had their sequence simplified:

- , type `\dh<tab>`, instead of `\eth<tab>`
- , type `\hbar<tab>`, instead of `\Elzxh<tab>`
- , type `\ltphi<tab>`, instead of `\textphi<tab>`
- , type `\varTheta<tab>`, instead of `\textTheta<tab>`
- , type `\eulermascheroni<tab>`, instead of `\Eulerconst<tab>`
- , type `\planck<tab>`, instead of `\Planckconst<tab>`

- U+0336 (COMBINING LONG STROKE OVERLAY), type `\strike<tab>`, instead of `\Elzbar<tab>`.

A couple of sequences have been updated:

- `\varepsilon` now gives (GREEK SMALL LETTER EPSILON) instead of (GREEK LUNATE EPSILON SYMBOL),
- `\underbar` now gives U+0331 (COMBINING MACRON BELOW) instead of U+0332 (COMBINING LOW LINE).

2.4.40 IPython 7.0.0

Released Thursday September 27th, 2018

IPython 7 includes major feature improvements. This is also the second major version of IPython to support only Python 3 – starting at Python 3.4. Python 2 is still community-supported on the bugfix only 5.x branch, but we remind you that Python 2 «end of life» is on Jan 1st 2020.

We were able to backport bug fixes to the 5.x branch thanks to our backport bot which backported more than [70 Pull-Requests](#), but there are still many PRs that required manual work. This is an area of the project where you can easily contribute by looking for [PRs that still need manual backport](#)

The IPython 6.x branch will likely not see any further release unless critical bugs are found.

Make sure you have `pip > 9.0` before upgrading. You should be able to update by running:

```
pip install ipython --upgrade
```

If you are trying to install or update an `alpha`, `beta`, or `rc` version, use `pip --pre` flag.

```
pip install ipython --upgrade --pre
```

Or, if you have conda installed:

```
conda install ipython
```

Prompt Toolkit 2.0

IPython 7.0+ now uses `prompt_toolkit 2.0`. If you still need to use an earlier `prompt_toolkit` version, you may need to pin IPython to `<7.0`.

Autowait: Asynchronous REPL

Starting with IPython 7.0 on Python 3.6+, IPython can automatically `await` top level code. You should not need to access an event loop or runner yourself. To learn more, read the [Asynchronous in REPL: Autoawait](#) section of our docs, see [PR #11265](#), or try the following code:

```
Python 3.6.0
Type 'copyright', 'credits' or 'license' for more information
IPython 7.0.0 -- An enhanced Interactive Python. Type '?' for help.

In [1]: import aiohttp
...: result = aiohttp.get('https://api.github.com')

In [2]: response = await result
```

(continues on next page)

(продолжение с предыдущей страницы)

```
<pause for a few 100s ms>

In [3]: await response.json()
Out[3]:
{'authorizations_url': 'https://api.github.com/authorizations',
 'code_search_url': 'https://api.github.com/search/code?q={query}&page,per_page,sort,
↩order}',
 ...
}
```

Примечание: Async integration is experimental code, behavior may change or be removed between Python and IPython versions without warnings.

Integration is by default with `asyncio`, but other libraries can be configured – like `curio` or `trio` – to improve concurrency in the REPL:

```
In [1]: %autoawait trio

In [2]: import trio

In [3]: async def child(i):
...:     print("  child %s goes to sleep"%i)
...:     await trio.sleep(2)
...:     print("  child %s wakes up"%i)

In [4]: print('parent start')
...: async with trio.open_nursery() as n:
...:     for i in range(3):
...:         n.spawn(child, i)
...:     print('parent end')
parent start
  child 2 goes to sleep
  child 0 goes to sleep
  child 1 goes to sleep
<about 2 seconds pause>
  child 2 wakes up
  child 1 wakes up
  child 0 wakes up
parent end
```

See *Asynchronous in REPL: Autoawait* for more information.

Asynchronous code in a Notebook interface or any other frontend using the Jupyter Protocol will require further updates to the IPykernel package.

Non-Asynchronous code

As the internal API of IPython is now asynchronous, IPython needs to run under an event loop. In order to allow many workflows, (like using the `%run` magic, or copy-pasting code that explicitly starts/stop event loop), when top-level code is detected as not being asynchronous, IPython code is advanced via a pseudo-synchronous runner, and may not advance pending tasks.

Change to Nested Embed

The introduction of the ability to run async code had some effect on the `IPython.embed()` API. By default, embed will not allow you to run asynchronous code unless an event loop is specified.

Effects on Magics

Some magics will not work with async until they're updated. Contributions welcome.

Expected Future changes

We expect more internal but public IPython functions to become `async`, and will likely end up having a persistent event loop while IPython is running.

Thanks

This release took more than a year in the making. The code was rebased a number of times; leading to commit authorship that may have been lost in the final Pull-Request. Huge thanks to many people for contribution, discussion, code, documentation, use-cases: dalejung, danielballan, ellisonbg, fperez, gnestor, minrk, njsmith, pganssle, tacaswell, takluyver, vidartf ... And many others.

Autoreload Improvement

The magic `%autoreload 2` now captures new methods added to classes. Earlier, only methods existing as of the initial import were being tracked and updated.

This new feature helps dual environment development - Jupyter+IDE - where the code gradually moves from notebook cells to package files as it gets structured.

Example: An instance of the class `MyClass` will be able to access the method `cube()` after it is uncommented and the file `file1.py` is saved on disk.

```
# notebook

from mymodule import MyClass
first = MyClass(5)
```

```
# mymodule/file1.py

class MyClass:

    def __init__(self, a=10):
```

(continues on next page)

(продолжение с предыдущей страницы)

```
self.a = a

def square(self):
    print('compute square')
    return self.a*self.a

# def cube(self):
#     print('compute cube')
#     return self.a*self.a*self.a
```

Misc

The autoindent feature that was deprecated in 5.x was re-enabled and un-deprecated in [PR #11257](#)

Make `%run -n -i ...` work correctly. Earlier, if `%run` was passed both arguments, `-n` would be silently ignored. See [PR #10308](#)

The `%%script` (as well as `%%bash`, `%%ruby...`) cell magics now raise by default if the return code of the given code is non-zero (thus halting execution of further cells in a notebook). The behavior can be disabled by passing the `--no-raise-error` flag.

Deprecations

A couple of unused functions and methods have been deprecated and will be removed in future versions:

- `IPython.utils.io.raw_print_err`
- `IPython.utils.io.raw_print`

Backwards incompatible changes

- The API for transforming input before it is parsed as Python code has been completely redesigned: any custom input transformations will need to be rewritten. See [Custom input transformation](#) for details of the new API.

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

2.5 Issues closed in the 7.x development cycle

Stats are not collected after version 7.17, all contribution will show up as part of the 8.0 release.

2.5.1 Issues closed in 7.17

GitHub stats for 2020/06/26 - 2020/07/31 (tag: 7.16.1)

These lists are automatically generated, and may be incomplete or contain duplicates.

We closed 2 issues and merged 19 pull requests. The full list can be seen [on GitHub](#)

The following 3 authors contributed 31 commits.

- Maor Kleinberger
- Matthias Bussonnier
- Quentin Peter

2.5.2 Issues closed in 7.16

GitHub stats for 2020/05/29 - 2020/06/26 (tag: 7.15.0)

These lists are automatically generated, and may be incomplete or contain duplicates.

We closed 0 issues and merged 18 pull requests. The full list can be seen [on GitHub](#)

The following 7 authors contributed 22 commits.

- Benjamin Ragan-Kelley
- dalthviz
- Frank Tobia
- Matthias Bussonnier
- palewire
- Paul McCarthy
- Talley Lambert

2.5.3 Issues closed in 7.15

GitHub stats for 2020/05/01 - 2020/05/29 (tag: 7.14.0)

These lists are automatically generated, and may be incomplete or contain duplicates.

We closed 1 issues and merged 29 pull requests. The full list can be seen [on GitHub](#)

The following 6 authors contributed 31 commits.

- Blake Griffin
- Inception95
- Marcio Mazza
- Matthias Bussonnier
- Talley Lambert

- Thomas

2.5.4 Issues closed in 7.14

GitHub stats for 2020/02/29 - 2020/05/01 (tag: 7.13.0)

These lists are automatically generated, and may be incomplete or contain duplicates.

We closed 0 issues and merged 30 pull requests. The full list can be seen [on GitHub](#)

The following 10 authors contributed 47 commits.

- Eric Wieser
- foobarbyte
- Ian Castleden
- Itamar Turner-Trauring
- Lumir Balhar
- Markus Wageringel
- Matthias Bussonnier
- Matthieu Ancellin
- Quentin Peter
- Theo Ouzhinski

2.5.5 Issues closed in 7.13

GitHub stats for 2020/02/01 - 2020/02/28 (tag: 7.12.0)

These lists are automatically generated, and may be incomplete or contain duplicates.

We closed 1 issues and merged 24 pull requests. The full list can be seen [on GitHub](#)

The following 12 authors contributed 108 commits.

- Alex Hall
- Augusto
- Coon, Ethan T
- Daniel Hahler
- Inception95
- Itamar Turner-Trauring
- Jonas Haag
- Jonathan Slenders
- linar-jether
- Matthias Bussonnier
- Nathan Goldbaum
- Terry Davis

2.5.6 Issues closed in 7.12

GitHub stats for 2020/01/01 - 2020/01/31 (tag: 7.11.1)

These lists are automatically generated, and may be incomplete or contain duplicates.

We closed 2 issues and merged 14 pull requests. The full list can be seen [on GitHub](#)

The following 11 authors contributed 48 commits.

- Augusto
- Eric Wieser
- Jeff Potter
- Mark E. Haase
- Matthias Bussonnier
- ossdev07
- ras44
- takuya fujiwara
- Terry Davis
- Thomas A Caswell
- yangyang

2.5.7 Issues closed in 7.11

GitHub stats for 2019/12/01 - 2019/12/27 (tag: 7.10.1)

These lists are automatically generated, and may be incomplete or contain duplicates.

We closed 4 issues and merged 36 pull requests. The full list can be seen [on GitHub](#)

The following 16 authors contributed 114 commits.

- Augusto
- Benjamin Ragan-Kelley
- Chemss Eddine Ben Hassine
- Danny Hermes
- Dominik Miedziński
- Jonathan Feinberg
- Jonathan Slenders
- Joseph Kahn
- kousik
- Kousik Mitra
- Marc Hernandez Cabot
- Matthias Bussonnier
- Naveen Honest Raj K

- Pratyay Pandey
- Quentin Peter
- takuya fujiwara

2.5.8 Issues closed in 7.10.2

GitHub stats for 2019/12/01 - 2019/12/14 (tag: 7.10.1)

These lists are automatically generated, and may be incomplete or contain duplicates.

We closed 3 issues and merged 10 pull requests. The full list can be seen [on GitHub](#)

The following 3 authors contributed 11 commits.

- Jonathan Slenders
- Joseph Kahn
- Matthias Bussonnier

2.5.9 Issues closed in 7.10.1

GitHub stats for 2019/11/27 - 2019/12/01 (tag: 7.10.0)

These lists are automatically generated, and may be incomplete or contain duplicates.

We closed 5 issues and merged 7 pull requests. The full list can be seen [on GitHub](#)

The following 2 authors contributed 14 commits.

- Jonathan Slenders
- Matthias Bussonnier

2.5.10 Issues closed in 7.10

GitHub stats for 2019/10/25 - 2019/11/27 (tag: 7.9.0)

These lists are automatically generated, and may be incomplete or contain duplicates.

We closed 4 issues and merged 22 pull requests. The full list can be seen [on GitHub](#)

The following 15 authors contributed 101 commits.

- anatoly techtonik
- Ben Lewis
- Benjamin Ragan-Kelley
- Gerrit Buss
- grey275
- Gökçen Eraslan
- Jonathan Slenders
- Joris Van den Bossche
- kousik

- Matthias Bussonnier
- Nicholas Bollweg
- Paul McCarthy
- Srinivas Reddy Thatiparthi
- Timo Kaufmann
- Tony Fast

2.5.11 Issues closed in 7.9

GitHub stats for 2019/08/30 - 2019/10/25 (tag: 7.8.0)

These lists are automatically generated, and may be incomplete or contain duplicates.

We closed 1 issues and merged 9 pull requests. The full list can be seen [on GitHub](#)

The following 8 authors contributed 20 commits.

- Benjamin Ragan-Kelley
- Hugo
- Matthias Bussonnier
- mfh92
- Mohammad Hossein Sekhavat
- Niclas
- Vidar Tonaas Fauske
- Георгий Фролов

2.5.12 Issues closed in 7.8

GitHub stats for 2019/07/26 - 2019/08/30 (tag: 7.7.0)

These lists are automatically generated, and may be incomplete or contain duplicates.

We closed 1 issues and merged 4 pull requests. The full list can be seen [on GitHub](#)

The following 5 authors contributed 27 commits.

- Dan Allan
- Matthias Bussonnier
- Min ho Kim
- Oscar Gustafsson
- Terry Davis

2.5.13 Issues closed in 7.7

GitHub stats for 2019/07/03 - 2019/07/26 (tag: 7.6.1)

These lists are automatically generated, and may be incomplete or contain duplicates.

We closed 5 issues and merged 9 pull requests. The full list can be seen [on GitHub](#)

The following 8 authors contributed 26 commits.

- Brandon T. Willard
- juanis2112
- llf
- Matthias Bussonnier
- Min ho Kim
- Oriol (Prodesk)
- Po-Chuan Hsieh
- techassetskris

2.5.14 Issues closed in 7.6

GitHub stats for 2019/04/24 - 2019/06/28 (tag: 7.5.0)

These lists are automatically generated, and may be incomplete or contain duplicates.

We closed 9 issues and merged 43 pull requests. The full list can be seen [on GitHub](#)

The following 19 authors contributed 144 commits.

- Alok Singh
- Andreas
- Antony Lee
- Daniel Hahler
- Ed OBrien
- Kevin Sheppard
- Luciana da Costa Marques
- Maor Kleinberger
- Matthias Bussonnier
- Miro Hrončok
- Niclas
- Nikita Bezdolny
- Oriol Abril
- Piers Titus van der Torren
- Pragnya Srinivasan
- Robin Gustafsson

- stonebig
- Thomas A Caswell
- zzzz-qq

2.5.15 Issues closed in 7.5

GitHub stats for 2019/03/21 - 2019/04/24 (tag: 7.4.0)

These lists are automatically generated, and may be incomplete or contain duplicates.

We closed 2 issues and merged 9 pull requests. The full list can be seen [on GitHub](#)

The following 7 authors contributed 28 commits.

- Akshay Paropkari
- Benjamin Ragan-Kelley
- Ivan Tham
- Matthias Bussonnier
- Nick Tallant
- Sebastian Witowski
- stef-ubuntu

2.5.16 Issues closed in 7.4

GitHub stats for 2019/02/18 - 2019/03/21 (tag: 7.3.0)

These lists are automatically generated, and may be incomplete or contain duplicates.

We closed 9 issues and merged 20 pull requests. The full list can be seen [on GitHub](#)

The following 23 authors contributed 69 commits.

- anatoly techtonik
- Benjamin Ragan-Kelley
- bnables
- Frédéric Chapoton
- Gabriel Potter
- Ian Bell
- Jake VanderPlas
- Jan S. (Milania1)
- Jesse Widner
- jsnydes
- Kyungdahm Yun
- Laurent Gautier
- Luciana da Costa Marques
- Matan Gover

- Matthias Bussonnier
- memeplex
- Mickaël Schoentgen
- Partha P. Mukherjee
- Philipp A
- Sanyam Agarwal
- Steve Nicholson
- Tony Fast
- Wouter Overmeire

2.5.17 Issues closed in 7.3

GitHub stats for 2018/11/30 - 2019/02/18 (tag: 7.2.0)

These lists are automatically generated, and may be incomplete or contain duplicates.

We closed 4 issues and merged 20 pull requests. The full list can be seen [on GitHub](#)

The following 17 authors contributed 99 commits.

- anatoly techtonik
- Benjamin Ragan-Kelley
- Gabriel Potter
- Ian Bell
- Jake VanderPlas
- Jan S. (Milania1)
- Jesse Widner
- Kyungdahm Yun
- Laurent Gautier
- Matthias Bussonnier
- memeplex
- Mickaël Schoentgen
- Partha P. Mukherjee
- Philipp A
- Sanyam Agarwal
- Steve Nicholson
- Tony Fast

2.5.18 Issues closed in 7.2

GitHub stats for 2018/10/28 - 2018/11/29 (tag: 7.1.1)

These lists are automatically generated, and may be incomplete or contain duplicates.

We closed 2 issues and merged 18 pull requests. The full list can be seen [on GitHub](#)

The following 16 authors contributed 95 commits.

- Antony Lee
- Benjamin Ragan-Kelley
- CarsonGSmith
- Chris Mentzel
- Christopher Brown
- Dan Allan
- Elliott Morgan Jobson
- is-this-valid
- kd2718
- Kevin Hess
- Martin Bergtholdt
- Matthias Bussonnier
- Nicholas Bollweg
- Pavel Karateev
- Philipp A
- Reuben Morais

2.5.19 Issues closed in 7.1

GitHub stats for 2018/09/27 - 2018/10/27 (since tag: 7.0.1)

These lists are automatically generated, and may be incomplete or contain duplicates.

We closed 31 issues and merged 54 pull requests. The full list can be seen [on GitHub](#)

The following 33 authors contributed 254 commits.

- ammarmallik
- Audrey Dutcher
- Bart Skowron
- Benjamin Ragan-Kelley
- BinaryCrochet
- Chris Barker
- Christopher Moura
- Dedipyaman Das

- Dominic Kuang
- Elyashiv
- Emil Hessman
- felixzhuologist
- hongshaoyang
- Hugo
- kd2718
- kory donati
- Kory Donati
- koryd
- luciana
- luz.paz
- Massimo Santini
- Matthias Bussonnier
- Matthias Geier
- meeseeksdev[bot]
- Michael Penkov
- Mukesh Bhandarkar
- Nguyen Duy Hai
- Roy Wellington
- Sha Liu
- Shao Yang
- Shashank Kumar
- Tony Fast
- wim glenn

2.5.20 Issues closed in 7.0

GitHub stats for 2018/07/29 - 2018/09/27 (since tag: 6.5.0)

These lists are automatically generated, and may be incomplete or contain duplicates.

We closed 20 issues and merged 76 pull requests. The full list can be seen [on GitHub](#)

The following 49 authors contributed 471 commits.

- alphaCTzo7G
- Alyssa Whitwell
- Anatol Ulrich
- apunisal
- Benjamin Ragan-Kelley

- Chaz Reid
- Christoph
- Dale Jung
- Dave Hirschfeld
- dhirschf
- Doug Latornell
- Fernando Perez
- Fred Mitchell
- Gabriel Potter
- gpotter2
- Grant Nestor
- hongshaoyang
- Hugo
- J Forde
- Jonathan Slenders
- Jörg Dietrich
- Kyle Kelley
- luz.paz
- M Pacer
- Matthew R. Scott
- Matthew Seal
- Matthias Bussonnier
- meeseeksdev[bot]
- Michael Käufl
- Olesya Baranova
- oscar6echo
- Paul Ganssle
- Paul Ivanov
- Peter Parente
- prasanth
- Shailyn javier Ortiz jimenez
- Sourav Singh
- Srinivas Reddy Thatiparthi
- Steven Silvester
- stonebig
- Subhendu Ranjan Mishra

- Takafumi Arakaki
- Thomas A Caswell
- Thomas Kluyver
- Todd
- Wei Yen
- Yarko Tymciurak
- Yutao Yuan
- Zi Chong Kao

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

2.6 6.x Series

2.6.1 IPython 6.5.0

Miscellaneous bug fixes and compatibility with Python 3.7.

- Autocompletion fix for modules with out `__init__.py` [PR #11227](#)
- update the `%pastebin` magic to use `dpaste.com` instead of GitHub Gist which now requires authentication [PR #11182](#)
- Fix crash with multiprocessing [PR #11185](#)

2.6.2 IPython 6.4.0

Everything new in *IPython 5.7*

- Fix display object not emitting metadata [PR #11106](#)
- Comments failing Jedi test [PR #11110](#)

2.6.3 IPython 6.3.1

This is a bugfix release to switch the default completions back to IPython's own completion machinery. We discovered some problems with the completions from Jedi, including completing column names on pandas data frames.

You can switch the completions source with the config option `Completer.use_jedi`.

2.6.4 IPython 6.3

IPython 6.3 contains all the bug fixes and features in *IPython 5.6*. In addition:

- A new display class `IPython.display.Code` can be used to display syntax highlighted code in a notebook (PR #10978).
- The `%%html` magic now takes a `--isolated` option to put the content in an iframe (PR #10962).
- The code to find completions using the Jedi library has had various adjustments. This is still a work in progress, but we hope this version has fewer annoyances (PR #10956, PR #10969, PR #10999, PR #11035, PR #11063, PR #11065).
- The `post` event callbacks are now always called, even when the execution failed (for example because of a `SyntaxError`).
- The execution info and result objects are now made available in the corresponding `pre` or `post *_run_cell event callbacks` in a backward compatible manner (#10774 and PR #10795).
- Performance with very long code cells (hundreds of lines) is greatly improved (PR #10898). Further improvements are planned for IPython 7.

You can see all pull requests for the 6.3 milestone.

2.6.5 IPython 6.2

IPython 6.2 contains all the bugs fixes and features *available in IPython 5.5*, like built in progress bar support, and system-wide configuration

The following features are specific to IPython 6.2:

Function signature in completions

Terminal IPython will now show the signature of the function while completing. Only the currently highlighted function will show its signature on the line below the completer by default. This functionality is recent, so it might be limited; we welcome bug reports and requests for enhancements. PR #10507

Assignments return values

IPython can now trigger the display hook on the last assignment of cells. Up until 6.2 the following code wouldn't show the value of the assigned variable:

```
In[1]: xyz = "something"
# nothing shown
```

You would have to actually make it the last statement:

```
In [2]: xyz = "something else"
...     : xyz
Out[2]: "something else"
```

With the option `InteractiveShell.ast_node_interactivity='last_expr_or_assign'` you can now do:

```
In [2]: xyz = "something else"
Out[2]: "something else"
```

This option can be toggled at runtime with the `%config` magic, and will trigger on assignment `a = 1`, augmented assignment `+=`, `-=`, `|=` ... as well as type annotated assignments: `a:int = 2`.

See [PR #10598](#)

Recursive Call of `ipdb`

Advanced users of the debugger can now correctly recursively enter `ipdb`. This is thanks to [@segevfiner](#) on [PR #10721](#).

2.6.6 IPython 6.1

- Quotes in a filename are always escaped during tab-completion on non-Windows. [PR #10069](#)
- Variables now shadow magics in autocompletion. See [#4877](#) and [PR #10542](#).
- Added the ability to add parameters to `alias_magic`. For example:

```
In [2]: %alias_magic hist history --params "-l 2" --line
Created `hist` as an alias for `history -l 2`.

In [3]: hist
%alias_magic hist history --params "-l 30" --line
%alias_magic hist history --params "-l 2" --line
```

Previously it was only possible to have an alias attached to a single function, and you would have to pass in the given parameters every time:

```
In [4]: %alias_magic hist history --line
Created `hist` as an alias for `history`.

In [5]: hist -l 2
hist
%alias_magic hist history --line
```

- To suppress log state messages, you can now either use `%logstart -q`, pass `--LoggingMagics.quiet=True` on the command line, or set `c.LoggingMagics.quiet=True` in your configuration file.
- An additional flag `--TerminalInteractiveShell.term_title_format` is introduced to allow the user to control the format of the terminal title. It is specified as a python format string, and currently the only variable it will format is `{cwd}`.
- `??/%pinfo2` will now show object docstrings if the source can't be retrieved. [PR #10532](#)
- `IPython.display` has gained a `%markdown` cell magic. [PR #10563](#)
- `%config` options can now be tab completed. [PR #10555](#)

- `%config` with no arguments are now unique and sorted. [PR #10548](#)
- Completion on keyword arguments does not duplicate = sign if already present. [PR #10547](#)
- `%run -m <module>` now `<module>` passes extra arguments to `<module>`. [PR #10546](#)
- completer now understand «snake case auto complete»: if `foo_bar_kittens` is a valid completion, I can type `f_b<tab>` will complete to it. [PR #10537](#)
- tracebacks are better standardized and will compress `/path/to/home` to `~`. [PR #10515](#)

The following changes were also added to IPython 5.4, see [what's new in IPython 5.4](#) for more detail description:

- `TerminalInteractiveShell` is configurable and can be configured to (re)-use the readline interface.
- objects can now define a `_repr_mimebundle_`
- Execution heuristics improve for single line statements
- `display()` can now return a display id to update display areas.

2.6.7 IPython 6.0

Released April 19th, 2017

IPython 6 features a major improvement in the completion machinery which is now capable of completing non-executed code. It is also the first version of IPython to stop compatibility with Python 2, which is still supported on the bugfix only 5.x branch. Read below for a non-exhaustive list of new features.

Make sure you have `pip > 9.0` before upgrading. You should be able to update by using:

```
pip install ipython --upgrade
```

Примечание: If your pip version is greater than or equal to pip 9.0.1 you will automatically get the most recent version of IPython compatible with your system: on Python 2 you will get the latest IPython 5.x bugfix, while in Python 3 you will get the latest 6.x stable version.

New completion API and Interface

The completer Completion API has seen an overhaul, and the new completer has plenty of improvements both from the end users of terminal IPython and for consumers of the API.

This new API is capable of pulling completions from `jedi`, thus allowing type inference on non-executed code. If `jedi` is installed, completions like the following are now possible without code evaluation:

```
>>> data = ['Number of users', 123_456]
... data[0].<tab>
```

That is to say, IPython is now capable of inferring that `data[0]` is a string, and will suggest completions like `.capitalize`. The completion power of IPython will increase with new Jedi releases, and a number of bug-fixes and more completions are already available on the development version of `jedi` if you are curious.

With the help of prompt toolkit, types of completions can be shown in the completer interface:

```
In [1]: n = 123_456
...: data = [f'Number of users: {n}', n]
...: data[0].
...:
...: capitalize      function
...: casfold          function
...: center            function
...: count             function
...: encode            function
...: endswith          function
...: expandtabs        function
...: find              function
...: format            function
```

The appearance of the completer is controlled by the `c.TerminalInteractiveShell.display_completions` option that will show the type differently depending on the value among 'column', 'multicolumn' and 'readlinelike'

The use of Jedi also fulfills a number of requests and fixes a number of bugs like case-insensitive completion and completion after division operator: See [PR #10182](#).

Extra patches and updates will be needed to the `ipykernel` package for this feature to be available to other clients like Jupyter Notebook, Lab, Nteract, Hydrogen...

The use of Jedi should be barely noticeable on recent machines, but can be slower on older ones. To tweak the performance, the amount of time given to Jedi to compute type inference can be adjusted with `c.IPCompleter.jedi_compute_type_timeout`. The objects whose type were not inferred will be shown as `<unknown>`. Jedi can also be completely deactivated by using the `c.Completer.use_jedi=False` option.

The old `Completer.complete()` API is waiting deprecation and should be replaced by `Completer.completions()` in the near future. Feedback on the current state of the API and suggestions are welcome.

Python 3 only codebase

One of the large challenges in IPython 6.0 has been the adoption of a pure Python 3 codebase, which has led to upstream patches in pip, pypi and warehouse to make sure Python 2 systems still upgrade to the latest compatible Python version.

We remind our Python 2 users that IPython 5 is still compatible with Python 2.7, still maintained and will get regular releases. Using pip 9+, upgrading IPython will automatically upgrade to the latest version compatible with your system.

Предупреждение: If you are on a system using an older version of pip on Python 2, pip may still install IPython 6.0 on your system, and IPython will refuse to start. You can fix this by upgrading pip, and reinstalling ipython, or forcing pip to install an earlier version: `pip install 'ipython<6'`

The ability to use only Python 3 on the code base of IPython brings a number of advantages. Most of the newly written code make use of `optional function type annotation` leading to clearer code and better documentation.

The total size of the repository has also decreased by about 1500 lines (for the first time excluding the big split for 4.0). The decrease is potentially a bit more for the sour as some documents like this one are append only and are about 300 lines long.

The removal of the Python2/Python3 shim layer has made the code quite a lot clearer and more idiomatic in a number of locations, and much friendlier to work with and understand. We hope to further embrace Python 3 capabilities in the next release cycle and introduce more of the Python 3 only idioms (yield from, kwarg only, general unpacking) in the IPython code base, and see if we can take advantage of these to improve user experience with better error messages and hints.

Configurable `TerminalInteractiveShell`, readline interface

IPython gained a new `c.TerminalIPythonApp.interactive_shell_class` option that allows customizing the class used to start the terminal frontend. This should allow a user to use custom interfaces, like reviving the former readline interface which is now a separate package not actively maintained by the core team. See the project to bring back the readline interface: [rlipython](#).

This change will be backported to the IPython 5.x series.

Misc improvements

- The `%%capture` magic can now capture the result of a cell (from an expression on the last line), as well as printed and displayed output. [PR #9851](#).
- Pressing Ctrl-Z in the terminal debugger now suspends IPython, as it already does in the main terminal prompt.
- Autoreload can now reload `Enum`. See [#10232](#) and [PR #10316](#)
- `IPython.display` has gained a `GeoJSON` object. [PR #10288](#) and [PR #10253](#)

Functions Deprecated in 6.x Development cycle

- Loading extensions from `ipython_extension_dir` prints a warning that this location is pending deprecation. This should only affect users still having extensions installed with `%install_ext` which has been deprecated since IPython 4.0, and removed in 5.0. Extensions still present in `ipython_extension_dir` may shadow more recently installed versions using pip. It is thus recommended to clean `ipython_extension_dir` of any extension now available as a package.
- `IPython.utils.warn` was deprecated in IPython 4.0, and has now been removed. instead of `IPython.utils.warn` inbuilt `warnings` module is used.
- The function `IPython.core.oinspect.py:call_tip` is unused, was marked as deprecated (raising a `DeprecationWarning`) and marked for later removal. [PR #10104](#)

Backward incompatible changes

Functions Removed in 6.x Development cycle

The following functions have been removed in the development cycle marked for Milestone 6.0.

- `IPython/utils/process.py - is_cmd_found`
- `IPython/utils/process.py - pycmd2argv`
- The `--deep-reload` flag and the corresponding options to inject `dreload` or `reload` into the interactive namespace have been removed. You have to explicitly import `reload` from `IPython.lib.deepreload` to use it.

- The `%profile` used to print the current IPython profile, and which was deprecated in IPython 2.0 does now raise a `DeprecationWarning` error when used. It is often confused with the `%prun` and the deprecation removal should free up the `profile` name in future versions.

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

2.7 Issues closed in the 6.x development cycle

2.7.1 Issues closed in 6.3

GitHub stats for 2017/09/15 - 2018/04/02 (tag: 6.2.0)

These lists are automatically generated, and may be incomplete or contain duplicates.

We closed 10 issues and merged 50 pull requests. The full list can be seen [on GitHub](#)

The following 35 authors contributed 253 commits.

- Anatoly Techtonik
- Antony Lee
- Benjamin Ragan-Kelley
- Corey McCandless
- Craig Citro
- Cristian Ciupitu
- David Cottrell
- David Straub
- Doug Latornell
- Fabio Niephaus
- Gergely Nagy
- Henry Fredrick Schreiner
- Hugo
- Ismael Venegas Castelló
- Ivan Gonzalez
- J Forde
- Jeremy Sikes
- Joris Van den Bossche

- Lesley Cordero
- luzpaz
- madhu94
- Matthew R. Scott
- Matthias Bussonnier
- Matthias Geier
- Olesya Baranova
- Peter Williams
- Rastislav Barlik
- Roshan Rao
- rs2
- Samuel Lelièvre
- Shailyn javier Ortiz jimenez
- Sjoerd de Vries
- Teddy Rendahl
- Thomas A Caswell
- Thomas Kluyver

2.7.2 Issues closed in 6.2

GitHub stats for 2017/05/31 - 2017/09/15 (tag: 6.1.0)

These lists are automatically generated, and may be incomplete or contain duplicates.

We closed 3 issues and merged 37 pull requests. The full list can be seen [on GitHub](#)

The following 32 authors contributed 196 commits.

- adityausathe
- Antony Lee
- Benjamin Ragan-Kelley
- Carl Smith
- Eren Halici
- Erich Spaker
- Grant Nestor
- Jean Cruypenynck
- Jeroen Demeyer
- jfbu
- jlstevens
- jus1tin
- Kyle Kelley

- M Pacer
- Marc Richter
- Marius van Niekerk
- Matthias Bussonnier
- mpacer
- Mradul Dubey
- ormung
- pepie34
- Ritesh Kadmawala
- ryan thielke
- Segev Finer
- Srinath
- Srinivas Reddy Thatiparthi
- Steven Maude
- Sudarshan Raghunathan
- Sudarshan Rangarajan
- Thomas A Caswell
- Thomas Ballinger
- Thomas Kluyver

2.7.3 Issues closed in 6.1

GitHub stats for 2017/04/19 - 2017/05/30 (tag: 6.0.0)

These lists are automatically generated, and may be incomplete or contain duplicates.

We closed 10 issues and merged 43 pull requests. The full list can be seen [on GitHub](#)

The following 26 authors contributed 116 commits.

- Alex Alekseyev
- Benjamin Ragan-Kelley
- Brian E. Granger
- Christopher C. Aycock
- Dave Willmer
- David Bradway
- ICanWaitAndFishAllDay
- Ignat Shining
- Jarrod Janssen
- Joshua Storck
- Luke Pfister

- Matthias Bussonnier
- Matti Remes
- meeseeksdev[bot]
- memeplex
- Ming Zhang
- Nick Weseman
- Paul Ivanov
- Piotr Zielinski
- ryan thielke
- sagnak
- Sang Min Park
- Srinivas Reddy Thatiparthi
- Steve Bartz
- Thomas Kluyver
- Tory Haavik

2.7.4 Issues closed in 6.0

GitHub stats for 2017/04/10 - 2017/04/19 (milestone: 6.0)

These lists are automatically generated, and may be incomplete or contain duplicates.

We closed 49 issues and merged 145 pull requests. The full list can be seen [on GitHub](#)

The following 34 authors contributed 176 commits.

- Adam Eury
- anantkaushik89
- Antonino Ingargiola
- Benjamin Ragan-Kelley
- Carol Willing
- Chilaka Ramakrishna
- chillaranand
- Denis S. Tereshchenko
- Diego Garcia
- fatData
- Fermi paradox
- fuho
- Grant Nestor
- Ian Rose
- Jeroen Demeyer

- kaushikanant
- Keshav Ramaswamy
- Matteo
- Matthias Bussonnier
- mbyt
- Michael Käußl
- michaelpacer
- Moez Bouhlel
- Pablo Galindo
- Paul Ivanov
- Piotr Przetacznik
- Rounak Banik
- sachet-mittal
- Srinivas Reddy Thatiparthi
- Tamir Bahar
- Thomas Hisch
- Thomas Kluyver
- Utkarsh Upadhyay
- Yuri Numerov

<p>Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.</p>
--

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

2.8 5.x Series

2.8.1 IPython 5.8.0

- Update inspecting function/methods for future-proofing. [PR #11139](#)

2.8.2 IPython 5.7

- Fix IPython trying to import non-existing matplotlib backends [PR #11087](#)
- fix for display hook not publishing object metadata [PR #11101](#)

2.8.3 IPython 5.6

- In Python 3.6 and above, dictionaries preserve the order items were added to them. On these versions, IPython will display dictionaries in their native order, rather than sorting by the keys ([PR #10958](#)).
- `ProgressBar` can now be used as an iterator ([PR #10813](#)).
- The shell object gains a `check_complete()` method, to allow a smoother transition to new input processing machinery planned for IPython 7 ([PR #11044](#)).
- IPython should start faster, as it no longer looks for all available pygments styles on startup ([PR #10859](#)).

You can see all the PR marked for the [5.6. milestone](#), and all the [backport versions](#).

2.8.4 IPython 5.5

System Wide config

- IPython now looks for config files in `{sys.prefix}/etc/ipython` for environment-specific configuration.
- Startup files can be found in `/etc/ipython/startup` or `{sys.prefix}/etc/ipython/startup` in addition to the profile directory, for system-wide or env-specific startup files.

See [PR #10644](#)

ProgressBar

IPython now has built-in support for progressbars:

```
In[1]: from IPython.display import ProgressBar
...   : pb = ProgressBar(100)
...   : pb

In[2]: pb.progress = 50

# progress bar in cell 1 updates.
```

See [PR #10755](#)

Misc

- Fix `IPython.core.display.Pretty._repr_pretty_` had the wrong signature. (PR #10625)
- `%timeit` now give a correct `SyntaxError` if naked `return` used. (PR #10637)
- Prepare the `:ipython:` directive to be compatible with Sphinx 1.7. (PR #10668)
- Make IPython work with OpenSSL in FIPS mode; change hash algorithm of input from md5 to sha1. (PR #10696)
- Clear breakpoints before running any script with debugger. (PR #10699)
- Document that `%profile` is deprecated, not to be confused with `%prun`. (PR #10707)
- Limit default number of returned completions to 500. (PR #10743)

You can see all the PR marked for the 5.5. milestone, and all the backport versions.

2.8.5 IPython 5.4.1

Released a few hours after 5.4, fix a crash when `backports.shutil-get-terminal-size` is not installed. #10629

2.8.6 IPython 5.4

IPython 5.4-LTS is the first release of IPython after the release of the 6.x series which is Python 3 only. It backports most of the new exposed API additions made in IPython 6.0 and 6.1 and avoid having to write conditional logics depending of the version of IPython.

Please upgrade to pip 9 or greater before upgrading IPython. Failing to do so on Python 2 may lead to a broken IPython install.

Configurable TerminalInteractiveShell

Backported from the 6.x branch as an exceptional new feature. See PR #10373 and #10364

IPython gained a new `c.TerminalIPythonApp.interactive_shell_class` option that allow to customize the class used to start the terminal frontend. This should allow user to use custom interfaces, like reviving the former readline interface which is now a separate package not maintained by the core team.

Define _repr_mimebundle_

Object can now define `_repr_mimebundle_` in place of multiple `_repr*_` methods and return a full mimebundle. This greatly simplify many implementation and allow to publish custom mimetypes (like geojson, plotly, dataframes...). See the Custom Display Logic example notebook for more informations.

Execution Heuristics

The heuristic for execution in the command line interface is now more biased toward executing for single statement. While in IPython 4.x and before a single line would be executed when enter is pressed, IPython 5.x would insert a new line. For single line statement this is not true anymore and if a single line is valid Python, IPython will execute it regardless of the cursor position. Use `Ctrl-O` to insert a new line. [PR #10489](#)

Implement Display IDs

Implement display id and ability to update a given display. This should greatly simplify a lot of code by removing the need for widgets and allow other frontend to implement things like progress-bars. See [PR #10048](#)

Display function

The `display()` function is now available by default in an IPython session, meaning users can call it on any object to see their rich representation. This should allow for better interactivity both at the REPL and in notebook environment.

Scripts and library that rely on display and may be run outside of IPython still need to import the display function using `from IPython.display import display`. See [PR #10596](#)

Miscs

- `_mp_main_` is not reloaded which fixes issues with multiprocessing. [PR #10523](#)
- Use user colorscheme in Pdb as well [PR #10479](#)
- Faster shutdown. [PR #10408](#)
- Fix a crash in reverse search. [PR #10371](#)
- added `Completer.backslash_combining_completions` boolean option to deactivate backslash-tab completion that may conflict with windows path.

2.8.7 IPython 5.3

Released on February 24th, 2017. Remarkable changes and fixes:

- Fix a bug in `set_next_input` leading to a crash of terminal IPython. [PR #10231](#), [PR #10296](#), [PR #10229](#)
- Always wait for editor inputhook for terminal IPython [PR #10239](#), [PR #10240](#)
- Disable `_ipython_display_` in terminal [PR #10249](#), [PR #10274](#)
- Update terminal colors to be more visible by default on windows [PR #10260](#), [PR #10238](#), [PR #10281](#)
- Add Ctrl-Z shortcut (suspend) in terminal debugger [PR #10254](#), [PR #10273](#)
- Indent on new line by looking at the text before the cursor [PR #10264](#), [PR #10275](#), [PR #9283](#)
- Update QtEventloop integration to fix some matplotlib integration issues [PR #10201](#), [PR #10311](#), [PR #10201](#)
- Respect completions display style in terminal debugger [PR #10305](#), [PR #10313](#)

- Add a config option `TerminalInteractiveShell.extra_open_editor_shortcuts` to enable extra shortcuts to open the input in an editor. These are `v` in `vi` mode, and `C-X C-E` in `emacs` mode (PR #10330). The `F2` shortcut is always enabled.

2.8.8 IPython 5.2.2

- Fix error when starting with `IPCompleter.limit_to__all__` configured.

2.8.9 IPython 5.2.1

- Fix tab completion in the debugger. PR #10223

2.8.10 IPython 5.2

Released on January 29th, 2017. Remarkable changes and fixes:

- restore IPython's debugger to raise on quit. PR #10009
- The configuration value `c.TerminalInteractiveShell.highlighting_style` can now directly take a class argument for custom color style. PR #9848
- Correctly handle matplotlib figures dpi PR #9868
- Deprecate `-e` flag for the `%notebook` magic that had no effects. PR #9872
- You can now press `F2` while typing at a terminal prompt to edit the contents in your favourite terminal editor. Set the `EDITOR` environment variable to pick which editor is used. PR #9929
- `sdist`s will now only be `.tar.gz` as per upstream PyPI requirements. PR #9925
- `IPython.core.debugger` have gained a `set_trace()` method for convenience. PR #9947
- The „smart command mode“ added to the debugger in 5.0 was removed, as more people preferred the previous behaviour. Therefore, debugger commands such as `c` will act as debugger commands even when `c` is defined as a variable. PR #10050
- Fixes OS X event loop issues at startup, PR #10150
- Deprecate the `%autoindent` magic. PR #10176
- Emit a `DeprecationWarning` when setting the deprecated `limit_to_all` option of the completer. PR #10198
- The `%%capture` magic can now capture the result of a cell (from an expression on the last line), as well as printed and displayed output. PR #9851.

Changes of behavior to `InteractiveShellEmbed`.

`InteractiveShellEmbed` interactive behavior have changed a bit in between 5.1 and 5.2. By default `%kill_embedded` magic will prevent further invocation of the current `call location` instead of preventing further invocation of the current instance creation location. For most use case this will not change much for you, though previous behavior was confusing and less consistent with previous IPython versions.

You can now deactivate instances by using `%kill_embedded --instance` flag, (or `-i` in short). The `%kill_embedded` magic also gained a `--yes/-y` option which skip confirmation step, and `-x/--exit` which also exit the current embedded call without asking for confirmation.

See PR #10207.

2.8.11 IPython 5.1

- Broken `%timeit` on Python2 due to the use of `__qualname__`. PR #9804
- Restore `%gui qt` to create and return a `QApplication` if necessary. PR #9789
- Don't set terminal title by default. PR #9801
- Preserve indentation when inserting newlines with `Ctrl-O`. PR #9770
- Restore completion in debugger. PR #9785
- Deprecate `IPython.core.debugger.Tracer()` in favor of simpler, newer, APIs. PR #9731
- Restore `NoOpContext` context manager removed by mistake, and add `DeprecationWarning`. PR #9765
- Add option allowing `Prompt_toolkit` to use 24bits colors. PR #9736
- Fix for closing interactive matplotlib windows on OS X. PR #9854
- An embedded interactive shell instance can be used more than once. PR #9843
- More robust check for whether IPython is in a terminal. PR #9833
- Better pretty-printing of dicts on PyPy. PR #9827
- Some coloured output now looks better on dark background command prompts in Windows. PR #9838
- Improved tab completion of paths on Windows . PR #9826
- Fix tkinter event loop integration on Python 2 with `future` installed. PR #9824
- Restore `Ctrl-\` as a shortcut to quit IPython.
- Make `get_ipython()` accessible when modules are imported by startup files. PR #9818
- Add support for running directories containing a `__main__.py` file with the `ipython` command. PR #9813

True Color feature

`prompt_toolkit` uses `pygments` styles for syntax highlighting. By default, the colors specified in the style are approximated using a standard 256-color palette. `prompt_toolkit` also supports 24bit, a.k.a. «true», a.k.a. 16-million color escape sequences which enable compatible terminals to display the exact colors specified instead of an approximation. This `true_color` option exposes that capability in `prompt_toolkit` to the IPython shell.


Here is a good source for the current state of true color support in various terminal emulators and software projects: <https://gist.github.com/XVilka/8346728>

2.8.12 IPython 5.0

Released July 7, 2016

New terminal interface

IPython 5 features a major upgrade to the terminal interface, bringing live syntax highlighting as you type, proper multiline editing and multiline paste, and tab completions that don't clutter up your history.

A screenshot of a terminal window with a dark background. It shows two IPython prompts. The first prompt, 'In [1]:', is followed by a for loop: 'for a in range(1, 5):', '...', 'print(a, "squared:", a**2)', and '...'. The output shows four lines: '1 squared: 1', '2 squared: 4', '3 squared: 9', and '4 squared: 16'. The second prompt, 'In [2]:', is followed by 'import numpy'. A tab completion menu is visible, showing 'numbers' and 'numpy' as options.

These features are provided by the Python library `prompt_toolkit`, which replaces `readline` throughout our terminal interface.

Relying on this pure-Python, cross platform module also makes it simpler to install IPython. We have removed dependencies on `pyreadline` for Windows and `gnureadline` for Mac.

Backwards incompatible changes

- The `%install_ext` magic function, deprecated since 4.0, has now been deleted. You can distribute and install extensions as packages on PyPI.
- Callbacks registered while an event is being handled will now only be called for subsequent events; previously they could be called for the current event. Similarly, callbacks removed while handling an event *will* always get that event. See [#9447](#) and [PR #9453](#).
- Integration with `pydb` has been removed since `pydb` development has been stopped since 2012, and `pydb` is not installable from PyPI.
- The `autoedit_syntax` option has apparently been broken for many years. It has been removed.

New terminal interface

The overhaul of the terminal interface will probably cause a range of minor issues for existing users. This is inevitable for such a significant change, and we've done our best to minimise these issues. Some changes that we're aware of, with suggestions on how to handle them:

IPython no longer uses `readline` configuration (`~/.inputrc`). We hope that the functionality you want (e.g. vi input mode) will be available by configuring IPython directly (see [Terminal IPython options](#)). If something's missing, please file an issue.

The `PromptManager` class has been removed, and the prompt machinery simplified. See [Custom Prompts](#) to customise prompts with the new machinery.

`IPython.core.debugger` now provides a plainer interface. `IPython.terminal.debugger` contains the terminal debugger using `prompt_toolkit`.

There are new options to configure the colours used in syntax highlighting. We have tried to integrate them with our classic `--colors` option and `%colors` magic, but there's a mismatch in possibilities, so some configurations may produce unexpected results. See *Terminal Colors* for more information.

The new interface is not compatible with Emacs „inferior-shell“ feature. To continue using this, add the `--simple-prompt` flag to the command Emacs runs. This flag disables most IPython features, relying on Emacs to provide things like tab completion.

Provisional Changes

Provisional changes are experimental functionality that may, or may not, make it into a future version of IPython, and which API may change without warnings. Activating these features and using these API are at your own risk, and may have security implication for your system, especially if used with the Jupyter notebook,

When running via the Jupyter notebook interfaces, or other compatible client, you can enable rich documentation experimental functionality:

When the `docrepr` package is installed setting the boolean flag `InteractiveShell.sphinxify_docstring` to `True`, will process the various object through sphinx before displaying them (see the `docrepr` package documentation for more information).

You need to also enable the IPython pager display rich HTML representation using the `InteractiveShell.enable_html_pager` boolean configuration option. As usual you can set these configuration options globally in your configuration files, alternatively you can turn them on dynamically using the following snippet:

```
ip = get_ipython()
ip.sphinxify_docstring = True
ip.enable_html_pager = True
```

You can test the effect of various combinations of the above configuration in the Jupyter notebook, with things example like :

```
import numpy as np
np.histogram?
```

This is part of an effort to make Documentation in Python richer and provide in the long term if possible dynamic examples that can contain math, images, widgets... As stated above this is nightly experimental feature with a lot of (fun) problem to solve. We would be happy to get your feedback and expertise on it.

Deprecated Features

Some deprecated features are listed in this section. Don't forget to enable `DeprecationWarning` as an error if you are using IPython in a Continuous Integration setup or in your testing in general:

```
import warnings
warnings.filterwarnings('error', '.*', DeprecationWarning, module='yourmodule.*')
```

- `hooks.fix_error_editor` seems unused and is pending deprecation.
- `IPython/core/excolors.py:ExceptionColors` is deprecated.
- `IPython.core.InteractiveShell.write()` is deprecated; use `sys.stdout` instead.
- `IPython.core.InteractiveShell.write_err()` is deprecated; use `sys.stderr` instead.
- The `formatter` keyword argument to `Inspector.info` in `IPython.core.oinspec` has no effect.

- The `global_ns` keyword argument of IPython Embed was deprecated, and has no effect. Use `module` keyword argument instead.

Known Issues:

- <Esc> Key does not dismiss the completer and does not clear the current buffer. This is an on purpose modification due to current technical limitation. Cf [PR #9572](#). Escape the control character which is used for other shortcut, and there is no practical way to distinguish. Use Ctrl-G or Ctrl-C as an alternative.
- Cannot use Shift-Enter and Ctrl-Enter to submit code in terminal. cf [#9587](#) and [#9401](#). In terminal there is no practical way to distinguish these key sequences from a normal new line return.
- PageUp and pageDown do not move through completion menu.
- Color styles might not adapt to terminal emulator themes. This will need new version of Pygments to be released, and can be mitigated with custom themes.

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

2.9 Issues closed in the 5.x development cycle

2.9.1 Issues closed in 5.6

GitHub stats for 2017/09/15 - 2018/04/02 (tag: 5.5.0)

These lists are automatically generated, and may be incomplete or contain duplicates.

We closed 2 issues and merged 28 pull requests. The full list can be seen [on GitHub](#)

The following 10 authors contributed 47 commits.

- Benjamin Ragan-Kelley
- Henry Fredrick Schreiner
- Joris Van den Bossche
- Matthias Bussonnier
- Mradul Dubey
- Roshan Rao
- Samuel Lelièvre
- Teddy Rendahl
- Thomas A Caswell

- Thomas Kluyver

2.9.2 Issues closed in 5.4

GitHub stats for 2017/02/24 - 2017/05/30 (tag: 5.3.0)

These lists are automatically generated, and may be incomplete or contain duplicates.

We closed 8 issues and merged 43 pull requests. The full list can be seen [on GitHub](#)

The following 11 authors contributed 64 commits.

- Benjamin Ragan-Kelley
- Carol Willing
- Kyle Kelley
- Leo Singer
- Luke Pfister
- Lumir Balhar
- Matthias Bussonnier
- meeseeksdev[bot]
- memeplex
- Thomas Kluyver
- Ximin Luo

2.9.3 Issues closed in 5.3

GitHub stats for 2017/02/24 - 2017/05/30 (tag: 5.3.0)

These lists are automatically generated, and may be incomplete or contain duplicates.

We closed 6 issues and merged 28 pull requests. The full list can be seen [on GitHub](#)

The following 11 authors contributed 53 commits.

- Benjamin Ragan-Kelley
- Carol Willing
- Justin Jent
- Kyle Kelley
- Lumir Balhar
- Matthias Bussonnier
- meeseeksdev[bot]
- Segev Finer
- Steven Maude
- Thomas A Caswell
- Thomas Kluyver

2.9.4 Issues closed in 5.2

GitHub stats for 2016/08/13 - 2017/01/29 (tag: 5.1.0)

These lists are automatically generated, and may be incomplete or contain duplicates.

We closed 30 issues and merged 74 pull requests. The full list can be seen [on GitHub](#)

The following 40 authors contributed 434 commits.

- Adam Eury
- anantkaushik89
- anatoly techtonik
- Benjamin Ragan-Kelley
- Bibo Hao
- Carl Smith
- Carol Willing
- Chilaka Ramakrishna
- Christopher Welborn
- Denis S. Tereshchenko
- Diego Garcia
- fatData
- Fermi paradox
- Fernando Perez
- fuho
- Hassan Kibirige
- Jamshed Vesuna
- Jens Hedegaard Nielsen
- Jeroen Demeyer
- kaushikanant
- Kenneth Hoste
- Keshav Ramaswamy
- Kyle Kelley
- Matteo
- Matthias Bussonnier
- mbyt
- memplex
- Moez Bouhlel
- Pablo Galindo
- Paul Ivanov
- pietvo

- Piotr Przetacznik
- Rounak Banik
- sachet-mittal
- Srinivas Reddy Thatiparthi
- Tamir Bahar
- Thomas A Caswell
- Thomas Kluyver
- tillahoffmann
- Yuri Numerov

2.9.5 Issues closed in 5.1

GitHub stats for 2016/07/08 - 2016/08/13 (tag: 5.0.0)

These lists are automatically generated, and may be incomplete or contain duplicates.

We closed 33 issues and merged 43 pull requests. The full list can be seen [on GitHub](#)

The following 17 authors contributed 129 commits.

- Antony Lee
- Benjamin Ragan-Kelley
- Carol Willing
- Danilo J. S. Bellini
- ([dongweiming](#))
- Fernando Perez
- Gavin Cooper
- Gil Forsyth
- Jacob Niehus
- Julian Kuhlmann
- Matthias Bussonnier
- Michael Pacer
- Nik Nyby
- Pavol Juhas
- Luke Deen Taylor
- Thomas Kluyver
- Tamir Bahar

2.9.6 Issues closed in 5.0

GitHub stats for 2016/07/05 - 2016/07/07 (tag: 5.0.0)

These lists are automatically generated, and may be incomplete or contain duplicates.

We closed 95 issues and merged 191 pull requests. The full list can be seen [on GitHub](#)

The following 27 authors contributed 229 commits.

- Adam Greenhall
- Adrian
- Antony Lee
- Benjamin Ragan-Kelley
- Carlos Cordoba
- Carol Willing
- Chris
- Craig Citro
- Dmitry Zotikov
- Fernando Perez
- Gil Forsyth
- Jason Grout
- Jonathan Frederic
- Jonathan Slenders
- Justin Zymbaluk
- Kelly Liu
- klonuo
- Matthias Bussonnier
- nvdv
- Pavol Juhas
- Pierre Gerold
- sukisuki
- Sylvain Corlay
- Thomas A Caswell
- Thomas Kluyver
- Trevor Bekolay
- Yuri Numerov

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

2.10 4.x Series

2.10.1 IPython 4.2

IPython 4.2 (April, 2016) includes various bugfixes and improvements over 4.1.

- Fix `ipython -i` on errors, which was broken in 4.1.
- The delay meant to highlight deprecated commands that have moved to `jupyter` has been removed.
- Improve compatibility with future versions of `traitlets` and `matplotlib`.
- Use stdlib `shutil.get_terminal_size()` to measure terminal width when displaying tracebacks (provided by `backports.shutil_get_terminal_size` on Python 2).

You can see the rest [on GitHub](#).

2.10.2 IPython 4.1

IPython 4.1.2 (March, 2016) fixes installation issues with some versions of `setuptools`.

Released February, 2016. IPython 4.1 contains mostly bug fixes, though there are a few improvements.

- IPython debugger (IPdb) now supports the number of context lines for the `where` (and `w`) commands. The `context` keyword is also available in various APIs. See [PR #9097](#)
- YouTube video will now show thumbnail when exported to a media that do not support video. ([PR #9086](#))
- Add warning when running `ipython <subcommand>` when subcommand is deprecated. `jupyter` should now be used.
- Code in `%pinfo` (also known as `??`) are now highlighter ([PR #8947](#))
- `%aimport` now support module completion. ([PR #8884](#))
- `ipdb` output is now colored ! ([PR #8842](#))
- Add ability to transpose columns for completion: ([PR #8748](#))

Many many docs improvements and bug fixes, you can see the [list of changes](#)

2.10.3 IPython 4.0

Released August, 2015

IPython 4.0 is the first major release after the Big Split. IPython no longer contains the notebook, qtconsole, etc. which have moved to [jupyter](#). IPython subprojects, such as [IPython.parallel](#) and [widgets](#) have moved to their own repos as well.

The following subpackages are deprecated:

- `IPython.kernel` (now `jupyter_client` and `ipykernel`)
- `IPython.consoleapp` (now `jupyter_client.consoleapp`)
- `IPython.nbformat` (now `nbformat`)
- `IPython.nbconvert` (now `nbconvert`)
- `IPython.html` (now `notebook`)
- `IPython.parallel` (now `ipyparallel`)
- `IPython.utils.traitlets` (now `traitlets`)
- `IPython.config` (now `traitlets.config`)
- `IPython.qt` (now `qtconsole`)
- `IPython.terminal.console` (now `jupyter_console`)

and a few other utilities.

Shims for the deprecated subpackages have been added, so existing code should continue to work with a warning about the new home.

There are few changes to the code beyond the reorganization and some bugfixes.

IPython highlights:

- Public APIs for discovering IPython paths is moved from `IPython.utils.path` to `IPython.paths`. The old function locations continue to work with deprecation warnings.
- Code raising `DeprecationWarning` entered by the user in an interactive session will now display the warning by default. See [PR #8480](#) and [#8478](#).
- The `--deep-reload` flag and the corresponding options to inject `dreload` or `reload` into the interactive namespace have been deprecated, and will be removed in future versions. You should now explicitly import `reload` from `IPython.lib.deepreload` to use it.

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

2.11 Issues closed in the 4.x development cycle

2.11.1 Issues closed in 4.2

GitHub stats for 2015/02/02 - 2016/04/20 (since 4.1)

These lists are automatically generated, and may be incomplete or contain duplicates.

We closed 10 issues and merged 22 pull requests. The full list can be seen [on GitHub](#)

The following 10 authors contributed 27 commits.

- Benjamin Ragan-Kelley
- Carlos Cordoba
- Gökhan Karabulut
- Jonas Rauber
- Matthias Bussonnier
- Paul Ivanov
- Sebastian Bank
- Thomas A Caswell
- Thomas Kluyver
- Vincent Woo

2.11.2 Issues closed in 4.1

GitHub stats for 2015/08/12 - 2016/02/02 (since 4.0.0)

These lists are automatically generated, and may be incomplete or contain duplicates.

We closed 60 issues and merged 148 pull requests. The full list can be seen [on GitHub](#)

The following 52 authors contributed 468 commits.

- Aaron Meurer
- Alexandre Avanian
- Anthony Sottile
- Antony Lee
- Arthur Loder
- Ben Kasel
- Ben Rousch
- Benjamin Ragan-Kelley
- bollwyvl
- Carol Willing
- Christopher Roach
- Douglas La Rocca
- Fairly

- Fernando Perez
- Frank Sachsenheim
- Guillaume DOUMENC
- Gábor Luk
- Hoyt Koepke
- Ivan Timokhin
- Jacob Niehus
- JamshedVesuna
- Jan Schulz
- Jan-Philip Gehrcke
- jc
- Jessica B. Hamrick
- jferrara
- John Bohannon
- John Kirkham
- Jonathan Frederic
- Kyle Kelley
- Lev Givon
- Lilian Besson
- lingxz
- Matthias Bussonnier
- memeplex
- Michael Droettboom
- naught101
- Peter Waller
- Pierre Gerold
- Rémy Léone
- Scott Sanderson
- Shanzhuo Zhang
- Sylvain Corlay
- Tayfun Sen
- Thomas A Caswell
- Thomas Ballinger
- Thomas Kluyver
- Vincent Legoll
- Wouter Bolsterlee

- xconverge
- Yuri Numerov
- Zachary Pincus

2.11.3 Issues closed in 4.0

GitHub stats for 2015/02/27 - 2015/08/11 (since 3.0)

These lists are automatically generated, and may be incomplete or contain duplicates.

We closed 35 issues and merged 125 pull requests. The full list can be seen [on GitHub](#)

The following 69 authors contributed 1186 commits.

- Abe Guerra
- Adal Chiriliuc
- Alexander Belopolsky
- Andrew Murray
- Antonio Russo
- Benjamin Ragan-Kelley
- Björn Linse
- Brian Drawert
- chebee7i
- Daniel Rocco
- Donny Winston
- Drekin
- Erik Hvatum
- Fernando Perez
- Francisco de la Peña
- Frazer McLean
- Gareth Elston
- Gert-Ludwig Ingold
- Giuseppe Venturini
- Ian Barfield
- Ivan Pozdeev
- Jakob Gager
- Jan Schulz
- Jason Grout
- Jeff Hussmann
- Jessica B. Hamrick
- Joe Borg

- Joel Nothman
- Johan Forsberg
- Jonathan Frederic
- Justin Tyberg
- Koen van Besien
- Kyle Kelley
- Lorena Pantano
- Lucretiel
- Marin Gilles
- mashenjun
- Mathieu
- Matthias Bussonnier
- Merlijn van Deen
- Mikhail Korobov
- Naveen Nathan
- Nicholas Bollweg
- nottaanibot
- Omer Katz
- onesandzeroes
- Patrick Snape
- patter001
- Peter Parente
- Pietro Battiston
- RickWinter
- Robert Smith
- Ryan Nelson
- Scott Sanderson
- Sebastiaan Mathot
- Sylvain Corlay
- thethomask
- Thomas A Caswell
- Thomas Adriaan Hellinger
- Thomas Kluyver
- Tianhui Michael Li
- tmtabor
- unknown

- Victor Ramirez
- Volker Braun
- Wieland Hoffmann
- Yuval Langer
- Zoltán Vörös
- Élie Michel

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

2.12 3.x Series

2.12.1 IPython 3.2.3

Fixes compatibility with Python 3.4.4.

2.12.2 IPython 3.2.2

Address vulnerabilities when files have maliciously crafted filenames (CVE-2015-6938), or vulnerability when opening text files with malicious binary content (CVE pending).

Users are **strongly** encouraged to upgrade immediately. There are also a few small unicode and nbconvert-related fixes.

2.12.3 IPython 3.2.1

IPython 3.2.1 is a small bugfix release, primarily for cross-site security fixes in the notebook. Users are **strongly** encouraged to upgrade immediately. There are also a few small unicode and nbconvert-related fixes.

See *Issues closed in the 3.x development cycle* for details.

2.12.4 IPython 3.2

IPython 3.2 contains important security fixes. Users are **strongly** encouraged to upgrade immediately.

Highlights:

- Address cross-site scripting vulnerabilities CVE-2015-4706, CVE-2015-4707
- A security improvement that set the secure attribute to login cookie to prevent them to be sent over http
- Revert the face color of matplotlib axes in the inline backend to not be transparent.
- Enable mathjax safe mode by default
- Fix XSS vulnerability in JSON error messages
- Various widget-related fixes

See *Issues closed in the 3.x development cycle* for details.

2.12.5 IPython 3.1

Released April 3, 2015

The first 3.x bugfix release, with 33 contributors and 344 commits. This primarily includes bugfixes to notebook layout and focus problems.

Highlights:

- Various focus jumping and scrolling fixes in the notebook.
- Various message ordering and widget fixes in the notebook.
- Images in markdown and output are confined to the notebook width. An `.unconfined` CSS class is added to disable this behavior per-image. The resize handle on output images is removed.
- Improved ordering of tooltip content for Python functions, putting the signature at the top.
- Fix UnicodeErrors when displaying some objects with unicode reprs on Python 2.
- Set the kernel's working directory to the notebook directory when running `nbconvert --execute`, so that behavior matches the live notebook.
- Allow setting custom SSL options for the tornado server with `NotebookApp.ssl_options`, and protect against POODLE with default settings by disabling SSLv3.
- Fix memory leak in the IPython.parallel Controller on Python 3.

See *Issues closed in the 3.x development cycle* for details.

2.12.6 Release 3.0


Released February 27, 2015

This is a really big release. Over 150 contributors, and almost 6000 commits in a bit under a year. Support for languages other than Python is greatly improved, notebook UI has been significantly redesigned, and a lot of improvement has happened in the experimental interactive widgets. The message protocol and document format have both been updated, while maintaining better compatibility with previous versions than prior updates. The notebook webapp now enables editing of any text file, and even a web-based terminal (on Unix platforms).

3.x will be the last monolithic release of IPython, as the next release cycle will see the growing project split into its Python-specific and language-agnostic components. Language-agnostic projects (notebook, qtconsole, etc.) will move under the umbrella of the new Project Jupyter name, while Python-specific projects (interactive Python shell, Python kernel, IPython.parallel) will remain under IPython, and be split into a few smaller packages. To reflect this, IPython is in a bit of a transition state. The logo on the notebook is now the Jupyter logo. When installing kernels system-wide, they go in a **jupyter** directory. We are going to do our best to ease this transition for users and developers.

Big changes are ahead.

Using different kernels



You can now choose a kernel for a notebook within the user interface, rather than starting up a separate notebook server for each kernel you want to use. The syntax highlighting adapts to match the language you're working in.

Information about the kernel is stored in the notebook file, so when you open a notebook, it will automatically start the correct kernel.


It is also easier to use the Qt console and the terminal console with other kernels, using the `--kernel` flag:

```
ipython qtconsole --kernel bash
ipython console --kernel bash

# To list available kernels
ipython kernelspec list
```

Kernel authors should see [Kernel specs](#) for how to register their kernels with IPython so that these mechanisms work.

Typing unicode identifiers



Complex expressions can be much cleaner when written with a wider choice of characters. Python 3 allows unicode identifiers, and IPython 3 makes it easier to type those, using a feature from Julia. Type a backslash followed by a LaTeX style short name, such as `\alpha`. Press tab, and it will turn into `α`.

Widget migration guide

The widget framework has a lot of backwards incompatible changes. For information about migrating widget notebooks and custom widgets to 3.0 refer to the [widget migration guide](#).

Other new features

- `TextWidget` and `TextareaWidget` objects now include a `placeholder` attribute, for displaying placeholder text before the user has typed anything.
- The `%load` magic can now find the source for objects in the user namespace. To enable searching the namespace, use the `-n` option.

```
In [1]: %load -n my_module.some_function
```

- `DirectView` objects have a new `use_cloudpickle()` method, which works like `view.use_dill()`, but causes the `cloudpickle` module from PiCloud's `cloud` library to be used rather than `dill` or the builtin pickle module.
- Added a `.ipynb` exporter to `nbconvert`. It can be used by passing `--to notebook` as a commandline argument to `nbconvert`.
- New `nbconvert` preprocessor called `ClearOutputPreprocessor`. This clears the output from IPython notebooks.
- New preprocessor for `nbconvert` that executes all the code cells in a notebook. To run a notebook and save its output in a new notebook:

```
ipython nbconvert InputNotebook --ExecutePreprocessor.enabled=True --to notebook --  
↪output Executed
```

- Consecutive stream (`stdout/stderr`) output is merged into a single output in the notebook document. Previously, all output messages were preserved as separate output fields in the JSON. Now, the same merge is applied to the stored output as the displayed output, improving document load time for notebooks with many small outputs.
- `NotebookApp.webapp_settings` is deprecated and replaced with the more informatively named `NotebookApp.tornado_settings`.
- Using `%timeit` prints warnings if there is at least a 4x difference in timings between the slowest and fastest runs, since this might mean that the multiple runs are not independent of one another.

- It's now possible to provide mechanisms to integrate IPython with other event loops, in addition to the ones we already support. This lets you run GUI code in IPython with an interactive prompt, and to embed the IPython kernel in GUI applications. See *Integrating with GUI event loops* for details. As part of this, the direct `enable_*` and `disable_*` functions for various GUIs in `IPython.lib.inputhook` have been deprecated in favour of `enable_gui()` and `disable_gui()`.
- A `ScrollManager` was added to the notebook. The `ScrollManager` controls how the notebook document is scrolled using keyboard. Users can inherit from the `ScrollManager` or `TargetScrollManager` to customize how their notebook scrolls. The default `ScrollManager` is the `SlideScrollManager`, which tries to scroll to the nearest slide or sub-slide cell.
- The function `interact_manual()` has been added which behaves similarly to `interact()`, but adds a button to explicitly run the interacted-with function, rather than doing it automatically for every change of the parameter widgets. This should be useful for long-running functions.
- The `%cython` magic is now part of the Cython module. Use `%load_ext Cython` with a version of Cython `>= 0.21` to have access to the magic now.
- The Notebook application now offers integrated terminals on Unix platforms, intended for when it is used on a remote server. To enable these, install the `terminado` Python package.
- The Notebook application can now edit any plain text files, via a full-page CodeMirror instance.
- Setting the default highlighting language for nbconvert with the config option `NbConvertBase.default_language` is deprecated. Nbconvert now respects metadata stored in the `kernel spec`.
- IPython can now be configured systemwide, with files in `/etc/ipython` or `/usr/local/etc/ipython` on Unix systems, or `%PROGRAMDATA%\ipython` on Windows.
- Added support for configurable user-supplied Jinja HTML templates for the notebook. Paths to directories containing template files can be specified via `NotebookApp.extra_template_paths`. User-supplied template directories searched first by the notebook, making it possible to replace existing templates with your own files.

For example, to replace the notebook's built-in `error.html` with your own, create a directory like `/home/my_templates` and put your override template at `/home/my_templates/error.html`. To start the notebook with your custom error page enabled, you would run:

```
ipython notebook '--extra_template_paths=["/home/my_templates/"]'
```

It's also possible to override a template while also *inheriting* from that template, by prepending `templates/` to the `{% extends %}` target of your child template. This is useful when you only want to override a specific block of a template. For example, to add additional CSS to the built-in `error.html`, you might create an override that looks like:

```
{% extends "templates/error.html" %}

{% block stylesheet %}
{{super()}}
<style type="text/css">
  /* My Awesome CSS */
</style>
{% endblock %}
```

- Added a widget persistence API. This allows you to persist your notebooks interactive widgets. Two levels of control are provided: 1. Higher level- `WidgetManager.set_state_callbacks` allows you to register callbacks for loading and saving widget state. The callbacks you register are automatically called when necessary. 2. Lower level- the `WidgetManager` Javascript class now has `get_state` and `set_state` methods that allow you to get and set the state of the widget runtime.

Example code for persisting your widget state to session data:

```
%%javascript
require(['widgets/js/manager'], function(manager) {
    manager.WidgetManager.set_state_callbacks(function() { // Load
        return JSON.parse(sessionStorage.widgets_state || '{}');
    }, function(state) { // Save
        sessionStorage.widgets_state = JSON.stringify(state);
    });
});
```

- Enhanced support for `%env` magic. As before, `%env` with no arguments displays all environment variables and values. Additionally, `%env` can be used to get or set individual environment variables. To display an individual value, use the `%env var` syntax. To set a value, use `env var val` or `env var=val`. Python value expansion using `$` works as usual.

Backwards incompatible changes

- The `message protocol` has been updated from version 4 to version 5. Adapters are included, so IPython frontends can still talk to kernels that implement protocol version 4.
- The notebook format has been updated from version 3 to version 4. Read-only support for v4 notebooks has been backported to IPython 2.4. Notable changes:
 - heading cells are removed in favor of markdown headings
 - notebook outputs and output messages are more consistent with each other
 - use `IPython.nbformat.read()` and `write()` to read and write notebook files instead of the deprecated `IPython.nbformat.current` APIs.

You can downgrade a notebook to v3 via `nbconvert`:

```
ipython nbconvert --to notebook --nbformat 3 <notebook>
```

which will create `notebook.v3.ipynb`, a copy of the notebook in v3 format.

- `IPython.core.oinspect.getsource()` call specification has changed:
 - `oname` keyword argument has been added for property source formatting
 - `is_binary` keyword argument has been dropped, passing `True` had previously short-circuited the function to return `None` unconditionally
- Removed the `octavemagic` extension: it is now available as `oct2py.ipython`.
- Creating PDFs with LaTeX no longer uses a post processor. Use `nbconvert --to pdf` instead of `nbconvert --to latex --post pdf`.
- Used <https://github.com/jdfreder/bootstrap2to3> to migrate the Notebook to Bootstrap 3.

Additional changes:

- Set `.tab-content .row 0px`; left and right margin (bootstrap default is -15px;)
- Removed `height: @btn_mini_height`; from `.list_header>div`, `.list_item>div` in `tree.less`
- Set `#header div margin-bottom: 0px`;
- Set `#menus` to `float: left`;

- Set `#maintoolbar .navbar-text` to `float: none;`
- Added no-padding convenience class.
- Set border of `#maintoolbar` to `0px`
- Accessing the `container` DOM object when displaying javascript has been deprecated in IPython 2.0 in favor of accessing `element`. Starting with IPython 3.0 trying to access `container` will raise an error in browser javascript console.
- `IPython.utils.py3compat.open` was removed: `io.open()` provides all the same functionality.
- The `NotebookManager` and `/api/notebooks` service has been replaced by a more generic `ContentsManager` and `/api/contents` service, which supports all kinds of files.
- The Dashboard now lists all files, not just notebooks and directories.
- The `--script` hook for saving notebooks to Python scripts is removed, use `ipython nbconvert --to python notebook` instead.
- The `rmagic` extension is deprecated, as it is now part of `rpy2`. See `rpy2.ipython.rmagic`.
- `start_kernel()` and `format_kernel_cmd()` no longer accept a `executable` parameter. Use the `kernelspec` machinery instead.
- The widget classes have been renamed from `*Widget` to `*`. The old names are still functional, but are deprecated. i.e. `IntSliderWidget` has been renamed to `IntSlider`.
- The `ContainerWidget` was renamed to `Box` and no longer defaults as a flexible box in the web browser. A new `FlexBox` widget was added, which allows you to use the flexible box model.
- The notebook now uses a single websocket at `/kernels/<kernel-id>/channels` instead of separate `/kernels/<kernel-id>/{shell|iopub|stdin}` channels. Messages on each channel are identified by a `channel` key in the message dict, for both send and recv.

Content Security Policy

The Content Security Policy is a web standard for adding a layer of security to detect and mitigate certain classes of attacks, including Cross Site Scripting (XSS) and data injection attacks. This was introduced into the notebook to ensure that the IPython Notebook and its APIs (by default) can only be embedded in an `iframe` on the same origin.

Override `headers['Content-Security-Policy']` within your notebook configuration to extend for alternate domains and security settings.:

```
c.NotebookApp.tornado_settings = {
    'headers': {
        'Content-Security-Policy': "frame-ancestors 'self'"
    }
}
```

Example policies:

```
Content-Security-Policy: default-src 'self' https://*.jupyter.org
```

Matches embeddings on any subdomain of `jupyter.org`, so long as they are served over SSL.

There is a `report-uri` endpoint available for logging CSP violations, located at `/api/security/csp-report`. To use it, set `report-uri` as part of the CSP:

```
c.NotebookApp.tornado_settings = {
    'headers': {
        'Content-Security-Policy': "frame-ancestors 'self'; report-uri /api/security/csp-
↪report"
    }
}
```

It simply provides the CSP report as a warning in IPython's logs. The default CSP sets this report-uri relative to the `base_url` (not shown above).

For a more thorough and accurate guide on Content Security Policies, check out [MDN's Using Content Security Policy](#) for more examples.

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

2.13 Issues closed in the 3.x development cycle

2.13.1 Issues closed in 3.2.1

GitHub stats for 2015/06/22 - 2015/07/12 (since 3.2)

These lists are automatically generated, and may be incomplete or contain duplicates.

We closed 1 issue and merged 3 pull requests. The full list can be seen [on GitHub](#)

The following 5 authors contributed 9 commits.

- Benjamin Ragan-Kelley
- Matthias Bussonnier
- Nitin Dahyabhai
- Sebastiaan Mathot
- Thomas Kluyver

2.13.2 Issues closed in 3.2

GitHub stats for 2015/04/03 - 2015/06/21 (since 3.1)

These lists are automatically generated, and may be incomplete or contain duplicates.

We closed 7 issues and merged 30 pull requests. The full list can be seen [on GitHub](#)

The following 15 authors contributed 74 commits.

- Benjamin Ragan-Kelley
- Brian Gough
- Damián Avila
- Ian Barfield
- Jason Grout
- Jeff Hussmann
- Jessica B. Hamrick
- Kyle Kelley
- Matthias Bussonnier
- Nicholas Bollweg
- Randy Lai
- Scott Sanderson
- Sylvain Corlay
- Thomas A Caswell
- Thomas Kluyver

2.13.3 Issues closed in 3.1

GitHub stats for 2015/02/27 - 2015/04/03 (since 3.0)

These lists are automatically generated, and may be incomplete or contain duplicates.

We closed 46 issues and merged 133 pull requests. The full list can be seen [on GitHub](#).

The following 33 authors contributed 344 commits:

- Abe Guerra
- Adal Chiriliuc
- Benjamin Ragan-Kelley
- Brian Drawert
- Fernando Perez
- Gareth Elston
- Gert-Ludwig Ingold
- Giuseppe Venturini
- Jakob Gager

- Jan Schulz
- Jason Grout
- Jessica B. Hamrick
- Jonathan Frederic
- Justin Tyberg
- Lorena Pantano
- mashenjun
- Mathieu
- Matthias Bussonnier
- Morten Enemark Lund
- Naveen Nathan
- Nicholas Bollweg
- onesandzeroes
- Patrick Snape
- Peter Parente
- RickWinter
- Robert Smith
- Ryan Nelson
- Scott Sanderson
- Sylvain Corlay
- Thomas Kluyver
- tmtabor
- Wieland Hoffmann
- Yuval Langer

2.13.4 Issues closed in 3.0

GitHub stats for 2014/04/02 - 2015/02/13 (since 2.0)

These lists are automatically generated, and may be incomplete or contain duplicates.

We closed 469 issues and merged 925 pull requests. The full list can be seen [on GitHub](#).

The following 155 authors contributed 5975 commits.

- A.J. Holyoake
- abalkin
- Adam Hodgen
- Adrian Price-Whelan
- Amin Bandali
- Andreas Amann

- Andrew Dawes
- Andrew Jesaitis
- Andrew Payne
- AnneTheAgile
- Aron Ahmadia
- Ben Duffield
- Benjamin ABEL
- Benjamin Ragan-Kelley
- Benjamin Schultz
- Björn Grüning
- Björn Linse
- Blake Griffith
- Boris Egorov
- Brian E. Granger
- bsvh
- Carlos Cordoba
- Cedric GESTES
- cel
- chebee7i
- Christoph Gohlke
- CJ Carey
- Cyrille Rossant
- Dale Jung
- Damián Avila
- Damon Allen
- Daniel B. Vasquez
- Daniel Rocco
- Daniel Wehner
- Dav Clark
- David Hirschfeld
- David Neto
- dexterdev
- Dmitry Kloper
- dongweiming
- Doug Blank
- drevicko

- Dustin Rodriguez
- Eric Firing
- Eric Galloway
- Erik M. Bray
- Erik Tollerud
- Ezequiel (Zac) Panepucci
- Fernando Perez
- foogunlana
- Francisco de la Peña
- George Titsworth
- Gordon Ball
- gporras
- Grzegorz Rożniecki
- Helen ST
- immerrr
- Ingolf Becker
- Jakob Gager
- James Goppert
- James Porter
- Jan Schulz
- Jason Goad
- Jason Gors
- Jason Grout
- Jason Newton
- jdavidheiser
- Jean-Christophe Jaskula
- Jeff Hemmelgarn
- Jeffrey Bush
- Jeroen Demeyer
- Jessica B. Hamrick
- Jessica Frazelle
- jhemmelg
- Jim Garrison
- Joel Nothman
- Johannes Feist
- John Stowers

- John Zwinck
- jonasc
- Jonathan Frederic
- Juergen Hasch
- Julia Evans
- Justyna Ilczuk
- Jörg Dietrich
- K.-Michael Aye
- Kalibri
- Kester Tong
- Kyle Kelley
- Kyle Rawlins
- Lev Abalkin
- Manuel Riel
- Martin Bergtholdt
- Martin Spacek
- Mateusz Paprocki
- Mathieu
- Matthias Bussonnier
- Maximilian Albert
- mbyt
- MechCoder
- Mohan Raj Rajamanickam
- mvr
- Narahari
- Nathan Goldbaum
- Nathan Heijermans
- Nathaniel J. Smith
- ncornette
- Nicholas Bollweg
- Nick White
- Nikolay Koldunov
- Nile Geisinger
- Olga Botvinnik
- Osada Paranaliyanage
- Pankaj Pandey

- Pascal Bugnion
- patricktokeeffe
- Paul Ivanov
- Peter Odding
- Peter Parente
- Peter Würtz
- Phil Elson
- Phillip Nordwall
- Pierre Gerold
- Pierre Haessig
- Raffaele De Feo
- Ramiro Gómez
- Reggie Pierce
- Remi Rampin
- Renaud Richardet
- Richard Everson
- Scott Sanderson
- Silvia Vinyes
- Simon Guillot
- Spencer Nelson
- Stefan Zimmermann
- Steve Chan
- Steven Anton
- Steven Silvester
- sunny
- Susan Tan
- Sylvain Corlay
- Tarun Gaba
- Thomas Ballinger
- Thomas Kluyver
- Thomas Robitaille
- Thomas Spura
- Tobias Oberstein
- Torsten Bittner
- unknown
- v923z

- vaibhavsagar
- W. Trevor King
- weichm
- Xiuming Chen
- Yaroslav Halchenko
- zah

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

2.14 Migrating Widgets to IPython 3

2.14.1 Upgrading Notebooks

1. The first thing you'll notice when upgrading an IPython 2.0 widget notebook to IPython 3.0 is the «Notebook converted» dialog. Click «ok».
2. All of the widgets distributed with IPython have been renamed. The «Widget» suffix was removed from the end of the class name. i.e. `ButtonWidget` is now `Button`.
3. `ContainerWidget` was renamed to `Box`.
4. `PopupWidget` was removed from IPython, because `bootstrapjs` was problematic (creates global variables, etc.). If you use the `PopupWidget`, try using a `Box` widget instead. If your notebook can't live without the popup functionality, subclass the `Box` widget (both in Python and JS) and use JQuery UI's `draggable()` and `resizable()` methods to mimic the behavior.
5. `add_class` and `remove_class` were removed. More often than not a new attribute exists on the widget that allows you to achieve the same explicitly. i.e. the `Button` widget now has a `button_style` attribute which you can set to „primary“, „success“, „info“, „warning“, „danger“, or „“ instead of using `add_class` to add the bootstrap class. `VBox` and `HBox` classes (flexible `Box` subclasses) were added that allow you to avoid using `add_class` and `remove_class` to make flexible box model layouts. As a last resort, if you can't find a built in attribute for the class you want to use, a new `_dom_classes` list trait was added, which combines `add_class` and `remove_class` into one stateful list.
6. `set_css` and `get_css` were removed in favor of explicit style attributes - `visible`, `width`, `height`, `padding`, `margin`, `color`, `background_color`, `border_color`, `border_width`, `border_radius`, `border_style`, `font_style`, `font_weight`, `font_size`, and `font_family` are a few. If you can't find a trait to see the css attribute you need, you can, in order of preference, (A) subclass or create your own custom widget, (B) use CSS and the `_dom_classes` trait to set `_dom_classes`, or (C) use the `_css` dictionary to set CSS styling like `set_css` and `get_css`.
7. For selection widgets, such as `Dropdown`, the `values` argument has been renamed to `options`.

2.14.2 Upgrading Custom Widgets

Javascript

1. If you are distributing your widget and decide to use the deferred loading technique (preferred), you can remove all references to the `WidgetManager` and the `register model/view` calls (see the Python section below for more information).
2. In 2.0 `require.js` was used incorrectly, that has been fixed and now loading works more like Python's import. Requiring `widgets/js/widget` doesn't import the `WidgetManager` class, instead it imports a dictionary that exposes the classes within that module:

```
{
  'WidgetModel': WidgetModel,
  'WidgetView': WidgetView,
  'DOMWidgetView': DOMWidgetView,
  'ViewList': ViewList,
}
```

If you decide to continue to use the widget registry (by registering your widgets with the manager), you can import a dictionary with a handle to the `WidgetManager` class by requiring `widgets/js/manager`. Doing so will import:

```
{'WidgetManager': WidgetManager}
```

3. Don't rely on the `IPython` namespace for anything. To inherit from the `DOMWidgetView`, `WidgetView`, or `WidgetModel`, require `widgets/js/widget` as `widget`. If you were inheriting from `DOMWidgetView`, and the code looked like this:

```
IPython.DOMWidgetView.extend({...})
```

It would become this:

```
widget.DOMWidgetView.extend({...})
```

4. Custom models are encouraged. When possible, it's recommended to move your code into a custom model, so actions are performed 1 time, instead of N times where N is the number of displayed views.

Python

Generally, custom widget Python code can remain unchanged. If you distribute your custom widget, you may be using `display` and `Javascript` to publish the widget's Javascript to the front-end. That is no longer the recommended way of distributing widget Javascript. Instead have the user install the Javascript to his/her `nbextension` directory or their profile's static directory. Then use the new `_view_module` and `_model_module` traitlets in combination with `_view_name` and `_model_name` to instruct `require.js` on how to load the widget's Javascript. The Javascript is then loaded when the widget is used for the first time.

2.14.3 Details

Asynchronous

In the IPython 2.x series the only way to register custom widget views and models was to use the registry in the widget manager. Unfortunately, using this method made distributing and running custom widgets difficult. The widget maintainer had to either use the rich display framework to push the widget's Javascript to the notebook or instruct the users to install the Javascript by hand in a custom profile. With the first method, the maintainer would have to be careful about when the Javascript was pushed to the front-end. If the Javascript was pushed on Python widget `import`, the widgets wouldn't work after page refresh. This is because refreshing the page does not restart the kernel, and the Python `import` statement only runs once in a given kernel instance (unless you reload the Python modules, which isn't straight forward). This meant the maintainer would have to have a separate `push_js()` method that the user would have to call after importing the widget's Python code.

Our solution was to add support for loading widget views and models using `require.js` paths. Thus the comm and widget frameworks now support lazy loading. To do so, everything had to be converted to asynchronous code. HTML5 promises are used to accomplish that ([#6818](#), [#6914](#)).

Symmetry

In IPython 3.0, widgets can be instantiated from the front-end ([#6664](#)). On top of this, a widget persistence API was added ([#7163](#), [#7227](#)). With the widget persistence API, you can persist your widget instances using Javascript. This makes it easy to persist your widgets to your notebook document (with a small amount of custom JS). By default, the widgets are persisted to your web browsers local storage which makes them reappear when you refresh the page.

Smaller Changes

- Latex math is supported in widget descriptions ([#5937](#)).
- Widgets can be display more than once within a single container widget ([#5963](#), [#6990](#)).
- `FloatRangeSlider` and `IntRangeSlider` were added ([#6050](#)).
- «Widget» was removed from the ends of all of the widget class names ([#6125](#)).
- `ContainerWidget` was renamed to `Box` ([#6125](#)).
- `HBox` and `VBox` widgets were added ([#6125](#)).
- `add_class` and `remove_class` were removed in favor of a `_dom_classes` list ([#6235](#)).
- `get_css` and `set_css` were removed in favor of explicit traits for widget styling ([#6235](#)).
- `jslink` and `jsdlink` were added ([#6454](#), [#7468](#)).
- An `Output` widget was added, which allows you to `print` and `display` within widgets ([#6670](#)).
- `PopupWidget` was removed ([#7341](#)).
- A visual cue was added for widgets with „dead“ comms ([#7227](#)).
- A `SelectMultiple` widget was added (a `Select` widget that allows multiple things to be selected at once) ([#6890](#)).
- A class was added to help manage children views ([#6990](#)).
- A warning was added that shows on widget import because it's expected that the API will change again by IPython 4.0. This warning can be suppressed ([#7107](#), [#7200](#), [#7201](#), [#7204](#)).

2.14.4 Comm and Widget PR Index

Here is a chronological list of PRs affecting the widget and comm frameworks for IPython 3.0. Note that later PRs may revert changes made in earlier PRs:

- Add placeholder attribute to text widgets [#5652](#)
- Add latex support in widget labels, [#5937](#)
- Allow widgets to display more than once within container widgets. [#5963](#)
- use require.js, [#5980](#)
- Range widgets [#6050](#)
- Interact on_demand option [#6051](#)
- Allow text input on slider widgets [#6106](#)
- support binary buffers in comm messages [#6110](#)
- Embrace the flexible box model in the widgets [#6125](#)
- Widget trait serialization [#6128](#)
- Make Container widgets take children as the first positional argument [#6153](#)
- once-displayed [#6168](#)
- Validate slider value, when limits change [#6171](#)
- Unregistering comms in Comm Manager [#6216](#)
- Add EventfulList and EventfulDict trait types. [#6228](#)
- Remove add/remove_class and set/get_css. [#6235](#)
- avoid unregistering widget model twice [#6250](#)
- Widget property lock should compare json states, not python states [#6332](#)
- Strip the IPY_MODEL_ prefix from widget IDs before referencing them. [#6377](#)
- «event» is not defined error in Firefox [#6437](#)
- Javascript link [#6454](#)
- Bulk update of widget attributes [#6463](#)
- Creating a widget registry on the Python side. [#6493](#)
- Allow widget views to be loaded from require modules [#6494](#)
- Fix Issue [#6530](#) [#6532](#)
- Make comm manager (mostly) independent of InteractiveShell [#6540](#)
- Add semantic classes to top-level containers for single widgets [#6609](#)
- Selection Widgets: forcing „value“ to be in „values“ [#6617](#)
- Allow widgets to be constructed from Javascript [#6664](#)
- Output widget [#6670](#)
- Minor change in widgets.less to fix alignment issue [#6681](#)
- Make Selection widgets respect values order. [#6747](#)
- Widget persistence API [#6789](#)

- Add promises to the widget framework. #6818
- SelectMultiple widget #6890
- Tooltip on toggle button #6923
- Allow empty text box *while typing* for numeric widgets #6943
- Ignore failure of widget MathJax typesetting #6948
- Refactor the do_diff and manual child view lists into a separate ViewList object #6990
- Add warning to widget namespace import. #7107
- lazy load widgets #7120
- Fix padding of widgets. #7139
- Persist widgets across page refresh #7163
- Make the widget experimental error a real python warning #7200
- Make the widget error message shorter and more understandable. #7201
- Make the widget warning brief and easy to filter #7204
- Add visual cue for widgets with dead comms #7227
- Widget values as positional arguments #7260
- Remove the popup widget #7341
- document and validate link, dlink #7468
- Document interact 5637 #7525
- Update some broken examples of using widgets #7547
- Use Output widget with Interact #7554
- don't send empty execute_result messages #7560
- Validation on the python side #7602
- only show prompt overlay if there's a prompt #7661
- Allow predicate to be used for comparison in selection widgets #7674
- Fix widget view persistence. #7680
- Revert «Use Output widget with Interact» #7703

<p>Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.</p>
--

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7. If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

2.15 2.x Series

2.15.1 Release 2.4

January, 2014

Примечание: Some of the patches marked for 2.4 were left out of 2.4.0. Please use 2.4.1.

- backport read support for nbformat v4 from IPython 3
- support for PyQt5 in the kernel (not QtConsole)
- support for Pygments 2.0

For more information on what fixes have been backported to 2.4, see our [detailed release info](#).

2.15.2 Release 2.3.1

November, 2014

- Fix CRCRLF line-ending bug in notebooks on Windows

For more information on what fixes have been backported to 2.3.1, see our [detailed release info](#).

2.15.3 Release 2.3.0

October, 2014

- improve qt5 support
- prevent notebook data loss with atomic writes

For more information on what fixes have been backported to 2.3, see our [detailed release info](#).

2.15.4 Release 2.2.0

August, 2014

- Add CORS configuration

For more information on what fixes have been backported to 2.2, see our [detailed release info](#).

2.15.5 Release 2.1.0

May, 2014

IPython 2.1 is the first bugfix release for 2.0. For more information on what fixes have been backported to 2.1, see our [detailed release info](#).

2.15.6 Release 2.0.0

April, 2014

IPython 2.0 requires Python 2.7.2 or 3.3.0. It does not support Python 3.0, 3.1, 3.2, 2.5, or 2.6.

The principal milestones of 2.0 are:

- interactive widgets for the notebook
- directory navigation in the notebook dashboard
- persistent URLs for notebooks
- a new modal user interface in the notebook
- a security model for notebooks


Contribution summary since IPython 1.0 in August, 2013:

- ~8 months of work
- ~650 pull requests merged
- ~400 issues closed (non-pull requests)
- contributions from ~100 authors
- ~4000 commits

The amount of work included in this release is so large that we can only cover here the main highlights; please see our [detailed release statistics](#) for links to every issue and pull request closed on GitHub as well as a full list of individual contributors.

New stuff in the IPython notebook


Directory navigation



The IPython notebook dashboard allows navigation into subdirectories. URLs are persistent based on the notebook's path and name, so no more random UUID URLs.

Serving local files no longer needs the `files/` prefix. Relative links across notebooks and other files should work just as if notebooks were regular HTML files.

Interactive widgets




IPython 2.0 adds `IPython.html.widgets`, for manipulating Python objects in the kernel with GUI controls in the notebook. IPython comes with a few built-in widgets for simple data types, and an API designed for developers to build more complex widgets. See the [widget docs](#) for more information.

Modal user interface

The notebook has added separate Edit and Command modes, allowing easier keyboard commands and making keyboard shortcut customization possible. See the new [User Interface notebook](#) for more information.

You can familiarize yourself with the updated notebook user interface, including an explanation of Edit and Command modes, by going through the short guided tour which can be started from the Help menu.




Security

2.0 introduces a security model for notebooks, to prevent untrusted code from executing on users' behalf when notebooks open. A quick summary of the model:

- Trust is determined by signing notebooks.
- Untrusted HTML output is sanitized.
- Untrusted Javascript is never executed.
- HTML and Javascript in Markdown are never trusted.

Dashboard «Running» tab



The dashboard now has a «Running» tab which shows all of the running notebooks.

Single codebase Python 3 support

IPython previously supported Python 3 by running 2to3 during setup. We have now switched to a single codebase which runs natively on Python 2.7 and 3.3.

For notes on how to maintain this, see [/development/pycompat](#).

Selecting matplotlib figure formats

Deprecate single-format `InlineBackend.figure_format` configurable in favor of `InlineBackend.figure_formats`, which is a set, supporting multiple simultaneous figure formats (e.g. png, pdf).

This is available at runtime with the new API function `IPython.display.set_matplotlib_formats()`.

clear_output changes

- There is no longer a 500ms delay when calling `clear_output`.
- The ability to clear stderr and stdout individually was removed.
- A new `wait` flag that prevents `clear_output` from being executed until new output is available. This eliminates animation flickering by allowing the user to double buffer the output.
- The output div height is remembered when the `wait=True` flag is used.

Extending configurable containers

Some configurable traits are containers (list, dict, set) Config objects now support calling `extend`, `update`, `insert`, etc. on traits in config files, which will ultimately result in calling those methods on the original object.

The effect being that you can now add to containers without having to copy/paste the initial value:

```
c = get_config()
c.InlineBackend.rc.update({ 'figure.figsize' : (6, 4) })
```

Changes to hidden namespace on startup

Previously, all names declared in code run at startup (startup files, `ipython -i script.py`, etc.) were added to the hidden namespace, which hides the names from tools like `%whos`. There are two changes to this behavior:

1. Scripts run on the command-line `ipython -i script.py` now behave the same as if they were passed to ```%run`, so their variables are never hidden.
2. A boolean config flag `InteractiveShellApp.hide_initial_ns` has been added to optionally disable the hidden behavior altogether. The default behavior is unchanged.

Using dill to expand serialization support

The new function `use_dill()` allows dill to extend serialization support in `IPython.parallel` (closures, etc.). A `DirectView.use_dill()` convenience method was also added, to enable dill locally and on all engines with one call.

New IPython console lexer

The IPython console lexer has been rewritten and now supports tracebacks and customized input/output prompts. See the *new lexer docs* for details.

DisplayFormatter changes

There was no official way to query or remove callbacks in the Formatter API. To remedy this, the following methods are added to `BaseFormatter`:

- `lookup(instance)` - return appropriate callback or a given object
- `lookup_by_type(type_or_str)` - return appropriate callback for a given type or 'mod.name' type string
- `pop(type_or_str)` - remove a type (by type or string). Pass a second argument to avoid `KeyError` (like dict).

All of the above methods raise a `KeyError` if no match is found.

And the following methods are changed:

- `for_type(type_or_str)` - behaves the same as before, only adding support for 'mod.name' type strings in addition to plain types. This removes the need for `for_type_by_name()`, but it remains for backward compatibility.

Formatters can now raise `NotImplementedError` in addition to returning `None` to indicate that they cannot format a given object.

Exceptions and Warnings

Exceptions are no longer silenced when formatters fail. Instead, these are turned into a *FormatterWarning*. A `FormatterWarning` will also be issued if a formatter returns data of an invalid type (e.g. an integer for „image/png“).

Other changes

- `%%capture` cell magic now captures the rich display output, not just `stdout/stderr`
- In notebook, Showing tooltip on tab has been disabled to avoid conflict with completion, Shift-Tab could still be used to invoke tooltip when inside function signature and/or on selection.
- `object_info_request` has been replaced by `object_info` for consistency in the javascript API. `object_info` is a simpler interface to register callback that is incompatible with `object_info_request`.
- Previous versions of IPython on Linux would use the XDG config directory, creating `~/.config/ipython` by default. We have decided to go back to `~/.ipython` for consistency among systems. IPython will issue a warning if it finds the XDG location, and will move it to the new location if there isn't already a directory there.

- Equations, images and tables are now centered in Markdown cells.
- Multiline equations are now centered in output areas; single line equations remain left justified.
- IPython config objects can be loaded from and serialized to JSON. JSON config file have the same base name as their `.py` counterpart, and will be loaded with higher priority if found.
- bash completion updated with support for all ipython subcommands and flags, including `nbconvert`
- `ipython history trim`: added `--keep=<N>` as an alias for the more verbose `--HistoryTrim.keep=<N>`
- New `ipython history clear` subcommand, which is the same as the newly supported `ipython history trim --keep=0`
- You can now run notebooks in an interactive session via `%run notebook.ipynb`.
- Print preview is back in the notebook menus, along with options to download the open notebook in various formats. This is powered by `nbconvert`.
- `PandocMissing` exceptions will be raised if Pandoc is unavailable, and warnings will be printed if the version found is too old. The recommended Pandoc version for use with `nbconvert` is 1.12.1.
- The `InlineBackend.figure_format` now supports JPEG output if PIL/Pillow is available.
- Input transformers (see *Custom input transformation*) may now raise `SyntaxError` if they determine that input is invalid. The input transformation machinery in IPython will handle displaying the exception to the user and resetting state.
- Calling `container.show()` on javascript display is deprecated and will trigger errors on future IPython notebook versions. `container` now show itself as soon as non-empty
- Added `InlineBackend.print_figure_kwargs` to allow passing keyword arguments to matplotlib's `Canvas.print_figure`. This can be used to change the value of `bbox_inches`, which is „tight“ by default, or set the quality of JPEG figures.
- A new callback system has been introduced. For details, see *IPython Events*.
- jQuery and require.js are loaded from CDNs in the default HTML template, so javascript is available in static HTML export (e.g. `nbviewer`).

Backwards incompatible changes

- Python 2.6 and 3.2 are no longer supported: the minimum required Python versions are now 2.7 and 3.3.
- The `Transformer` classes have been renamed to `Preprocessor` in `nbconvert` and their `call` methods have been renamed to `preprocess`.
- The `call` methods of `nbconvert` post-processors have been renamed to `postprocess`.
- The module `IPython.core.fakemodule` has been removed.
- The alias system has been reimplemented to use magic functions. There should be little visible difference while automagics are enabled, as they are by default, but parts of the *AliasManager* API have been removed.
- We fixed an issue with switching between matplotlib inline and GUI backends, but the fix requires matplotlib 1.1 or newer. So from now on, we consider matplotlib 1.1 to be the minimally supported version for IPython. Older versions for the most part will work, but we make no guarantees about it.
- The `pycolor` command has been removed. We recommend the much more capable `pygmentize` command from the *Pygments* project. If you need to keep the exact output of `pycolor`, you can still use `python -m IPython.utils.PyColorize foo.py`.

- `IPython.lib.irunner` and its command-line entry point have been removed. It had fallen out of use long ago.
- The `input_prefilter` hook has been removed, as it was never actually used by the code. The input transformer system offers much more powerful APIs to work with input code. See [Custom input transformation](#) for details.
- `IPython.core.inputsplitter.IPythonInputSplitter` no longer has a method `source_raw_reset()`, but gains `raw_reset()` instead. Use of `source_raw_reset` can be replaced with:

```
raw = isp.source_raw
transformed = isp.source_reset()
```

- The Azure notebook manager was removed as it was no longer compatible with the notebook storage scheme.
- Simplifying configurable URLs
 - `base_project_url` is renamed to `base_url` (`base_project_url` is kept as a deprecated alias, for now)
 - `base_kernel_url` configurable is removed (use `base_url`)
 - `websocket_url` configurable is removed (use `base_url`)

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

2.16 Issues closed in the 2.x development cycle

2.16.1 Issues closed in 2.4.1

GitHub stats for 2014/11/01 - 2015/01/30

Примечание: IPython 2.4.0 was released without a few of the backports listed below. 2.4.1 has the correct patches intended for 2.4.0.

These lists are automatically generated, and may be incomplete or contain duplicates.

The following 7 authors contributed 35 commits.

- Benjamin Ragan-Kelley
- Carlos Cordoba
- Damon Allen

- Jessica B. Hamrick
- Mateusz Paprocki
- Peter Würtz
- Thomas Kluyver

We closed 10 issues and merged 6 pull requests; this is the full list (generated with the script `tools/github_stats.py`):

Pull Requests (10):

- [PR #7106](#): Changed the display order of rich output in the live notebook.
- [PR #6878](#): Update pygments monkeypatch for compatibility with Pygments 2.0
- [PR #6778](#): backport nbformat v4 to 2.x
- [PR #6761](#): `object_info_reply` field is `oname`, not `name`
- [PR #6653](#): Fix `IPython.utils.ansispan()` to ignore stray `[0m`
- [PR #6706](#): Correctly display prompt numbers that are `None`
- [PR #6634](#): don't use `contains` in `SelectWidget` `item_query`
- [PR #6593](#): note how to start the `qtconsole`
- [PR #6281](#): more minor fixes to release scripts
- [PR #5458](#): Add support for `PyQt5`.

Issues (6):

- [#7272](#): `qtconsole` problems with `pygments`
- [#7049](#): Cause `TypeError`: „`NoneType`“ object is not callable in `qtconsole`
- [#6877](#): Qt console doesn't work with `pygments 2.0rc1`
- [#6689](#): Problem with string containing two or more question marks
- [#6702](#): Cell numbering after `ClearOutput` preprocessor
- [#6633](#): `selectwidget` doesn't display 1 as a selection choice when passed in as a member of values list

2.16.2 Issues closed in 2.3.1

Just one bugfix: fixed bad `CRCRLF` line-endings in notebooks on Windows

Pull Requests (1):

- [PR #6911](#): don't use text mode in `mkstemp`

Issues (1):

- [#6599](#): Notebook.ipynb `CR+LF` turned into `CR+CR+LF`

2.16.3 Issues closed in 2.3.0

GitHub stats for 2014/08/06 - 2014/10/01

These lists are automatically generated, and may be incomplete or contain duplicates.

The following 6 authors contributed 31 commits.

- Benjamin Ragan-Kelley
- David Hirschfeld
- Eric Firing
- Jessica B. Hamrick
- Matthias Bussonnier
- Thomas Kluyver

We closed 16 issues and merged 9 pull requests; this is the full list (generated with the script `tools/github_stats.py`):

Pull Requests (16):

- [PR #6587](#): support `%matplotlib qt5` and `%matplotlib nbagg`
- [PR #6583](#): Windows symlink test fixes
- [PR #6585](#): fixes [#6473](#)
- [PR #6581](#): Properly mock winreg functions for test
- [PR #6556](#): Use some more informative asserts in inprocess kernel tests
- [PR #6514](#): Fix for copying metadata flags
- [PR #6453](#): Copy file metadata in atomic save
- [PR #6480](#): only compare host:port in `Websocket.check_origin`
- [PR #6483](#): Trim anchor link in heading cells, fixes [#6324](#)
- [PR #6410](#): Fix relative import in appnope
- [PR #6395](#): update mathjax CDN url in nbconvert template
- [PR #6269](#): Implement atomic save
- [PR #6374](#): Rename `abort_queues` -> `_abort_queues`
- [PR #6321](#): Use appnope in qt and wx gui support from the terminal; closes [#6189](#)
- [PR #6318](#): use `write_error` instead of `get_error_html`
- [PR #6303](#): Fix error message when failing to load a notebook

Issues (9):

- [#6057](#): `%matplotlib + qt5`
- [#6518](#): Test failure in atomic save on Windows
- [#6473](#): Switching between «Raw Cell Format» and «Edit Metadata» does not work
- [#6405](#): Creating a notebook should respect directory permissions; saving should respect prior permissions
- [#6324](#): Anchors in Heading don't work.

- [#6409](#): No module named „_dummy“
- [#6392](#): Mathjax library link broken
- [#6329](#): IPython Notebook Server URL now requires «tree» at the end of the URL? (version 2.2)
- [#6189](#): ipython console freezes for increasing no of seconds in %pylab mode

2.16.4 Issues closed in 2.2.0

GitHub stats for 2014/05/21 - 2014/08/06 (tag: rel-2.1.0)

These lists are automatically generated, and may be incomplete or contain duplicates.

The following 13 authors contributed 36 commits.

- Adam Hodgen
- Benjamin Ragan-Kelley
- Björn Grüning
- Dara Adib
- Eric Galloway
- Jonathan Frederic
- Kyle Kelley
- Matthias Bussonnier
- Paul Ivanov
- Shayne Hodge
- Steven Anton
- Thomas Kluyver
- Zahari

We closed 23 issues and merged 11 pull requests; this is the full list (generated with the script `tools/github_stats.py`):

Pull Requests (23):

- [PR #6279](#): minor updates to release scripts
- [PR #6273](#): Upgrade default mathjax version.
- [PR #6249](#): always use HTTPS getting mathjax from CDN
- [PR #6114](#): update hmac signature comparison
- [PR #6195](#): Close handle on new temporary files before returning filename
- [PR #6143](#): pin tornado to < 4 on travis js tests
- [PR #6134](#): remove rackcdn https workaround for mathjax cdn
- [PR #6120](#): Only allow iframe embedding on same origin.
- [PR #6117](#): Remove / from route of TreeRedirectHandler.
- [PR #6105](#): only set allow_origin_pat if defined
- [PR #6102](#): Add newline if missing to end of script magic cell

- [PR #6077](#): allow unicode keys in dicts in `json_clean`
- [PR #6061](#): make CORS configurable
- [PR #6081](#): don't modify dict keys while iterating through them
- [PR #5803](#): unify visual line handling
- [PR #6005](#): Changed right arrow key movement function to mirror left arrow key
- [PR #6029](#): add `pickleutil.PICKLE_PROTOCOL`
- [PR #6003](#): Set `kernel_id` before checking websocket
- [PR #5994](#): Fix ssh tunnel for Python3
- [PR #5973](#): Do not create `checkpoint_dir` relative to current dir
- [PR #5933](#): fix `qt_loader` import hook signature
- [PR #5944](#): Markdown rendering bug fix.
- [PR #5917](#): use `shutil.move` instead of `os.rename`

Issues (11):

- [#6246](#): Include MathJax by default or access the CDN over a secure connection
- [#5525](#): Websocket origin check fails when used with Apache WS proxy
- [#5901](#): 2 test failures in Python 3.4 in parallel group
- [#5926](#): QT console: text selection cannot be made from left to right with keyboard
- [#5998](#): `use_dill` does not work in Python 3.4
- [#5964](#): Traceback on Qt console exit
- [#5787](#): Error in Notebook-Generated latex (`nbconvert`)
- [#5950](#): `qtconsole` truncates help
- [#5943](#): 2.x: notebook fails to load when using HTML comments
- [#5932](#): Qt ImportDenier Does Not Adhere to PEP302
- [#5898](#): `OSError` when moving configuration file

2.16.5 Issues closed in 2.1.0

GitHub stats for 2014/04/02 - 2014/05/21 (since 2.0.0)

These lists are automatically generated, and may be incomplete or contain duplicates.

The following 35 authors contributed 145 commits.

- Adrian Price-Whelan
- Aron Ahmadi
- Benjamin Ragan-Kelley
- Benjamin Schultz
- Björn Linse
- Blake Griffith
- chebee7i

- [Damián Avila](#)
- [Dav Clark](#)
- [dexterdev](#)
- [Erik Tollerud](#)
- [Grzegorz Rożniecki](#)
- [Jakob Gager](#)
- [jdavidheiser](#)
- [Jessica B. Hamrick](#)
- [Jim Garrison](#)
- [Jonathan Frederic](#)
- [Matthias Bussonnier](#)
- [Maximilian Albert](#)
- [Mohan Raj Rajamanickam](#)
- [ncornette](#)
- [Nikolay Koldunov](#)
- [Nile Geisinger](#)
- [Pankaj Pandey](#)
- [Paul Ivanov](#)
- [Pierre Haessig](#)
- [Raffaele De Feo](#)
- [Renaud Richardet](#)
- [Spencer Nelson](#)
- [Steve Chan](#)
- [sunny](#)
- [Susan Tan](#)
- [Thomas Kluyver](#)
- [Yaroslav Halchenko](#)
- [zah](#)

We closed a total of 129 issues, 92 pull requests and 37 regular issues; this is the full list (generated with the script `tools/github_stats.py --milestone 2.1`):

Pull Requests (92):

- [PR #5871](#): specify encoding in `msgpack.unpackb`
- [PR #5869](#): Catch more errors from clipboard access on Windows
- [PR #5866](#): Make test robust against differences in line endings
- [PR #5605](#): Two cell toolbar fixes.
- [PR #5843](#): remove Firefox-specific CSS workaround

- PR #5845: Pass Windows interrupt event to kernels as an environment variable
- PR #5835: fix typo in v2 convert
- PR #5841: Fix writing history with output to a file in Python 2
- PR #5842: fix typo in nbconvert help
- PR #5846: Fix typos in Cython example
- PR #5839: Close graphics dev in finally clause
- PR #5837: pass on install docs
- PR #5832: Fixed example to work with python3
- PR #5826: allow notebook tour instantiation to fail
- PR #5560: Minor expansion of Cython example
- PR #5818: interpret any exception in getcallargs as not callable
- PR #5816: Add output to IPython directive when in verbatim mode.
- PR #5822: Don't overwrite widget description in interact
- PR #5782: Silence exception thrown by completer when dir() does not return a list
- PR #5807: Drop log level to info for Qt console shutdown
- PR #5814: Remove -i options from mv, rm and cp aliases
- PR #5812: Fix application name when printing subcommand help.
- PR #5804: remove an inappropriate !
- PR #5805: fix engine startup files
- PR #5806: Don't auto-move .config/ipython if symbolic link
- PR #5716: Add booktabs package to latex base.tplx
- PR #5669: allows threadsafe sys.stdout.flush from background threads
- PR #5668: allow async output on the most recent request
- PR #5768: fix cursor keys in long lines wrapped in markdown
- PR #5788: run cells with `silent=True` in `%run nb.ipynb`
- PR #5715: log all failed ajax API requests
- PR #5769: Don't unescape the text that goes into a title tag
- PR #5762: Fix check for pickling closures
- PR #5766: View.map with empty sequence should return empty list
- PR #5758: Applied bug fix: using fc and ec did not properly set the figure canvas ...
- PR #5754: Format command name into subcommand_description at run time, not import
- PR #5744: Describe using PyPI/pip to distribute & install extensions
- PR #5712: monkeypatch inspect.findsource only when we use it
- PR #5708: create checkpoints dir in notebook subdirectories
- PR #5714: log error message when API requests fail
- PR #5732: Quick typo fix in nbformat/convert.py

- PR #5713: Fix a NameError in IPython.parallel
- PR #5704: Update nbconvertapp.py
- PR #5534: cleanup some `pre` css inheritance
- PR #5699: don't use common names in require decorators
- PR #5692: Update notebook.rst fixing broken reference to notebook examples readme
- PR #5693: Update parallel_intro.rst to fix a broken link to examples
- PR #5486: disambiguate to location when no IPs can be determined
- PR #5574: Remove the outdated keyboard shortcuts from notebook docs
- PR #5568: Use `__qualname__` in pretty reprs for Python 3
- PR #5678: Fix copy & paste error in docstring of ImageWidget class
- PR #5677: Fix `%bookmark -l` for Python 3
- PR #5670: nbconvert: Fix CWD imports
- PR #5647: Mention git hooks in install documentation
- PR #5671: Fix blank slides issue in Reveal slideshow pdf export
- PR #5657: use „localhost“ as default for the notebook server
- PR #5584: more semantic icons
- PR #5594: update components with marked-0.3.2
- PR #5500: check for Python 3.2
- PR #5582: reset readline after running PYTHONSTARTUP
- PR #5630: Fixed Issue #4012 Added Help menubar link to Github markdown doc
- PR #5613: Fixing bug #5607
- PR #5633: Provide more help if lessc is not found.
- PR #5620: fixed a typo in IPython.core.formatters
- PR #5619: Fix typo in storemagic module docstring
- PR #5592: add missing `browser` to `notebook_aliases` list
- PR #5506: Fix ipconfig regex pattern
- PR #5581: Fix `rmagic` for cells ending in comment.
- PR #5576: only process `cr` if it's found
- PR #5478: Add git-hooks install script. Update README.md
- PR #5546: do not shutdown notebook if „n“ is part of answer
- PR #5527: Don't remove upload items from nav tree unless explicitly requested.
- PR #5501: remove inappropriate wheel tag override
- PR #5548: FileNotebookManager: Use `shutil.move()` instead of `os.rename()`
- PR #5524: never use `for (var i in array)`
- PR #5459: Fix interact animation page jump FF
- PR #5559: Minor typo fix in «Cython Magics.ipynb»

- PR #5507: Fix typo in interactive widgets examples index notebook
- PR #5554: Make HasTraits pickleable
- PR #5535: fix n^2 performance issue in `coalesce_streams` preprocessor
- PR #5522: fix iteration over `Client`
- PR #5488: Added missing `require` and `jquery` from `cdn`.
- PR #5516: ENH: list generated config files in `generated`, and `rm` them upon `clean`
- PR #5493: made a minor fix to one of the widget examples
- PR #5512: Update tooltips to refer to `shift-tab`
- PR #5505: Make `backport_pr` work on Python 3
- PR #5503: check explicitly for „dev“ before adding the note to docs
- PR #5498: use milestones to indicate backport
- PR #5492: Polish `whatsnew` docs
- PR #5495: Fix various broken things in docs
- PR #5496: Exclude `whatsnew/pr` directory from docs builds
- PR #5489: Fix required Python versions

Issues (37):

- #5364: Horizontal scrollbar hides cell's last line on Firefox
- #5192: horizontal scrollbar overlaps output or touches next cell
- #5840: Third-party Windows kernels don't get interrupt signal
- #2412: print history to file using `qtconsole` and `notebook`
- #5703: Notebook doesn't render with «ask me every time» cookie setting in Firefox
- #5817: calling mock object in IPython 2.0.0 under Python 3.4.0 raises `AttributeError`
- #5499: Error running widgets `nbconvert` example
- #5654: Broken links from `ipython` documentation
- #5019: `print` in QT event callback doesn't show up in `ipython` notebook.
- #5800: Only last In prompt number set ?
- #5801: `startup_command` specified in `ipengine_config.py` is not executed
- #5690: `ipython 2.0.0` and `pandoc 1.12.2.1` problem
- #5408: Add checking/flushing of background output from kernel in `mainloop`
- #5407: clearing message handlers on `status=idle` loses `async` output
- #5467: Incorrect behavior of up/down keyboard arrows in code cells on wrapped lines
- #3085: nicer notebook error message when lacking permissions
- #5765: `map_sync` over empty list raises `IndexError`
- #5553: Notebook `matplotlib` inline backend: can't set `figure facecolor`
- #5710: `inspect.findsource` monkeypatch raises wrong exception for C extensions
- #5706: Multi-Directory notebooks overwrite each other's checkpoints

- #5698: can't require a function named `f`
- #5569: Keyboard shortcuts in documentation are out of date
- #5566: Function name printing should use `__qualname__` instead of `__name__` (Python 3)
- #5676: «bookmark -l» not working in ipython 2.0
- #5555: Differentiate more clearly between Notebooks and Folders in new UI
- #5590: Marked double escape
- #5514: import tab-complete fail with ipython 2.0 shell
- #4012: Notebook: link to markdown formatting reference
- #5611: Typo in „storemagic“ documentation
- #5589: Kernel start fails when using `-browser` argument
- #5491: Bug in Windows ipconfig ip address regular expression
- #5579: rmagic extension throws „Error while parsing the string.“ when last line is comment
- #5518: Ipython2 will not open ipynb in example directory
- #5561: New widget documentation has missing notebook link
- #5128: Page jumping when output from widget interaction replaced
- #5519: IPython.parallel.Client behavior as iterator
- #5510: Tab-completion for function argument list

2.16.6 Issues closed in 2.0.0

GitHub stats for 2013/08/09 - 2014/04/01 (since 1.0.0)

These lists are automatically generated, and may be incomplete or contain duplicates.

The following 94 authors contributed 3949 commits.

- Aaron Meurer
- Abhinav Upadhyay
- Adam Riggall
- Alex Rudy
- Andrew Mark
- Angus Griffith
- Antony Lee
- Aron Ahmadi
- Arun Persaud
- Benjamin Ragan-Kelley
- Bing Xia
- Blake Griffith
- Bouke van der Bijl
- Bradley M. Froehle

- Brian E. Granger
- Carlos Cordoba
- chapmanb
- chebee7i
- Christoph Gohlke
- Christophe Pradal
- Cyrille Rossant
- Damián Avila
- Daniel B. Vasquez
- Dav Clark
- David Hirschfeld
- David P. Sanders
- David Wyde
- David Österberg
- Doug Blank
- Dražen Lučanin
- epifanio
- Fernando Perez
- Gabriel Becker
- Geert Barentsen
- Hans Meine
- Ingolf Becker
- Jake Vanderplas
- Jakob Gager
- James Porter
- Jason Grout
- Jeffrey Tratner
- Jonah Graham
- Jonathan Frederic
- Joris Van den Bossche
- Juergen Hasch
- Julian Taylor
- Katie Silverio
- Kevin Burke
- Kieran O'Mahony
- Konrad Hinsen

- Kyle Kelley
- Lawrence Fu
- Marc Molla
- Martín Gaitán
- Matt Henderson
- Matthew Brett
- Matthias Bussonnier
- Michael Droettboom
- Mike McKerns
- Nathan Goldbaum
- Pablo de Oliveira
- Pankaj Pandey
- Pascal Schetelat
- Paul Ivanov
- Paul Moore
- Pere Vilas
- Peter Davis
- Philippe Mallet-Ladeira
- Preston Holmes
- Puneeth Chaganti
- Richard Everson
- Roberto Bonvallet
- Samuel Ainsworth
- Sean Vig
- Shashi Gowda
- Skipper Seabold
- Stephan Rave
- Steve Fox
- Steven Silvester
- stonebig
- Susan Tan
- Sylvain Corlay
- Takeshi Kanmae
- Ted Drain
- Thomas A Caswell
- Thomas Kluyver

- Théophile Studer
- Volker Braun
- Wieland Hoffmann
- Yaroslav Halchenko
- Yoval P.
- Yung Siang Liao
- Zachary Sailer
- zah

We closed a total of 1121 issues, 687 pull requests and 434 regular issues; this is the full list (generated with the script `tools/github_stats.py`):

Pull Requests (687):

- [PR #5487](#): remove weird unicode space in the new copyright header
- [PR #5476](#): For 2.0: Fix links in Notebook Help Menu
- [PR #5337](#): Examples reorganization
- [PR #5436](#): CodeMirror shortcuts in QuickHelp
- [PR #5444](#): Fix numeric verification for Int and Float text widgets.
- [PR #5449](#): Stretch keyboard shortcut dialog
- [PR #5473](#): Minor corrections of git-hooks setup instructions
- [PR #5471](#): Add coding magic comment to nbconvert Python template
- [PR #5452](#): `print_figure` returns unicode for svg
- [PR #5450](#): proposal: remove codename
- [PR #5462](#): DOC : fixed minor error in using topological sort
- [PR #5463](#): make `spin_thread` tests more forgiving of slow VMs
- [PR #5464](#): Fix starting notebook server with file/directory at command line.
- [PR #5453](#): remove gitwash
- [PR #5454](#): Improve history API docs
- [PR #5431](#): update `github_stats` and `gh_api` for 2.0
- [PR #5290](#): Add dual mode JS tests
- [PR #5451](#): check that a handler is actually registered in `ShortcutManager.handles`
- [PR #5447](#): Add `%%python2` cell magic
- [PR #5439](#): Point to the stable SymPy docs, not the dev docs
- [PR #5437](#): Install jquery-ui images
- [PR #5434](#): fix check for empty cells in rst template
- [PR #5432](#): update links in notebook help menu
- [PR #5435](#): Update whatsnew (notebook tour)
- [PR #5433](#): Document extraction of octave and R magics

- PR #5428: Update COPYING.txt
- PR #5426: Separate get_session_info between HistoryAccessor and HistoryManager
- PR #5419: move prompts from margin to main column on small screens
- PR #5430: Make sure `element` is correct in the context of displayed JS
- PR #5396: prevent saving of partially loaded notebooks
- PR #5429: Fix tooltip pager feature
- PR #5330: Updates to shell reference doc
- PR #5404: Fix broken accordion widget
- PR #5339: Don't use fork to start the notebook in js tests
- PR #5320: Fix for Tooltip & completer click focus bug.
- PR #5421: Move configuration of Python test controllers into setup()
- PR #5418: fix typo in ssh launcher send_file
- PR #5403: remove alt- shortcut
- PR #5389: better log message in deprecated files/ redirect
- PR #5333: Fix `filenbmanager.list_dirs` fails for Windows user profile directory
- PR #5390: finish PR #5333
- PR #5326: Some gardening on `iptest` result reporting
- PR #5375: remove unnecessary onload hack from mathjax macro
- PR #5368: Flexbox classes specificity fixes
- PR #5331: fix `raw_input` CSS
- PR #5395: urlencode images for rst files
- PR #5049: update quickhelp on adding and removing shortcuts
- PR #5391: Fix Gecko (Netscape) keyboard handling
- PR #5387: Respect „r“ characters in `nbconvert`.
- PR #5399: Revert PR #5388
- PR #5388: Suppress output even when a comment follows `;`. Fixes #4525.
- PR #5394: `nbconvert` doc update
- PR #5359: do not install less sources
- PR #5346: give hint on where to find `custom.js`
- PR #5357: catch exception in `copystat`
- PR #5380: Remove `DefineShortVerb...` line from latex base template
- PR #5376: elide long containers in pretty
- PR #5310: remove raw cell placeholder on focus, closes #5238
- PR #5332: semantic names for indicator icons
- PR #5386: Fix import of `socketserver` on Python 3
- PR #5360: remove some redundant font-family: monospace

- PR #5379: don't instantiate Application just for default logger
- PR #5372: Don't autoclose strings
- PR #5296: unify keyboard shortcut and codemirror interaction
- PR #5349: Make Hub.registration_timeout configurable
- PR #5340: install bootstrap-tour css
- PR #5335: Update docstring for deepreload module
- PR #5321: Improve assignment regex to match more tuple unpacking syntax
- PR #5325: add NotebookNotary to NotebookApp's class list
- PR #5313: avoid loading preprocessors twice
- PR #5308: fix HTML capitalization in Highlight2HTML
- PR #5295: OutputArea.append_type functions are not prototype methods
- PR #5318: Fix local import of select_figure_formats
- PR #5300: Fix NameError: name „_rl“ is not defined
- PR #5292: focus next cell on shift+enter
- PR #5291: debug occasional error in test_queue_status
- PR #5289: Finishing up #5274 (widget paths fixes)
- PR #5232: Make nbconvert html full output like notebook's html.
- PR #5288: Correct initial state of kernel status indicator
- PR #5253: display any output from this session in terminal console
- PR #4802: Tour of the notebook UI (was UI elements inline with highlighting)
- PR #5285: Update signature presentation in pininfo classes
- PR #5268: Refactoring Notebook.command_mode
- PR #5226: Don't run PYTHONSTARTUP file if a file or code is passed
- PR #5283: Remove Widget.closed attribute
- PR #5279: nbconvert: Make sure node is atleast version 0.9.12
- PR #5281: fix a typo introduced by a rebased PR
- PR #5280: append Firefox overflow-x fix
- PR #5277: check that PIL can save JPEG to BytesIO
- PR #5044: Store timestamps for modules to autoreload
- PR #5278: Update whatsnew doc from pr files
- PR #5276: Fix kernel restart in case connection file is deleted.
- PR #5272: allow highlighting language to be set from notebook metadata
- PR #5158: log refusal to serve hidden directories
- PR #5188: New events system
- PR #5265: Missing class def for TimeoutError
- PR #5267: normalize unicode in notebook API tests

- PR #5076: Refactor keyboard handling
- PR #5241: Add some tests for utils
- PR #5261: Don't allow edit mode up arrow to continue past index == 0
- PR #5223: use on-load event to trigger resizable images
- PR #5252: make one strptime call at import of jsonutil
- PR #5153: Dashboard sorting
- PR #5169: Allow custom header
- PR #5242: clear `_reply_content` cache before using it
- PR #5194: require latex titles to be ascii
- PR #5244: try to avoid EADDRINUSE errors on travis
- PR #5245: support extracted output in HTML template
- PR #5209: make `input_area` css generic to cells
- PR #5246: less `%pylab`, more `cowbell`!
- PR #4895: Improvements to `%run` completions
- PR #5243: Add Javascript to base display priority list.
- PR #5175: Audit `.html()` calls take #2
- PR #5146: Dual mode bug fixes.
- PR #5207: Children fire event
- PR #5215: Dashboard «Running» Tab
- PR #5240: Remove unused `IPython.nbconvert.utils.console` module
- PR #5239: Fix exclusion of tests directories from coverage reports
- PR #5203: capture some logging/warning output in some tests
- PR #5216: fixup positional arg handling in notebook app
- PR #5229: get `_ipython_display_` method safely
- PR #5234: DOC : modified docs is `HasTraits.traits` and `HasTraits.class_traits`
- PR #5221: Change widget children List to Tuple.
- PR #5231: don't forget `base_url` when updating address bar in rename
- PR #5173: Moved widget files into `static/widgets/`*
- PR #5222: Unset `PYTHONWARNINGS` envvar before running subprocess tests.
- PR #5172: Prevent page breaks when printing notebooks via print-view.
- PR #4985: Add automatic `Closebrackets` function to `Codemirror`.
- PR #5220: Make traitlets notify check more robust against classes redefining equality and bool
- PR #5197: If there is an error comparing traitlet values when setting a trait, default to go ahead and notify of the new value.
- PR #5210: fix `pyreadline` import in `rlineimpl`
- PR #5212: Wrap `nbconvert` Markdown/Heading cells in live divs

- PR #5200: Allow to pass option to jinja env
- PR #5202: handle nodejs executable on debian
- PR #5112: band-aid for completion
- PR #5187: handle missing output metadata in nbconvert
- PR #5181: use gnureadline on OS X
- PR #5136: set default value from signature defaults in interact
- PR #5132: remove application/pdf->pdf transform in javascript
- PR #5116: reorganize who knows what about paths
- PR #5165: Don't introspect `__call__` for simple callables
- PR #5170: Added `msg_throttle sync=True` widget traitlet
- PR #5191: Translate markdown link to rst
- PR #5037: FF Fix: alignment and scale of text widget
- PR #5179: remove websocket url
- PR #5110: add `InlineBackend.print_figure_kwargs`
- PR #5147: Some template URL changes
- PR #5100: remove `base_kernel_url`
- PR #5163: Simplify implementation of `TemporaryWorkingDirectory`.
- PR #5166: remove `mktemp` usage
- PR #5133: don't use `combine` option on `ucs` package
- PR #5089: Remove legacy `azure nbmanager`
- PR #5159: remove `append_json` reference
- PR #5095: handle image size metadata in nbconvert html
- PR #5156: fix IPython typo, closes #5155
- PR #5150: fix a link that was broken
- PR #5114: use non-breaking space for button with no description
- PR #4778: add APIs for installing notebook extensions
- PR #5125: Fix the display of functions with keyword-only arguments on Python 3.
- PR #5097: minor notebook logging changes
- PR #5047: only validate `package_data` when it might be used
- PR #5121: fix remove event in `KeyboardManager.register_events`
- PR #5119: Removed „list“ view from Variable Inspector example
- PR #4925: Notebook manager api fixes
- PR #4996: require `print_method` to be a bound method
- PR #5108: require specifying the version for gh-pages
- PR #5111: Minor typo in docstring of `IPython.parallel DirectView`
- PR #5098: mostly debugging changes for `IPython.parallel`

- PR #5087: trust cells with no output
- PR #5059: Fix incorrect `Patch` logic in widget code
- PR #5075: More flexible box model fixes
- PR #5091: Provide logging messages in ipcluster log when engine or controllers fail to start
- PR #5090: Print a warning when `iptest` is run from the IPython source directory
- PR #5077: flush replies when entering an eventloop
- PR #5055: Minimal changes to import IPython from IronPython
- PR #5078: Updating JS tests README.md
- PR #5083: don't create js test directories unless they are being used
- PR #5062: adjust some events in `nb_roundtrip`
- PR #5043: various unicode / url fixes
- PR #5066: remove (almost) all mentions of `pylab` from our examples
- PR #4977: ensure scp destination directories exist (with `mkdir -p`)
- PR #5053: Move&rename JS tests
- PR #5067: show traceback in widget handlers
- PR #4920: Adding `PDFFormatter` and kernel side handling of PDF display data
- PR #5048: Add edit/command mode indicator
- PR #5061: make execute button in menu bar match shift-enter
- PR #5052: Add `q` to toggle the pager.
- PR #5070: fix flex: auto
- PR #5065: Add example of using annotations in interact
- PR #5063: another pass on Interact example notebooks
- PR #5051: FF Fix: code cell missing hscroll (2)
- PR #4960: Interact/Interactive for widget
- PR #5045: Clear timeout in multi-press keyboard shortcuts.
- PR #5060: Change „bind“ to „link“
- PR #5039: Expose `kernel_info` method on inprocess kernel client
- PR #5058: Fix `iopubwatcher.py` example script.
- PR #5035: FF Fix: code cell missing hscroll
- PR #5040: Polishing some docs
- PR #5001: Add directory navigation to dashboard
- PR #5042: Remove duplicated Channel ABC classes.
- PR #5036: FF Fix: ext link icon same line as link text in help menu
- PR #4975: `setup.py` changes for 2.0
- PR #4774: emit event on appended element on dom
- PR #5023: Widgets- add ability to pack and unpack arrays on JS side.

- PR #5003: Fix pretty reprs of `super()` objects
- PR #4974: make paste focus the pasted cell
- PR #5012: Make `SelectionWidget.values` a dict
- PR #5018: Prevent „iptest IPython“ from trying to run.
- PR #5025: citation2latex filter (using HTMLParser)
- PR #5027: pin lessc to 1.4
- PR #4952: Widget test inconsistencies
- PR #5014: Fix command mode & popup view bug
- PR #4842: more subtle kernel indicator
- PR #5017: Add notebook examples link to help menu.
- PR #5015: don't write `cell.trusted` to disk
- PR #5007: Update whatsnew doc from PR files
- PR #5010: Fixes for widget alignment in FF
- PR #4901: Add a convenience class to sync traitlet attributes
- PR #5008: updated explanation of „pyin“ messages
- PR #5004: Fix widget vslider spacing
- PR #4933: Small Widget inconsistency fixes
- PR #4979: add versioning notes to small message spec changes
- PR #4893: add font-awesome 3.2.1
- PR #4982: Live readout for slider widgets
- PR #4813: make help menu a template
- PR #4939: Embed qtconsole docs (continued)
- PR #4964: remove shift-= merge keyboard shortcut
- PR #4504: Allow input transformers to raise `SyntaxError`
- PR #4929: Fixing various modal/focus related bugs
- PR #4971: Fixing issues with js tests
- PR #4972: Work around problem in doctest discovery in Python 3.4 with PyQt
- PR #4937: pickle arrays with `dtype=object`
- PR #4934: `ipython profile create` respects `--ipython-dir`
- PR #4954: generate unicode filename
- PR #4845: Add Origin Checking.
- PR #4916: Fine tuning the behavior of the modal UI
- PR #4966: Ignore `sys.argv` for `NotebookNotary` in tests
- PR #4967: Fix typo in warning about web socket being closed
- PR #4965: Remove mention of `iplogger` from `setup.py`
- PR #4962: Fixed typos in quick-help text

- PR #4953: add `utils.wait_for_idle` in js tests
- PR #4870: `ipython_directive`, report `except/warn` in block and add `:okexcept:` `:okwarning:` options to suppress
- PR #4662: Menu cleanup
- PR #4824: sign notebooks
- PR #4943: Docs shotgun 4
- PR #4848: avoid import of nearby temporary with `%edit`
- PR #4950: Two fixes for file upload related bugs
- PR #4927: there shouldn't be a „files/“ prefix in `FileLink[s]`
- PR #4928: use `importlib.machinery` when available
- PR #4949: Remove the `docsrape` modules, which are part of `numpydoc`
- PR #4849: Various unicode fixes (mostly on Windows)
- PR #4932: always point `py3compat.input` to `builtin_mod.input`
- PR #4807: Correct handling of ansi colour codes when `nbconverting` to latex
- PR #4922: Python `nbconvert` output shouldn't have output
- PR #4912: Skip some Windows io failures
- PR #4919: flush output before showing tracebacks
- PR #4915: `ZMQCompleter` inherits from `IPCompleter`
- PR #4890: better cleanup channel FDs
- PR #4880: set profile name from `profile_dir`
- PR #4853: fix setting image height/width from metadata
- PR #4786: Reduce spacing of heading cells
- PR #4680: Minimal `pandoc` version warning
- PR #4908: detect builtin docstrings in `inspect`
- PR #4911: Don't use `python -m package` on Windows Python 2
- PR #4909: sort dictionary keys before comparison, ordering is not guaranteed
- PR #4374: IPEP 23: Backbone.js Widgets
- PR #4903: use https for all embeds
- PR #4894: Shortcut changes
- PR #4897: More detailed documentation about `kernel_cmd`
- PR #4891: Squash a few Sphinx warnings from `nbconvert.utils.lexers` docstrings
- PR #4679: JPG compression for inline pylab
- PR #4708: Fix indent and center
- PR #4789: fix `IPython.embed`
- PR #4655: prefer `marked` to `pandoc` for `markdown2html`
- PR #4876: don't show tooltip if object is not found

- PR #4873: use „combine“ option to ucs package
- PR #4732: Accents in notebook names and in command-line (nbconvert)
- PR #4867: Update URL for Lawrence Hall of Science webcam image
- PR #4868: Static path fixes
- PR #4858: fix tb_offset when running a file
- PR #4826: some \$.html(-> \$.text(
- PR #4847: add js kernel_info request
- PR #4832: allow NotImplementedError in formatters
- PR #4803: BUG: fix cython magic support in ipython_directive
- PR #4865: build listed twice in .gitignore. Removing one.
- PR #4851: fix tooltip token regex for single-character names
- PR #4846: Remove some leftover traces of irunner
- PR #4820: fix regex for cleaning old logs with ipcluster
- PR #4844: adjustments to notebook app logging
- PR #4840: Error in Session.send_raw()
- PR #4819: update CodeMirror to 3.21
- PR #4823: Minor fixes for typos/inconsistencies in parallel docs
- PR #4811: document code mirror tab and shift-tab
- PR #4795: merge reveal templates
- PR #4796: update components
- PR #4806: Correct order of packages for unicode in nbconvert to LaTeX
- PR #4800: Qt frontend: Handle „aborted“ prompt replies.
- PR #4794: Compatibility fix for Python3 (Issue #4783)
- PR #4799: minor js test fix
- PR #4788: warn when notebook is started in pylab mode
- PR #4772: Notebook server info files
- PR #4797: be conservative about kernel_info implementation
- PR #4787: non-python kernels run python code with qtconsole
- PR #4565: various display type validations
- PR #4703: Math macro in jinja templates.
- PR #4781: Fix «Source» text for the «Other Syntax» section of the «Typesetting Math» notebook
- PR #4776: Manually document py3compat module.
- PR #4533: propagate display metadata to all mimetypes
- PR #4785: Replacing a for-in loop by an index loop on an array
- PR #4780: Updating CSS for UI example.
- PR #3605: Modal UI

- PR #4758: Python 3.4 fixes
- PR #4735: add some HTML error pages
- PR #4775: Update whatsnew doc from PR files
- PR #4760: Make examples and docs more Python 3 aware
- PR #4773: Don't wait forever for notebook server to launch/die for tests
- PR #4768: Qt console: Fix `_prompt_pos` accounting on timer flush output.
- PR #4727: Remove Nbconvert template loading magic
- PR #4763: Set numpdoc options to produce fewer Sphinx warnings.
- PR #4770: always define aliases, even if empty
- PR #4766: add `python -m` entry points for everything
- PR #4767: remove manpages for `irunner`, `iplogger`
- PR #4751: Added `-post-serve` explanation into the `nbconvert` docs.
- PR #4762: whitelist alphanumeric characters for `cookie_name`
- PR #4625: Deprecate `%profile` magic
- PR #4745: warn on failed formatter calls
- PR #4746: remove redundant `cls` alias on Windows
- PR #4749: Fix bug in determination of public ips.
- PR #4715: restore use of `tornado static_url` in templates
- PR #4748: fix race condition in `profiledir` creation.
- PR #4720: never use `ssh multiplexer` in tunnels
- PR #4658: Bug fix for #4643: `Regex` object needs to be reset between calls in `toolt...`
- PR #4561: Add `Formatter.pop(type)`
- PR #4712: Docs shotgun 3
- PR #4713: Fix saving kernel history in Python 2
- PR #4744: don't use lazily-evaluated `rc.ids` in `wait_for_idle`
- PR #4740: `%env` can't set variables
- PR #4737: check every link when detecting `virtualenv`
- PR #4738: don't inject help into `user_ns`
- PR #4739: skip html `nbconvert` tests when their dependencies are missing
- PR #4730: Fix stripping continuation prompts when copying from Qt console
- PR #4725: Doc fixes
- PR #4656: Nbconvert HTTP service
- PR #4710: make `@interactive` decorator friendlier with `dill`
- PR #4722: allow purging local results as long as they are not outstanding
- PR #4549: Updated IPython console lexers.
- PR #4570: Update IPython directive

- PR #4719: Fix comment typo in prefilter.py
- PR #4575: make sure to encode URL components for API requests
- PR #4718: Fixed typo in displaypub
- PR #4716: Remove input_prefilter hook
- PR #4691: survive failure to bind to localhost in zmq.iostream
- PR #4696: don't do anything if add_anchor fails
- PR #4711: some typos in the docs
- PR #4700: use if main block in entry points
- PR #4692: setup.py symlink improvements
- PR #4265: JSON configuration file
- PR #4505: Nbconvert latex markdown images2
- PR #4608: transparent background match ... all colors
- PR #4678: allow ipython console to handle text/plain display
- PR #4706: remove irunner, iplogger
- PR #4701: Delete an old dictionary available for selecting the alignment of text.
- PR #4702: Making reveal font-size a relative unit.
- PR #4649: added a quiet option to %cpaste to suppress output
- PR #4690: Option to spew subprocess streams during tests
- PR #4688: Fixed various typos in docstrings.
- PR #4645: CasperJs utility functions.
- PR #4670: Stop bundling the numpydoc Sphinx extension
- PR #4675: common IPython prefix for ModIndex
- PR #4672: Remove unused „attic“ module
- PR #4671: Fix docstrings in utils.text
- PR #4669: add missing help strings to HistoryManager configurables
- PR #4668: Make non-ASCII docstring unicode
- PR #4650: added a note about sharing of nbconvert templates
- PR #4646: Fixing various output related things:
- PR #4665: check for libedit in readline on OS X
- PR #4606: Make running PYTHONSTARTUP optional
- PR #4654: Fixing left padding of text cells to match that of code cells.
- PR #4306: add raw_mimetype metadata to raw cells
- PR #4576: Tighten up the vertical spacing on cells and make the padding of cells more consistent
- PR #4353: Don't reset the readline completer after each prompt
- PR #4567: Adding prompt area to non-CodeCells to indent content.
- PR #4446: Use SVG plots in OctaveMagic by default due to lack of Ghostscript on Windows Octave

- PR #4613: remove configurable.created
- PR #4631: Use argument lists for command help tests
- PR #4633: Modifies test_get_long_path_name_winx32() to allow for long path names in temp dir
- PR #4642: Allow docs to build without PyQt installed.
- PR #4641: Don't check for wx in the test suite.
- PR #4622: make QtConsole Lexer configurable
- PR #4594: Fixed #2923 Move Save Away from Cut in toolbar
- PR #4593: don't interfere with set_next_input contents in qtconsole
- PR #4640: Support matplotlib's Gtk3 backend in -pylab mode
- PR #4639: Minor import fix to get qtconsole with -pylab=qt working
- PR #4637: Fixed typo in links.txt.
- PR #4634: Fix nrun in notebooks with non-code cells.
- PR #4632: Restore the ability to run tests from a function.
- PR #4624: Fix crash when \$EDITOR is non-ASCII
- PR #4453: Play nice with App Nap
- PR #4541: relax ipconfig matching on Windows
- PR #4552: add pickleutil.use_dill
- PR #4590: Font awesome for IPython slides
- PR #4589: Inherit the width of pre code inside the input code cells.
- PR #4588: Update reveal.js CDN to 2.5.0.
- PR #4569: store cell toolbar preset in notebook metadata
- PR #4609: Fix bytes regex for Python 3.
- PR #4581: Writing unicode to stdout
- PR #4591: Documenting codemirror shortcuts.
- PR #4607: Tutorial doc should link to user config intro
- PR #4601: test that rename fails with 409 if it would clobber
- PR #4599: re-cast int/float subclasses to int/float in json_clean
- PR #4542: new `ipython history clear` subcommand
- PR #4568: don't use lazily-evaluated rc.ids in wait_for_idle
- PR #4572: DOC: %profile docstring should reference %prun
- PR #4571: no longer need 3 suffix on travis, tox
- PR #4566: Fixing cell_type in CodeCell constructor.
- PR #4563: Specify encoding for reading notebook file.
- PR #4452: support notebooks in %run
- PR #4546: fix warning condition on notebook startup
- PR #4540: Apidocs3

- PR #4553: Fix Python 3 handling of urllib
- PR #4543: make hiding of initial namespace optional
- PR #4517: send shutdown_request on exit of `ipython console`
- PR #4528: improvements to bash completion
- PR #4532: Hide dynamically defined metaclass base from Sphinx.
- PR #4515: Spring Cleaning, and Load speedup
- PR #4529: note routing identities needed for input requests
- PR #4514: allow restart in `%run -d`
- PR #4527: add redirect for 1.0-style „files/“ prefix links
- PR #4526: Allow unicode arguments to `passwd_check` on Python 2
- PR #4403: Global highlight language selection.
- PR #4250: `outputarea.js`: Wrap inline SVGs inside an `iframe`
- PR #4521: Read wav files in binary mode
- PR #4444: Css cleaning
- PR #4523: Use username and password for MongoDB on ShiningPanda
- PR #4510: Update `whatsnew` from PR files
- PR #4441: add `setup.py jsversion`
- PR #4518: Fix for race condition in url file decoding.
- PR #4497: don't automatically unpack datetime objects in the message spec
- PR #4506: wait for empty queues as well as load-balanced tasks
- PR #4492: Configuration docs refresh
- PR #4508: Fix some uses of `map()` in Qt console completion code.
- PR #4498: Daemon StreamCapturer
- PR #4499: Skip clipboard test on unix systems if headless.
- PR #4460: Better clipboard handling, esp. with `pywin32`
- PR #4496: Pass `nbformat` object to write call to save `.py` script
- PR #4466: various pandoc latex fixes
- PR #4473: Setup for Python 2/3
- PR #4459: protect against broken repr in `lib.pretty`
- PR #4457: Use `~/.ipython` as default config directory
- PR #4489: check realpath of env in `init_virtualenv`
- PR #4490: fix possible race condition in `test_await_data`
- PR #4476: Fix: Remove space added by `display(JavaScript)` on page reload
- PR #4398: [Notebook] Deactivate tooltip on tab by default.
- PR #4480: Docs shotgun 2
- PR #4488: fix typo in message spec doc

- PR #4479: yet another JS race condition fix
- PR #4477: Allow incremental builds of the `html_noapi` docs target
- PR #4470: Various Config object cleanups
- PR #4410: make close-and-halt work on new tabs in Chrome
- PR #4469: Python 3 & `getcwd`
- PR #4451: fix: allow JS test to run after shutdown test
- PR #4456: Simplify StreamCapturer for subprocess testing
- PR #4464: Correct description for Bytes traitlet type
- PR #4465: Clean up MANIFEST.in
- PR #4461: Correct TypeError message in `svg2pdf`
- PR #4458: use `signalstatus` if `exit` status is undefined
- PR #4438: Single codebase Python 3 support (again)
- PR #4198: Version conversion, support for X to Y even if $Y < X$ (`nbformat`)
- PR #4415: More tooltips in the Notebook menu
- PR #4450: remove monkey patch for older versions of tornado
- PR #4423: Fix progress bar and scrolling bug.
- PR #4435: raise 404 on not found static file
- PR #4442: fix and add shim for change introduced by #4195
- PR #4436: allow `require("nbextensions/extension")` to load from `IPYTHONDIR/nbextensions`
- PR #4437: don't compute etags in static file handlers
- PR #4427: notebooks should always have one checkpoint
- PR #4425: fix js pythonisme
- PR #4195: IPEP 21: widget messages
- PR #4434: Fix broken link for Dive Into Python.
- PR #4428: bump minimum tornado version to 3.1.0
- PR #4302: Add an Audio display class
- PR #4285: Notebook javascript test suite using CasperJS
- PR #4420: Allow checking for backports via milestone
- PR #4426: set kernel cwd to notebook's directory
- PR #4389: By default, Magics inherit from Configurable
- PR #4393: Capture output from subprocesses during test, and display on failure
- PR #4419: define `InlineBackend` configurable in its own file
- PR #4303: Multidirectory support for the Notebook
- PR #4371: Restored ipython profile locate dir and fixed typo. (Fixes #3708).
- PR #4414: Specify unicode type properly in `rmagic`
- PR #4413: don't instantiate IPython shell as class attr

- PR #4400: Remove 5s wait on inactivity on GUI inputhook loops
- PR #4412: Fix traitlet `_notify_trait` by-ref issue
- PR #4378: split adds new cell above, rather than below
- PR #4405: Bring display of builtin types and functions in line with Py 2
- PR #4367: clean up of documentation files
- PR #4401: Provide a name of the HistorySavingThread
- PR #4384: fix menubar height measurement
- PR #4377: fix tooltip cancel
- PR #4293: Factorise code in tooltip for julia monkeypatching
- PR #4292: improve js-completer logic.
- PR #4363: `set_next_input`: keep only last input when repeatedly called in a single cell
- PR #4382: Use `safe_hasattr` in `dir2`
- PR #4379: fix (CTRL-M -) shortcut for splitting cell in FF
- PR #4380: Test and fixes for localinterfaces
- PR #4372: Don't assume that SyntaxTB is always called with a SyntaxError
- PR #4342: Return value directly from the try block and avoid a variable
- PR #4154: Center LaTeX and figures in markdown
- PR #4311: `%load -s` to load specific functions or classes
- PR #4350: WinHPC launcher fixes
- PR #4345: Make irunner compatible with upcoming pexpect 3.0 interface
- PR #4276: Support container methods in config
- PR #4359: `test_pylabtools` also needs to modify `matplotlib.rcParamsOrig`
- PR #4355: remove hardcoded box-orient
- PR #4333: Add Edit Notebook Metadata to Edit menu
- PR #4349: Script to update What's New file
- PR #4348: Call PDF viewer after latex compiling (nbconvert)
- PR #4346: `getpass()` on Windows & Python 2 needs bytes prompt
- PR #4304: use `netifaces` for faster `IPython.utils.localinterfaces`
- PR #4305: Add even more ways to populate localinterfaces
- PR #4313: remove `strip_math_space`
- PR #4325: Some changes to improve readability.
- PR #4281: Adjust tab completion widget if too close to bottom of page.
- PR #4347: Remove `pycolor` script
- PR #4322: Scroll to the top after change of slides in the IPython slides
- PR #4289: Fix scrolling output (not working post `clear_output` changes)
- PR #4343: Make parameters for kernel start method more general

- PR #4237: Keywords should shadow magic functions
- PR #4338: adjust default value of level in sync_imports
- PR #4328: Remove unused loop variable.
- PR #4340: fix mathjax download url to new GitHub format
- PR #4336: use simple replacement rather than string formatting in format_kernel_cmd
- PR #4264: catch unicode error listing profiles
- PR #4314: catch EACCES when binding notebook app
- PR #4324: Remove commented addthis toolbar
- PR #4327: Use the with statement to open a file.
- PR #4318: fix initial sys.path
- PR #4315: Explicitly state what version of Pandoc is supported in docs/install
- PR #4316: underscore missing on notebook_p4
- PR #4295: Implement boundary option for load magic (#1093)
- PR #4300: traits defaults are strings not object
- PR #4297: Remove an unreachable return statement.
- PR #4260: Use subprocess for system_raw
- PR #4277: add nbextensions
- PR #4294: don't require tornado 3 in --post serve
- PR #4270: adjust Scheduler timeout logic
- PR #4278: add -a to easy_install command in libedit warning
- PR #4282: Enable automatic line breaks in MathJax.
- PR #4279: Fixing line-height of list items in tree view.
- PR #4253: fixes #4039.
- PR #4131: Add module's name argument in %%cython magic
- PR #4269: Add mathletters option and longtable package to latex_base.tplx
- PR #4230: Switch correctly to the user's default matplotlib backend after inline.
- PR #4271: Hopefully fix ordering of output on ShiningPanda
- PR #4239: more informative error message for bad serialization
- PR #4263: Fix excludes for IPython.testing
- PR #4112: nbconvert: Latex template refactor
- PR #4261: Fixing a formatting error in the custom display example notebook.
- PR #4259: Fix Windows test exclusions
- PR #4229: Clear_output: Animation & widget related changes.
- PR #4151: Refactor alias machinery
- PR #4153: make timeit return an object that contains values
- PR #4258: to-backport label is now 1.2

- PR #4242: Allow passing extra arguments to ipctest through for nose
- PR #4257: fix unicode argv parsing
- PR #4166: avoid executing code in utils.localinterfaces at import time
- PR #4214: engine ID metadata should be unicode, not bytes
- PR #4232: no highlight if no language specified
- PR #4218: Fix display of SyntaxError when .py file is modified
- PR #4207: add `setup.py css` command
- PR #4224: clear previous callbacks on execute
- PR #4180: Iptest refactoring
- PR #4105: JS output area misaligned
- PR #4220: Various improvements to docs formatting
- PR #4187: Select adequate highlighter for cell magic languages
- PR #4228: update -dev docs to reflect latest stable version
- PR #4219: Drop bundled argparse
- PR #3851: Adds an explicit newline for pretty-printing.
- PR #3622: Drop fakemodule
- PR #4080: change default behavior of database task storage
- PR #4197: enable cython highlight in notebook
- PR #4225: Updated docstring for `core.display.Image`
- PR #4175: nbconvert: Jinjaless exporter base
- PR #4208: Added a lightweight «htmlcore» Makefile entry
- PR #4209: Magic doc fixes
- PR #4217: avoid importing numpy at the module level
- PR #4213: fixed dead link in examples/notebooks readme to Part 3
- PR #4183: ESC should be handled by CM if tooltip is not on
- PR #4193: Update for #3549: Append Firefox overflow-x fix
- PR #4205: use TextIOWrapper when communicating with pandoc subprocess
- PR #4204: remove some extraneous print statements from `IPython.parallel`
- PR #4201: HeadingCells cannot be split or merged
- PR #4048: finish up speaker-notes PR
- PR #4079: trigger `Kernel.status_started` after websockets open
- PR #4186: moved DummyMod to proper namespace to enable dill pickling
- PR #4190: update version-check message in `setup.py` and `IPython.__init__`
- PR #4188: Allow `user_ns` trait to be None
- PR #4189: always fire `LOCAL_IPS.extend(PUBLIC_IPS)`
- PR #4174: various issues in markdown and rst templates

- PR #4178: add missing `data_javascript`
- PR #4168: Py3 failing tests
- PR #4181: nbconvert: Fix, sphinx template not removing new lines from headers
- PR #4043: don't „restore_bytes“ in `from_JSON`
- PR #4149: reuse more kernels in kernel tests
- PR #4163: Fix for incorrect default encoding on Windows.
- PR #4136: catch javascript errors in any output
- PR #4171: add nbconvert config file when creating profiles
- PR #4172: add ability to check what PRs should be backported in `backport_pr`
- PR #4167: `-fast` flag for test suite!
- PR #4125: Basic exercise of `ipython [subcommand] -h` and `help-all`
- PR #4085: nbconvert: Fix sphinx preprocessor date format string for Windows
- PR #4159: don't split `.cell` and `div.cell` CSS
- PR #4165: Remove use of parametric tests
- PR #4158: generate choices for `--gui` configurable from real mapping
- PR #4083: Implement a better check for hidden values for `%who` etc.
- PR #4147: Reference notebook examples, fixes #4146.
- PR #4065: do not include specific css in embedable one
- PR #4092: nbconvert: Fix for unicode html headers, Windows + Python 2.x
- PR #4074: close Client sockets if connection fails
- PR #4064: Store default codemirror mode in only 1 place
- PR #4104: Add way to install MathJax to a particular profile
- PR #4161: Select name when renaming a notebook
- PR #4160: Add quotes around `«. [notebook] »` in readme
- PR #4144: `help_end` transformer shouldn't pick up `?` in multiline string
- PR #4090: Add LaTeX citation handling to nbconvert
- PR #4143: update example `custom.js`
- PR #4142: DOC: unwrap openssl line in `public_server` doc
- PR #4126: update `tox.ini`
- PR #4141: add files with a separate `add` call in `backport_pr`
- PR #4137: Restore `autorestore` option for `storemagic`
- PR #4098: pass `profile-dir` instead of profile name to Kernel
- PR #4120: support `input` in Python 2 kernels
- PR #4088: nbconvert: Fix `coalescestreams` line with incorrect nesting causing strange behavior
- PR #4060: only strip continuation prompts if regular prompts seen first
- PR #4132: Fixed name error bug in function `safe_unicode` in module `py3compat`.

- PR #4121: move `test_kernel` from `IPython.zmq` to `IPython.kernel`
- PR #4118: ZMQ heartbeat channel: catch `EINTR` exceptions and continue.
- PR #4070: New changes should go into `pr/` folder
- PR #4054: use unicode for HTML export
- PR #4106: fix a couple of default block values
- PR #4107: update parallel magic tests with `capture_output` API
- PR #4102: Fix clashes between debugger tests and `coverage.py`
- PR #4115: Update docs on declaring a magic function
- PR #4101: restore accidentally removed `EngineError`
- PR #4096: minor docs changes
- PR #4094: Update target branch before backporting PR
- PR #4069: Drop monkeypatch for pre-1.0 nose
- PR #4056: respect `pylab_import_all` when `--pylab` specified at the command-line
- PR #4091: Make Qt console banner configurable
- PR #4086: fix missing `errno` import
- PR #4084: Use `msvcrt.getwch()` for Windows pager.
- PR #4073: rename `post_processors` submodule to `postprocessors`
- PR #4075: Update supported Python versions in `tools/test_pr`
- PR #4068: minor bug fix, define „cell“ in `dialog.js`.
- PR #4044: rename call methods to `transform` and `postprocess`
- PR #3744: capture rich output as well as `stdout/err` in `capture_output`
- PR #3969: «use strict» in most (if not all) our javascript
- PR #4030: exclude `.git` in `MANIFEST.in`
- PR #4047: Use `istype()` when checking if canned object is a dict
- PR #4031: don't close `_fds` on Windows
- PR #4029: `bson.Binary` moved
- PR #3883: skip test on unix when `x11` not available
- PR #3863: Added working speaker notes for slides.
- PR #4035: Fixed custom jinja2 templates being ignored when setting `template_path`
- PR #4002: Drop Python 2.6 and 3.2
- PR #4026: small doc fix in `nbconvert`
- PR #4016: Fix `IPython.start_*` functions
- PR #4021: Fix `parallel.client.View.map()` on numpy arrays
- PR #4022: DOC: fix links to matplotlib, notebook docs
- PR #4018: Fix warning when running `IPython.kernel` tests
- PR #4017: Add REPL-like printing of final/return value to `%%R` cell magic

- PR #4019: Test skipping without unicode paths
- PR #4008: Transform code before %prun/%prun runs
- PR #4014: Fix typo in ipapp
- PR #3997: DOC: typos + rewording in examples/notebooks/Cell Magics.ipynb
- PR #3914: nbconvert: Transformer tests
- PR #3987: get files list in backport_pr
- PR #3923: nbconvert: Writer tests
- PR #3974: nbconvert: Fix app tests on Window7 w/ Python 3.3
- PR #3937: make tab visible in codemirror and light red background
- PR #3933: nbconvert: Post-processor tests
- PR #3978: fix `--existing` with non-localhost IP
- PR #3939: minor checkpoint cleanup
- PR #3955: complete on % for magic in notebook
- PR #3981: BF: fix nbconvert rst input prompt spacing
- PR #3960: Don't make sphinx a dependency for importing nbconvert
- PR #3973: logging.Formatter is not new-style in 2.6

Issues (434):

- #5476: For 2.0: Fix links in Notebook Help Menu
- #5337: Examples reorganization
- #5436: CodeMirror shortcuts in QuickHelp
- #5444: Fix numeric verification for Int and Float text widgets.
- #5443: Int and Float Widgets don't allow negative signs
- #5449: Stretch keyboard shortcut dialog
- #5471: Add coding magic comment to nbconvert Python template
- #5470: UTF-8 Issue When Converting Notebook to a Script.
- #5369: FormatterWarning for SVG matplotlib output in notebook
- #5460: Can't start the notebook server specifying a notebook
- #2918: CodeMirror related issues.
- #5431: update github_stats and gh_api for 2.0
- #4887: Add tests for modal UI
- #5290: Add dual mode JS tests
- #5448: Cmd+/ shortcut doesn't work in IPython master
- #5447: Add %%python2 cell magic
- #5442: Make a «python2» alias or rename the «python» cell magic.
- #2495: non-ascii characters in the path
- #4554: dictDB: Exception due to str to datetime comparison

- #5006: Comm code is not run in the same context as notebook code
- #5118: Weird interact behavior
- #5401: Empty code cells in nbconvert rst output cause problems
- #5434: fix check for empty cells in rst template
- #4944: Trouble finding ipynb path in Windows 8
- #4605: Change the url of Editor Shortcuts in the notebook menu.
- #5425: Update COPYING.txt
- #5348: BUG: HistoryAccessor.get_session_info(0) - exception
- #5293: Javascript(«element.append()») looks broken.
- #5363: Disable saving if notebook has stopped loading
- #5189: Tooltip pager mode is broken
- #5330: Updates to shell reference doc
- #5397: Accordion widget broken
- #5106: Flexbox CSS specificity bugs
- #5297: tooltip triggers focus bug
- #5417: scp checking for existence of directories: directory names are incorrect
- #5302: Parallel engine registration fails for slow engines
- #5334: notebook's split-cell shortcut dangerous / incompatible with Neo layout (for instance)
- #5324: Style of `raw_input` UI is off in notebook
- #5350: Converting notebooks with spaces in their names to RST gives broken images
- #5049: update quickhelp on adding and removing shortcuts
- #4941: Eliminating display of intermediate stages in progress bars
- #5345: nbconvert to markdown does not use backticks
- #5357: catch exception in copystat
- #5351: Notebook saving fails on smb share
- #4946: TeX produced cannot be converted to PDF
- #5347: pretty print list too slow
- #5238: Raw cell placeholder is not removed when you edit the cell
- #5382: Qtconsole doesn't run in Python 3
- #5378: Unexpected and new conflict between PyFileConfigLoader and IPythonQtConsoleApp
- #4945: Heading/cells positioning problem and cell output wrapping
- #5084: Consistent approach for HTML/JS output on nbviewer
- #4902: print preview does not work, custom.css not found
- #5336: TypeError in bootstrap-tour.min.js
- #5303: Changed Hub.registration_timeout to be a config input.
- #995: Paste-able mode in terminal

- #5305: Tuple unpacking for shell escape
- #5232: Make nbconvert html full output like notebook's html.
- #5224: Audit nbconvert HTML output
- #5253: display any output from this session in terminal console
- #5251: ipython console ignoring some stream messages?
- #4802: Tour of the notebook UI (was UI elements inline with highlighting)
- #5103: Moving Constructor definition to the top like a Function definition
- #5264: Test failures on master with Anaconda
- #4833: Serve /usr/share/javascript at /_sysassets/javascript/ in notebook
- #5071: Prevent %pylab from clobbering interactive
- #5282: Exception in widget `__del__` methods in Python 3.4.
- #5280: append Firefox overflow-x fix
- #5120: append Firefox overflow-x fix, again
- #4127: autoreload shouldn't rely on .pyc modification times
- #5272: allow highlighting language to be set from notebook metadata
- #5050: Notebook cells truncated with Firefox
- #4839: Error in `Session.send_raw()`
- #5188: New events system
- #5076: Refactor keyboard handling
- #4886: Refactor and consolidate different keyboard logic in JavaScript code
- #5002: the green cell border moving forever in Chrome, when there are many code cells.
- #5259: Codemirror still active in command mode
- #5219: Output images appear as small thumbnails (Notebook)
- #4829: Not able to connect qtconsole in Windows 8
- #5152: Hide `__pycache__` in dashboard directory list
- #5151: Case-insensitive sort for dashboard list
- #4603: Warn when overwriting a notebook with upload
- #4895: Improvements to %run completions
- #3459: Filename completion when run script with %run
- #5225: Add JavaScript to nbconvert HTML display priority
- #5034: Audit the places where we call `.html(something)`
- #5094: Dancing cells in notebook
- #4999: Notebook focus effects
- #5149: Clicking on a TextBoxWidget in FF completely breaks dual mode.
- #5207: Children fire event
- #5227: display_method of objects with custom `__getattr__`

- [#5236](#): Cursor keys do not work to leave Markdown cell while it's being edited
- [#5205](#): Use CTuple traitlet for Widget children
- [#5230](#): notebook rename does not respect url prefix
- [#5218](#): Test failures with Python 3 and enabled warnings
- [#5115](#): Page Breaks for Print Preview Broken by display: flex - Simple CSS Fix
- [#5024](#): Make nbconvert HTML output smart about page breaking
- [#4985](#): Add automatic Closebrackets function to Codemirror.
- [#5184](#): print „xa“ crashes the interactive shell
- [#5214](#): Downloading notebook as Python (.py) fails
- [#5211](#): AttributeError: „module“ object has no attribute „_outputfile“
- [#5206](#): [CSS?] Inconsistencies in nbconvert divs and IPython Notebook divs?
- [#5201](#): node != nodejs within Debian packages
- [#5112](#): band-aid for completion
- [#4860](#): Completer As-You-Type Broken
- [#5116](#): reorganize who knows what about paths
- [#4973](#): Adding security.js with 1st attempt at is_safe
- [#5164](#): test_oinspect.test_calltip_builtin failure with python3.4
- [#5127](#): Widgets: skip intermediate callbacks during throttling
- [#5013](#): Widget alignment differs between FF and Chrome
- [#5141](#): tornado error static file
- [#5160](#): TemporaryWorkingDirectory incompatible with python3.4
- [#5140](#): WIP: %kernels magic
- [#4987](#): Widget lifecycle problems
- [#5129](#): UCS package break latex export on non-ascii
- [#4986](#): Cell horizontal scrollbar is missing in FF but not in Chrome
- [#4685](#): nbconvert ignores image size metadata
- [#5155](#): Notebook logout button does not work (source typo)
- [#2678](#): Ctrl-m keyboard shortcut clash on Chrome OS
- [#5113](#): ButtonWidget without caption wrong height.
- [#4778](#): add APIs for installing notebook extensions
- [#5046](#): python setup.py failed vs git submodule update worked
- [#4925](#): Notebook manager api fixes
- [#5073](#): Cannot align widgets horizontally in the notebook
- [#4996](#): require print_method to be a bound method
- [#4990](#): _repr_html_ exception reporting corner case when using type(foo)
- [#5099](#): Notebook: Changing base_project_url results in failed WebSockets call

- #5096: Client.map is not fault tolerant
- #4997: Inconsistent %matplotlib qt behavior
- #5041: Remove more .html(...) calls.
- #5078: Updating JS tests README.md
- #4977: ensure scp destination directories exist (with mkdir -p)
- #3411: ipython parallel: scp failure.
- #5064: Errors during interact display at the terminal, not anywhere in the notebook
- #4921: Add PDF formatter and handling
- #4920: Adding PDFFormatter and kernel side handling of PDF display data
- #5048: Add edit/command mode indicator
- #4889: Add UI element for indicating command/edit modes
- #5052: Add q to toggle the pager.
- #5000: Closing pager with keyboard in modal UI
- #5069: Box model changes broke the Keyboard Shortcuts help modal
- #4960: Interact/Interactive for widget
- #4883: Implement interact/interactive for widgets
- #5038: Fix multiple press keyboard events
- #5054: UnicodeDecodeError: „ascii“ codec can't decode byte 0xc6 in position 1: ordinal not in range(128)
- #5031: Bug during integration of IPython console in Qt application
- #5057: iopubwatcher.py example is broken.
- #4747: Add event for output_area adding an output
- #5001: Add directory navigation to dashboard
- #5016: Help menu external-link icons break layout in FF
- #4885: Modal UI behavior changes
- #5009: notebook signatures don't work
- #4975: setup.py changes for 2.0
- #4774: emit event on appended element on dom
- #5020: Python Lists translated to javascript objects in widgets
- #5003: Fix pretty reprs of super() objects
- #5012: Make SelectionWidget.values a dict
- #4961: Bug when constructing a selection widget with both values and labels
- #4283: A < in a markdown cell strips cell content when converting to latex
- #4006: iptest IPython broken
- #4251: & escaped to & in tex ?
- #5027: pin lessc to 1.4

- [#4323](#): Take 2: citation2latex filter (using HTMLParser)
- [#4196](#): Printing notebook from browser gives 1-page truncated output
- [#4842](#): more subtle kernel indicator
- [#4057](#): No path to notebook examples from Help menu
- [#5015](#): don't write cell.trusted to disk
- [#4617](#): Changed url link in Help dropdown menu.
- [#4976](#): Container widget layout broken on Firefox
- [#4981](#): Vertical slider layout broken
- [#4793](#): Message spec changes related to `clear_output`
- [#4982](#): Live readout for slider widgets
- [#4813](#): make help menu a template
- [#4989](#): Filename tab completion completely broken
- [#1380](#): Tab should insert 4 spaces in `#` comment lines
- [#2888](#): spaces vs tabs
- [#1193](#): Allow resizing figures in notebook
- [#4504](#): Allow input transformers to raise `SyntaxError`
- [#4697](#): Problems with height after toggling header and toolbar...
- [#4951](#): TextWidget to code cell command mode bug.
- [#4809](#): Arbitrary scrolling (jumping) in clicks in modal UI for notebook
- [#4971](#): Fixing issues with js tests
- [#4972](#): Work around problem in doctest discovery in Python 3.4 with PyQt
- [#4892](#): IPython.qt test failure with python3.4
- [#4863](#): BUG: cannot create an OBJECT array from memory buffer
- [#4704](#): Subcommand `profile` ignores `-ipython-dir`
- [#4845](#): Add Origin Checking.
- [#4870](#): `ipython_directive`, report `except/warn` in block and add `:okexcept:` `:okwarning:` options to suppress
- [#4956](#): Shift-Enter does not move to next cell
- [#4662](#): Menu cleanup
- [#4824](#): sign notebooks
- [#4848](#): avoid import of nearby temporary with `%edit`
- [#4731](#): `%edit` files mistakenly import modules in `/tmp`
- [#4950](#): Two fixes for file upload related bugs
- [#4871](#): Notebook upload fails after Delete
- [#4825](#): File Upload URL set incorrectly
- [#3867](#): `display.FileLinks` should work in the exported html verion of a notebook

- [#4948](#): reveal: ipython css overrides reveal themes
- [#4947](#): reveal: slides that are too big?
- [#4051](#): Test failures with Python 3 and enabled warnings
- [#3633](#): outstanding issues over in ipython/nbconvert repo
- [#4087](#): Sympy printing in the example notebook
- [#4627](#): Document various QtConsole embedding approaches.
- [#4849](#): Various unicode fixes (mostly on Windows)
- [#3653](#): autocompletion in «from package import <tab>»
- [#4583](#): overwrite? prompt gets EOFError in 2 process
- [#4807](#): Correct handling of ansi colour codes when nbconverting to latex
- [#4611](#): Document how to compile .less files in dev docs.
- [#4618](#): «Editor Shortcuts» link is broken in help menu dropdown notebook
- [#4522](#): DeprecationWarning: the sets module is deprecated
- [#4368](#): No symlink from ipython to ipython3 when inside a python3 virtualenv
- [#4234](#): Math without \$\$ doesn't show up when converted to slides
- [#4194](#): config.TerminalIPythonApp.nosep does not work
- [#1491](#): prefilter not called for multi-line notebook cells
- [#4001](#): Windows IPython executable /scripts/ipython not working
- [#3959](#): think more carefully about text wrapping in nbconvert
- [#4907](#): Test for traceback depth fails on Windows
- [#4906](#): Test for IPython.embed() fails on Windows
- [#4912](#): Skip some Windows io failures
- [#3700](#): stdout/stderr should be flushed printing exception output...
- [#1181](#): greedy completer bug in terminal console
- [#2032](#): check for a few places we should be using DEFAULT_ENCODING
- [#4882](#): Too many files open when starting and stopping kernel repeatedly
- [#4880](#): set profile name from profile_dir
- [#4238](#): parallel.Client() not using profile that notebook was run with?
- [#4853](#): fix setting image height/width from metadata
- [#4786](#): Reduce spacing of heading cells
- [#4680](#): Minimal pandoc version warning
- [#3707](#): nbconvert: Remove IPython magic commands from -format=>python> output
- [#4130](#): PDF figures as links from png or svg figures
- [#3919](#): Allow -profile to be passed a dir.
- [#2136](#): Handle hard newlines in pretty printer

- #4790: Notebook modal UI: «merge cell below» key binding, `shift+=`, does not work with some keyboard layouts
- #4884: Keyboard shortcut changes
- #1184: slow handling of keyboard input
- #4913: Mathjax, Markdown, `tex`, `env*` and `italic`
- #3972: nbconvert: Template output testing
- #4903: use `https` for all embeds
- #4874: `-debug` does not work if you set `.kernel_cmd`
- #4679: JPG compression for inline pylab
- #4708: Fix indent and center
- #4789: fix `IPython.embed`
- #4759: `Application._load_config_files` log parameter default fails
- #3153: docs / file menu: explain how to exit the notebook
- #4791: Did updates to `ipython_directive` bork support for cython magic snippets?
- #4385: «Part 4 - Markdown Cells.ipynb» nbviewer example seems not well referenced in current online documentation page <https://ipython.org/ipython-doc/stable/interactive/notebook.htm>
- #4655: prefer `marked` to `pandoc` for `markdown2html`
- #3441: Fix focus related problems in the notebook
- #3402: Feature Request: Save As (`latex`, `html`,...etc) as a menu option in Notebook rather than explicit need to invoke `nbconvert`
- #3224: Revisit layout of notebook area
- #2746: rerunning a cell with long output (exception) scrolls to much (html notebook)
- #2667: can't save opened notebook if accidentally delete the notebook in the dashboard
- #3026: Reporting errors from `__repr__` <type> __ methods
- #1844: Notebook does not exist and permalinks
- #2450: [closed PR] Prevent jumping of window to input when output is clicked.
- #3166: IPEP 16: Notebook multi directory dashboard and URL mapping
- #3691: Slight misalignment of Notebook menu bar with focus box
- #4875: Empty tooltip with `object_found = false` still being shown
- #4432: The SSL cert for the MathJax CDN is invalid and URL is not protocol agnostic
- #2633: Help text should leave current cell active
- #3976: DOC: Pandas link on the notebook help menu?
- #4082: `/new` handler redirect cached by browser
- #4298: Slow `ipython -pylab` and `ipython` notebook startup
- #4545: `%store` magic not working
- #4610: toolbar UI enhancements
- #4782: New modal UI

- [#4732](#): Accents in notebook names and in command-line (nbconvert)
- [#4752](#): link broken in docs/examples
- [#4835](#): running ipython on python files adds an extra traceback frame
- [#4792](#): repr_html exception warning on qtconsole with pandas [#4745](#)
- [#4834](#): function tooltip issues
- [#4808](#): Docstrings in Notebook not displayed properly and introspection
- [#4846](#): Remove some leftover traces of irunner
- [#4810](#): ipcluster bug in clean_logs flag
- [#4812](#): update CodeMirror for the notebook
- [#671](#): add migration guide for old IPython config
- [#4783](#): ipython 2dev under windows / (win)python 3.3 experiment
- [#4772](#): Notebook server info files
- [#4765](#): missing build script for highlight.js
- [#4787](#): non-python kernels run python code with qtconsole
- [#4703](#): Math macro in jinja templates.
- [#4595](#): ipython notebook XSS vulnerable
- [#4776](#): Manually document py3compat module.
- [#4686](#): For-in loop on an array in cell.js
- [#3605](#): Modal UI
- [#4769](#): Ipython 2.0 will not startup on py27 on windows
- [#4482](#): reveal.js converter not including CDN by default?
- [#4761](#): ipv6 address triggers cookie exception
- [#4580](#): rename or remove %profile magic
- [#4643](#): Docstring does not open properly
- [#4714](#): Static URLs are not auto-versioned
- [#2573](#): document code mirror keyboard shortcuts
- [#4717](#): hang in parallel.Client when using SSHAgent
- [#4544](#): Clarify the requirement for pyreadline on Windows
- [#3451](#): revisit REST /new handler to avoid systematic crawling.
- [#2922](#): File => Save as „py“ saves magic as code
- [#4728](#): Copy/Paste stripping broken in version > 0.13.x in QTConsole
- [#4539](#): Nbconvert: Latex to PDF conversion fails on notebooks with accented letters
- [#4721](#): purge_results with jobid crashing - looking for insight
- [#4620](#): Notebook with ? in title defies autosave, renaming and deletion.
- [#4574](#): Hash character in notebook name breaks a lot of things
- [#4709](#): input_prefilter hook not called

- #1680: qtconsole should support `--no-banner` and custom banner
- #4689: IOStream IP address configurable
- #4698: Missing `«if __name__ == „__main__“:»` check in `/usr/bin/ipython`
- #4191: NBConvert: markdown inline and locally referenced files have incorrect file location for latex
- #2865: `%%!?` does not display the shell execute docstring
- #1551: Notebook should be saved before printing
- #4612: remove `Configurable.created` ?
- #4629: Lots of tests fail due to space in `sys.executable`
- #4644: Fixed URLs for notebooks
- #4621: IPython 1.1.0 Qtconsole syntax highlighting highlights python 2 only built-ins when using python 3
- #2923: Move Delete Button Away from Save Button in the HTML notebook toolbar
- #4615: UnicodeDecodeError
- #4431: ipython slow in os x mavericks?
- #4538: DOC: document how to change `ipcontroller-engine.json` in case controller was started with `-ip=»*»`
- #4551: Serialize methods and closures
- #4081: [Nbconvert][reveal] link to font awesome ?
- #4602: `«ipcluster stop»` fails after `«ipcluster start --daemonize»` using python3.3
- #4578: NBconvert fails with unicode errors when `--stdout` and file redirection is specified and HTML entities are present
- #4600: Renaming new notebook to an exist name silently deletes the old one
- #4598: Qtconsole docstring pop-up fails on method containing defaulted enum argument
- #951: Remove Tornado monkeypatch
- #4564: Notebook save failure
- #4562: nbconvert: Default encoding problem on OS X
- #1675: add `file_to_run=file.ipynb` capability to the notebook
- #4516: `ipython console` doesn't send a `shutdown_request`
- #3043: can't restart pdb session in ipython
- #4524: Fix bug with non ascii passwords in notebook login
- #1866: problems rendering an SVG?
- #4520: unicode error when trying `Audio(„data/Bach Cello Suite #3.wav“)`
- #4493: Qtconsole cannot print an ISO8601 date at nanosecond precision
- #4502: intermittent parallel test failure `test_purge_everything`
- #4495: firefox 25.0: notebooks report «Notebook save failed», `.py` script save fails, but `.ipynb` save succeeds
- #4245: nbconvert latex: code highlighting causes error

- [#4486](#): Test for whether inside virtualenv does not work if directory is symlinked
- [#4485](#): Incorrect info in «Messaging in IPython» documentation.
- [#4447](#): Ipcontroller broken in current HEAD on windows
- [#4241](#): Audio display object
- [#4463](#): Error on empty `c.Session.key`
- [#4454](#): `UnicodeDecodeError` when starting Ipython notebook on a directory containing a file with a non-ascii character
- [#3801](#): Autocompletion: Fix issue [#3723](#) – ordering of completions for magic commands and variables with same name
- [#3723](#): Code completion: „matplotlib“ and „%matplotlib“
- [#4396](#): Always checkpoint at least once ?
- [#2524](#): [Notebook] Clear kernel queue
- [#2292](#): Client side tests for the notebook
- [#4424](#): Dealing with images in multidirectory environment
- [#4388](#): Make writing configurable magics easier
- [#852](#): Notebook should be saved before downloading
- [#3708](#): ipython profile locate should also work
- [#1349](#): ? may generate hundreds of cell
- [#4381](#): Using `hasattr` for `trait_names` instead of just looking for it directly/using `__dir__`?
- [#4361](#): Crash `Ultratraceback/` session history
- [#3044](#): IPython notebook autocomplete for filename string converts multiple spaces to a single space
- [#3346](#): Up arrow history search shows duplicates in `Qtconsole`
- [#3496](#): Fix import errors when running tests from the source directory
- [#4114](#): If default profile doesn't exist, can't install mathjax to any location
- [#4335](#): `TestPylabSwitch.test_qt` fails
- [#4291](#): `serve like` option for `nbconvert -to latex`
- [#1824](#): Exception before prompting for password during ssh connection
- [#4309](#): Error in `nbconvert` - closing `</code>` tag is not inserted in HTML under some circumstances
- [#4351](#): `/parallel/apps/launcher.py` error
- [#3603](#): Upcoming issues with `nbconvert`
- [#4296](#): `sync_imports()` fails in python 3.3
- [#4339](#): local mathjax install doesn't work
- [#4334](#): `NotebookApp.webapp_settings static_url_prefix` causes crash
- [#4308](#): Error when use «ipython notebook» in win7 64 with python2.7.3 64.
- [#4317](#): Relative imports broken in the notebook (Windows)
- [#3658](#): Saving Notebook clears «Kernel Busy» status from the page and titlebar
- [#4312](#): Link broken on ipython-doc stable

- [#1093](#): Add boundary options to %load
- [#3619](#): Multi-dir webservice design
- [#4299](#): Nbconvert, default _preprocessors to list of dotted name not list of obj
- [#3210](#): IPython.parallel tests seem to hang on ShiningPanda
- [#4280](#): MathJax Automatic Line Breaking
- [#4039](#): Celltoolbar example issue
- [#4247](#): nbconvert -to latex: error when converting greek letter
- [#4273](#): %%capture not capturing rich objects like plots (IPython 1.1.0)
- [#3866](#): Vertical offsets in LaTeX output for nbconvert
- [#3631](#): xked mode for the IPython notebook
- [#4243](#): Test exclusions not working on Windows
- [#4256](#): IPython no longer handles unicode file names
- [#3656](#): Audio displayobject
- [#4223](#): Double output on Ctrl-enter-enter
- [#4184](#): nbconvert: use r pygmentize backend when highlighting «%%R» cells
- [#3851](#): Adds an explicit newline for pretty-printing.
- [#3622](#): Drop fakemodule
- [#4122](#): Nbconvert [windows]: Inconsistent line endings in markdown cells exported to latex
- [#3819](#): nbconvert add extra blank line to code block on Windows.
- [#4203](#): remove spurious print statement from parallel annotated functions
- [#4200](#): Notebook: merging a heading cell and markdown cell cannot be undone
- [#3747](#): ipynb -> ipynb transformer
- [#4024](#): nbconvert markdown issues
- [#3903](#): on Windows, „ipython3 nbconvert «C:/blabla/first_try.ipynb» -to slides“ gives an unexpected result, and „-post serve“ fails
- [#4095](#): Catch js error in append html in stream/pyerr
- [#1880](#): Add parallelism to test_pr
- [#4085](#): nbconvert: Fix sphinx preprocessor date format string for Windows
- [#4156](#): Specifying -gui=tk at the command line
- [#4146](#): Having to prepend „files/“ to markdown image paths is confusing
- [#3818](#): nbconvert can't handle Heading with Chinese characters on Japanese Windows OS.
- [#4134](#): multi-line parser fails on „““ in comment, qtconsole and notebook.
- [#3998](#): sample custom.js needs to be updated
- [#4078](#): StoreMagic.autorestore not working in 1.0.0
- [#3990](#): Buitlin input doesn't work over zmq
- [#4015](#): nbconvert fails to convert all the content of a notebook

- [#4059](#): Issues with Ellipsis literal in Python 3
- [#2310](#): «ZMQError: Interrupted system call» from RichIPythonWidget
- [#3807](#): qtconsole ipython 0.13.2 - html/xhtml export fails
- [#4103](#): Wrong default argument of DirectView.clear
- [#4100](#): parallel.client.client references undefined error.EngineError
- [#484](#): Drop nosepatch
- [#3350](#): Added longlist support in ipdb.
- [#1591](#): Keying „q“ doesn't quit the interactive help in Wins7
- [#40](#): The tests in test_process fail under Windows
- [#3744](#): capture rich output as well as stdout/err in capture_output
- [#3742](#): %%capture to grab rich display outputs
- [#3863](#): Added working speaker notes for slides.
- [#4013](#): Iptest fails in dual python installation
- [#4005](#): IPython.start_kernel doesn't work.
- [#4020](#): IPython parallel map fails on numpy arrays
- [#3914](#): nbconvert: Transformer tests
- [#3923](#): nbconvert: Writer tests
- [#3945](#): nbconvert: commandline tests fail Win7x64 Py3.3
- [#3937](#): make tab visible in codemirror and light red background
- [#3935](#): No feedback for mixed tabs and spaces
- [#3933](#): nbconvert: Post-processor tests
- [#3977](#): unable to complete remote connections for two-process
- [#3939](#): minor checkpoint cleanup
- [#3955](#): complete on % for magic in notebook
- [#3954](#): all magics should be listed when completing on %
- [#3980](#): nbconvert rst output lacks needed blank lines
- [#3968](#): TypeError: super() argument 1 must be type, not classobj (Python 2.6.6)
- [#3880](#): nbconvert: R&D remaining tests
- [#2440](#): IPEP 4: Python 3 Compatibility

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

2.17 1.0 Series

2.17.1 Release 1.0.0: An Afternoon Hack

IPython 1.0 requires Python 2.6.5 or 3.2.1. It does not support Python 3.0, 3.1, or 2.5.

This is a big release. The principal milestone is the addition of `IPython.nbconvert`, but there has been a great deal of work improving all parts of IPython as well.

The previous version (0.13) was released on June 30, 2012, and in this development cycle we had:

- ~12 months of work.
- ~700 pull requests merged.
- ~600 issues closed (non-pull requests).
- contributions from ~150 authors.
- ~4000 commits.

The amount of work included in this release is so large that we can only cover here the main highlights; please see our [detailed release statistics](#) for links to every issue and pull request closed on GitHub as well as a full list of individual contributors. It includes

Reorganization

There have been two major reorganizations in IPython 1.0:

- Added `IPython.kernel` for all kernel-related code. This means that `IPython.zmq` has been removed, and much of it is now in `IPython.kernel.zmq`, some of it being in the top-level `IPython.kernel`.
- We have removed the `frontend` subpackage, as it caused unnecessary depth. So what was `IPython.frontend.qt` is now `IPython.qt`, and so on. The one difference is that the notebook has been further flattened, so that `IPython.frontend.html.notebook` is now just `IPython.html`. There is a shim module, so `IPython.frontend` is still importable in 1.0, but there will be a warning.
- The IPython sphinx directives are now installed in `IPython.sphinx`, so they can be imported by other projects.

Public APIs

For the first time since 0.10 (sorry, everyone), there is an official public API for starting IPython:

```
from IPython import start_ipython
start_ipython()
```

This is what packages should use that start their own IPython session, but don't actually want embedded IPython (most cases). `IPython.embed()` is used for embedding IPython into the calling namespace, similar to calling `Pdb.set_trace()`, whereas `start_ipython()` will start a plain IPython session, loading config and startup files as normal.

We also have added:

```
from IPython import get_ipython
```

Which is a *library* function for getting the current IPython instance, and will return `None` if no IPython instance is running. This is the official way to check whether your code is called from inside an IPython session. If you want to check for IPython without unnecessarily importing IPython, use this function:

```
def get_ipython():
    """return IPython instance if there is one, None otherwise"""
    import sys
    if "IPython" in sys.modules:
        import IPython
        return IPython.get_ipython()
```

Core

- The input transformation framework has been reworked. This fixes some corner cases, and adds more flexibility for projects which use IPython, like SymPy & SAGE. For more details, see *Custom input transformation*.
- Exception types can now be displayed with a custom traceback, by defining a `_render_traceback_()` method which returns a list of strings, each containing one line of the traceback.
- A new command, `ipython history trim` can be used to delete everything but the last 1000 entries in the history database.
- `__file__` is defined in both config files at load time, and `.ipy` files executed with `%run`.
- `%logstart` and `%logappend` are no longer broken.
- Add glob expansion for `%run`, e.g. `%run -g script.py *.txt`.
- Expand variables (`$foo`) in Cell Magic argument line.
- By default, `iptest` will exclude various slow tests. All tests can be run with `iptest --all`.
- SQLite history can be disabled in the various cases that it does not behave well.
- `%edit` works on interactively defined variables.
- editor hooks have been restored from quarantine, enabling TextMate as editor, etc.
- The env variable `PYTHONSTARTUP` is respected by IPython.
- The `%matplotlib` magic was added, which is like the old `%pylab` magic, but it does not import anything to the interactive namespace. It is recommended that users switch to `%matplotlib` and explicit imports.
- The `--matplotlib` command line flag was also added. It invokes the new `%matplotlib` magic and can be used in the same way as the old `--pylab` flag. You can either use it by itself as a flag (`--matplotlib`), or you can also pass a backend explicitly (`--matplotlib qt` or `--matplotlib=wx`, etc).

Backwards incompatible changes

- Calling `InteractiveShell.prefilter()` will no longer perform static transformations - the processing of escaped commands such as `%magic` and `!system`, and stripping input prompts from code blocks. This functionality was duplicated in `IPython.core.inputsplitter`, and the latter version was already what IPython relied on. A new API to transform input will be ready before release.
- Functions from `IPython.lib.inpthook` to control integration with GUI event loops are no longer exposed in the top level of `IPython.lib`. Code calling these should make sure to import them from `IPython.lib.inpthook`.
- For all kernel managers, the `sub_channel` attribute has been renamed to `iopub_channel`.
- Users on Python versions before 2.6.6, 2.7.1 or 3.2 will now need to call `IPython.utils.doctestreload.doctest_reload()` to make doctests run correctly inside IPython. Python releases since those versions are unaffected. For details, see [PR #3068](#) and [Python issue 8048](#).
- The `InteractiveShell.cache_main_mod()` method has been removed, and `new_main_mod()` has a different signature, expecting a filename where earlier versions expected a namespace. See [PR #3555](#) for details.
- The short-lived plugin system has been removed. Extensions are the way to go.

NbConvert

The major milestone for IPython 1.0 is the addition of `IPython.nbconvert` - tools for converting IPython notebooks to various other formats.

Предупреждение: nbconvert is -level preview code in 1.0

To use nbconvert to convert various file formats:

```
ipython nbconvert --to html *.ipynb
```

See `ipython nbconvert --help` for more information. nbconvert depends on [pandoc](#) for many of the translations to and from various formats.

Notebook

Major changes to the IPython Notebook in 1.0:

- The notebook is now autosaved, by default at an interval of two minutes. When you press „save“ or Ctrl-S, a *checkpoint* is made, in a hidden folder. This checkpoint can be restored, so that the autosave model is strictly safer than traditional save. If you change nothing about your save habits, you will always have a checkpoint that you have written, and an autosaved file that is kept up to date.
- The notebook supports `raw_input()` / `input()`, and thus also `%debug`, and many other Python calls that expect user input.
- You can load custom javascript and CSS in the notebook by editing the files `$(ipython locate profile)/static/custom/custom.js,css`.
- Add `%%html`, `%%svg`, `%%javascript`, and `%%latex` cell magics for writing raw output in notebook cells.
- add a redirect handler and anchors on heading cells, so you can link across notebooks, directly to heading cells in other notebooks.

- Images support width and height metadata, and thereby 2x scaling (retina support).
- `_repr_foo_` methods can return a tuple of (data, metadata), where metadata is a dict containing metadata about the displayed object. This is used to set size, etc. for retina graphics. To enable retina matplotlib figures, simply set `InlineBackend.figure_format = 'retina'` for 2x PNG figures, in your *IPython config file* or via the `%config` magic.
- Add `display.FileLink` and `FileLinks` for quickly displaying HTML links to local files.
- Cells have metadata, which can be edited via cell toolbars. This metadata can be used by external code (e.g. `reveal.js` or exporters), when examining the notebook.
- Fix an issue parsing LaTeX in markdown cells, which required users to type `\\`, instead of `\`.
- Notebook templates are rendered with Jinja instead of Tornado.
- `%%file` has been renamed `%%writefile` (`%%file` is deprecated).
- ANSI (and VT100) color parsing has been improved in both performance and supported values.
- The static files path can be found as `IPython.html.DEFAULT_STATIC_FILES_PATH`, which may be changed by package managers.
- IPython's CSS is installed in `static/css/style.min.css` (all style, including bootstrap), and `static/css/ipython.min.css`, which only has IPython's own CSS. The latter file should be useful for embedding IPython notebooks in other pages, blogs, etc.
- The Print View has been removed. Users are encouraged to test *`ipython nbconvert`* to generate a static view.

JavaScript Components

The javascript components used in the notebook have been updated significantly.

- updates to jQuery (2.0) and jQueryUI (1.10)
- Update CodeMirror to 3.14
- Twitter Bootstrap (2.3) for layout
- Font-Awesome (3.1) for icons
- highlight.js (7.3) for syntax highlighting
- marked (0.2.8) for markdown rendering
- require.js (2.1) for loading javascript

Some relevant changes that are results of this:

- Markdown cells now support GitHub-flavored Markdown (GFM), which includes ````python` code blocks and tables.
- Notebook UI behaves better on more screen sizes.
- Various code cell input issues have been fixed.

Kernel

The kernel code has been substantially reorganized.

New features in the kernel:

- Kernels support ZeroMQ IPC transport, not just TCP
- The message protocol has added a top-level metadata field, used for information about messages.
- Add a `data_pub` message that functions much like `display_pub`, but publishes raw (usually pickled) data, rather than representations.
- Ensure that `sys.stdout.encoding` is defined in Kernels.
- Stdout from forked subprocesses should be forwarded to frontends (instead of crashing).

IPEP 13

The `KernelManager` has been split into a `KernelManager` and a `KernelClient`. The Manager owns a kernel and starts / signals / restarts it. There is always zero or one `KernelManager` per Kernel. Clients communicate with Kernels via zmq channels, and there can be zero-to-many Clients connected to a Kernel at any given time.

The `KernelManager` now automatically restarts the kernel when it dies, rather than requiring user input at the notebook or QtConsole UI (which may or may not exist at restart time).

In-process kernels

The Python-language frontends, particularly the Qt console, may now communicate with in-process kernels, in addition to the traditional out-of-process kernels. An in-process kernel permits direct access to the kernel namespace, which is necessary in some applications. It should be understood, however, that the in-process kernel is not robust to bad user input and will block the main (GUI) thread while executing. Developers must decide on a case-by-case basis whether this tradeoff is appropriate for their application.

Parallel

`IPython.parallel` has had some refactoring as well. There are many improvements and fixes, but these are the major changes:

- Connections have been simplified. All ports and the serialization in use are written to the connection file, rather than the initial two-stage system.
- Serialization has been rewritten, fixing many bugs and dramatically improving performance serializing large containers.
- Load-balancing scheduler performance with large numbers of tasks has been dramatically improved.
- There should be fewer (hopefully zero) false-positives for engine failures.
- Increased compatibility with various use cases that produced serialization / argument errors with `map`, etc.
- The controller can attempt to resume operation if it has crashed, by passing `ipcontroller --restore`.
- Engines can monitor the Hub heartbeat, and shutdown if the Hub disappears for too long.
- add HTCondor support in launchers

QtConsole

Various fixes, including improved performance with lots of text output, and better drag and drop support. The initial window size of the qtconsole is now configurable via `IPythonWidget.width` and `IPythonWidget.height`.

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

2.18 Issues closed in the 1.0 development cycle

2.18.1 Issues closed in 1.2

GitHub stats for 2013/09/09 - 2014/02/21

These lists are automatically generated, and may be incomplete or contain duplicates.

The following 13 authors contributed 84 commits.

- Benjamin Ragan-Kelley
- Daryl Herzmann
- Doug Blank
- Fernando Perez
- James Porter
- Juergen Hasch
- Julian Taylor
- Kyle Kelley
- Lawrence Fu
- Matthias Bussonnier
- Paul Ivanov
- Pascal Schetelat
- Puneeth Chaganti
- Takeshi Kanmae
- Thomas Kluyver

We closed a total of 55 issues, 38 pull requests and 17 regular issues; this is the full list (generated with the script `tools/github_stats.py`):

Pull Requests (38):

1.2.1:

- PR #4372: Don't assume that SyntaxTB is always called with a SyntaxError
- PR #5166: remove mktemp usage
- PR #5163: Simplify implementation of TemporaryWorkingDirectory.
- PR #5105: add index to format to support py2.6

1.2.0:

- PR #4972: Work around problem in doctest discovery in Python 3.4 with PyQt
- PR #4934: `ipython profile create` respects `--ipython-dir`
- PR #4845: Add Origin Checking.
- PR #4928: use `importlib.machinery` when available
- PR #4849: Various unicode fixes (mostly on Windows)
- PR #4880: set profile name from `profile_dir`
- PR #4908: detect builtin docstrings in `inspect`
- PR #4909: sort dictionary keys before comparison, ordering is not guaranteed
- PR #4903: use https for all embeds
- PR #4868: Static path fixes
- PR #4820: fix regex for cleaning old logs with `ipcluster`
- PR #4840: Error in `Session.send_raw()`
- PR #4762: whitelist alphanumeric characters for `cookie_name`
- PR #4748: fix race condition in `profiledir` creation.
- PR #4720: never use ssh multiplexer in tunnels
- PR #4738: don't inject help into `user_ns`
- PR #4722: allow purging local results as long as they are not outstanding
- PR #4668: Make non-ASCII docstring unicode
- PR #4639: Minor import fix to get `qtconsole` with `-pylab=qt` working
- PR #4453: Play nice with App Nap
- PR #4609: Fix bytes regex for Python 3.
- PR #4488: fix typo in message spec doc
- PR #4346: `getpass()` on Windows & Python 2 needs bytes prompt
- PR #4230: Switch correctly to the user's default matplotlib backend after inline.
- PR #4214: engine ID metadata should be unicode, not bytes
- PR #4232: no highlight if no language specified
- PR #4218: Fix display of SyntaxError when `.py` file is modified
- PR #4217: avoid importing numpy at the module level
- PR #4213: fixed dead link in examples/notebooks readme to Part 3
- PR #4183: ESC should be handled by CM if tooltip is not on

- [PR #4193](#): Update for [#3549](#): Append Firefox overflow-x fix
- [PR #4205](#): use TextIOWrapper when communicating with pandoc subprocess
- [PR #4204](#): remove some extraneous print statements from IPython.parallel
- [PR #4201](#): HeadingCells cannot be split or merged

1.2.1:

- [#5101](#): IPython 1.2.0: notebook fail with «500 Internal Server Error»

1.2.0:

- [#4892](#): IPython.qt test failure with python3.4
- [#4810](#): ipcluster bug in clean_logs flag
- [#4765](#): missing build script for highlight.js
- [#4761](#): ipv6 address triggers cookie exception
- [#4721](#): purge_results with jobid crashing - looking for insight
- [#4602](#): «ipcluster stop» fails after «ipcluster start -daemonize» using python3.3
- [#3386](#): Magic %paste not working in Python 3.3.2. TypeError: Type str doesn't support the buffer API
- [#4485](#): Incorrect info in «Messaging in IPython» documentation.
- [#4351](#): /parallel/apps/launcher.py error
- [#4334](#): NotebookApp.webapp_settings static_url_prefix causes crash
- [#4039](#): Celltoolbar example issue
- [#4256](#): IPython no longer handles unicode file names
- [#4122](#): Nbconvert [windows]: Inconsistent line endings in markdown cells exported to latex
- [#3819](#): nbconvert add extra blank line to code block on Windows.
- [#4203](#): remove spurious print statement from parallel annotated functions
- [#4200](#): Notebook: merging a heading cell and markdown cell cannot be undone

2.18.2 Issues closed in 1.1

GitHub stats for 2013/08/08 - 2013/09/09 (since 1.0)

These lists are automatically generated, and may be incomplete or contain duplicates.

The following 25 authors contributed 337 commits.

- Benjamin Ragan-Kelley
- Bing Xia
- Bradley M. Froehle
- Brian E. Granger
- Damián Avila
- dhirschfeld
- Dražen Lučanin

- gmbecker
- Jake Vanderplas
- Jason Grout
- Jonathan Frederic
- Kevin Burke
- Kyle Kelley
- Matt Henderson
- Matthew Brett
- Matthias Bussonnier
- Pankaj Pandey
- Paul Ivanov
- rossant
- Samuel Ainsworth
- Stephan Rave
- stonebig
- Thomas Kluyver
- Yaroslav Halchenko
- Zachary Sailer

We closed a total of 76 issues, 58 pull requests and 18 regular issues; this is the full list (generated with the script `tools/github_stats.py`):

Pull Requests (58):

- [PR #4188](#): Allow `user_ns` trait to be `None`
- [PR #4189](#): always fire `LOCAL_IPS.extend(PUBLIC_IPS)`
- [PR #4174](#): various issues in markdown and rst templates
- [PR #4178](#): add missing `data_javascript`
- [PR #4181](#): nbconvert: Fix, sphinx template not removing new lines from headers
- [PR #4043](#): don't „restore_bytes“ in `from_JSON`
- [PR #4163](#): Fix for incorrect default encoding on Windows.
- [PR #4136](#): catch javascript errors in any output
- [PR #4171](#): add nbconvert config file when creating profiles
- [PR #4125](#): Basic exercise of `ipython [subcommand] -h` and `help-all`
- [PR #4085](#): nbconvert: Fix sphinx preprocessor date format string for Windows
- [PR #4159](#): don't split `.cell` and `div.cell` CSS
- [PR #4158](#): generate choices for `--gui` configurable from real mapping
- [PR #4065](#): do not include specific css in embedable one
- [PR #4092](#): nbconvert: Fix for unicode html headers, Windows + Python 2.x

- PR #4074: close Client sockets if connection fails
- PR #4064: Store default codemirror mode in only 1 place
- PR #4104: Add way to install MathJax to a particular profile
- PR #4144: help_end transformer shouldn't pick up ? in multiline string
- PR #4143: update example custom.js
- PR #4142: DOC: unwrap openssl line in public_server doc
- PR #4141: add files with a separate add call in backport_pr
- PR #4137: Restore autorestore option for storemagic
- PR #4098: pass profile-dir instead of profile name to Kernel
- PR #4120: support input in Python 2 kernels
- PR #4088: nbconvert: Fix coalesce_streams line with incorrect nesting causing strange behavior
- PR #4060: only strip continuation prompts if regular prompts seen first
- PR #4132: Fixed name error bug in function safe_unicode in module py3compat.
- PR #4121: move test_kernel from IPython.zmq to IPython.kernel
- PR #4118: ZMQ heartbeat channel: catch EINTR exceptions and continue.
- PR #4054: use unicode for HTML export
- PR #4106: fix a couple of default block values
- PR #4115: Update docs on declaring a magic function
- PR #4101: restore accidentally removed EngineError
- PR #4096: minor docs changes
- PR #4056: respect pylab_import_all when --pylab specified at the command-line
- PR #4091: Make Qt console banner configurable
- PR #4086: fix missing errno import
- PR #4030: exclude .git in MANIFEST.in
- PR #4047: Use istype() when checking if canned object is a dict
- PR #4031: don't close_fds on Windows
- PR #4029: bson.Binary moved
- PR #4035: Fixed custom jinja2 templates being ignored when setting template_path
- PR #4026: small doc fix in nbconvert
- PR #4016: Fix IPython.start_* functions
- PR #4021: Fix parallel.client.View map() on numpy arrays
- PR #4022: DOC: fix links to matplotlib, notebook docs
- PR #4018: Fix warning when running IPython.kernel tests
- PR #4019: Test skipping without unicode paths
- PR #4008: Transform code before %prun/%%prun runs
- PR #4014: Fix typo in ipapp

- [PR #3987](#): get files list in backport_pr
- [PR #3974](#): nbconvert: Fix app tests on Window7 w/ Python 3.3
- [PR #3978](#): fix `--existing` with non-localhost IP
- [PR #3939](#): minor checkpoint cleanup
- [PR #3981](#): BF: fix nbconvert rst input prompt spacing
- [PR #3960](#): Don't make sphinx a dependency for importing nbconvert
- [PR #3973](#): logging.Formatter is not new-style in 2.6

Issues (18):

- [#4024](#): nbconvert markdown issues
- [#4095](#): Catch js error in append html in stream/pyerr
- [#4156](#): Specifying `-gui=tk` at the command line
- [#3818](#): nbconvert can't handle Heading with Chinese characters on Japanese Windows OS.
- [#4134](#): multi-line parser fails on „“ in comment, qtconsole and notebook.
- [#3998](#): sample custom.js needs to be updated
- [#4078](#): StoreMagic.autorestore not working in 1.0.0
- [#3990](#): Builtlin `input` doesn't work over zmq
- [#4015](#): nbconvert fails to convert all the content of a notebook
- [#4059](#): Issues with Ellipsis literal in Python 3
- [#4103](#): Wrong default argument of `DirectVew.clear`
- [#4100](#): `parallel.client.client` references undefined `error.EngineError`
- [#4005](#): `IPython.start_kernel` doesn't work.
- [#4020](#): IPython parallel map fails on numpy arrays
- [#3945](#): nbconvert: commandline tests fail Win7x64 Py3.3
- [#3977](#): unable to complete remote connections for two-process
- [#3980](#): nbconvert rst output lacks needed blank lines
- [#3968](#): `TypeError: super() argument 1 must be type, not classobj` (Python 2.6.6)

2.18.3 Issues closed in 1.0

GitHub stats for 2012/06/30 - 2013/08/08 (since 0.13)

These lists are automatically generated, and may be incomplete or contain duplicates.

The following 155 authors contributed 4258 commits.

- Aaron Meurer
- Adam Davis
- Ahmet Bakan
- Alberto Valverde
- Allen Riddell

- Anders Hovmöller
- Andrea Bedini
- Andrew Spiers
- Andrew Vandever
- Anthony Scopatz
- Anton Akhmerov
- Anton I. Sipos
- Antony Lee
- Aron Ahmadi
- Benedikt Sauer
- Benjamin Jones
- Benjamin Ragan-Kelley
- Benjie Chen
- Boris de Laage
- Brad Reisfeld
- Bradley M. Froehle
- Brian E. Granger
- Cameron Bates
- Cavendish McKay
- chapmanb
- Chris Beaumont
- Chris Laumann
- Christoph Gohlke
- codebraker
- codespaced
- Corran Webster
- DamianHeard
- Damián Avila
- Dan Kilman
- Dan McDougall
- Danny Staple
- David Hirschfeld
- David P. Sanders
- David Warde-Farley
- David Wolever
- David Wyde

- debjan
- Diane Trout
- dkua
- Dominik Dabrowski
- Donald Curtis
- Dražen Lučanin
- drevicko
- Eric O. LEBIGOT
- Erik M. Bray
- Erik Tollerud
- Eugene Van den Bulke
- Evan Patterson
- Fernando Perez
- Francesco Montesano
- Frank Murphy
- Greg Caporaso
- Guy Haskin Fernald
- guziy
- Hans Meine
- Harry Moreno
- henryiii
- Ivan Djokic
- Jack Feser
- Jake Vanderplas
- jakobgager
- James Booth
- Jan Schulz
- Jason Grout
- Jeff Knisley
- Jens Hedegaard Nielsen
- jeremiahbuddha
- Jerry Fowler
- Jessica B. Hamrick
- Jez Ng
- John Zwinck
- Jonathan Frederic

- Jonathan Taylor
- Joon Ro
- Joseph Lansdowne
- Juergen Hasch
- Julian Taylor
- Jussi Sainio
- Jörgen Stenarson
- kevin
- klonuo
- Konrad Hinsen
- Kyle Kelley
- Lars Solberg
- Lessandro Mariano
- Mark Sienkiewicz at STScI
- Martijn Vermaat
- Martin Spacek
- Matthias Bussonnier
- Maxim Grechkin
- Maximilian Albert
- MercuryRising
- Michael Droettboom
- Michael Shuffett
- Michał Górny
- Mikhail Korobov
- mr.Shu
- Nathan Goldbaum
- ocefpaf
- Ohad Ravid
- Olivier Grisel
- Olivier Verdier
- Owen Healy
- Pankaj Pandey
- Paul Ivanov
- Pawel Jasinski
- Pietro Berkes
- Piti Ongmongkolkul

- Puneeth Chaganti
- Rich Wareham
- Richard Everson
- Rick Lupton
- Rob Young
- Robert Kern
- Robert Marchman
- Robert McGibbon
- Rui Pereira
- Rustam Safin
- Ryan May
- s8weber
- Samuel Ainsworth
- Sean Vig
- Siyu Zhang
- Skylar Saveland
- slojo404
- smithjl
- Stefan Karpinski
- Stefan van der Walt
- Steven Silvester
- Takafumi Arakaki
- Takeshi Kanmae
- tcmulcahy
- teegaar
- Thomas Kluyver
- Thomas Robitaille
- Thomas Spura
- Thomas Weißschuh
- Timothy O'Donnell
- Tom Dimiduk
- ugurthemaster
- urielshaolin
- v923z
- Valentin Haenel
- Victor Zverovich

- W. Trevor King
- y-p
- Yoav Ram
- Zbigniew Jędrzejewski-Szmek
- Zoltán Vörös

We closed a total of 1484 issues, 793 pull requests and 691 regular issues; this is the full list (generated with the script `tools/github_stats.py`):

Pull Requests (793):

- [PR #3958](#): doc update
- [PR #3965](#): Fix ansi color code for background yellow
- [PR #3964](#): Fix casing of message.
- [PR #3942](#): Pass on install docs
- [PR #3962](#): exclude IPython.lib.kernel in iptest
- [PR #3961](#): Longpath test fix
- [PR #3905](#): Remove references to 0.11 and 0.12 from config/overview.rst
- [PR #3951](#): nbconvert: fixed latex characters not escaped properly in nbconvert
- [PR #3949](#): log fatal error when PDF conversion fails
- [PR #3947](#): nbconvert: Make writer & post-processor aliases case insensitive.
- [PR #3938](#): Recompile css.
- [PR #3948](#): sphinx and PDF tweaks
- [PR #3943](#): nbconvert: Serve post-processor Windows fix
- [PR #3934](#): nbconvert: fix logic of verbose flag in PDF post processor
- [PR #3929](#): swallow enter event in rename dialog
- [PR #3924](#): nbconvert: Backport fixes
- [PR #3925](#): Replace `-pylab` flag with `-matplotlib` in usage
- [PR #3910](#): Added explicit error message for missing configuration arguments.
- [PR #3913](#): grffile to support spaces in notebook names
- [PR #3918](#): added `check_for_tornado`, closes [#3916](#)
- [PR #3917](#): change docs/examples refs to be just examples
- [PR #3908](#): what's new tweaks
- [PR #3896](#): two column quickhelp dialog, closes [#3895](#)
- [PR #3911](#): explicitly load python mode before IPython mode
- [PR #3901](#): don't force `.` relative path, fix [#3897](#)
- [PR #3891](#): fix [#3889](#)
- [PR #3892](#): Fix documentation of `Kernel.stop_channels`
- [PR #3888](#): posixify paths for Windows latex

- PR #3882: quick fix for #3881
- PR #3877: don't use `shell=True` in PDF export
- PR #3878: minor template loading cleanup
- PR #3855: nbconvert: Filter tests
- PR #3879: finish 3870
- PR #3870: Fix for converting notebooks that contain unicode characters.
- PR #3876: Update `parallel_winhpc.rst`
- PR #3872: removing vim-ipython, since it has it's own repo
- PR #3871: updating docs
- PR #3873: remove old examples
- PR #3868: update CodeMirror component to 3.15
- PR #3865: Escape filename for `pdflatex` in nbconvert
- PR #3861: remove old `external.js`
- PR #3864: add keyboard shortcut to docs
- PR #3834: This PR fixes a few issues with nbconvert tests
- PR #3840: prevent `profile_dir` from being undefined
- PR #3859: Add «An Afternoon Hack» to docs
- PR #3854: Catch errors filling readline history on startup
- PR #3857: Delete extra auto
- PR #3845: nbconvert: Serve from original build directory
- PR #3846: Add basic logging to nbconvert
- PR #3850: add missing `store_history` key to Notebook `execute_requests`
- PR #3844: update payload source
- PR #3830: mention `metadata / display_data` similarity in pyout spec
- PR #3848: fix incorrect `empty-docstring`
- PR #3836: Parse markdown correctly when `mathjax` is disabled
- PR #3849: skip a failing test on windows
- PR #3828: `signature_scheme` lives in Session
- PR #3831: update nbconvert doc with new CLI
- PR #3822: add output flag to nbconvert
- PR #3780: Added serving the output directory if html-based format are selected.
- PR #3764: Cleanup nbconvert templates
- PR #3829: remove now-duplicate „this is dev“ note
- PR #3814: add `ConsoleWidget.execute_on_complete_input` flag
- PR #3826: try `rtd`
- PR #3821: add sphinx prolog

- PR #3817: relax timeouts in terminal console and tests
- PR #3825: fix more tests that fail when pandoc is missing
- PR #3824: don't set target on internal markdown links
- PR #3816: s/pylab/matplotlib in docs
- PR #3812: Describe differences between start_ipython and embed
- PR #3805: Print View has been removed
- PR #3820: Make it clear that 1.0 is not released yet
- PR #3784: nbconvert: Export flavors & PDF writer (ipy dev meeting)
- PR #3800: semantic-versionify version number for non-releases
- PR #3802: Documentation .txt to .rst
- PR #3765: cleanup terminal console iopub handling
- PR #3720: Fix for #3719
- PR #3787: re-raise KeyboardInterrupt in raw_input
- PR #3770: Organizing reveal's templates.
- PR #3751: Use link(2) when possible in nbconvert
- PR #3792: skip tests that require pandoc
- PR #3782: add Importing Notebooks example
- PR #3752: nbconvert: Add cwd to sys.path
- PR #3789: fix raw_input in qtconsole
- PR #3756: document the wire protocol
- PR #3749: convert IPython syntax to Python syntax in nbconvert python template
- PR #3793: Closes #3788
- PR #3794: Change logo link to ipython.org
- PR #3746: Raise a named exception when pandoc is missing
- PR #3781: comply with the message spec in the notebook
- PR #3779: remove bad if logged_in preventing new-notebook without login
- PR #3743: remove notebook read-only view
- PR #3732: add delay to autosave in beforeunload
- PR #3761: Added rm_math_space to markdown cells in the basichtml.tpl to be rendered ok by mathjax after the nbconversion.
- PR #3758: nbconvert: Filter names cleanup
- PR #3769: Add configurability to tabcompletion timeout
- PR #3771: Update px pylab test to match new output of pylab
- PR #3741: better message when notebook format is not supported
- PR #3753: document Ctrl-C not working in ipython kernel
- PR #3766: handle empty metadata in pyout messages more gracefully.

- PR #3736: my attempt to fix #3735
- PR #3759: nbconvert: Provide a more useful error for invalid use case.
- PR #3760: nbconvert: Allow notebook filenames without their extensions
- PR #3750: nbconvert: Add cwd to default templates search path.
- PR #3748: Update nbconvert docs
- PR #3734: Nbconvert: Export extracted files into `nbname_files` subdirectory
- PR #3733: Nicer message when pandoc is missing, closes #3730
- PR #3722: fix two failing test in IPython.lib
- PR #3704: Start what's new for 1.0
- PR #3705: Complete rewrite of IPython Notebook documentation: docs/source/interactive/htmlnotebook.txt
- PR #3709: Docs cleanup
- PR #3716: raw_input fixes for kernel restarts
- PR #3683: use `%matplotlib` in example notebooks
- PR #3686: remove quarantine
- PR #3699: svg2pdf unicode fix
- PR #3695: fix SVG2PDF
- PR #3685: fix Pager.detach
- PR #3675: document new dependencies
- PR #3690: Fixing some css minors in full_html and reveal.
- PR #3671: nbconvert tests
- PR #3692: Fix rename notebook - show error with invalid name
- PR #3409: Prevent qtconsole frontend freeze on lots of output.
- PR #3660: refocus active cell on dialog close
- PR #3598: Statelessify mathjaxutils
- PR #3673: enable comment/uncomment selection
- PR #3677: remove special-case in get_home_dir for frozen dists
- PR #3674: add CONTRIBUTING.md
- PR #3670: use Popen command list for ipexec
- PR #3568: pylab import adjustments
- PR #3559: add create.Cell and delete.Cell js events
- PR #3606: push cell magic to the head of the transformer line
- PR #3607: NbConvert: Writers, No YAML, and stuff...
- PR #3665: Pywin32 skips
- PR #3669: set default client_class for QtKernelManager
- PR #3662: add strip_encoding_cookie transformer

- PR #3641: increase patience for slow kernel startup in tests
- PR #3651: remove a bunch of unused `default_config_file` assignments
- PR #3630: CSS adjustments
- PR #3645: Don't require HistoryManager to have a shell
- PR #3643: don't assume tested ipython is on the PATH
- PR #3654: fix single-result AsyncResults
- PR #3601: Markdown in heading cells (take 2)
- PR #3652: Remove old `docs/examples`
- PR #3621: catch any exception appending output
- PR #3585: don't blacklist builtin names
- PR #3647: Fix `frontend` deprecation warnings in several examples
- PR #3649: fix `AsyncResult.get_dict` for single result
- PR #3648: Fix store magic test
- PR #3650: Fix, `config_file_name` was ignored
- PR #3640: `Gcf.get_active()` can return None
- PR #3571: Added shortcuts to split cell, merge cell above and merge cell below.
- PR #3635: Added missing slash to `print-pdf` call.
- PR #3487: Drop patch for compatibility with `pyreadline 1.5`
- PR #3338: Allow filename with extension in `find_cmd` in Windows.
- PR #3628: Fix test for Python 3 on Windows.
- PR #3642: Fix typo in docs
- PR #3627: use `DEFAULT_STATIC_FILES_PATH` in a test instead of package dir
- PR #3624: fix some unicode in `zmqhandlers`
- PR #3460: Set calling program to `UNKNOWN`, when `argv` not in `sys`
- PR #3632: Set calling program to `UNKNOWN`, when `argv` not in `sys` (take #2)
- PR #3629: Use new entry point for `python -m IPython`
- PR #3626: passing cell to `showInPager`, closes #3625
- PR #3618: expand terminal color support
- PR #3623: raise `UsageError` for unsupported GUI backends
- PR #3071: Add magic function `%drun` to run code in debugger
- PR #3608: a nicer error message when using `%pylab` magic
- PR #3592: add `extra_config_file`
- PR #3612: updated `.mailmap`
- PR #3616: Add examples for interactive use of MPI.
- PR #3615: fix regular expression for ANSI escapes
- PR #3586: Corrected a typo in the format string for `strftime` the sphinx.py transformer of `nbconvert`

- PR #3611: check for markdown no longer needed, closes #3610
- PR #3555: Simplify caching of modules with %run
- PR #3583: notebook small things
- PR #3594: Fix duplicate completion in notebook
- PR #3600: parallel: Improved logging for errors during BatchSystemLauncher.stop
- PR #3595: Revert «allow markdown in heading cells»
- PR #3538: add IPython.start_ipython
- PR #3562: Allow custom nbconvert template loaders
- PR #3582: pandoc adjustments
- PR #3560: Remove max_msg_size
- PR #3591: Refer to Setuptools instead of Distribute
- PR #3590: IPython.sphinxext needs an __init__.py
- PR #3581: Added the possibility to read a custom.css file for tweaking the final html in full_html and reveal templates.
- PR #3576: Added support for markdown in heading cells when they are nbconverted.
- PR #3575: tweak run -d message to „continue execution“
- PR #3569: add PYTHONSTARTUP to startup files
- PR #3567: Trigger a single event on js app initialized
- PR #3565: style.min.css should always exist...
- PR #3531: allow markdown in heading cells
- PR #3577: Simplify codemirror ipython-mode
- PR #3495: Simplified regexp, and suggestions for clearer regexps.
- PR #3578: Use adjustbox to specify figure size in nbconvert -> latex
- PR #3572: Skip import irunner test on Windows.
- PR #3574: correct static path for CM modes autoload
- PR #3558: Add IPython.sphinxext
- PR #3561: mention double-control-C to stop notebook server
- PR #3566: fix event names
- PR #3564: Remove trivial nbconvert example
- PR #3540: allow cython cache dir to be deleted
- PR #3527: cleanup stale, unused exceptions in parallel.error
- PR #3529: ensure raw_input returns str in zmq shell
- PR #3541: respect image size metadata in qtconsole
- PR #3550: Fixing issue preventing the correct read of images by full_html and reveal exporters.
- PR #3557: open markdown links in new tabs
- PR #3556: remove mention of nonexistent _margv in macro

- PR #3552: set overflow-x: hidden on Firefox only
- PR #3554: Fix missing import os in latex exporter.
- PR #3546: Don't hardcode **latex** posix paths in nbconvert
- PR #3551: fix path prefix in nbconvert
- PR #3533: Use a CDN to get reveal.js library.
- PR #3498: When a notebook is written to file, name the metadata name u`""`.
- PR #3548: Change to standard save icon in Notebook toolbar
- PR #3539: Don't hardcode posix paths in nbconvert
- PR #3508: notebook supports raw_input and %debug now
- PR #3526: ensure „default“ is first in cluster profile list
- PR #3525: basic timezone info
- PR #3532: include nbconvert templates in installation
- PR #3515: update CodeMirror component to 3.14
- PR #3513: add „No Checkpoints“ to Revert menu
- PR #3536: format positions are required in Python 2.6.x
- PR #3521: Nbconvert fix, silent fail if template doesn't exist
- PR #3530: update %store magic docstring
- PR #3528: fix local mathjax with custom base_project_url
- PR #3518: Clear up unused imports
- PR #3506: %store -r restores saved aliases and directory history, as well as variables
- PR #3516: make css highlight style configurable
- PR #3523: Exclude frontend shim from docs build
- PR #3514: use bootstrap disabled instead of ui-state-disabled
- PR #3520: Added relative import of RevealExporter to __init__.py inside exporters module
- PR #3507: fix HTML capitalization in nbconvert exporter classes
- PR #3512: fix nbconvert filter validation
- PR #3511: Get Tracer working after ipapi.get replaced with get_ipython
- PR #3510: use window.onbeforeunload= for nav-away warning
- PR #3504: don't use parent=self in handlers
- PR #3500: Merge nbconvert into IPython
- PR #3478: restore «unsaved changes» warning on unload
- PR #3493: add a dialog when the kernel is auto-restarted
- PR #3488: Add test suite for autoreload extension
- PR #3484: Catch some pathological cases inside oinspect
- PR #3481: Display R errors without Python traceback
- PR #3468: fix %magic output

- PR #3430: add parent to Configurable
- PR #3491: Remove unexpected keyword parameter to remove_kernel
- PR #3485: SymPy has changed its recommended way to initialize printing
- PR #3486: Add test for non-ascii characters in docstrings
- PR #3483: Inputtransformer: Allow classic prompts without space
- PR #3482: Use an absolute path to iptest, because the tests are not always run from \$IPYTHONDIR.
- PR #3381: enable 2x (retina) display
- PR #3450: Flatten IPython.frontend
- PR #3477: pass config to subapps
- PR #3466: Kernel fails to start when username has non-ascii characters
- PR #3465: Add HTCondor bindings to IPython.parallel
- PR #3463: fix typo, closes #3462
- PR #3456: Notice for users who disable javascript
- PR #3453: fix cell execution in firefox, closes #3447
- PR #3393: [WIP] bootstrapify
- PR #3440: Fix installing mathjax from downloaded file via command line
- PR #3431: Provide means for starting the Qt console maximized and with the menu bar hidden
- PR #3425: base IPClusterApp inherits from BaseIPythonApp
- PR #3433: Update IPythonexternalpath__init__.py
- PR #3298: Some fixes in IPython Sphinx directive
- PR #3428: process escapes in mathjax
- PR #3420: thank -> thanks
- PR #3416: Fix doc: «principle» not «principal»
- PR #3413: more unique filename for test
- PR #3364: Inject requirejs in notebook and start using it.
- PR #3390: Fix %paste with blank lines
- PR #3403: fix creating config objects from dicts
- PR #3401: rollback #3358
- PR #3373: make cookie_secret configurable
- PR #3307: switch default ws_url logic to js side
- PR #3392: Restore anchor link on h2-h6
- PR #3369: Use different threshold for (auto)scroll in output
- PR #3370: normalize unicode notebook filenames
- PR #3372: base default cookie name on request host+port
- PR #3378: disable CodeMirror drag/drop on Safari
- PR #3358: workaround spurious CodeMirror scrollbars

- PR #3371: make setting the notebook dirty flag an event
- PR #3366: remove long-dead zmq frontend.py and completer.py
- PR #3382: cull Session digest history
- PR #3330: Fix get_ipython_dir when \$HOME is /
- PR #3319: IPEP 13: user-expressions and user-variables
- PR #3384: comments in tools/gitwash_dumper.py changed („““ to «»»)
- PR #3387: Make submodule checks work under Python 3.
- PR #3357: move anchor-link off of heading text
- PR #3351: start basic tests of ipcluster Launchers
- PR #3377: allow class.__module__ to be None
- PR #3340: skip submodule check in package managers
- PR #3328: decode subprocess output in launchers
- PR #3368: Reenable bracket matching
- PR #3356: Mpr fixes
- PR #3336: Use new input transformation API in %time magic
- PR #3325: Organize the JS and less files by component.
- PR #3342: fix test_find_cmd_python
- PR #3354: catch socket.error in utils.localinterfaces
- PR #3341: fix default cluster count
- PR #3286: don't use get_ipython from builtins in library code
- PR #3333: notebookapp: add missing whitespace to warnings
- PR #3323: Strip prompts even if the prompt isn't present on the first line.
- PR #3321: Reorganize the python/server side of the notebook
- PR #3320: define __file__ in config files
- PR #3317: rename %%file to %%writefile
- PR #3304: set unlimited HWM for all relay devices
- PR #3315: Update Sympy_printing extension load
- PR #3310: further clarify Image docstring
- PR #3285: load extensions in builtin trap
- PR #3308: Speed up AsyncResult._wait_for_outputs(0)
- PR #3294: fix callbacks as optional in js kernel.execute
- PR #3276: Fix: «python ABS/PATH/TO/ipython.py» fails
- PR #3301: allow python3 tests without python installed
- PR #3282: allow view.map to work with a few more things
- PR #3284: remove ipython.py entry point
- PR #3281: fix ignored IOPub messages with no parent

- PR #3275: improve submodule messages / git hooks
- PR #3239: Allow «x» icon and esc key to close pager in notebook
- PR #3290: Improved heartbeat controller to engine monitoring for long running tasks
- PR #3142: Better error message when CWD doesn't exist on startup
- PR #3066: Add support for relative import to %run -m (fixes #2727)
- PR #3269: protect highlight.js against unknown languages
- PR #3267: add missing return
- PR #3101: use marked / highlight.js instead of pagedown and prettify
- PR #3264: use https url for submodule
- PR #3263: fix set_last_checkpoint when no checkpoint
- PR #3258: Fix submodule location in setup.py
- PR #3254: fix a few URLs from previous PR
- PR #3240: remove js components from the repo
- PR #3158: IPEP 15: autosave the notebook
- PR #3252: move images out of _static folder into _images
- PR #3251: Fix for cell magics in Qt console
- PR #3250: Added a simple __html__() method to the HTML class
- PR #3249: remove copy of sphinx inheritance_diagram.py
- PR #3235: Remove the unused print notebook view
- PR #3238: Improve the design of the tab completion UI
- PR #3242: Make changes of Application.log_format effective
- PR #3219: Workaround so only one CTRL-C is required for a new prompt in -gui=qt
- PR #3190: allow formatters to specify metadata
- PR #3231: improve discovery of public IPs
- PR #3233: check prefixes for swallowing kernel args
- PR #3234: Removing old autogrow JS code.
- PR #3232: Update to CodeMirror 3 and start to ship our components
- PR #3229: The HTML output type accidentally got removed from the OutputArea.
- PR #3228: Typo in IPython.Parallel documentation
- PR #3226: Text in rename dialog was way too big - making it <p>.
- PR #3225: Removing old restuctured text handler and web service.
- PR #3222: make BlockingKernelClient the default Client
- PR #3223: add missing mathjax_url to new settings dict
- PR #3089: add stdin to the notebook
- PR #3221: Remove references to HTMLCell (dead code)
- PR #3205: add ignored *args to HasTraits constructor

- PR #3088: cleanup IPython handler settings
- PR #3201: use much faster regexp for ansi coloring
- PR #3220: avoid race condition in profile creation
- PR #3011: IPEP 12: add KernelClient
- PR #3217: informative error when trying to load directories
- PR #3174: Simple class
- PR #2979: CM configurable Take 2
- PR #3215: Updates storemagic extension to allow for specifying variable name to load
- PR #3181: backport If-Modified-Since fix from tornado
- PR #3200: IFrame (VimeoVideo, ScribdDocument, ...)
- PR #3186: Fix small inconsistency in nbconvert: etype -> ename
- PR #3212: Fix issue #2563, «core.profiledir.check_startup_dir() doesn't work inside py2exe'd installation»
- PR #3211: Fix inheritance_diagram Sphinx extension for Sphinx 1.2
- PR #3208: Update link to extensions index
- PR #3203: Separate InputSplitter for transforming whole cells
- PR #3189: Improve completer
- PR #3194: finish up PR #3116
- PR #3188: Add new keycodes
- PR #2695: Key the root modules cache by sys.path entries.
- PR #3182: clarify %%file docstring
- PR #3163: BUG: Fix the set and frozenset pretty printer to handle the empty case correctly
- PR #3180: better UsageError for cell magic with no body
- PR #3184: Cython cache
- PR #3175: Added missing s
- PR #3173: Little bits of documentation cleanup
- PR #2635: Improve Windows start menu shortcuts (#2)
- PR #3172: Add missing import in IPython parallel magics example
- PR #3170: default application logger shouldn't propagate
- PR #3159: Autocompletion for zsh
- PR #3105: move DEFAULT_STATIC_FILES_PATH to IPython.html
- PR #3144: minor bower tweaks
- PR #3141: Default color output for ls on OSX
- PR #3137: fix dot syntax error in inheritance diagram
- PR #3072: raise UnsupportedOperation on iostream.fileno()
- PR #3147: Notebook support for a reverse proxy which handles SSL

- PR #3152: make qtconsole size at startup configurable
- PR #3162: adding stream kwarg to `current.new_output`
- PR #2981: IPEP 10: kernel side filtering of display formats
- PR #3058: add redirect handler for notebooks by name
- PR #3041: support non-modules in `@require`
- PR #2447: Stateful line transformers
- PR #3108: fix some $O(N)$ and $O(N^2)$ operations in `parallel.map`
- PR #2791: forward stdout from forked processes
- PR #3157: use Python 3-style for pretty-printed sets
- PR #3148: closes #3045, #3123 for tornado < version 3.0
- PR #3143: minor heading-link tweaks
- PR #3136: Strip useless ANSI escape codes in notebook
- PR #3126: Prevent errors when pressing arrow keys in an empty notebook
- PR #3135: quick dev installation instructions
- PR #2889: Push pandas dataframes to R magic
- PR #3068: Don't monkeypatch doctest during IPython startup.
- PR #3133: fix argparse version check
- PR #3102: set `spellcheck=false` in CodeCell inputarea
- PR #3064: add anchors to heading cells
- PR #3097: PyQt 4.10: use `self._document = self.document()`
- PR #3117: propagate automagic change to shell
- PR #3118: don't give up on weird os names
- PR #3115: Fix example
- PR #2640: fix quarantine/ipy_editors.py
- PR #3070: Add info make target that was missing in old Sphinx
- PR #3082: A few small patches to image handling
- PR #3078: fix regular expression for detecting links in stdout
- PR #3054: restore default behavior for automatic cluster size
- PR #3073: fix ipython usage text
- PR #3083: fix `DisplayMagics.html` docstring
- PR #3080: noted `sub_channel` being renamed to `iopub_channel`
- PR #3079: actually use `IPKernelApp.kernel_class`
- PR #3076: Improve notebook.js documentation
- PR #3063: add missing `%%html` magic
- PR #3075: check for SIGUSR1 before using it, closes #3074
- PR #3051: add `width:100%` to `vbox` for webkit / FF consistency

- PR #2999: increase registration timeout
- PR #2997: fix DictDB default size limit
- PR #3033: on resume, print server info again
- PR #3062: test double pyximport
- PR #3046: cast kernel cwd to bytes on Python 2 on Windows
- PR #3038: remove xml from notebook magic docstrings
- PR #3032: fix time format to international time format
- PR #3022: Fix test for Windows
- PR #3024: changed instances of „outout“ to „output“ in alt texts
- PR #3013: py3 workaround for reload in cythonmagic
- PR #2961: time magic: shorten unnecessary output on windows
- PR #2987: fix local files examples in markdown
- PR #2998: fix css in .output_area pre
- PR #3003: add \$include /etc/inputrc to suggested ~/.inputrc
- PR #2957: Refactor qt import logic. Fixes #2955
- PR #2994: expanduser on %%file targets
- PR #2983: fix run-all (that-> this)
- PR #2964: fix count when testing composite error output
- PR #2967: shows entire session history when only startsess is given
- PR #2942: Move CM IPython theme out of codemirror folder
- PR #2929: Cleanup cell insertion
- PR #2933: Minordocupdate
- PR #2968: fix notebook deletion.
- PR #2966: Added assert msg to extract_hist_ranges()
- PR #2959: Add command to trim the history database.
- PR #2681: Don't enable pylab mode, when matplotlib is not importable
- PR #2901: Fix inputhook_wx on osx
- PR #2871: truncate potentially long CompositeErrors
- PR #2951: use istype on lists/tuples
- PR #2946: fix qtconsole history logic for end-of-line
- PR #2954: fix logic for append_javascript
- PR #2941: fix baseUrl
- PR #2903: Specify toggle value on cell line number
- PR #2911: display order in output area configurable
- PR #2897: Don't rely on BaseProjectUrl data in body tag
- PR #2894: Cm configurable

- PR #2927: next release will be 1.0
- PR #2932: Simplify using notebook static files from external code
- PR #2915: added small config section to notebook docs page
- PR #2924: safe_run_module: Silence SystemExit codes 0 and None.
- PR #2906: Unpatch/Monkey patch CM
- PR #2921: add menu item for undo delete cell
- PR #2917: Don't add logging handler if one already exists.
- PR #2910: Respect DB_IP and DB_PORT in mongodb tests
- PR #2926: Don't die if stderr/stdout do not support set_parent() #2925
- PR #2885: get monospace pager back
- PR #2876: fix celltoolbar layout on FF
- PR #2904: Skip remaining IPC test on Windows
- PR #2908: fix last remaining KernelApp reference
- PR #2905: fix a few remaining KernelApp/IPKernelApp changes
- PR #2900: Don't assume test case for %time will finish in 0 time
- PR #2893: exclude fabfile from tests
- PR #2884: Correct import for kernelmanager on Windows
- PR #2882: Utils cleanup
- PR #2883: Don't call ast.fix_missing_locations unless the AST could have been modified
- PR #2855: time(it) magic: Implement minutes/hour formatting and «%%time» cell magic
- PR #2874: Empty cell warnings
- PR #2819: tweak history prefix search (up/^p) in qtconsole
- PR #2868: Import performance
- PR #2877: minor css fixes
- PR #2880: update examples docs with kernel move
- PR #2878: Pass host environment on to kernel
- PR #2599: func_kw_complete for builtin and cython with embededsignature=True using docstring
- PR #2792: Add key «unique» to history_request protocol
- PR #2872: fix payload keys
- PR #2869: Fixing styling of toolbar selects on FF.
- PR #2708: Less css
- PR #2854: Move kernel code into IPython.kernel
- PR #2864: Fix %run -t -N<N> TypeError
- PR #2852: future pyzmq compatibility
- PR #2863: whatsnew/version0.9.txt: Fix „~/ipython“ -> „~/ipython“ typo
- PR #2861: add missing KernelManager to ConsoleApp class list

- PR #2850: Consolidate host IP detection in `utils.localinterfaces`
- PR #2859: Correct docstring of `ipython.py`
- PR #2831: avoid string version comparisons in `external.qt`
- PR #2844: this should address the failure in #2732
- PR #2849: `utils/data`: Use list comprehension for `uniq_stable()`
- PR #2839: add `jinja` to `install docs / setup.py`
- PR #2841: Miscellaneous docs fixes
- PR #2811: Still more `KernelManager` cleanup
- PR #2820: add „=“ to greedy completer delims
- PR #2818: log user tracebacks in the kernel (INFO-level)
- PR #2828: Clean up notebook Javascript
- PR #2829: avoid comparison error in `dictdb` hub history
- PR #2830: BUG: Opening parenthesis after non-callable raises `ValueError`
- PR #2718: try to fallback to `pysqlite2.dbapi2` as `sqlite3` in `core.history`
- PR #2816: in `%edit`, don't save «`last_call`» unless last call succeeded
- PR #2817: change `ol` format order
- PR #2537: Organize example notebooks
- PR #2815: update `release/authors`
- PR #2808: improve patience for slow Hub in client tests
- PR #2812: remove nonfunctional `-la` short arg in `cython` magic
- PR #2810: remove dead `utils.upgradedir`
- PR #1671: `__future__` environments
- PR #2804: skip `ipc` tests on Windows
- PR #2789: Fixing styling issues with `CellToolbar`.
- PR #2805: fix `KeyError` creating `ZMQStreams` in notebook
- PR #2775: General cleanup of kernel manager code.
- PR #2340: Initial Code to reduce `parallel.Client` caching
- PR #2799: Exit code
- PR #2800: use `type(obj) is cls` as switch when canning
- PR #2801: Fix a breakpoint bug
- PR #2795: Remove outdated code from `extensions.autoreload`
- PR #2796: P3K: fix cookie parsing under Python 3.x (+ duplicate import is removed)
- PR #2724: In-process kernel support (take 3)
- PR #2687: [WIP] `Metaui` slideshow
- PR #2788: Chrome frame awareness
- PR #2649: Add `version_request/reply` messaging protocol

- PR #2753: add `%%px --local` for local execution
- PR #2783: Prefilter shouldn't touch `execution_count`
- PR #2333: UI For Metadata
- PR #2396: create a `ipynbv3` json schema and a validator
- PR #2757: check for complete `pyside` presence before trying to import
- PR #2782: Allow the `%run` magic with `„b“` to specify a file.
- PR #2778: P3K: fix `DeprecationWarning` under Python 3.x
- PR #2776: remove non-functional `View.kill` method
- PR #2755: can interactively defined classes
- PR #2774: Removing unused code in the notebook `MappingKernelManager`.
- PR #2773: Fixed minor typo causing `AttributeError` to be thrown.
- PR #2609: Add `„unique“` option to `history_request` messaging protocol
- PR #2769: Allow shutdown when no engines are registered
- PR #2766: Define `__file__` when we `%edit` a real file.
- PR #2476: allow `%edit <variable>` to work when interactively defined
- PR #2763: Reset readline delimiters after loading `rmagic`.
- PR #2460: Better handling of `__file__` when running scripts.
- PR #2617: Fix for `units` argument. Adds a `res` argument.
- PR #2738: Unicode content crashes the pager (console)
- PR #2749: Tell Travis CI to test on Python 3.3 as well
- PR #2744: Don't show `„try %paste“` message while using magics
- PR #2728: shift tab for tooltip
- PR #2741: Add note to `%cython` Black-Scholes example warning of missing `erf`.
- PR #2743: BUG: `Octavemagic` inline plots not working on Windows: Fixed
- PR #2740: Following #2737 this error is now a name error
- PR #2737: `Rmagic`: error message when moving an non-existent variable from python to R
- PR #2723: diverse fixes for project url
- PR #2731: `%Rpush`: Look for variables in the local scope first.
- PR #2544: Infinite loop when multiple debuggers have been attached.
- PR #2726: Add `qthelp` docs creation
- PR #2730: added blockquote CSS
- PR #2729: Fix Read the doc build, Again
- PR #2446: [alternate 2267] Offline `mathjax`
- PR #2716: remove unexisting headings level
- PR #2717: One liner to fix debugger printing stack traces when lines of context are larger than source.
- PR #2713: Doc bugfix: `user_ns` is not an attribute of Magic objects.

- PR #2690: Fix `„import „... completion for py3 & egg files.`
- PR #2691: Document OpenMP in `%%cython` magic
- PR #2699: fix jinja2 rendering for password protected notebooks
- PR #2700: Skip notebook testing if jinja2 is not available.
- PR #2692: Add `%%cython` magics to generated documentation.
- PR #2685: Fix pretty print of types when `__module__` is not available.
- PR #2686: Fix `tox.ini`
- PR #2604: Backslashes are misinterpreted as escape-sequences by the R-interpreter.
- PR #2689: fix error in doc (`arg->kwarg`) and pep-8
- PR #2683: for downloads, replaced `window.open` with `window.location.assign`
- PR #2659: small bugs in js are fixed
- PR #2363: Refactor notebook templates to use Jinja2
- PR #2662: qtconsole: wrap argument list in tooltip to match width of text body
- PR #2328: addition of classes to generate a link or list of links from files local to the IPython HTML notebook
- PR #2668: `pylab_not_importable`: Catch all exceptions, not just `RuntimeErrors`.
- PR #2663: Fix issue #2660: parsing of help and version arguments
- PR #2656: Fix `irunner` tests when `$PYTHONSTARTUP` is set
- PR #2312: Add bracket matching to code cells in notebook
- PR #2571: Start to document Javascript
- PR #2641: undefined that `->` this
- PR #2638: Fix `%paste` in Python 3 on Mac
- PR #2301: Ast transformers
- PR #2616: Revamp API docs
- PR #2572: Make „Paste Above“ the default paste behavior.
- PR #2574: Fix #2244
- PR #2582: Fix displaying history when output cache is disabled.
- PR #2591: Fix for Issue #2584
- PR #2526: Don't kill paramiko tunnels when receiving `^C`
- PR #2559: Add `psource`, `pfile`, `pinfo2` commands to `ipdb`.
- PR #2546: use 4 Pythons to build 4 Windows installers
- PR #2561: Fix display of plain text containing multiple carriage returns before line feed
- PR #2549: Add a simple „undo“ for cell deletion.
- PR #2525: Add event to kernel execution/shell reply.
- PR #2554: Avoid stopping in `ipdb` until we reach the main script.
- PR #2404: Option to limit search result in history magic command

- PR #2294: inputhook_qt4: Use QEventLoop instead of starting up the QCoreApplication
- PR #2233: Refactored Drag and Drop Support in Qt Console
- PR #1747: switch between hsplit and vsplit paging (request for feedback)
- PR #2530: Adding time offsets to the video
- PR #2542: Allow starting IPython as `python -m IPython`.
- PR #2534: Do not unescape backslashes in Windows (shellglob)
- PR #2517: Improved MathJax, bug fixes
- PR #2511: trigger default `remote_profile_dir` when `profile_dir` is set
- PR #2491: color is supported in ironpython
- PR #2462: Track which extensions are loaded
- PR #2464: Locate URLs in text output and convert them to hyperlinks.
- PR #2490: add ZMQInteractiveShell to IPEngineApp class list
- PR #2498: Don't catch tab press when something selected
- PR #2527: Run All Above and Run All Below
- PR #2513: add GitHub uploads to release script
- PR #2529: Windows aware tests for shellglob
- PR #2478: Fix `doctest_run_option_parser` for Windows
- PR #2519: clear `In[]` prompt numbers again
- PR #2467: Clickable links
- PR #2500: Add `encoding` attribute to `OutStream` class.
- PR #2349: ENH: added StackExchange-style MathJax filtering
- PR #2503: Fix traceback handling of `SyntaxErrors` without line numbers.
- PR #2492: add missing „qtconsole“ `extras_require`
- PR #2480: Add deprecation warnings for `sympyprinting`
- PR #2334: Make the ipengine monitor the ipcontroller heartbeat and die if the ipcontroller goes down
- PR #2479: use new `_winapi` instead of removed `_subprocess`
- PR #2474: fix bootstrap name conflicts
- PR #2469: Treat `__init__.pyc` same as `__init__.py` in `module_list`
- PR #2165: Add -g option to `%run` to glob expand arguments
- PR #2468: Tell git to ignore `__pycache__` directories.
- PR #2421: Some notebook tweaks.
- PR #2291: Remove old plugin system
- PR #2127: Ability to build toolbar in JS
- PR #2445: changes for ironpython
- PR #2420: Pass `ipython_dir` to `__init__()` method of `TerminalInteractiveShell`'s superclass.
- PR #2432: Revert #1831, the `__file__` injection in `safe_execfile` / `safe_execfile_ipy`.

- PR #2216: Autochange highlight with cell magics
- PR #1946: Add image message handler in ZMQTerminalInteractiveShell
- PR #2424: skip find_cmd when setting up script magics
- PR #2389: Catch sqlite DatabaseErrors in more places when reading the history database
- PR #2395: Don't catch ImportError when trying to unpack module functions
- PR #1868: enable IPC transport for kernels
- PR #2437: don't let log cleanup prevent engine start
- PR #2441: `sys.maxsize` is the maximum length of a container.
- PR #2442: allow iptest to be interrupted
- PR #2240: fix message built for engine dying during task
- PR #2369: Block until kernel termination after sending a kill signal
- PR #2439: Py3k: Octal (0777 -> 0o777)
- PR #2326: Detachable pager in notebook.
- PR #2377: Fix installation of man pages in Python 3
- PR #2407: add IPython version to message headers
- PR #2408: Fix Issue #2366
- PR #2405: clarify TaskScheduler.hwm doc
- PR #2399: IndentationError display
- PR #2400: Add scroll_to_cell(cell_number) to the notebook
- PR #2401: unmock read-the-docs modules
- PR #2311: always perform requested trait assignments
- PR #2393: New option n to limit history search hits
- PR #2386: Adapt inline backend to changes in matplotlib
- PR #2392: Remove suspicious double quote
- PR #2387: Added -L library search path to cythonmagic cell magic
- PR #2370: qtconsole: Create a prompt newline by inserting a new block (w/o formatting)
- PR #1715: Fix for #1688, traceback-unicode issue
- PR #2378: use Singleton.instance() for embed() instead of manual global
- PR #2373: fix missing imports in core.interactiveshell
- PR #2368: remove notification widget leftover
- PR #2327: Parallel: Support get/set of nested objects in view (e.g. dv[„a.b“])
- PR #2362: Clean up ProgressBar class in example notebook
- PR #2346: Extra xterm identification in set_term_title
- PR #2352: Notebook: Store the username in a cookie whose name is unique.
- PR #2358: add backport_pr to tools
- PR #2365: fix names of notebooks for download/save

- PR #2364: make clients use „location“ properly (fixes #2361)
- PR #2354: Refactor notebook templates to use Jinja2
- PR #2339: add bash completion example
- PR #2345: Remove references to „version“ no longer in argparse. Github issue #2343.
- PR #2347: adjust division error message checking to account for Python 3
- PR #2305: RemoteError._render_traceback_ calls self.render_traceback
- PR #2338: Normalize line endings for ipexec_validate, fix for #2315.
- PR #2192: Introduce Notification Area
- PR #2329: Better error messages for common magic commands.
- PR #2337: ENH: added StackExchange-style MathJax filtering
- PR #2331: update css for qtconsole in doc
- PR #2317: adding cluster_id to parallel.Client.__init__
- PR #2130: Add -l option to %R magic to allow passing in of local namespace
- PR #2196: Fix for bad command line argument to latex
- PR #2300: bug fix: was crashing when sqlite3 is not installed
- PR #2184: Expose store_history to execute_request messages.
- PR #2308: Add welcome_message option to enable_pylab
- PR #2302: Fix variable expansion on „self“
- PR #2299: Remove code from prefilter that duplicates functionality in inputsplitter
- PR #2295: allow pip install from github repository directly
- PR #2280: fix SSH passwordless check for OpenSSH
- PR #2290: nbmanager
- PR #2288: s/assertEquals/assertEqual (again)
- PR #2287: Removed outdated dev docs.
- PR #2218: Use redirect for new notebooks
- PR #2277: nb: up/down arrow keys move to begin/end of line at top/bottom of cell
- PR #2045: Refactoring notebook managers and adding Azure backed storage.
- PR #2271: use display instead of send_figure in inline backend hooks
- PR #2278: allow disabling SQLite history
- PR #2225: Add «-annotate» option to %%cython magic.
- PR #2246: serialize individual args/kwargs rather than the containers
- PR #2274: CLN: Use name to id mapping of notebooks instead of searching.
- PR #2270: SSHLauncher tweaks
- PR #2269: add missing location when disambiguating controller IP
- PR #2263: Allow docs to build on <https://readthedocs.io/>
- PR #2256: Adding data publication example notebook.

- PR #2255: better flush iopub with AsyncResults
- PR #2261: Fix: longest_substr([]) -> „“
- PR #2260: fix mpr again
- PR #2242: Document globbing in `%history -g <pattern>`.
- PR #2250: fix html in notebook example
- PR #2245: Fix regression in `embed()` from pull-request #2096.
- PR #2248: track sha of master in `test_pr` messages
- PR #2238: Fast tests
- PR #2211: add data publication message
- PR #2236: minor `test_pr` tweaks
- PR #2231: Improve Image format validation and add html width,height
- PR #2232: Reapply monkeypatch to `inspect.findsource()`
- PR #2235: remove spurious print statement from `setupbase.py`
- PR #2222: adjust how canning deals with import strings
- PR #2224: fix css typo
- PR #2223: Custom tracebacks
- PR #2214: use `KernelApp.exec_lines/files` in `IPEngineApp`
- PR #2199: Wrap JS published by `%%javascript` in `try/catch`
- PR #2212: catch errors in markdown javascript
- PR #2190: Update code mirror 2.22 to 2.32
- PR #2200: documentation build broken in bb429da5b
- PR #2194: clean nan/inf in `json_clean`
- PR #2198: fix mpr for earlier git version
- PR #2175: add `FileFindHandler` for Notebook static files
- PR #1990: can `func_defaults`
- PR #2069: start improving serialization in parallel code
- PR #2202: Create a unique & temporary `IPYTHONDIR` for each testing group.
- PR #2204: Work around lack of `os.kill` in win32.
- PR #2148: win32 `iptest`: Use `subprocess.Popen()` instead of `os.system()`.
- PR #2179: Pylab switch
- PR #2124: Add an API for registering magic aliases.
- PR #2169: `ipdb`: `pdef`, `pdoc`, `pinfo` magics all broken
- PR #2174: Ensure consistent indentation in `%magic`.
- PR #1930: add size-limiting to the DictDB backend
- PR #2189: Fix `IPython.lib.latextools` for Python 3
- PR #2186: removed references to h5py dependence in octave magic documentation

- PR #2183: Include the kernel object in the event object passed to kernel events
- PR #2185: added test for %store, fixed storemagic
- PR #2138: Use breqn.sty in dvipng backend if possible
- PR #2182: handle undefined param in notebooklist
- PR #1831: fix #1814 set `__file__` when running .ipy files
- PR #2051: Add a metadata attribute to messages
- PR #1471: simplify IPython.parallel connections and enable Controller Resume
- PR #2181: add %%javascript, %%svg, and %%latex display magics
- PR #2116: different images in 00_notebook-tour
- PR #2092: %prun: Restore `stats.stream` after running `print_stream`.
- PR #2159: show message on notebook list if server is unreachable
- PR #2176: fix git mpr
- PR #2152: [qtconsole] Namespace not empty at startup
- PR #2177: remove numpy install from travis/tox scripts
- PR #2090: New keybinding for code cell execution + cell insertion
- PR #2160: Updating the parallel options pricing example
- PR #2168: expand line in cell magics
- PR #2170: Fix tab completion with `IPython.embed_kernel()`.
- PR #2096: `embed()`: Default to the future compiler flags of the calling frame.
- PR #2163: fix „remote_profile_dir“ typo in SSH launchers
- PR #2158: [2to3 compat] Tuple params in func defs
- PR #2089: Fix unittest DeprecationWarnings
- PR #2142: Refactor test_pr.py
- PR #2140: 2to3: Apply `has_key` fixer.
- PR #2131: Add option `append (-a)` to %save
- PR #2117: use explicit url in notebook example
- PR #2133: Tell git that *.py files contain Python code, for use in word-diffs.
- PR #2134: Apply 2to3 `next` fix.
- PR #2126: ipcluster broken with any batch launcher (PBS/LSF/SGE)
- PR #2104: Windows make file for Sphinx documentation
- PR #2074: Make BG color of inline plot configurable
- PR #2123: BUG: Look up the `_repr_pretty_` method on the class within the MRO path...
- PR #2100: [in progress] python 2 and 3 compatibility without 2to3, second try
- PR #2128: open notebook copy in different tabs
- PR #2073: allows password and prefix for notebook
- PR #1993: Print View

- PR #2086: re-alias %ed to %edit in qtconsole
- PR #2110: Fixes and improvements to the input splitter
- PR #2101: fix completer deleting newline
- PR #2102: Fix logging on interactive shell.
- PR #2088: Fix (some) Python 3.2 ResourceWarnings
- PR #2064: conform to pep 3110
- PR #2076: Skip notebook „static“ dir in test suite.
- PR #2063: Remove umlauts so py3 installations on LANG=C systems succeed.
- PR #2068: record sysinfo in sdist
- PR #2067: update tools/release_windows.py
- PR #2065: Fix parentheses typo
- PR #2062: Remove duplicates and auto-generated files from repo.
- PR #2061: use explicit tuple in exception
- PR #2060: change minus to - or (hy in manpages

Issues (691):

- #3940: Install process documentation overhaul
- #3946: The PDF option for --post should work with lowercase
- #3957: Notebook help page broken in Firefox
- #3894: nbconvert test failure
- #3887: 1.0.0a1 shows blank screen in both firefox and chrome (windows 7)
- #3703: nbconvert: Output options – names and documentation
- #3931: Tab completion not working during debugging in the notebook
- #3936: Ipcluster plugin is not working with IPython 1.0dev
- #3941: IPython Notebook kernel crash on Win7x64
- #3926: Ending Notebook renaming dialog with return creates new-line
- #3932: Incorrect empty docstring
- #3928: Passing variables to script from the workspace
- #3774: Notebooks with spaces in their names breaks nbconvert latex graphics
- #3916: tornado needs its own check
- #3915: Link to Parallel examples «found on GitHub» broken in docs
- #3895: Keyboard shortcuts box in notebook doesn't fit the screen
- #3912: IPython.utils fails automated test for RC1 1.0.0
- #3636: Code cell missing highlight on load
- #3897: under Windows, «ipython3 nbconvert «C:/blabla/first_try.ipynb» -to latex -post PDF» POST processing action fails because of a bad parameter
- #3900: python3 install syntax errors (OS X 10.8.4)

- #3899: nbconvert to latex fails on notebooks with spaces in file name
- #3881: Temporary Working Directory Test Fails
- #2750: A way to freeze code cells in the notebook
- #3893: Resize Local Image Files in Notebook doesn't work
- #3823: nbconvert on windows: tex and paths
- #3885: under Windows, «ipython3 nbconvert «C:/blabla/first_try.ipynb» -to latex» write «" instead of «/» to reference file path in the .tex file
- #3889: test_qt fails due to assertion error „qt4“ != „qt“
- #3890: double post, disregard this issue
- #3689: nbconvert, remaining tests
- #3874: Up/Down keys don't work to «Search previous command history» (besides Ctrl-p/Ctrl-n)
- #3853: CodeMirror locks up in the notebook
- #3862: can only connect to an ipcluster started with v1.0.0-dev (master branch) using an older ipython (v0.13.2), but cannot connect using ipython (v1.0.0-dev)
- #3869: custom css not working.
- #2960: Keyboard shortcuts
- #3795: ipcontroller process goes to 100% CPU, ignores connection requests
- #3553: Ipython and pylab crashes in windows and canopy
- #3837: Cannot set custom mathjax url, crash notebook server.
- #3808: «Naming» releases ?
- #2431: TypeError: must be string without null bytes, not str
- #3856: ? at end of comment causes line to execute
- #3731: nbconvert: add logging for the different steps of nbconvert
- #3835: Markdown cells do not render correctly when mathjax is disabled
- #3843: nbconvert to rst: leftover «In[]»
- #3799: nbconvert: Ability to specify name of output file
- #3726: Document when IPython.start_ipython() should be used versus IPython.embed()
- #3778: Add no more readonly view in what's new
- #3754: No Print View in Notebook in 1.0dev
- #3798: IPython 0.12.1 Crashes on autocompleting sqlalchemy.func.row_number properties
- #3811: Opening notebook directly from the command line with multi-directory support installed
- #3775: Annoying behavior when clicking on cell after execution (Ctrl+Enter)
- #3809: Possible to add some bpython features?
- #3810: Printing the contents of an image file messes up shell text
- #3702: nbconvert: Default help message should be that of -help
- #3735: Nbconvert 1.0.0a1 does not take into account the pdf extensions in graphs
- #3719: Bad strftime format, for windows, in nbconvert exporter

- #3786: Zmq errors appearing with `Ctrl-C` in console/qtconsole
- #3019: disappearing scrollbar on tooltip in Chrome 24 on Ubuntu 12.04
- #3785: ipdb completely broken in Qt console
- #3796: Document the meaning of milestone/issues-tags for users.
- #3788: Do not auto show tooltip if docstring empty.
- #1366: [Web page] No link to front page from documentation
- #3739: nbconvert (to slideshow) misses some of the math in markdown cells
- #3768: increase and make timeout configurable in console completion.
- #3724: ipcluster only running on one cpu
- #1592: better message for unsupported nbformat
- #2049: Can not stop «ipython kernel» on windows
- #3757: Need direct entry point to given notebook
- #3745: ImportError: cannot import name check_linecache_ipython
- #3701: nbconvert: Final output file should be in same directory as input file
- #3738: history -o works but history with -n produces identical results
- #3740: error when attempting to run „make“ in docs directory
- #3737: ipython nbconvert crashes with ValueError: Invalid format string.
- #3730: nbconvert: unhelpful error when pandoc isn't installed
- #3718: markdown cell cursor misaligned in notebook
- #3710: multiple input fields for %debug in the notebook after resetting the kernel
- #3713: PyCharm has problems with IPython working inside PyPy created by virtualenv
- #3712: Code completion: Complete on dictionary keys
- #3680: -pylab and -matplotlib flag
- #3698: nbconvert: Unicode error with minus sign
- #3693: nbconvert does not process SVGs into PDFs
- #3688: nbconvert, figures not extracting with Python 3.x
- #3542: note new dependencies in docs / setup.py
- #2556: [pagedown] do not target_blank anchor link
- #3684: bad message when %pylab fails due import *other* than matplotlib
- #3682: ipython notebook pylab inline import_all=False
- #3596: MathjaxUtils race condition?
- #1540: Comment/uncomment selection in notebook
- #2702: frozen setup: permission denied for default ipython_dir
- #3672: allow_none on Number-like traits.
- #2411: add CONTRIBUTING.md
- #481: IPython terminal issue with Qt4Agg on XP SP3

- #2664: How to preserve user variables from import clashing?
- #3436: `enable_pylab(import_all=False)` still imports `np`
- #2630: `lib.pylabtools.figsize` : `NameError` when using `Qt4Agg` backend and `%pylab` magic.
- #3154: Notebook: no event triggered when a Cell is created
- #3579: `Nbconvert`: `SVG` are not transformed to `PDF` anymore
- #3604: `MathJax` rendering problem in `%%latex` cell
- #3668: `AttributeError`: „`BlockingKernelClient`“ object has no attribute „`started_channels`“
- #3245: `SyntaxError`: encoding declaration in Unicode string
- #3639: `%pylab` inline in `IPYTHON` notebook throws «`RuntimeError`: Cannot activate multiple GUI eventloops»
- #3663: frontend deprecation warnings
- #3661: `run -m` not behaving like `python -m`
- #3597: re-do PR #3531 - allow markdown in Header cell
- #3053: Markdown in header cells is not rendered
- #3655: `IPython` finding its way into pasted strings.
- #3620: uncaught errors in `HTML` output
- #3646: `get_dict()` error
- #3004: `%load_ext rmagic` fails when legacy `ipy_user_conf.py` is installed (in `ipython 0.13.1` / `OSX 10.8`)
- #3638: `setp()` issue in `ipython` notebook with figure references
- #3634: `nbconvert` reveal to pdf conversion ignores styling, prints only a single page.
- #1307: Remove `pyreadline` workarounds, we now require `pyreadline >= 1.7.1`
- #3316: `find_cmd` test failure on Windows
- #3494: `input()` in notebook doesn't work in Python 3
- #3427: Deprecate `$` as `mathjax` delimiter
- #3625: Pager does not open from button
- #3149: Miscellaneous small `nbconvert` feedback
- #3617: 256 color escapes support
- #3609: `%pylab` inline blows up for single process `ipython`
- #2934: Publish the Interactive MPI Demo Notebook
- #3614: ansi escapes broken in master (`ls -color`)
- #3610: If you don't have markdown, `python setup.py` install says no `pygments`
- #3547: `%run` modules clobber each other
- #3602: `import_item` fails when one tries to use `DottedObjectName` instead of a string
- #3563: Duplicate tab completions in the notebook
- #3599: Problems trying to run `IPython` on `python3` without installing...
- #2937: too long completion in notebook

- [#3479](#): Write empty name for the notebooks
- [#3505](#): nbconvert: Failure in specifying user filter
- [#1537](#): think a bit about namespaces
- [#3124](#): Long multiline strings in Notebook
- [#3464](#): run -d message unclear
- [#2706](#): IPython 0.13.1 ignoring \$PYTHONSTARTUP
- [#3587](#): LaTeX escaping bug in nbconvert when exporting to HTML
- [#3213](#): Long running notebook died with a coredump
- [#3580](#): Running ipython with pypy on windows
- [#3573](#): custom.js not working
- [#3544](#): IPython.lib test failure on Windows
- [#3352](#): Install Sphinx extensions
- [#2971](#): [notebook]user needs to press ctrl-c twice to stop notebook server should be put into terminal window
- [#2413](#): ipython3 qtconsole fails to install: ipython 0.13 has no such extra feature „qtconsole“
- [#2618](#): documentation is incorrect for install process
- [#2595](#): mac 10.8 qtconsole export history
- [#2586](#): cannot store aliases
- [#2714](#): ipython qtconsole print unittest messages in console instead his own window.
- [#2669](#): cython magic failing to work with openmp.
- [#3256](#): Vagrant pandas instance of IPython Notebook does not respect additional plotting arguments
- [#3010](#): cython magic fail if cache dir is deleted while in session
- [#2044](#): prune unused names from parallel.error
- [#1145](#): Online help utility broken in QtConsole
- [#3439](#): Markdown links no longer open in new window (with change from pagedown to marked)
- [#3476](#): `_margv` for macros seems to be missing
- [#3499](#): Add reveal.js library (version 2.4.0) inside IPython
- [#2771](#): Wiki Migration to GitHub
- [#2887](#): ipcontroller purging some engines during connect
- [#626](#): Enable Resuming Controller
- [#2824](#): Kernel restarting after message «Kernel XXXX failed to respond to heartbeat»
- [#2823](#): `%%cython` magic gives `ImportError: dlopen(long_file_name.so, 2): image not found`
- [#2891](#): In IPython for Python 3, system site-packages comes before user site-packages
- [#2928](#): Add magic «watch» function (example)
- [#2931](#): Problem rendering pandas dataframe in Firefox for Windows
- [#2939](#): [notebook] Figure legend not shown in inline backend if outside the box of the axes

- #2972: [notebook] in Markdown mode, press Enter key at the end of <some http link>, the next line is indented unexpectedly
- #3069: Instructions for installing IPython notebook on Windows
- #3444: Encoding problem: cannot use if user's name is not ascii?
- #3335: Reenable bracket matching
- #3386: Magic %paste not working in Python 3.3.2. TypeError: Type str doesn't support the buffer API
- #3543: Exception shutting down kernel from notebook dashboard (0.13.1)
- #3549: Codecell size changes with selection
- #3445: Adding newlines in %%latex cell
- #3237: [notebook] Can't close a notebook without errors
- #2916: colon invokes auto(un)indent in markdown cells
- #2167: Indent and dedent in htmlnotebook
- #3545: Notebook save button icon not clear
- #3534: nbconvert incompatible with Windows?
- #3489: Update example notebook that raw_input is allowed
- #3396: Notebook checkpoint time is displayed an hour out
- #3261: Empty revert to checkpoint menu if no checkpoint...
- #2984: «print» magic does not work in Python 3
- #3524: Issues with pyzmq and ipython on EPD update
- #2434: %store magic not auto-restoring
- #2720: base_url and static path
- #2234: Update various low resolution graphics for retina displays
- #2842: Remember passwords for pw-protected notebooks
- #3244: qtconsole: ValueError(„close_fds is not supported on Windows platforms if you redirect stdin/stdout/stderr“,)
- #2215: AsyncResult.wait(0) can hang waiting for the client to get results?
- #2268: provide mean to retrieve static data path
- #1905: Expose UI for worksheets within each notebook
- #2380: Qt inputhook prevents modal dialog boxes from displaying
- #3185: prettify on double //
- #2821: Test failure: IPython.parallel.tests.test_client.test_resubmit_header
- #2475: [Notebook] Line is deindented when typing eg a colon in markdown mode
- #2470: Do not destroy valid notebooks
- #860: Allow the standalone export of a notebook to HTML
- #2652: notebook with qt backend crashes at save image location popup
- #1587: Improve kernel restarting in the notebook

- #2710: Saving a plot in Mac OS X backend crashes IPython
- #2596: notebook «Last saved:» is misleading on file opening.
- #2671: TypeError :NoneType when executed «ipython qtconsole» in windows console
- #2703: Notebook scrolling breaks after pager is shown
- #2803: KernelManager and KernelClient should be two separate objects
- #2693: TerminalIPythonApp configuration fails without ipython_config.py
- #2531: IPython 0.13.1 python 2 32-bit installer includes 64-bit ipython*.exe launchers in the scripts folder
- #2520: Control-C kills port forwarding
- #2279: Setting `__file__` to None breaks Mayavi import
- #2161: When logged into notebook, long titles are incorrectly positioned
- #1292: Notebook, Print view should not be editable...
- #1731: test parallel launchers
- #3227: Improve documentation of ipcontroller and possible BUG
- #2896: IPController very unstable
- #3517: documentation build broken in head
- #3522: UnicodeDecodeError: „ascii“ codec can't decode byte on Pycharm on Windows
- #3448: Please include MathJax fonts with IPython Notebook
- #3519: IPython Parallel map mysteriously turns pandas Series into numpy ndarray
- #3345: IPython embedded shells ask if I want to exit, but I set `confirm_exit = False`
- #3509: IPython won't close without asking «Are you sure?» in Firefox
- #3471: Notebook jinja2/markupsafe dependencies in manual
- #3502: Notebook broken in master
- #3302: autoreload does not work in ipython 0.13.x, python 3.3
- #3475: no warning when leaving/closing notebook on master without saved changes
- #3490: No obvious feedback when kernel crashes
- #1912: Move all autoreload tests to their own group
- #2577: sh.py and ipython for python 3.3
- #3467: %magic doesn't work
- #3501: Editing markdown cells that wrap has off-by-one errors in cursor positioning
- #3492: IPython for Python3
- #3474: unexpected keyword argument to `remove_kernel`
- #2283: TypeError when using „?“ after a string in a %logstart session
- #2787: rmagic and pandas DataFrame
- #2605: Ellipsis literal triggers AttributeError
- #1179: Test unicode source in pinfo

- #2055: drop Python 3.1 support
- #2293: IPEP 2: Input transformations
- #2790: %paste and %cpaste not removing «...» lines
- #3480: Testing fails because iptest.py cannot be found
- #2580: will not run within PIL build directory
- #2797: RMagic, Dataframe Conversion Problem
- #2838: Empty lines disappear from triple-quoted literals.
- #3050: Broken link on IPython.core.display page
- #3473: Config not passed down to subcommands
- #3462: Setting log_format in config file results in error (and no format changes)
- #3311: Notebook (occasionally) not working on windows (Sophos AV)
- #3461: Cursor positioning off by a character in auto-wrapped lines
- #3454: _repr_html_ error
- #3457: Space in long Paragraph Markdown cell with Chinese or Japanese
- #3447: Run Cell Does not Work
- #1373: Last lines in long cells are hidden
- #1504: Revisit serialization in IPython.parallel
- #1459: Can't connect to 2 HTTPS notebook servers on the same host
- #678: Input prompt stripping broken with multiline data structures
- #3001: IPython.notebook.dirty flag is not set when a cell has unsaved changes
- #3077: Multiprocessing semantics in parallel.view.map
- #3056: links across notebooks
- #3120: Tornado 3.0
- #3156: update pretty to use Python 3 style for sets
- #3197: Can't escape multiple dollar signs in a markdown cell
- #3309: Image() signature/doc improvements
- #3415: Bug in IPython/external/path/_init_.py
- #3446: Feature suggestion: Download matplotlib figure to client browser
- #3295: autoexported notebooks: only export explicitly marked cells
- #3442: Notebook: Summary table extracted from markdown headers
- #3438: Zooming notebook in chrome is broken in master
- #1378: Implement autosave in notebook
- #3437: Highlighting matching parentheses
- #3435: module search segfault
- #3424: ipcluster -version
- #3434: 0.13.2 Ipython/genutils.py doesn't exist

- #3426: Feature request: Save by cell and not by line #: IPython %save magic
- #3412: Non Responsive Kernel: Running a Django development server from an IPython Notebook
- #3408: Save cell toolbar and slide type metadata in notebooks
- #3246: %paste regression with blank lines
- #3404: Weird error with \$variable and grep in command line magic (!command)
- #3405: Key auto-completion in dictionaries?
- #3259: Codemirror linenumber css broken
- #3397: Vertical text misalignment in Markdown cells
- #3391: Revert #3358 once fix integrated into CM
- #3360: Error 500 while saving IPython notebook
- #3375: Frequent Safari/Webkit crashes
- #3365: zmq frontend
- #2654: User_expression issues
- #3389: Store history as plain text
- #3388: Ipython parallel: open TCP connection created for each result returned from engine
- #3385: setup.py failure on Python 3
- #3376: Setting `__module__` to None breaks pretty printing
- #3374: ipython qtconsole does not display the prompt on OSX
- #3380: simple call to kernel
- #3379: TaskRecord key „started“ not set
- #3241: notebook connection time out
- #3334: magic interpreter interprets non magic commands?
- #3326: python3.3: Type error when launching SGE cluster in IPython notebook
- #3349: pip3 doesn't run 2to3?
- #3347: Longlist support in ipdb
- #3343: Make pip install / easy_install faster
- #3337: git submodules broke nightly PPA builds
- #3206: Copy/Paste Regression in QtConsole
- #3329: Buggy linewidth in Mac OSX Terminal (Mountain Lion)
- #3327: Qt version check broken
- #3303: parallel tasks never finish under heavy load
- #1381: „\“ for equation continuations require an extra „' in markdown cells
- #3314: Error launching IPython
- #3306: Test failure when running on a Vagrant VM
- #3280: IPython.utils.process.getoutput returns stderr
- #3299: variables named `_` or `__` exhibit incorrect behavior

- #3196: add an «x» or similar to htmlnotebook pager
- #3293: Several 404 errors for js files Firefox
- #3292: syntax highlighting in chrome on OSX 10.8.3
- #3288: Latest dev version hangs on page load
- #3283: ipython dev retains directory information after directory change
- #3279: custom.css is not overridden in the dev IPython (1.0)
- #2727: %run -m doesn't support relative imports
- #3268: GFM triple backquote and unknown language
- #3273: Suppressing all plot related outputs
- #3272: Backspace while completing load previous page
- #3260: Js error in savewidget
- #3247: scrollbar in notebook when not needed?
- #3243: notebook: option to view json source from browser
- #3265: 404 errors when running IPython 1.0dev
- #3257: setup.py not finding submodules
- #3253: Incorrect Qt and PySide version comparison
- #3248: Cell magics broken in Qt console
- #3012: Problems with the less based style.min.css
- #2390: Image width/height don't work in embedded images
- #3236: cannot set TerminalIPythonApp.log_format
- #3214: notebook kernel dies if started with invalid parameter
- #2980: Remove HTMLCell ?
- #3128: qtconsole hangs on importing pylab (using X forwarding)
- #3198: Hitting recursive depth causing all notebook pages to hang
- #3218: race conditions in profile directory creation
- #3177: OverflowError execption in handlers.py
- #2563: core.profiledir.check_startup_dir() doesn't work inside py2exe'd installation
- #3207: [Feature] folders for ipython notebook dashboard
- #3178: cell magics do not work with empty lines after #2447
- #3204: Default plot() colors unsuitable for red-green colorblind users
- #1789: : \n/*foo turns into : \n*(foo) in triple-quoted strings.
- #3202: File cell magic fails with blank lines
- #3199: %%cython -a stopped working?
- #2688: obsolete imports in import autocompletion
- #3192: Python2, Unhandled exception, __builtin__.True = False
- #3179: script magic error message loop

- #3009: use XDG_CACHE_HOME for cython objects
- #3059: Bugs in 00_notebook_tour example.
- #3104: Integrate a javascript file manager into the notebook front end
- #3176: Particular equation not rendering (notebook)
- #1133: [notebook] readonly and upload files/UI
- #2975: [notebook] python file and cell toolbar
- #3017: SciPy.weave broken in IPython notebook/ qtconsole
- #3161: paste macro not reading spaces correctly
- #2835: %paste not working on WinXpSP3/ipython-0.13.1.py2-win32-PROPER.exe/python27
- #2628: Make transformers work for lines following decorators
- #2612: Multiline String containing «:n?foon» confuses interpreter to replace ?foo with get_ipython().magic(u'pinfo foo')
- #2539: Request: Enable cell magics inside of .ipy scripts
- #2507: Multiline string does not work (includes ...) with doctest type input in IPython notebook
- #2164: Request: Line breaks in line magic command
- #3106: poor parallel performance with many jobs
- #2438: print inside multiprocessing crashes Ipython kernel
- #3155: Bad md5 hash for package 0.13.2
- #3045: [Notebook] Ipython Kernel does not start if disconnected from internet(/network?)
- #3146: Using celery in python 3.3
- #3145: The notebook viewer is down
- #2385: grep -color not working well with notebook
- #3131: Quickly install from source in a clean virtualenv?
- #3139: Rolling log for ipython
- #3127: notebook with pylab=inline appears to call figure.draw twice
- #3129: Walking up and down the call stack
- #3123: Notebook crashed if unplugged ethernet cable
- #3121: NB should use normalize.css? was #3049
- #3087: Disable spellchecking in notebook
- #3084: ipython PyQt 4.10 incompatibility, QTextBlockUserData
- #3113: Fails to install under Jython 2.7 beta
- #3110: Render of h4 headers is not correct in notebook (error in renderedhtml.css)
- #3109: BUG: read_csv: dtype={,id": np.str}: Datatype not understood
- #3107: Autocompletion of object attributes in arrays
- #3103: Reset locale setting in qtconsole
- #3090: python3.3 Entry Point not found

- #3081: UnicodeDecodeError when using Image(data=»some.jpeg«)
- #2834: url regexp only finds one link
- #3091: qtconsole breaks doctest.testmod() in Python 3.3
- #3074: SIGUSR1 not available on Windows
- #2996: registration::purging stalled registration high occurrence in small clusters
- #3065: diff-ability of notebooks
- #3067: Crash with pygit2
- #3061: Bug handling Ellipsis
- #3049: NB css inconsistent behavior between ff and webkit
- #3039: unicode errors when opening a new notebook
- #3048: Installing ipython qtConsole should be easier att Windows
- #3042: Profile creation fails on 0.13.2 branch
- #3035: docstring typo/inconsistency: mention of an xml notebook format?
- #3031: HDF5 library segfault (possibly due to mismatching headers?)
- #2991: In notebook importing sympy closes ipython kernel
- #3027: f.__globals__ causes an error in Python 3.3
- #3020: Failing test test_interactiveshell.TestAstTransform on Windows
- #3023: alt text for «click to expand output» has typo in alt text
- #2963: %history to print all input history of a previous session when line range is omitted
- #3018: IPython installed within virtualenv. WARNING «Please install IPython inside the virtualenv»
- #2484: Completion in Emacs *Python* buffer causes prompt to be increased.
- #3014: Ctrl-C finishes notebook immediately
- #3007: cython_pyximport reload broken in python3
- #2955: Incompatible Qt imports when running inprocess_qtconsole
- #3006: [IPython 0.13.1] The check of PyQt version is wrong
- #3005: Renaming a notebook to an existing notebook name overwrites the other file
- #2940: Abort trap in IPython Notebook after installing matplotlib
- #3000: issue #3000
- #2995: ipython_directive.py fails on multiline when prompt number < 100
- #2993: File magic (%%file) does not work with paths beginning with tilde (e.g., ~/anaconda/stuff.txt)
- #2992: Cell-based input for console and qt frontends?
- #2425: Liaise with Spyder devs to integrate newer IPython
- #2986: requesting help in a loop can damage a notebook
- #2978: v1.0-dev build errors on Arch with Python 3.
- #2557: [refactor] Insert_cell_at_index()
- #2969: ipython command does not work in terminal

- #2762: OSX wxPython (osx_cocoa, 64bit) command «%gui wx» blocks the interpreter
- #2956: Silent importing of submodules differs from standard Python3.2 interpreter's behavior
- #2943: Up arrow key history search gets stuck in QTConsole
- #2953: using „nonlocal“ declaration in global scope causes ipython3 crash
- #2952: qtconsole ignores exec_lines
- #2949: ipython crashes due to atexit()
- #2947: From rmagic to an R console
- #2938: docstring pane not showing in notebook
- #2936: Tornado assumes invalid signature for parse_qs on Python 3.1
- #2935: unable to find python after easy_install / pip install
- #2920: Add undo-cell deletion menu
- #2914: BUG:saving a modified .py file after loading a module kills the kernel
- #2925: BUG: kernel dies if user sets sys.stderr or sys.stdout to a file object
- #2909: LaTeX sometimes fails to render in markdown cells with some curly bracket + underscore combinations
- #2898: Skip ipc tests on Windows
- #2902: ActiveState attempt to build ipython 0.12.1 for python 3.2.2 for Mac OS failed
- #2899: Test failure in IPython.core.tests.test_magic.test_time
- #2890: Test failure when fabric not installed
- #2892: IPython tab completion bug for paths
- #1340: Allow input cells to be collapsed
- #2881: ? command in notebook does not show help in Safari
- #2751: %%timeit should use minutes to format running time in long running cells
- #2879: When importing a module with a wrong name, ipython crashes
- #2862: %%timeit should warn of empty contents
- #2485: History navigation breaks in qtconsole
- #2785: gevent input hook
- #2843: Silently running code in clipboard (with paste, cpaste and variants)
- #2784: %run -t -N<N> error
- #2732: Test failure with FileLinks class on Windows
- #2860: ipython help notebook -> KeyError: „KernelManager“
- #2858: Where is the installed ipython script?
- #2856: Edit code entered from ipython in external editor
- #2722: IPC transport option not taking effect ?
- #2473: Better error messages in ipengine/ipcontroller
- #2836: Cannot send builtin module definitions to IP engines

- #2833: Any reason not to use `super()` ?
- #2781: Cannot interrupt infinite loops in the notebook
- #2150: `clippath_demo.py` in matplotlib example does not work with inline backend
- #2634: Numbered list in notebook markdown cell renders with Roman numerals instead of numbers
- #2230: IPython crashing during startup with «`AttributeError: „NoneType“ object has no attribute „rstrip“`»
- #2483: nbviewer bug? with multi-file gists
- #2466: mistyping `ed -p` breaks `ed -p`
- #2477: Glob expansion tests fail on Windows
- #2622: doc issue: notebooks that ship with IPython .13 are written for python 2.x
- #2626: Add «Cell -> Run All Keep Going» for notebooks
- #1223: Show last modification date of each notebook
- #2621: user request: put link to example notebooks in Dashboard
- #2564: grid blanks plots in ipython pylab inline mode (interactive)
- #2532: Django shell (IPython) gives `NameError` on dict comprehensions
- #2188: ipython crashes on `ctrl-c`
- #2391: Request: nbformat API to load/save without changing version
- #2355: Restart kernel message even though kernel is perfectly alive
- #2306: Garbled input text after reverse search on Mac OS X
- #2297: ipdb with separate kernel/client pushing stdout to kernel process only
- #2180: Have `[kernel busy]` overridden only by `[kernel idle]`
- #1188: Pylab with OSX backend keyboard focus issue and hang
- #2107: `test_octavemagic.py[everything]` fails
- #1212: Better understand/document browser compatibility
- #1585: Refactor notebook templates to use Jinja2 and make each page a separate directory
- #1443: xticks scaling factor partially obscured with qtconsole and inline plotting
- #1209: can't make `%result` work as in doc.
- #1200: IPython 0.12 Windows install fails on Vista
- #1127: Interactive test scripts for Qt/nb issues
- #959: Matplotlib figures hide
- #2071: win32 installer issue on Windows XP
- #2610: `ZMQInteractiveShell.colors` being ignored
- #2505: Markdown Cell incorrectly highlighting after «<»
- #165: Installer fails to create Start Menu entries on Windows
- #2356: failing traceback in terminal ipython for first exception
- #2145: Have dashboad show when server disconnect

- #2098: Do not crash on kernel shutdown if json file is missing
- #2813: Offline MathJax is broken on 0.14dev
- #2807: Test failure: IPython.parallel.tests.test_client.TestClient.test_purge_everything
- #2486: Readline's history search in ipython console does not clear properly after cancellation with Ctrl+C
- #2709: Cython -la doesn't work
- #2767: What is IPython.utils.upgradedir ?
- #2210: Placing matplotlib legend outside axis bounds causes inline display to clip it
- #2553: IPython Notebooks not robust against client failures
- #2536: ImageDraw in Ipython notebook not drawing lines
- #2264: Feature request: Versioning messaging protocol
- #2589: Creation of ~300+ MPI-spawned engines causes instability in ipcluster
- #2672: notebook: inline option without pylab
- #2673: Indefinite Articles & Traitlets
- #2705: Notebook crashes Safari with select and drag
- #2721: drelload kills ipython when it hits zmq
- #2806: ipython.parallel doesn't discover globals under Python 3.3
- #2794: _exit_code behaves differently in terminal vs ZMQ frontends
- #2793: IPython.parallel issue with pushing pandas TimeSeries
- #1085: In process kernel for Qt frontend
- #2760: IndexError: list index out of range with Python 3.2
- #2780: Save and load notebooks from github
- #2772: AttributeError: „Client“ object has no attribute „kill“
- #2754: Fail to send class definitions from interactive session to engines namespaces
- #2764: TypeError while using „cd“
- #2765: name „__file__“ is not defined
- #2540: Wrap tooltip if line exceeds threshold?
- #2394: Startup error on ipython qtconsole (version 0.13 and 0.14-dev)
- #2440: IPEP 4: Python 3 Compatibility
- #1814: __file__ is not defined when file end with .ipy
- #2759: R magic extension interferes with tab completion
- #2615: Small change needed to rmagic extension.
- #2748: collapse parts of a html notebook
- #1661: %paste still bugs about IndentationError and says to use %paste
- #2742: Octavemagic fails to deliver inline images in IPython (on Windows)
- #2739: wiki.ipython.org contaminated with prescription drug spam

- #2588: Link error while executing code from cython example notebook
- #2550: Rpush magic doesn't find local variables and doesn't support comma separated lists of variables
- #2675: Markdown/html blockquote need css.
- #2419: TerminalInteractiveShell.__init__() ignores value of ipython_dir argument
- #1523: Better LaTeX printing in the qtconsole with the sympy profile
- #2719: ipython fails with `pkg_resources.DistributionNotFound: ipython==0.13`
- #2715: url crashes nbviewer.ipython.org
- #2555: «import» module completion on MacOSX
- #2707: Problem installing the new version of IPython in Windows
- #2696: SymPy magic bug in IPython Notebook
- #2684: pretty print broken for types created with `PyType_FromSpec`
- #2533: rmagic breaks on Windows
- #2661: Qtconsole tooltip is too wide when the function has many arguments
- #2679: ipython3 qtconsole via Homebrew on Mac OS X 10.8 - pyqt/pyside import error
- #2646: `pylab_not_importable`
- #2587: cython magic pops 2 CLI windows upon execution on Windows
- #2660: Certain arguments (-h, -help, -version) never passed to scripts run with ipython
- #2665: Missing docs for rmagic and some other extensions
- #2611: Travis wants to drop 3.1 support
- #2658: Incorrect parsing of raw multiline strings
- #2655: Test fails if `from __future__ import print_function` in `.pythonrc.py`
- #2651: nonlocal with no existing variable produces too many errors
- #2645: python3 is a pain (minor unicode bug)
- #2637: %paste in Python 3 on Mac doesn't work
- #2624: Error on launching IPython on Win 7 and Python 2.7.3
- #2608: disk IO activity on cursor press
- #1275: Markdown parses LaTeX math symbols as its formatting syntax in notebook
- #2613: `display(Math(...))` doesn't render tau correctly
- #925: Tab-completion in Qt console needn't use pager
- #2607: `%load_ext sympy.interactive.ipythonprinting` dammaging output
- #2593: Toolbar button to open qtconsole from notebook
- #2602: IPython html documentation for downloading
- #2598: ipython notebook `-pylab=inline` replaces built-in `any()`
- #2244: small issue: wrong printout
- #2590: add easier way to execute scripts in the current directory
- #2581: `%hist` does not work when `InteractiveShell.cache_size = 0`

- #2584: No file COPYING
- #2578: AttributeError: „module“ object has no attribute „TestCase“
- #2576: One of my notebooks won't load any more – is there a maximum notebook size?
- #2560: Notebook output is invisible when printing strings with `\r\n` line endings
- #2566: if pyside partially present ipython qtconsole fails to load even if pyqt4 present
- #1308: ipython qtconsole `-ssh=server -existing ...` hangs
- #1679: List command doesn't work in ipdb debugger the first time
- #2545: pypi win32 installer creates 64bit executibles
- #2080: Event loop issues with IPython 0.12 and PyQt4 (`QDialog.exec_` and more)
- #2541: Allow `python -m IPython`
- #2508: `subplots_adjust()` does not work correctly in ipython notebook
- #2289: Incorrect mathjax rendering of certain arrays of equations
- #2487: Selecting and indenting
- #2521: more fine-grained „run“ controls, such as „run from here“ and „run until here“
- #2535: Funny bounding box when plot with text
- #2523: History not working
- #2514: Issue with zooming in qtconsole
- #2220: No `sys.stdout.encoding` in kernel based IPython
- #2512: ERROR: Internal Python error in the inspect module.
- #2496: Function `passwd` does not work in QtConsole
- #1453: make engines reconnect/die when controller was restarted
- #2481: ipython notebook – clicking in a code cell's output moves the screen to the top of the code cell
- #2488: Undesired plot outputs in Notebook inline mode
- #2482: ipython notebook – download may not get the latest notebook
- #2471: `_subprocess` module removed in Python 3.3
- #2374: Issues with man pages
- #2316: `parallel.Client.__init__` should take `cluster_id` kwarg
- #2457: Can a R library wrapper be created with Rmagic?
- #1575: Fallback frontend for console when connecting `pylab=inline` -enabled kernel?
- #2097: Do not crash if history db is corrupted
- #2435: ipengines fail if `clean_logs` enabled
- #2429: Using `warnings.warn()` results in `TypeError`
- #2422: Multiprocessing in ipython notebook kernel crash
- #2426: ipython crashes with the following message. I do not what went wrong. Can you help me identify the problem?
- #2423: Docs typo?

- #2257: pip install -e fails
- #2418: rmagic can't run R's read.csv on data files with NA data
- #2417: HTML notebook: Backspace sometimes deletes multiple characters
- #2275: notebook: «Down_Arrow» on last line of cell should move to end of line
- #2414: 0.13.1 does not work with current EPD 7.3-2
- #2409: there is a redundant None
- #2410: Use /usr/bin/python3 instead of /usr/bin/python
- #2366: Notebook Dashboard -notebook-dir and fullpath
- #2406: Inability to get docstring in debugger
- #2398: Show line number for IndentationErrors
- #2314: HTML lists seem to interfere with the QtConsole display
- #1688: unicode exception when using %run with failing script
- #1884: IPython.embed changes color on error
- #2381: %time doesn't work for multiline statements
- #1435: Add size keywords in Image class
- #2372: interactiveshell.py misses urllib and io_open imports
- #2371: IPython not working
- #2367: Tab expansion moves to next cell in notebook
- #2359: nbviewer alters the order of print and display() output
- #2227: print name for IPython Notebooks has become uninformative
- #2361: client doesn't use connection file's „location“ in disambiguating „interface“
- #2357: failing traceback in terminal ipython for first exception
- #2343: Installing in a python 3.3b2 or python 3.3rc1 virtual environment.
- #2315: Failure in test: «Test we're not loading modules on startup that we shouldn't.»
- #2351: Multiple Notebook Apps: cookies not port specific, clash with each other
- #2350: running unittest from qtconsole prints output to terminal
- #2303: remote tracebacks broken since 952d0d6 (PR #2223)
- #2330: qtconsole does not highlight tab-completion suggestion with custom stylesheet
- #2325: Parsing Tex formula fails in Notebook
- #2324: Parsing Tex formula fails
- #1474: Add argument to run -n for custom namespace
- #2318: C-m n/p don't work in Markdown cells in the notebook
- #2309: time.time() in ipython notebook producing impossible results
- #2307: schedule tasks on newly arrived engines
- #2313: Allow Notebook HTML/JS to send messages to Python code
- #2304: ipengine throws KeyError: url

- #1878: shell access using ! will not fill class or function scope vars
- #2253: %paste does not retrieve clipboard contents under screen/tmux on OS X
- #1510: Add-on (or Monkey-patch) infrastructure for HTML notebook
- #2273: triple quote and %s at beginning of line with %paste
- #2243: Regression in .embed()
- #2266: SSH passwordless check with OpenSSH checks for the wrong thing
- #2217: Change NewNotebook handler to use 30x redirect
- #2276: config option for disabling history store
- #2239: can't use parallel.Reference in view.map
- #2272: Sympy piecewise messed up rendering
- #2252: %paste throws an exception with empty clipboard
- #2259: git-mpr is currently broken
- #2247: Variable expansion in shell commands should work in substrings
- #2026: Run „fast“ tests only
- #2241: read a list of notebooks on server and bring into browser only notebook
- #2237: please put python and text editor in the web only ipython
- #2053: Improvements to the IPython.display.Image object
- #1456: ERROR: Internal Python error in the inspect module.
- #2221: Avoid importing from IPython.parallel in core
- #2213: Can't trigger startup code in Engines
- #1464: Strange behavior for backspace with lines ending with more than 4 spaces in notebook
- #2187: NaN in object_info_reply JSON causes parse error
- #214: system command requiring administrative privileges
- #2195: Unknown option no-edit in git-mpr
- #2201: Add documentation build to tools/test_pr.py
- #2205: Command-line option for default Notebook output collapsing behavior
- #1927: toggle between inline and floating figures
- #2171: Can't start StarCluster after upgrading to IPython 0.13
- #2173: oct2py v >= 0.3.1 doesn't need h5py anymore
- #2099: storemagic needs to use self.shell
- #2166: DirectView map_sync() with Lambdas Using Generators
- #2091: Unable to use print_stats after %prun -r in notebook
- #2132: Add fail-over for pastebin
- #2156: Make it possible to install ipython without nasty gui dependencies
- #2154: Scrolled long output should be off in print view by default
- #2162: Tab completion does not work with IPython.embed_kernel()

- #2157: IPython 0.13 / github-master cannot create logfile from scratch
- #2151: missing newline when a magic is called from the qtconsole menu
- #2139: 00_notebook_tour Image example broken on master
- #2143: Add a %%cython_annotate magic
- #2135: Running IPython from terminal
- #2093: Makefile for building Sphinx documentation on Windows
- #2122: Bug in pretty printing
- #2120: Notebook «Make a Copy...» keeps opening duplicates in the same tab
- #1997: password cannot be used with url prefix
- #2129: help/doc displayed multiple times if requested in loop
- #2121: ipdb does not support input history in qtconsole
- #2114: %logstart doesn't log
- #2085: %ed magic fails in qtconsole
- #2119: IPython fails to run on MacOS Lion
- #2052: %pylab inline magic does not work on windows
- #2111: Ipython won't start on W7
- #2112: Strange internal traceback
- #2108: Backslash () at the end of the line behavior different from default Python
- #1425: Ampersands can't be typed sometimes in notebook cells
- #1513: Add expand/collapse support for long output elements like stdout and tracebacks
- #2087: error when starting ipython
- #2103: Ability to run notebook file from commandline
- #2082: Qt Console output spacing
- #2083: Test failures with Python 3.2 and PYTHONWARNINGS=»d»
- #2094: about inline
- #2077: Starting IPython3 on the terminal
- #1760: easy_install ipython fails on py3.2-win32
- #2075: Local Mathjax install causes iptest3 error under python3
- #2057: setup fails for python3 with LANG=C
- #2070: shebang on Windows
- #2054: sys_info missing git hash in sdists
- #2059: duplicate and modified files in documentation
- #2056: except-shadows-builtin osm.py:687
- #2058: hyphen-used-as-minus-sign in manpages

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

2.19 0.13 Series

2.19.1 Release 0.13

IPython 0.13 contains several major new features, as well as a large amount of bug and regression fixes. The previous version (0.12) was released on December 19 2011, and in this development cycle we had:


- ~6 months of work.
- 373 pull requests merged.
- 742 issues closed (non-pull requests).
- contributions from 62 authors.
- 1760 commits.
- a diff of 114226 lines.

The amount of work included in this release is so large, that we can only cover here the main highlights; please see our [detailed release statistics](#) for links to every issue and pull request closed on GitHub as well as a full list of individual contributors.

Major Notebook improvements: new user interface and more

The IPython Notebook, which has proven since its release to be wildly popular, has seen a massive amount of work in this release cycle, leading to a significantly improved user experience as well as many new features.

The first user-visible change is a reorganization of the user interface; the left panel has been removed and was replaced by a real menu system and a toolbar with icons. Both the toolbar and the header above the menu can be collapsed to leave an unobstructed working area:




The notebook handles very long outputs much better than before (this was a serious usability issue when running processes that generated massive amounts of output). Now, in the presence of outputs longer than ~100 lines, the notebook will automatically collapse to a scrollable area and the entire left part of this area controls the display: one click in this area will expand the output region completely, and a double-click will hide it completely. This figure shows both the scrolled and hidden modes:



Примечание: The auto-folding of long outputs is disabled in Firefox due to bugs in its scrolling behavior. See [PR #2047](#) for details.


Uploading notebooks to the dashboard is now easier: in addition to drag and drop (which can be finicky sometimes), you can now click on the upload text and use a regular file dialog box to select notebooks to upload. Furthermore, the notebook dashboard now auto-refreshes its contents and offers buttons to shut

down any running kernels ([PR #1739](#)):



Cluster management

The notebook dashboard can now also start and stop clusters, thanks to a new tab in the dashboard user interface:



This interface allows, for each profile you have configured, to start and stop a cluster (and optionally override the default number of engines corresponding to that configuration). While this hides all error reporting, once you have a configuration that you know works smoothly, it is a very convenient interface for controlling your parallel resources.

New notebook format

The notebooks saved now use version 3 of our format, which supports heading levels as well as the concept of „raw“ text cells that are not rendered as Markdown. These will be useful with [converters](#) we are developing, to pass raw markup (say LaTeX). That conversion code is still under heavy development and not quite ready for prime time, but we welcome help on this front so that we can merge it for full production use as soon as possible.

Примечание: v3 notebooks can *not* be read by older versions of IPython, but we provide a [simple script](#) that you can use in case you need to export a v3 notebook to share with a v2 user.

JavaScript refactoring

All the client-side JavaScript has been decoupled to ease reuse of parts of the machinery without having to build a full-blown notebook. This will make it much easier to communicate with an IPython kernel from existing web pages and to integrate single cells into other sites, without loading the full notebook document-like UI. [PR #1711](#).

This refactoring also enables the possibility of writing dynamic javascript widgets that are returned from Python code and that present an interactive view to the user, with callbacks in Javascript executing calls to the Kernel. This will enable many interactive elements to be added by users in notebooks.

An example of this capability has been provided as a proof of concept in `examples/widgets` that lets you directly communicate with one or more parallel engines, acting as a mini-console for parallel debugging and introspection.

Improved tooltips

The object tooltips have gained some new functionality. By pressing tab several times, you can expand them to see more of a docstring, keep them visible as you fill in a function's parameters, or transfer the information to the pager at the bottom of the screen. For the details, look at the example notebook `01_notebook_introduction.ipynb`.

Other improvements to the Notebook

These are some other notable small improvements to the notebook, in addition to many bug fixes and minor changes to add polish and robustness throughout:

- The notebook pager (the area at the bottom) is now Resizable by dragging its divider handle, a feature that had been requested many times by just about anyone who had used the notebook system. [PR #1705](#).
- It is now possible to open notebooks directly from the command line; for example: `ipython notebook path/` will automatically set `path/` as the notebook directory, and `ipython notebook path/foo.ipynb` will further start with the `foo.ipynb` notebook opened. [PR #1686](#).
- If a notebook directory is specified with `--notebook-dir` (or with the corresponding configuration flag `NotebookManager.notebook_dir`), all kernels start in this directory.
- Fix codemirror clearing of cells with `Ctrl-Z`; [PR #1965](#).
- Text (markdown) cells now line wrap correctly in the notebook, making them much easier to edit [PR #1330](#).
- PNG and JPEG figures returned from plots can be interactively resized in the notebook, by dragging them from their lower left corner. [PR #1832](#).
- Clear In `[]` prompt numbers on «Clear All Output». For more version-control-friendly `.ipynb` files, we now strip all prompt numbers when doing a «Clear all output». This reduces the amount of noise in commit-to-commit diffs that would otherwise show the (highly variable) prompt number changes. [PR #1621](#).
- The notebook server now requires *two* consecutive `Ctrl-C` within 5 seconds (or an interactive confirmation) to terminate operation. This makes it less likely that you will accidentally kill a long-running server by typing `Ctrl-C` in the wrong terminal. [PR #1609](#).
- Using `Ctrl-S` (or `Cmd-S` on a Mac) actually saves the notebook rather than providing the fairly useless browser html save dialog. [PR #1334](#).



Рис. 1: The new notebook tooltips.

- Allow accessing local files from the notebook (in urls), by serving any local file as the url `files/<relativepath>`. This makes it possible to, for example, embed local images in a notebook. [PR #1211](#).

Cell magics

We have completely refactored the magic system, finally moving the magic objects to standalone, independent objects instead of being the mixin class we'd had since the beginning of IPython ([PR #1732](#)). Now, a separate base class is provided in `IPython.core.magic.Magics` that users can subclass to create their own magics. Decorators are also provided to create magics from simple functions without the need for object orientation. Please see the [Magic command system](#) docs for further details.

All builtin magics now exist in a few subclasses that group together related functionality, and the new `IPython.core.magics` package has been created to organize this into smaller files.

This cleanup was the last major piece of deep refactoring needed from the original 2001 codebase.

We have also introduced a new type of magic function, prefixed with `%%` instead of `%`, which operates at the whole-cell level. A cell magic receives two arguments: the line it is called on (like a line magic) and the body of the cell below it.

Cell magics are most natural in the notebook, but they also work in the terminal and qt console, with the usual approach of using a blank line to signal cell termination.

For example, to time the execution of several statements:

```
%%timeit x = 0    # setup
for i in range(100000):
    x += i**2
```

This is particularly useful to integrate code in another language, and cell magics already exist for shell scripts, Cython, R and Octave. Using `%%script /usr/bin/foo`, you can run a cell in any interpreter that accepts code via stdin.

Another handy cell magic makes it easy to write short text files: `%%file ~/save/to/here.txt`.

The following cell magics are now included by default; all those that use special interpreters (Perl, Ruby, bash, etc.) assume you have the requisite interpreter installed:

- `%%!`: run cell body with the underlying OS shell; this is similar to prefixing every line in the cell with `!`.
- `%%bash`: run cell body under bash.
- `%%capture`: capture the output of the code in the cell (and stderr as well). Useful to run codes that produce too much output that you don't even want scrolled.
- `%%file`: save cell body as a file.
- `%%perl`: run cell body using Perl.
- `%%prun`: run cell body with profiler (cell extension of `%prun`).
- `%%python3`: run cell body using Python 3.
- `%%ruby`: run cell body using Ruby.
- `%%script`: run cell body with the script specified in the first line.
- `%%sh`: run cell body using sh.
- `%%sx`: run cell with system shell and capture process output (cell extension of `%sx`).
- `%%system`: run cell with system shell (`%%!` is an alias to this).

- `%%timeit`: time the execution of the cell (extension of `%timeit`).

This is what some of the script-related magics look like in action:

IPython also creates aliases for a few common interpreters, such as `bash`, `ruby`, `perl`, etc.

These are all equivalent to `%%script <name>`

```
In [4]: %%ruby
puts "Hello from Ruby #{RUBY_VERSION}"

Hello from Ruby 1.8.7
```

```
In [5]: %%bash
echo "hello from $BASH"

hello from /usr/local/bin/bash
```

In addition, we have also a number of *extensions* that provide specialized magics. These typically require additional software to run and must be manually loaded via `%load_ext <extension name>`, but are extremely useful. The following extensions are provided:

Cython magics (extension `cythonmagic`)

This extension provides magics to automatically build and compile Python extension modules using the [Cython](#) language. You must install Cython separately, as well as a C compiler, for this to work. The examples directory in the source distribution ships with a full notebook demonstrating these capabilities:

The %cython magic

Probably the most important magic is the %cython magic. This is similar to the %%cython_pyximport magic, but doesn't require you to specify a module name. Instead, the %%cython magic uses manages everything using temporary files in the ~/.cython/magic directory. All of the symbols in the Cython module are imported automatically by the magic.

Here is a simple example of a Black-Scholes options pricing algorithm written in Cython:

```
In [6]: %%cython
import cython
from libc.math cimport exp, sqrt, pow, log, erf

@cython.cdivision(True)
cdef double std_norm_cdf(double x) nogil:
    return 0.5*(1+erf(x/sqrt(2.0)))

@cython.cdivision(True)
def black_scholes(double s, double k, double t, double v,
                  double rf, double div, double cp):
    """Price an option using the Black-Scholes model.

    s : initial stock price
    k : strike price
    t : expiration time
    v : volatility
    rf : risk-free rate
    div : dividend
    cp : +1/-1 for call/put
    """
    cdef double d1, d2, optprice
    with nogil:
        d1 = (log(s/k)+(rf-div+0.5*pow(v,2))*t)/(v*sqrt(t))
        d2 = d1 - v*sqrt(t)
        optprice = cp*s*exp(-div*t)*std_norm_cdf(cp*d1) - \
            cp*k*exp(-rf*t)*std_norm_cdf(cp*d2)
    return optprice
```

```
In [7]: black_scholes(100.0, 100.0, 1.0, 0.3, 0.03, 0.0, -1)
```


```
Out[7]: 10.327861752731728
```

```
In [8]: %timeit black_scholes(100.0, 100.0, 1.0, 0.3, 0.03, 0.0, -1)
```

```
1000000 loops, best of 3: 821 ns per loop
```


Octave magics (extension octavemagic)

This extension provides several magics that support calling code written in the [Octave](#) language for numerical computing. You can execute single-lines or whole blocks of Octave code, capture both output and figures inline (just like matplotlib plots), and have variables automatically converted between the two languages. To use this extension, you must have Octave installed as well as the [oct2py](#) package. The examples directory in the source distribution ships with a full notebook demonstrating these capabilities:



R magics (extension rmagic)

This extension provides several magics that support calling code written in the [R](#) language for statistical data analysis. You can execute single-lines or whole blocks of R code, capture both output and figures inline (just like matplotlib plots), and have variables automatically converted between the two languages. To use this extension, you must have R installed as well as the [rpy2](#) package that bridges Python and R. The examples directory in the source distribution ships with a full notebook demonstrating these capabilities:



Tab completer improvements

Useful tab-completion based on live inspection of objects is one of the most popular features of IPython. To make this process even more user-friendly, the completers of both the Qt console and the Notebook have been reworked.

The Qt console comes with a new ncurses-like tab completer, activated by default, which lets you cycle through the available completions by pressing tab, or select a completion with the arrow keys (PR #1851).

In the notebook, completions are now sourced both from object introspection and analysis of surrounding code, so limited completions can be offered for variables defined in the current cell, or while the kernel is busy (PR #1711).

```
In [2]: import numpy.random as random

In [3]: numpy.random.<tab>
...      ...      ...      ...
beta      logistic power      standard_exponential
binomial  lognormal rand      standard_gamma
bytes     logseries randint   standard_normal
chisquare mtrand  randn    standard_t
dirichlet multinomial random    test
exponential multivariate_normal random_integers triangular
f         negative_binomial random_sample uniform
...      ...      ...      ...
```

Рис. 2: The new improved Qt console's ncurses-like completer allows to easily navigate thought long list of completions.

We have implemented a new configurable flag to control tab completion on modules that provide the `__all__` attribute:

```
IPCompleter.limit_to__all__= Boolean
```

This instructs the completer to honor `__all__` for the completion. Specifically, when completing on `object.<tab>`, if `True`: only those names in `obj.__all__` will be included. When `False` [default]: the `__all__` attribute is ignored. [PR #1529](#).

Improvements to the Qt console

The Qt console continues to receive improvements and refinements, despite the fact that it is by now a fairly mature and robust component. Lots of small polish has gone into it, here are a few highlights:

- A number of changes were made to the underlying code for easier integration into other projects such as [Spyder \(PR #2007, PR #2024\)](#).
- Improved menus with a new Magic menu that is organized by magic groups (this was made possible by the reorganization of the magic system internals). [PR #1782](#).
- Allow for restarting kernels without clearing the qtconsole, while leaving a visible indication that the kernel has restarted. [PR #1681](#).
- Allow the native display of jpeg images in the qtconsole. [PR #1643](#).

Parallel

The parallel tools have been improved and fine-tuned on multiple fronts. Now, the creation of an `IPython.parallel.Client` object automatically activates a line and cell magic function `%px` that sends its code to all the engines. Further magics can be easily created with the `Client.activate()` method, to conveniently execute code on any subset of engines. [PR #1893](#).

The `%px` cell magic can also be given an optional `targets` argument, as well as a `--out` argument for storing its output.

A new magic has also been added, `%pxconfig`, that lets you configure various defaults of the parallel magics. As usual, type `%pxconfig?` for details.

The exception reporting in parallel contexts has been improved to be easier to read. Now, IPython directly reports the remote exceptions without showing any of the internal execution parts:

```
In [1]: from IPython.parallel import Client
        c = Client()

In [2]: %px 1/0

[0:execute]:
-----
ZeroDivisionError                                Traceback (most recent call
last)<ipython-input-1-05c9758a9c21> in <module>()
----> 1 1/0
ZeroDivisionError: integer division or modulo by zero

[1:execute]:
-----
ZeroDivisionError                                Traceback (most recent call
last)<ipython-input-1-05c9758a9c21> in <module>()
----> 1 1/0
ZeroDivisionError: integer division or modulo by zero
```

The parallel tools now default to using NoDB as the storage backend for intermediate results. This means that the default usage case will have a significantly reduced memory footprint, though certain advanced features are not available with this backend.

The parallel magics now display all output, so you can do parallel plotting or other actions with complex display. The `px` magic has now both line and cell modes, and in cell mode finer control has been added about how to collate output from multiple engines. [PR #1768](#).

There have also been incremental improvements to the SSH launchers:

- add to `_send/fetch` steps for moving connection files around.
- add `SSHProxyEngineSetLauncher`, for invoking to `ipcluster engines` on a remote host. This can be used to start a set of engines via `PBS/SGE/MPI remotely`.

This makes the `SSHLauncher` usable on machines without shared filesystems.

A number of „sugar“ methods/properties were added to `AsyncResult` that are quite useful ([PR #1548](#)) for everyday work:

- `ar.wall_time` = received - submitted
- `ar.serial_time` = sum of serial computation time
- `ar.elapsed` = time since submission (`wall_time` if done)
- `ar.progress` = (int) number of sub-tasks that have completed
- `len(ar)` = # of tasks
- `ar.wait_interactive()`: prints progress

Added `Client.spin_thread()` / `stop_spin_thread()` for running spin in a background thread, to keep zmq queue clear. This can be used to ensure that timing information is as accurate as possible (at the cost of having a background thread active).

Set `TaskScheduler.hwm` default to 1 instead of 0. 1 has more predictable/intuitive behavior, if often slower, and thus a more logical default. Users whose workloads require maximum throughput and are largely homogeneous in time per task can make the optimization themselves, but now the behavior will be less surprising to new users. [PR #1294](#).

Kernel/Engine unification

This is mostly work „under the hood“, but it is actually a *major* achievement for the project that has deep implications in the long term: at last, we have unified the main object that executes as the user’s interactive shell (which we refer to as the *IPython kernel*) with the objects that run in all the worker nodes of the parallel computing facilities (the *IPython engines*). Ever since the first implementation of IPython’s parallel code back in 2006, we had wanted to have these two roles be played by the same machinery, but a number of technical reasons had prevented that from being true.

In this release we have now merged them, and this has a number of important consequences:

- It is now possible to connect any of our clients (qtconsole or terminal console) to any individual parallel engine, with the *exact* behavior of working at a „regular“ IPython console/qtconsole. This makes debugging, plotting, etc. in parallel scenarios vastly easier.
- Parallel engines can always execute arbitrary „IPython code“, that is, code that has magics, shell extensions, etc. In combination with the `%%px` magics, it is thus extremely natural for example to send to all engines a block of Cython or R code to be executed via the new Cython and R magics. For example, this snippet would send the R block to all active engines in a cluster:

```
%%px
%%R
... R code goes here
```

- It is possible to embed not only an interactive shell with the `IPython.embed()` call as always, but now you can also embed a *kernel* with `IPython.embed_kernel()`. Embedding an IPython kernel in an application is useful when you want to use `IPython.embed()` but don’t have a terminal attached on stdin and stdout.
- The new `IPython.parallel.bind_kernel()` allows you to promote Engines to listening Kernels, and connect QtConsoles to an Engine and debug it directly.

In addition, having a single core object through our entire architecture also makes the project conceptually cleaner, easier to maintain and more robust. This took a lot of work to get in place, but we are thrilled to have this major piece of architecture finally where we’d always wanted it to be.

Official Public API

We have begun organizing our API for easier public use, with an eye towards an official IPython 1.0 release which will firmly maintain this API compatible for its entire lifecycle. There is now an `IPython.display` module that aggregates all display routines, and the `traitlets.config` namespace has all public configuration tools. We will continue improving our public API layout so that users only need to import names one level deeper than the main IPython package to access all public namespaces.

IPython notebook file icons

The directory `docs/resources` in the source distribution contains SVG and PNG versions of our file icons, as well as an `Info.plist.example` file with instructions to install them on Mac OSX. This is a first draft of our icons, and we encourage contributions from users with graphic talent to improve them in the future.

New top-level `locate` command

Add `locate` entry points; these would be useful for quickly locating IPython directories and profiles from other (non-Python) applications. [PR #1762](#).

Examples:

```
$> ipython locate
/Users/me/.ipython

$> ipython locate profile foo
/Users/me/.ipython/profile_foo

$> ipython locate profile
/Users/me/.ipython/profile_default

$> ipython locate profile dne
[ProfileLocate] Profile u'dne' not found.
```

Other new features and improvements

- `%install_ext`: A new magic function to install an IPython extension from a URL. E.g. `%install_ext https://bitbucket.org/birkenfeld/ipython-physics/raw/default/physics.py`.
- The `%loadpy` magic is no longer restricted to Python files, and has been renamed `%load`. The old name remains as an alias.
- New command line arguments will help external programs find IPython folders: `ipython locate` finds the user's IPython directory, and `ipython locate profile foo` finds the folder for the „foo“ profile (if it exists).
- The `IPYTHON_DIR` environment variable, introduced in the Great Reorganization of 0.11 and existing only in versions 0.11-0.13, has been deprecated. As described in [PR #1167](#), the complexity and confusion of migrating to this variable is not worth the aesthetic improvement. Please use the historical `IPYTHONDIR` environment variable instead.
- The default value of *interactivity* passed from `run_cell()` to `run_ast_nodes()` is now configurable.
- New `%alias_magic` function to conveniently create aliases of existing magics, if you prefer to have shorter names for personal use.
- We ship unminified versions of the JavaScript libraries we use, to better comply with Debian's packaging policies.
- Simplify the information presented by `obj?/obj??` to eliminate a few redundant fields when possible. [PR #2038](#).
- Improved continuous integration for IPython. We now have automated test runs on [Shining Panda](#) and [Travis-CI](#), as well as [Tox support](#).
- The `vim-ipython` functionality (externally developed) has been updated to the latest version.
- The `%save` magic now has a `-f` flag to force overwriting, which makes it much more usable in the notebook where it is not possible to reply to interactive questions from the kernel. [PR #1937](#).
- Use `dvipng` to format `sympy.Matrix`, enabling display of matrices in the Qt console with the `sympy` printing extension. [PR #1861](#).

- Our messaging protocol now has a reasonable test suite, helping ensure that we don't accidentally deviate from the spec and possibly break third-party applications that may have been using it. We encourage users to contribute more stringent tests to this part of the test suite. [PR #1627](#).
- Use LaTeX to display, on output, various built-in types with the SymPy printing extension. [PR #1399](#).
- Add Gtk3 event loop integration and example. [PR #1588](#).
- `clear_output` improvements, which allow things like progress bars and other simple animations to work well in the notebook ([PR #1563](#)):
 - `clear_output()` clears the line, even in terminal IPython, the QtConsole and plain Python as well, by printing `r` to streams.
 - `clear_output()` avoids the flicker in the notebook by adding a delay, and firing immediately upon the next actual display message.
 - `display_javascript` hides its `output_area` element, so using `display` to run a bunch of javascript doesn't result in ever-growing vertical space.
- Add simple support for running inside a virtualenv. While this doesn't supplant proper installation (as users should do), it helps ad-hoc calling of IPython from inside a virtualenv. [PR #1388](#).

Major Bugs fixed

In this cycle, we have *closed over 740 issues*, but a few major ones merit special mention:

- The `%pastebin` magic has been updated to point to gist.github.com, since unfortunately <http://paste.pocoo.org> has closed down. We also added a `-d` flag for the user to provide a gist description string. [PR #1670](#).
- Fix `%paste` that would reject certain valid inputs. [PR #1258](#).
- Fix sending and receiving of Numpy structured arrays (those with composite dtypes, often used as recarrays). [PR #2034](#).
- Reconnect when the websocket connection closes unexpectedly. [PR #1577](#).
- Fix truncated representation of objects in the debugger by showing at least 80 characters' worth of information. [PR #1793](#).
- Fix logger to be Unicode-aware: logging could crash ipython if there was unicode in the input. [PR #1792](#).
- Fix images missing from XML/SVG export in the Qt console. [PR #1449](#).
- Fix deepreload on Python 3. [PR #1625](#), as well as having a much cleaner and more robust implementation of deepreload in general. [PR #1457](#).

Backwards incompatible changes

- The exception `IPython.core.error.TryNext` previously accepted arguments and keyword arguments to be passed to the next implementation of the hook. This feature was removed as it made error message propagation difficult and violated the principle of loose coupling.

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

2.20 Issues closed in the 0.13 development cycle

2.20.1 Issues closed in 0.13

GitHub stats since IPython 0.12 (2011/12/19 - 2012/06/30)

These lists are automatically generated, and may be incomplete or contain duplicates.

The following 62 authors contributed 1760 commits.

- Aaron Culich
- Aaron Meurer
- Alex Kramer
- Andrew Giessel
- Andrew Straw
- André Matos
- Aron Ahmadi
- Ben Edwards
- Benjamin Ragan-Kelley
- Bradley M. Froehle
- Brandon Parsons
- Brian E. Granger
- Carlos Cordoba
- David Hirschfeld
- David Zderic
- Ernie French
- Fernando Perez
- Ian Murray
- Jason Grout
- Jens H Nielsen
- Jez Ng
- Jonathan March
- Jonathan Taylor
- Julian Taylor

- Jörgen Stenarson
- Kent Inverarity
- Marc Abramowitz
- Mark Wiebe
- Matthew Brett
- Matthias BUSSONNIER
- Michael Droettboom
- Mike Hansen
- Nathan Rice
- Pankaj Pandey
- Paul
- Paul Ivanov
- Piotr Zolnierczuk
- Piti Ongmongkolkul
- Puneeth Chaganti
- Robert Kern
- Ross Jones
- Roy Hyunjin Han
- Scott Tsai
- Skipper Seabold
- Stefan van der Walt
- Steven Johnson
- Takafumi Arakaki
- Ted Wright
- Thomas Hisch
- Thomas Kluyver
- Thomas Spura
- Thomi Richards
- Tim Couper
- Timo Paulssen
- Toby Gilham
- Tony S Yu
- W. Trevor King
- Walter Doerwald
- anatoly techtonik
- fawce

- [mcelrath](#)
- [wilsaj](#)

We closed a total of 1115 issues, 373 pull requests and 742 regular issues; this is the full list (generated with the script `tools/github_stats.py`):

Pull Requests (373):

- [PR #1943](#): add screenshot and link into releasenotes
- [PR #1954](#): update some example notebooks
- [PR #2048](#): move `_encode_binary` to `jsonutil.encode_images`
- [PR #2050](#): only add quotes around xunit-file on Windows
- [PR #2047](#): disable auto-scroll on mozilla
- [PR #2015](#): Fixes for `%paste` with special transformations
- [PR #2046](#): Iptest unicode
- [PR #1939](#): Namespaces
- [PR #2042](#): increase auto-scroll threshold to 100 lines
- [PR #2043](#): move `RemoteError` import to top-level
- [PR #2036](#): `%alias_magic`
- [PR #1968](#): Proposal of icons for `.ipynb` files
- [PR #2037](#): remove `ipython-qtconsole` gui-script
- [PR #2038](#): add extra clear warning to shell doc
- [PR #2029](#): Ship unminified js
- [PR #2007](#): Add `custom_control` and `custom_page_control` variables to override the Qt widgets used by `qtconsole`
- [PR #2034](#): fix&test push/pull recarrays
- [PR #2028](#): Reduce unhelpful information shown by `pinf`
- [PR #2030](#): check wxPython version in `inputhook`
- [PR #2024](#): Make `interactive_usage` a bit more rst friendly
- [PR #2031](#): disable `^C^C` confirmation on Windows
- [PR #2027](#): match stdin encoding in frontend readline test
- [PR #2025](#): Fix parallel test on WinXP - wait for resource cleanup.
- [PR #2016](#): BUG: test runner fails in Windows if filenames contain spaces.
- [PR #2020](#): Fix home path expansion test in Windows.
- [PR #2021](#): Fix Windows pathname issue in „odd encoding“ test.
- [PR #2022](#): don't check writability in test for `get_home_dir` when `HOME` is undefined
- [PR #1996](#): frontend test tweaks
- [PR #2014](#): relax profile regex in notebook
- [PR #2012](#): Mono cursor offset
- [PR #2004](#): Clarify generic message spec vs. Python message API in docs

- PR #2010: notebook: Print a warning (but do not abort) if no webbrowser can be found.
- PR #2002: Refactor %magic into a lsmagic_docs API function.
- PR #1999: %magic help: display line and cell magics in alphabetical order.
- PR #1981: Clean BG processes created by %%script on kernel exit
- PR #1994: Fix RST misformatting.
- PR #1951: minor notebook startup/notebook-dir adjustments
- PR #1974: Allow path completion on notebook.
- PR #1964: allow multiple instances of a Magic
- PR #1991: fix _ofind attr in %page
- PR #1988: check for active frontend in update_restart_checkbox
- PR #1979: Add support for tox (<https://tox.readthedocs.io/>) and Travis CI (<http://travis-ci.org/>)
- PR #1970: dblclick to restore size of images
- PR #1978: Notebook names truncating at the first period
- PR #1825: second attempt at scrolled long output
- PR #1934: Cell/Worksheet metadata
- PR #1746: Confirm restart (configuration option, and checkbox UI)
- PR #1944: [qtconsole] take %%% prefix into account for completion
- PR #1973: fix another FreeBSD \$HOME symlink issue
- PR #1967: Fix psums example description in docs
- PR #1965: fix for #1678, undo no longer clears cells
- PR #1952: avoid duplicate «Websockets closed» dialog on ws close
- PR #1962: Support unicode prompts
- PR #1955: update to latest version of vim-ipython
- PR #1945: Add -proc option to %%script
- PR #1956: move import RemoteError after get_exc_info
- PR #1950: Fix for copy action (Ctrl+C) when there is no pager defined in qtconsole
- PR #1948: Fix help string for InteractiveShell.ast_node_interactivity
- PR #1942: swallow stderr of which in utils.process.find_cmd
- PR #1940: fix completer css on some Chrome versions
- PR #1938: remove remaining references to deprecated XREP/XREQ names
- PR #1925: Fix styling of superscripts and subscripts. Closes #1924.
- PR #1936: increase duration of save messages
- PR #1937: add %save -f
- PR #1935: add version checking to pyreadline import test
- PR #1849: Octave magics
- PR #1759: github, merge PR(s) just by number(s)

- PR #1931: Win py3fixes
- PR #1933: oinspect.find_file: Additional safety if file cannot be found.
- PR #1932: Fix adding functions to CommandChainDispatcher with equal priority on Py 3
- PR #1928: Select NoDB by default
- PR #1923: Add IPython syntax support to the %timeit magic, in line and cell mode
- PR #1926: Make completer recognize escaped quotes in strings.
- PR #1893: Update Parallel Magics and Exception Display
- PR #1921: magic_arguments: dedent but otherwise preserve indentation.
- PR #1919: Use oinspect in CodeMagics._find_edit_target
- PR #1918: don't warn in iptest if deathrow/quarantine are missing
- PR #1917: Fix for %pdef on Python 3
- PR #1913: Fix for #1428
- PR #1911: temporarily skip autoreload tests
- PR #1909: Fix for #1908, use os.path.normcase for safe filename comparisons
- PR #1907: py3compat fixes for %%script and tests
- PR #1906: ofind finds non-unique cell magics
- PR #1845: Fixes to inspection machinery for magics
- PR #1902: Workaround fix for gh-1632; minimal revert of gh-1424
- PR #1900: Cython libs
- PR #1899: add ScriptMagics to class list for generated config
- PR #1898: minimize manpages
- PR #1897: use glob for bad exclusion warning
- PR #1855: %%script and %%file magics
- PR #1870: add %%capture for capturing stdout/err
- PR #1861: Use dvipng to format sympy.Matrix
- PR #1867: Fix 1px margin bouncing of selected menu item.
- PR #1889: Reconnect when the websocket connection closes unexpectedly
- PR #1886: Fix a bug in renaming notebook
- PR #1895: Fix error in test suite with ip.system()
- PR #1762: add locate entry points
- PR #1883: Fix vertical offset due to bold/italics, and bad browser fonts.
- PR #1875: re-write columnize, with intermediate step.
- PR #1851: new completer for qtconsole.
- PR #1892: Remove suspicious quotes in interactiveshell.py
- PR #1864: Rmagic exceptions
- PR #1829: [notebook] don't care about leading prct in completion

- PR #1832: Make svg, jpeg and png images resizable in notebook.
- PR #1674: HTML Notebook carriage-return handling, take 2
- PR #1882: Remove importlib dependency which not available in Python 2.6.
- PR #1879: Correct stack depth for variable expansion in !system commands
- PR #1841: [notebook] deduplicate completion results
- PR #1850: Remove args/kwargs handling in TryNext, fix %paste error messages.
- PR #1663: Keep line-endings in ipynb
- PR #1815: Make : invalid in filenames in the Notebook JS code.
- PR #1819: doc: cleanup the parallel psums example a little
- PR #1839: External cleanup
- PR #1782: fix Magic menu in qtconsole, split in groups
- PR #1862: Minor bind_kernel improvements
- PR #1857: Prevent jumping of window to input when output is clicked.
- PR #1856: Fix 1px jumping of cells and menus in Notebook.
- PR #1852: fix chained resubmissions
- PR #1780: Rmagic extension
- PR #1847: add InlineBackend to ConsoleApp class list
- PR #1836: preserve header for resubmitted tasks
- PR #1828: change default extension to .ipy for %save -r
- PR #1800: Reintroduce recall
- PR #1830: lsmagic lists magics in alphabetical order
- PR #1773: Update SymPy profile: SymPy's latex() can now print set and frozenset
- PR #1761: Edited documentation to use IPYTHONDIR in place of ~/.ipython
- PR #1822: aesthetics pass on AsyncResult.display_outputs
- PR #1821: ENTER submits the rename notebook dialog.
- PR #1820: NotebookApp: Make the number of ports to retry user configurable.
- PR #1816: Always use filename as the notebook name.
- PR #1813: Add assert_in method to nose for Python 2.6
- PR #1711: New Tooltip, New Completer and JS Refactor
- PR #1798: a few simple fixes for docs/parallel
- PR #1812: Ensure AsyncResult.display_outputs doesn't display empty streams
- PR #1811: warn on nonexistent exclusions in iptest
- PR #1810: fix for #1809, failing tests in IPython.zmq
- PR #1808: Reposition alternate upload for firefox [need cross browser/OS/language test]
- PR #1742: Check for custom_exceptions only once
- PR #1807: add missing cython exclusion in iptest

- PR #1805: Fixed a vcvarsall.bat error on win32/Py2.7 when trying to compile with m...
- PR #1739: Dashboard improvement (necessary merge of #1658 and #1676 + fix #1492)
- PR #1770: Cython related magic functions
- PR #1707: Accept `-gui=<...>` switch in IPython qtconsole.
- PR #1797: Fix comment which breaks Emacs syntax highlighting.
- PR #1795: fix `%gui` magic
- PR #1793: Raise repr limit for strings to 80 characters (from 30).
- PR #1794: don't use XDG path on OS X
- PR #1792: Unicode-aware logger
- PR #1791: update zmqshell magics
- PR #1787: DOC: Remove regression from qt-console docs.
- PR #1758: test_pr, fallback on http if git protocol fail, and SSL errors...
- PR #1748: Fix some tests for Python 3.3
- PR #1755: test for pygments before running qt tests
- PR #1771: Make default value of interactivity passed to `run_ast_nodes` configurable
- PR #1784: restore loadpy to load
- PR #1768: Update parallel magics
- PR #1779: Tidy up error raising in magic decorators.
- PR #1769: Allow cell mode timeit without setup code.
- PR #1716: Fix for fake filenames in verbose traceback
- PR #1763: [qtconsole] fix `append_plain_html` -> `append_html`
- PR #1732: Refactoring of the magics system and implementation of cell magics
- PR #1630: Merge divergent Kernel implementations
- PR #1705: [notebook] Make pager resizable, and remember size...
- PR #1606: Share code for `%pycat` and `%loadpy`, make `%pycat` aware of URLs
- PR #1757: Open IPython notebook hyperlinks in a new window using `target=_blank`
- PR #1754: Fix typo `enconters`->`encounters`
- PR #1753: Clear window title when kernel is restarted
- PR #1449: Fix for bug #735 : Images missing from XML/SVG export
- PR #1743: Tooltip completer js refactor
- PR #1681: add qt config option to `clear_on_kernel_restart`
- PR #1733: Tooltip completer js refactor
- PR #1727: terminate kernel after `embed_kernel` tests
- PR #1737: add HistoryManager to ipapp class list
- PR #1686: ENH: Open a notebook from the command line
- PR #1709: fixes #1708, failing test in `arg_split` on windows

- PR #1718: Use CRegExp trait for regular expressions.
- PR #1729: Catch failure in repr() for %whos
- PR #1726: use eval for command-line args instead of exec
- PR #1724: fix scatter/gather with targets="all"
- PR #1725: add -no-ff to git pull in test_pr
- PR #1721: Tooltip completer js refactor
- PR #1657: Add wait optional argument to hooks.editor
- PR #1717: Define generic sys.ps{1,2,3}, for use by scripts.
- PR #1691: Finish PR #1446
- PR #1710: update MathJax CDN url for https
- PR #1713: Make autocall regexp's configurable.
- PR #1703: Allow TryNext to have an error message without it affecting the command chain
- PR #1714: minor adjustments to test_pr
- PR #1704: ensure all needed qt parts can be imported before settling for one
- PR #1706: Mark test_push_numpy_nocopy as a known failure for Python 3
- PR #1698: fix tooltip on token with number
- PR #1245: pythonw py3k fixes for issue #1226
- PR #1685: Add script to test pull request
- PR #1693: deprecate IPYTHON_DIR in favor of IPYTHONDIR
- PR #1695: Avoid deprecated warnings from ipython-qtconsole.desktop.
- PR #1694: Add quote to notebook to allow it to load
- PR #1689: Fix sys.path missing „“ as first entry in ipython kernel.
- PR #1687: import Binary from bson instead of pymongo
- PR #1616: Make IPython.core.display.Image less notebook-centric
- PR #1684: CLN: Remove redundant function definition.
- PR #1670: Point %pastebin to gist
- PR #1669: handle pyout messages in test_message_spec
- PR #1295: add binary-tree engine interconnect example
- PR #1642: Cherry-picked commits from 0.12.1 release
- PR #1659: Handle carriage return characters (»r») in HTML notebook output.
- PR #1656: ensure kernels are cleaned up in embed_kernel tests
- PR #1664: InteractiveShell.run_code: Update docstring.
- PR #1662: Delay flushing softspace until after cell finishes
- PR #1643: handle jpg/jpeg in the qtconsole
- PR #1652: add patch_pyzmq() for backporting a few changes from newer pyzmq
- PR #1650: DOC: moving files with SSH launchers

- PR #1357: add `IPython.embed_kernel()`
- PR #1640: Finish up `embed_kernel`
- PR #1651: Remove bundled `Itpl` module
- PR #1634: incremental improvements to SSH launchers
- PR #1649: move `examples/test_embed` into `examples/tests/embed`
- PR #1633: Fix installing extension from local file on Windows
- PR #1645: Exclude `UserDict` when deep reloading `NumPy`.
- PR #1637: Removed a „“ which shouldn't have been there
- PR #1631: TST: `QApplication` doesn't quit early enough with `PySide`.
- PR #1629: evaluate a few dangling `validate_message` generators
- PR #1621: clear `In[]` prompt numbers on «Clear All Output»
- PR #1627: Test the Message Spec
- PR #1624: Fixes for byte-compilation on Python 3
- PR #1615: Add `show()` method to figure objects.
- PR #1625: Fix deepreload on Python 3
- PR #1620: `pyin` message now have `execution_count`
- PR #1457: Update deepreload to use a rewritten `knee.py`. Fixes `dreload(numpy)`.
- PR #1613: allow `map / parallel` function for single-engine views
- PR #1609: exit notebook cleanly on `SIGINT`, `SIGTERM`
- PR #1607: cleanup `sqlitedb` temporary db file after tests
- PR #1608: don't rely on `timedelta.total_seconds` in `AsyncResult`
- PR #1599: Fix for `%run -d` on Python 3
- PR #1602: Fix `%env` magic on Python 3.
- PR #1603: Remove `python3` profile
- PR #1604: Exclude `IPython.quarantine` from installation
- PR #1600: Specify encoding for `io.open` in `notebook_reformat` tests
- PR #1605: Small fixes for Animation and Progress notebook
- PR #1529: `__all__` feature, improvement to `dir2`, and tests for both
- PR #1548: add sugar methods/properties to `AsyncResult`
- PR #1535: Fix pretty printing dispatch
- PR #1399: Use LaTeX to print various built-in types with the `SymPy` printing extension
- PR #1597: re-enter `kernel.eventloop` after catching `SIGINT`
- PR #1490: rename plaintext cell -> raw cell
- PR #1480: Fix `%notebook` magic, etc. `nbformat` unicode tests and fixes
- PR #1588: `Gtk3` integration with `ipython` works.
- PR #1595: Examples syntax (avoid errors installing on Python 3)

- PR #1526: Find encoding for Python files
- PR #1594: Fix writing git commit ID to a file on build with Python 3
- PR #1556: shallow-copy DictDB query results
- PR #1502: small changes in response to pyflakes pass
- PR #1445: Don't build sphinx docs for sdists
- PR #1538: store git commit hash in `utils._sysinfo` instead of hidden data file
- PR #1546: attempt to suppress exceptions in channel threads at shutdown
- PR #1559: update `tools/github_stats.py` to use GitHub API v3
- PR #1563: `clear_output` improvements
- PR #1560: remove obsolete discussion of Twisted/trial from testing docs
- PR #1569: BUG: `qtconsole` – non-standard handling of a and b. [Fixes #1561]
- PR #1573: BUG: Ctrl+C crashes wx pylab kernel in `qtconsole`.
- PR #1568: fix PR #1567
- PR #1567: Fix: `openssh_tunnel` did not parse port in `server`
- PR #1565: fix `AsyncResult.abort`
- PR #1552: use `os.getcwd` in `NotebookManager`
- PR #1541: `display_pub` flushes `stdout/err`
- PR #1544: make `MultiKernelManager.kernel_manager_class` configurable
- PR #1517: Fix indentation bug in `IPython/lib/pretty.py`
- PR #1519: BUG: Include the name of the exception type in its pretty format.
- PR #1489: Fix zero-copy push
- PR #1477: fix dangling `buffer` in `IPython.parallel.util`
- PR #1514: DOC: Fix references to `IPython.lib.pretty` instead of the old location
- PR #1481: BUG: Improve placement of `CallTipWidget`
- PR #1496: BUG: LBYL when clearing the output history on shutdown.
- PR #1508: fix sorting profiles in `clustermanager`
- PR #1495: BUG: Fix pretty-printing for overzealous objects
- PR #1472: more general fix for #662
- PR #1483: updated `magic_history` docstring
- PR #1383: First version of cluster web service.
- PR #1398: fix `%tb` after `SyntaxError`
- PR #1440: Fix for failing testsuite when using `-with-xml-coverage` on windows.
- PR #1419: Add `%install_ext` magic function.
- PR #1424: Win32 shell interactivity
- PR #1468: Simplify structure of a Job in the `TaskScheduler`
- PR #1447: 1107 - Tab autocompletion can suggest invalid syntax

- PR #1469: Fix typo in comment (insert space)
- PR #1463: Fix completion when importing modules in the cwd.
- PR #1466: Fix for issue #1437, unfriendly windows qtconsole error handling
- PR #1432: Fix ipython directive
- PR #1465: allow `ipython help subcommand` syntax
- PR #1416: Conditional import of ctypes in inputhook
- PR #1462: expedite parallel tests
- PR #1410: Add javascript library and css stylesheet loading to JS class.
- PR #1448: Fix for #875 Never build unicode error messages
- PR #1458: use eval to uncan References
- PR #1450: load mathjax from CDN via https
- PR #1451: include heading level in JSON
- PR #1444: Fix pyhton -> python typos
- PR #1414: ignore errors in shell.var_expand
- PR #1430: Fix for tornado check for tornado < 1.1.0
- PR #1413: get_home_dir expands symlinks, adjust test accordingly
- PR #1385: updated and prettified magic doc strings
- PR #1406: Browser selection
- PR #1377: Saving non-ascii history
- PR #1402: fix symlinked /home issue for FreeBSD
- PR #1405: Only monkeypatch xunit when the tests are run using it.
- PR #1395: Xunit & KnownFailure
- PR #1396: Fix for %tb magic.
- PR #1386: Jsd3
- PR #1388: Add simple support for running inside a virtualenv
- PR #1391: Improve Hub/Scheduler when no engines are registered
- PR #1369: load header with engine id when engine dies in TaskScheduler
- PR #1353: Save notebook as script using unicode file handle.
- PR #1352: Add „-m mod : run library module as a script“ option.
- PR #1363: Fix some minor color/style config issues in the qtconsole
- PR #1371: Adds a quiet keyword to sync_imports
- PR #1387: Fixing Cell menu to update cell type select box.
- PR #1296: Wx gui example: fixes the broken example for %gui wx.
- PR #1372: ipcontroller cleans up connection files unless reuse=True
- PR #1374: remove calls to meaningless ZMQStream.on_err
- PR #1370: allow draft76 websockets (Safari)

- PR #1368: Ensure handler patterns are str, not unicode
- PR #1361: Notebook bug fix branch
- PR #1364: avoid jsonlib returning Decimal
- PR #1362: Don't log complete contents of history replies, even in debug
- PR #1347: fix weird magic completion in notebook
- PR #1346: fixups for alternate URL prefix stuff
- PR #1336: crack at making notebook.html use the layout.html template
- PR #1331: RST and heading cells
- PR #1247: fixes a bug causing extra newlines after comments.
- PR #1332: notebook - allow prefixes in URL path.
- PR #1341: Don't attempt to tokenize binary files for tracebacks
- PR #1334: added key handler for control-s to notebook, seems to work pretty well
- PR #1338: Fix see also in docstrings so API docs build
- PR #1335: Notebook toolbar UI
- PR #1299: made notebook.html extend layout.html
- PR #1318: make Ctrl-D in qtconsole act same as in terminal (ready to merge)
- PR #1328: Coverage
- PR #1206: don't preserve fixConsole output in json
- PR #1330: Add linewrapping to text cells (new feature in CodeMirror).
- PR #1309: Inoculate clearcmd extension into %reset functionality
- PR #1327: Updatetcm2
- PR #1326: Removing Ace edit capability.
- PR #1325: forgotten selected_cell -> get_selected_cell
- PR #1316: Pass subprocess test runners a suitable location for xunit output
- PR #1303: Updatetcm
- PR #1312: minor heartbeat tweaks
- PR #1306: Fix %prun input parsing for escaped characters (closes #1302)
- PR #1301: New «Fix for issue #1202» based on current master.
- PR #1289: Make autoreload extension work on Python 3.
- PR #1288: Don't ask for confirmation when stdin isn't available
- PR #1294: TaskScheduler.hwm default to 1 instead of 0
- PR #1283: HeartMonitor.period should be an Integer
- PR #1264: Aceify
- PR #1284: a fix for GH 1269
- PR #1213: BUG: Minor typo in history_console_widget.py
- PR #1267: add NoDB for non-recording Hub

- PR #1222: allow Reference as callable in map/apply
- PR #1257: use self.kernel_manager_class in qtconsoleapp
- PR #1253: set auto_create flag for notebook apps
- PR #1262: Heartbeat no longer shares the app's Context
- PR #1229: Fix display of SyntaxError in Python 3
- PR #1256: Dewijmoize
- PR #1246: Skip tests that require X, when importing pylab results in RuntimeError.
- PR #1211: serve local files in notebook-dir
- PR #1224: edit text cells on double-click instead of single-click
- PR #1187: misc notebook: connection file cleanup, first heartbeat, startup flush
- PR #1207: fix loadpy duplicating newlines
- PR #1129: Unified setup.py
- PR #1199: Reduce IPython.external.*
- PR #1218: Added -q option to %prun for suppression of the output, along with editing the dochelp string.
- PR #1217: Added -q option to %prun for suppression of the output, along with editing the dochelp string
- PR #1175: core.completer: Clean up excessive and unused code.
- PR #1196: docs: looks like a file path might have been accidentally pasted in the middle of a word
- PR #1190: Fix link to Chris Fonnesebeck blog post about 0.11 highlights.

Issues (742):

- #1943: add screenshot and link into releasenotes
- #1570: [notebook] remove „left panel“ references from example.
- #1954: update some example notebooks
- #2048: move _encode_binary to jsonutil.encode_images
- #2050: only add quotes around xunit-file on Windows
- #2047: disable auto-scroll on mozilla
- #1258: Magic %paste error
- #2015: Fixes for %paste with special transformations
- #760: Windows: test runner fails if repo path contains spaces
- #2046: Iptest unicode
- #1939: Namespaces
- #2042: increase auto-scroll threshold to 100 lines
- #2043: move RemoteError import to top-level
- #641: In %magic help, remove duplicate aliases
- #2036: %alias_magic
- #1968: Proposal of icons for .ipynb files

- #825: keyboardinterrupt crashes gtk gui when gtk.set_interactive is not available
- #1971: Remove duplicate magics docs
- #2040: Namespaces for cleaner public APIs
- #2039: ipython parallel import exception
- #2035: Getdefaultencoding test error with sympy 0.7.1_git
- #2037: remove `ipython-qtconsole` gui-script
- #1516: ipython-qtconsole script isn't installed for Python 2.x
- #1297: `«ipython -p sh»` is in documentation but doesn't work
- #2038: add extra clear warning to shell doc
- #1265: please ship unminified js and css sources
- #2029: Ship unminified js
- #1920: Provide an easy way to override the Qt widget used by qtconsole
- #2007: Add `custom_control` and `custom_page_control` variables to override the Qt widgets used by qtconsole
- #2009: In `%magic help`, remove duplicate aliases
- #2033: ipython parallel pushing and pulling recarrays
- #2034: fix `&test` push/pull recarrays
- #2028: Reduce unhelpful information shown by `pinfo`
- #1992: Tab completion fails with many spaces in filename
- #1885: handle too old wx
- #2030: check wxPython version in `inputhook`
- #2024: Make `interactive_usage` a bit more rst friendly
- #2031: disable `^C^C` confirmation on Windows
- #2023: Unicode test failure on OS X
- #2027: match stdin encoding in frontend readline test
- #1901: Windows: parallel test fails assert, leaves 14 python processes alive
- #2025: Fix parallel test on WinXP - wait for resource cleanup.
- #1986: Line magic function `%R` not found. (`Rmagic`)
- #1712: test failure in ubuntu package daily build
- #1183: 0.12 testsuite failures
- #2016: BUG: test runner fails in Windows if filenames contain spaces.
- #1806: Alternate upload methods in firefox
- #2019: Windows: home directory expansion test fails
- #2020: Fix home path expansion test in Windows.
- #2017: Windows core test error - filename quoting
- #2021: Fix Windows pathname issue in „odd encoding“ test.

- #1998: call to `nt.assert_true(path._writable_dir(home))` returns false in `test_path.py`
- #2022: don't check writability in test for `get_home_dir` when `HOME` is undefined
- #1589: Test failures and docs don't build on Mac OS X Lion
- #1996: frontend test tweaks
- #2011: Notebook server can't start cluster with hyphen-containing profile name
- #2014: relax profile regex in notebook
- #2013: brew install pyqt
- #2005: Strange output artifacts in footer of notebook
- #2012: Mono cursor offset
- #2004: Clarify generic message spec vs. Python message API in docs
- #2006: Don't crash when starting notebook server if runnable browser not found
- #2010: notebook: Print a warning (but do not abort) if no webbrowser can be found.
- #2008: pip install virtualenv
- #2003: Wrong case of `rmagic` in docs
- #2002: Refactor `%magic` into a `lsmagic_docs` API function.
- #2000: `kernel.js` consistency with generic IPython message format.
- #1999: `%magic` help: display line and cell magics in alphabetical order.
- #1635: `test_prun_quotes` fails on Windows
- #1984: Cannot restart Notebook when using `%%script --bg`
- #1981: Clean BG processes created by `%%script` on kernel exit
- #1994: Fix RST misformatting.
- #1949: Introduce Notebook Magics
- #1985: Kernels should start in notebook dir when manually specified
- #1980: Notebook should check that `--notebook-dir` exists
- #1951: minor notebook startup/notebook-dir adjustments
- #1969: tab completion in notebook for paths not triggered
- #1974: Allow path completion on notebook.
- #1964: allow multiple instances of a Magic
- #1960: `%page` not working
- #1991: fix `_ofind` attr in `%page`
- #1982: Shutdown qtconsole problem?
- #1988: check for active frontend in `update_restart_checkbox`
- #1979: Add support for tox (<https://tox.readthedocs.io/>) and Travis CI (<http://travis-ci.org/>)
- #1989: Parallel: output of `%px` and `%px${suffix}` is inconsistent
- #1966: `ValueError`: packer could not serialize a simple message
- #1987: Notebook: MathJax offline install not recognized

- #1970: dblclick to restore size of images
- #1983: Notebook does not save heading level
- #1978: Notebook names truncating at the first period
- #1553: Limited size of output cells and provide scroll bars for such output cells
- #1825: second attempt at scrolled long output
- #1915: add cell-level metadata
- #1934: Cell/Worksheet metadata
- #1746: Confirm restart (configuration option, and checkbox UI)
- #1790: Commenting function.
- #1767: Tab completion problems with cell magics
- #1944: [qtconsole] take %,%% prefix into account for completion
- #1973: fix another FreeBSD \$HOME symlink issue
- #1972: Fix completion of „%tim“ in the Qt console
- #1887: Make it easy to resize jpeg/png images back to original size.
- #1967: Fix psums example description in docs
- #1678: ctrl-z clears cell output in notebook when pressed enough times
- #1965: fix for #1678, undo no longer clears cells
- #1952: avoid duplicate «Websockets closed» dialog on ws close
- #1961: UnicodeDecodeError on directory with unicode chars in prompt
- #1963: styling prompt, {color.Normal} excepts
- #1962: Support unicode prompts
- #1959: %page not working on qtconsole for Windows XP 32-bit
- #1955: update to latest version of vim-ipython
- #1945: Add -proc option to %%script
- #1957: fix indentation in kernel.js
- #1956: move import RemoteError after get_exc_info
- #1950: Fix for copy action (Ctrl+C) when there is no pager defined in qtconsole
- #1948: Fix help string for InteractiveShell.ast_node_interactivity
- #1941: script magics cause terminal spam
- #1942: swallow stderr of which in utils.process.find_cmd
- #1833: completer draws slightly too small on Chrome
- #1940: fix completer css on some Chrome versions
- #1938: remove remaining references to deprecated XREP/XREQ names
- #1924: HTML superscripts not shown raised in the notebook
- #1925: Fix styling of superscripts and subscripts. Closes #1924.
- #1461: User notification if notebook saving fails

- [#1936](#): increase duration of save messages
- [#1542](#): %save magic fails in clients without stdin if file already exists
- [#1937](#): add %save -f
- [#1572](#): pyreadline version dependency not correctly checked
- [#1935](#): add version checking to pyreadline import test
- [#1849](#): Octave magics
- [#1759](#): github, merge PR(s) just by number(s)
- [#1931](#): Win py3fixes
- [#1646](#): Meaning of restart parameter in client.shutdown() unclear
- [#1933](#): oinspect.find_file: Additional safety if file cannot be found.
- [#1916](#): %paste doesn't work on py3
- [#1932](#): Fix adding functions to CommandChainDispatcher with equal priority on Py 3
- [#1928](#): Select NoDB by default
- [#1923](#): Add IPython syntax support to the %timeit magic, in line and cell mode
- [#1926](#): Make completer recognize escaped quotes in strings.
- [#1929](#): Ipython-qtconsole (0.12.1) hangs with Python 2.7.3, Windows 7 64 bit
- [#1409](#): [qtconsole] forward delete bring completion into current line
- [#1922](#): py3k compatibility for setupegg.py
- [#1598](#): document that sync_imports() can't handle «import foo as bar»
- [#1893](#): Update Parallel Magics and Exception Display
- [#1890](#): Docstrings for magics that use @magic_arguments are rendered wrong
- [#1921](#): magic_arguments: dedent but otherwise preserve indentation.
- [#1919](#): Use oinspect in CodeMagics._find_edit_target
- [#1918](#): don't warn in iptest if deathrow/quarantine are missing
- [#1914](#): %pdef failing on python3
- [#1917](#): Fix for %pdef on Python 3
- [#1428](#): Failing test that prun does not clobber string escapes
- [#1913](#): Fix for [#1428](#)
- [#1911](#): temporarily skip autoreload tests
- [#1549](#): autoreload extension crashes ipython
- [#1908](#): find_file errors on windows
- [#1909](#): Fix for [#1908](#), use os.path.normcase for safe filename comparisons
- [#1907](#): py3compat fixes for %%script and tests
- [#1904](#): %%px? doesn't work, shows info for %px, general cell magic problem
- [#1906](#): ofind finds non-unique cell magics
- [#1894](#): Win64 binary install fails

- #1799: Source file not found for magics
- #1845: Fixes to inspection machinery for magics
- #1774: Some magics seems broken
- #1586: Clean up tight coupling between Notebook, CodeCell and Kernel Javascript objects
- #1632: Win32 shell interactivity apparently broke qtconsole «cd» magic
- #1902: Workaround fix for gh-1632; minimal revert of gh-1424
- #1900: Cython libs
- #1503: Cursor is offset in notebook in Chrome 17 on Linux
- #1426: Qt console doesn't handle the --gui flag correctly.
- #1180: Can't start IPython kernel in Spyder
- #581: test IPython.zmq
- #1593: Name embedded in notebook overrides filename
- #1899: add ScriptMagics to class list for generated config
- #1618: generate or minimize manpages
- #1898: minimize manpages
- #1896: Windows: apparently spurious warning „Excluding nonexistent file“ ... test_exampleip
- #1897: use glob for bad exclusion warning
- #1215: updated %quickref to show short-hand for %sc and %sx
- #1855: %%script and %%file magics
- #1863: Ability to silence a cell in the notebook
- #1870: add %%capture for capturing stdout/err
- #1861: Use dvipng to format sympy.Matrix
- #1867: Fix 1px margin bouncing of selected menu item.
- #1889: Reconnect when the websocket connection closes unexpectedly
- #1577: If a notebook loses its network connection WebSockets won't reconnect
- #1886: Fix a bug in renaming notebook
- #1895: Fix error in test suite with ip.system()
- #1762: add locate entry points
- #1883: Fix vertical offset due to bold/italics, and bad browser fonts.
- #1875: re-write columnize, with intermediate step.
- #1860: IPython.utils.columnize sometime wrong...
- #1851: new completer for qtconsole.
- #1892: Remove suspicious quotes in interactiveshell.py
- #1854: Class %hierarchy and graphiz %%dot magics
- #1827: Sending tracebacks over ZMQ should protect against unicode failure
- #1864: Rmagic exceptions

- #1829: [notebook] don't care about leading pret in completion
- #1832: Make svg, jpeg and png images resizable in notebook.
- #1674: HTML Notebook carriage-return handling, take 2
- #1874: cython_magic uses importlib, which doesn't ship with py2.6
- #1882: Remove importlib dependency which not available in Python 2.6.
- #1878: shell access using ! will not fill class or function scope vars
- #1879: Correct stack depth for variable expansion in !system commands
- #1840: New JS completer should merge completions before display
- #1841: [notebook] deduplicate completion results
- #1736: no good error message on missing tkinter and %paste
- #1741: Display message from TryNext error in magic_paste
- #1850: Remove args/kwargs handling in TryNext, fix %paste error messages.
- #1663: Keep line-endings in ipynb
- #1872: Matplotlib window freezes using intreractive plot in qtconsole
- #1869: Improve CodeMagics._find_edit_target
- #1781: Colons in notebook name causes notebook deletion without warning
- #1815: Make : invalid in filenames in the Notebook JS code.
- #1819: doc: cleanup the parallel psums example a little
- #1838: externals cleanup
- #1839: External cleanup
- #1782: fix Magic menu in qtconsole, split in groups
- #1862: Minor bind_kernel improvements
- #1859: kernmagic during console startup
- #1857: Prevent jumping of window to input when output is clicked.
- #1856: Fix 1px jumping of cells and menus in Notebook.
- #1848: task fails with «AssertionError: not enough buffers!» after second resubmit
- #1852: fix chained resubmissions
- #1780: Rmagic extension
- #1853: Fix jumpy notebook behavior
- #1842: task with UnmetDependency error still owned by engine
- #1847: add InlineBackend to ConsoleApp class list
- #1846: Exceptions within multiprocessing crash IPython notebook kernel
- #1843: Notebook does not exist and permalinks
- #1837: edit magic broken in head
- #1834: resubmitted tasks doesn't have same session name
- #1836: preserve header for resubmitted tasks

- #1776: fix magic menu in qtconsole
- #1828: change default extension to .ipy for %save -r
- #1800: Reintroduce recall
- #1671: `__future__` environments
- #1830: lsmagic lists magics in alphabetical order
- #1835: Use Python import in ipython profile config
- #1773: Update SymPy profile: SymPy's `latex()` can now print set and frozenset
- #1761: Edited documentation to use IPYTHONDIR in place of `~/ipython`
- #1772: notebook autocomplete fail when typing number
- #1822: aesthetics pass on `AsyncResult.display_outputs`
- #1460: Redirect http to https for notebook
- #1287: Refactor the notebook tab completion/tooltip
- #1596: In rename dialog, `<return>` should submit
- #1821: ENTER submits the rename notebook dialog.
- #1750: Let the user disable random port selection
- #1820: NotebookApp: Make the number of ports to retry user configurable.
- #1816: Always use filename as the notebook name.
- #1775: `assert_in` not present on Python 2.6
- #1813: Add `assert_in` method to nose for Python 2.6
- #1498: Add tooltip keyboard shortcuts
- #1711: New Tooltip, New Completer and JS Refactor
- #1798: a few simple fixes for docs/parallel
- #1818: possible bug with latex / markdown
- #1647: Aborted parallel tasks can't be resubmitted
- #1817: Change behavior of ipython notebook `-port=...`
- #1738: IPython.embed_kernel issues
- #1610: Basic bold and italic in HTML output cells
- #1576: Start and stop kernels from the notebook dashboard
- #1515: impossible to shutdown notebook kernels
- #1812: Ensure `AsyncResult.display_outputs` doesn't display empty streams
- #1811: warn on nonexistent exclusions in `iptest`
- #1809: test suite error in IPython.zmq on windows
- #1810: fix for #1809, failing tests in IPython.zmq
- #1808: Reposition alternate upload for firefox [need cross browser/OS/language test]
- #1742: Check for custom_exceptions only once
- #1802: cythonmagic tests should be skipped if Cython not available

- #1062: warning message in IPython.extensions test
- #1807: add missing cython exclusion in iptest
- #1805: Fixed a vcvarsall.bat error on win32/Py2.7 when trying to compile with m...
- #1803: MPI parallel %px bug
- #1804: Fixed a vcvarsall.bat error on win32/Py2.7 when trying to compile with mingw.
- #1492: Drag target very small if IPython Dashboard has no notebooks
- #1562: Offer a method other than drag-n-drop to upload notebooks
- #1739: Dashboard improvement (necessary merge of #1658 and #1676 + fix #1492)
- #1770: Cython related magic functions
- #1532: qtconsole does not accept -gui switch
- #1707: Accept -gui=<...> switch in IPython qtconsole.
- #1797: Fix comment which breaks Emacs syntax highlighting.
- #1796: %gui magic broken
- #1795: fix %gui magic
- #1788: extreme truncating of return values
- #1793: Raise repr limit for strings to 80 characters (from 30).
- #1794: don't use XDG path on OS X
- #1777: ipython crash on wrong encoding
- #1792: Unicode-aware logger
- #1791: update zmqshell magics
- #1787: DOC: Remove regression from qt-console docs.
- #1785: IPython.utils.tests.test_process.SubProcessTestCase
- #1758: test_pr, fallback on http if git protocol fail, and SSL errors...
- #1786: Make notebook save failures more salient
- #1748: Fix some tests for Python 3.3
- #1755: test for pygments before running qt tests
- #1771: Make default value of interactivity passed to run_ast_nodes configurable
- #1783: part of PR #1606 (loadpy -> load) erased by magic refactoring.
- #1784: restore loadpy to load
- #1768: Update parallel magics
- #1778: string exception in IPython/core/magic.py:232
- #1779: Tidy up error raising in magic decorators.
- #1769: Allow cell mode timeit without setup code.
- #1716: Fix for fake filenames in verbose traceback
- #1763: [qtconsole] fix append_plain_html -> append_html
- #1766: Test failure in IPython.parallel

- [#1611](#): IPEP1: Cell magics and general cleanup of the Magic system
- [#1732](#): Refactoring of the magics system and implementation of cell magics
- [#1765](#): `test_pr` should clear `PYTHONPATH` for the subprocesses
- [#1630](#): Merge divergent Kernel implementations
- [#1705](#): [notebook] Make pager resizable, and remember size...
- [#1606](#): Share code for `%pycat` and `%loadpy`, make `%pycat` aware of URLs
- [#1720](#): Adding interactive inline plotting to notebooks with `flot`
- [#1701](#): [notebook] Open HTML links in a new window by default
- [#1757](#): Open IPython notebook hyperlinks in a new window using `target=_blank`
- [#1735](#): Open IPython notebook hyperlinks in a new window using `target=_blank`
- [#1754](#): Fix typo `enconters->encounters`
- [#1753](#): Clear window title when kernel is restarted
- [#735](#): Images missing from XML/SVG export (for me)
- [#1449](#): Fix for bug [#735](#) : Images missing from XML/SVG export
- [#1752](#): Reconnect Websocket when it closes unexpectedly
- [#1751](#): Reconnect Websocket when it closes unexpectedly
- [#1749](#): Load `MathJax.js` using HTTPS when IPython notebook server is HTTPS
- [#1743](#): Tooltip completer js refactor
- [#1700](#): A module for sending custom user messages from the kernel.
- [#1745](#): `htmlnotebook`: Cursor is off
- [#1728](#): `ipython` crash with `matplotlib` during picking
- [#1681](#): add qt config option to `clear_on_kernel_restart`
- [#1733](#): Tooltip completer js refactor
- [#1676](#): Kernel status/shutdown from dashboard
- [#1658](#): Alternate notebook upload methods
- [#1727](#): terminate kernel after `embed_kernel` tests
- [#1737](#): add `HistoryManager` to `ipapp` class list
- [#945](#): Open a notebook from the command line
- [#1686](#): ENH: Open a notebook from the command line
- [#1709](#): fixes [#1708](#), failing test in `arg_split` on windows
- [#1718](#): Use `CRegExp` trait for regular expressions.
- [#1729](#): Catch failure in `repr()` for `%whos`
- [#1726](#): use `eval` for command-line args instead of `exec`
- [#1723](#): `scatter/gather` fail with `targets="all"`
- [#1724](#): fix `scatter/gather` with `targets="all"`
- [#1725](#): add `-no-ff` to git pull in `test_pr`

- [#1722](#): unicode exception when evaluating expression with non-ascii characters
- [#1721](#): Tooltip completer js refactor
- [#1657](#): Add `wait` optional argument to `hooks.editor`
- [#123](#): Define `sys.ps{1,2}`
- [#1717](#): Define generic `sys.ps{1,2,3}`, for use by scripts.
- [#1442](#): cache-size issue in `qtconsole`
- [#1691](#): Finish PR [#1446](#)
- [#1446](#): Fixing Issue [#1442](#)
- [#1710](#): update MathJax CDN url for https
- [#81](#): Autocall fails if first function argument begins with `<->` or `<+`
- [#1713](#): Make autocall regexp's configurable.
- [#211](#): paste command not working
- [#1703](#): Allow TryNext to have an error message without it affecting the command chain
- [#1714](#): minor adjustments to `test_pr`
- [#1509](#): New tooltip for notebook
- [#1697](#): Major refactoring of the Notebook, Kernel and CodeCell JavaScript.
- [#788](#): Progress indicator in the notebook (and perhaps the Qt console)
- [#1034](#): Single process Qt console
- [#1557](#): magic function conflict while using `-pylab`
- [#1476](#): Pylab figure objects not properly updating
- [#1704](#): ensure all needed qt parts can be imported before settling for one
- [#1708](#): test failure in `arg_split` on windows
- [#1706](#): Mark `test_push_numpy_nocopy` as a known failure for Python 3
- [#1696](#): notebook tooltip fail on function with number
- [#1698](#): fix tooltip on token with number
- [#1226](#): Windows GUI only (`pythonw`) bug for IPython on Python 3.x
- [#1245](#): `pythonw` py3k fixes for issue [#1226](#)
- [#1417](#): Notebook Completer Class
- [#1690](#): [Bogus] Deliberately make a test fail
- [#1685](#): Add script to test pull request
- [#1167](#): Settle on a choice for `$IPYTHONDIR`
- [#1693](#): deprecate `IPYTHON_DIR` in favor of `IPYTHONDIR`
- [#1672](#): `ipython-qtconsole.desktop` is using a deprecated format
- [#1695](#): Avoid deprecated warnings from `ipython-qtconsole.desktop`.
- [#1694](#): Add quote to notebook to allow it to load
- [#1240](#): `sys.path` missing `' '` as first entry when kernel launched without interface

- #1689: Fix sys.path missing „“ as first entry in ipython kernel.
- #1683: Parallel controller failing with Pymongo 2.2
- #1687: import Binary from bson instead of pymongo
- #1614: Display Image in Qtconsole
- #1616: Make IPython.core.display.Image less notebook-centric
- #1684: CLN: Remove redundant function definition.
- #1655: Add %open magic command to open editor in non-blocking manner
- #1677: middle-click paste broken in notebook
- #1670: Point %pastebin to gist
- #1667: Test failure in test_message_spec
- #1668: Test failure in IPython.zmq.tests.test_message_spec.test_complete «„pyout“ != „status“»
- #1669: handle pyout messages in test_message_spec
- #1295: add binary-tree engine interconnect example
- #1642: Cherry-picked commits from 0.12.1 release
- #1659: Handle carriage return characters (»r») in HTML notebook output.
- #1313: Figure out MathJax 2 support
- #1653: Test failure in IPython.zmq
- #1656: ensure kernels are cleaned up in embed_kernel tests
- #1666: pip install ipython==dev installs version 0.8 from an old svn repo
- #1664: InteractiveShell.run_code: Update docstring.
- #1512: print stuff, should avoid newline
- #1662: Delay flushing softspace until after cell finishes
- #1643: handle jpg/jpeg in the qtconsole
- #966: dreload fails on Windows XP with IPython 0.11 «Unexpected Error»
- #1500: dreload doesn't seem to exclude numpy
- #1520: kernel crash when showing tooltip (?)
- #1652: add patch_pyzmq() for backporting a few changes from newer pyzmq
- #1650: DOC: moving files with SSH launchers
- #1357: add IPython.embed_kernel()
- #1640: Finish up embed_kernel
- #1651: Remove bundled Itpl module
- #1634: incremental improvements to SSH launchers
- #1649: move examples/test_embed into examples/tests/embed
- #1171: Recognise virtualenvs
- #1479: test_extension failing in Windows
- #1633: Fix installing extension from local file on Windows

- #1644: Update copyright date to 2012
- #1636: Test_deepreload breaks pylab irunner tests
- #1645: Exclude UserDict when deep reloading NumPy.
- #1454: make it possible to start engine in „disabled“ mode and „enable“ later
- #1641: Escape code for the current time in PromptManager
- #1638: ipython console clobbers custom sys.path
- #1637: Removed a „:“ which shouldn't have been there
- #1536: ipython 0.12 embed shell won't run startup scripts
- #1628: error: QApplication already exists in TestKillRing
- #1631: TST: QApplication doesn't quit early enough with PySide.
- #1629: evaluate a few dangling validate_message generators
- #1621: clear In[] prompt numbers on «Clear All Output»
- #1627: Test the Message Spec
- #1470: SyntaxError on setup.py install with Python 3
- #1624: Fixes for byte-compilation on Python 3
- #1612: pylab=inline fig.show() non-existent in notebook
- #1615: Add show() method to figure objects.
- #1622: deepreload fails on Python 3
- #1625: Fix deepreload on Python 3
- #1626: Failure in new dreload tests under Python 3.2
- #1623: IPython / matplotlib Memory error with imshow
- #1619: pyin messages should have execution_count
- #1620: pyin message now have execution_count
- #32: dreload produces spurious traceback when numpy is involved
- #1457: Update deepreload to use a rewritten knee.py. Fixes dreload(numpy).
- #1613: allow map / parallel function for single-engine views
- #1609: exit notebook cleanly on SIGINT, SIGTERM
- #1531: Function keyword completion fails if cursor is in the middle of the complete parentheses
- #1607: cleanup sqllitedb temporary db file after tests
- #1608: don't rely on timedelta.total_seconds in AsyncResult
- #1421: ipython32 %run -d breaks with NameError name „execfile“ is not defined
- #1599: Fix for %run -d on Python 3
- #1201: %env magic fails with Python 3.2
- #1602: Fix %env magic on Python 3.
- #1603: Remove python3 profile
- #1604: Exclude IPython.quarantine from installation

- [#1601](#): Security file is not removed after shutdown by Ctrl+C or kill -INT
- [#1600](#): Specify encoding for io.open in notebook_reformat tests
- [#1605](#): Small fixes for Animation and Progress notebook
- [#1452](#): Bug fix for approval
- [#13](#): Improve robustness and debuggability of test suite
- [#70](#): IPython should prioritize `__all__` during tab completion
- [#1529](#): `__all__` feature, improvement to `dir2`, and tests for both
- [#1475](#): Custom namespace for `%run`
- [#1564](#): calling `.abort` on `AsyncMapResult` results in traceback
- [#1548](#): add sugar methods/properties to `AsyncResult`
- [#1535](#): Fix pretty printing dispatch
- [#1522](#): Discussion: some potential Qt console refactoring
- [#1399](#): Use LaTeX to print various built-in types with the SymPy printing extension
- [#1597](#): re-enter `kernel.eventloop` after catching SIGINT
- [#1490](#): rename plaintext cell -> raw cell
- [#1487](#): `%notebook` fails in qtconsole
- [#1545](#): trailing newline not preserved in splitline ipynb
- [#1480](#): Fix `%notebook` magic, etc. `nbformat` unicode tests and fixes
- [#1588](#): Gtk3 integration with ipython works.
- [#1595](#): Examples syntax (avoid errors installing on Python 3)
- [#1526](#): Find encoding for Python files
- [#1594](#): Fix writing git commit ID to a file on build with Python 3
- [#1556](#): shallow-copy DictDB query results
- [#1499](#): various pyflakes issues
- [#1502](#): small changes in response to pyflakes pass
- [#1445](#): Don't build sphinx docs for sdist
- [#1484](#): unhide `.git_commit_info.ini`
- [#1538](#): store git commit hash in `utils._sysinfo` instead of hidden data file
- [#1546](#): attempt to suppress exceptions in channel threads at shutdown
- [#1524](#): unhide `git_commit_info.ini`
- [#1559](#): update `tools/github_stats.py` to use GitHub API v3
- [#1563](#): `clear_output` improvements
- [#1558](#): Ipython testing documentation still mentions twisted and trial
- [#1560](#): remove obsolete discussion of Twisted/trial from testing docs
- [#1561](#): Qtconsole - nonstandard a and b
- [#1569](#): BUG: qtconsole – non-standard handling of a and b. [Fixes [#1561](#)]

- #1574: BUG: Ctrl+C crashes wx pylab kernel in qtconsole
- #1573: BUG: Ctrl+C crashes wx pylab kernel in qtconsole.
- #1590: „IPython3 qtconsole“ doesn't work in Windows 7
- #602: User test the html notebook
- #613: Implement Namespace panel section
- #879: How to handle Javascript output in the notebook
- #1255: figure.show() raises an error with the inline backend
- #1467: Document or bundle a git-integrated facility for stripping VCS-unfriendly binary data
- #1237: Kernel status and logout button overlap
- #1319: Running a cell with ctrl+Enter selects text in cell
- #1571: module member autocomplete should respect `__all__`
- #1566: ipython3 doesn't run in Win7 with Python 3.2
- #1568: fix PR #1567
- #1567: Fix: openssh_tunnel did not parse port in `server`
- #1565: fix `AsyncResult.abort`
- #1550: Crash when starting notebook in a non-ascii path
- #1552: use `os.getcwd` in `NotebookManager`
- #1554: wrong behavior of the `all` function on iterators
- #1541: `display__pub` flushes `stdout/err`
- #1539: Asynchronous issue when using `clear_display` and `print x,y,z`
- #1544: make `MultiKernelManager.kernel_manager_class` configurable
- #1494: Untrusted Secure Websocket broken on latest chrome dev
- #1521: only install `ipython-qtconsole` gui script on Windows
- #1528: Tab completion optionally respects `__all__` (+ `dir2()` cleanup)
- #1527: Making a progress bar work in IPython Notebook
- #1497: `__all__` functionality added to `dir2(obj)`
- #1518: Pretty printing exceptions is broken
- #811: Fixes for ipython unhandled `OSError` exception on failure of `os.getcwd()`
- #1517: Fix indentation bug in `IPython/lib/pretty.py`
- #1519: BUG: Include the name of the exception type in its pretty format.
- #1525: A hack for auto-complete numpy recarray
- #1489: Fix zero-copy push
- #1401: numpy arrays cannot be used with `View.apply()` in Python 3
- #1477: fix dangling `buffer` in `IPython.parallel.util`
- #1514: DOC: Fix references to `IPython.lib.pretty` instead of the old location
- #1511: Version comparison error („2.1.11“ < „2.1.4“ ==> True)

- #1506: «Fixing» the Notebook scroll to help in visually comparing outputs
- #1481: BUG: Improve placement of CallTipWidget
- #1241: When our debugger class is used standalone `_oh` key errors are thrown
- #676: `IPython.embed()` from `ipython` crashes twice on exit
- #1496: BUG: LBYL when clearing the output history on shutdown.
- #1507: python3 notebook: `TypeError: unorderable types`
- #1508: fix sorting profiles in `clustermanager`
- #1495: BUG: Fix pretty-printing for overzealous objects
- #1505: SQLite objects created in a thread can only be used in that same thread
- #1482: `%history` documentation out of date?
- #1501: `dreload` doesn't seem to exclude `numpy`
- #1472: more general fix for #662
- #1486: save state of `qtconsole`
- #1485: add history search to `qtconsole`
- #1483: updated `magic_history` docstring
- #1383: First version of cluster web service.
- #482: `test_run.test_tclass` fails on Windows
- #1398: fix `%tb` after `SyntaxError`
- #1478: key function or lambda in sorted function doesn't find global variables
- #1415: handle `exit/quit/exit()/quit()` variants in `zmqconsole`
- #1440: Fix for failing testsuite when using `-with-xml-coverage` on windows.
- #1419: Add `%install_ext` magic function.
- #1424: Win32 shell interactivity
- #1434: Controller should schedule tasks of multiple clients at the same time
- #1268: notebook `%reset` magic fails with `StdinNotImplementedError`
- #1438: `from cherypy import expose` fails when running script from parent directory
- #1468: Simplify structure of a Job in the TaskScheduler
- #875: never build unicode error messages
- #1107: Tab autocompletion can suggest invalid syntax
- #1447: 1107 - Tab autocompletion can suggest invalid syntax
- #1469: Fix typo in comment (insert space)
- #1463: Fix completion when importing modules in the `cwd`.
- #1437: unfriendly error handling with `pythonw` and `ipython-qtconsole`
- #1466: Fix for issue #1437, unfriendly windows `qtconsole` error handling
- #1432: Fix `ipython` directive
- #1465: allow `ipython help subcommand` syntax

- [#1394](#): Wishlist: Remove hard dependency on ctypes
- [#1416](#): Conditional import of ctypes in inputhook
- [#1462](#): expedite parallel tests
- [#1418](#): Strict mode in javascript
- [#1410](#): Add javascript library and css stylesheet loading to JS class.
- [#1427](#): [#922](#) again
- [#1448](#): Fix for [#875](#) Never build unicode error messages
- [#1458](#): use eval to uncan References
- [#1455](#): Python3 install fails
- [#1450](#): load mathjax from CDN via https
- [#1182](#): Qtconsole, multiwindow
- [#1439](#): Notebook not storing heading celltype information
- [#1451](#): include heading level in JSON
- [#1444](#): Fix pyhton -> python typos
- [#1412](#): Input parsing issue with %prun
- [#1414](#): ignore errors in shell.var_expand
- [#1441](#): (1) Enable IPython.notebook.kernel.execute to publish display_* even it is not called with a code cell and (2) remove empty html element when execute «display_*»
- [#1431](#): Beginner Error: ipython qtconsole
- [#1436](#): «ipython-qtconsole -gui qt» hangs on 64-bit win7
- [#1433](#): websocket connection fails on Chrome
- [#1430](#): Fix for tornado check for tornado < 1.1.0
- [#1408](#): test_get_home_dir_3 failed on Mac OS X
- [#1413](#): get_home_dir expands symlinks, adjust test accordingly
- [#1420](#): fixes [#922](#)
- [#823](#): KnownFailure tests appearing as errors
- [#1385](#): updated and prettified magic doc strings
- [#1406](#): Browser selection
- [#1411](#): ipcluster starts 8 engines «successfully» but Client only finds two
- [#1375](#): %history -g -f file encoding issue
- [#1377](#): Saving non-ascii history
- [#797](#): Source introspection needs to be smarter in python 3.2
- [#846](#): Autoreload extension doesn't work with Python 3.2
- [#1360](#): IPython notebook not starting on winXP
- [#1407](#): Qtconsole segfaults on OSX when displaying some pop-up function tooltips
- [#1402](#): fix symlinked /home issue for FreeBSD

- #1403: pyreadline cyclic dependency with pdb++/pdbpp module
- #1405: Only monkeypatch xunit when the tests are run using it.
- #1404: Feature Request: List/Dictionary tab completion
- #1395: Xunit & KnownFailure
- #1396: Fix for %tb magic.
- #1397: Stay or leave message not working, Safari session lost.
- #1389: pylab=inline inoperant through ssh tunnelling?
- #1386: Jsd3
- #1388: Add simple support for running inside a virtualenv
- #826: Add support for creation of parallel task when no engine is running
- #1391: Improve Hub/Scheduler when no engines are registered
- #1369: load header with engine id when engine dies in TaskScheduler
- #1345: notebook can't save unicode as script
- #1353: Save notebook as script using unicode file handle.
- #1352: Add „-m mod : run library module as a script“ option.
- #1363: Fix some minor color/style config issues in the qtconsole
- #1371: Adds a quiet keyword to sync_imports
- #1390: Blank screen for notebooks on Safari
- #1387: Fixing Cell menu to update cell type select box.
- #645: Standalone WX GUI support is broken
- #1296: Wx gui example: fixes the broken example for %gui wx.
- #1254: typo in notebooklist.js breaks links
- #781: Users should be able to clone a notebook
- #1372: ipcontroller cleans up connection files unless reuse=True
- #1374: remove calls to meaningless ZMQStream.on_err
- #1382: Update RO for Notebook
- #1370: allow draft76 websockets (Safari)
- #1368: Ensure handler patterns are str, not unicode
- #1379: Sage link on website homepage broken
- #1376: FWIW does not work with Chrome 16.0.912.77 Ubuntu 10.10
- #1358: Cannot install ipython on Windows 7 64-bit
- #1367: Ctrl - m t does not toggle output in chrome
- #1359: [sympypprinting] MathJax can't render root{m}{n}
- #1337: Tab in the notebook after (should not indent, only give a tooltip
- #1339: Notebook printing broken
- #1344: Ctrl + M + L does not toggle line numbering in htmlnotebook

- #1348: Ctrl + M + M does not switch to markdown cell
- #1361: Notebook bug fix branch
- #1364: avoid jsonlib returning Decimal
- #1362: Don't log complete contents of history replies, even in debug
- #888: ReST support in notebooks
- #1205: notebook stores HTML escaped text in the file
- #1351: add IPython.embed_kernel()
- #1243: magic commands without % are not completed properly in htmlnotebook
- #1347: fix weird magic completion in notebook
- #1355: notebook.html extends layout.html now
- #1354: min and max in the notebook
- #1346: fixups for alternate URL prefix stuff
- #1336: crack at making notebook.html use the layout.html template
- #1331: RST and heading cells
- #1350: Add „-m mod : run library module as a script“ option
- #1247: fixes a bug causing extra newlines after comments.
- #1329: add base_url to notebook configuration options
- #1332: notebook - allow prefixes in URL path.
- #1317: Very slow traceback construction from Cython extension
- #1341: Don't attempt to tokenize binary files for tracebacks
- #1300: Cell Input collapse
- #1334: added key handler for control-s to notebook, seems to work pretty well
- #1338: Fix see also in docstrings so API docs build
- #1335: Notebook toolbar UI
- #1299: made notebook.html extend layout.html
- #1318: make Ctrl-D in qtconsole act same as in terminal (ready to merge)
- #873: ReST support in notebook frontend
- #1139: Notebook webkit notification
- #1314: Insertcell
- #1328: Coverage
- #1206: don't preserve fixConsole output in json
- #1330: Add linewrapping to text cells (new feature in CodeMirror).
- #1309: Inoculate clearecmd extension into %reset functionality
- #1327: Updatecm2
- #1326: Removing Ace edit capability.
- #1325: forgotten selected_cell -> get_selected_cell

- #1316: Pass subprocess test runners a suitable location for xunit output
- #1315: Collect results from subprocess runners and spit out Xunit XML output.
- #1233: Update CodeMirror to the latest version
- #1234: Refactor how the notebook focuses cells
- #1235: After upgrading CodeMirror check the status of some bugs
- #1236: Review how select is called when notebook cells are inserted
- #1303: Updatecm
- #1311: Fixing CM related indentation problems.
- #1304: controller/server load can disrupt heartbeat
- #1312: minor heartbeat tweaks
- #1302: Input parsing with %prun clobbers escapes
- #1306: Fix %prun input parsing for escaped characters (closes #1302)
- #1251: IPython-0.12 can't import map module on Python 3.1
- #1202: Pyreadline install exclusion for 64 bit windows no longer required, version dependency not correctly specified.
- #1301: New «Fix for issue #1202» based on current master.
- #1242: changed key map name to match changes to python mode
- #1203: Fix for issue #1202
- #1289: Make autoreload extension work on Python 3.
- #1263: Different „C-x“ for shortcut, „C-m c“ not toCodeCell anymore
- #1259: Replace «from (|..) import» with absolute imports.
- #1278: took a crack at making notebook.html extend layout.html
- #1210: Add „quiet“ option to suppress screen output during %prun calls, edited dochelp
- #1288: Don't ask for confirmation when stdin isn't available
- #1290: Cell-level cut & paste overwrites multiple cells
- #1291: Minor, but important fixes to cut/copy/paste.
- #1293: TaskScheduler.hwm default value
- #1294: TaskScheduler.hwm default to 1 instead of 0
- #1281: in Hub: registration_timeout must be an integer, but heartmonitor.period is CFloat
- #1283: HeartMonitor.period should be an Integer
- #1162: Allow merge/split adjacent cells in notebook
- #1264: Aceify
- #1261: Mergesplit
- #1269: Another strange input handling error
- #1284: a fix for GH 1269
- #1232: Dead kernel loop

- #1279: ImportError: cannot import name S1 (from logging)
- #1276: notebook menu item to send a KeyboardInterrupt to the kernel
- #1213: BUG: Minor typo in history_console_widget.py
- #1248: IPython notebook doesn't work with latest version of tornado
- #1267: add NoDB for non-recording Hub
- #1222: allow Reference as callable in map/apply
- #1257: use self.kernel_manager_class in qtconsoleapp
- #1220: Open a new notebook while connecting to an existing kernel (opened by qtconsole or terminal or standalone)
- #1253: set auto_create flag for notebook apps
- #1260: heartbeat failure on long gil-holding operation
- #1262: Heartbeat no longer shares the app's Context
- #1225: SyntaxError display broken in Python 3
- #1229: Fix display of SyntaxError in Python 3
- #1256: Dewijmoize
- #1246: Skip tests that require X, when importing pylab results in RuntimeError.
- #1250: Wijmoize
- #1244: can not input chinese word «» , exit right now
- #1194: Adding Opera 11 as a compatible browser for ipython notebook
- #1198: Kernel Has Died error in Notebook
- #1211: serve local files in notebook-dir
- #1224: edit text cells on double-click instead of single-click
- #1187: misc notebook: connection file cleanup, first heartbeat, startup flush
- #1207: fix loadpy duplicating newlines
- #1060: Always save the .py file to disk next to the .ipynb
- #1066: execute cell in place should preserve the current insertion-point in the notebook
- #1141: «In» numbers are not invalidated when restarting kernel
- #1231: pip on OSX tries to install files in /System directory.
- #1129: Unified setup.py
- #1199: Reduce IPython.external.*
- #1219: Make all the static files path absolute.
- #1218: Added -q option to %prun for suppression of the output, along with editing the dochelp string.
- #1217: Added -q option to %prun for suppression of the output, along with editing the dochelp string
- #1216: Pdb tab completion does not work in QtConsole
- #1197: Interactive shell trying to: from ... import history
- #1175: core.completer: Clean up excessive and unused code.

- [#1208](#): should `dv.sync_import` print failed imports ?
- [#1186](#): `payloadpage.py` not used by `qtconsole`
- [#1204](#): double newline from `%loadpy` in python notebook (at least on mac)
- [#1192](#): Invalid JSON data
- [#1196](#): docs: looks like a file path might have been accidentally pasted in the middle of a word
- [#1189](#): Right justify of „in“ prompt in variable prompt size configurations
- [#1185](#): ipython console not work proper with `stdout...`
- [#1191](#): profile/startup files not executed with «notebook»
- [#1190](#): Fix link to Chris Fongesbeck blog post about 0.11 highlights.
- [#1174](#): Remove `%install_default_config` and `%install_profiles`

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

2.21 0.12 Series

2.21.1 Release 0.12.1

IPython 0.12.1 is a bugfix release of 0.12, pulling only bugfixes and minor cleanup from 0.13, timed for the Ubuntu 12.04 LTS release.

See the *[list of fixed issues](#)* for specific backported issues.

2.21.2 Release 0.12

IPython 0.12 contains several major new features, as well as a large amount of bug and regression fixes. The 0.11 release brought with it a lot of new functionality and major refactorings of the codebase; by and large this has proven to be a success as the number of contributions to the project has increased dramatically, proving that the code is now much more approachable. But in the refactoring inevitably some bugs were introduced, and we have also squashed many of those as well as recovered some functionality that had been temporarily disabled due to the API changes.

The following major new features appear in this version.

An interactive browser-based Notebook with rich media support

A powerful new interface puts IPython in your browser. You can start it with the command `ipython notebook`:




Рис. 3: The new IPython notebook showing text, mathematical expressions in LaTeX, code, results and embedded figures created with Matplotlib.

This new interface maintains all the features of IPython you are used to, as it is a new client that communicates with the same IPython kernels used by the terminal and Qt console. But the web notebook provides for a different workflow where you can integrate, along with code execution, also text, mathematical expressions, graphics, video, and virtually any content that a modern browser is capable of displaying.

You can save your work sessions as documents that retain all these elements and which can be version controlled, emailed to colleagues or saved as HTML or PDF files for printing or publishing statically on the web. The internal storage format is a JSON file that can be easily manipulated for manual exporting to other formats.

This Notebook is a major milestone for IPython, as for years we have tried to build this kind of system. We were inspired originally by the excellent implementation in Mathematica, we made a number of attempts using older technologies in earlier Summer of Code projects in 2005 (both students and Robert Kern developed early prototypes), and in recent years we have seen the excellent implementation offered by the Sage <<http://sagemath.org>> system. But we continued to work on something that would be consistent with the rest of IPython's design, and it is clear now that the effort was worth it: based on the ZeroMQ communications architecture introduced in version 0.11, the notebook can now retain 100% of the features of the real IPython. But it can also provide the rich media support and high quality Javascript libraries that were not available in browsers even one or two years ago (such as high-quality mathematical rendering or built-in video).

The notebook has too many useful and important features to describe in these release notes; our documentation now contains a directory called `examples/notebooks` with several notebooks that illustrate various aspects of the system. You should start by reading those named `00_notebook_tour.ipynb` and `01_notebook_introduction.ipynb` first, and then can proceed to read the others in any order you want.

To start the notebook server, go to a directory containing the notebooks you want to open (or where you want to create new ones) and type:

```
ipython notebook
```

You can see all the relevant options with:

```
ipython notebook --help
ipython notebook --help-all # even more
```

and just like the Qt console, you can start the notebook server with pylab support by using:

```
ipython notebook --pylab
```

for floating matplotlib windows or:

```
ipython notebook --pylab inline
```

for plotting support with automatically inlined figures. Note that it is now possible also to activate pylab support at runtime via `%pylab`, so you do not need to make this decision when starting the server.

Two-process terminal console

Based on the same architecture as the notebook and the Qt console, we also have now a terminal-based console that can connect to an external IPython kernel (the same kernels used by the Qt console or the notebook, in fact). While this client behaves almost identically to the usual IPython terminal application, this capability can be very useful to attach an interactive console to an existing kernel that was started externally. It lets you use the interactive `%debug` facilities in a notebook, for example (the web browser can't interact directly with the debugger) or debug a third-party code where you may have embedded an IPython kernel.

This is also something that we have wanted for a long time, and which is a culmination (as a team effort) of the work started last year during the 2010 Google Summer of Code project.

Tabbed QtConsole

The QtConsole now supports starting multiple kernels in tabs, and has a menubar, so it looks and behaves more like a real application. Keyboard enthusiasts can disable the menubar with ctrl-shift-M ([PR #887](#)).

Full Python 3 compatibility

IPython can now be installed from a single codebase on Python 2 and Python 3. The installation process for Python 3 automatically runs 2to3. The same „default“ profile is now used for Python 2 and 3 (the previous version had a separate „python3“ profile).

Standalone Kernel

The `ipython kernel` subcommand has been added, to allow starting a standalone kernel, that can be used with various frontends. You can then later connect a Qt console or a terminal console to this kernel by typing e.g.:

```
ipython qtconsole --existing
```

if it's the only one running, or by passing explicitly the connection parameters (printed by the kernel at startup).




Рис. 4: The improved Qt console for IPython, now with tabs to control multiple kernels and full menu support.

PyPy support

The terminal interface to IPython now runs under [PyPy](#). We will continue to monitor PyPy's progress, and hopefully before long at least we'll be able to also run the notebook. The Qt console may take longer, as Qt is a very complex set of bindings to a huge C++ library, and that is currently the area where PyPy still lags most behind. But for everyday interactive use at the terminal, with this release and PyPy 1.7, things seem to work quite well from our admittedly limited testing.

Other important new features

- **SSH Tunnels:** In 0.11, the `IPython.parallel` Client could tunnel its connections to the Controller via ssh. Now, the QtConsole supports ssh tunneling, as do parallel engines.
- **relaxed command-line parsing:** 0.11 was released with overly-strict command-line parsing, preventing the ability to specify arguments with spaces, e.g. `ipython --pylab qt` or `ipython -c "print 'hi'"`. This has been fixed, by using `argparse`. The new parsing is a strict superset of 0.11, so any commands in 0.11 should still work in 0.12.
- **HistoryAccessor:** The `HistoryManager` class for interacting with your IPython SQLite history database has been split, adding a parent `HistoryAccessor` class, so that users can write code to access and search their IPython history without being in an IPython session ([PR #824](#)).
- **kernel %gui and %pylab:** The `%gui` and `%pylab` magics have been restored to the IPython kernel (e.g. in the qtconsole or notebook). This allows activation of pylab-mode, or eventloop integration after starting the kernel, which was unavailable in 0.11. Unlike in the terminal, this can be set only once, and cannot be changed.
- **%config:** A new `%config` magic has been added, giving easy access to the IPython configuration system at runtime ([PR #923](#)).
- **Multiline History:** Multiline readline history has been restored to the Terminal frontend by default ([PR #838](#)).
- **%store:** The `%store` magic from earlier versions has been updated and re-enabled (*storemagic*; [PR #1029](#)). To autorestore stored variables on startup, specify `c.StoreMagic.autorestore = True` in `ipython_config.py`.

Major Bugs fixed

In this cycle, we have *closed over 500 issues*, but a few major ones merit special mention:

- Simple configuration errors should no longer crash IPython. In 0.11, errors in config files, as well as invalid trait values, could crash IPython. Now, such errors are reported, and help is displayed.
- Certain SyntaxErrors no longer crash IPython (e.g. just typing keywords, such as `return`, `break`, etc.). See [#704](#).
- IPython path utils, such as `get_ipython_dir()` now check for write permissions, so IPython should function on systems where the default path resolution might point to a read-only location, such as HOMESHARE on Windows ([#669](#)).
- `raw_input()` now works in the kernel when multiple frontends are in use. The request will be sent to the frontend that made the request, and an exception is raised if that frontend does not support stdin requests (e.g. the notebook) ([#673](#)).
- `zmq` version detection no longer uses simple lexicographical comparison to check minimum version, which prevents 0.11 from working with `pyzmq-2.1.10` ([PR #758](#)).

- A bug in PySide < 1.0.7 caused crashes on OSX when tooltips were shown ([#711](#)). these tooltips are now disabled on old PySide ([PR #963](#)).
- IPython no longer crashes when started on recent versions of Python 3 in Windows ([#737](#)).
- Instances of classes defined interactively can now be pickled ([#29](#); [PR #648](#)). Note that pickling saves a reference to the class definition, so unpickling the instances will only work where the class has been defined.

Backwards incompatible changes

- IPython connection information is no longer specified via ip/port directly, rather via json connection files. These files are stored in the security directory, and enable us to turn on HMAC message authentication by default, significantly improving the security of kernels. Various utility functions have been added to `IPython.lib.kernel`, for easier connecting to existing kernels.
- `KernelManager` now has one ip, and several port traits, rather than several ip/port pair `_addr` traits. This better matches the rest of the code, where the ip cannot not be set separately for each channel.
- Custom prompts are now configured using a new class, `PromptManager`, which has traits for `in_template`, `in2_template` (the `...:` continuation prompt), `out_template` and `rewrite_template`. This uses Python's string formatting system, so you can use `{time}` and `{cwd}`, although we have preserved the abbreviations from previous versions, e.g. `\#` (prompt number) and `\w` (working directory). For the list of available fields, refer to the source of `IPython/core/prompts.py`.
- The class inheritance of the Launchers in `IPython.parallel.apps.launcher` used by `ipcluster` has changed, so that trait names are more consistent across batch systems. This may require a few renames in your config files, if you customized the command-line args for launching controllers and engines. The configurable names have also been changed to be clearer that they point to class names, and can now be specified by name only, rather than requiring the full import path of each class, e.g.:

```
IPClusterEngines.engine_launcher = 'IPython.parallel.apps.launcher.  
↳MPIExecEngineSetLauncher'  
IPClusterStart.controller_launcher = 'IPython.parallel.apps.launcher.  
↳SSHControllerLauncher'
```

would now be specified as:

```
IPClusterEngines.engine_launcher_class = 'MPI'  
IPClusterStart.controller_launcher_class = 'SSH'
```

The full path will still work, and is necessary for using custom launchers not in IPython's launcher module.

Further, `MPIExec` launcher names are now prefixed with just `MPI`, to better match other batch launchers, and be generally more intuitive. The `MPIExec` names are deprecated, but continue to work.

- For embedding a shell, note that the parameters `user_global_ns` and `global_ns` have been deprecated in favour of `user_module` and `module` respectively. The new parameters expect a module-like object, rather than a namespace dict. The old parameters remain for backwards compatibility, although `user_global_ns` is now ignored. The `user_ns` parameter works the same way as before, and calling `embed()` with no arguments still works as before.

Development summary and credits

The previous version (IPython 0.11) was released on July 31 2011, so this release cycle was roughly 4 1/2 months long, we closed a total of 515 issues, 257 pull requests and 258 regular issues (a [detailed list](#) is available).

Many users and developers contributed code, features, bug reports and ideas to this release. Please do not hesitate in contacting us if we've failed to acknowledge your contribution here. In particular, for this release we have had commits from the following 45 contributors, a mix of new and regular names (in alphabetical order by first name):

- Alcides <alcides-at-do-not-span-me.com>
- Ben Edwards <bedwards-at-cs.unm.edu>
- Benjamin Ragan-Kelley <benjaminrk-at-gmail.com>
- Benjamin Thyreau <benjamin.thyreau-at-gmail.com>
- Bernardo B. Marques <bernardo.fire-at-gmail.com>
- Bernard Paulus <bprecyclebin-at-gmail.com>
- Bradley M. Froehle <brad.froehle-at-gmail.com>
- Brian E. Granger <ellisonbg-at-gmail.com>
- Christian Boos <cboos-at-bct-technology.com>
- Daniel Velkov <danielv-at-mylife.com>
- Erik Tollerud <erik.tollerud-at-gmail.com>
- Evan Patterson <epatters-at-enthought.com>
- Felix Werner <Felix.Werner-at-kit.edu>
- Fernando Perez <Fernando.Perez-at-berkeley.edu>
- Gabriel <g2p.code-at-gmail.com>
- Grahame Bowland <grahame-at-angrygoats.net>
- Hannes Schulz <schulz-at-ais.uni-bonn.de>
- Jens Hedegaard Nielsen <jenshnielsen-at-gmail.com>
- Jonathan March <jmarch-at-enthought.com>
- Jörgen Stenarson <jorgen.stenarson-at-bostream.nu>
- Julian Taylor <jtaylor.debian-at-googlemail.com>
- Kefu Chai <tchaikov-at-gmail.com>
- macgyver <neil.rabinowitz-at-merton.ox.ac.uk>
- Matt Cottingham <matt.cottingham-at-gmail.com>
- Matthew Brett <matthew.brett-at-gmail.com>
- Matthias BUSSONNIER <bussonniermatthias-at-gmail.com>
- Michael Droettboom <mdboom-at-gmail.com>
- Nicolas Rougier <Nicolas.Rougier-at-inria.fr>
- Olivier Verdier <olivier.verdier-at-gmail.com>

- Omar Andres Zapata Mesa <andresete.chaos-at-gmail.com>
- Pablo Winant <pablo.winant-at-gmail.com>
- Paul Ivanov <pivanov314-at-gmail.com>
- Pauli Virtanen <pav-at-iki.fi>
- Pete Aykroyd <aykroyd-at-gmail.com>
- Prabhu Ramachandran <prabhu-at-enthought.com>
- Puneeth Chaganti <punchagan-at-gmail.com>
- Robert Kern <robert.kern-at-gmail.com>
- Satrajit Ghosh <satra-at-mit.edu>
- Stefan van der Walt <stefan-at-sun.ac.za>
- Szabolcs Horvát <szhorvat-at-gmail.com>
- Thomas Kluyver <takowl-at-gmail.com>
- Thomas Spura <thomas.spura-at-gmail.com>
- Timo Paulssen <timonator-at-perpetuum-immobile.de>
- Valentin Haenel <valentin.haenel-at-gmx.de>
- Yaroslav Halchenko <debian-at-onerussian.com>

Примечание: This list was generated with the output of `git log rel-0.11..HEAD --format='%aN <%aE>' | sed 's/@/\-at\-/ ' | sed 's/</>/' | sort -u` after some cleanup. If you should be on this list, please add yourself.

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

2.22 Issues closed in the 0.12 development cycle

2.22.1 Issues closed in 0.12.1

GitHub stats for bugfix release 0.12.1 (12/28/2011-04/16/2012), backporting pull requests from 0.13.

We closed a total of 71 issues: 44 pull requests and 27 issues; this is the full list (generated with the script `tools/github_stats.py`).

This list is automatically generated, and may be incomplete:

Pull Requests (44):

- PR #1175: core.completer: Clean up excessive and unused code.
- PR #1187: misc notebook: connection file cleanup, first heartbeat, startup flush
- PR #1190: Fix link to Chris Fettes blog post about 0.11 highlights.
- PR #1196: docs: looks like a file path might have been accidentally pasted in the middle of a word
- PR #1206: don't preserve fixConsole output in json
- PR #1207: fix loadpy duplicating newlines
- PR #1213: BUG: Minor typo in history_console_widget.py
- PR #1218: Added -q option to %prun for suppression of the output, along with editing the dochelp string.
- PR #1222: allow Reference as callable in map/apply
- PR #1229: Fix display of SyntaxError in Python 3
- PR #1246: Skip tests that require X, when importing pylab results in RuntimeError.
- PR #1253: set auto_create flag for notebook apps
- PR #1257: use self.kernel_manager_class in qtconsoleapp
- PR #1262: Heartbeat no longer shares the app's Context
- PR #1283: HeartMonitor.period should be an Integer
- PR #1284: a fix for GH 1269
- PR #1289: Make autoreload extension work on Python 3.
- PR #1306: Fix %prun input parsing for escaped characters (closes #1302)
- PR #1312: minor heartbeat tweaks
- PR #1318: make Ctrl-D in qtconsole act same as in terminal (ready to merge)
- PR #1341: Don't attempt to tokenize binary files for tracebacks
- PR #1353: Save notebook as script using unicode file handle.
- PR #1363: Fix some minor color/style config issues in the qtconsole
- PR #1364: avoid jsonlib returning Decimal
- PR #1369: load header with engine id when engine dies in TaskScheduler
- PR #1370: allow draft76 websockets (Safari)
- PR #1374: remove calls to meaningless ZMQStream.on_err
- PR #1377: Saving non-ascii history
- PR #1396: Fix for %tb magic.
- PR #1402: fix symlinked /home issue for FreeBSD
- PR #1413: get_home_dir expands symlinks, adjust test accordingly
- PR #1414: ignore errors in shell.var_expand
- PR #1430: Fix for tornado check for tornado < 1.1.0
- PR #1445: Don't build sphinx docs for sdists
- PR #1463: Fix completion when importing modules in the cwd.

- PR #1477: fix dangling `buffer` in `IPython.parallel.util`
- PR #1495: BUG: Fix pretty-printing for overzealous objects
- PR #1496: BUG: LBYL when clearing the output history on shutdown.
- PR #1514: DOC: Fix references to `IPython.lib.pretty` instead of the old location
- PR #1517: Fix indentation bug in `IPython/lib/pretty.py`
- PR #1538: store git commit hash in `utils._sysinfo` instead of hidden data file
- PR #1599: Fix for `%run -d` in Python 3
- PR #1602: Fix `%env` for Python 3
- PR #1607: cleanup `sqlitedb` temporary db file after tests

Issues (27):

- #676: `IPython.embed()` from `ipython` crashes twice on exit
- #846: Autoreload extension doesn't work with Python 3.2
- #1187: misc notebook: connection file cleanup, first heartbeat, startup flush
- #1191: profile/startup files not executed with «notebook»
- #1197: Interactive shell trying to: `from ... import history`
- #1198: Kernel Has Died error in Notebook
- #1201: `%env` magic fails with Python 3.2
- #1204: double newline from `%loadpy` in python notebook (at least on mac)
- #1208: should `dv.sync_import` print failed imports ?
- #1225: `SyntaxError` display broken in Python 3
- #1232: Dead kernel loop
- #1241: When our debugger class is used standalone `_oh` key errors are thrown
- #1254: typo in `notebooklist.js` breaks links
- #1260: heartbeat failure on long gil-holding operation
- #1268: notebook `%reset` magic fails with `StdinNotImplementedError`
- #1269: Another strange input handling error
- #1281: in Hub: `registration_timeout` must be an integer, but `heartmonitor.period` is `CFloat`
- #1302: Input parsing with `%prun` clobbers escapes
- #1304: controller/server load can disrupt heartbeat
- #1317: Very slow traceback construction from Cython extension
- #1345: notebook can't save unicode as script
- #1375: `%history -g -f` file encoding issue
- #1401: numpy arrays cannot be used with `View.apply()` in Python 3
- #1408: `test_get_home_dir_3` failed on Mac OS X
- #1412: Input parsing issue with `%prun`
- #1421: `ipython32 %run -d` breaks with `NameError` name „`execfile`“ is not defined

- [#1484](#): unhide `.git_commit_info.ini`

2.22.2 Issues closed in 0.12

In this cycle, from August 1 to December 28 2011, we closed a total of 515 issues, 257 pull requests and 258 regular issues; this is the full list (generated with the script `tools/github_stats.py`).

Pull requests (257):

- [1174](#): Remove `%install_default_config` and `%install_profiles`
- [1178](#): Correct string type casting in `pinfo`.
- [1096](#): Show class init and call tooltips in notebook
- [1176](#): Modifications to profile list
- [1173](#): don't load `gui/pylab` in console frontend
- [1168](#): Add `--script` flag as shorthand for notebook `save_script` option.
- [1165](#): encode `image_tag` as utf8 in `[x]html` export
- [1161](#): Allow `%loadpy` to load remote URLs that don't end in `.py`
- [1158](#): Add coding header when notebook exported to `.py` file.
- [1160](#): don't ignore ctrl-C during `%gui qt`
- [1159](#): Add encoding header to Python files downloaded from notebooks.
- [1155](#): minor post-execute fixes ([#1154](#))
- [1153](#): Pager tearing bug
- [1152](#): Add support for displaying `matplotlib` axes directly.
- [1079](#): Login/out button cleanups
- [1151](#): allow access to `user_ns` in `prompt_manager`
- [1120](#): updated `vim-ipython` (pending)
- [1150](#): BUG: Scrolling pager in `vsplit` on Mac OSX tears.
- [1149](#): [#1148](#) (`win32 arg_split`)
- [1147](#): Put `qtconsole` foreground when launching
- [1146](#): allow saving `notebook.py` next to `notebook.ipynb`
- [1128](#): fix `pylab` `StartMenu` item
- [1140](#): Namespaces for embedding
- [1132](#): `[notebook]` read-only: disable name field
- [1125](#): notebook : update logo
- [1135](#): allow customized template and static file paths for the notebook web app
- [1122](#): BUG: Issue [#755](#) `qt IPythonWidget.execute_file` fails if filename contains...
- [1137](#): rename `MPIExecLaunchers` to `MPILaunchers`
- [1130](#): optionally ignore `shlex`'s `ValueError` in `arg_split`
- [1116](#): `Shlex` unicode

- 1073: Storemagic plugin
- 1143: Add post_install script to create start menu entries in Python 3
- 1138: Fix tests to work when ~/.config/ipython contains a symlink.
- 1121: Don't transform function calls on IPyAutocall objects
- 1118: protect CRLF from carriage-return action
- 1105: Fix for prompts containing newlines.
- 1126: Totally remove pager when read only (notebook)
- 1091: qtconsole : allow copy with shortcut in pager
- 1114: fix magics history in two-process ipython console
- 1113: Fixing #1112 removing failing asserts for test_carriage_return and test_beep
- 1089: Support carriage return ("r") and beep ("b") characters in the qtconsole
- 1108: Completer usability 2 (rebased of pr #1082)
- 864: Two-process terminal frontend (ipython core branch)
- 1082: usability and cross browser compat for completer
- 1053: minor improvements to text placement in qtconsole
- 1106: Fix display of errors in compiled code on Python 3
- 1077: allow the notebook to run without MathJax
- 1072: If object has a getdoc() method, override its normal docstring.
- 1059: Switch to simple __IPYTHON__ global
- 1070: Execution count after SyntaxError
- 1098: notebook: config section UI
- 1101: workaround spawnb missing from pexpect.__all__
- 1097: typo, should fix #1095
- 1099: qtconsole export xhtml/utf8
- 1083: Prompts
- 1081: Fix wildcard search for updated namespaces
- 1084: write busy in notebook window title...
- 1078: PromptManager fixes
- 1064: Win32 shlex
- 1069: As you type completer, fix on Firefox
- 1039: Base of an as you type completer.
- 1065: Qtconsole fix racecondition
- 507: Prompt manager
- 1056: Warning in code. qtconsole ssh -X
- 1036: Clean up javascript based on js2-mode feedback.
- 1052: Pylab fix

- 648: Usermod
- 969: Pexpect-u
- 1007: Fix paste/cpaste bug and refactor/cleanup that code a lot.
- 506: make ENTER on a previous input field replace current input buffer
- 1040: json/jsonapi cleanup
- 1042: fix firefox (windows) break line on empty prompt number
- 1015: emacs freezes when tab is hit in ipython with latest python-mode
- 1023: flush stdout/stderr at the end of kernel init
- 956: Generate «All magics...» menu live
- 1038: Notebook: don't change cell when selecting code using shift+up/down.
- 987: Add Tooltip to notebook.
- 1028: Cleaner minimum version comparison
- 998: defer to stdlib for path.get_home_dir()
- 1033: update copyright to 2011/20xx-2011
- 1032: Intercept <esc> avoid closing websocket on Firefox
- 1030: use pyzmq tools where appropriate
- 1029: Restore pspersistence, including %store magic, as an extension.
- 1025: Dollar escape
- 999: Fix issue #880 - more useful message to user when %paste fails
- 938: changes to get ipython.el to work with the latest python-mode.el
- 1012: Add logout button.
- 1020: Dollar formatter for ! shell calls
- 1019: Use repr() to make quoted strings
- 1008: don't use crash_handler by default
- 1003: Drop consecutive duplicates when refilling readline history
- 997: don't unregister interrupted post-exec functions
- 996: add Integer traitlet
- 1016: Fix password hashing for Python 3
- 1014: escape minus signs in manpages
- 1013: [NumPyExampleDocstring] link was pointing to raw file
- 1011: Add hashed password support.
- 1005: Quick fix for os.system requiring str parameter
- 994: Allow latex formulas in HTML output
- 955: Websocket Adjustments
- 979: use system_raw in terminal, even on Windows
- 989: fix arguments for commands in _process_posix

- 991: Show traceback, continuing to start kernel if pylab init fails
- 981: Split likely multiline text when writing JSON notebooks
- 957: allow change of png DPI in inline backend
- 968: add wantDirectory to ipdoctest, so that directories will be checked for e
- 984: Do not expose variables defined at startup to %who etc.
- 985: Fixes for parallel code on Python 3
- 963: disable calltips in PySide < 1.0.7 to prevent segfault
- 976: Getting started on what's new
- 929: Multiline history
- 964: Default profile
- 961: Disable the pager for the test suite
- 953: Physics extension
- 950: Add directory for startup files
- 940: allow setting HistoryManager.hist_file with config
- 948: Monkeypatch Tornado 2.1.1 so it works with Google Chrome 16.
- 916: Run p (<https://github.com/ipython/ipython/pull/901>)
- 923: %config magic
- 920: unordered iteration of AsyncMapResults (+ a couple fixes)
- 941: Follow-up to 387dcd6a, _r1.__doc__ is None with pyreadline
- 931: read-only notebook mode
- 921: Show invalid config message on TraitErrors during init
- 815: Fix #481 using custom qt4 input hook
- 936: Start webbrowser in a thread. Prevents lockup with Chrome.
- 937: add dirty trick for readline import on OSX
- 913: Py3 tests2
- 933: Cancel in qt console closeevent should trigger event.ignore()
- 930: read-only notebook mode
- 910: Make import checks more explicit in %whos
- 926: reincarnate -V cmdline option
- 928: BUG: Set context for font size change shortcuts in ConsoleWidget
- 901: - There is a bug when running the profiler in the magic command (prun) with python3
- 912: Add magic for cls on windows. Fix for #181.
- 905: enable %gui/%pylab magics in the Kernel
- 909: Allow IPython to run without sqlite3
- 887: Qtconsole menu
- 895: notebook download implies save

- 896: Execfile
- 899: Brian's Notebook work
- 892: don't close figures every cycle with inline matplotlib backend
- 893: Adding clear_output to kernel and HTML notebook
- 789: Adding clear_output to kernel and HTML notebook.
- 898: Don't pass unicode sys.argv with %run or `ipython script.py`
- 897: Add tooltips to the notebook via „title“ attr.
- 877: partial fix for issue #678
- 838: reenable multiline history for terminals
- 872: The constructor of Client() checks for AssertionError in validate_url to open a file instead of connection to a URL if it fails.
- 884: Notebook usability fixes
- 883: User notification if notebook saving fails
- 889: Add drop_by_id method to shell, to remove variables added by extensions.
- 891: Ability to open the notebook in a browser when it starts
- 813: Create menu bar for qtconsole
- 876: protect IPython from bad custom exception handlers
- 856: Backgroundjobs
- 868: Warn user if MathJax can't be fetched from notebook closes #744
- 878: store_history=False default for run_cell
- 824: History access
- 850: Update codemirror to 2.15 and make the code internally more version-agnostic
- 861: Fix for issue #56
- 819: Adding -m option to %run, similar to -m for python interpreter.
- 855: promote aliases and flags, to ensure they have priority over config files
- 862: BUG: Completion widget position and pager focus.
- 847: Allow connection to kernels by files
- 708: Two-process terminal frontend
- 857: make sdist flags work again (e.g. --manifest-only)
- 835: Add Tab key to list of keys that scroll down the paging widget.
- 859: Fix for issue #800
- 848: Python3 setup.py install failiure
- 845: Tests on Python 3
- 802: DOC: extensions: add documentation for the bundled extensions
- 830: contiguous stdout/stderr in notebook
- 761: Windows: test runner fails if repo path (e.g. home dir) contains spaces

- 801: Py3 notebook
- 809: use CFFRunLoop directly in `ipython kernel --pylab osx`
- 841: updated old scipy.org links, other minor doc fixes
- 837: remove all trailing spaces
- 834: Issue <https://github.com/ipython/ipython/issues/832> resolution
- 746: ENH: extensions: port autoreload to current API
- 828: fixed permissions (sub-modules should not be executable) + added shebang for `run_ipy_in_profiler.py`
- 798: pexpect & Python 3
- 804: Magic „range“ crash if greater than `len(input_hist)`
- 821: update tornado dependency to 2.1
- 807: Facilitate ssh tunnel sharing by announcing ports
- 795: Add cluster-id for multiple cluster instances per profile
- 742: Glut
- 668: Greedy completer
- 776: Reworking qtconsole shortcut, add fullscreen
- 790: TST: add future unicode_literals test (#786)
- 775: `redirect_in/redirect_out` should be constrained to windows only
- 793: Don't use readline in the ZMQShell
- 743: Pyglet
- 774: basic/initial .mailmap for nice shortlog summaries
- 770: #769 (reopened)
- 784: Parse user code to AST using compiler flags.
- 783: always use StringIO, never cStringIO
- 782: flush stdout/stderr on displayhook call
- 622: Make pylab import all configurable
- 745: Don't assume history requests succeed in qtconsole
- 725: don't assume `cursor.selectedText()` is a string
- 778: don't override `execfile` on Python 2
- 663: Python 3 compatibility work
- 762: qtconsole ipython widget's `execute_file` fails if filename contains spaces or quotes
- 763: Set context for shortcuts in ConsoleWidget
- 722: PyPy compatibility
- 757: `ipython.el` is broken in 0.11
- 764: fix «`--colors=<color>`» option in `py-python-command-args`.
- 758: use ROUTER/DEALER socket names instead of XREP/XREQ

- 736: enh: added authentication ability for webapp
- 748: Check for tornado before running frontend.html tests.
- 754: restore msg_id/msg_type aliases in top level of msg dict
- 769: Don't treat bytes objects as json-safe
- 753: DOC: msg[,msg_type"] removed
- 766: fix «-colors=<color>» option in py-python-command-args.
- 765: fix «-colors=<color>» option in py-python-command-args.
- 741: Run PyOs_InputHook in pager to keep plot windows interactive.
- 664: Remove ipythonrc references from documentation
- 750: Tiny doc fixes
- 433: ZMQ terminal frontend
- 734: Allow %magic argument filenames with spaces to be specified with quotes under win32
- 731: respect encoding of display data from urls
- 730: doc improvements for running notebook via secure protocol
- 729: use null char to start markdown cell placeholder
- 727: Minor fixes to the htmlnotebook
- 726: use bundled argparse if system argparse is < 1.1
- 705: Htmlnotebook
- 723: Add „import time“ to IPython/parallel/apps/launcher.py as time.sleep is called without time being imported
- 714: Install mathjax for offline use
- 718: Underline keyboard shortcut characters on appropriate buttons
- 717: Add source highlighting to markdown snippets
- 716: update EvalFormatter to allow arbitrary expressions
- 712: Reset execution counter after cache is cleared
- 713: Align colons in html notebook help dialog
- 709: Allow usage of „“ in notebook names
- 706: Implement static publishing of HTML notebook
- 674: use argparse to parse aliases & flags
- 679: HistoryManager.get_session_info()
- 696: Fix columnize bug, where tab completion with very long filenames would crash Qt console
- 686: add ssh tunnel support to qtconsole
- 685: Add SSH tunneling to engines
- 384: Allow pickling objects defined interactively.
- 647: My fix rpmlint
- 587: don't special case for py3k+numpy

- 703: make config-loading debug messages more explicit
- 699: make calltips configurable in qtconsole
- 666: parallel tests & extra readline escapes
- 683: BF - allow nose with-doctest setting in environment
- 689: Protect ipkernel from bad messages
- 702: Prevent ipython.py launcher from being imported.
- 701: Prevent ipython.py from being imported by accident
- 670: check for writable dirs, not just existence, in utils.path
- 579: Sessionwork
- 687: add `ipython kernel` for starting just a kernel
- 627: Qt Console history search
- 646: Generate package list automatically in `find_packages`
- 660: i658
- 659: don't crash on bad config files

Regular issues (258):

- 1177: UnicodeDecodeError in py3compat from «xlrd??»
- 1094: Tooltip doesn't show constructor docstrings
- 1170: double pylab greeting with `c.InteractiveShellApp.pylab = «tk»` in `zmqconsole`
- 1166: E-mail cpaste broken
- 1164: IPython qtconsole (0.12) can't export to html with external png
- 1103: `%loadpy` should cut out encoding declaration
- 1156: Notebooks downloaded as Python files require a header stating the encoding
- 1157: Ctrl-C not working when GUI/pylab integration is active
- 1154: We should be less aggressive in de-registering post-execution functions
- 1134: «select-all, kill» leaves qtconsole in unusable state
- 1148: A lot of testerrors
- 803: Make doctests work with Python 3
- 1119: Start menu shortcuts not created in Python 3
- 1136: The embedding machinery ignores `user_ns`
- 607: Use the new IPython logo/font in the notebook header
- 755: qtconsole ipython widget's `execute_file` fails if filename contains spaces or quotes
- 1115: `shlex_split` should return unicode
- 1109: `timeit` with string ending in space gives «ValueError: No closing quotation»
- 1142: Install problems
- 700: Some SVG images render incorrectly in `htmlnotebook`
- 1117: `quit()` doesn't work in terminal

- 1111: ls broken after merge of #1089
- 1104: Prompt spacing weird
- 1124: Seg Fault 11 when calling PySide using «run» command
- 1088: QtConsole : can't copy from pager
- 568: Test error and failure in IPython.core on windows
- 1112: testfailure in IPython.frontend on windows
- 1102: magic in IPythonDemo fails when not located at top of demo file
- 629: r and b in qtconsole don't behave as expected
- 1080: Notebook: tab completion should close on «(»
- 973: Qt Console close dialog and on-top Qt Console
- 1087: QtConsole xhtml/Svg export broken ?
- 1067: Parallel test suite hangs on Python 3
- 1018: Local mathjax breaks install
- 993: raw_input redirection to foreign kernels is extremely brittle
- 1100: ipython3 traceback unicode issue from extensions
- 1071: Large html-notebooks hang on load on a slow machine
- 89: %pdoc np.ma.compress shows docstring twice
- 22: Include improvements from anythingipython.el
- 633: Execution count & SyntaxError
- 1095: Uncaught TypeError: Object has no method „remove_and_cancel_tooltip“
- 1075: We're ignoring prompt customizations
- 1086: Can't open qtconsole from outside source tree
- 1076: namespace changes broke `foo.*bar*?` syntax
- 1074: pprinting old-style class objects fails (TypeError: „tuple“ object is not callable)
- 1063: IPython.utils test error due to missing unicodedata module
- 592: Bug in argument parsing for %run
- 378: Windows path escape issues
- 1068: Notebook tab completion broken in Firefox
- 75: No tab completion after «/»
- 103: customizable cpaste
- 324: Remove code in IPython.testing that is not being used
- 131: Global variables not seen by cprofile.run()
- 851: IPython shell swallows exceptions in certain circumstances
- 882: ipython freezes at start if IPYTHONDIR is on an NFS mount
- 1057: Blocker: Qt console broken after «all magics» menu became dynamic
- 1027: ipython does not like white space at end of file

- 1058: New bug: Notebook asks for confirmation to leave even saved pages.
- 1061: rep (magic recall) under pypy
- 1047: Document the notebook format
- 102: Properties accessed twice for classes defined interactively
- 16: %store raises exception when storing compiled regex
- 67: tab expansion should only take one directory level at the time
- 62: Global variables undefined in interactive use of embedded ipython shell
- 57: debugging with ipython does not work well outside ipython
- 38: Line entry edge case error
- 980: Update parallel docs for new parallel architecture
- 1017: Add small example about ipcluster/ssh startup
- 1041: Proxy Issues
- 967: KernelManagers don't use zmq eventloop properly
- 1055: «All Magics» display on Ubuntu
- 1054: ipython explodes on syntax error
- 1051: ipython3 set_next_input() failure
- 693: «run -i» no longer works after %reset in terminal
- 29: cPickle works in standard interpreter, but not in IPython
- 1050: ipython3 broken by commit 8bb887c8c2c447bf7
- 1048: Update docs on notebook password
- 1046: Searies of questions/issues?
- 1045: crash when exiting - previously launched embedded sub-shell
- 1043: pylab doesn't work in qtconsole
- 1044: run -p doesn't work in python 3
- 1010: emacs freezes when ipython-complete is called
- 82: Update devel docs with discussion about good changelogs
- 116: Update release management scripts and release.revision for git
- 1022: Pylab banner shows up with first cell to execute
- 787: Keyboard selection of multiple lines in the notebook behaves inconsistently
- 1037: notepad + jsonlib: TypeError: Only whitespace may be used for indentation.
- 970: Default home not writable, %HOME% does not help (windows)
- 747: HOMESHARE not a good choice for «writable homedir» on Windows
- 810: cleanup utils.path.get_home_dir
- 2: Fix the copyright statement in source code files to be accurate
- 1031: <esc> on Firefox crash websocket
- 684: %Store eliminated in configuration and magic commands in 0.11

- 1026: BUG: wrong default parameter in ask_yes_no
- 880: Better error message if %paste fails
- 1024: autopx magic broken
- 822: Unicode bug in Itpl when expanding shell variables in syscalls with !
- 1009: Windows: regression in cd magic handling of paths
- 833: Crash python with matplotlib and unequal length arrays
- 695: Crash handler initialization is too aggressive
- 1000: Remove duplicates when refilling readline history
- 992: Interrupting certain matplotlib operations leaves the inline backend „wedged“
- 942: number traits should cast if value doesn't change
- 1006: ls crashes when run on a UNC path or with non-ascii args
- 944: Decide the default image format for inline figures: SVG or PNG?
- 842: Python 3 on Windows (pyreadline) - expected an object with the buffer interface
- 1002: ImportError due to incorrect version checking
- 1001: IPython «source» command?
- 954: IPython embed doesn't respect namespaces
- 681: pdb freezes inside qtconsole
- 698: crash report «TypeError: can only concatenate list (not «unicode») to list»
- 978: ipython 0.11 buffers external command output till the cmd is done
- 952: Need user-facing warning in the browser if websocket connection fails
- 988: Error using idlsave
- 990: ipython notebook - kernel dies if matplotlib is not installed
- 752: Matplotlib figures showed only once in notebook
- 54: Exception hook should be optional for embedding IPython in GUIs
- 918: IPython.frontend tests fail without tornado
- 986: Views created with c.direct_view() fail
- 697: Filter out from %who names loaded at initialization time
- 932: IPython 0.11 quickref card has superfluous «%recall and»
- 982: png files with executable permissions
- 914: Simpler system for running code after InteractiveShell is initialised
- 911: ipython crashes on startup if readline is missing
- 971: bookmarks created in 0.11 are corrupt in 0.12
- 974: object feature tab-completion crash
- 939: ZMQShell always uses default profile
- 946: Multi-tab Close action should offer option to leave all kernels alone
- 949: Test suite must not require any manual interaction

- 643: enable gui eventloop integration in ipkernel
- 965: ipython is crashed without launch.(python3.2)
- 958: Can't use os X clipboard on with qtconsole
- 962: Don't require tornado in the tests
- 960: crash on syntax error on Windows XP
- 934: The latest ipython branch doesn't work in Chrome
- 870: zmq version detection
- 943: HISTIGNORE for IPython
- 947: qtconsole segfaults at startup
- 903: Expose a magic to control config of the inline pylab backend
- 908: bad user config shouldn't crash IPython
- 935: Typing **break** causes IPython to crash.
- 869: Tab completion of ~/ shows no output post 0.10.x
- 904: whos under pypy1.6
- 773: check_security_dir() and check_pid_dir() fail on network filesystem
- 915: OS X Lion Terminal.app line wrap problem
- 886: Notebook kernel crash when specifying --notebook-dir on commandline
- 636: debugger.py: pydb broken
- 808: Ctrl+C during %reset confirm message crash Qtconsole
- 927: Using return outside a function crashes ipython
- 919: Pop-up segfault when moving cursor out of qtconsole window
- 181: cls command does not work on windows
- 917: documentation typos
- 818: %run does not work with non-ascii characters in path
- 907: Errors in custom completer functions can crash IPython
- 867: doc: notebook password authentication howto
- 211: paste command not working
- 900: Tab key should insert 4 spaces in qt console
- 513: [Qt console] cannot insert new lines into console functions using tab
- 906: qtconsoleapp „parse_command_line“ doesn't like --existing anymore
- 638: Qt console --pylab=inline and getfigs(), etc.
- 710: unwanted unicode passed to args
- 436: Users should see tooltips for all buttons in the notebook UI
- 207: ipython crashes if atexit handler raises exception
- 692: use of Tracer() when debugging works but gives error messages
- 690: debugger does not print error message by default in 0.11

- 571: history of multiline entries
- 749: IPython.parallel test failure under Windows 7 and XP
- 890: ipclusterapp.py - help
- 885: `ws-hostname` alias not recognized by notebook
- 881: Missing manual.pdf?
- 744: cannot create notebook in offline mode if mathjax not installed
- 865: Make tracebacks from `%paste` show the code
- 535: exception unicode handling in `%run` is faulty in qtconsole
- 817: IPython crashed
- 799: `%edit` magic not working on windows xp in qtconsole
- 732: QtConsole wrongly promotes the index of the input line on which user presses Enter
- 662: ipython test failures on Mac OS X Lion
- 650: Handle bad config files better
- 829: We should not insert new lines after all print statements in the notebook
- 874: ipython-qtconsole: pyzmq Version Comparison
- 640: matplotlib macosx windows don't respond in qtconsole
- 624: ipython intermittently segfaults when figure is closed (Mac OS X)
- 871: Notebook crashes if a profile is used
- 56: Have `%cpaste` accept also Ctrl-D as a termination marker
- 849: Command line options to not override profile options
- 806: Provide single-port connection to kernels
- 691: [wishlist] Automatically find existing kernel
- 688: local security vulnerability: all ports visible to any local user.
- 866: DistributionNotFound on running ipython 0.11 on Windows XP x86
- 673: `raw_input` appears to be round-robin for qtconsole
- 863: Graceful degradation when home directory not writable
- 800: Timing scripts with `run -t -N <N>` fails on report output
- 858: Typing „continue“ makes ipython0.11 crash
- 840: all processes run on one CPU core
- 843: «import braces» crashes ipython
- 836: Strange Output after IPython Install
- 839: Qtconsole segfaults when mouse exits window with active tooltip
- 827: Add support for checking several limits before running task on engine
- 826: Add support for creation of parallel task when no engine is running
- 832: Improve error message for `%logstop`
- 831: `%logstart` in read-only directory forbid any further command

- 814: ipython does not start – DistributionNotFound
- 794: Allow >1 controller per profile
- 820: Tab Completion feature
- 812: Qt console crashes on Ubuntu 11.10
- 816: Import error using Python 2.7 and dateutil2.0 No module named `_thread`
- 756: qtconsole Windows fails to print error message for „%run nonexistent_file“
- 651: Completion doesn't work on element of a list
- 617: [qtconsole] %hist doesn't show anything in qtconsole
- 786: from `__future__` import `unicode_literals` does not work
- 779: Using `irunner` from virtual env uses systemwide ipython
- 768: codepage handling of output from scripts and shellcommands are not handled properly by qtconsole
- 785: Don't strip leading whitespace in `repr()` in notebook
- 737: in `pickleshare.py` line52 should be «if not `os.path.isdir(self.root):`»?
- 738: in `ipthon_win_post_install.py` line 38
- 777: `print(..., sep=...)` raises `SyntaxError`
- 728: ipcontroller crash with MPI
- 780: qtconsole Out value prints before the print statements that precede it
- 632: IPython Crash Report (0.10.2)
- 253: Unable to install ipython on windows
- 80: Split `IPClusterApp` into multiple Application subclasses for each subcommand
- 34: non-blocking `pendingResult` partial results
- 739: Tests fail if tornado not installed
- 719: Better support Pypy
- 667: qtconsole problem with default pylab profile
- 661: `ipythonrc` referenced in magic command in 0.11
- 665: Source introspection with `??` is broken
- 724: crash - ipython qtconsole, %quickref
- 655: ipython with qtconsole crashes
- 593: HTML Notebook Prompt can be deleted ...
- 563: use `argparse` instead of `kvloader` for flags&aliases
- 751: Tornado version greater than 2.0 needed for firefox 6
- 720: Crash report when importing easter egg
- 740: Ctrl-Enter clears line in notebook
- 772: ipengine fails on Windows with «XXX lineno: 355, opcode: 0»
- 771: Add python 3 tag to `setup.py`
- 767: non-ascii in `__doc__` string crashes qtconsole kernel when showing tooltip

- 733: In Windows, %run fails to strip quotes from filename
- 721: no completion in emacs by `ipython(ipython.el)`
- 669: Do not accept an `ipython_dir` that's not writeable
- 711: segfault on mac os x
- 500: «RuntimeError: Cannot change input buffer during execution» in `console_widget.py`
- 707: Copy and paste keyboard shortcuts do not work in Qt Console on OS X
- 478: PyZMQ's use of memoryviews breaks reconstruction of numpy arrays
- 694: Turning off callout tips in `qtconsole`
- 704: `return` kills IPython
- 442: Users should have intelligent autoindenting in the notebook
- 615: Wireframe and implement a project dashboard page
- 614: Wireframe and implement a notebook dashboard page
- 606: Users should be able to use the notebook to import/export a notebook to `.py` or `.rst`
- 604: A user should be able to leave a kernel running in the notebook and reconnect
- 298: Users should be able to save a notebook and then later reload it
- 649: `ipython qtconsole (v0.11)`: setting «`c.IPythonWidget.in_prompt = „>>> „`», crashes
- 672: What happened to `Exit`?
- 658: Put the `InteractiveShellApp` section first in the auto-generated config files
- 656: [suggestion] dependency checking for `pyqt` for Windows installer
- 654: broken documentation link on download page
- 653: Test failures in `IPython.parallel`

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

2.23 0.11 Series

2.23.1 Release 0.11

IPython 0.11 is a *major* overhaul of IPython, two years in the making. Most of the code base has been rewritten or at least reorganized, breaking backward compatibility with several APIs in previous versions. It is the first major release in two years, and probably the most significant change to IPython since its inception. We plan to have a relatively quick succession of releases, as people discover new bugs and regressions. Once we iron out any significant bugs in this process and settle down the new APIs, this series will become IPython 1.0. We encourage feedback now on the core APIs, which we hope to maintain stable during the 1.0 series.

Since the internal APIs have changed so much, projects using IPython as a library (as opposed to end-users of the application) are the most likely to encounter regressions or changes that break their existing use patterns. We will make every effort to provide updated versions of the APIs to facilitate the transition, and we encourage you to contact us on the [development mailing list](#) with questions and feedback.

Chris Fongesbeck recently wrote an [excellent post](#) that highlights some of our major new features, with examples and screenshots. We encourage you to read it as it provides an illustrated, high-level overview complementing the detailed feature breakdown in this document.

A quick summary of the major changes (see below for details):

- **Standalone Qt console:** a new rich console has been added to IPython, started with `ipython qtconsole`. In this application we have tried to retain the feel of a terminal for fast and efficient workflows, while adding many features that a line-oriented terminal simply can not support, such as inline figures, full multiline editing with syntax highlighting, graphical tooltips for function calls and much more. This development was sponsored by [Enthought Inc.](#). See [below](#) for details.
- **High-level parallel computing with ZeroMQ.** Using the same architecture that our Qt console is based on, we have completely rewritten our high-level parallel computing machinery that in prior versions used the Twisted networking framework. While this change will require users to update their codes, the improvements in performance, memory control and internal consistency across our codebase convinced us it was a price worth paying. We have tried to explain how to best proceed with this update, and will be happy to answer questions that may arise. A full tutorial describing these features [was presented at SciPy'11](#), more details [below](#).
- **New model for GUI/plotting support in the terminal.** Now instead of the various `-Xthread` flags we had before, GUI support is provided without the use of any threads, by directly integrating GUI event loops with Python's `PyOS_InputHook` API. A new command-line flag `--gui` controls GUI support, and it can also be enabled after IPython startup via the new `%gui` magic. This requires some changes if you want to execute GUI-using scripts inside IPython, see [the GUI support section](#) for more details.
- **A two-process architecture.** The Qt console is the first use of a new model that splits IPython between a kernel process where code is executed and a client that handles user interaction. We plan on also providing terminal and web-browser based clients using this infrastructure in future releases. This model allows multiple clients to interact with an IPython process through a [well-documented messaging protocol](#) using the ZeroMQ networking library.
- **Refactoring.** the entire codebase has been refactored, in order to make it more modular and easier to contribute to. IPython has traditionally been a hard project to participate because the old codebase was very monolithic. We hope this (ongoing) restructuring will make it easier for new developers to join us.
- **Vim integration.** Vim can be configured to seamlessly control an IPython kernel, see the files in [docs/examples/vim](#) for the full details. This work was done by Paul Ivanov, who prepared a nice [video demonstration](#) of the features it provides.

- **Integration into Microsoft Visual Studio.** Thanks to the work of the Microsoft [Python Tools for Visual Studio](#) team, this version of IPython has been integrated into Microsoft Visual Studio's Python tools open source plug-in. [Details below](#)
- **Improved unicode support.** We closed many bugs related to unicode input.
- **Python 3.** IPython now runs on Python 3.x. See [Python 3 support](#) for details.
- **New profile model.** Profiles are now directories that contain all relevant information for that session, and thus better isolate IPython use-cases.
- **SQLite storage for history.** All history is now stored in a SQLite database, providing support for multiple simultaneous sessions that won't clobber each other as well as the ability to perform queries on all stored data.
- **New configuration system.** All parts of IPython are now configured via a mechanism inspired by the Enthought Traits library. Any configurable element can have its attributes set either via files that now use real Python syntax or from the command-line.
- **Pasting of code with prompts.** IPython now intelligently strips out input prompts, be they plain Python ones (`>>>` and `...`) or IPython ones (`In [N]:` and `...:`). More details [here](#).

Authors and support

Over 60 separate authors have contributed to this release, see [below](#) for a full list. In particular, we want to highlight the extremely active participation of two new core team members: Evan Patterson implemented the Qt console, and Thomas Kluyver started with our Python 3 port and by now has made major contributions to just about every area of IPython.

We are also grateful for the support we have received during this development cycle from several institutions:

- [Enthought Inc](#) funded the development of our new Qt console, an effort that required developing major pieces of underlying infrastructure, which now power not only the Qt console but also our new parallel machinery. We'd like to thank Eric Jones and Travis Oliphant for their support, as well as Ilan Schnell for his tireless work integrating and testing IPython in the [Enthought Python Distribution](#).
- Nipy/NIH: funding via the [NiPy project](#) (NIH grant 5R01MH081909-02) helped us jumpstart the development of this series by restructuring the entire codebase two years ago in a way that would make modular development and testing more approachable. Without this initial groundwork, all the new features we have added would have been impossible to develop.
- Sage/NSF: funding via the grant [Sage: Unifying Mathematical Software for Scientists, Engineers, and Mathematicians](#) (NSF grant DMS-1015114) supported a meeting in spring 2011 of several of the core IPython developers where major progress was made integrating the last key pieces leading to this release.
- Microsoft's team working on [Python Tools for Visual Studio](#) developed the integration of IPython into the Python plugin for Visual Studio 2010.
- Google Summer of Code: in 2010, we had two students developing prototypes of the new machinery that is now maturing in this release: [Omar Zapata](#) and [Gerardo Gutiérrez](#).

Development summary: moving to Git and Github

In April 2010, after [one breakage too many with bazaar](#), we decided to move our entire development process to Git and Github.com. This has proven to be one of the best decisions in the project's history, as the combination of git and github have made us far, far more productive than we could be with our previous tools. We first converted our bazaar repo to a git one without losing history, and a few weeks later ported all open Launchpad bugs to github issues with their comments mostly intact (modulo some formatting changes). This ensured a smooth transition where no development history or submitted bugs were lost. Feel free to use our little Launchpad to Github issues [porting script](#) if you need to make a similar transition.

These simple statistics show how much work has been done on the new release, by comparing the current code to the last point it had in common with the 0.10 series. A huge diff and ~2200 commits make up this cycle:

```
git diff $(git merge-base 0.10.2 HEAD) | wc -l
288019

git log $(git merge-base 0.10.2 HEAD)..HEAD --oneline | wc -l
2200
```

Since our move to github, 511 issues were closed, 226 of which were pull requests and 285 regular issues ([a full list with links](#) is available for those interested in the details). Github's pull requests are a fantastic mechanism for reviewing code and building a shared ownership of the project, and we are making enthusiastic use of it.

Примечание: This undercounts the number of issues closed in this development cycle, since we only moved to github for issue tracking in May 2010, but we have no way of collecting statistics on the number of issues closed in the old Launchpad bug tracker prior to that.

Qt Console

IPython now ships with a Qt application that feels very much like a terminal, but is in fact a rich GUI that runs an IPython client but supports inline figures, saving sessions to PDF and HTML, multiline editing with syntax highlighting, graphical calltips and much more:

We hope that many projects will embed this widget, which we've kept deliberately very lightweight, into their own environments. In the future we may also offer a slightly more featureful application (with menus and other GUI elements), but we remain committed to always shipping this easy to embed widget.

See the [Jupyter Qt Console site](#) for a detailed description of the console's features and use.

High-level parallel computing with ZeroMQ

We have completely rewritten the Twisted-based code for high-level parallel computing to work atop our new ZeroMQ architecture. While we realize this will break compatibility for a number of users, we hope to make the transition as easy as possible with our docs, and we are convinced the change is worth it. ZeroMQ provides us with much tighter control over memory, higher performance, and its communications are impervious to the Python Global Interpreter Lock because they take place in a system-level C++ thread. The impact of the GIL in our previous code was something we could simply not work around, given that Twisted is itself a Python library. So while Twisted is a very capable framework, we think ZeroMQ fits our needs much better and we hope you will find the change to be a significant improvement in the long run.

Our manual contains a full description of how to use IPython for parallel computing, and the [tutorial](#) presented by Min Ragan-Kelley at the SciPy 2011 conference provides a hands-on complement to the reference




Рис. 5: The Qt console for IPython, using inline matplotlib plots.

docs.

Refactoring

As of this release, a significant portion of IPython has been refactored. This refactoring is founded on a number of new abstractions. The main new classes that implement these abstractions are:

- `traitlets.HasTraits`.
- `traitlets.config.configurable.Configurable`.
- `traitlets.config.application.Application`.
- `traitlets.config.loader.ConfigLoader`.
- `traitlets.config.loader.Config`

We are still in the process of writing developer focused documentation about these classes, but for now our *configuration documentation* contains a high level overview of the concepts that these classes express.

The biggest user-visible change is likely the move to using the config system to determine the command-line arguments for IPython applications. The benefit of this is that *all* configurable values in IPython are exposed on the command-line, but the syntax for specifying values has changed. The gist is that assigning values is pure Python assignment. Simple flags exist for commonly used options, these are always prefixed with „-“,

The IPython command-line help has the details of all the options (via `ipython --help`), but a simple example should clarify things; the `pylab` flag can be used to start in pylab mode with the qt4 backend:

```
ipython --pylab=qt
```

which is equivalent to using the fully qualified form:

```
ipython --TerminalIPythonApp.pylab=qt
```

The long-form options can be listed via `ipython --help-all`.

ZeroMQ architecture

There is a new GUI framework for IPython, based on a client-server model in which multiple clients can communicate with one IPython kernel, using the ZeroMQ messaging framework. There is already a Qt console client, which can be started by calling `ipython qtconsole`. The protocol is [documented](#).

The parallel computing framework has also been rewritten using ZMQ. The protocol is described [here](#), and the code is in the new `IPython.parallel` module.

Python 3 support

A Python 3 version of IPython has been prepared. For the time being, this is maintained separately and updated from the main codebase. Its code can be found [here](#). The parallel computing components are not perfect on Python3, but most functionality appears to be working. As this work is evolving quickly, the best place to find updated information about it is our [Python 3 wiki page](#).

Unicode

Entering non-ascii characters in unicode literals (`u"€"`) now works properly on all platforms. However, entering these in byte/string literals (`"€"`) will not work as expected on Windows (or any platform where the terminal encoding is not UTF-8, as it typically is for Linux & Mac OS X). You can use escape sequences (`"\xe9\x82"`) to get bytes above 128, or use unicode literals and encode them. This is a limitation of Python 2 which we cannot easily work around.

Integration with Microsoft Visual Studio

IPython can be used as the interactive shell in the Python plugin for Microsoft Visual Studio, as seen here:




Рис. 6: IPython console embedded in Microsoft Visual Studio.

The Microsoft team developing this currently has a release candidate out using IPython 0.11. We will continue to collaborate with them to ensure that as they approach their final release date, the integration with IPython remains smooth. We'd like to thank Dino Viehland and Shahrokh Mortazavi for the work they have done towards this feature, as well as Wenming Ye for his support of our WinHPC capabilities.

Additional new features

- Added `Bytes` traitlet, removing `Str`. All „string“ traitlets should either be `Unicode` if a real string, or `Bytes` if a C-string. This removes ambiguity and helps the Python 3 transition.
- New magic `%loadpy` loads a python file from disk or web URL into the current input buffer.
- New magic `%pastebin` for sharing code via the „Lodge it“ pastebin.
- New magic `%precision` for controlling float and numpy pretty printing.
- IPython applications initiate logging, so any object can gain access to a the logger of the currently running Application with:

```
from traitlets.config.application import Application
logger = Application.instance().log
```

- You can now get help on an object halfway through typing a command. For instance, typing `a = zip?` shows the details of `zip()`. It also leaves the command at the next prompt so you can carry on with it.
- The input history is now written to an SQLite database. The API for retrieving items from the history has also been redesigned.
- The `IPython.extensions.pretty` extension has been moved out of quarantine and fully updated to the new extension API.
- New magics for loading/unloading/reloading extensions have been added: `%load_ext`, `%unload_ext` and `%reload_ext`.
- The configuration system and configuration files are brand new. See the configuration system [documentation](#) for more details.
- The `InteractiveShell` class is now a `Configurable` subclass and has traitlets that determine the defaults and runtime environment. The `__init__` method has also been refactored so this class can be instantiated and run without the old `ipmaker` module.
- The methods of `InteractiveShell` have been organized into sections to make it easier to turn more sections of functionality into components.
- The embedded shell has been refactored into a truly standalone subclass of `InteractiveShell` called `InteractiveShellEmbed`. All embedding logic has been taken out of the base class and put into the embedded subclass.
- Added methods of `InteractiveShell` to help it cleanup after itself. The `cleanup()` method controls this. We couldn't do this in `__del__()` because we have cycles in our object graph that prevent it from being called.
- Created a new module `IPython.utils.importstring` for resolving strings like `foo.bar.Bar` to the actual class.
- Completely refactored the `IPython.core.prefilter` module into `Configurable` subclasses. Added a new layer into the prefilter system, called «transformations» that all new prefilter logic should use (rather than the older «checker/handler» approach).
- Aliases are now components (`IPython.core.alias`).
- New top level `embed()` function that can be called to embed IPython at any place in user's code. On the first call it will create an `InteractiveShellEmbed` instance and call it. In later calls, it just calls the previously created `InteractiveShellEmbed`.
- Created a configuration system (`traitlets.config.configurable`) that is based on `traitlets`. Configurables are arranged into a runtime containment tree (not inheritance) that i) automatically propagates configuration information and ii) allows singletons to discover each other in a loosely coupled manner. In the future all parts of IPython will be subclasses of `Configurable`. All IPython developers should become familiar with the config system.
- Created a new `Config` for holding configuration information. This is a dict like class with a few extras: i) it supports attribute style access, ii) it has a merge function that merges two `Config` instances recursively and iii) it will automatically create sub-`Config` instances for attributes that start with an uppercase character.
- Created new configuration loaders in `traitlets.config.loader`. These loaders provide a unified loading interface for all configuration information including command line arguments and configuration files. We have two default implementations based on `argparse` and plain python files. These are used to implement the new configuration system.
- Created a top-level `Application` class in `IPython.core.application` that is designed to encapsulate the starting of any basic Python program. An application loads and merges all the configuration objects, constructs the main application, configures and initiates logging, and creates and

configures any `Configurable` instances and then starts the application running. An extended `BaseIPythonApplication` class adds logic for handling the IPython directory as well as profiles, and all IPython entry points extend it.

- The `Type` and `Instance` traitlets now handle classes given as strings, like `foo.bar.Bar`. This is needed for forward declarations. But, this was implemented in a careful way so that string to class resolution is done at a single point, when the parent `HasTraitlets` is instantiated.
- `IPython.utils.ipstruct` has been refactored to be a subclass of `dict`. It also now has full docstrings and doctests.
- Created a Traits like implementation in `traitlets`. This is a pure Python, lightweight version of a library that is similar to Enthought's Traits project, but has no dependencies on Enthought's code. We are using this for validation, defaults and notification in our new component system. Although it is not 100% API compatible with Enthought's Traits, we plan on moving in this direction so that eventually our implementation could be replaced by a (yet to exist) pure Python version of Enthought Traits.
- Added a new module `IPython.lib.inputhook` to manage the integration with GUI event loops using `PyOS_InputHook`. See the docstrings in this module or the main IPython docs for details.
- For users, GUI event loop integration is now handled through the new `%gui` magic command. Type `%gui?` at an IPython prompt for documentation.
- For developers `IPython.lib.inputhook` provides a simple interface for managing the event loops in their interactive GUI applications. Examples can be found in our `examples/lib` directory.

Backwards incompatible changes

- The Twisted-based `IPython.kernel` has been removed, and completely rewritten as `IPython.parallel`, using ZeroMQ.
- Profiles are now directories. Instead of a profile being a single config file, profiles are now self-contained directories. By default, profiles get their own IPython history, log files, and everything. To create a new profile, do `ipython profile create <name>`.
- All IPython applications have been rewritten to use `KeyValueConfigLoader`. This means that command-line options have changed. Now, all configurable values are accessible from the command-line with the same syntax as in a configuration file.
- The command line options `-wthread`, `-qthread` and `-gthread` have been removed. Use `--gui=wx`, `--gui=qt`, `--gui=gtk` instead.
- The extension loading functions have been renamed to `load_ipython_extension()` and `unload_ipython_extension()`.
- `InteractiveShell` no longer takes an `embedded` argument. Instead just use the `InteractiveShellEmbed` class.
- `__IPYTHON__` is no longer injected into `__builtin__`.
- `Struct.__init__()` no longer takes `None` as its first argument. It must be a `dict` or `Struct`.
- `ipmagic()` has been renamed `()`
- The functions `ipmagic()` and `ipalias()` have been removed from `__builtins__`.
- The references to the global `InteractiveShell` instance (`_ip`, and `__IP`) have been removed from the user's namespace. They are replaced by a new function called `get_ipython()` that returns the current `InteractiveShell` instance. This function is injected into the user's namespace and is now the main way of accessing the running IPython.

- Old style configuration files `ipythonrc` and `ipy_user_conf.py` are no longer supported. Users should migrate there configuration files to the new format described [here](#) and [here](#).
- The old IPython extension API that relied on `ipapi()` has been completely removed. The new extension API is described [here](#).
- Support for `qt3` has been dropped. Users who need this should use previous versions of IPython.
- Removed `shellglobals` as it was obsolete.
- Removed all the threaded shells in `IPython.core.shell`. These are no longer needed because of the new capabilities in `IPython.lib.inputhook`.
- New top-level sub-packages have been created: `IPython.core`, `IPython.lib`, `IPython.utils`, `IPython.deathrow`, `IPython.quarantine`. All existing top-level modules have been moved to appropriate sub-packages. All internal import statements have been updated and tests have been added. The build system (`setup.py` and `friends`) have been updated. See [The IPython API](#) for details of these new sub-packages.
- `IPython.ipapi` has been moved to `IPython.core.ipapi`. `IPython.Shell` and `IPython.iplib` have been split and removed as part of the refactor.
- `Extensions` has been moved to `extensions` and all existing extensions have been moved to either `IPython.quarantine` or `IPython.deathrow`. `IPython.quarantine` contains modules that we plan on keeping but that need to be updated. `IPython.deathrow` contains modules that are either dead or that should be maintained as third party libraries.
- Previous IPython GUIs in `IPython.frontend` and `IPython.gui` are likely broken, and have been removed to `IPython.deathrow` because of the refactoring in the core. With proper updates, these should still work.

Known Regressions

We do our best to improve IPython, but there are some known regressions in 0.11 relative to 0.10.2. First of all, there are features that have yet to be ported to the new APIs, and in order to ensure that all of the installed code runs for our users, we have moved them to two separate directories in the source distribution, `quarantine` and `deathrow`. Finally, we have some other miscellaneous regressions that we hope to fix as soon as possible. We now describe all of these in more detail.

Quarantine

These are tools and extensions that we consider relatively easy to update to the new classes and APIs, but that we simply haven't had time for. Any user who is interested in one of these is encouraged to help us by porting it and submitting a pull request on our [development site](#).

Currently, the quarantine directory contains:

<code>clearcmd.py</code>	<code>ipy_fsops.py</code>	<code>ipy_signals.py</code>
<code>envpersist.py</code>	<code>ipy_gnuglobal.py</code>	<code>ipy_synchronize_with.py</code>
<code>ext_rescapture.py</code>	<code>ipy_greedycompleter.py</code>	<code>ipy_system_conf.py</code>
<code>InterpreterExec.py</code>	<code>ipy_jot.py</code>	<code>ipy_which.py</code>
<code>ipy_app_completers.py</code>	<code>ipy_lookfor.py</code>	<code>ipy_winpdb.py</code>
<code>ipy_autoreload.py</code>	<code>ipy_profile_doctest.py</code>	<code>ipy_workdir.py</code>
<code>ipy_completers.py</code>	<code>ipy_pydb.py</code>	<code>jobctrl.py</code>
<code>ipy_editors.py</code>	<code>ipy_rehashdir.py</code>	<code>ledit.py</code>
<code>ipy_exportdb.py</code>	<code>ipy_render.py</code>	<code>pspersistence.py</code>
<code>ipy_extutil.py</code>	<code>ipy_server.py</code>	<code>win32clip.py</code>

Deathrow

These packages may be harder to update or make most sense as third-party libraries. Some of them are completely obsolete and have been already replaced by better functionality (we simply haven't had the time to carefully weed them out so they are kept here for now). Others simply require fixes to code that the current core team may not be familiar with. If a tool you were used to is included here, we encourage you to contact the dev list and we can discuss whether it makes sense to keep it in IPython (if it can be maintained).

Currently, the deathrow directory contains:

<code>astyle.py</code>	<code>ipy_defaults.py</code>	<code>ipy_vimserver.py</code>
<code>dtutils.py</code>	<code>ipy_kitcfg.py</code>	<code>numeric_formats.py</code>
<code>Gnuplot2.py</code>	<code>ipy_legacy.py</code>	<code>numutils.py</code>
<code>GnuplotInteractive.py</code>	<code>ipy_p4.py</code>	<code>outputtrap.py</code>
<code>GnuplotRuntime.py</code>	<code>ipy_profile_none.py</code>	<code>PhysicalQInput.py</code>
<code>ibrowse.py</code>	<code>ipy_profile_numpy.py</code>	<code>PhysicalQInteractive.py</code>
<code>igrid.py</code>	<code>ipy_profile_scipy.py</code>	<code>quitter.py*</code>
<code>ipipe.py</code>	<code>ipy_profile_sh.py</code>	<code>scitedirector.py</code>
<code>iplib.py</code>	<code>ipy_profile_zope.py</code>	<code>Shell.py</code>
<code>ipy_constants.py</code>	<code>ipy_traits_completer.py</code>	<code>twshell.py</code>

Other regressions

- The machinery that adds functionality to the „sh“ profile for using IPython as your system shell has not been updated to use the new APIs. As a result, only the aesthetic (prompt) changes are still implemented. We intend to fix this by 0.12. Tracked as issue [547](#).
- The installation of scripts on Windows was broken without `setuptools`, so we now depend on `setuptools` on Windows. We hope to fix `setuptools`-less installation, and then remove the `setuptools` dependency. Issue [539](#).
- The directory history `_dh` is not saved between sessions. Issue [634](#).

Removed Features

As part of the updating of IPython, we have removed a few features for the purposes of cleaning up the codebase and interfaces. These removals are permanent, but for any item listed below, equivalent functionality is available.

- The magics `Exit` and `Quit` have been dropped as ways to exit IPython. Instead, the lowercase forms of both work either as a bare name (`exit`) or a function call (`exit()`). You can assign these to other names using `exec_lines` in the config file.

Credits

Many users and developers contributed code, features, bug reports and ideas to this release. Please do not hesitate in contacting us if we've failed to acknowledge your contribution here. In particular, for this release we have contribution from the following people, a mix of new and regular names (in alphabetical order by first name):

- Aenugu Sai Kiran Reddy <saikrn08-at-gmail.com>
- andy wilson <wilson.andrew.j+github-at-gmail.com>

- Antonio Cuni <antocuni>
- Barry Wark <barrywark-at-gmail.com>
- Beetoju Anuradha <anu.beethoju-at-gmail.com>
- Benjamin Ragan-Kelley <minrk-at-Mercury.local>
- Brad Reisfeld
- Brian E. Granger <ellisonbg-at-gmail.com>
- Christoph Gohlke <cgohlke-at-uci.edu>
- Cody Precord
- dan.milstein
- Darren Dale <dsdale24-at-gmail.com>
- Dav Clark <davclark-at-berkeley.edu>
- David Warde-Farley <wardefar-at-iro.umontreal.ca>
- epatters <ejpatters-at-gmail.com>
- epatters <epatters-at-caltech.edu>
- epatters <epatters-at-enthought.com>
- Eric Firing <efiring-at-hawaii.edu>
- Erik Tollerud <erik.tollerud-at-gmail.com>
- Evan Patterson <epatters-at-enthought.com>
- Fernando Perez <Fernando.Perez-at-berkeley.edu>
- Gael Varoquaux <gael.varoquaux-at-normalesup.org>
- Gerardo <muzgash-at-Muzpelheim>
- Jason Grout <jason.grout-at-drake.edu>
- John Hunter <jdh2358-at-gmail.com>
- Jens Hedegaard Nielsen <jenshnielsen-at-gmail.com>
- Johann Cohen-Tanugi <johann.cohentanugi-at-gmail.com>
- Jörgen Stenarson <jorgen.stenarson-at-bostream.nu>
- Justin Riley <justin.t.riley-at-gmail.com>
- Kiorky
- Laurent Dufrechou <laurent.dufrechou-at-gmail.com>
- Luis Pedro Coelho <lpc-at-cmu.edu>
- Mani chandra <mchandra-at-iitk.ac.in>
- Mark E. Smith
- Mark Voorhies <mark.voorhies-at-ucsf.edu>
- Martin Spacek <git-at-mspacek.mm.st>
- Michael Droettboom <mdroe-at-stsci.edu>
- MinRK <benjaminrk-at-gmail.com>

- muzuiget <muзуiget-at-gmail.com>
- Nick Tarleton <nick-at-quixey.com>
- Nicolas Rougier <Nicolas.rougier-at-inria.fr>
- Omar Andres Zapata Mesa <andresete.chaos-at-gmail.com>
- Paul Ivanov <pivanov314-at-gmail.com>
- Pauli Virtanen <pauli.virtanen-at-iki.fi>
- Prabhu Ramachandran
- Ramana <sramana9-at-gmail.com>
- Robert Kern <robert.kern-at-gmail.com>
- Sathesh Chandra <satheshchandra88-at-gmail.com>
- Satrajit Ghosh <satra-at-mit.edu>
- Sebastian Busch
- Skipper Seabold <jsseabold-at-gmail.com>
- Stefan van der Walt <bzr-at-mentat.za.net>
- Stephan Peijnik <debian-at-sp.or.at>
- Steven Bethard
- Thomas Kluyver <takowl-at-gmail.com>
- Thomas Spura <tomspur-at-fedoraproject.org>
- Tom Fetherston <tfetherston-at-aol.com>
- Tom MacWright
- tzanko
- vankayala sowjanya <hai.sowjanya-at-gmail.com>
- Vivian De Smedt <vds2212-at-VIVIAN>
- Ville M. Vainio <vivainio-at-gmail.com>
- Vishal Vatsa <vishal.vatsa-at-gmail.com>
- Vishnu S G <sgvishnu777-at-gmail.com>
- Walter Doerwald <walter-at-livinglogic.de>

Примечание: This list was generated with the output of `git log dev-0.11 HEAD --format='%aN <%aE>' | sed 's/@/\-at\-' | sed 's/</>/' | sort -u` after some cleanup. If you should be on this list, please add yourself.

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

2.24 Issues closed in the 0.11 development cycle

In this cycle, we closed a total of 511 issues, 226 pull requests and 285 regular issues; this is the full list (generated with the script `tools/github_stats.py`). We should note that a few of these were made on the 0.10.x series, but we have no automatic way of filtering the issues by branch, so this reflects all of our development over the last two years, including work already released in 0.10.2:

Pull requests (226):

- 620: Release notes and updates to GUI support docs for 0.11
- 642: fix typo in docs/examples/vim/README.rst
- 631: two-way vim-ipython integration
- 637: print is a function, this allows to properly exit ipython
- 635: support html representations in the notebook frontend
- 639: Updating the credits file
- 628: import pexpect from IPython.external in irunner
- 596: Iranner
- 598: Fix templates for CrashHandler
- 590: Desktop
- 600: Fix bug with non-ascii reprs inside pretty-printed lists.
- 618: I617
- 599: Gui Qt example and docs
- 619: manpage update
- 582: Updating sympy profile to match the `exec_lines` of isympy.
- 578: Check to see if correct source for decorated functions can be displayed
- 589: issue 588
- 591: simulate shell expansion on `%run` arguments, at least tilde expansion
- 576: Show message about `%paste` magic on an `IndentationError`
- 574: Getcwd
- 565: don't move old config files, keep nagging the user
- 575: Added more docstrings to `IPython.zmq.session`.
- 567: fix trailing whitespace from resetting indentation
- 564: Command line args in docs
- 560: reorder qt support in kernel
- 561: command-line suggestions
- 556: `qt_for_kernel`: use `matplotlib.rcParams` to decide between `PyQt4` and `PySide`

- 557: Update usage.py to newapp
- 555: Rm default old config
- 552: update parallel code for py3k
- 504: Updating string formatting
- 551: Make pylab import all configurable
- 496: Qt editing keybindings
- 550: Support v2 PyQt4 APIs and PySide in kernel's GUI support
- 546: doc update
- 548: Fix sympy profile to work with sympy 0.7.
- 542: issue 440
- 533: Remove unused configobj and validate libraries from externals.
- 538: fix various tests on Windows
- 540: support -pylab flag with deprecation warning
- 537: Docs update
- 536: `setup.py install` depends on `setuptools` on Windows
- 480: Get help mid-command
- 462: Str and Bytes traitlets
- 534: Handle unicode properly in `IPython.zmq.iostream`
- 527: ZMQ displayhook
- 526: Handle asynchronous output in Qt console
- 528: Do not import deprecated functions from external decorators library.
- 454: New `BaseIPythonApplication`
- 532: Zmq unicode
- 531: Fix Parallel test
- 525: fallback on `lsf` if `otool` not found in `libedit` detection
- 517: Merge `IPython.parallel.streamsession` into `IPython.zmq.session`
- 521: use `dict.get(key)` instead of `dict[key]` for safety from `KeyErrors`
- 492: add `QtConsoleApp` using `newapplication`
- 485: terminal IPython with `newapp`
- 486: Use `newapp` in parallel code
- 511: Add a new line before displaying multiline strings in the Qt console.
- 509: i508
- 501: ignore `EINTR` in channel loops
- 495: Better selection of Qt bindings when `QT_API` is not specified
- 498: Check for `.pyd` as extension for binary files.
- 494: QtConsole zoom adjustments

- 490: fix UnicodeEncodeError writing SVG string to .svg file, fixes #489
- 491: add QtConsoleApp using newapplication
- 479: embed() doesn't load default config
- 483: Links launchpad -> github
- 419: %xdel magic
- 477: Add n to lines in the log
- 459: use os.system for shell.system in Terminal frontend
- 475: i473
- 471: Add test decorator onlyif_unicode_paths.
- 474: Fix support for raw GTK and WX matplotlib backends.
- 472: Kernel event loop is robust against random SIGINT.
- 460: Share code for magic_edit
- 469: Add exit code when running all tests with ipctest.
- 464: Add home directory expansion to IPYTHON_DIR environment variables.
- 455: Bugfix with logger
- 448: Separate out skip_doctest decorator
- 453: Draft of new main BaseIPythonApplication.
- 452: Use list/tuple/dict/set subclass's overridden __repr__ instead of the pretty
- 398: allow toggle of svg/png inline figure format
- 381: Support inline PNGs of matplotlib plots
- 413: Retries and Resubmit (#411 and #412)
- 370: Fixes to the display system
- 449: Fix issue 447 - inspecting old-style classes.
- 423: Allow type checking on elements of List,Tuple,Set traits
- 400: Config5
- 421: Generalise mechanism to put text at the next prompt in the Qt console.
- 443: pinfo code duplication
- 429: add check_pid, and handle stale PID info in ipcluster.
- 431: Fix error message in test_irunner
- 427: handle different SyntaxError messages in test_irunner
- 424: Irunner test failure
- 430: Small parallel doc typo
- 422: Make ipython-qtconsole a GUI script
- 420: Permit kernel std* to be redirected
- 408: History request
- 388: Add Emacs-style kill ring to Qt console

- 414: Warn on old config files
- 415: Prevent prefilter from crashing IPython
- 418: Minor configuration doc fixes
- 407: Update What's new documentation
- 410: Install notebook frontend
- 406: install IPython.zmq.gui
- 393: ipdir unicode
- 397: `utils.io.Term.cin/out/err -> utils.io.stdin/out/err`
- 389: DB fixes and Scheduler HWM
- 374: Various Windows-related fixes to `IPython.parallel`
- 362: fallback on `defaultencoding` if `filesystemencoding` is `None`
- 382: Shell's `reset` method clears namespace from last `%run` command.
- 385: Update `iptest` exclusions (fix #375)
- 383: Catch errors in querying readline which occur with `pyreadline`.
- 373: Remove runlines etc.
- 364: Single output
- 372: Multiline input push
- 363: Issue 125
- 361: don't rely on `setuptools` for readline dependency check
- 349: Fix `%autopx` magic
- 355: History save thread
- 356: Usability improvements to history in Qt console
- 357: Exit autocall
- 353: Rewrite `quit()/exit()/Quit()/Exit()` calls as magic
- 354: Cell tweaks
- 345: Attempt to address (partly) issue `ipython/#342` by rewriting `quit()`, `exit()`, etc.
- 352: #342: Try to recover as intelligently as possible if user calls `magic()`.
- 346: Dedent prefix bugfix + tests: #142
- 348: `%reset` doesn't reset prompt number.
- 347: Make `ip.reset()` work the same in interactive or non-interactive code.
- 343: make readline a dependency on OSX
- 344: restore auto debug behavior
- 339: fix for issue 337: incorrect/phantom tooltips for magics
- 254: newparallel branch (add `zmq.parallel` submodule)
- 334: Hard reset
- 316: Unicode win process

- 332: AST splitter
- 325: Removetwisted
- 330: Magic pastebin
- 309: Bug tests for GH Issues 238, 284, 306, 307. Skip module machinery if not installed. Known failures reported as „K“
- 331: Tweak config loader for PyPy compatibility.
- 319: Rewrite code to restore readline history after an action
- 329: Do not store file contents in history when running a .ipy file.
- 179: Html notebook
- 323: Add missing external.pexpect to packages
- 295: Magic local scope
- 315: Unicode magic args
- 310: allow Unicode Command-Line options
- 313: Readline shortcuts
- 311: Qtconsole exit
- 312: History memory
- 294: Issue 290
- 292: Issue 31
- 252: Unicode issues
- 235: Fix history magic command's bugs wrt to full history and add -O option to display full history
- 236: History minus p flag
- 261: Adapt magic commands to new history system.
- 282: SQLite history
- 191: Unbundle external libraries
- 199: Magic arguments
- 204: Emacs completion bugfix
- 293: Issue 133
- 249: Writing unicode characters to a log file. (IPython 0.10.2.git)
- 283: Support for 256-color escape sequences in Qt console
- 281: Refactored and improved Qt console's HTML export facility
- 237: Fix185 (take two)
- 251: Issue 129
- 278: add basic XDG_CONFIG_HOME support
- 275: inline pylab cuts off labels on log plots
- 280: Add %precision magic
- 259: Pyside support

- 193: Make ipython cProfile-able
- 272: Magic examples
- 219: Doc magic pycat
- 221: Doc magic alias
- 230: Doc magic edit
- 224: Doc magic cpaste
- 229: Doc magic pdef
- 273: Docs build
- 228: Doc magic who
- 233: Doc magic cd
- 226: Doc magic pwd
- 218: Doc magic history
- 231: Doc magic reset
- 225: Doc magic save
- 222: Doc magic timeit
- 223: Doc magic colors
- 203: Small typos in zmq/blockingkernelmanager.py
- 227: Doc magic logon
- 232: Doc magic profile
- 264: Kernel logging
- 220: Doc magic edit
- 268: PyZMQ \geq 2.0.10
- 267: GitHub Pages (again)
- 266: OSX-specific fixes to the Qt console
- 255: Gitwash typo
- 265: Fix string input2
- 260: Kernel crash with empty history
- 243: New display system
- 242: Fix terminal exit
- 250: always use Session.send
- 239: Makefile command & script for GitHub Pages
- 244: My exit
- 234: Timed history save
- 217: Doc magic lsmagic
- 215: History fix
- 195: Formatters

- 192: Ready colorize bug
- 198: Windows workdir
- 174: Whitespace cleanup
- 188: Version info: update our version management system to use git.
- 158: Ready for merge
- 187: Resolved Print shortcut collision with ctrl-P emacs binding
- 183: cleanup of exit/quit commands for qt console
- 184: Logo added to sphinx docs
- 180: Cleanup old code
- 171: Expose Pygments styles as options
- 170: HTML Fixes
- 172: Fix del method exit test
- 164: Qt frontend shutdown behavior fixes and enhancements
- 167: Added HTML export
- 163: Execution refactor
- 159: Ipy3 preparation
- 155: Ready startup fix
- 152: 0.10.1 sge
- 151: mk_object_info -> object_info
- 149: Simple bug-fix

Regular issues (285):

- 630: new.py in pwd prevents ipython from starting
- 623: Execute DirectView commands while running LoadBalancedView tasks
- 437: Users should have autocompletion in the notebook
- 583: update manpages
- 594: irunner command line options defer to file extensions
- 603: Users should see colored text in tracebacks and the pager
- 597: UnicodeDecodeError: „ascii“ codec can't decode byte 0xc2
- 608: Organize and layout buttons in the notebook panel sections
- 609: Implement controls in the Kernel panel section
- 611: Add kernel status widget back to notebook
- 610: Implement controls in the Cell section panel
- 612: Implement Help panel section
- 621: [qtconsole] on windows xp, cannot PageUp more than once
- 616: Store exit status of last command
- 605: Users should be able to open different notebooks in the cwd

- 302: Users should see a consistent behavior in the Out prompt in the html notebook
- 435: Notebook should not import anything by default
- 595: qtconsole command issue
- 588: ipython-qtconsole uses 100% CPU
- 586: ? + plot() Command B0rks QTConsole Strangely
- 585: %pdoc throws Errors for classes without `__init__` or docstring
- 584: %pdoc throws TypeError
- 580: Client instantiation AssertionError
- 569: UnicodeDecodeError during startup
- 572: Indented command hits error
- 573: -wthread breaks indented top-level statements
- 570: «-pylab inline» vs. «-pylab=inline»
- 566: Can't use `exec_file` in config file
- 562: update docs to reflect „-args=values“
- 558: triple quote and %s at beginning of line
- 554: Update 0.11 docs to explain Qt console and how to do a clean install
- 553: `embed()` fails if config files not installed
- 8: Ensure %gui qt works with new Mayavi and pylab
- 269: Provide compatibility api for `IPython.Shell().start().mainloop()`
- 66: Update the main What's New document to reflect work on 0.11
- 549: Don't check for „linux2“ value in `sys.platform`
- 505: Qt windows created within imported functions won't show()
- 545: qtconsole ignores `exec_lines`
- 371: segfault in qtconsole when kernel quits
- 377: Failure: error (nothing to repeat)
- 544: Ipython qtconsole pylab config issue.
- 543: RuntimeError in completer
- 440: %run filename autocompletion «The kernel heartbeat has been inactive ... » error
- 541: `log_level` is broken in the ipython Application
- 369: windows source install doesn't create scripts correctly
- 351: Make sure that the Windows installer handles the top-level IPython scripts.
- 512: Two displayhooks in zmq
- 340: Make sure that the Windows HPC scheduler support is working for 0.11
- 98: Should be able to get help on an object mid-command
- 529: unicode problem in qtconsole for windows
- 476: Separate input area in Qt Console

- 175: Qt console needs configuration support
- 156: Key history lost when debugging program crash
- 470: decorator: uses deprecated features
- 30: readline in OS X does not have correct key bindings
- 503: merge IPython.parallel.streamsession and IPython.zmq.session
- 456: pathname in document punctuated by dots not slashes
- 451: Allow switching the default image format for inline mpl backend
- 79: Implement more robust handling of config stages in Application
- 522: Encoding problems
- 524: otool should not be unconditionally called on osx
- 523: Get profile and config file inheritance working
- 519: qtconsole -pure: «TypeError: string indices must be integers, not str»
- 516: qtconsole -pure: «KeyError: „ismagic“»
- 520: qtconsole -pure: «TypeError: string indices must be integers, not str»
- 450: resubmitted tasks sometimes stuck as pending
- 518: JSON serialization problems with ObjectId type (MongoDB)
- 178: Channels should be named for their function, not their socket type
- 515: [ipcluster] termination on os x
- 510: qtconsole: indentation problem printing numpy arrays
- 508: «AssertionError: Missing message part.» in ipython-qtconsole -pure
- 499: «ZMQError: Interrupted system call» when saving inline figure
- 426: %edit magic fails in qtconsole
- 497: Don't show info from .pyd files
- 493: QFont::setPointSize: Point size <= 0 (0), must be greater than 0
- 489: UnicodeEncodeError in qt.svg.save_svg
- 458: embed() doesn't load default config
- 488: Using IPython with RubyPython leads to problems with IPython.parallel.client.client.Client.__init()
- 401: Race condition when running lbview.apply() fast multiple times in loop
- 168: Scrub Launchpad links from code, docs
- 141: garbage collection problem (revisited)
- 59: test_magic.test_obj_del fails on win32
- 457: Backgrounded Tasks not Allowed? (but easy to slip by ...)
- 297: Shouldn't use pexpect for subprocesses in in-process terminal frontend
- 110: magic to return exit status
- 473: OSX readline detection fails in the debugger

- 466: tests fail without unicode filename support
- 468: iptest script has 0 exit code even when tests fail
- 465: client.db_query() behaves different with SQLite and MongoDB
- 467: magic_install_default_config test fails when there is no .ipython directory
- 463: IPYTHON_DIR (and IPYTHONDIR) don't expand tilde to „~“ directory
- 446: Test machinery is imported at normal runtime
- 438: Users should be able to use Up/Down for cell navigation
- 439: Users should be able to copy notebook input and output
- 291: Rename special display methods and put them lower in priority than display functions
- 447: Instantiating classes without __init__ function causes kernel to crash
- 444: Ctrl + t in WxIPython Causes Unexpected Behavior
- 445: qt and console Based Startup Errors
- 428: ipcluster doesn't handle stale pid info well
- 434: 10.0.2 seg fault with rpy2
- 441: Allow running a block of code in a file
- 432: Silent request fails
- 409: Test failure in IPython.lib
- 402: History section of messaging spec is incorrect
- 88: Error when inputting UTF8 CJK characters
- 366: Ctrl-K should kill line and store it, so that Ctrl-y can yank it back
- 425: typo in %gui magic help
- 304: Persistent warnings if old configuration files exist
- 216: crash of ipython when alias is used with %s and echo
- 412: add support to automatic retry of tasks
- 411: add support to continue tasks
- 417: IPython should display things unsorted if it can't sort them
- 416: wrong encode when printing unicode string
- 376: Failing InputsplitterTest
- 405: TraitError in traitlets.py(332) on any input
- 392: UnicodeEncodeError on start
- 137: sys.getfilesystemencoding return value not checked
- 300: Users should be able to manage kernels and kernel sessions from the notebook UI
- 301: Users should have access to working Kernel, Tabs, Edit, Help menus in the notebook
- 396: cursor move triggers a lot of IO access
- 379: Minor doc nit: -paging argument
- 399: Add task queue limit in engine when load-balancing

- 78: StringTask won't take unicode code strings
- 391: MongoDB.add_record() does not work in 0.11dev
- 365: newparallel on Windows
- 386: FAIL: test that pushed functions have access to globals
- 387: Interactively defined functions can't access user namespace
- 118: Snow Leopard ipy_vimserver POLL error
- 394: System escape interpreted in multi-line string
- 26: find_job_cmd is too hasty to fail on Windows
- 368: Installation instructions in dev docs are completely wrong
- 380: qtconsole pager RST - HTML not happening consistently
- 367: Qt console doesn't support ibus input method
- 375: Missing libraries cause ImportError in tests
- 71: temp file errors in iptest IPython.core
- 350: Decide how to handle displayhook being triggered multiple times
- 360: Remove runlines method
- 125: Exec lines in config should not contribute to line numbering or history
- 20: Robust readline support on OS X's builtin Python
- 147: On Windows, %page is being too restrictive to split line by rn only
- 326: Update docs and examples for parallel stuff to reflect movement away from Twisted
- 341: Fix Parallel Magics for newparallel
- 338: Usability improvements to Qt console
- 142: unexpected auto-indenting when variables names that start with „pass“
- 296: Automatic PDB via %pdb doesn't work
- 337: exit(and quit(in Qt console produces phantom signature/docstring popup, even though quit() or exit() raises NameError
- 318: %debug broken in master: invokes missing save_history() method
- 307: lines ending with semicolon should not go to cache
- 104: have ipengine run start-up scripts before registering with the controller
- 33: The skip_doctest decorator is failing to work on Shell.MatplotlibShellBase.magic_run
- 336: Missing figure development/figs/iopubfade.png for docs
- 49: %clear should also delete _NN references and Out[NN] ones
- 335: using setuptools installs every script twice
- 306: multiline strings at end of input cause noop
- 327: PyPy compatibility
- 328: %run script.ipynb raises «ERROR! Session/line number was not unique in database.»
- 7: Update the changes doc to reflect the kernel config work

- 303: Users should be able to scroll a notebook w/o moving the menu/buttons
- 322: Embedding an interactive IPython shell
- 321: %debug broken in master
- 287: Crash when using %macros in sqlite-history branch
- 55: Can't edit files whose names begin with numbers
- 284: In variable no longer works in 0.11
- 92: Using multiprocessing module crashes parallel IPython
- 262: Fail to recover history after force-kill.
- 320: Tab completing re.search objects crashes IPython
- 317: IPython.kernel: parallel map issues
- 197: ipython-qtconsole unicode problem in magic ls
- 305: more readline shortcuts in qtconsole
- 314: Multi-line, multi-block cells can't be executed.
- 308: Test suite should set sqlite history to work in :memory:
- 202: Matplotlib native „MacOSX“ backend broken in „-pylab“ mode
- 196: IPython can't deal with unicode file name.
- 25: unicode bug - encoding input
- 290: try/except/else clauses can't be typed, code input stops too early.
- 43: Implement SSH support in ipcluster
- 6: Update the Sphinx docs for the new ipcluster
- 9: Getting «DeadReferenceError: Calling Stale Broker» after ipcontroller restart
- 132: Ipython prevent south from working
- 27: generics.complete_object broken
- 60: Improve absolute import management for iptest.py
- 31: Issues in magic_whos code
- 52: Document testing process better
- 44: Merge history from multiple sessions
- 182: ipython q4thread in version 10.1 not starting properly
- 143: Ipython.gui.wx.ipython_view.IPShellWidget: ignores user*_ns arguments
- 127: %edit does not work on filenames consisted of pure numbers
- 126: Can't transfer command line argument to script
- 28: Offer finer control for initialization of input streams
- 58: ipython change char „0xe9“ to 4 spaces
- 68: Problems with Control-C stopping ipcluster on Windows/Python2.6
- 24: ipcluster does not start all the engines
- 240: Incorrect method displayed in %psource

- 120: `inspect.getsource` fails for functions defined on command line
- 212: IPython ignores exceptions in the first evaluation of class attrs
- 108: ipython disables python logger
- 100: Overzealous introspection
- 18: `%cpaste` freeze sync frontend
- 200: Unicode error when starting ipython in a folder with non-ascii path
- 130: Deadlock when importing a module that creates an IPython client
- 134: multiline block scrolling
- 46: Input to `%timeit` is not preparsed
- 285: `ipcluster local -n 4` fails
- 205: In the Qt console, Tab should insert 4 spaces when not completing
- 145: Bug on MSW systems: idle can not be set as default IPython editor. Fix Suggested.
- 77: ipython oops in cygwin
- 121: If plot windows are closed via window controls, no more plotting is possible.
- 111: Iterator version of `TaskClient.map()` that returns results as they become available
- 109: WinHPCLauncher is a hard dependency that causes errors in the test suite
- 86: Make IPython work with multiprocessing
- 15: Implement SGE support in `ipcluster`
- 3: Implement PBS support in `ipcluster`
- 53: Internal Python error in the inspect module
- 74: `Manager()` [from multiprocessing module] hangs `ipythonx` but not `ipython`
- 51: Out not working with `ipythonx`
- 201: use `session.send` throughout `zmq` code
- 115: multiline specials not defined in 0.11 branch
- 93: when looping, cursor appears at leftmost point in newline
- 133: whitespace after Source introspection
- 50: Ctrl-C with `-gthread` on Windows, causes uncaught `IOError`
- 65: Do not use `.message` attributes in exceptions, deprecated in 2.6
- 76: syntax error when `raise` is inside `except` process
- 107: `bdist_rpm` causes traceback looking for a non-existent file
- 113: initial magic ? (question mark) fails before wildcard
- 128: `Pdb` instance has no attribute „`curframe`“
- 139: running with `-pylab` pollutes namespace
- 140: malloc error during tab completion of numpy array member functions starting with „`c`“
- 153: `ipy_vimserver` traceback on Windows
- 154: using ipython in Slicer3 show how `os.environ[„HOME“]` is not defined

- 185: `show()` blocks in pylab mode with ipython 0.10.1
- 189: Crash on tab completion
- 274: bashism in `sshx.sh`
- 276: Calling `sip.setapi` does not work if app has already imported from PyQt4
- 277: `matplotlib.image.imshow` from 10.1 segfault
- 288: Incorrect docstring in `zmq/kernelmanager.py`
- 286: Fix IPython.Shell compatibility layer
- 99: blank lines in history
- 129: `psearch`: `TypeError: expected string or buffer`
- 190: Add option to format float point output
- 246: Application not conforms XDG Base Directory Specification
- 48: IPython should follow the XDG Base Directory spec for configuration
- 176: Make client-side history persistence readline-independent
- 279: Backtraces when using `ipdb` do not respect `-colour` `LightBG` setting
- 119: Broken type filter in `magic_who_ls`
- 271: Intermittent problem with print output in Qt console.
- 270: Small typo in IPython developer's guide
- 166: Add keyboard accelerators to Qt close dialog
- 173: asymmetrical `ctrl-A/ctrl-E` behavior in multiline
- 45: Autosave history for robustness
- 162: make command history persist in `ipythonqt`
- 161: make `ipythonqt` exit without dialog when `exit()` is called
- 263: [ipython + numpy] Some test errors
- 256: reset docstring ipython 0.10
- 258: allow caching to avoid matplotlib object references
- 248: Can't open and read files after upgrade from 0.10 to 0.10.0
- 247: `ipython + Stackless`
- 245: Magic save and macro missing newlines, line ranges don't match prompt numbers.
- 241: «exit» hangs on terminal version of IPython
- 213: `ipython -pylab` no longer plots interactively on 0.10.1
- 4: wx frontend don't display well commands output
- 5: `ls` command not supported in `ipythonx` wx frontend
- 1: Document `winhpcjob.py` and `launcher.py`
- 83: Usage of `testing.util.DeferredTestCase` should be replace with `twisted.trial.unittest.TestCase`
- 117: Redesign how Component instances are tracked and queried
- 47: `IPython.kernel.client` cannot be imported inside an engine

- 105: Refactor the task dependencies system
- 210: 0.10.1 doc mistake - New IPython Sphinx directive error
- 209: can't activate IPython parallel magics
- 206: Buggy linewrap in Mac OSX Terminal
- 194: !sudo <command> displays password in plain text
- 186: %edit issue under OS X 10.5 - IPython 0.10.1
- 11: Create a daily build PPA for ipython
- 144: logo missing from sphinx docs
- 181: cls command does not work on windows
- 169: Kernel can only be bound to localhost
- 36: tab completion does not escape ()
- 177: Report tracebacks of interactively entered input
- 148: dictionary having multiple keys having frozenset fails to print on IPython
- 160: magic_gui throws TypeError when gui magic is used
- 150: History entries ending with parentheses corrupt command line on OS X 10.6.4
- 146: -ipythondir - using an alternative .ipython dir for rc type stuff
- 114: Interactive strings get mangled with «_ip.magic»
- 135: crash on invalid print
- 69: Usage of «mycluster» profile in docs and examples
- 37: Fix colors in output of ResultList on Windows

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

2.25 0.10 series

2.25.1 Release 0.10.2

IPython 0.10.2 was released April 9, 2011. This is a minor bugfix release that preserves backward compatibility. At this point, all IPython development resources are focused on the 0.11 series that includes a complete architectural restructuring of the project as well as many new capabilities, so this is likely to be the last release of the 0.10.x series. We have tried to fix all major bugs in this series so that it remains a viable platform for those not ready yet to transition to the 0.11 and newer codebase (since that will require some porting effort, as a number of APIs have changed).

Thus, we are not opening a 0.10.3 active development branch yet, but if the user community requires new patches and is willing to maintain/release such a branch, we'll be happy to host it on the IPython github repositories.

Highlights of this release:

- The main one is the closing of github ticket #185, a major regression we had in 0.10.1 where pylab mode with GTK (or gthread) was not working correctly, hence plots were blocking with GTK. Since this is the default matplotlib backend on Unix systems, this was a major annoyance for many users. Many thanks to Paul Ivanov for helping resolve this issue.
- Fix IOError bug on Windows when used with -gthread.
- Work robustly if \$HOME is missing from environment.
- Better POSIX support in ssh scripts (remove bash-specific idioms).
- Improved support for non-ascii characters in log files.
- Work correctly in environments where GTK can be imported but not started (such as a linux text console without X11).

For this release we merged 24 commits, contributed by the following people (please let us know if we omitted your name and we'll gladly fix this in the notes for the future):

- Fernando Perez
- MinRK
- Paul Ivanov
- Pieter Cristiaan de Groot
- TvrtkoM

2.25.2 Release 0.10.1

IPython 0.10.1 was released October 11, 2010, over a year after version 0.10. This is mostly a bugfix release, since after version 0.10 was released, the development team's energy has been focused on the 0.11 series. We have nonetheless tried to backport what fixes we could into 0.10.1, as it remains the stable series that many users have in production systems they rely on.

Since the 0.11 series changes many APIs in backwards-incompatible ways, we are willing to continue maintaining the 0.10.x series. We don't really have time to actively write new code for 0.10.x, but we are happy to accept patches and pull requests on the IPython [github site](#). If sufficient contributions are made that improve 0.10.1, we will roll them into future releases. For this purpose, we will have a branch called 0.10.2 on github, on which you can base your contributions.

For this release, we applied approximately 60 commits totaling a diff of over 7000 lines:

```
(0.10.1)amirbar[dist]> git diff --oneline rel-0.10.. | wc -l
7296
```

Highlights of this release:

- The only significant new feature is that IPython's parallel computing machinery now supports natively the Sun Grid Engine and LSF schedulers. This work was a joint contribution from Justin Riley, Satra Ghosh and Matthieu Brucher, who put a lot of work into it. We also improved traceback handling in remote tasks, as well as providing better control for remote task IDs.

- New IPython Sphinx directive contributed by John Hunter. You can use this directive to mark blocks in reStructuredText documents as containing IPython syntax (including figures) and the will be executed during the build:

```
In [2]: plt.figure()  # ensure a fresh figure

@savefig psimple.png width=4in
In [3]: plt.plot([1,2,3])
Out[3]: [<matplotlib.lines.Line2D object at 0x9b74d8c>]
```

- Various fixes to the standalone ipython-wx application.
- We now ship internally the excellent argparse library, graciously licensed under BSD terms by Steven Bethard. Now (2010) that argparse has become part of Python 2.7 this will be less of an issue, but Steven's relicensing allowed us to start updating IPython to using argparse well before Python 2.7. Many thanks!
- Robustness improvements so that IPython doesn't crash if the readline library is absent (though obviously a lot of functionality that requires readline will not be available).
- Improvements to tab completion in Emacs with Python 2.6.
- Logging now supports timestamps (see `%logstart?` for full details).
- A long-standing and quite annoying bug where parentheses would be added to `print` statements, under Python 2.5 and 2.6, was finally fixed.
- Improved handling of libreadline on Apple OSX.
- Fix `reload` method of IPython demos, which was broken.
- Fixes for the ipipe/ibrowse system on OSX.
- Fixes for Zope profile.
- Fix `%timeit` reporting when the time is longer than 1000s.
- Avoid lockups with `?` or `??` in SunOS, due to a bug in termios.
- The usual assortment of miscellaneous bug fixes and small improvements.

The following people contributed to this release (please let us know if we omitted your name and we'll gladly fix this in the notes for the future):

- Beni Cherniavsky
- Boyd Waters.
- David Warde-Farley
- Fernando Perez
- Gökhan Sever
- John Hunter
- Justin Riley
- Kiorky
- Laurent Dufrechou
- Mark E. Smith
- Matthieu Brucher
- Satrajit Ghosh

- Sebastian Busch
- Václav Šmilauer

2.25.3 Release 0.10

This release brings months of slow but steady development, and will be the last before a major restructuring and cleanup of IPython's internals that is already under way. For this reason, we hope that 0.10 will be a stable and robust release so that while users adapt to some of the API changes that will come with the refactoring that will become IPython 0.11, they can safely use 0.10 in all existing projects with minimal changes (if any).

IPython 0.10 is now a medium-sized project, with roughly (as reported by David Wheeler's `sloccount` utility) 40750 lines of Python code, and a diff between 0.9.1 and this release that contains almost 28000 lines of code and documentation. Our documentation, in PDF format, is a 495-page long PDF document (also available in HTML format, both generated from the same sources).

Many users and developers contributed code, features, bug reports and ideas to this release. Please do not hesitate in contacting us if we've failed to acknowledge your contribution here. In particular, for this release we have contribution from the following people, a mix of new and regular names (in alphabetical order by first name):

- Alexander Clausen: fix [#341726](#).
- Brian Granger: lots of work everywhere (features, bug fixes, etc).
- Daniel Ashbrook: bug report on `MemoryError` during compilation, now fixed.
- Darren Dale: improvements to documentation build system, feedback, design ideas.
- Fernando Perez: various places.
- Gaël Varoquaux: core code, `ipythonx` GUI, design discussions, etc. Lots...
- John Hunter: suggestions, bug fixes, feedback.
- Jorgen Stenarson: work on many fronts, tests, fixes, win32 support, etc.
- Laurent Dufrécho: many improvements to `ipython-wx` standalone app.
- Lukasz Pankowski: `prefilter`, `%edit`, demo improvements.
- Matt Foster: TextMate support in `%edit`.
- Nathaniel Smith: fix [#237073](#).
- Pauli Virtanen: fixes and improvements to extensions, documentation.
- Prabhu Ramachandran: improvements to `%timeit`.
- Robert Kern: several extensions.
- Sameer D'Costa: help on critical bug [#269966](#).
- Stephan Peijnik: feedback on Debian compliance and many man pages.
- Steven Bethard: we are now shipping his `argparse` module.
- Tom Fetherston: many improvements to `IPython.demos` module.
- Ville Vainio: lots of work everywhere (features, bug fixes, etc).
- Vishal Vasta: ssh support in `ipcluster`.
- Walter Doerwald: work on the `IPython.ipipe` system.

Below we give an overview of new features, bug fixes and backwards-incompatible changes. For a detailed account of every change made, feel free to view the project log with `bzr log`.

New features

- New `%paste` magic automatically extracts current contents of clipboard and pastes it directly, while correctly handling code that is indented or prepended with `>>>` or `...` python prompt markers. A very useful new feature contributed by Robert Kern.
- IPython „demos“, created with the `IPython.demo` module, can now be created from files on disk or strings in memory. Other fixes and improvements to the demo system, by Tom Fetherston.
- Added `find_cmd()` function to `IPython.platutils` module, to find commands in a cross-platform manner.
- Many improvements and fixes to Gaël Varoquaux’s `ipythonx`, a WX-based lightweight IPython instance that can be easily embedded in other WX applications. These improvements have made it possible to now have an embedded IPython in Mayavi and other tools.
- `MultiengineClient` objects now have a `benchmark()` method.
- The manual now includes a full set of auto-generated API documents from the code sources, using Sphinx and some of our own support code. We are now using the [Numpy Documentation Standard](#) for all docstrings, and we have tried to update as many existing ones as possible to this format.
- The new `IPython.Extensions.ipy_pretty` extension by Robert Kern provides configurable pretty-printing.
- Many improvements to the `ipython-wx` standalone WX-based IPython application by Laurent Dufr  chou. It can optionally run in a thread, and this can be toggled at runtime (allowing the loading of Matplotlib in a running session without ill effects).
- IPython includes a copy of Steven Bethard’s `argparse` in the `IPython.external` package, so we can use it internally and it is also available to any IPython user. By installing it in this manner, we ensure zero conflicts with any system-wide installation you may already have while minimizing external dependencies for new users. In IPython 0.10, We ship `argparse` version 1.0.
- An improved and much more robust test suite, that runs groups of tests in separate subprocesses using either Nose or Twisted’s `trial` runner to ensure proper management of Twisted-using code. The test suite degrades gracefully if optional dependencies are not available, so that the `iptest` command can be run with only Nose installed and nothing else. We also have more and cleaner test decorators to better select tests depending on runtime conditions, do setup/teardown, etc.
- The new `ipcluster` now has a fully working ssh mode that should work on Linux, Unix and OS X. Thanks to Vishal Vatsa for implementing this!
- The wonderful TextMate editor can now be used with `%edit` on OS X. Thanks to Matt Foster for this patch.
- The documentation regarding parallel uses of IPython, including MPI and PBS, has been significantly updated and improved.
- The developer guidelines in the documentation have been updated to explain our workflow using `bzr` and Launchpad.
- Fully refactored `ipcluster` command line program for starting IPython clusters. This new version is a complete rewrite and 1) is fully cross platform (we now use Twisted’s process management), 2) has much improved performance, 3) uses subcommands for different types of clusters, 4) uses `argparse` for parsing command line options, 5) has better support for starting clusters using `mpirun`, 6) has experimental support for starting engines using PBS. It can also reuse FURL files, by appropriately

passing options to its subcommands. However, this new version of ipcluster should be considered a technology preview. We plan on changing the API in significant ways before it is final.

- Full description of the security model added to the docs.
- cd completer: show bookmarks if no other completions are available.
- sh profile: easy way to give „title“ to prompt: assign to variable „_prompt_title“. It looks like this:

```
[~]|1> _prompt_title = 'sudo!'
sudo! [~]|2>
```

- %edit: If you do „%edit pasted_block“, pasted_block variable gets updated with new data (so repeated editing makes sense)

Bug fixes

- Fix #368719, removed top-level debian/ directory to make the job of Debian packagers easier.
- Fix #291143 by including man pages contributed by Stephan Peijnik from the Debian project.
- Fix #358202, effectively a race condition, by properly synchronizing file creation at cluster startup time.
- %timeit now handles correctly functions that take a long time to execute even the first time, by not repeating them.
- Fix #239054, releasing of references after exiting.
- Fix #341726, thanks to Alexander Clausen.
- Fix #269966. This long-standing and very difficult bug (which is actually a problem in Python itself) meant long-running sessions would inevitably grow in memory size, often with catastrophic consequences if users had large objects in their scripts. Now, using %run repeatedly should not cause any memory leaks. Special thanks to John Hunter and Sameer D’Costa for their help with this bug.
- Fix #295371, bug in %history.
- Improved support for py2exe.
- Fix #270856: IPython hangs with PyGTK
- Fix #270998: A magic with no docstring breaks the „%magic magic“
- fix #271684: -c startup commands screw up raw vs. native history
- Numerous bugs on Windows with the new ipcluster have been fixed.
- The ipengine and ipcontroller scripts now handle missing furl files more gracefully by giving better error messages.
- %rehashx: Aliases no longer contain dots. python3.0 binary will create alias python30. Fixes: #259716 «commands with dots in them don’t work»
- %cpaste: %cpaste -r repeats the last pasted block. The block is assigned to pasted_block even if code raises exception.
- Bug #274067 „The code in get_home_dir is broken for py2exe“ was fixed.
- Many other small bug fixes not listed here by number (see the bazaar log for more info).

Backwards incompatible changes

- `ipykit` and related files were unmaintained and have been removed.
- The `IPython.genutils.doctest_reload()` does not actually call `reload(doctest)` anymore, as this was causing many problems with the test suite. It still resets `doctest.master` to `None`.
- While we have not deliberately broken Python 2.4 compatibility, only minor testing was done with Python 2.4, while 2.5 and 2.6 were fully tested. But if you encounter problems with 2.4, please do report them as bugs.
- The `ipcluster` now requires a mode argument; for example to start a cluster on the local machine with 4 engines, you must now type:

```
$ ipcluster local -n 4
```

- The controller now has a `-r` flag that needs to be used if you want to reuse existing furl files. Otherwise they are deleted (the default).
- Remove `ipy_leo.py`. You can use `easy_install ipython-extension` to get it. (done to decouple it from `ipython` release cycle)

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

2.26 0.9 series

2.26.1 Release 0.9.1

This release was quickly made to restore compatibility with Python 2.4, which version 0.9 accidentally broke. No new features were introduced, other than some additional testing support for internal use.

2.26.2 Release 0.9

New features

- All furl files and security certificates are now put in a read-only directory named `~/ipython/security`.
- A single function `get_ipython_dir()`, in `IPython.genutils` that determines the user's IPython directory in a robust manner.
- Laurent's WX application has been given a top-level script called `ipython-wx`, and it has received numerous fixes. We expect this code to be architecturally better integrated with Gael's WX „ipython widget“ over the next few releases.

- The Editor synchronization work by Vivian De Smedt has been merged in. This code adds a number of new editor hooks to synchronize with editors under Windows.
- A new, still experimental but highly functional, WX shell by Gael Varoquaux. This work was sponsored by Enthought, and while it's still very new, it is based on a more cleanly organized architecture of the various IPython components. We will continue to develop this over the next few releases as a model for GUI components that use IPython.
- Another GUI frontend, Cocoa based (Cocoa is the OSX native GUI framework), authored by Barry Wark. Currently the WX and the Cocoa ones have slightly different internal organizations, but the whole team is working on finding what the right abstraction points are for a unified codebase.
- As part of the frontend work, Barry Wark also implemented an experimental event notification system that various ipython components can use. In the next release the implications and use patterns of this system regarding the various GUI options will be worked out.
- IPython finally has a full test system, that can test docstrings with IPython-specific functionality. There are still a few pieces missing for it to be widely accessible to all users (so they can run the test suite at any time and report problems), but it now works for the developers. We are working hard on continuing to improve it, as this was probably IPython's major Achilles heel (the lack of proper test coverage made it effectively impossible to do large-scale refactoring). The full test suite can now be run using the `iptest` command line program.
- The notion of a task has been completely reworked. An `ITask` interface has been created. This interface defines the methods that tasks need to implement. These methods are now responsible for things like submitting tasks and processing results. There are two basic task types: `IPython.kernel.task.StringTask` (this is the old `Task` object, but renamed) and the new `IPython.kernel.task.MapTask`, which is based on a function.
- A new interface, `IPython.kernel.mapper.IMapper` has been defined to standardize the idea of a `map` method. This interface has a single `map` method that has the same syntax as the built-in `map`. We have also defined a `mapper` factory interface that creates objects that implement `IPython.kernel.mapper.IMapper` for different controllers. Both the multiengine and task controller now have mapping capabilities.
- The parallel function capabilities have been reworks. The major changes are that i) there is now an `@parallel` magic that creates parallel functions, ii) the syntax for multiple variable follows that of `map`, iii) both the multiengine and task controller now have a parallel function implementation.
- All of the parallel computing capabilities from `ipython1-dev` have been merged into IPython proper. This resulted in the following new subpackages: `IPython.kernel`, `IPython.kernel.core`, `traitlets.config`, `IPython.tools` and `IPython.testing`.
- As part of merging in the `ipython1-dev` stuff, the `setup.py` script and friends have been completely refactored. Now we are checking for dependencies using the approach that matplotlib uses.
- The documentation has been completely reorganized to accept the documentation from `ipython1-dev`.
- We have switched to using Foolscape for all of our network protocols in `IPython.kernel`. This gives us secure connections that are both encrypted and authenticated.
- We have a brand new `COPYING.txt` files that describes the IPython license and copyright. The biggest change is that we are putting «The IPython Development Team» as the copyright holder. We give more details about exactly what this means in this file. All developer should read this and use the new banner in all IPython source code files.
- sh profile: `./foo` runs `foo` as system command, no need to do `!./foo` anymore
- String lists now support `sort(field, nums = True)` method (to easily sort system command output). Try it with `a = !ls -l ; a.sort(1, nums=1)`.

- „%cpaste foo“ now assigns the pasted block as string list, instead of string
- The ipcluster script now run by default with no security. This is done because the main usage of the script is for starting things on localhost. Eventually when ipcluster is able to start things on other hosts, we will put security back.
- „cd -foo“ searches directory history for string foo, and jumps to that dir. Last part of dir name is checked first. If no matches for that are found, look at the whole path.

Bug fixes

- The Windows installer has been fixed. Now all IPython scripts have .bat versions created. Also, the Start Menu shortcuts have been updated.
- The colors escapes in the multiengine client are now turned off on win32 as they don't print correctly.
- The `IPython.kernel.scripts.ipengine` script was exec'ing `mpi_import_statement` incorrectly, which was leading the engine to crash when mpi was enabled.
- A few subpackages had missing `__init__.py` files.
- The documentation is only created if Sphinx is found. Previously, the `setup.py` script would fail if it was missing.
- Greedy `cd` completion has been disabled again (it was enabled in 0.8.4) as it caused problems on certain platforms.

Backwards incompatible changes

- The `clusterfile` options of the `ipcluster` command has been removed as it was not working and it will be replaced soon by something much more robust.
- The `IPython.kernel` configuration now properly find the user's IPython directory.
- In `ipapi`, the `make_user_ns()` function has been replaced with `make_user_namespaces()`, to support dict subclasses in namespace creation.
- `IPython.kernel.client.Task` has been renamed `IPython.kernel.client.StringTask` to make way for new task types.
- The keyword argument `style` has been renamed `dist` in `scatter`, `gather` and `map`.
- Renamed the values that the rename `dist` keyword argument can have from 'basic' to 'b'.
- IPython has a larger set of dependencies if you want all of its capabilities. See the `setup.py` script for details.
- The constructors for `IPython.kernel.client.MultiEngineClient` and `IPython.kernel.client.TaskClient` no longer take the (ip,port) tuple. Instead they take the filename of a file that contains the FURL for that client. If the FURL file is in your `IPYTHONDIR`, it will be found automatically and the constructor can be left empty.
- The asynchronous clients in `IPython.kernel.asyncclient` are now created using the factory functions `get_multiengine_client()` and `get_task_client()`. These return a `Deferred` to the actual client.
- The command line options to `ipcontroller` and `ipengine` have changed to reflect the new Foolscape network protocol and the FURL files. Please see the help for these scripts for details.
- The configuration files for the kernel have changed because of the Foolscape stuff. If you were using custom config files before, you should delete them and regenerate new ones.

Changes merged in from IPython1

New features

- Much improved `setup.py` and `setuptools.py` scripts. Because Twisted and `zope.interface` are now easy installable, we can declare them as dependencies in our `setuptools.py` script.
- IPython is now compatible with Twisted 2.5.0 and 8.x.
- Added a new example of how to use `ipython1.kernel.asyncclient`.
- Initial draft of a process daemon in `ipython1.daemon`. This has not been merged into IPython and is still in `ipython1-dev`.
- The `TaskController` now has methods for getting the queue status.
- The `TaskResult` objects not have information about how long the task took to run.
- We are attaching additional attributes to exceptions (`_ipython_*`) that we use to carry additional info around.
- New top-level module `asyncclient` that has asynchronous versions (that return deferreds) of the client classes. This is designed to users who want to run their own Twisted reactor.
- All the clients in `client` are now based on Twisted. This is done by running the Twisted reactor in a separate thread and using the `blockingCallFromThread()` function that is in recent versions of Twisted.
- Functions can now be pushed/pulled to/from engines using `MultiEngineClient.push_function()` and `MultiEngineClient.pull_function()`.
- Gather/scatter are now implemented in the client to reduce the work load of the controller and improve performance.
- Complete rewrite of the IPython documentation. All of the documentation from the IPython website has been moved into `docs/source` as restructured text documents. PDF and HTML documentation are being generated using Sphinx.
- New developer oriented documentation: development guidelines and roadmap.
- Traditional `ChangeLog` has been changed to a more useful `changes.txt` file that is organized by release and is meant to provide something more relevant for users.

Bug fixes

- Created a proper `MANIFEST.in` file to create source distributions.
- Fixed a bug in the `MultiEngine` interface. Previously, multi-engine actions were being collected with a `DeferredList` with `fireononeerrback=1`. This meant that methods were returning before all engines had given their results. This was causing extremely odd bugs in certain cases. To fix this problem, we have 1) set `fireononeerrback=0` to make sure all results (or exceptions) are in before returning and 2) introduced a `CompositeError` exception that wraps all of the engine exceptions. This is a huge change as it means that users will have to catch `CompositeError` rather than the actual exception.

Backwards incompatible changes

- All names have been renamed to conform to the lowercase_with_underscore convention. This will require users to change references to all names like `queueStatus` to `queue_status`.
- Previously, methods like `MultiEngineClient.push()` and `MultiEngineClient.pull()` used `*args` and `**kwargs`. This was becoming a problem as we weren't able to introduce new keyword arguments into the API. Now these methods simply take a dict or sequence. This has also allowed us to get rid of the `*All` methods like `pushAll()` and `pullAll()`. These things are now handled with the `targets` keyword argument that defaults to `'all'`.
- The `MultiEngineClient.magicTargets` has been renamed to `MultiEngineClient.targets`.
- All methods in the `MultiEngine` interface now accept the optional keyword argument `block`.
- Renamed `RemoteController` to `MultiEngineClient` and `TaskController` to `TaskClient`.
- Renamed the top-level module from `api` to `client`.
- Most methods in the multiengine interface now raise a `CompositeError` exception that wraps the user's exceptions, rather than just raising the raw user's exception.
- Changed the `setupNS` and `resultNames` in the `Task` class to `push` and `pull`.

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

2.27 0.8 series

2.27.1 Release 0.8.4

This was a quick release to fix an unfortunate bug that slipped into the 0.8.3 release. The `--twisted` option was disabled, as it turned out to be broken across several platforms.

2.27.2 Release 0.8.3

- `pydb` is now disabled by default (due to `%run -d` problems). You can enable it by passing `-pydb` command line argument to IPython. Note that setting it in config file won't work.

2.27.3 Release 0.8.2

- `%pushd/%popd` behave differently; now «`pushd /foo`» pushes CURRENT directory and jumps to `/foo`. The current behaviour is closer to the documented behaviour, and should not trip anyone.

2.27.4 Older releases

Changes in earlier releases of IPython are described in the older file `ChangeLog`. Please refer to this document for details.

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

3.1 Installing IPython

IPython 6 requires Python 3.3. IPython 5.x can be installed on Python 2.

3.1.1 Quick Install

With `pip` already installed :

```
$ pip install ipython
```

This installs IPython as well as its dependencies.

If you want to use IPython with notebooks or the Qt console, you should also install Jupyter `pip install jupyter`.

3.1.2 Overview

This document describes in detail the steps required to install IPython. For a few quick ways to get started with package managers or full Python distributions, see [the install page](#) of the IPython website.

Please let us know if you have problems installing IPython or any of its dependencies.

IPython and most dependencies should be installed via `pip`. In many scenarios, this is the simplest method of installing Python packages. More information about `pip` can be found on [its PyPI page](#).

More general information about installing Python packages can be found in [Python's documentation](#).

Dependencies

IPython relies on a number of other Python packages. Installing using a package manager like `pip` or `conda` will ensure the necessary packages are installed. Manual installation without dependencies is possible, but not recommended. The dependencies can be viewed with package manager commands, such as `pip show ipython` or `conda info ipython`.

Installing IPython itself

IPython requires several dependencies to work correctly, it is not recommended to install IPython and all its dependencies manually as this can be quite long and troublesome. You should use the python package manager `pip`.

Installation using pip

Make sure you have the latest version of `pip` (the Python package manager) installed. If you do not, head to [Pip documentation](#) and install `pip` first.

The quickest way to get up and running with IPython is to install it with `pip`:

```
$ pip install ipython
```

That's it.

Installation from source

To install IPython from source, grab the latest stable tarball of IPython [from PyPI](#). Then do the following:

```
tar -xzf ipython-5.1.0.tar.gz
cd ipython-5.1.0
# The [test] extra ensures test dependencies are installed too:
pip install '.[test]'
```

Do not invoke `setup.py` directly as this can have undesirable consequences for further upgrades. We do not recommend using `easy_install` either.

If you are installing to a location (like `/usr/local`) that requires higher permissions, you may need to run the last command with `sudo`. You can also install in user specific location by using the `--user` flag in conjunction with `pip`.

To run IPython's test suite, use the `pytest` command:

```
$ pytest
```

Installing the development version

It is also possible to install the development version of IPython from our [Git](#) source code repository. To do this you will need to have Git installed on your system.

Then do:

```
$ git clone https://github.com/ipython/ipython.git
$ cd ipython
$ pip install -e '.[test]'
```

The `pip install -e .` command allows users and developers to follow the development branch as it changes by creating links in the right places and installing the command line scripts to the appropriate locations.

Then, if you want to update your IPython at any time, do:

```
$ git pull
```

If the dependencies or entrypoints have changed, you may have to run

```
$ pip install -e .
```

again, but this is infrequent.

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

3.2 Installing the IPython kernel

См.также:

Installing Jupyter

The IPython kernel is the Python execution backend for Jupyter.

The Jupyter Notebook and other frontends automatically ensure that the IPython kernel is available. However, if you want to use a kernel with a different version of Python, or in a virtualenv or conda environment, you'll need to install that manually.

3.2.1 Kernels for Python 2 and 3

If you're running Jupyter on Python 3, you can set up a Python 2 kernel after checking your version of pip is greater than 9.0:

```
python2 -m pip --version
```

Then install with

```
python2 -m pip install ipykernel
python2 -m ipykernel install --user
```

Or using conda, create a Python 2 environment:

```
conda create -n ipykernel_py2 python=2 ipykernel
source activate ipykernel_py2      # On Windows, remove the word 'source'
python -m ipykernel install --user
```

Примечание: IPython 6.0 stopped support for Python 2, so installing IPython on Python 2 will give you an older version (5.x series).

If you're running Jupyter on Python 2 and want to set up a Python 3 kernel, follow the same steps, replacing 2 with 3.

The last command installs a [kernel spec](#) file for the current python installation. Kernel spec files are JSON files, which can be viewed and changed with a normal text editor.

3.2.2 Kernels for different environments

If you want to have multiple IPython kernels for different virtualenvs or conda environments, you will need to specify unique names for the kernelspecs.

Make sure you have ipykernel installed in your environment. If you are using pip to install ipykernel in a conda env, make sure pip is installed:

```
source activate myenv
conda install pip
conda install ipykernel # or pip install ipykernel
```

For example, using conda environments, install a Python (myenv) Kernel in a first environment:

```
source activate myenv
python -m ipykernel install --user --name myenv --display-name "Python (myenv)"
```

And in a second environment, after making sure ipykernel is installed in it:

```
source activate other-env
python -m ipykernel install --user --name other-env --display-name "Python (other-env)"
```

The `--name` value is used by Jupyter internally. These commands will overwrite any existing kernel with the same name. `--display-name` is what you see in the notebook menus.

Using virtualenv or conda envs, you can make your IPython kernel in one env available to Jupyter in a different env. To do so, run ipykernel install from the kernel's env, with `-prefix` pointing to the Jupyter env:

```
/path/to/kernel/env/bin/python -m ipykernel install --prefix=/path/to/jupyter/env --name
↪ 'python-my-env'
```

Note that this command will create a new configuration for the kernel in one of the preferred location (see `jupyter --paths` command for more details):

- system-wide (e.g. `/usr/local/share`),
- in Jupyter's env (`sys.prefix/share`),
- per-user (`~/local/share` or `~/Library/share`)

If you want to edit the kernelspec before installing it, you can do so in two steps. First, ask IPython to write its spec to a temporary location:

```
ipython kernel install --prefix /tmp
```

edit the files in `/tmp/share/jupyter/kernels/python3` to your liking, then when you are ready, tell Jupyter to install it (this will copy the files into a place Jupyter will look):

```
jupyter kernelspec install /tmp/share/jupyter/kernels/python3
```

This sections will guide you through *installing IPython itself*, and installing *kernels for Jupyter* if you wish to work with multiple version of Python, or multiple environments.

3.3 Quick install reminder

Here is a quick reminder of the commands needed for installation if you are already familiar with IPython and are just searching to refresh your memory:

Install IPython:

```
$ pip install ipython
```

Install and register an IPython kernel with Jupyter:

```
$ python -m pip install ipykernel

$ python -m ipykernel install [--user] [--name <machine-readable-name>] [--display-name <
↪ "User Friendly Name">]
```

for more help see

```
$ python -m ipykernel install --help
```

См.также:

Installing Jupyter

The Notebook, nbconvert, and many other former pieces of IPython are now part of Project Jupyter.

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

В этом разделе документации IPython вы познакомитесь с большинством функций IPython. Вам не нужно обладать глубокими знаниями Python, чтобы прочитать это руководство, хотя некоторые разделы могут иметь немного больше смысла, если вы уже проделали некоторую работу в классическом Python REPL.

Примечание: Некоторым частям этой документации более десяти лет, поэтому они могут устареть, мы приветствуем любые сообщения о неточностях и запросы на извлечение, которые делают его актуальным.

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

4.1 Introducing IPython

You don't need to know anything beyond Python to start using IPython – just type commands as you would at the standard Python prompt. But IPython can do much more than the standard prompt. Some key features are described here. For more information, check the [tips page](#), or look at examples in the [IPython cookbook](#).

If you haven't done that yet see [how to install ipython](#).

If you've never used Python before, you might want to look at [the official tutorial](#) or an alternative, [Dive into Python](#).

Start IPython by issuing the `ipython` command from your shell, you should be greeted by the following:

```
Python 3.6.0
Type 'copyright', 'credits' or 'license' for more information
IPython 6.0.0.dev -- An enhanced Interactive Python. Type '?' for help.

In [1]:
```

Unlike the Python REPL, you will see that the input prompt is `In [N]:` instead of `>>>`. The number `N` in the prompt will be used later in this tutorial but should usually not impact the computation.

You should be able to type single line expressions and press enter to evaluate them. If an expression is incomplete, IPython will automatically detect this and add a new line when you press **Enter** instead of executing right away.

Feel free to explore multi-line text input. Unlike many other REPLs, with IPython you can use the up and down arrow keys when editing multi-line code blocks.

Here is an example of a longer interaction with the IPython REPL, which we often refer to as an IPython *session*

```
In [1]: print('Hello IPython')
Hello IPython

In [2]: 21 * 2
Out[2]: 42

In [3]: def say_hello(name):
...:     print('Hello {name}'.format(name=name))
...:
```

We won't get into details right now, but you may notice a few differences to the standard Python REPL. First, your code should be syntax-highlighted as you type. Second, you will see that some results will have an `Out[N]:` prompt, while some other do not. We'll come to this later.

Depending on the exact command you are typing you might realize that sometimes **Enter** will add a new line, and sometimes it will execute the current statement. IPython tries to guess what you are doing, so most of the time you should not have to care. Though if by any chance IPython does not do the right thing you can force execution of the current code block by pressing in sequence **Esc** and **Enter**. You can also force the insertion of a new line at the position of the cursor by using **Ctrl-o**.

4.1.1 The four most helpful commands

The four most helpful commands, as well as their brief description, is shown to you in a banner, every time you start IPython:

command	description
?	Introduction and overview of IPython's features.
%quickref	Quick reference.
help	Python's own help system.
object?	Details about „object“, use „object??“ for extra details.

4.1.2 Tab completion

Tab completion, especially for attributes, is a convenient way to explore the structure of any object you're dealing with. Simply type `object_name.<TAB>` to view the object's attributes. Besides Python objects and keywords, tab completion also works on file and directory names.

Starting with IPython 6.0, if `jedi` is installed, IPython will try to pull completions from Jedi as well. This allows to not only inspect currently existing objects, but also to infer completion statically without executing code. There is nothing particular needed to get this to work, simply use tab completion on more complex expressions like the following:

```
>>> data = ['Number of users', 123456]
... data[0].<tab>
```

IPython and Jedi will be able to infer that `data[0]` is actually a string and should show relevant completions like `upper()`, `lower()` and other string methods. You can use the **Tab** key to cycle through completions, and while a completion is highlighted, its type will be shown as well. When the type of the completion is a function, the completer will also show the signature of the function when highlighted.

4.1.3 Exploring your objects

Typing `object_name?` will print all sorts of details about any object, including docstrings, function definition lines (for call arguments) and constructor details for classes. To get specific information on an object, you can use the magic commands `%pdoc`, `%pdef`, `%psource` and `%pfile`

4.1.4 Magic functions

IPython has a set of predefined „magic functions“ that you can call with a command line style syntax. There are two kinds of magics, line-oriented and cell-oriented. **Line magics** are prefixed with the `%` character and work much like OS command-line calls: they get as an argument the rest of the line, where arguments are passed without parentheses or quotes. **Lines magics** can return results and can be used in the right hand side of an assignment. **Cell magics** are prefixed with a double `%%`, and they are functions that get as an argument not only the rest of the line, but also the lines below it in a separate argument.

Magics are useful as convenient functions where Python syntax is not the most natural one, or when one want to embed invalid python syntax in their work flow.

The following examples show how to call the built-in `%timeit` magic, both in line and cell mode:

```
In [1]: %timeit range(1000)
100000 loops, best of 3: 7.76 us per loop

In [2]: %%timeit x = range(10000)
...: max(x)
...:
1000 loops, best of 3: 223 us per loop
```

The built-in magics include:

- Functions that work with code: `%run`, `%edit`, `%save`, `%macro`, `%recall`, etc.
- Functions which affect the shell: `%colors`, `%xmode`, `%automagic`, etc.
- Other functions such as `%reset`, `%timeit`, `%%writefile`, `%load`, or `%paste`.

You can always call magics using the `%` prefix, and if you're calling a line magic on a line by itself, as long as the identifier is not defined in your namespace, you can omit even that:

```
run thescript.py
```

You can toggle this behavior by running the `%automagic` magic. Cell magics must always have the `%%` prefix.

A more detailed explanation of the magic system can be obtained by calling `%magic`, and for more details on any magic function, call `%somemagic?` to read its docstring. To see all the available magic functions, call `%lsmagic`.

См.также:

The *Magic command system* section of the documentation goes more in depth into how the magics works and how to define your own, and *Built-in magic commands* for a list of built-in magics.

[Cell magics example notebook](#)

Running and Editing

The `%run` magic command allows you to run any python script and load all of its data directly into the interactive namespace. Since the file is re-read from disk each time, changes you make to it are reflected immediately (unlike imported modules, which have to be specifically reloaded). IPython also includes `dreload`, a recursive reload function.

`%run` has special flags for timing the execution of your scripts (`-t`), or for running them under the control of either Python's pdb debugger (`-d`) or profiler (`-p`).

The `%edit` command gives a reasonable approximation of multi-line editing, by invoking your favorite editor on the spot. IPython will execute the code you type in there as if it were typed interactively. Note that for `%edit` to work, the call to startup your editor has to be a blocking call. In a GUI environment, your editor likely will have such an option.

Debugging

After an exception occurs, you can call `%debug` to jump into the Python debugger (pdb) and examine the problem. Alternatively, if you call `%pdb`, IPython will automatically start the debugger on any uncaught exception. You can print variables, see code, execute statements and even walk up and down the call stack to track down the true source of the problem. This can be an efficient way to develop and debug code, in many cases eliminating the need for print statements or external debugging tools.

You can also step through a program from the beginning by calling `%run -d theprogram.py`.

4.1.5 History

IPython stores both the commands you enter, and the results it produces. You can easily go through previous commands with the up- and down-arrow keys, or access your history in more sophisticated ways.

Input and output history are kept in variables called `In` and `Out`, keyed by the prompt numbers, e.g. `In[4]`. The last three objects in output history are also kept in variables named `_`, `__` and `___`.

You can use the `%history` magic function to examine past input and output. Input history from previous sessions is saved in a database, and IPython can be configured to save output history.

Several other magic functions can use your input history, including `%edit`, `%rerun`, `%recall`, `%macro`, `%save` and `%pastebin`. You can use a standard format to refer to lines:

```
%pastebin 3 18-20 ~1/1-5
```

This will take line 3 and lines 18 to 20 from the current session, and lines 1-5 from the previous session.

4.1.6 System shell commands

To run any command at the system shell, simply prefix it with `!`, e.g.:

```
!ping www.bbc.co.uk
```

You can capture the output into a Python list, e.g.: `files = !ls`. To pass the values of Python variables or expressions to system commands, prefix them with `$`: `!grep -rF $pattern ipython/*` or wrap in `{braces}`. See [our shell section](#) for more details.

Define your own system aliases

It's convenient to have aliases to the system commands you use most often. This allows you to work seamlessly from inside IPython with the same commands you are used to in your system shell. IPython comes with some pre-defined aliases and a complete system for changing directories, both via a stack (see `%pushd`, `%popd` and `%dhist`) and via direct `%cd`. The latter keeps a history of visited directories and allows you to go to any previously visited one.

4.1.7 Configuration

Much of IPython can be tweaked through *configuration*. To get started, use the command `ipython profile create` to produce the default config files. These will be placed in `~/.ipython/profile_default`, and contain comments explaining what the various options do.

Profiles allow you to use IPython for different tasks, keeping separate config files and history for each one. More details in *the profiles section*.

Startup Files

If you want some code to be run at the beginning of every IPython session, the easiest way is to add Python (.py) or IPython (.ipy) scripts to your `profile_default/startup/` directory. Files here will be executed as soon as the IPython shell is constructed, before any other code or scripts you have specified. The files will be run in order of their names, so you can control the ordering with prefixes, like `10-myimports.py`.

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

4.2 Rich Outputs

One of the main feature of IPython when used as a kernel is its ability to show rich output. This means that object that can be representing as image, sounds, animation, (etc...) can be shown this way if the frontend support it.

In order for this to be possible, you need to use the `display()` function, that should be available by default on IPython 5.4+ and 6.1+, or that you can import with `from IPython.display import display`. Then use `display(<your object>)` instead of `print()`, and if possible your object will be displayed with a richer representation. In the terminal of course, there won't be much difference as object are most of the time represented by text, but in notebook and similar interface you will get richer outputs.

4.3 Plotting

Примечание: Starting with IPython 5.0 and matplotlib 2.0 you can avoid the use of IPython's specific magic and use `matplotlib.pyplot.ion()/matplotlib.pyplot.ioff()` which have the advantages of working outside of IPython as well.

One major feature of the IPython kernel is the ability to display plots that are the output of running code cells. The IPython kernel is designed to work seamlessly with the `matplotlib` plotting library to provide this functionality.

To set this up, before any plotting or import of `matplotlib` is performed you must execute the `%matplotlib magic command`. This performs the necessary behind-the-scenes setup for IPython to work correctly hand in hand with `matplotlib`; it does *not*, however, actually execute any Python `import` commands, that is, no names are added to the namespace.

If the `%matplotlib` magic is called without an argument, the output of a plotting command is displayed using the default `matplotlib` backend in a separate window. Alternatively, the backend can be explicitly requested using, for example:

```
%matplotlib gtk
```

A particularly interesting backend, provided by IPython, is the `inline` backend. This is available only for the Jupyter Notebook and the Jupyter QtConsole. It can be invoked as follows:

```
%matplotlib inline
```

With this backend, the output of plotting commands is displayed *inline* within frontends like the Jupyter notebook, directly below the code cell that produced it. The resulting plots will then also be stored in the notebook document.

См.также:

[Plotting with Matplotlib example notebook](#)

The `matplotlib` library also ships with `%matplotlib notebook` command that allows interactive figures if your environment allows it.

See the `matplotlib` documentation for more information.

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

4.4 IPython reference

4.4.1 Command-line usage

You start IPython with the command:

```
$ ipython [options] files
```

If invoked with no options, it executes the file and exits, passing the remaining arguments to the script, just as if you had specified the same command with `python`. You may need to specify `--` before args to be passed to the script, to prevent IPython from attempting to parse them. If you add the `-i` flag, it drops you into the interpreter while still acknowledging any options you may have set in your `ipython_config.py`. This behavior is different from standard Python, which when called as `python -i` will only execute one file and ignore your configuration setup.

Please note that some of the configuration options are not available at the command line, simply because they are not practical here. Look into your configuration files for details on those. There are separate configuration files for each profile, and the files look like `ipython_config.py` or `ipython_config_<frontendname>.py`. Profile directories look like `profile_<profilename>` and are typically installed in the `IPYTHONDIR` directory, which defaults to `$HOME/.ipython`. For Windows users, `HOME` resolves to `C:\Users\{YourUserName}` in most instances.

Command-line Options

To see the options IPython accepts, use `ipython --help` (and you probably should run the output through a pager such as `ipython --help | less` for more convenient reading). This shows all the options that have a single-word alias to control them, but IPython lets you configure all of its objects from the command-line by passing the full class name and a corresponding value; type `ipython --help-all` to see this full list. For example:

```
$ ipython --help-all
<...snip...>
--matplotlib=<CaselessStrEnum> (InteractiveShellApp.matplotlib)
  Default: None
  Choices: ['auto', 'gtk', 'gtk3', 'gtk4', 'inline', 'nbagg', 'notebook', 'osx', 'qt',
  → 'qt5', 'qt6', 'tk', 'wx']
  Configure matplotlib for interactive use with the default matplotlib
  backend.
<...snip...>
```

Indicate that the following:

```
$ ipython --matplotlib qt
```

is equivalent to:

```
$ ipython --InteractiveShellApp.matplotlib='qt'
```

Note that in the second form, you *must* use the equal sign, as the expression is evaluated as an actual Python assignment. While in the above example the short form is more convenient, only the most common options have a short form, while any configurable variable in IPython can be set at the command-line by using the long form. This long form is the same syntax used in the configuration files, if you want to set these options permanently.

4.4.2 Interactive use

IPython is meant to work as a drop-in replacement for the standard interactive interpreter. As such, any code which is valid python should execute normally under IPython (cases where this is not true should be reported as bugs). It does, however, offer many features which are not available at a standard python prompt. What follows is a list of these.

Caution for Windows users

Windows, unfortunately, uses the `\` character as a path separator. This is a terrible choice, because `\` also represents the escape character in most modern programming languages, including Python. For this reason, using `./` character is recommended if you have problems with `\`. However, in Windows commands `./` flags options, so you can not use it for the root directory. This means that paths beginning at the root must be typed in a contrived manner like: `%copy \opt/foo/bar.txt \tmp`

Magic command system

IPython will treat any line whose first character is a `%` as a special call to a „magic“ function. These allow you to control the behavior of IPython itself, plus a lot of system-type features. They are all prefixed with a `%` character, but parameters are given without parentheses or quotes.

Lines that begin with `%%` signal a *cell magic*: they take as arguments not only the rest of the current line, but all lines below them as well, in the current execution block. Cell magics can in fact make arbitrary modifications to the input they receive, which need not even be valid Python code at all. They receive the whole block as a single string.

As a line magic example, the `%cd` magic works just like the OS command of the same name:

```
In [8]: %cd
/home/fperez
```

The following uses the builtin `%timeit` in cell mode:

```
In [10]: %%timeit x = range(10000)
...: min(x)
...: max(x)
...:
1000 loops, best of 3: 438 us per loop
```

In this case, `x = range(10000)` is called as the line argument, and the block with `min(x)` and `max(x)` is called as the cell body. The `%timeit` magic receives both.

If you have „automagic“ enabled (as it is by default), you don’t need to type in the single `%` explicitly for line magics; IPython will scan its internal list of magic functions and call one if it exists. With automagic on you can then just type `cd mydir` to go to directory „mydir“:

```
In [9]: cd mydir
/home/fperez/mydir
```

Cell magics *always* require an explicit `%%` prefix, automagic calling only works for line magics.

The automagic system has the lowest possible precedence in name searches, so you can freely use variables with the same names as magic commands. If a magic command is „shadowed“ by a variable, you will need the explicit `%` prefix to use it:

```
In [1]: cd ipython      # %cd is called by automagic
/home/fperez/ipython

In [2]: cd=1            # now cd is just a variable

In [3]: cd ..           # and doesn't work as a function anymore
File "<ipython-input-3-9fedb3aff56c>", line 1
```

(continues on next page)

(продолжение с предыдущей страницы)

```
cd ..
^
SyntaxError: invalid syntax

In [4]: %cd ..          # but %cd always works
/home/fperez

In [5]: del cd          # if you remove the cd variable, automagic works again

In [6]: cd ipython
/home/fperez/ipython
```

Line magics, if they return a value, can be assigned to a variable using the syntax `l = %sx ls` (which in this particular case returns the result of `ls` as a python list). See [below](#) for more information.

Type `%magic` for more information, including a list of all available magic functions at any time and their docstrings. You can also type `%magic_function_name?` (see [below](#) for information on the „?” system) to get information about any particular magic function you are interested in.

The API documentation for the `IPython.core.magic` module contains the full docstrings of all currently available magic commands.

См.также:

Built-in magic commands

A list of the line and cell magics available in IPython by default

Defining custom magics

How to define and register additional magic functions

Access to the standard Python help

Simply type `help()` to access Python’s standard help system. You can also type `help(object)` for information about a given object, or `help('keyword')` for information on a keyword. You may need to configure your PYTHONDOCS environment variable for this feature to work correctly.

Dynamic object information

Typing `?word` or `word?` prints detailed information about an object. If certain strings in the object are too long (e.g. function signatures) they get snipped in the center for brevity. This system gives access variable types and values, docstrings, function prototypes and other useful information.

If the information will not fit in the terminal, it is displayed in a pager (`less` if available, otherwise a basic internal pager).

Typing `??word` or `word??` gives access to the full information, including the source code where possible. Long strings are not snipped.

The following magic functions are particularly useful for gathering information about your working environment:

- `%pdoc <object>`: Print (or run through a pager if too long) the docstring for an object. If the given object is a class, it will print both the class and the constructor docstrings.

- `%pdef <object>`: Print the call signature for any callable object. If the object is a class, print the constructor information.
- `%psource <object>`: Print (or run through a pager if too long) the source code for an object.
- `%pfile <object>`: Show the entire source file where an object was defined via a pager, opening it at the line where the object definition begins.
- `%who / %whos`: These functions give information about identifiers you have defined interactively (not things you loaded or defined in your configuration files). `%who` prints a list of identifiers and `%whos` prints a table with some basic details about each identifier.

The dynamic object information functions (`?/??`, `%pdoc`, `%pfile`, `%pdef`, `%psource`) work on object attributes, as well as directly on variables. For example, after doing `import os`, you can use `os.path.abspath??`.

Command line completion

At any time, hitting TAB will complete any available python commands or variable names, and show you a list of the possible completions if there's no unambiguous one. It will also complete filenames in the current directory if no python names match what you've typed so far.

Search command history

IPython provides two ways for searching through previous input and thus reduce the need for repetitive typing:

1. Start typing, and then use the up and down arrow keys (or `Ctrl-p` and `Ctrl-n`) to search through only the history items that match what you've typed so far.
2. Hit `Ctrl-r`: to open a search prompt. Begin typing and the system searches your history for lines that contain what you've typed so far, completing as much as it can.

IPython will save your input history when it leaves and reload it next time you restart it. By default, the history file is named `.ipython/profile_name/history.sqlite`.

Autoindent

Starting with 5.0, IPython uses `prompt_toolkit` in place of `readline`, it thus can recognize lines ending in `„,“` and indent the next line, while also un-indenting automatically after `„raise“` or `„return“`, and support real multi-line editing as well as syntactic coloration during edition.

This feature does not use the `readline` library anymore, so it will not honor your `~/inputrc` configuration (or whatever file your `INPUTRC` environment variable points to).

In particular if you want to change the input mode to `vi`, you will need to set the `TerminalInteractiveShell.editing_mode` configuration option of IPython.

Session logging and restoring

You can log all input from a session either by starting IPython with the command line switch `--logfile=foo.py` (see [here](#)) or by activating the logging at any moment with the magic function `%logstart`.

Log files can later be reloaded by running them as scripts and IPython will attempt to „replay“ the log by executing all the lines in it, thus restoring the state of a previous session. This feature is not quite perfect, but can still be useful in many cases.

The log files can also be used as a way to have a permanent record of any code you wrote while experimenting. Log files are regular text files which you can later open in your favorite text editor to extract code or to „clean them up“ before using them to replay a session.

The `%logstart` function for activating logging in mid-session is used as follows:

```
%logstart [log_name [log_mode]]
```

If no name is given, it defaults to a file named „ipython_log.py“ in your current working directory, in „rotate“ mode (see below).

„%logstart name“ saves to file „name“ in „backup“ mode. It saves your history up to that point and then continues logging.

`%logstart` takes a second optional parameter: logging mode. This can be one of (note that the modes are given unquoted):

- [over:] overwrite existing log_name.
- [backup:] rename (if exists) to log_name~ and start log_name.
- [append:] well, that says it.
- [rotate:] create rotating logs log_name.1~, log_name.2~, etc.

Adding the „-o“ flag to „%logstart“ magic (as in „%logstart -o [log_name [log_mode]]“) will also include output from iPython in the log file.

The `%logoff` and `%logon` functions allow you to temporarily stop and resume logging to a file which had previously been started with `%logstart`. They will fail (with an explanation) if you try to use them before logging has been started.

System shell access

Any input line beginning with a `!` character is passed verbatim (minus the `!`, of course) to the underlying operating system. For example, typing `!ls` will run „ls“ in the current directory.

Manual capture of command output and magic output

You can assign the result of a system command to a Python variable with the syntax `myfiles = !ls`. Similarly, the result of a magic (as long as it returns a value) can be assigned to a variable. For example, the syntax `myfiles = %sx ls` is equivalent to the above system command example (the `%sx` magic runs a shell command and captures the output). Each of these gets machine readable output from stdout (e.g. without colours), and splits on newlines. To explicitly get this sort of output without assigning to a variable, use two exclamation marks (`!!ls`) or the `%sx` magic command without an assignment. (However, `!!` commands cannot be assigned to a variable.)

The captured list in this example has some convenience features. `myfiles.n` or `myfiles.s` returns a string delimited by newlines or spaces, respectively. `myfiles.p` produces [path objects](#) from the list items. See [String lists](#) for details.

IPython also allows you to expand the value of python variables when making system calls. Wrap variables or expressions in `{braces}`:

```
In [1]: pyvar = 'Hello world'
In [2]: !echo "A python variable: {pyvar}"
A python variable: Hello world
In [3]: import math
In [4]: x = 8
In [5]: !echo {math.factorial(x)}
40320
```

For simple cases, you can alternatively prepend `$` to a variable name:

```
In [6]: !echo $sys.argv
[/home/fperez/usr/bin/ipython]
In [7]: !echo "A system variable: $$HOME" # Use $$ for literal $
A system variable: /home/fperez
```

Note that `$$` is used to represent a literal `$`.

System command aliases

The `%alias` magic function allows you to define magic functions which are in fact system shell commands. These aliases can have parameters.

`%alias alias_name cmd` defines „alias_name“ as an alias for „cmd“

Then, typing `alias_name params` will execute the system command „cmd params“ (from your underlying operating system).

You can also define aliases with parameters using `%s` specifiers (one per parameter). The following example defines the `parts` function as an alias to the command `echo first %s second %s` where each `%s` will be replaced by a positional parameter to the call to `%parts`:

```
In [1]: %alias parts echo first %s second %s
In [2]: parts A B
first A second B
In [3]: parts A
ERROR: Alias <parts> requires 2 arguments, 1 given.
```

If called with no parameters, `%alias` prints the table of currently defined aliases.

The `%rehashx` magic allows you to load your entire `$PATH` as ipython aliases. See its docstring for further details.

Recursive reload

The `IPython.lib.deepreload` module allows you to recursively reload a module: changes made to any of its dependencies will be reloaded without having to exit. To start using it, do:

```
from IPython.lib.deepreload import reload as dreload
```

Verbose and colored exception traceback printouts

IPython provides the option to see very detailed exception tracebacks, which can be especially useful when debugging large programs. You can run any Python file with the `%run` function to benefit from these detailed tracebacks. Furthermore, both normal and verbose tracebacks can be colored (if your terminal supports it) which makes them much easier to parse visually.

See the magic `%xmode` and `%colors` functions for details.

These features are basically a terminal version of Ka-Ping Yee's `cgitb` module, now part of the standard Python library.

Input caching system

IPython offers numbered prompts (In/Out) with input and output caching (also referred to as „input history“). All input is saved and can be retrieved as variables (besides the usual arrow key recall), in addition to the `%rep` magic command that brings a history entry up for editing on the next command line.

The following variables always exist:

- `_i`, `_ii`, `_iii`: store previous, next previous and next-next previous inputs.
- `In`, `_ih`: a list of all inputs; `_ih[n]` is the input from line `n`. If you overwrite `In` with a variable of your own, you can remake the assignment to the internal list with a simple `In=_ih`.

Additionally, global variables named `_i<n>` are dynamically created (`<n>` being the prompt counter), so `_i<n> == _ih[<n>] == In[<n>]`.

For example, what you typed at prompt 14 is available as `_i14`, `_ih[14]` and `In[14]`.

This allows you to easily cut and paste multi line interactive prompts by printing them out: they print like a clean string, without prompt characters. You can also manipulate them like regular variables (they are strings), modify or exec them.

You can also re-execute multiple lines of input easily by using the magic `%rerun` or `%macro` functions. The macro system also allows you to re-execute previous lines which include magic function calls (which require special processing). Type `%macro?` for more details on the macro system.

A history function `%history` allows you to see any part of your input history by printing a range of the `_i` variables.

You can also search („grep“) through your history by typing `%hist -g somestring`. This is handy for searching for URLs, IP addresses, etc. You can bring history entries listed by „`%hist -g`“ up for editing with the `%recall` command, or run them immediately with `%rerun`.

Output caching system

For output that is returned from actions, a system similar to the input cache exists but using `_` instead of `_i`. Only actions that produce a result (NOT assignments, for example) are cached. If you are familiar with Mathematica, IPython's `_` variables behave exactly like Mathematica's `%` variables.

The following variables always exist:

- `_` (a single underscore): stores previous output, like Python's default interpreter.
- `__` (two underscores): next previous.
- `___` (three underscores): next-next previous.

Additionally, global variables named `_<n>` are dynamically created (`<n>` being the prompt counter), such that the result of output `<n>` is always available as `_<n>` (don't use the angle brackets, just the number, e.g. `_21`).

These variables are also stored in a global dictionary (not a list, since it only has entries for lines which returned a result) available under the names `_oh` and `Out` (similar to `_ih` and `In`). So the output from line 12 can be obtained as `_12`, `Out[12]` or `_oh[12]`. If you accidentally overwrite the `Out` variable you can recover it by typing `Out=_oh` at the prompt.

This system obviously can potentially put heavy memory demands on your system, since it prevents Python's garbage collector from removing any previously computed results. You can control how many results are kept in memory with the configuration option `InteractiveShell.cache_size`. If you set it to 0, output caching is disabled. You can also use the `%reset` and `%xdel` magics to clear large items from memory.

Directory history

Your history of visited directories is kept in the global list `_dh`, and the magic `%cd` command can be used to go to any entry in that list. The `%dhist` command allows you to view this history. Do `cd -<TAB>` to conveniently view the directory history.

Automatic parentheses and quotes

These features were adapted from Nathan Gray's LazyPython. They are meant to allow less typing for common situations.

Callable objects (i.e. functions, methods, etc) can be invoked like this (notice the commas between the arguments):

```
In [1]: callable_ob arg1, arg2, arg3
-----> callable_ob(arg1, arg2, arg3)
```

Примечание: This feature is disabled by default. To enable it, use the `%autocall` magic command. The commands below with special prefixes will always work, however.

You can force automatic parentheses by using `„/“` as the first character of a line. For example:

```
In [2]: /globals # becomes 'globals()'
```

Note that the `„/“` MUST be the first character on the line! This won't work:

```
In [3]: print /globals # syntax error
```

In most cases the automatic algorithm should work, so you should rarely need to explicitly invoke `/`. One notable exception is if you are trying to call a function with a list of tuples as arguments (the parenthesis will confuse IPython):

```
In [4]: zip (1,2,3),(4,5,6) # won't work
```

but this will work:

```
In [5]: /zip (1,2,3),(4,5,6)
-----> zip ((1,2,3),(4,5,6))
Out[5]: [(1, 4), (2, 5), (3, 6)]
```

IPython tells you that it has altered your command line by displaying the new command line preceded by `--->`.

You can force automatic quoting of a function's arguments by using `,` or `;` as the first character of a line. For example:

```
In [1]: ,my_function /home/me # becomes my_function("/home/me")
```

If you use `,”` the whole argument is quoted as a single string, while `,”` splits on whitespace:

```
In [2]: ,my_function a b c # becomes my_function("a", "b", "c")
```

```
In [3]: ;my_function a b c # becomes my_function("a b c")
```

Note that the `,”` or `,”` MUST be the first character on the line! This won't work:

```
In [4]: x = ,my_function /home/me # syntax error
```

4.4.3 IPython as your default Python environment

Python honors the environment variable `PYTHONSTARTUP` and will execute at startup the file referenced by this variable. If you put the following code at the end of that file, then IPython will be your working environment anytime you start Python:

```
import os, IPython
os.environ['PYTHONSTARTUP'] = '' # Prevent running this again
IPython.start_ipython()
raise SystemExit
```

The `raise SystemExit` is needed to exit Python when it finishes, otherwise you'll be back at the normal Python `>>>` prompt.

This is probably useful to developers who manage multiple Python versions and don't want to have correspondingly multiple IPython versions. Note that in this mode, there is no way to pass IPython any command-line options, as those are trapped first by Python itself.

4.4.4 Embedding IPython

You can start a regular IPython session with

```
import IPython
IPython.start_ipython(argv=[])
```

at any point in your program. This will load IPython configuration, startup files, and everything, just as if it were a normal IPython session. For information on setting configuration options when running IPython from python, see *Running IPython from Python*.

It is also possible to embed an IPython shell in a namespace in your Python code. This allows you to evaluate dynamically the state of your code, operate with your variables, analyze them, etc. For example, if you run the following code snippet:

```
import IPython
```

(continues on next page)

(продолжение с предыдущей страницы)

```
a = 42
IPython.embed()
```

and within the IPython shell, you reassign `a` to 23 to do further testing of some sort, you can then exit:

```
>>> IPython.embed()
Python 3.6.2 (default, Jul 17 2017, 16:44:45)
Type 'copyright', 'credits' or 'license' for more information
IPython 6.2.0.dev -- An enhanced Interactive Python. Type '?' for help.

In [1]: a = 23

In [2]: exit()
```

Once you exit and print `a`, the value 23 will be shown:

```
In: print(a)
23
```

It's important to note that the code run in the embedded IPython shell will *not* change the state of your code and variables, **unless** the shell is contained within the global namespace. In the above example, `a` is changed because this is true.

To further exemplify this, consider the following example:

```
import IPython
def do():
    a = 42
    print(a)
    IPython.embed()
    print(a)
```

Now if call the function and complete the state changes as we did above, the value 42 will be printed. Again, this is because it's not in the global namespace:

```
do()
```

Running a file with the above code can lead to the following session:

```
>>> do()
42
Python 3.6.2 (default, Jul 17 2017, 16:44:45)
Type 'copyright', 'credits' or 'license' for more information
IPython 6.2.0.dev -- An enhanced Interactive Python. Type '?' for help.

In [1]: a = 23

In [2]: exit()
42
```

Примечание: At present, embedding IPython cannot be done from inside IPython. Run the code samples below outside IPython.

This feature allows you to easily have a fully functional python environment for doing object introspection anywhere in your code with a simple function call. In some cases a simple print statement is enough, but if you need to do more detailed analysis of a code fragment this feature can be very valuable.

It can also be useful in scientific computing situations where it is common to need to do some automatic, computationally intensive part and then stop to look at data, plots, etc. Opening an IPython instance will give you full access to your data and functions, and you can resume program execution once you are done with the interactive part (perhaps to stop again later, as many times as needed).

The following code snippet is the bare minimum you need to include in your Python programs for this to work (detailed examples follow later):

```
from IPython import embed

embed() # this call anywhere in your program will start IPython
```

You can also embed an IPython *kernel*, for use with qtconsole, etc. via `IPython.embed_kernel()`. This should work the same way, but you can connect an external frontend (`ipython qtconsole` or `ipython console`), rather than interacting with it in the terminal.

You can run embedded instances even in code which is itself being run at the IPython interactive prompt with „`%run <filename>`“. Since it's easy to get lost as to where you are (in your top-level IPython or in your embedded one), it's a good idea in such cases to set the in/out prompts to something different for the embedded instances. The code examples below illustrate this.

You can also have multiple IPython instances in your program and open them separately, for example with different options for data presentation. If you close and open the same instance multiple times, its prompt counters simply continue from each execution to the next.

Please look at the docstrings in the `embed` module for more details on the use of this system.

The following sample file illustrating how to use the embedding functionality is provided in the examples directory as `embed_class_long.py`. It should be fairly self-explanatory:

```
#!/usr/bin/env python
"""An example of how to embed an IPython shell into a running program.

Please see the documentation in the IPython.Shell module for more details.

The accompanying file embed_class_short.py has quick code fragments for
embedding which you can cut and paste in your code once you understand how
things work.

The code in this file is deliberately extra-verbose, meant for learning."""

# The basics to get you going:

# IPython injects get_ipython into builtins, so you can know if you have nested
# copies running.

# Try running this code both at the command line and from inside IPython (with
# %run example-embed.py)

from IPython.terminal.prompts import Prompts, Token

class CustomPrompt(Prompts):
```

(continues on next page)

(продолжение с предыдущей страницы)

```

def in_prompt_tokens(self, cli=None):

    return [
        (Token.Prompt, 'In <'),
        (Token.PromptNum, str(self.shell.execution_count)),
        (Token.Prompt, '>: '),
    ]

def out_prompt_tokens(self):
    return [
        (Token.OutPrompt, 'Out<'),
        (Token.OutPromptNum, str(self.shell.execution_count)),
        (Token.OutPrompt, '>: '),
    ]

from traitlets.config.loader import Config
try:
    get_ipython
except NameError:
    nested = 0
    cfg = Config()
    cfg.TerminalInteractiveShell.prompts_class=CustomPrompt
else:
    print("Running nested copies of IPython.")
    print("The prompts for the nested copy have been modified")
    cfg = Config()
    nested = 1

# First import the embeddable shell class
from IPython.terminal.embed import InteractiveShellEmbed

# Now create an instance of the embeddable shell. The first argument is a
# string with options exactly as you would type them if you were starting
# IPython at the system command line. Any parameters you want to define for
# configuration can thus be specified here.
ipshell = InteractiveShellEmbed(config=cfg,
                                banner1 = 'Dropping into IPython',
                                exit_msg = 'Leaving Interpreter, back to program.')

# Make a second instance, you can have as many as you want.
ipshell2 = InteractiveShellEmbed(config=cfg,
                                banner1 = 'Second IPython instance.')

print('\nHello. This is printed from the main controller program.\n')

# You can then call ipshell() anywhere you need it (with an optional
# message):
ipshell('***Called from top level. '
        'Hit Ctrl-D to exit interpreter and continue program.\n'
        'Note that if you use %kill_embedded, you can fully deactivate\n')

```

(continues on next page)

(продолжение с предыдущей страницы)

```

        'This embedded instance so it will never turn on again')

print('\nBack in caller program, moving along...\n')

#-----
# More details:

# InteractiveShellEmbed instances don't print the standard system banner and
# messages. The IPython banner (which actually may contain initialization
# messages) is available as get_ipython().banner in case you want it.

# InteractiveShellEmbed instances print the following information every time they
# start:

# - A global startup banner.

# - A call-specific header string, which you can use to indicate where in the
# execution flow the shell is starting.

# They also print an exit message every time they exit.

# Both the startup banner and the exit message default to None, and can be set
# either at the instance constructor or at any other time with the
# by setting the banner and exit_msg attributes.

# The shell instance can be also put in 'dummy' mode globally or on a per-call
# basis. This gives you fine control for debugging without having to change
# code all over the place.

# The code below illustrates all this.

# This is how the global banner and exit_msg can be reset at any point
ipshell.banner2 = 'Entering interpreter - New Banner'
ipshell.exit_msg = 'Leaving interpreter - New exit_msg'

def foo(m):
    s = 'spam'
    ipshell('***In foo(). Try %whos, or print s or m:')
    print('foo says m = ',m)

def bar(n):
    s = 'eggs'
    ipshell('***In bar(). Try %whos, or print s or n:')
    print('bar says n = ',n)

# Some calls to the above functions which will trigger IPython:
print('Main program calling foo("eggs")\n')
foo('eggs')

# The shell can be put in 'dummy' mode where calls to it silently return. This
# allows you, for example, to globally turn off debugging for a program with a

```

(continues on next page)

(продолжение с предыдущей страницы)

```

# single call.
ipshell.dummy_mode = True
print('\nTrying to call IPython which is now "dummy":')
ipshell()
print('Nothing happened...')
# The global 'dummy' mode can still be overridden for a single call
print('\nOverriding dummy mode manually:')
ipshell(dummy=False)

# Reactivate the IPython shell
ipshell.dummy_mode = False

print('You can even have multiple embedded instances:')
ipshell2()

print('\nMain program calling bar("spam")\n')
bar('spam')

print('Main program finished. Bye!')

```

Once you understand how the system functions, you can use the following code fragments in your programs which are ready for cut and paste:

```

"""Quick code snippets for embedding IPython into other programs.
See embed_class_long.py for full details, this file has the bare minimum code for
cut and paste use once you understand how to use the system."""

#-----
# This code loads IPython but modifies a few things if it detects it's running
# embedded in another IPython session (helps avoid confusion)

try:
    get_ipython
except NameError:
    banner=exit_msg=''
else:
    banner = '*** Nested interpreter ***'
    exit_msg = '*** Back in main IPython ***'

# First import the embed function
from IPython.terminal.embed import InteractiveShellEmbed
# Now create the IPython shell instance. Put ipshell() anywhere in your code
# where you want it to open.
ipshell = InteractiveShellEmbed(banner1=banner, exit_msg=exit_msg)

#-----
# This code will load an embeddable IPython shell always with no changes for
# nested embededings.

from IPython import embed
# Now embed() will open IPython anywhere in the code.

```

(continues on next page)

(продолжение с предыдущей страницы)

```

#-----
# This code loads an embeddable shell only if NOT running inside
# IPython. Inside IPython, the embeddable shell variable ipshell is just a
# dummy function.

try:
    get_ipython
except NameError:
    from IPython.terminal.embed import InteractiveShellEmbed
    ipshell = InteractiveShellEmbed()
    # Now ipshell() will open IPython anywhere in the code
else:
    # Define a dummy ipshell() so the same code doesn't crash inside an
    # interactive IPython
    def ipshell(): pass

```

4.4.5 Using the Python debugger (pdb)

Running entire programs via pdb

pdb, the Python debugger, is a powerful interactive debugger which allows you to step through code, set breakpoints, watch variables, etc. IPython makes it very easy to start any script under the control of pdb, regardless of whether you have wrapped it into a „main()“ function or not. For this, simply type `%run -d myscript` at an IPython prompt. See the `%run` command's documentation for more details, including how to control where pdb will stop execution first.

For more information on the use of the pdb debugger, see [Debugger Commands](#) in the Python documentation.

IPython extends the debugger with a few useful additions, like coloring of tracebacks. The debugger will adopt the color scheme selected for IPython.

The `where` command has also been extended to take as argument the number of context line to show. This allows to a many line of context on shallow stack trace:

```

In [5]: def foo(x):
...:     1
...:     2
...:     3
...:     return 1/x+foo(x-1)
...:     5
...:     6
...:     7
...:

In[6]: foo(1)
# ...
ipdb> where 8
<ipython-input-6-9e45007b2b59>(1)<module>
----> 1 foo(1)

<ipython-input-5-7baadc3d1465>(5)foo()

```

(continues on next page)

(продолжение с предыдущей страницы)

```

1 def foo(x):
2     1
3     2
4     3
----> 5     return 1/x+foo(x-1)
6     5
7     6
8     7

> <ipython-input-5-7baadc3d1465>(5)foo()
1 def foo(x):
2     1
3     2
4     3
----> 5     return 1/x+foo(x-1)
6     5
7     6
8     7

```

And less context on shallower Stack Trace:

```

ipdb> where 1
<ipython-input-13-afa180a57233>(1)<module>
----> 1 foo(7)

<ipython-input-5-7baadc3d1465>(5)foo()
----> 5     return 1/x+foo(x-1)

<ipython-input-5-7baadc3d1465>(5)foo()
----> 5     return 1/x+foo(x-1)

<ipython-input-5-7baadc3d1465>(5)foo()
----> 5     return 1/x+foo(x-1)

<ipython-input-5-7baadc3d1465>(5)foo()
----> 5     return 1/x+foo(x-1)

```

Post-mortem debugging

Going into a debugger when an exception occurs can be extremely useful in order to find the origin of subtle bugs, because pdb opens up at the point in your code which triggered the exception, and while your program is at this point „dead“, all the data is still available and you can walk up and down the stack frame and understand the origin of the problem.

You can use the `%debug` magic after an exception has occurred to start post-mortem debugging. IPython can also call debugger every time your code triggers an uncaught exception. This feature can be toggled with the `%pdb` magic command, or you can start IPython with the `--pdb` option.

For a post-mortem debugger in your programs outside IPython, put the following lines toward the top of your „main“ routine:

```
import sys
from IPython.core import ultratb
sys.excepthook = ultratb.FormattedTB(mode='Verbose',
color_scheme='Linux', call_pdb=1)
```

The mode keyword can be either „Verbose“ or „Plain“, giving either very detailed or normal tracebacks respectively. The color_scheme keyword can be one of „NoColor“, „Linux“ (default) or „LightBG“. These are the same options which can be set in IPython with `--colors` and `--xmode`.

This will give any of your programs detailed, colored tracebacks with automatic invocation of pdb.

4.4.6 Pasting of code starting with Python or IPython prompts

IPython is smart enough to filter out input prompts, be they plain Python ones (`>>>` and `...`) or IPython ones (`In [N]:` and `...:`). You can therefore copy and paste from existing interactive sessions without worry.

The following is a „screenshot“ of how things work, copying an example from the standard Python tutorial:

```
In [1]: >>> # Fibonacci series:

In [2]: ... # the sum of two elements defines the next

In [3]: ... a, b = 0, 1

In [4]: >>> while b < 10:
...:     ...     print(b)
...:     ...     a, b = b, a+b
...:
1
1
2
3
5
8
```

And pasting from IPython sessions works equally well:

```
In [1]: In [5]: def f(x):
...:     ...:     "A simple function"
...:     ...:     return x**2
...:     ...:

In [2]: f(3)
Out[2]: 9
```


4.4.7 GUI event loop support

IPython has excellent support for working interactively with Graphical User Interface (GUI) toolkits, such as wxPython, PyQt/PySide, PyGTK and Tk. This is implemented by running the toolkit's event loop while IPython is waiting for input.

For users, enabling GUI event loop integration is simple. You simply use the `%gui` magic as follows:

```
%gui [GUINAME]
```

With no arguments, `%gui` removes all GUI support. Valid `GUINAME` arguments include `wx`, `qt`, `qt5`, `qt6`, `gtk`, `gtk3`, `gtk4`, and `tk`.

Thus, to use wxPython interactively and create a running `wx.App` object, do:

```
%gui wx
```

You can also start IPython with an event loop set up using the `--gui` flag:

```
$ ipython --gui=qt
```

For information on IPython's `matplotlib` integration (and the `matplotlib` mode) see [this section](#).

For developers that want to integrate additional event loops with IPython, see [Integrating with GUI event loops](#).

When running inside IPython with an integrated event loop, a GUI application should *not* start its own event loop. This means that applications that are meant to be used both in IPython and as standalone apps need to have special code to detect how the application is being run. We highly recommend using IPython's support for this. Since the details vary slightly between toolkits, we point you to the various examples in our source directory `examples/IPython Kernel/gui/` that demonstrate these capabilities.

PyQt and PySide

When you use `--gui=qt` or `--matplotlib=qt`, IPython can work with either PyQt or PySide. `qt` implies «use the latest version available», and it favors PyQt over PySide. To request a specific version, use `qt5` or `qt6`. Note that Qt4 is not supported with the `--gui` switch (and has not been for some time now).

If specified, IPython will respect the environment variable `QT_API` used by ETS. ETS 4.0 also works with both PyQt4 and PySide, but it requires PyQt4 to use its v2 API. So if `QT_API=pyside` PySide will be used, and if `QT_API=pyqt` then PyQt4 will be used *with the v2 API* for `QString` and `QVariant`, so ETS codes like `MayaVi` will also work with IPython.

If you launch IPython in `matplotlib` mode with `ipython --matplotlib=qt`, then IPython will ask `matplotlib` which Qt library to use (only if `QT_API` is *not set*), via the „backend.qt4“ rcParam. If `matplotlib` is version 1.0.1 or older, then IPython will always use PyQt4 without setting the v2 APIs, since neither v2 PyQt nor PySide work.

Предупреждение: Note that this means for ETS 4 to work with PyQt4, `QT_API` *must* be set to work with IPython's qt integration, because otherwise PyQt4 will be loaded in an incompatible mode.

It also means that you must *not* have `QT_API` set if you want to use `--gui=qt` with code that requires PyQt4 API v1.

4.4.8 Plotting with matplotlib

`matplotlib` provides high quality 2D and 3D plotting for Python. `matplotlib` can produce plots on screen using a variety of GUI toolkits, including Tk, PyGTK, PyQt4 and wxPython. It also provides a number of commands useful for scientific computing, all with a syntax compatible with that of the popular Matlab program.

To start IPython with `matplotlib` support, use the `--matplotlib` switch. If IPython is already running, you can run the `%matplotlib` magic. If no arguments are given, IPython will automatically detect your choice of `matplotlib` backend. You can also request a specific backend with `%matplotlib backend`, where `backend` must be one of: „tk“, „qt“, „wx“, „gtk“, „osx“. In the web notebook and Qt console, „inline“ is also a valid backend value, which produces static figures inlined inside the application window instead of `matplotlib`'s interactive figures that live in separate windows.

4.4.9 Interactive demos with IPython

IPython ships with a basic system for running scripts interactively in sections, useful when presenting code to audiences. A few tags embedded in comments (so that the script remains valid Python code) divide a file into separate blocks, and the demo can be run one block at a time, with IPython printing (with syntax highlighting) the block before executing it, and returning to the interactive prompt after each block. The interactive namespace is updated after each block is run with the contents of the demo's namespace.

This allows you to show a piece of code, run it and then execute interactively commands based on the variables just created. Once you want to continue, you simply execute the next block of the demo. The following listing shows the markup necessary for dividing a script into sections for execution as a demo:

```
# -*- coding: utf-8 -*-
"""A simple interactive demo to illustrate the use of IPython's Demo class.

Any python script can be run as a demo, but that does little more than showing
it on-screen, syntax-highlighted in one shot. If you add a little simple
markup, you can stop at specified intervals and return to the ipython prompt,
resuming execution later.

This is a unicode test, äö
"""

print('Hello, welcome to an interactive IPython demo.')
print('Executing this block should require confirmation before proceeding,')
print('unless auto_all has been set to true in the demo object')

# The mark below defines a block boundary, which is a point where IPython will
# stop execution and return to the interactive prompt.
# <demo> --- stop ---

x = 1
y = 2

# <demo> --- stop ---

# the mark below makes this block as silent
# <demo> silent
```

(continues on next page)

(продолжение с предыдущей страницы)

```

print('This is a silent block, which gets executed but not printed.')

# <demo> --- stop ---
# <demo> auto
print('This is an automatic block.')
print('It is executed without asking for confirmation, but printed.')
z = x+y

print('z=',x)

# <demo> --- stop ---
# This is just another normal block.
print('z is now:', z)

print('bye!')
```

In order to run a file as a demo, you must first make a Demo object out of it. If the file is named `myscript.py`, the following code will make a demo:

```

from IPython.lib.demo import Demo

mydemo = Demo('myscript.py')
```

This creates the `mydemo` object, whose blocks you run one at a time by simply calling the object with no arguments. Then call it to run each step of the demo:

```
mydemo()
```

Demo objects can be restarted, you can move forward or back skipping blocks, re-execute the last block, etc. See the `IPython.lib.demo` module and the `Demo` class for details.

Limitations: These demos are limited to fairly simple uses. In particular, you cannot break up sections within indented code (loops, if statements, function definitions, etc.) Supporting something like this would basically require tracking the internal execution state of the Python interpreter, so only top-level divisions are allowed. If you want to be able to open an IPython instance at an arbitrary point in a program, you can use IPython's *embedding facilities*.

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

Примечание: This page has been kept for historical reason. You most likely want to use [Xonsh](#) instead of this.

4.5 IPython as a system shell

4.5.1 Overview

It is possible to adapt IPython for system shell usage. In the past, IPython shipped a special „sh“ profile for this purpose, but it had been quarantined since 0.11 release, and in 1.0 it was removed altogether. Nevertheless, much of this section relies on machinery which does not require a custom profile.

You can set up your own „sh“ *profile* to be different from the default profile such that:

- Prompt shows the current directory (see *Prompt customization*)
- Make system commands directly available (in alias table) by running the `%rehashx` magic. If you install new programs along your `PATH`, you might want to run `%rehashx` to update the alias table
- turn `%autocall` to full mode

4.5.2 Environment variables

Rather than manipulating `os.environ` directly, you may like to use the magic `%env` command. With no arguments, this displays all environment variables and values. To get the value of a specific variable, use `%env var`. To set the value of a specific variable, use `%env foo bar`, `%env foo=bar`. By default values are considered to be strings so quoting them is unnecessary. However, Python variables are expanded as usual in the magic command, so `%env foo=$bar` means «set the environment variable `foo` to the value of the Python variable `bar`».

4.5.3 Aliases

Once you run `%rehashx`, all of your `$PATH` has been loaded as IPython aliases, so you should be able to type any normal system command and have it executed. See `%alias?` and `%unalias?` for details on the alias facilities. See also `%rehashx?` for details on the mechanism used to load `$PATH`.

Предупреждение: See info at the top of the page. You most likely want to use `Xonsh` instead of this.

4.5.4 Directory management

Since each command passed by IPython to the underlying system is executed in a subshell which exits immediately, you can NOT use `!cd` to navigate the filesystem.

IPython provides its own builtin `%cd` magic command to move in the filesystem (the `%` is not required with automagic on). It also maintains a list of visited directories (use `%dhist` to see it) and allows direct switching to any of them. Type `cd?` for more details.

`%pushd`, `%popd` and `%dirs` are provided for directory stack handling.

4.5.5 Prompt customization

See *Custom Prompts*.

4.5.6 String lists

String lists (IPython.utils.text.SList) are handy way to process output from system commands. They are produced by `var = !cmd` syntax.

First, we acquire the output of „ls -l“:

```
[Q:doc/examples]|2> lines = !ls -l
==
['total 23',
 '-rw-rw-rw- 1 ville None 1163 Sep 30 2006 example-demo.py',
 '-rw-rw-rw- 1 ville None 1927 Sep 30 2006 example-embed-short.py',
 '-rwxrwxrwx 1 ville None 4606 Sep 1 17:15 example-embed.py',
 '-rwxrwxrwx 1 ville None 1017 Sep 30 2006 example-gnuplot.py',
 '-rwxrwxrwx 1 ville None 339 Jun 11 18:01 extension.py',
 '-rwxrwxrwx 1 ville None 113 Dec 20 2006 seteditor.py',
 '-rwxrwxrwx 1 ville None 245 Dec 12 2006 seteditor.pyc']
```

Now, let's take a look at the contents of „lines“ (the first number is the list element number):

```
[Q:doc/examples]|3> lines
<3> SList (.p, .n, .l, .s, .grep(), .fields() available). Value:

0: total 23
1: -rw-rw-rw- 1 ville None 1163 Sep 30 2006 example-demo.py
2: -rw-rw-rw- 1 ville None 1927 Sep 30 2006 example-embed-short.py
3: -rwxrwxrwx 1 ville None 4606 Sep 1 17:15 example-embed.py
4: -rwxrwxrwx 1 ville None 1017 Sep 30 2006 example-gnuplot.py
5: -rwxrwxrwx 1 ville None 339 Jun 11 18:01 extension.py
6: -rwxrwxrwx 1 ville None 113 Dec 20 2006 seteditor.py
7: -rwxrwxrwx 1 ville None 245 Dec 12 2006 seteditor.pyc
```

Now, let's filter out the „embed“ lines:

```
[Q:doc/examples]|4> l2 = lines.grep('embed',prune=1)
[Q:doc/examples]|5> l2
<5> SList (.p, .n, .l, .s, .grep(), .fields() available). Value:

0: total 23
1: -rw-rw-rw- 1 ville None 1163 Sep 30 2006 example-demo.py
2: -rwxrwxrwx 1 ville None 1017 Sep 30 2006 example-gnuplot.py
3: -rwxrwxrwx 1 ville None 339 Jun 11 18:01 extension.py
4: -rwxrwxrwx 1 ville None 113 Dec 20 2006 seteditor.py
5: -rwxrwxrwx 1 ville None 245 Dec 12 2006 seteditor.pyc
```

Now, we want strings having just file names and permissions:

```
[Q:doc/examples]|6> l2.fields(8,0)
<6> SList (.p, .n, .l, .s, .grep(), .fields() available). Value:
```

(continues on next page)

(продолжение с предыдущей страницы)

```

0: total
1: example-demo.py -rw-rw-rw-
2: example-gnuplot.py -rwxrwxrwx
3: extension.py -rwxrwxrwx
4: seteditor.py -rwxrwxrwx
5: seteditor.pyc -rwxrwxrwx

```

Note how the line with „total“ does not raise IndexError.

If you want to split these (yielding lists), call `fields()` without arguments:

```

[Q:doc/examples] |7> _.fields()
<7>
[['total'],
 ['example-demo.py', '-rw-rw-rw-'],
 ['example-gnuplot.py', '-rwxrwxrwx'],
 ['extension.py', '-rwxrwxrwx'],
 ['seteditor.py', '-rwxrwxrwx'],
 ['seteditor.pyc', '-rwxrwxrwx']]

```

If you want to pass these separated with spaces to a command (typical for lists of files), use the `.s` property:

```

[Q:doc/examples] |13> files = l2.fields(8).s
[Q:doc/examples] |14> files
<14> 'example-demo.py example-gnuplot.py extension.py seteditor.py
↪seteditor.pyc'
[Q:doc/examples] |15> ls $files
example-demo.py example-gnuplot.py extension.py seteditor.py seteditor.pyc

```

SLists are inherited from normal Python lists, so every list method is available:

```

[Q:doc/examples] |21> lines.append('hey')

```

Real world example: remove all files outside version control

First, capture output of «hg status»:

```

[Q:/ipython] |28> out = !hg status
==
['M IPython\\extensions\\ipy_kitcfg.py',
 'M IPython\\extensions\\ipy_rehashdir.py',
 ...
 '? build\\lib\\IPython\\Debugger.py',
 '? build\\lib\\IPython\\extensions\\InterpreterExec.py',
 '? build\\lib\\IPython\\extensions\\InterpreterPasteInput.py',
 ...

```

(lines starting with ? are not under version control).

```

[Q:/ipython] |35> junk = out.grep(r'^\?').fields(1)
[Q:/ipython] |36> junk

```

(continues on next page)

(продолжение с предыдущей страницы)

```

<36> SList (.p, .n, .l, .s, .grep(), .fields() availab
...
10: build\bdist.win32\winexe\temp\_ctypes.py
11: build\bdist.win32\winexe\temp\_hashlib.py
12: build\bdist.win32\winexe\temp\_socket.py

```

Now we can just remove these files by doing „rm \$junk.s“.

The .n, .s, .p properties

Properties of `SList` wrapper provide a convenient ways to use contained text in different formats:

- `.n` returns (original) string with lines separated by a newline
- `.s` returns string with lines separated by single space (for convenient passing to system commands)
- `.p` returns list of «path» objects from detected file names

Ошибка: You went too far scroll back up. You most likely want to use `Xonsh` instead of this.

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

4.6 Asynchronous in REPL: Autoawait

Примечание: This feature is experimental and behavior can change between python and IPython version without prior deprecation.

Starting with IPython 7.0, and when using Python 3.6 and above, IPython offer the ability to run asynchronous code from the REPL. Constructs which are `SyntaxError`s in the Python REPL can be used seamlessly in IPython.

The examples given here are for terminal IPython, running async code in a notebook interface or any other frontend using the Jupyter protocol needs IPykernel version 5.0 or above. The details of how async code runs in IPykernel will differ between IPython, IPykernel and their versions.

When a supported library is used, IPython will automatically allow Futures and Coroutines in the REPL to be `await` ed. This will happen if an `await` (or any other async constructs like `async-with`, `async-for`) is used at top level scope, or if any structure valid only in `async def` function context are present. For example, the following being a syntax error in the Python REPL:

```
Python 3.6.0
[GCC 4.2.1]
Type "help", "copyright", "credits" or "license" for more information.
>>> import aiohttp
>>> session = aiohttp.ClientSession()
>>> result = session.get('https://api.github.com')
>>> response = await result
      File "<stdin>", line 1
            response = await result
                          ^
SyntaxError: invalid syntax
```

Should behave as expected in the IPython REPL:

```
Python 3.6.0
Type 'copyright', 'credits' or 'license' for more information
IPython 7.0.0 -- An enhanced Interactive Python. Type '?' for help.

In [1]: import aiohttp
...: session = aiohttp.ClientSession()
...: result = session.get('https://api.github.com')

In [2]: response = await result
<pause for a few 100s ms>

In [3]: await response.json()
Out[3]:
{'authorizations_url': 'https://api.github.com/authorizations',
 'code_search_url': 'https://api.github.com/search/code?q={query}...',
 ...
}
```

You can use the `c.InteractiveShell.autoawait` configuration option and set it to `False` to deactivate automatic wrapping of asynchronous code. You can also use the `%autoawait` magic to toggle the behavior at runtime:

```
In [1]: %autoawait False

In [2]: %autoawait
IPython autoawait is `Off`, and set to use `asyncio`
```

By default IPython will assume integration with Python's provided `asyncio`, but integration with other libraries is provided. In particular we provide experimental integration with the `curio` and `trio` library.

You can switch the current integration by using the `c.InteractiveShell.loop_runner` option or the `autoawait <name integration>` magic.

For example:

```
In [1]: %autoawait trio

In [2]: import trio

In [3]: async def child(i):
```

(continues on next page)

(продолжение с предыдущей страницы)

```

...:     print("  child %s goes to sleep"%i)
...:     await trio.sleep(2)
...:     print("  child %s wakes up"%i)

In [4]: print('parent start')
...:     async with trio.open_nursery() as n:
...:         for i in range(5):
...:             n.spawn(child, i)
...:     print('parent end')
parent start
  child 2 goes to sleep
  child 0 goes to sleep
  child 3 goes to sleep
  child 1 goes to sleep
  child 4 goes to sleep
<about 2 seconds pause>
  child 2 wakes up
  child 1 wakes up
  child 0 wakes up
  child 3 wakes up
  child 4 wakes up
parent end

```

In the above example, `async with` at top level scope is a syntax error in Python.

Using this mode can have unexpected consequences if used in interaction with other features of IPython and various registered extensions. In particular if you are a direct or indirect user of the AST transformers, these may not apply to your code.

When using command line IPython, the default loop (or runner) does not process in the background, so top level asynchronous code must finish for the REPL to allow you to enter more code. As with usual Python semantics, the awaitables are started only when awaited for the first time. That is to say, in first example, no network request is done between `In[1]` and `In[2]`.

4.6.1 Effects on `IPython.embed()`

IPython core being asynchronous, the use of `IPython.embed()` will now require a loop to run. By default IPython will use a fake coroutine runner which should allow `IPython.embed()` to be nested. Though this will prevent usage of the `%autoawait` feature when using IPython embed.

You can set a coroutine runner explicitly for `embed()` if you want to run asynchronous code, though the exact behavior is undefined.

4.6.2 Effects on Magics

A couple of magics (`%timeit`, `%timeit`, `%%time`, `%%prun`) have not yet been updated to work with asynchronous code and will raise syntax errors when trying to use top-level `await`. We welcome any contribution to help fix those, and extra cases we haven't caught yet. We hope for better support in Core Python for top-level Async code.

4.6.3 Internals

As running asynchronous code is not supported in interactive REPL (as of Python 3.7) we have to rely to a number of complex workarounds and heuristics to allow this to happen. It is interesting to understand how this works in order to comprehend potential bugs, or provide a custom runner.

Among the many approaches that are at our disposition, we find only one that suited our need. Under the hood we use the code object from a `async-def` function and run it in global namespace after modifying it to not create a new `locals()` scope:

```
async def inner_async():
    locals().update(**global_namespace)
    #
    # here is user code
    #
    return last_user_statement
codeobj = modify(inner_async.__code__)
coroutine = eval(codeobj, user_ns)
display(loop_runner(coroutine))
```

The first thing you'll notice is that unlike classical `exec`, there is only one namespace. Second, user code runs in a function scope, and not a module scope.

On top of the above there are significant modifications to the AST of `function`, and `loop_runner` can be arbitrary complex. So there is a significant overhead to this kind of code.

By default the generated coroutine function will be consumed by Asyncio's `loop_runner = asyncio.get_event_loop().run_until_complete()` method if `async` mode is deemed necessary, otherwise the coroutine will just be exhausted in a simple runner. It is possible, though, to change the default runner.

A loop runner is a *synchronous* function responsible for running a coroutine object.

The runner is responsible for ensuring that `coroutine` runs to completion, and it should return the result of executing the coroutine. Let's write a runner for `trio` that prints a message when used as an exercise, `trio` is special as it usually prefers to run a function object and make a coroutine by itself, we can get around this limitation by wrapping it in an `async-def` without parameters and passing this value to `trio`:

```
In [1]: import trio
...: from types import CoroutineType
...:
...: def trio_runner(coro:CoroutineType):
...:     print('running asynchronous code')
...:     async def corowrap(coro):
...:         return await coro
...:     return trio.run(corowrap, coro)
```

We can set it up by passing it to `%autoawait`:

```
In [2]: %autoawait trio_runner

In [3]: async def async_hello(name):
...:     await trio.sleep(1)
...:     print(f'Hello {name} world !')
...:     await trio.sleep(1)

In [4]: await async_hello('async')
running asynchronous code
Hello async world !
```

Asynchronous programming in python (and in particular in the REPL) is still a relatively young subject. We expect some code to not behave as you expect, so feel free to contribute improvements to this codebase and give us feedback.

We invite you to thoroughly test this feature and report any unexpected behavior as well as propose any improvement.

4.6.4 Using Autoawait in a notebook (IPykernel)

Update ipykernel to version 5.0 or greater:

```
pip install ipykernel ipython --upgrade
# or
conda install ipykernel ipython --upgrade
```

This should automatically enable `%autoawait` integration. Unlike terminal IPython, all code runs on `asyncio` eventloop, so creating a loop by hand will not work, including with magics like `%run` or other frameworks that create the eventloop themselves. In cases like these you can try to use projects like `nest_asyncio` and follow [this discussion](#)

4.6.5 Difference between terminal IPython and IPykernel

The exact asynchronous code running behavior varies between Terminal IPython and IPykernel. The root cause of this behavior is due to IPykernel having a *persistent* `asyncio` loop running, while Terminal IPython starts and stops a loop for each code block. This can lead to surprising behavior in some cases if you are used to manipulating `asyncio` loop yourself, see for example [#11303](#) for a longer discussion but here are some of the astonishing cases.

This behavior is an implementation detail, and should not be relied upon. It can change without warnings in future versions of IPython.

In terminal IPython a loop is started for each code blocks only if there is top level `async` code:

```
$ ipython
In [1]: import asyncio
...: asyncio.get_event_loop()
Out[1]: <_UnixSelectorEventLoop running=False closed=False debug=False>

In [2]:

In [2]: import asyncio
...: await asyncio.sleep(0)
```

(continues on next page)

(продолжение с предыдущей страницы)

```
...: asyncio.get_event_loop()
Out[2]: <_UnixSelectorEventLoop running=True closed=False debug=False>
```

See that `running` is `True` only in the case were we `await sleep()`

In a Notebook, with ipykernel the `asyncio` eventloop is always running:

```
$ jupyter notebook
In [1]: import asyncio
...: loop1 = asyncio.get_event_loop()
...: loop1
Out[1]: <_UnixSelectorEventLoop running=True closed=False debug=False>

In [2]: loop2 = asyncio.get_event_loop()
...: loop2
Out[2]: <_UnixSelectorEventLoop running=True closed=False debug=False>

In [3]: loop1 is loop2
Out[3]: True
```

In Terminal IPython background tasks are only processed while the foreground task is running, if and only if the foreground task is `async`:

```
$ ipython
In [1]: import asyncio
...:
...: async def repeat(msg, n):
...:     for i in range(n):
...:         print(f"{msg} {i}")
...:         await asyncio.sleep(1)
...:     return f"{msg} done"
...:
...: asyncio.ensure_future(repeat("background", 10))
Out[1]: <Task pending coro=<repeat() running at <ipython-input-1-02d0ef250fe7>:3>>

In [2]: await asyncio.sleep(3)
background 0
background 1
background 2
background 3

In [3]: import time
...: time.sleep(5)

In [4]: await asyncio.sleep(3)
background 4
background 5
background 6g
```

In a Notebook, QtConsole, or any other frontend using IPykernel, background tasks should behave as expected.

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

4.7 IPython Tips & Tricks

The [IPython cookbook](#) details more things you can do with IPython.

4.7.1 Embed IPython in your programs

A few lines of code are enough to load a complete IPython inside your own programs, giving you the ability to work with your data interactively after automatic processing has been completed. See [the embedding section](#).

4.7.2 Run doctests

Run your doctests from within IPython for development and debugging. The special `%doctest_mode` command toggles a mode where the prompt, output and exceptions display matches as closely as possible that of the default Python interpreter. In addition, this mode allows you to directly paste in code that contains leading „>>>“ prompts, even if they have extra leading whitespace (as is common in doctest files). This combined with the `%hist -t` call to see your translated history allows for an easy doctest workflow, where you can go from doctest to interactive execution to pasting into valid Python code as needed.

4.7.3 Use IPython to present interactive demos

Use the `IPython.lib.demo.Demo` class to load any Python script as an interactive demo. With a minimal amount of simple markup, you can control the execution of the script, stopping as needed. See [here](#) for more.

4.7.4 Suppress output

Put a „;“ at the end of a line to suppress the printing of output. This is useful when doing calculations which generate long output you are not interested in seeing. It also keeps the object out of the output cache, so if you're working with large temporary objects, they'll be released from memory sooner.

4.7.5 Lightweight „version control“

When you call `%edit` with no arguments, IPython opens an empty editor with a temporary file, and it returns the contents of your editing session as a string variable. Thanks to IPython’s output caching mechanism, this is automatically stored:

```
In [1]: %edit

IPython will make a temporary file named: /tmp/ipython_edit_yR-HCN.py

Editing... done. Executing edited code...

hello - this is a temporary file

Out[1]: "print('hello - this is a temporary file')\n"
```

Now, if you call `%edit -p`, IPython tries to open an editor with the same data as the last time you used `%edit`. So if you haven’t used `%edit` in the meantime, this same contents will reopen; however, it will be done in a new file. This means that if you make changes and you later want to find an old version, you can always retrieve it by using its output number, via „`%edit _NN`“, where `NN` is the number of the output prompt.

Continuing with the example above, this should illustrate this idea:

```
In [2]: edit -p

IPython will make a temporary file named: /tmp/ipython_edit_nA09Qk.py

Editing... done. Executing edited code...

hello - now I made some changes

Out[2]: "print('hello - now I made some changes')\n"

In [3]: edit _1

IPython will make a temporary file named: /tmp/ipython_edit_gy6-zD.py

Editing... done. Executing edited code...

hello - this is a temporary file

IPython version control at work :)

Out[3]: "print('hello - this is a temporary file')\nprint('IPython version control at
↪work :)')\n"
```

This section was written after a contribution by Alexander Belchenko on the IPython user list.

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

4.8 Python vs IPython

This document is meant to highlight the main differences between the Python language and what are the specific constructs you can do only in IPython.

Unless expressed otherwise all of the constructs you will see here will raise a `SyntaxError` if run in a pure Python shell, or if executing in a Python script.

Each of these features is described more in detail in the further parts of the documentation.

4.8.1 Quick overview:

All the following constructs are valid IPython syntax:

```
In [1]: ?
```

```
In [1]: ?object
```

```
In [1]: object?
```

```
In [1]: *pattern*?
```

```
In [1]: %shell like --syntax
```

```
In [1]: !ls
```

```
In [1]: my_files = !ls ~/
In [1]: for i, file in enumerate(my_files):
...:     raw = !echo $file
...:     !echo {file[0].upper()} $raw
```

```
In [1]: %%perl magic --function
...: @months = ("July", "August", "September");
...: print $months[0];
```

Each of these constructs is compiled by IPython into valid python code and will do most of the time what you expect it will do. Let's see each of these examples in more detail.

4.8.2 Accessing help

As IPython is mostly an interactive shell, the question mark is a simple shortcut to get help. A question mark alone will bring up the IPython help:

```
In [1]: ?

IPython -- An enhanced Interactive Python
=====

IPython offers a combination of convenient shell features, special commands
and a history mechanism for both input (command history) and output (results
caching, similar to Mathematica). It is intended to be a fully compatible
replacement for the standard Python interpreter, while offering vastly
improved functionality and flexibility.

At your system command line, type 'ipython -h' to see the command line
options available. This document only describes interactive features.

MAIN FEATURES
-----
...
```

A single question mark before or after an object available in the current namespace will show help relative to this object:

```
In [6]: object?
Docstring: The most base type
Type:      type
```

A double question mark will try to pull out more information about the object, and if possible display the python source code of this object.

```
In[1]: import collections
In[2]: collections.Counter??

Init signature: collections.Counter(*args, **kwargs)
Source:
class Counter(dict):
    '''Dict subclass for counting hashable items.  Sometimes called a bag
    or multiset.  Elements are stored as dictionary keys and their counts
    are stored as dictionary values.

    >>> c = Counter('abcdeabcedabcaba') # count elements from a string

    >>> c.most_common(3)                  # three most common elements
    [('a', 5), ('b', 4), ('c', 3)]
    >>> sorted(c)                        # list all unique elements
    ['a', 'b', 'c', 'd', 'e']
    >>> ''.join(sorted(c.elements()))     # list elements with repetitions
    'aaaaabbbbcccdde'
    ...
```

If you are looking for an object, the use of wildcards `*` in conjunction with a question mark will allow you to search the current namespace for objects with matching names:


```
In [24]: *int*?
FloatingPointError
int
print
```

4.8.3 Shell Assignment

When doing interactive computing it is a common need to access the underlying shell. This is doable through the use of the exclamation mark ! (or bang).

This allows to execute simple commands when present in beginning of the line:

```
In[1]: !pwd
/User/home/
```

Change directory:

```
In[1]: !cd /var/etc
```

Or edit file:

```
In[1]: !mvim myfile.txt
```

The line after the bang can call any program installed in the underlying shell, and support variable expansion in the form of `$variable` or `{variable}`. The later form of expansion supports arbitrary python expressions:

```
In[1]: file = 'myfile.txt'

In[2]: !mv $file {file.upper()}
```

The bang (!) can also be present on the right hand side of an assignment, just after the equal sign, or separated from it by a white space. In this case the standard output of the command after the bang will be split out into lines in a list-like object and assigned to the left hand side.

This allows you, for example, to put the list of files of the current working directory in a variable:

```
In[1]: my_files = !ls
```

You can combine the different possibilities in for loops, conditions, functions...:

```
my_files = !ls ~/
for i, file in enumerate(my_files):
    raw = !echo $backup $file
    !cp $file {file.split('.')[0] + '.bak'}
```

Magics

Magic functions (magics) are often present in the form of shell-like syntax, but they are python functions under the hood. The syntax and assignment possibilities are similar to the one with the bang (!) syntax, but with more flexibility and power. Magic functions start with a percent sign (%) or double percent signs (%%).

A magic call with a single percent sign will act only on one line:

```
In[1]: %xmode
Exception reporting mode: Verbose
```

Magics support assignment:

```
In [1]: results = %timeit -r1 -n1 -o list(range(1000))
1 loops, best of 1: 21.1 µs per loop

In [2]: results
Out[2]: <TimeitResult : 1 loops, best of 1: 21.1 µs per loop>
```

Magics with double percent signs (%%) can spread over multiple lines, but they do not support assignments:

```
In[1]: %%bash
... : echo "My shell is:" $SHELL
... : echo "My disk usage is:"
... : df -h
My shell is: /usr/local/bin/bash
My disk usage is:
Filesystem      Size  Used Avail Capacity   iused   ifree %iused  Mounted on
/dev/disk1      233Gi  216Gi   16Gi    94% 56788108 4190706   93%    /
devfs           190Ki   190Ki    0Bi   100%     656      0  100%    /dev
map -hosts       0Bi     0Bi    0Bi   100%      0      0  100%    /net
map auto_home    0Bi     0Bi    0Bi   100%      0      0  100%    /hom
```

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

4.9 Built-in magic commands

Примечание: To Jupyter users: Magics are specific to and provided by the IPython kernel. Whether Magics are available on a kernel is a decision that is made by the kernel developer on a per-kernel basis. To work properly, Magics must use a syntax element which is not valid in the underlying language. For example, the IPython kernel uses the % syntax element for Magics as % is not a valid unary operator in Python. However, % might have meaning in other languages.

Here is the help auto-generated from the docstrings of all the available Magics functions that IPython ships with.

You can create and register your own Magics with IPython. You can find many user defined Magics on [PyPI](#). Feel free to publish your own and use the `Framework :: IPython` trove classifier.

4.9.1 Line magics

%alias

Define an alias for a system command.

„%alias alias_name cmd“ defines „alias_name“ as an alias for „cmd“

Then, typing „alias_name params“ will execute the system command „cmd params“ (from your underlying operating system).

Aliases have lower precedence than magic functions and Python normal variables, so if „foo“ is both a Python variable and an alias, the alias can not be executed until „del foo“ removes the Python variable.

You can use the %l specifier in an alias definition to represent the whole line when the alias is called. For example:

```
In [2]: alias bracket echo "Input in brackets: <%l>"
In [3]: bracket hello world
Input in brackets: <hello world>
```

You can also define aliases with parameters using %s specifiers (one per parameter):

```
In [1]: alias parts echo first %s second %s
In [2]: %parts A B
first A second B
In [3]: %parts A
Incorrect number of arguments: 2 expected.
parts is an alias to: 'echo first %s second %s'
```

Note that %l and %s are mutually exclusive. You can only use one or the other in your aliases.

Aliases expand Python variables just like system calls using ! or !! do: all expressions prefixed with „\$“ get expanded. For details of the semantic rules, see PEP-215: <https://peps.python.org/pep-0215/>. This is the library used by IPython for variable expansion. If you want to access a true shell variable, an extra \$ is necessary to prevent its expansion by IPython:

```
In [6]: alias show echo
In [7]: PATH='A Python string'
In [8]: show $PATH
```

(continues on next page)

(продолжение с предыдущей страницы)

```
A Python string
In [9]: show $$PATH
/usr/local/lf9560/bin:/usr/local/intel/compiler70/ia32/bin:...
```

You can use the alias facility to access all of \$PATH. See the %rehashx function, which automatically creates aliases for the contents of your \$PATH.

If called with no parameters, %alias prints the current alias table for your system. For posix systems, the default aliases are „cat“, „cp“, „mv“, „rm“, „rmdir“, and „mkdir“, and other platform-specific aliases are added. For windows-based systems, the default aliases are „copy“, „ddir“, „echo“, „ls“, „ldir“, „mkdir“, „ren“, and „rmdir“.

You can see the definition of alias by adding a question mark in the end:

```
In [1]: cat?
Repr: <alias cat for 'cat'>
```

%alias_magic

```
%alias_magic [-l] [-c] [-p PARAMS] name target
```

Create an alias for an existing line or cell magic.

Examples

```
In [1]: %alias_magic t timeit
Created `%t` as an alias for `%timeit`.
Created `%%t` as an alias for `%%timeit`.

In [2]: %t -n1 pass
1 loops, best of 3: 954 ns per loop

In [3]: %%t -n1
...: pass
...:
1 loops, best of 3: 954 ns per loop

In [4]: %alias_magic --cell whereami pwd
UsageError: Cell magic function `%pwd` not found.
In [5]: %alias_magic --line whereami pwd
Created `%whereami` as an alias for `%pwd`.

In [6]: %whereami
Out[6]: u'/home/testuser'

In [7]: %alias_magic h history "-p -l 30" --line
Created `%h` as an alias for `%history -l 30`.
```

positional arguments:

name Name of the magic to be created. target Name of the existing line or cell magic.

options:

-l, --line Create a line magic alias.

-c, --cell Create a cell magic alias.

-p PARAMS, --params PARAMS Parameters passed to the magic function.

%autoawait

Allow to change the status of the autoawait option.

This allow you to set a specific asynchronous code runner.

If no value is passed, print the currently used asynchronous integration and whether it is activated.

It can take a number of value evaluated in the following order:

- False/false/off deactivate autoawait integration
- True/true/on activate autoawait integration using configured default loop
- asyncio/curio/trio activate autoawait integration and use integration with said library.
- **sync** turn on the pseudo-sync integration (mostly used for `IPython.embed()` which does not run IPython with a real eventloop and deactivate running asynchronous code. Turning on Asynchronous code with the pseudo sync loop is undefined behavior and may lead IPython to crash.

If the passed parameter does not match any of the above and is a python identifier, get said object from user namespace and set it as the runner, and activate autoawait.

If the object is a fully qualified object name, attempt to import it and set it as the runner, and activate autoawait.

The exact behavior of autoawait is experimental and subject to change across version of IPython and Python.

%autocall

Make functions callable without having to type parentheses.

Usage:

```
%autocall [mode]
```

The mode can be one of: 0->Off, 1->Smart, 2->Full. If not given, the value is toggled on and off (remembering the previous state).

In more detail, these values mean:

0 -> fully disabled

1 -> active, but do not apply if there are no arguments on the line.

In this mode, you get:

```
In [1]: callable
Out[1]: <built-in function callable>

In [2]: callable 'hello'
-----> callable('hello')
Out[2]: False
```

2 -> Active always. Even if no arguments are present, the callable object is called:

```
In [2]: float
-----> float()
Out[2]: 0.0
```

Note that even with autocall off, you can still use „/“ at the start of a line to treat the first argument on the command line as a function and add parentheses to it:

```
In [8]: /str 43
-----> str(43)
Out[8]: '43'
```

all-random (note for auto-testing)

%automagic

Make magic functions callable without having to type the initial %.

Without arguments toggles on/off (when off, you must call it as %automagic, of course). With arguments it sets the value, and you can use any of (case insensitive):

- on, 1, True: to activate
- off, 0, False: to deactivate.

Note that magic functions have lowest priority, so if there's a variable whose name collides with that of a magic fn, automagic won't work for that function (you get the variable instead). However, if you delete the variable (del var), the previously shadowed magic function becomes visible to automagic again.

%bookmark

Manage IPython's bookmark system.

%bookmark <name> - set bookmark to current dir %bookmark <name> <dir> - set bookmark to <dir> %bookmark -l - list all bookmarks %bookmark -d <name> - remove bookmark %bookmark -r - remove all bookmarks

You can later on access a bookmarked folder with:

```
%cd -b <name>
```

or simply „%cd <name>“ if there is no directory called <name> AND there is such a bookmark defined.

Your bookmarks persist through IPython sessions, but they are associated with each profile.

%cd

Change the current working directory.

This command automatically maintains an internal list of directories you visit during your IPython session, in the variable `_dh`. The command `%dhist` shows this history nicely formatted. You can also do `cd -<tab>` to see directory history conveniently. Usage:

- `cd 'dir'`: changes to directory „dir“.
- `cd -`: changes to the last visited directory.
- `cd -<n>`: changes to the n-th directory in the directory history.
- `cd --foo`: change to directory that matches „foo“ in history
- `cd -b <bookmark_name>`: jump to a bookmark set by %bookmark
- Hitting a tab key after `cd -b` allows you to tab-complete bookmark names.

Примечание: `cd <bookmark_name>` is enough if there is no directory <bookmark_name>, but a bookmark with the name exists.

Options:

-q Be quiet. Do not print the working directory after the `cd` command is executed. By default IPython's `cd` command does print this directory, since the default prompts do not display path information.

Примечание: Note that `!cd` doesn't work for this purpose because the shell where `!command` runs is immediately discarded after executing „command“.

Examples

```
In [10]: cd parent/child
/home/tsuser/parent/child
```

%colors

Switch color scheme for prompts, info system and exception handlers.

Currently implemented schemes: NoColor, Linux, LightBG.

Color scheme names are not case-sensitive.

Examples

To get a plain black and white terminal:

```
%colors nocolor
```

%conda

Run the conda package manager within the current kernel.

Usage:

```
%conda install [pkgs]
```

%config

configure IPython

```
%config Class[.trait=value]
```

This magic exposes most of the IPython config system. Any Configurable class should be able to be configured with the simple line:

```
%config Class.trait=value
```

Where `value` will be resolved in the user's namespace, if it is an expression or variable name.

Examples

To see what classes are available for config, pass no arguments:

```
In [1]: %config
Available objects for config:
  AliasManager
  DisplayFormatter
  HistoryManager
  IPCompleter
  LoggingMagics
  MagicsManager
  OSMagics
```

(continues on next page)

(продолжение с предыдущей страницы)

```

PrefilterManager
ScriptMagics
TerminalInteractiveShell

```

To view what is configurable on a given class, just pass the class name:

```

In [2]: %config LoggingMagics
LoggingMagics(Magics) options

LoggingMagics.quiet=<Bool>
    Suppress output of log state when logging is enabled
    Current: False

```

but the real use is in setting values:

```

In [3]: %config LoggingMagics.quiet = True

```

and these values are read from the user_ns if they are variables:

```

In [4]: feeling_quiet=False

In [5]: %config LoggingMagics.quiet = feeling_quiet

```

%debug

```

%debug [--breakpoint FILE:LINE] [statement ...]

```

Activate the interactive debugger.

This magic command support two ways of activating debugger. One is to activate debugger before executing code. This way, you can set a break point, to step through the code from the point. You can use this mode by giving statements to execute and optionally a breakpoint.

The other one is to activate debugger in post-mortem mode. You can activate this mode simply running %debug without any argument. If an exception has just occurred, this lets you inspect its stack frames interactively. Note that this will always work only on the last traceback that occurred, so you must call this quickly after an exception that you wish to inspect has fired, because if another one occurs, it clobbers the previous one.

If you want IPython to automatically do this on every exception, see the %pdb magic for more details.

Изменено в версии 7.3: When running code, user variables are no longer expanded, the magic line is always left unmodified.

positional arguments:

statement Code to run in debugger. You can omit this in cell magic mode.

options:

--breakpoint <FILE:LINE>, **-b** <FILE:LINE> Set break point at LINE in FILE.

%dhist

Print your history of visited directories.

`%dhist ->` print full history
`%dhist n ->` print last `n` entries only
`%dhist n1 n2 ->` print entries between `n1` and `n2` (`n2` not included)

This history is automatically maintained by the `%cd` command, and always available as the global list variable `_dh`. You can use `%cd -<n>` to go to directory number `<n>`.

Note that most of time, you should view directory history by entering `cd -<TAB>`.

`%dirs`

Return the current directory stack.

`%doctest_mode`

Toggle doctest mode on and off.

This mode is intended to make IPython behave as much as possible like a plain Python shell, from the perspective of how its prompts, exceptions and output look. This makes it easy to copy and paste parts of a session into doctests. It does so by:

- Changing the prompts to the classic `>>>` ones.
- Changing the exception reporting mode to „Plain“.
- Disabling pretty-printing of output.

Note that IPython also supports the pasting of code snippets that have leading „`>>>`“ and „`...`“ prompts in them. This means that you can paste doctests from files or docstrings (even if they have leading whitespace), and the code will execute correctly. You can then use „`%history -t`“ to see the translated history; this will give you the input after removal of all the leading prompts and whitespace, which can be pasted back into an editor.

With these features, you can switch into this mode easily whenever you need to do testing and changes to doctests, without having to leave your existing IPython session.

`%edit`

Bring up an editor and execute the resulting code.

Usage:

`%edit [options] [args]`

`%edit` runs IPython’s editor hook. The default version of this hook is set to call the editor specified by your `$EDITOR` environment variable. If this isn’t found, it will default to `vi` under Linux/Unix and to `notepad` under Windows. See the end of this docstring for how to change the editor hook.

You can also set the value of this editor via the `TerminalInteractiveShell.editor` option in your configuration file. This is useful if you wish to use a different editor from your typical default with IPython (and for Windows users who typically don’t set environment variables).

This command allows you to conveniently edit multi-line code right in your IPython session.

If called without arguments, `%edit` opens up an empty editor with a temporary file and will execute the contents of this file when you close it (don’t forget to save it!).

Options:

`-n <number>`: open the editor at a specified line number. By default, the IPython editor hook uses the unix syntax „`editor +N filename`“, but you can configure this by providing your own modified hook if your favorite editor supports line-number specifications with a different syntax.

`-p`: this will call the editor with the same data as the previous time it was used, regardless of how long ago (in your current session) it was.

`-r`: use „raw“ input. This option only applies to input taken from the user’s history. By default, the „processed“ history is used, so that magics are loaded in their transformed version to valid Python. If

this option is given, the raw input as typed as the command line is used instead. When you exit the editor, it will be executed by IPython's own processor.

-x: do not execute the edited code immediately upon exit. This is mainly useful if you are editing programs which need to be called with command line arguments, which you can then do using %run.

Arguments:

If arguments are given, the following possibilities exist:

- If the argument is a filename, IPython will load that into the editor. It will execute its contents with `execfile()` when you exit, loading any code in the file into your interactive namespace.
- The arguments are ranges of input history, e.g. «7 ~1/4-6». The syntax is the same as in the %history magic.
- If the argument is a string variable, its contents are loaded into the editor. You can thus edit any string which contains python code (including the result of previous edits).
- If the argument is the name of an object (other than a string), IPython will try to locate the file where it was defined and open the editor at the point where it is defined. You can use `%edit function` to load an editor exactly at the point where „function“ is defined, edit it and have the file be executed automatically.
- If the object is a macro (see %macro for details), this opens up your specified editor with a temporary file containing the macro's data. Upon exit, the macro is reloaded with the contents of the file.

Note: opening at an exact line is only supported under Unix, and some editors (like kedit and gedit up to Gnome 2.8) do not understand the „+NUMBER“ parameter necessary for this feature. Good editors like (X)Emacs, vi, jed, pico and joe all do.

After executing your code, %edit will return as output the code you typed in the editor (except when it was an existing file). This way you can reload the code in further invocations of %edit as a variable, via `_<NUMBER>` or `Out[<NUMBER>]`, where <NUMBER> is the prompt number of the output.

Note that %edit is also available through the alias %ed.

This is an example of creating a simple function inside the editor and then modifying it. First, start up the editor:

```
In [1]: edit
Editing... done. Executing edited code...
Out[1]: 'def foo():\n    print "foo() was defined in an editing
session"\n'
```

We can then call the function `foo()`:

```
In [2]: foo()
foo() was defined in an editing session
```

Now we edit `foo`. IPython automatically loads the editor with the (temporary) file where `foo()` was previously defined:

```
In [3]: edit foo
Editing... done. Executing edited code...
```

And if we call `foo()` again we get the modified version:

```
In [4]: foo()
foo() has now been changed!
```

Here is an example of how to edit a code snippet successive times. First we call the editor:

```
In [5]: edit
Editing... done. Executing edited code...
hello
Out[5]: "print 'hello'\n"
```

Now we call it again with the previous output (stored in `_`):

```
In [6]: edit _
Editing... done. Executing edited code...
hello world
Out[6]: "print 'hello world'\n"
```

Now we call it with the output `#8` (stored in `_8`, also as `Out[8]`):

```
In [7]: edit _8
Editing... done. Executing edited code...
hello again
Out[7]: "print 'hello again'\n"
```

Changing the default editor hook:

If you wish to write your own editor hook, you can put it in a configuration file which you load at startup time. The default hook is defined in the `IPython.core.hooks` module, and you can use that as a starting example for further modifications. That file also has general instructions on how to set a new hook for use once you've defined it.

%env

Get, set, or list environment variables.

Usage:

```
%env
    lists all environment variables/values

%env var
    get value for var

%env var val
    set value for var

%env var=val
    set value for var

%env var=$val
    set value for var, using python expansion if possible
```

%gui

Enable or disable IPython GUI event loop integration.

```
%gui [GUINAME]
```

This magic replaces IPython's threaded shells that were activated using the (pylab/wthread/etc.) command line flags. GUI toolkits can now be enabled at runtime and keyboard interrupts should work

without any problems. The following toolkits are supported: wxPython, PyQt4, PyGTK, Tk and Cocoa (OSX):

```
%gui wx      # enable wxPython event loop integration
%gui qt      # enable PyQt/PySide event loop integration
              # with the latest version available.
%gui qt6     # enable PyQt6/PySide6 event loop integration
%gui qt5     # enable PyQt5/PySide2 event loop integration
%gui gtk     # enable PyGTK event loop integration
%gui gtk3    # enable Gtk3 event loop integration
%gui gtk4    # enable Gtk4 event loop integration
%gui tk      # enable Tk event loop integration
%gui osx     # enable Cocoa event loop integration
              # (requires %matplotlib 1.1)
%gui        # disable all event loop integration
```

WARNING: after any of these has been called you can simply create an application object, but DO NOT start the event loop yourself, as we have already handled that.

%history

```
%history [-n] [-o] [-p] [-t] [-f FILENAME] [-g [PATTERN ...]]
        [-l [LIMIT]] [-u]
        [range ...]
```

Print input history (`_i<n>` variables), with most recent last.

By default, input history is printed without line numbers so it can be directly pasted into an editor. Use `-n` to show them.

By default, all input history from the current session is displayed. Ranges of history can be indicated using the syntax:

4

Line 4, current session

4-6

Lines 4-6, current session

243/1-5

Lines 1-5, session 243

~2/7

Line 7, session 2 before current

~8/1-~6/5

From the first line of 8 sessions ago, to the fifth line of 6 sessions ago.

Multiple ranges can be entered, separated by spaces

The same syntax is used by `%macro`, `%save`, `%edit`, `%rerun`

Examples

```
In [6]: %history -n 4-6
4:a = 12
5:print a**2
6:%history -n 4-6
```

positional arguments:

range

options:

- n** print line numbers for each input. This feature is only available if numbered prompts are in use.
- o** also print outputs for each input.
- p** print classic „>>>“ python prompts before each input. This is useful for making documentation, and in conjunction with -o, for producing doctest-ready output.
- t** print the „translated“ history, as IPython understands it. IPython filters your input and converts it all into valid Python source before executing it (things like magics or aliases are turned into function calls, for example). With this option, you'll see the native history instead of the user-entered version: „%cd /“ will be seen as „get_ipython().run_line_magic(«cd», «/»)“ instead of „%cd /“.
- f FILENAME** FILENAME: instead of printing the output to the screen, redirect it to the given file. The file is always overwritten, though *when it can*, IPython asks for confirmation first. In particular, running the command „history -f FILENAME“ from the IPython Notebook interface will replace FILENAME even if it already exists *without* confirmation.
- g <[PATTERN ...]>** treat the arg as a glob pattern to search for in (full) history. This includes the saved history (almost all commands ever written). The pattern may contain „?“ to match one unknown character and „*“ to match any number of unknown characters. Use „%hist -g“ to show full saved history (may be very long).
- l <[LIMIT]>** get the last n lines from all sessions. Specify n as a single arg, or the default is the last 10 lines.
- u** when searching history using -g, show only unique history.

%killbgscripts

Kill all BG processes started by %%script and its family.

%load

Load code into the current frontend.

Usage:

%load [options] source

where source can be a filename, URL, input history range, macro, or element in the user namespace

If no arguments are given, loads the history of this session up to this point.

Options:

-r <lines>: Specify lines or ranges of lines to load from the source. Ranges could be specified as x-y (x..y) or in python-style x:y (x..(y-1)). Both limits x and y can be left blank (meaning the beginning and end of the file, respectively).

- s <symbols>: Specify function or classes to load from python source.
- y : Don't ask confirmation for loading source above 200 000 characters.
- n : Include the user's namespace when searching for source code.

This magic command can either take a local filename, a URL, an history range (see %history) or a macro as argument, it will prompt for confirmation before loading source with more than 200 000 characters, unless -y flag is passed or if the frontend does not support raw_input:

```
%load
%load myscript.py
%load 7-27
%load myMacro
%load http://www.example.com/myscript.py
%load -r 5-10 myscript.py
%load -r 10-20,30,40: foo.py
%load -s MyClass,wonder_function myscript.py
%load -n MyClass
%load -n my_module.wonder_function
```

%load_ext

Load an IPython extension by its module name.

%loadpy

Alias of %load

%loadpy has gained some flexibility and dropped the requirement of a .py extension. So it has been renamed simply into %load. You can look at %load's docstring for more info.

%logoff

Temporarily stop logging.

You must have previously started logging.

%logon

Restart logging.

This function is for restarting logging which you've temporarily stopped with %logoff. For starting logging for the first time, you must use the %logstart function, which allows you to specify an optional log filename.

%logstart

Start logging anywhere in a session.

%logstart [-o|-r|-t|-q] [log_name [log_mode]]

If no name is given, it defaults to a file named „ipython_log.py“ in your current directory, in „rotate“ mode (see below).

„%logstart name“ saves to file „name“ in „backup“ mode. It saves your history up to that point and then continues logging.

%logstart takes a second optional parameter: logging mode. This can be one of (note that the modes are given unquoted):

append

Keep logging at the end of any existing file.

backup

Rename any existing file to name~ and start name.

global

Append to a single logfile in your home directory.

over

Overwrite any existing log.

rotate

Create rotating logs: name.1~, name.2~, etc.

Options:

-o log also IPython's output. In this mode, all commands which generate an Out[NN] prompt are recorded to the logfile, right after their corresponding input line. The output lines are always prepended with a „#[Out]# „ marker, so that the log remains valid Python code.

Since this marker is always the same, filtering only the output from a log is very easy, using for example a simple awk call:

```
awk -F'#[Out\]# ' '{if($2) {print $2}}' ipython_log.py
```

-r log „raw“ input. Normally, IPython's logs contain the processed input, so that user lines are logged in their final form, converted into valid Python. For example, %Exit is logged as _ip.magic(«Exit»). If the -r flag is given, all input is logged exactly as typed, with no transformations applied.

-t put timestamps before each input line logged (these are put in comments).

-q suppress output of logstate message when logging is invoked

%logstate

Print the status of the logging system.

%logstop

Fully stop logging and close log file.

In order to start logging again, a new %logstart call needs to be made, possibly (though not necessarily) with a new filename, mode and other options.

%lsmagic

List currently available magic functions.

%macro

Define a macro for future re-execution. It accepts ranges of history, filenames or string objects.

Usage:

```
%macro [options] name n1-n2 n3-n4 ... n5 .. n6 ...
```

Options:

-r: use „raw“ input. By default, the „processed“ history is used, so that magics are loaded in their transformed version to valid Python. If this option is given, the raw input as typed at the command line is used instead.

-q: quiet macro definition. By default, a tag line is printed to indicate the macro has been created, and then the contents of the macro are printed. If this option is given, then no printout is produced once the macro is created.

This will define a global variable called `name` which is a string made of joining the slices and lines you specify (`n1,n2,...` numbers above) from your input history into a single string. This variable acts like an automatic function which re-executes those lines as if you had typed them. You just type „name“ at the prompt and the code executes.

The syntax for indicating input ranges is described in `%history`.

Note: as a „hidden“ feature, you can also use traditional python slice notation, where `N:M` means numbers `N` through `M-1`.

For example, if your history contains (print using `%hist -n`):

```
44: x=1
45: y=3
46: z=x+y
47: print x
48: a=5
49: print 'x',x,'y',y
```

you can create a macro with lines 44 through 47 (included) and line 49 called `my_macro` with:

```
In [55]: %macro my_macro 44-47 49
```

Now, typing `my_macro` (without quotes) will re-execute all this code in one pass.

You don't need to give the line-numbers in order, and any given line number can appear multiple times. You can assemble macros with any lines from your input history in any order.

The macro is a simple object which holds its value in an attribute, but IPython's display system checks for macros and executes them as code instead of printing them when you type their name.

You can view a macro's contents by explicitly printing it with:

```
print macro_name
```

`%magic`

Print information about the magic function system.

Supported formats: `-latex`, `-brief`, `-rest`

`%matplotlib`

```
%matplotlib [-l] [gui]
```

Set up matplotlib to work interactively.

This function lets you activate matplotlib interactive support at any point during an IPython session. It does not import anything into the interactive namespace.

If you are using the inline matplotlib backend in the IPython Notebook you can set which figure formats are enabled using the following:

```
In [1]: from matplotlib_inline.backend_inline import set_matplotlib_formats

In [2]: set_matplotlib_formats('pdf', 'svg')
```


The default for inline figures sets `bbox_inches` to „tight“. This can cause discrepancies between the displayed image and the identical image created using `savefig`. This behavior can be disabled using the `%config` magic:

```
In [3]: %config InlineBackend.print_figure_kwargs = {'bbox_inches':None}
```

In addition, see the docstrings of `matplotlib_inline.backend_inline.set_matplotlib_formats` and `matplotlib_inline.backend_inline.set_matplotlib_close` for more information on changing additional behaviors of the inline backend.

Examples

To enable the inline backend for usage with the IPython Notebook:

```
In [1]: %matplotlib inline
```

In this case, where the matplotlib default is TkAgg:

```
In [2]: %matplotlib
Using matplotlib backend: TkAgg
```

But you can explicitly request a different GUI backend:

```
In [3]: %matplotlib qt
```

You can list the available backends using the `-l/--list` option:

```
In [4]: %matplotlib --list
Available matplotlib backends: ['osx', 'qt4', 'qt5', 'gtk3', 'gtk4', 'notebook', 'wx
↪', 'qt', 'nbagg',
'gtk', 'tk', 'inline']
```

positional arguments:

gui Name of the matplotlib backend to use („agg“, „gtk“, „gtk3“, „gtk4“, „inline“, „ipympl“, „nbagg“, „notebook“, „osx“, „pdf“, „ps“, „qt“, „qt4“, „qt5“, „qt6“, „svg“, „tk“, „webagg“, „widget“, „wx“). If given, the corresponding matplotlib backend is used, otherwise it will be matplotlib’s default (which you can set in your matplotlib config file).

options:

`-l, --list` Show available matplotlib backends

%notebook

```
%notebook filename
```

Export and convert IPython notebooks.

This function can export the current IPython history to a notebook file. For example, to export the history to «foo.ipynb» do «`%notebook foo.ipynb`».

positional arguments:

filename Notebook name or filename

%page

Pretty print the object and display it through a pager.

`%page [options] OBJECT`

If no object is given, use `_` (last output).

Options:

`-r:` page `str(object)`, don't pretty-print it.

%pastebin

Upload code to `dpaste.com`, returning the URL.

Usage:

`%pastebin [-d «Custom description»][-e 24] 1-7`

The argument can be an input history range, a filename, or the name of a string or macro.

If no arguments are given, uploads the history of this session up to this point.

Options:

-d: Pass a custom description. The default will say
«Pasted from IPython».

-e: Pass number of days for the link to be expired.
The default will be 7 days.

%pdb

Control the automatic calling of the `pdb` interactive debugger.

Call as „`%pdb on`“, „`%pdb 1`“, „`%pdb off`“ or „`%pdb 0`“. If called without argument it works as a toggle.

When an exception is triggered, IPython can optionally call the interactive `pdb` debugger after the traceback printout. `%pdb` toggles this feature on and off.

The initial state of this feature is set in your configuration file (the option is `InteractiveShell.pdb`).

If you want to just activate the debugger AFTER an exception has fired, without having to type „`%pdb on`“ and rerunning your code, you can use the `%debug` magic.

%pdef

Print the call signature for any callable object.

If the object is a class, print the constructor information.

Examples

```
In [3]: %pdef urllib.urlopen
urllib.urlopen(url, data=None, proxies=None)
```

%pdoc

Print the docstring for an object.

If the given object is a class, it will print both the class and the constructor docstrings.

%pfile

Print (or run through pager) the file where an object is defined.

The file opens at the line where the object definition begins. IPython will honor the environment variable `PAGER` if set, and otherwise will do its best to print the file in a convenient form.

If the given argument is not an object currently defined, IPython will try to interpret it as a filename (automatically adding a .py extension if needed). You can thus use %pfile as a syntax highlighting code viewer.

%pinfo

Provide detailed information about an object.

„%pinfo object“ is just a synonym for object? or ?object.

%pinfo2

Provide extra detailed information about an object.

„%pinfo2 object“ is just a synonym for object?? or ??object.

%pip

Run the pip package manager within the current kernel.

Usage:

%pip install [pkgs]

%popd

Change to directory popped off the top of the stack.

%pprint

Toggle pretty printing on/off.

%precision

Set floating point precision for pretty printing.

Can set either integer precision or a format string.

If numpy has been imported and precision is an int, numpy display precision will also be set, via `numpy.set_printoptions`.

If no argument is given, defaults will be restored.

Examples

```
In [1]: from math import pi
```

```
In [2]: %precision 3
```

```
Out[2]: u'%.3f'
```

```
In [3]: pi
```

```
Out[3]: 3.142
```

```
In [4]: %precision %i
```

```
Out[4]: u'%i'
```

```
In [5]: pi
```

```
Out[5]: 3
```

```
In [6]: %precision %e
```

```
Out[6]: u'%e'
```

```
In [7]: pi**10
```

```
Out[7]: 9.364805e+04
```

(continues on next page)

(продолжение с предыдущей страницы)

```
In [8]: %precision
Out[8]: u' %r'

In [9]: pi**10
Out[9]: 93648.047476082982
```

%prun

Run a statement through the python code profiler.

Usage, in line mode:

`%prun [options] statement`

Usage, in cell mode:

`%%prun [options] [statement] code... code...`

In cell mode, the additional code lines are appended to the (possibly empty) statement in the first line. Cell mode allows you to easily profile multiline blocks without having to put them in a separate function.

The given statement (which doesn't require quote marks) is run via the python profiler in a manner similar to the `profile.run()` function. Namespaces are internally managed to work correctly; `profile.run` cannot be used in IPython because it makes certain assumptions about namespaces which do not hold under IPython.

Options:

- l <limit>** you can place restrictions on what or how much of the profile gets printed. The limit value can be:
- A string: only information for function names containing this string is printed.
 - An integer: only these many lines are printed.
 - A float (between 0 and 1): this fraction of the report is printed (for example, use a limit of 0.4 to see the topmost 40% only).

You can combine several limits with repeated use of the option. For example, `-l __init__ -l 5` will print only the topmost 5 lines of information about class constructors.

- r** return the `pstats.Stats` object generated by the profiling. This object has all the information about the profile in it, and you can later use it for further analysis or in other functions.

- s <key>** sort profile by given key. You can provide more than one key by using the option several times: `„-s key1 -s key2 -s key3...“`. The default sorting key is „time“.

The following is copied verbatim from the profile documentation referenced below:

When more than one key is provided, additional keys are used as secondary criteria when there is equality in all keys selected before them.

Abbreviations can be used for any key names, as long as the abbreviation is unambiguous. The following are the keys currently defined:

Valid Arg	Meaning
«calls»	call count
«cumulative»	cumulative time
«file»	file name
«module»	file name
«pcalls»	primitive call count
«line»	line number
«name»	function name
«nfl»	name/file/line
«stdname»	standard name
«time»	internal time

Note that all sorts on statistics are in descending order (placing most time consuming items first), where as name, file, and line number searches are in ascending order (i.e., alphabetical). The subtle distinction between «nfl» and «stdname» is that the standard name is a sort of the name as printed, which means that the embedded line numbers get compared in an odd way. For example, lines 3, 20, and 40 would (if the file names were the same) appear in the string order «20» «3» and «40». In contrast, «nfl» does a numeric compare of the line numbers. In fact, `sort_stats(«nfl»)` is the same as `sort_stats(«name», «file», «line»)`.

- T <filename>** save profile results as shown on screen to a text file. The profile is still shown on screen.
- D <filename>** save (via `dump_stats`) profile statistics to given filename. This data is in a format understood by the `pstats` module, and is generated by a call to the `dump_stats()` method of profile objects. The profile is still shown on screen.
- q** suppress output to the pager. Best used with -T and/or -D above.

If you want to run complete programs under the profiler's control, use `%run -p [prof_opts] filename.py [args to program]` where `prof_opts` contains profiler specific options as described here.

You can read the complete documentation for the profile module with:

```
In [1]: import profile; profile.help()
```

Изменено в версии 7.3: User variables are no longer expanded, the magic line is always left unmodified.

`%psearch`

Search for object in namespaces by wildcard.

`%psearch [options] PATTERN [OBJECT TYPE]`

Note: `?` can be used as a synonym for `%psearch`, at the beginning or at the end: both `a*?` and `?a*` are equivalent to `„%psearch a*“`. Still, the rest of the command line must be unchanged (options come first), so for example the following forms are equivalent

```
%psearch -i a* function -i a* function? ?-i a* function
```

Arguments:

PATTERN

where PATTERN is a string containing `*` as a wildcard similar to its use in a shell. The pattern is matched in all namespaces on the search path. By default objects starting with

a single `_` are not matched, many IPython generated objects have a single underscore. The default is case insensitive matching. Matching is also done on the attributes of objects and not only on the objects in a module.

[OBJECT TYPE]

Is the name of a python type from the types module. The name is given in lowercase without the ending type, ex. StringType is written string. By adding a type here only objects matching the given type are matched. Using all here makes the pattern match all types (this is the default).

Options:

-a: makes the pattern match even objects whose names start with a single underscore. These names are normally omitted from the search.

-i/-c: make the pattern case insensitive/sensitive. If neither of these options are given, the default is read from your configuration file, with the option `InteractiveShell.wildcards_case_sensitive`. If this option is not specified in your configuration file, IPython's internal default is to do a case sensitive search.

-e/-s NAMESPACE: exclude/search a given namespace. The pattern you specify can be searched in any of the following namespaces: „builtin“, „user“, „user_global“, „internal“, „alias“, where „builtin“ and „user“ are the search defaults. Note that you should not use quotes when specifying namespaces.

-l: List all available object types for object matching. This function can be used without arguments.

„Builtin“ contains the python module builtin, „user“ contains all user data, „alias“ only contain the shell aliases and no python objects, „internal“ contains objects used by IPython. The „user_global“ namespace is only used by embedded IPython instances, and it contains module-level globals. You can add namespaces to the search with -s or exclude them with -e (these options can be given more than once).

Examples

```
%psearch a*           -> objects beginning with an a
%psearch -e builtin a* -> objects NOT in the builtin space starting in a
%psearch a* function  -> all functions beginning with an a
%psearch re.e*        -> objects beginning with an e in module re
%psearch r*.e*        -> objects that start with e in modules starting in r
%psearch r*.* string  -> all strings in modules beginning with r
```

Case sensitive search:

```
%psearch -c a*      list all object beginning with lower case a
```

Show objects beginning with a single `_`:

```
%psearch -a _*      list objects beginning with a single underscore
```

List available objects:

```
%psearch -l         list all available object types
```

%psource

Print (or run through pager) the source code for an object.

%pushd

Place the current dir on stack and change directory.

Usage:`%pushd [.,dirname“]`**%pwd**

Return the current working directory path.

Examples

```
In [9]: pwd
Out[9]: '/home/tsuser/sprint/ipython'
```

%pycat

Show a syntax-highlighted file through a pager.

This magic is similar to the cat utility, but it will assume the file to be Python source and will show it with syntax highlighting.

This magic command can either take a local filename, an url, an history range (see %history) or a macro as argument.

If no parameter is given, prints out history of current session up to this point.

```
%pycat myscript.py
%pycat 7-27
%pycat myMacro
%pycat http://www.example.com/myscript.py
```

%pylab

```
%pylab [--no-import-all] [gui]
```

Load numpy and matplotlib to work interactively.

This function lets you activate pylab (matplotlib, numpy and interactive support) at any point during an IPython session.

%pylab makes the following imports:

```
import numpy
import matplotlib
from matplotlib import pylab, mlab, pyplot
np = numpy
plt = pyplot

from IPython.display import display
from IPython.core.pylabtools import figsize, getfigs

from pylab import *
from numpy import *
```

If you pass `--no-import-all`, the last two `*` imports will be excluded.

See the %matplotlib magic for more details about activating matplotlib without affecting the interactive namespace.

positional arguments:

gui Name of the matplotlib backend to use („agg“, „gtk“, „gtk3“, „gtk4“, „inline“, „ipympl“, „nbagg“, „notebook“, „osx“, „pdf“, „ps“, „qt“, „qt4“, „qt5“, „qt6“, „svg“, „tk“, „webagg“, „widget“, „wx“). If given, the corresponding matplotlib backend is used, otherwise it will be matplotlib’s default (which you can set in your matplotlib config file).

options:

--no-import-all Prevent IPython from performing `import *` into the interactive namespace. You can govern the default behavior of this flag with the `InteractiveShellApp.pylab_import_all` configurable.

%quickref

Show a quick reference sheet

%recall

Repeat a command, or get command to input line for editing.

%recall and %rep are equivalent.

- %recall (no arguments):

Place a string version of last computation result (stored in the special „_“ variable) to the next input prompt. Allows you to create elaborate command lines without using copy-paste:

```
In[1]: l = ["hei", "vaan"]
In[2]: "".join(l)
Out[2]: heivaan
In[3]: %recall
In[4]: heivaan_ <== cursor blinking
```

%recall 45

Place history line 45 on the next input prompt. Use %hist to find out the number.

%recall 1-4

Combine the specified lines into one cell, and place it on the next input prompt. See %history for the slice syntax.

%recall foo+bar

If `foo+bar` can be evaluated in the user namespace, the result is placed at the next input prompt. Otherwise, the history is searched for lines which contain that substring, and the most recent one is placed at the next input prompt.

%rehashx

Update the alias table with all executable files in \$PATH.

rehashx explicitly checks that every entry in \$PATH is a file with execute access (`os.X_OK`).

Under Windows, it checks executability as a match against a „|“-separated string of extensions, stored in the IPython config variable `win_exec_ext`. This defaults to „exe|com|bat“.

This function also resets the root module cache of module completer, used on slow filesystems.

%reload_ext

Reload an IPython extension by its module name.

%rerun

Re-run previous input

By default, you can specify ranges of input history to be repeated (as with %history). With no arguments, it will repeat the last line.

Options:

-l <n> : Repeat the last n lines of input, not including the current command.

-g foo : Repeat the most recent line which contains foo

%reset

Resets the namespace by removing all names defined by the user, if called without arguments, or by removing some types of objects, such as everything currently in IPython's In[] and Out[] containers (see the parameters for details).

Parameters

-f	force reset without asking for confirmation.
-s	„Soft“ reset: Only clears your namespace, leaving history intact. References to objects may be kept. By default (without this option), we do a „hard“ reset, giving you a new session and removing all references to objects from the current session.
--aggressive	Try to aggressively remove modules from sys.modules ; this may allow you to reimport Python modules that have been updated and pick up changes, but can have unintended consequences.

in

reset input history

out

reset output history

dhist

reset directory history

array

reset only variables that are NumPy arrays

See Also

reset_selective : invoked as %reset_selective

Examples

```
In [6]: a = 1

In [7]: a
Out[7]: 1

In [8]: 'a' in get_ipython().user_ns
Out[8]: True

In [9]: %reset -f

In [1]: 'a' in get_ipython().user_ns
Out[1]: False
```

(continues on next page)

(продолжение с предыдущей страницы)

```
In [2]: %reset -f in
Flushing input history

In [3]: %reset -f dhists in
Flushing directory history
Flushing input history
```

Notes

Calling this magic from clients that do not implement standard input, such as the ipython notebook interface, will reset the namespace without confirmation.

%reset_selective

Resets the namespace by removing names defined by the user.

Input/Output history are left around in case you need them.

%reset_selective [-f] regex

No action is taken if regex is not included

Options

-f : force reset without asking for confirmation.

See Also

reset : invoked as %reset

Examples

We first fully reset the namespace so your output looks identical to this example for pedagogical reasons; in practice you do not need a full reset:

```
In [1]: %reset -f
```

Now, with a clean namespace we can make a few variables and use %reset_selective to only delete names that match our regexp:

```
In [2]: a=1; b=2; c=3; b1m=4; b2m=5; b3m=6; b4m=7; b2s=8

In [3]: who_ls
Out[3]: ['a', 'b', 'b1m', 'b2m', 'b2s', 'b3m', 'b4m', 'c']

In [4]: %reset_selective -f b[2-3]m

In [5]: who_ls
Out[5]: ['a', 'b', 'b1m', 'b2s', 'b4m', 'c']

In [6]: %reset_selective -f d

In [7]: who_ls
Out[7]: ['a', 'b', 'b1m', 'b2s', 'b4m', 'c']

In [8]: %reset_selective -f c

In [9]: who_ls
```

(continues on next page)

(продолжение с предыдущей страницы)

```
Out[9]: ['a', 'b', 'b1m', 'b2s', 'b4m']
```

```
In [10]: %reset_selective -f b
```

```
In [11]: who_ls
```

```
Out[11]: ['a']
```

Notes

Calling this magic from clients that do not implement standard input, such as the ipython notebook interface, will reset the namespace without confirmation.

%run

Run the named file inside IPython as a program.

Usage:

```
%run [-n -i -e -G]
      [( -t [-N<N>] | -d [-b<N>] | -p [profile options] )]
      ( -m mod | filename ) [args]
```

The filename argument should be either a pure Python script (with extension `.py`), or a file with custom IPython syntax (such as magics). If the latter, the file can be either a script with `.ipy` extension, or a Jupyter notebook with `.ipynb` extension. When running a Jupyter notebook, the output from print statements and other displayed objects will appear in the terminal (even matplotlib figures will open, if a terminal-compliant backend is being used). Note that, at the system command line, the `jupyter run` command offers similar functionality for executing notebooks (albeit currently with some differences in supported options).

Parameters after the filename are passed as command-line arguments to the program (put in `sys.argv`). Then, control returns to IPython's prompt.

This is similar to running at a system prompt `python file args`, but with the advantage of giving you IPython's tracebacks, and of loading all variables into your interactive namespace for further use (unless `-p` is used, see below).

The file is executed in a namespace initially consisting only of `__name__ == '__main__'` and `sys.argv` constructed as indicated. It thus sees its environment as if it were being run as a stand-alone program (except for sharing global objects such as previously imported modules). But after execution, the IPython interactive namespace gets updated with all variables defined in the program (except for `__name__` and `sys.argv`). This allows for very convenient loading of code for interactive work, while giving each program a „clean sheet“ to run in.

Arguments are expanded using shell-like glob match. Patterns `„*“, „?“, „[seq]“` and `„[!seq]“` can be used. Additionally, tilde `„~“` will be expanded into user's home directory. Unlike real shells, quotation does not suppress expansions. Use *two* back slashes (e.g. `*`) to suppress expansions. To completely disable these expansions, you can use `-G` flag.

On Windows systems, the use of single quotes `'` when specifying a file is not supported. Use double quotes `"`.

Options:

-n `__name__` is NOT set to `„__main__“`, but to the running file's name without extension (as python does under `import`). This allows running scripts and reloading the definitions in them without calling code protected by an `if __name__ == "__main__"` clause.

- i** run the file in IPython's namespace instead of an empty one. This is useful if you are experimenting with code written in a text editor which depends on variables defined interactively.
- e** ignore `sys.exit()` calls or `SystemExit` exceptions in the script being run. This is particularly useful if IPython is being used to run unittests, which always exit with a `sys.exit()` call. In such cases you are interested in the output of the test results, not in seeing a traceback of the unittest module.
- t** print timing information at the end of the run. IPython will give you an estimated CPU time consumption for your script, which under Unix uses the resource module to avoid the wraparound problems of `time.clock()`. Under Unix, an estimate of time spent on system tasks is also given (for Windows platforms this is reported as 0.0).

If `-t` is given, an additional `-N<N>` option can be given, where `<N>` must be an integer indicating how many times you want the script to run. The final timing report will include total and per run results.

For example (testing the script `uniq_stable.py`):

```
In [1]: run -t uniq_stable

IPython CPU timings (estimated):
  User :    0.19597 s.
 System:    0.0 s.

In [2]: run -t -N5 uniq_stable

IPython CPU timings (estimated):
Total runs performed: 5
  Times :      Total      Per run
  User  :    0.910862 s,  0.1821724 s.
 System:    0.0 s,      0.0 s.
```

- d** run your program under the control of `pdb`, the Python debugger. This allows you to execute your program step by step, watch variables, etc. Internally, what IPython does is similar to calling:

```
pdb.run('execfile("YOURFILENAME")')
```

with a breakpoint set on line 1 of your file. You can change the line number for this automatic breakpoint to be `<N>` by using the `-bN` option (where `N` must be an integer). For example:

```
%run -d -b40 myscript
```

will set the first breakpoint at line 40 in `myscript.py`. Note that the first breakpoint must be set on a line which actually does something (not a comment or docstring) for it to stop execution.

Or you can specify a breakpoint in a different file:

```
%run -d -b myotherfile.py:20 myscript
```

When the `pdb` debugger starts, you will see a `(Pdb)` prompt. You must first enter `„c“` (without quotes) to start execution up to the

first breakpoint.

Entering „help“ gives information about the use of the debugger. You can easily see pdb's full documentation with «import pdb;pdb.help()» at a prompt.

-p run program under the control of the Python profiler module (which prints a detailed report of execution times, function calls, etc).

You can pass other options after -p which affect the behavior of the profiler itself. See the docs for %prun for details.

In this mode, the program's variables do NOT propagate back to the IPython interactive namespace (because they remain in the namespace where the profiler executes them).

Internally this triggers a call to %prun, see its documentation for details on the options available specifically for profiling.

There is one special usage for which the text above doesn't apply: if the filename ends with .ipy[nb], the file is run as ipython script, just as if the commands were written on IPython prompt.

-m specify module name to load instead of script path. Similar to the -m option for the python interpreter. Use this option last if you want to combine with other %run options. Unlike the python interpreter only source modules are allowed no .pyc or .pyo files. For example:

```
%run -m example
```

will run the example module.

-G disable shell-like glob expansion of arguments.

%save

Save a set of lines or a macro to a given filename.

Usage:

%save [options] filename [history]

Options:

-r: use „raw“ input. By default, the „processed“ history is used, so that magics are loaded in their transformed version to valid Python. If this option is given, the raw input as typed as the command line is used instead.

-f: force overwrite. If file exists, %save will prompt for overwrite unless -f is given.

-a: append to the file instead of overwriting it.

The history argument uses the same syntax as %history for input ranges, then saves the lines to the filename you specify.

If no ranges are specified, saves history of the current session up to this point.

It adds a „py“ extension to the file if you don't do so yourself, and it asks for confirmation before overwriting existing files.

If -r option is used, the default extension is .ipy.

%sc

Shell capture - run shell command and capture output (DEPRECATED use !).

DEPRECATED. Suboptimal, retained for backwards compatibility.

You should use the form „var = !command“ instead. Example:

```
«%sc -l myfile = ls ~» should now be written as
«myfile = !ls ~»
```

myfile.s, myfile.l and myfile.n still apply as documented below.

```
%sc [options] varname=command
```

IPython will run the given command using `commands.getoutput()`, and will then update the user's interactive namespace with a variable called `varname`, containing the value of the call. Your command can contain shell wildcards, pipes, etc.

The „=“ sign in the syntax is mandatory, and the variable name you supply must follow Python's standard conventions for valid names.

(A special format without variable name exists for internal use)

Options:

- l: list output. Split the output on newlines into a list before assigning it to the given variable. By default the output is stored as a single string.
- v: verbose. Print the contents of the variable.

In most cases you should not need to split as a list, because the returned value is a special type of string which can automatically provide its contents either as a list (split on newlines) or as a space-separated string. These are convenient, respectively, either for sequential processing or to be passed to a shell command.

For example:

```
# Capture into variable a
In [1]: sc a=ls *py

# a is a string with embedded newlines
In [2]: a
Out[2]: 'setup.py\nwin32_manual_post_install.py'

# which can be seen as a list:
In [3]: a.l
Out[3]: ['setup.py', 'win32_manual_post_install.py']

# or as a whitespace-separated string:
In [4]: a.s
Out[4]: 'setup.py win32_manual_post_install.py'

# a.s is useful to pass as a single command line:
In [5]: !wc -l $a.s
146 setup.py
130 win32_manual_post_install.py
276 total

# while the list form is useful to loop over:
In [6]: for f in a.l:
...:     !wc -l $f
...:
146 setup.py
130 win32_manual_post_install.py
```

Similarly, the lists returned by the `-l` option are also special, in the sense that you can equally invoke the `.s` attribute on them to automatically get a whitespace-separated string from their contents:

```
In [7]: sc -l b=ls *py

In [8]: b
Out[8]: ['setup.py', 'win32_manual_post_install.py']

In [9]: b.s
Out[9]: 'setup.py win32_manual_post_install.py'
```

In summary, both the lists and strings used for output capture have the following special attributes:

```
.l (or .list) : value as list.
.n (or .nlstr): value as newline-separated string.
.s (or .spstr): value as space-separated string.
```

%set_env

Set environment variables. Assumptions are that either «val» is a name in the user namespace, or val is something that evaluates to a string.

Usage:

```
%set_env var val
    set value for var

%set_env var=val
    set value for var

%set_env var=$val
    set value for var, using python expansion if possible
```

%sx

Shell execute - run shell command and capture output (!! is short-hand).

%sx command

IPython will run the given command using `commands.getoutput()`, and return the result formatted as a list (split on „`\n`“). Since the output is `_returned_`, it will be stored in ipython’s regular output cache `Out[N]` and in the „`_N`“ automatic variables.

Notes:

- 1) If an input line begins with „`!!`“, then `%sx` is automatically invoked. That is, while:

```
!!ls
```

causes ipython to simply issue `system('ls')`, typing:

```
!!!ls
```

is a shorthand equivalent to:

```
%sx ls
```

- 2) `%sx` differs from `%sc` in that `%sx` automatically splits into a list, like „`%sc -l`“. The reason for this is to make it as easy as possible to process line-oriented shell output via further python commands. `%sc` is meant to provide much finer control, but requires more typing.

- 3) Just like `%sc -l`, this is a list with special attributes:

```
.l (or .list) : value as list.  
.n (or .nlstr): value as newline-separated string.  
.s (or .spstr): value as whitespace-separated string.
```

This is very useful when trying to use such lists as arguments to system commands.

%system

Shell execute - run shell command and capture output (!! is short-hand).

%sx command

IPython will run the given command using `commands.getoutput()`, and return the result formatted as a list (split on „`\n`“). Since the output is `_returned_`, it will be stored in ipython’s regular output cache `Out[N]` and in the „`_N`“ automatic variables.

Notes:

1) If an input line begins with „`!!`“, then %sx is automatically invoked. That is, while:

```
!!ls
```

causes ipython to simply issue `system(„ls“)`, typing:

```
!!ls
```

is a shorthand equivalent to:

```
%sx ls
```

2) %sx differs from %sc in that %sx automatically splits into a list, like „%sc -l“. The reason for this is to make it as easy as possible to process line-oriented shell output via further python commands. %sc is meant to provide much finer control, but requires more typing.

3) Just like %sc -l, this is a list with special attributes:

```
.l (or .list) : value as list.  
.n (or .nlstr): value as newline-separated string.  
.s (or .spstr): value as whitespace-separated string.
```

This is very useful when trying to use such lists as arguments to system commands.

%tb

Print the last traceback.

Optionally, specify an exception reporting mode, tuning the verbosity of the traceback. By default the currently-active exception mode is used. See %xmode for changing exception reporting modes.

Valid modes: Plain, Context, Verbose, and Minimal.

%time

Time execution of a Python statement or expression.

The CPU and wall clock times are printed, and the value of the expression (if any) is returned. Note that under Win32, system time is always reported as 0, since it can not be measured.

This function can be used both as a line and cell magic:

- In line mode you can time a single-line statement (though multiple ones can be chained with using semicolons).
- In cell mode, you can time the cell body (a directly following statement raises an error).

This function provides very basic timing functionality. Use the `timeit` magic for more control over the measurement.

Изменено в версии 7.3: User variables are no longer expanded, the magic line is always left unmodified.

Examples

```
In [1]: %time 2**128
CPU times: user 0.00 s, sys: 0.00 s, total: 0.00 s
Wall time: 0.00
Out[1]: 340282366920938463463374607431768211456L

In [2]: n = 1000000

In [3]: %time sum(range(n))
CPU times: user 1.20 s, sys: 0.05 s, total: 1.25 s
Wall time: 1.37
Out[3]: 499999500000L

In [4]: %time print 'hello world'
hello world
CPU times: user 0.00 s, sys: 0.00 s, total: 0.00 s
Wall time: 0.00
```

Примечание: The time needed by Python to compile the given expression will be reported if it is more than 0.1s.

In the example below, the actual exponentiation is done by Python at compilation time, so while the expression can take a noticeable amount of time to compute, that time is purely due to the compilation:

```
In [5]: %time 3**9999;
CPU times: user 0.00 s, sys: 0.00 s, total: 0.00 s
Wall time: 0.00 s

In [6]: %time 3**999999;
CPU times: user 0.00 s, sys: 0.00 s, total: 0.00 s
Wall time: 0.00 s
Compiler : 0.78 s
```

%timeit

Time execution of a Python statement or expression

Usage, in line mode:

```
%timeit [-n<N> -r<R> [-t|-c] -q -p<P> -o] statement
```

or in cell mode:

```
%%timeit [-n<N> -r<R> [-t|-c] -q -p<P> -o] setup_code code code...
```

Time execution of a Python statement or expression using the `timeit` module. This function can be used both as a line and cell magic:

- In line mode you can time a single-line statement (though multiple ones can be chained with using semicolons).
- In cell mode, the statement in the first line is used as setup code (executed but not timed) and the body of the cell is timed. The cell body has access to any variables created in the setup code.

Options: `-n<N>`: execute the given statement `<N>` times in a loop. If `<N>` is not provided, `<N>` is determined so as to get sufficient accuracy.

`-r<R>`: number of repeats `<R>`, each consisting of `<N>` loops, and take the best result. Default: 7

`-t`: use `time.time` to measure the time, which is the default on Unix. This function measures wall time.

`-c`: use `time.clock` to measure the time, which is the default on Windows and measures wall time. On Unix, `resource.getrusage` is used instead and returns the CPU user time.

`-p<P>`: use a precision of `<P>` digits to display the timing result. Default: 3

`-q`: Quiet, do not print result.

-o: return a `TimeitResult` that can be stored in a variable to inspect
the result in more details.

Изменено в версии 7.3: User variables are no longer expanded, the magic line is always left unmodified.

Examples

```
In [1]: %timeit pass
8.26 ns ± 0.12 ns per loop (mean ± std. dev. of 7 runs, 100000000 loops each)

In [2]: u = None

In [3]: %timeit u is None
29.9 ns ± 0.643 ns per loop (mean ± std. dev. of 7 runs, 10000000 loops each)

In [4]: %timeit -r 4 u == None

In [5]: import time

In [6]: %timeit -n1 time.sleep(2)
```

The times reported by `%timeit` will be slightly higher than those reported by the `timeit.py` script when variables are accessed. This is due to the fact that `%timeit` executes the statement in the namespace of the shell, compared with `timeit.py`, which uses a single setup statement to import function or create variables. Generally, the bias does not matter as long as results from `timeit.py` are not mixed with those from `%timeit`.

%unalias

Remove an alias

%unload_ext

Unload an IPython extension by its module name.

Not all extensions can be unloaded, only those which define an `unload_ipython_extension` function.

%who

Print all interactive variables, with some minimal formatting.

If any arguments are given, only variables whose type matches one of these are printed. For example:

```
%who function str
```

will only list functions and strings, excluding all other types of variables. To find the proper type names, simply use `type(var)` at a command line to see how python prints type names. For example:

```
In [1]: type('hello')\
Out[1]: <type 'str'>
```

indicates that the type name for strings is „str“.

`%who` always excludes executed names loaded through your configuration file and things which are internal to IPython.

This is deliberate, as typically you may load many modules and the purpose of `%who` is to show you only what you’ve manually defined.

Examples

Define two variables and list them with `who`:

```
In [1]: alpha = 123

In [2]: beta = 'test'

In [3]: %who
alpha    beta

In [4]: %who int
alpha

In [5]: %who str
beta
```

`%who_ls`

Return a sorted list of all interactive variables.

If arguments are given, only variables of types matching these arguments are returned.

Examples

Define two variables and list them with `who_ls`:

```
In [1]: alpha = 123

In [2]: beta = 'test'

In [3]: %who_ls
Out[3]: ['alpha', 'beta']

In [4]: %who_ls int
Out[4]: ['alpha']

In [5]: %who_ls str
Out[5]: ['beta']
```

`%whos`

Like `%who`, but gives some extra information about each variable.

The same type filtering of `%who` can be applied here.

For all variables, the type is printed. Additionally it prints:

- For `{}`, `[]`, `()`: their length.

- For numpy arrays, a summary with shape, number of elements, typecode and size in memory.
- Everything else: a string representation, snipping their middle if too long.

Examples

Define two variables and list them with whos:

```
In [1]: alpha = 123

In [2]: beta = 'test'

In [3]: %whos
Variable    Type      Data/Info
alpha      int       123
beta       str       test
```

`%xdel`

Delete a variable, trying to clear it from anywhere that IPython's machinery has references to it. By default, this uses the identity of the named object in the user namespace to remove references held under other names. The object is also removed from the output history.

Options

`-n` : Delete the specified name from all namespaces, without checking their identity.

`%xmode`

Switch modes for the exception handlers.

Valid modes: Plain, Context, Verbose, and Minimal.

If called without arguments, acts as a toggle.

When in verbose mode the value `--show` (and `--hide`) will respectively show (or hide) frames with `__tracebackhide__ = True` value set.

4.9.2 Cell magics

`%%bash`

`%%bash` script magic

Run cells with bash in a subprocess.

This is a shortcut for `%%script bash`

`%%capture`

```
%capture [--no-stderr] [--no-stdout] [--no-display] [output]
```

run the cell, capturing stdout, stderr, and IPython's rich `display()` calls.

positional arguments:

output The name of the variable in which to store output. This is a `utils.io.CapturedIO` object with `stdout/err` attributes for the text of the captured output. `CapturedOutput` also has a `show()` method for displaying the output, and `__call__` as well, so you can use that to quickly display the output. If unspecified, captured output is discarded.

options:

--no-stderr	Don't capture stderr.
--no-stdout	Don't capture stdout.
--no-display	Don't capture IPython's rich display.

%%html

```
%%html [--isolated]
```

Render the cell as a block of HTML

options:

--isolated	Annotate the cell as „isolated“. Isolated cells are rendered inside their own <code><iframe></code> tag
-------------------	---

%%javascript

Run the cell block of Javascript code

Starting with IPython 8.0 `%%javascript` is pending deprecation to be replaced by a more flexible system

Please See <https://github.com/ipython/ipython/issues/13376>

%%js

Run the cell block of Javascript code

Alias of `%%javascript`

Starting with IPython 8.0 `%%javascript` is pending deprecation to be replaced by a more flexible system

Please See <https://github.com/ipython/ipython/issues/13376>

%%latex

Render the cell as a block of LaTeX

The subset of LaTeX which is supported depends on the implementation in the client. In the Jupyter Notebook, this magic only renders the subset of LaTeX defined by MathJax [here](<https://docs.mathjax.org/en/v2.5-latest/tex.html>).

%%markdown

Render the cell as Markdown text block

%%perl

`%%perl` script magic

Run cells with perl in a subprocess.

This is a shortcut for `%%script perl`

%%pypy

`%%pypy` script magic

Run cells with pypy in a subprocess.

This is a shortcut for `%%script pypy`

%%python

`%%python` script magic

Run cells with python in a subprocess.

This is a shortcut for `%%script python`

%%python2

%%python2 script magic

Run cells with python2 in a subprocess.

This is a shortcut for **%%script python2**

%%python3

%%python3 script magic

Run cells with python3 in a subprocess.

This is a shortcut for **%%script python3**

%%ruby

%%ruby script magic

Run cells with ruby in a subprocess.

This is a shortcut for **%%script ruby**

%%script

%shebang [--no-raise-error] [--proc PROC] [--bg] [--err ERR] [--out OUT]

Run a cell via a shell command

The **%%script** line is like the `#!` line of script, specifying a program (bash, perl, ruby, etc.) with which to run.

The rest of the cell is run by that program.

Examples

```
In [1]: %%script bash
...: for i in 1 2 3; do
...:   echo $i
...: done
1
2
3
```

options:

--no-raise-error	Whether you should raise an error message in addition to a stream on stderr if you get a nonzero exit code.
--proc PROC	The variable in which to store Popen instance. This is used only when <code>-bg</code> option is given.
--bg	Whether to run the script in the background. If given, the only way to see the output of the command is with <code>-out/err</code> .
--err ERR	The variable in which to store stderr from the script. If the script is backgrounded, this will be the stderr <i>pipe</i> , instead of the stderr text itself and will not be autoclosed.
--out OUT	The variable in which to store stdout from the script. If the script is backgrounded, this will be the stdout <i>pipe</i> , instead of the stderr text itself and will not be auto closed.

`%%sh`

`%%sh` script magic

Run cells with sh in a subprocess.

This is a shortcut for `%%script sh`

`%%svg`

Render the cell as an SVG literal

`%%writefile`

`%%writefile [-a] filename`

Write the contents of the cell to a file.

The file will be overwritten unless the `-a` (`--append`) flag is specified.

positional arguments:

filename file to write

options:

`-a, --append`

Append contents of the cell to an existing file. The file will be created if it does not exist.

См.также:

[Консоль Qt для Jupyter The Jupyter Notebook](#)

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

Конфигурирование и донастройка

5.1 Конфигурирование IPython

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

5.1.1 Introduction to IPython configuration

Setting configurable options

Many of IPython's classes have configurable attributes (see *IPython options* for the list). These can be configured in several ways.

Python configuration files

To create the blank configuration files, run:

```
ipython profile create [profilename]
```

If you leave out the profile name, the files will be created for the `default` profile (see [Profiles](#)). These will typically be located in `~/.ipython/profile_default/`, and will be named `ipython_config.py`, for historical reasons you may also find files named with IPython prefix instead of Jupyter: `ipython_notebook_config.py`, etc. The settings in `ipython_config.py` apply to all IPython commands.

By default, configuration files are fully featured Python scripts that can execute arbitrary code, the main usage is to set value on the configuration object `c` which exist in your configuration file.

You can then configure class attributes like this:

```
c.InteractiveShell.automagic = False
```

Be careful with spelling—incorrect names will simply be ignored, with no error.

To add to a collection which may have already been defined elsewhere or have default values, you can use methods like those found on lists, dicts and sets: `append`, `extend`, `prepend()` (like `extend`, but at the front), `add` and `update` (which works both for dicts and sets):

```
c.InteractiveShellApp.extensions.append('Cython')
```

Добавлено в версии 2.0: list, dict and set methods for config values

Example configuration file

```
# sample ipython_config.py

c.TerminalIPythonApp.display_banner = True
c.InteractiveShellApp.log_level = 20
c.InteractiveShellApp.extensions = [
    'myextension'
]
c.InteractiveShellApp.exec_lines = [
    'import numpy',
    'import scipy'
]
c.InteractiveShellApp.exec_files = [
    'mycode.py',
    'fancy.ipy'
]
c.InteractiveShell.colors = 'LightBG'
c.InteractiveShell.xmode = 'Context'
c.TerminalInteractiveShell.confirm_exit = False
c.TerminalInteractiveShell.editor = 'nano'

c.PrefilterManager.multi_line_specials = True

c.AliasManager.user_aliases = [
```

(continues on next page)

(продолжение с предыдущей страницы)

```
('la', 'ls -al')
]
```

JSON Configuration files

In case where executability of configuration can be problematic, or configurations need to be modified programmatically, IPython also support a limited set of functionalities via `.json` configuration files.

You can defined most of the configuration options via a json object which hierarchy represent the value you would normally set on the `c` object of `.py` configuration files. The following `ipython_config.json` file:

```
{
  "InteractiveShell": {
    "colors": "LightBG",
  },
  "InteractiveShellApp": {
    "extensions": [
      "myextension"
    ]
  },
  "TerminalInteractiveShell": {
    "editor": "nano"
  }
}
```

Is equivalent to the following `ipython_config.py`:

```
c.InteractiveShellApp.extensions = [
    'myextension'
]

c.InteractiveShell.colors = 'LightBG'
c.TerminalInteractiveShell.editor = 'nano'
```

Command line arguments

Every configurable value can be set from the command line, using this syntax:

```
ipython --ClassName.attribute=value
```

Many frequently used options have short aliases and flags, such as `--matplotlib` (to integrate with a matplotlib GUI event loop) or `--pdb` (automatic post-mortem debugging of exceptions).

To see all of these abbreviated options, run:

```
ipython --help
jupyter notebook --help
# etc.
```

Options specified at the command line, in either format, override options set in a configuration file.

The config magic

You can also modify config from inside IPython, using a magic command:

```
%config IPCompleter.greedy = True
```

At present, this only affects the current session - changes you make to config are not saved anywhere. Also, some options are only read when IPython starts, so they can't be changed like this.

Running IPython from Python

If you are using *Embedding IPython* to start IPython from a normal python file, you can set configuration options the same way as in a config file by creating a traitlets `Config` object and passing it to `start_ipython` like in the example below.

```
"""Quick snippet explaining how to set config options when using start_ipython."""

# First create a config object from the traitlets library
from traitlets.config import Config
c = Config()

# Now we can set options as we would in a config file:
#   c.Class.config_value = value
# For example, we can set the exec_lines option of the InteractiveShellApp
# class to run some code when the IPython REPL starts
c.InteractiveShellApp.exec_lines = [
    'print("\\nimporting some things\\n")',
    'import math',
    "math"
]
c.InteractiveShell.colors = 'LightBG'
c.InteractiveShell.confirm_exit = False
c.TerminalIPythonApp.display_banner = False

# Now we start ipython with our configuration
import IPython
IPython.start_ipython(config=c)
```

Profiles

IPython can use multiple profiles, with separate configuration and history. By default, if you don't specify a profile, IPython always runs in the `default` profile. To use a new profile:

```
ipython profile create foo    # create the profile foo
ipython --profile=foo        # start IPython using the new profile
```

Profiles are typically stored in *The IPython directory*, but you can also keep a profile in the current working directory, for example to distribute it with a project. To find a profile directory on the filesystem:

```
ipython locate profile foo
```

The IPython directory

IPython stores its files—config, command history and extensions—in the directory `~/.ipython/` by default.

IPYTHONDIR

If set, this environment variable should be the path to a directory, which IPython will use for user data. IPython will create it if it does not exist.

`--ipython-dir=<path>`

This command line option can also be used to override the default IPython directory.

To see where IPython is looking for the IPython directory, use the command `ipython locate`, or the Python function `IPython.paths.get_ipython_dir()`.

Systemwide configuration

It can be useful to deploy systemwide `ipython` or `ipykernel` configuration when managing environment for many users. At startup time IPython and IPykernel will search for configuration file in multiple systemwide locations, mainly:

- `/etc/ipython/`
- `/usr/local/etc/ipython/`

When the global install is a standalone python distribution it may also search in distribution specific location, for example:

- `$ANACONDA_LOCATION/etc/ipython/`

In those locations, Terminal IPython will look for a file called `ipython_config.py` and `ipython_config.json`, `ipykernel` will look for `ipython_kernel_config.py` and `ipython_kernel.json`.

Configuration files are loaded in order and merged with configuration on later location taking precedence on earlier locations (that is to say a user can overwrite a systemwide configuration option).

You can see all locations in which IPython is looking for configuration files by starting `ipython` in debug mode:

```
$ ipython --debug -c 'exit()'
```

Identically with `ipykernel` though the command is currently blocking until this process is killed with `Ctrl-\\`:

```
$ python -m ipykernel --debug
```

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

5.1.2 IPython options

Any of the options listed here can be set in config files, at the command line, from inside IPython, or using a traitlets `Config` object. See *Setting configurable options* for details.

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

Terminal IPython options

`InteractiveShellApp.code_to_run`

Execute the given command string.

Trait type
Unicode

CLI option
-c

`InteractiveShellApp.exec_PYTHONSTARTUP`

Run the file referenced by the PYTHONSTARTUP environment variable at IPython startup.

Trait type
Bool

Default
True

`InteractiveShellApp.exec_files`

List of files to run at IPython startup.

Trait type
List

`InteractiveShellApp.exec_lines`

lines of code to run at IPython startup.

Trait type
List

`InteractiveShellApp.extensions`

A list of dotted module names of IPython extensions to load.

Trait type
List

InteractiveShellApp.extra_extensions

Dotted module name(s) of one or more IPython extensions to load.

For specifying extra extensions to load on the command-line.

Добавлено в версии 7.10.

Trait type

List

CLI option

--ext

InteractiveShellApp.file_to_run

A file to be run

Trait type

Unicode

InteractiveShellApp.gui

Enable GUI event loop integration with any of („asyncio“, „glut“, „gtk“, „gtk2“, „gtk3“, „gtk4“, „osx“, „pyglet“, „qt“, „qt5“, „qt6“, „tk“, „wx“, „gtk2“, „qt4“).

Options

'asyncio', 'glut', 'gtk', 'gtk2', 'gtk3', 'gtk4', 'osx', 'pyglet', 'qt', 'qt5',
'qt6', 'tk', 'wx', 'gtk2', 'qt4'

CLI option

--gui

InteractiveShellApp.hide_initial_ns

Should variables loaded at startup (by startup files, exec_lines, etc.) be hidden from tools like %who?

Trait type

Bool

Default

True

InteractiveShellApp.ignore_cwd

If True, IPython will not add the current working directory to sys.path. When False, the current working directory is added to sys.path, allowing imports of modules defined in the current directory.

Trait type

Bool

Default

False

CLI option

--ignore-cwd

InteractiveShellApp.matplotlib

Configure matplotlib for interactive use with the default matplotlib backend.

Options

'auto', 'agg', 'gtk', 'gtk3', 'gtk4', 'inline', 'ipyml', 'nbagg', 'notebook',
'osx', 'pdf', 'ps', 'qt', 'qt4', 'qt5', 'qt6', 'svg', 'tk', 'webagg', 'widget',
'wx'

CLI option

--matplotlib

`InteractiveShellApp.module_to_run`

Run the module as a script.

Trait type

Unicode

CLI option

-m

`InteractiveShellApp.pylab`

Pre-load matplotlib and numpy for interactive use, selecting a particular matplotlib backend and loop integration.

Options

'auto', 'agg', 'gtk', 'gtk3', 'gtk4', 'inline', 'ipympl', 'nbagg', 'notebook',
'osx', 'pdf', 'ps', 'qt', 'qt4', 'qt5', 'qt6', 'svg', 'tk', 'webagg', 'widget',
'wx'

CLI option

--pylab

`InteractiveShellApp.pylab_import_all`

If true, IPython will populate the user namespace with numpy, pylab, etc. and an `import *` is done from numpy and pylab, when using pylab mode.

When False, pylab mode should not import any names into the user namespace.

Trait type

Bool

Default

True

`InteractiveShellApp.reraise_ipython_extension_failures`

Reraise exceptions encountered loading IPython extensions?

Trait type

Bool

Default

False

`Application.log_datefmt`

The date format used by logging formatters for `%(asctime)s`

Trait type

Unicode

Default

'%Y-%m-%d %H:%M:%S'

`Application.log_format`

The Logging format template

Trait type

Unicode

Default

'[% (name)s]%(highlevel)s %(message)s'

Application.log_level

Set the log level by value or name.

Options

0, 10, 20, 30, 40, 50, 'DEBUG', 'INFO', 'WARN', 'ERROR', 'CRITICAL'

Default

30

CLI option

--log-level

Application.logging_config

Configure additional log handlers.

The default stderr logs handler is configured by the log_level, log_datefmt and log_format settings.

This configuration can be used to configure additional handlers (e.g. to output the log to a file) or for finer control over the default handlers.

If provided this should be a logging configuration dictionary, for more information see: <https://docs.python.org/3/library/logging.config.html#logging-config-dictschema>

This dictionary is merged with the base logging configuration which defines the following:

- A logging formatter intended for interactive use called `console`.
- A logging handler that writes to stderr called `console` which uses the formatter `console`.
- A logger with the name of this application set to `DEBUG` level.

This example adds a new handler that writes to a file:

```
c.Application.logging_config = {
    'handlers': {
        'file': {
            'class': 'logging.FileHandler',
            'level': 'DEBUG',
            'filename': '<path/to/file>',
        }
    },
    'loggers': {
        '<application-name>': {
            'level': 'DEBUG',
            # NOTE: if you don't list the default "console"
            # handler here then it will be disabled
            'handlers': ['console', 'file'],
        }
    }
}
```

Trait type

Dict

Application.show_config

Instead of starting the Application, dump configuration to stdout

Trait type

Bool

Default

False

CLI option`--show-config``Application.show_config_json`

Instead of starting the Application, dump configuration to stdout (as JSON)

Trait type

Bool

Default

False

CLI option`--show-config-json``BaseIPythonApplication.add_ipython_dir_to_sys_path`

No description

Trait type

Bool

Default

False

`BaseIPythonApplication.auto_create`

Whether to create profile dir if it doesn't exist

Trait type

Bool

Default

False

`BaseIPythonApplication.copy_config_files`

Whether to install the default config files into the profile dir. If a new profile is being created, and IPython contains config files for that profile, then they will be staged into the new directory. Otherwise, default config files will be automatically generated.

Trait type

Bool

Default

False

`BaseIPythonApplication.extra_config_file`

Path to an extra config file to load.

If specified, load this config file in addition to any other IPython config.

Trait type

Unicode

CLI option`--config``BaseIPythonApplication.ipython_dir`

The name of the IPython directory. This directory is used for logging configuration (through profiles), history storage, etc. The default is usually `$HOME/.ipython`. This option can also be specified through the environment variable `IPYTHONDIR`.

Trait type

Unicode

CLI option`--ipython-dir``BaseIPythonApplication.log_datefmt`The date format used by logging formatters for `%(asctime)s`**Trait type**

Unicode

Default`'%Y-%m-%d %H:%M:%S'``BaseIPythonApplication.log_format`

The Logging format template

Trait type

Unicode

Default`'[% (name)s]%(highlevel)s %(message)s'``BaseIPythonApplication.log_level`

Set the log level by value or name.

Options`0, 10, 20, 30, 40, 50, 'DEBUG', 'INFO', 'WARN', 'ERROR', 'CRITICAL'`**Default**`30``BaseIPythonApplication.logging_config`

Configure additional log handlers.

The default stderr logs handler is configured by the `log_level`, `log_datefmt` and `log_format` settings.

This configuration can be used to configure additional handlers (e.g. to output the log to a file) or for finer control over the default handlers.

If provided this should be a logging configuration dictionary, for more information see: <https://docs.python.org/3/library/logging.config.html#logging-config-dictscheme>

This dictionary is merged with the base logging configuration which defines the following:

- A logging formatter intended for interactive use called `console`.
- A logging handler that writes to stderr called `console` which uses the formatter `console`.
- A logger with the name of this application set to `DEBUG` level.

This example adds a new handler that writes to a file:

```
c.Application.logging_config = {
    'handlers': {
        'file': {
            'class': 'logging.FileHandler',
            'level': 'DEBUG',
            'filename': '<path/to/file>',
        }
    },
}
```

(continues on next page)

(продолжение с предыдущей страницы)

```
'loggers': {
    '<application-name>': {
        'level': 'DEBUG',
        # NOTE: if you don't list the default "console"
        # handler here then it will be disabled
        'handlers': ['console', 'file'],
    },
}
```

Trait type

Dict

BaseIPythonApplication.overwrite

Whether to overwrite existing config files when copying

Trait type

Bool

Default

False

BaseIPythonApplication.profile

The IPython profile to use.

Trait type

Unicode

Default

'default'

CLI option

--profile

BaseIPythonApplication.show_config

Instead of starting the Application, dump configuration to stdout

Trait type

Bool

Default

False

BaseIPythonApplication.show_config_json

Instead of starting the Application, dump configuration to stdout (as JSON)

Trait type

Bool

Default

False

BaseIPythonApplication.verbose_crash

Create a massive crash report when IPython encounters what may be an internal error. The default is to append a short message to the usual traceback

Trait type

Bool

Default

False

`TerminalIPythonApp.add_ipython_dir_to_sys_path`

No description

Trait type

Bool

Default

False

`TerminalIPythonApp.code_to_run`

Execute the given command string.

Trait type

Unicode

`TerminalIPythonApp.copy_config_files`

Whether to install the default config files into the profile dir. If a new profile is being created, and IPython contains config files for that profile, then they will be staged into the new directory. Otherwise, default config files will be automatically generated.

Trait type

Bool

Default

False

`TerminalIPythonApp.display_banner`

Whether to display a banner upon starting IPython.

Trait type

Bool

Default

True

CLI option`--banner``TerminalIPythonApp.exec_PYTHONSTARTUP`

Run the file referenced by the PYTHONSTARTUP environment variable at IPython startup.

Trait type

Bool

Default

True

`TerminalIPythonApp.exec_files`

List of files to run at IPython startup.

Trait type

List

`TerminalIPythonApp.exec_lines`

lines of code to run at IPython startup.

Trait type

List

`TerminalIPythonApp.extensions`

A list of dotted module names of IPython extensions to load.

Trait type

List

`TerminalIPythonApp.extra_config_file`

Path to an extra config file to load.

If specified, load this config file in addition to any other IPython config.

Trait type

Unicode

`TerminalIPythonApp.extra_extensions`

Dotted module name(s) of one or more IPython extensions to load.

For specifying extra extensions to load on the command-line.

Добавлено в версии 7.10.

Trait type

List

`TerminalIPythonApp.file_to_run`

A file to be run

Trait type

Unicode

`TerminalIPythonApp.force_interact`

If a command or file is given via the command-line, e.g. „ipython foo.py“, start an interactive shell after executing the file or command.

Trait type

Bool

Default

False

CLI option

-i

`TerminalIPythonApp.gui`

Enable GUI event loop integration with any of („asyncio“, „glut“, „gtk“, „gtk2“, „gtk3“, „gtk4“, „osx“, „pyglet“, „qt“, „qt5“, „qt6“, „tk“, „wx“, „gtk2“, „qt4“).

Options

'asyncio', 'glut', 'gtk', 'gtk2', 'gtk3', 'gtk4', 'osx', 'pyglet', 'qt', 'qt5',
'qt6', 'tk', 'wx', 'gtk2', 'qt4'

`TerminalIPythonApp.hide_initial_ns`

Should variables loaded at startup (by startup files, `exec_lines`, etc.) be hidden from tools like `%who?`

Trait type

Bool

Default

True

TerminalIPythonApp.ignore_cwd

If True, IPython will not add the current working directory to sys.path. When False, the current working directory is added to sys.path, allowing imports of modules defined in the current directory.

Trait type

Bool

Default

False

TerminalIPythonApp.interactive_shell_class

Class to use to instantiate the TerminalInteractiveShell object. Useful for custom Frontends

Trait type

Type

Default

'IPython.terminal.interactiveshell.TerminalInteractiveShell'

TerminalIPythonApp.ipython_dir

The name of the IPython directory. This directory is used for logging configuration (through profiles), history storage, etc. The default is usually \$HOME/.ipython. This option can also be specified through the environment variable IPYTHONDIR.

Trait type

Unicode

TerminalIPythonApp.log_datefmt

The date format used by logging formatters for %(asctime)s

Trait type

Unicode

Default

'%Y-%m-%d %H:%M:%S'

TerminalIPythonApp.log_format

The Logging format template

Trait type

Unicode

Default

'[% (name)s]%(highlevel)s %(message)s'

TerminalIPythonApp.log_level

Set the log level by value or name.

Options

0, 10, 20, 30, 40, 50, 'DEBUG', 'INFO', 'WARN', 'ERROR', 'CRITICAL'

Default

30

TerminalIPythonApp.logging_config

Configure additional log handlers.

The default stderr logs handler is configured by the log_level, log_datefmt and log_format settings.

This configuration can be used to configure additional handlers (e.g. to output the log to a file) or for finer control over the default handlers.

If provided this should be a logging configuration dictionary, for more information see: <https://docs.python.org/3/library/logging.config.html#logging-config-dictschema>

This dictionary is merged with the base logging configuration which defines the following:

- A logging formatter intended for interactive use called `console`.
- A logging handler that writes to stderr called `console` which uses the formatter `console`.
- A logger with the name of this application set to `DEBUG` level.

This example adds a new handler that writes to a file:

```
c.Application.logging_config = {
    'handlers': {
        'file': {
            'class': 'logging.FileHandler',
            'level': 'DEBUG',
            'filename': '<path/to/file>',
        }
    },
    'loggers': {
        '<application-name>': {
            'level': 'DEBUG',
            # NOTE: if you don't list the default "console"
            # handler here then it will be disabled
            'handlers': ['console', 'file'],
        },
    },
}
```

Trait type

Dict

`TerminalIPythonApp.matplotlib`

Configure matplotlib for interactive use with the default matplotlib backend.

Options

'auto', 'agg', 'gtk', 'gtk3', 'gtk4', 'inline', 'ipympl', 'nbagg', 'notebook',
'osx', 'pdf', 'ps', 'qt', 'qt4', 'qt5', 'qt6', 'svg', 'tk', 'webagg', 'widget',
'wx'

`TerminalIPythonApp.module_to_run`

Run the module as a script.

Trait type

Unicode

`TerminalIPythonApp.overwrite`

Whether to overwrite existing config files when copying

Trait type

Bool

Default

False

TerminalIPythonApp.profile

The IPython profile to use.

Trait type

Unicode

Default

'default'

TerminalIPythonApp.pylab

Pre-load matplotlib and numpy for interactive use, selecting a particular matplotlib backend and loop integration.

Options

'auto', 'agg', 'gtk', 'gtk3', 'gtk4', 'inline', 'ipympl', 'nbagg', 'notebook',
'osx', 'pdf', 'ps', 'qt', 'qt4', 'qt5', 'qt6', 'svg', 'tk', 'webagg', 'widget',
'wx'

TerminalIPythonApp.pylab_import_all

If true, IPython will populate the user namespace with numpy, pylab, etc. and an `import *` is done from numpy and pylab, when using pylab mode.

When False, pylab mode should not import any names into the user namespace.

Trait type

Bool

Default

True

TerminalIPythonApp.quick

Start IPython quickly by skipping the loading of config files.

Trait type

Bool

Default

False

CLI option

--quick

TerminalIPythonApp.reraise_ipython_extension_failures

Reraise exceptions encountered loading IPython extensions?

Trait type

Bool

Default

False

TerminalIPythonApp.show_config

Instead of starting the Application, dump configuration to stdout

Trait type

Bool

Default

False

`TerminalIPythonApp.show_config_json`

Instead of starting the Application, dump configuration to stdout (as JSON)

Trait type

Bool

Default

False

`TerminalIPythonApp.verbose_crash`

Create a massive crash report when IPython encounters what may be an internal error. The default is to append a short message to the usual traceback

Trait type

Bool

Default

False

`InteractiveShell.ast_node_interactivity`

„all“, „last“, „last_expr“ or „none“, „last_expr_or_assign“ specifying which nodes should be run interactively (displaying output from expressions).

Options

'all', 'last', 'last_expr', 'none', 'last_expr_or_assign'

Default

'last_expr'

`InteractiveShell.ast_transformers`

A list of `ast.NodeTransformer` subclass instances, which will be applied to user input before code is run.

Trait type

List

`InteractiveShell.autoawait`

Automatically run `await` statement in the top level repl.

Trait type

Bool

Default

True

`InteractiveShell.autocall`

Make IPython automatically call any callable object even if you didn't type explicit parentheses. For example, „str 43“ becomes „str(43)“ automatically. The value can be „0“ to disable the feature, „1“ for „smart“ autocall, where it is not applied if there are no more arguments on the line, and „2“ for „full“ autocall, where all callable objects are automatically called (even if no arguments are present).

Options

0, 1, 2

Default

0

CLI option

--autocall

`InteractiveShell.autoindent`

Autoindent IPython code entered interactively.

Trait type

Bool

Default

True

CLI option

--autoindent

`InteractiveShell.automagic`

Enable magic commands to be called without the leading %.

Trait type

Bool

Default

True

CLI option

--automagic

`InteractiveShell.banner1`

The part of the banner to be printed before the profile

Trait type

Unicode

Default

"Python 3.10.6 | packaged by conda-forge | (main, Aug 22 2022..."

`InteractiveShell.banner2`

The part of the banner to be printed after the profile

Trait type

Unicode

`InteractiveShell.cache_size`

Set the size of the output cache. The default is 1000, you can change it permanently in your config file. Setting it to 0 completely disables the caching system, and the minimum value accepted is 3 (if you provide a value less than 3, it is reset to 0 and a warning is issued). This limit is defined because otherwise you'll spend more time re-flushing a too small cache than working

Trait type

Int

Default

1000

CLI option

--cache-size

`InteractiveShell.color_info`

Use colors for displaying information about objects. Because this information is passed through a pager (like „less“), and some pagers get confused with color codes, this capability can be turned off.

Trait type

Bool

Default

True

CLI option`--color-info``InteractiveShell.colors`

Set the color scheme (NoColor, Neutral, Linux, or LightBG).

Options

'Neutral', 'NoColor', 'LightBG', 'Linux'

Default

'Neutral'

CLI option`--colors``InteractiveShell.debug`

No description

Trait type

Bool

Default

False

`InteractiveShell.disable_failing_post_execute`

Don't call post-execute functions that have failed in the past.

Trait type

Bool

Default

False

`InteractiveShell.display_page`

If True, anything that would be passed to the pager will be displayed as regular output instead.

Trait type

Bool

Default

False

`InteractiveShell.enable_html_pager`

(Provisional API) enables html representation in mime bundles sent to pagers.

Trait type

Bool

Default

False

`InteractiveShell.history_length`

Total length of command history

Trait type

Int

Default

10000

`InteractiveShell.history_load_length`

The number of saved history entries to be loaded into the history buffer at startup.

Trait type

Int

Default

1000

`InteractiveShell.inspector_class`

Class to use to instantiate the shell inspector

Trait type

Type

Default

'IPython.core.oinspect.Inspector'

`InteractiveShell.ipython_dir`

No description

Trait type

Unicode

`InteractiveShell.logappend`

Start logging to the given file in append mode. Use `logfile` to specify a log file to **overwrite** logs to.

Trait type

Unicode

CLI option

--logappend

`InteractiveShell.logfile`

The name of the logfile to use.

Trait type

Unicode

CLI option

--logfile

`InteractiveShell.logstart`

Start logging to the default log file in overwrite mode. Use `logappend` to specify a log file to **append** logs to.

Trait type

Bool

Default

False

`InteractiveShell.loop_runner`

Select the loop runner that will be used to execute top-level asynchronous code

Trait type

Any

Default

'IPython.core.interactiveshell._asyncio_runner'

`InteractiveShell.object_info_string_level`

No description

Options

0, 1, 2

Default

0

`InteractiveShell.pdb`

Automatically call the pdb debugger after every exception.

Trait type

Bool

Default

False

CLI option

--pdb

`InteractiveShell.quiet`

No description

Trait type

Bool

Default

False

`InteractiveShell.separate_in`

No description

Trait type

SeparateUnicode

Default

'\\n'

`InteractiveShell.separate_out`

No description

Trait type

SeparateUnicode

`InteractiveShell.separate_out2`

No description

Trait type

SeparateUnicode

`InteractiveShell.show_rewritten_input`

Show rewritten input, e.g. for autocall.

Trait type

Bool

Default

True

`InteractiveShell.sphinxify_docstring`

Enables rich html representation of docstrings. (This requires the docrepr module).

Trait type

Bool

Default

False

`InteractiveShell.warn_venv`

Warn if running in a virtual environment with no IPython installed (so IPython from the global environment is used).

Trait type

Bool

Default

True

`InteractiveShell.wildcards_case_sensitive`

No description

Trait type

Bool

Default

True

`InteractiveShell.xmode`

Switch modes for the IPython exception handlers.

Options

'Context', 'Plain', 'Verbose', 'Minimal'

Default

'Context'

`TerminalInteractiveShell.ast_node_interactivity`

„all“, „last“, „last_expr“ or „none“, „last_expr_or_assign“ specifying which nodes should be run interactively (displaying output from expressions).

Options

'all', 'last', 'last_expr', 'none', 'last_expr_or_assign'

Default

'last_expr'

`TerminalInteractiveShell.ast_transformers`

A list of ast.NodeTransformer subclass instances, which will be applied to user input before code is run.

Trait type

List

`TerminalInteractiveShell.auto_match`

Automatically add/delete closing bracket or quote when opening bracket or quote is entered/deleted. Brackets: (), [], {} Quotes: „, «»

Trait type

Bool

Default

False

`TerminalInteractiveShell.autoawait`

Automatically run await statement in the top level repl.

Trait type

Bool

Default

True

`TerminalInteractiveShell.autocall`

Make IPython automatically call any callable object even if you didn't type explicit parentheses. For example, „str 43“ becomes „str(43)“ automatically. The value can be „0“ to disable the feature, „1“ for „smart“ autocall, where it is not applied if there are no more arguments on the line, and „2“ for „full“ autocall, where all callable objects are automatically called (even if no arguments are present).

Options

0, 1, 2

Default

0

`TerminalInteractiveShell.autoformatter`

Autoformatter to reformat Terminal code. Can be 'black', 'yapf' or None

Trait type

Unicode

`TerminalInteractiveShell.autoindent`

Autoindent IPython code entered interactively.

Trait type

Bool

Default

True

`TerminalInteractiveShell.automagic`

Enable magic commands to be called without the leading %.

Trait type

Bool

Default

True

`TerminalInteractiveShell.autosuggestions_provider`

Specifies from which source automatic suggestions are provided. Can be set to 'NavigableAutoSuggestFromHistory' (up and down swap suggestions), 'AutoSuggestFromHistory', or None to disable automatic suggestions. Default is 'NavigableAutoSuggestFromHistory'.

Trait type

Unicode

Default

'NavigableAutoSuggestFromHistory'

TerminalInteractiveShell.banner1

The part of the banner to be printed before the profile

Trait type
Unicode

Default
"Python 3.10.6 | packaged by conda-forge | (main, Aug 22 2022..."

TerminalInteractiveShell.banner2

The part of the banner to be printed after the profile

Trait type
Unicode

TerminalInteractiveShell.cache_size

Set the size of the output cache. The default is 1000, you can change it permanently in your config file. Setting it to 0 completely disables the caching system, and the minimum value accepted is 3 (if you provide a value less than 3, it is reset to 0 and a warning is issued). This limit is defined because otherwise you'll spend more time re-flushing a too small cache than working

Trait type
Int

Default
1000

TerminalInteractiveShell.color_info

Use colors for displaying information about objects. Because this information is passed through a pager (like „less“), and some pagers get confused with color codes, this capability can be turned off.

Trait type
Bool

Default
True

TerminalInteractiveShell.colors

Set the color scheme (NoColor, Neutral, Linux, or LightBG).

Options
'Neutral', 'NoColor', 'LightBG', 'Linux'

Default
'Neutral'

TerminalInteractiveShell.confirm_exit

Set to confirm when you try to exit IPython with an EOF (Control-D in Unix, Control-Z/Enter in Windows). By typing „exit“ or „quit“, you can force a direct exit without any confirmation.

Trait type
Bool

Default
True

CLI option
--confirm-exit

TerminalInteractiveShell.debug

No description

Trait type

Bool

Default

False

`TerminalInteractiveShell.debugger_history_file`

File in which to store and read history

Trait type

Unicode

Default

'~/pdbhistory'

`TerminalInteractiveShell.disable_failing_post_execute`

Don't call post-execute functions that have failed in the past.

Trait type

Bool

Default

False

`TerminalInteractiveShell.display_completions`Options for displaying tab completions, „column“, „multicolumn“, and „readlinelike“. These options are for `prompt_toolkit`, see `prompt_toolkit` documentation for more information.**Options**

'column', 'multicolumn', 'readlinelike'

Default

'multicolumn'

`TerminalInteractiveShell.display_page`

If True, anything that would be passed to the pager will be displayed as regular output instead.

Trait type

Bool

Default

False

`TerminalInteractiveShell.editing_mode`

Shortcut style to use at the prompt. „vi“ or „emacs“.

Trait type

Unicode

Default

'emacs'

`TerminalInteractiveShell.editor`

Set the editor used by IPython (default to \$EDITOR/vi/notepad).

Trait type

Unicode

Default

'vi'

`TerminalInteractiveShell.emacs_bindings_in_vi_insert_mode`

Add shortcuts from „emacs“ insert mode to „vi“ insert mode.

Trait type

Bool

Default

True

`TerminalInteractiveShell.enable_history_search`

Allows to enable/disable the prompt toolkit history search

Trait type

Bool

Default

True

`TerminalInteractiveShell.enable_html_pager`

(Provisional API) enables html representation in mime bundles sent to pagers.

Trait type

Bool

Default

False

`TerminalInteractiveShell.extra_open_editor_shortcuts`

Enable vi (v) or Emacs (C-X C-E) shortcuts to open an external editor. This is in addition to the F2 binding, which is always enabled.

Trait type

Bool

Default

False

`TerminalInteractiveShell.handle_return`

Provide an alternative handler to be called when the user presses Return. This is an advanced option intended for debugging, which may be changed or removed in later releases.

Trait type

Any

`TerminalInteractiveShell.highlight_matching_brackets`

Highlight matching brackets.

Trait type

Bool

Default

True

`TerminalInteractiveShell.highlighting_style`

The name or class of a Pygments style to use for syntax highlighting. To see available styles, run `pygmentize -L styles`.

Trait type

Union

`TerminalInteractiveShell.highlighting_style_overrides`

Override highlighting format for specific tokens

Trait type

Dict

`TerminalInteractiveShell.history_length`

Total length of command history

Trait type

Int

Default

10000

`TerminalInteractiveShell.history_load_length`

The number of saved history entries to be loaded into the history buffer at startup.

Trait type

Int

Default

1000

`TerminalInteractiveShell.inspector_class`

Class to use to instantiate the shell inspector

Trait type

Type

Default

'IPython.core.oinspect.Inspector'

`TerminalInteractiveShell.ipython_dir`

No description

Trait type

Unicode

`TerminalInteractiveShell.logappend`

Start logging to the given file in append mode. Use `logfile` to specify a log file to **overwrite** logs to.

Trait type

Unicode

`TerminalInteractiveShell.logfile`

The name of the logfile to use.

Trait type

Unicode

`TerminalInteractiveShell.logstart`

Start logging to the default log file in overwrite mode. Use `logappend` to specify a log file to **append** logs to.

Trait type

Bool

Default

False

`TerminalInteractiveShell.loop_runner`

Select the loop runner that will be used to execute top-level asynchronous code

Trait type

Any

Default

'IPython.core.interactiveshell._asyncio_runner'

`TerminalInteractiveShell.mime_renderers`

No description

Trait type

Dict

`TerminalInteractiveShell.modal_cursor`

Cursor shape changes depending on vi mode: beam in vi insert mode, block in nav mode, underscore in replace mode.

Trait type

Bool

Default

True

`TerminalInteractiveShell.mouse_support`

Enable mouse support in the prompt (Note: prevents selecting text with the mouse)

Trait type

Bool

Default

False

`TerminalInteractiveShell.object_info_string_level`

No description

Options

0, 1, 2

Default

0

`TerminalInteractiveShell.pdb`

Automatically call the pdb debugger after every exception.

Trait type

Bool

Default

False

`TerminalInteractiveShell.prompt_includes_vi_mode`

Display the current vi mode (when using vi editing mode).

Trait type

Bool

Default

True

`TerminalInteractiveShell.prompts_class`

Class used to generate Prompt token for `prompt_toolkit`

Trait type

Type

Default

'IPython.terminal.prompts.Prompts'

`TerminalInteractiveShell.quiet`

No description

Trait type

Bool

Default

False

`TerminalInteractiveShell.separate_in`

No description

Trait type

SeparateUnicode

Default

'\\n'

`TerminalInteractiveShell.separate_out`

No description

Trait type

SeparateUnicode

`TerminalInteractiveShell.separate_out2`

No description

Trait type

SeparateUnicode

`TerminalInteractiveShell.shortcuts`

Add, disable or modifying shortcuts.

Each entry on the list should be a dictionary with `command` key identifying the target function executed by the shortcut and at least one of the following:

- `match_keys`: list of keys used to match an existing shortcut,
- `match_filter`: shortcut filter used to match an existing shortcut,
- `new_keys`: list of keys to set,
- `new_filter`: a new shortcut filter to set

The filters have to be composed of pre-defined verbs and joined by one of the following conjunctions: `&` (and), `|` (or), `~` (not). The pre-defined verbs are:

- `always`
- `never`
- `has_line_below`
- `has_line_above`
- `has_selection`

- `has_suggestion`
- `vi_mode`
- `vi_insert_mode`
- `emacs_insert_mode`
- `emacs_like_insert_mode`
- `has_completions`
- `insert_mode`
- `default_buffer_focused`
- `search_buffer_focused`
- `ebivim`
- `supports_suspend`
- `is_windows_os`
- `auto_match`
- `focused_insert`
- `not_inside_unclosed_string`
- `readline_like_completions`
- `preceded_by_paired_double_quotes`
- `preceded_by_paired_single_quotes`
- `preceded_by_raw_str_prefix`
- `preceded_by_two_double_quotes`
- `preceded_by_two_single_quotes`
- `followed_by_closing_paren_or_end`
- `preceded_by_opening_round_paren`
- `preceded_by_opening_bracket`
- `preceded_by_opening_brace`
- `preceded_by_double_quote`
- `preceded_by_single_quote`
- `followed_by_closing_round_paren`
- `followed_by_closing_bracket`
- `followed_by_closing_brace`
- `followed_by_double_quote`
- `followed_by_single_quote`
- `navigable_suggestions`
- `cursor_in_leading_ws`

To disable a shortcut set `new_keys` to an empty list. To add a shortcut add key `create` with value `True`.

When modifying/disabling shortcuts, `match_keys/match_filter` can be omitted if the provided specification uniquely identifies a shortcut to be modified/disabled. When modifying a shortcut `new_filter` or `new_keys` can be omitted which will result in reuse of the existing filter/keys.

Only shortcuts defined in IPython (and not default prompt-toolkit shortcuts) can be modified or disabled. The full list of shortcuts, command identifiers and filters is available under *IPython shortcuts*.

Trait type

List

TerminalInteractiveShell.show_rewritten_input

Show rewritten input, e.g. for autocall.

Trait type

Bool

Default

True

TerminalInteractiveShell.simple_promptUse `raw_input` for the REPL, without completion and prompt colors.

Useful when controlling IPython as a subprocess, and piping STDIN/OUT/ERR. Known usage are: IPython own testing machinery, and emacs inferior-shell integration through elpy.

This mode default to `True` if the `IPY_TEST_SIMPLE_PROMPT` environment variable is set, or the current terminal is not a tty.

Trait type

Bool

Default

True

CLI option`--simple-prompt`**TerminalInteractiveShell.space_for_menu**

Number of line at the bottom of the screen to reserve for the tab completion menu, search history, ...etc, the height of these menus will at most this value. Increase it is you prefer long and skinny menus, decrease for short and wide.

Trait type

Int

Default

6

TerminalInteractiveShell.sphinxify_docstringEnables rich html representation of docstrings. (This requires the `docrepr` module).**Trait type**

Bool

Default

False

TerminalInteractiveShell.term_title

Automatically set the terminal title

Trait type

Bool

Default

True

CLI option`--term-title``TerminalInteractiveShell.term_title_format`

Customize the terminal title format. This is a python format string. Available substitutions are: {cwd}.

Trait type

Unicode

Default

'IPython: {cwd}'

`TerminalInteractiveShell.timeoutlen`

The time in milliseconds that is waited for a mapped key sequence to complete.

Trait type

Float

Default

0.5

`TerminalInteractiveShell.true_color`

Use 24bit colors instead of 256 colors in prompt highlighting. If your terminal supports true color, the following command should print TRUECOLOR in orange:

```
printf "\x1b[38;2;255;100;0mTRUECOLOR\x1b[0m\n"
```

Trait type

Bool

Default

False

`TerminalInteractiveShell.ttimeoutlen`

The time in milliseconds that is waited for a key code to complete.

Trait type

Float

Default

0.01

`TerminalInteractiveShell.warn_venv`

Warn if running in a virtual environment with no IPython installed (so IPython from the global environment is used).

Trait type

Bool

Default

True

`TerminalInteractiveShell.wildcards_case_sensitive`

No description

Trait type

Bool

Default

True

`TerminalInteractiveShell.xmode`

Switch modes for the IPython exception handlers.

Options

'Context', 'Plain', 'Verbose', 'Minimal'

Default

'Context'

`HistoryAccessor.connection_options`

Options for configuring the SQLite connection

These options are passed as keyword args to `sqlite3.connect` when establishing database connections.

Trait type

Dict

`HistoryAccessor.enabled`

enable the SQLite history

set `enabled=False` to disable the SQLite history, in which case there will be no stored history, no SQLite connection, and no background saving thread. This may be necessary in some threaded environments where IPython is embedded.

Trait type

Bool

Default

True

`HistoryAccessor.hist_file`

Path to file to use for SQLite history database.

By default, IPython will put the history database in the IPython profile directory. If you would rather share one history among profiles, you can set this value in each, so that they are consistent.

Due to an issue with `fcntl`, SQLite is known to misbehave on some NFS mounts. If you see IPython hanging, try setting this to something on a local disk, e.g:

```
ipython --HistoryManager.hist_file=/tmp/ipython_hist.sqlite
```

you can also use the specific value `:memory:` (including the colon at both end but not the back ticks), to avoid creating an history file.

Trait type

Union

`HistoryManager.connection_options`

Options for configuring the SQLite connection

These options are passed as keyword args to `sqlite3.connect` when establishing database connections.

Trait type

Dict

`HistoryManager.db_cache_size`

Write to database every x commands (higher values save disk access & power). Values of 1 or less effectively disable caching.

Trait type

Int

Default

0

`HistoryManager.db_log_output`

Should the history database include output? (default: no)

Trait type

Bool

Default

False

`HistoryManager.enabled`

enable the SQLite history

set `enabled=False` to disable the SQLite history, in which case there will be no stored history, no SQLite connection, and no background saving thread. This may be necessary in some threaded environments where IPython is embedded.

Trait type

Bool

Default

True

`HistoryManager.hist_file`

Path to file to use for SQLite history database.

By default, IPython will put the history database in the IPython profile directory. If you would rather share one history among profiles, you can set this value in each, so that they are consistent.

Due to an issue with `fcntl`, SQLite is known to misbehave on some NFS mounts. If you see IPython hanging, try setting this to something on a local disk, e.g:

```
ipython --HistoryManager.hist_file=/tmp/ipython_hist.sqlite
```

you can also use the specific value `:memory:` (including the colon at both end but not the back ticks), to avoid creating an history file.

Trait type

Union

`MagicsManager.auto_magic`

Automatically call line magics without requiring explicit `%` prefix

Trait type

Bool

Default

True

MagicsManager.lazy_magics

Mapping from magic names to modules to load.

This can be used in IPython/IPykernel configuration to declare lazy magics that will only be imported/registered on first use.

For example:

```
c.MagicsManager.lazy_magics = {
    "my_magic": "slow.to.import",
    "my_other_magic": "also.slow",
}
```

On first invocation of `%my_magic`, `%%my_magic`, `%%my_other_magic` or `%%my_other_magic`, the corresponding module will be loaded as an ipython extensions as if you had previously done `%load_ext ipython`.

Magics names should be without percent(s) as magics can be both cell and line magics.

Lazy loading happen relatively late in execution process, and complex extensions that manipulate Python/IPython internal state or global state might not support lazy loading.

Trait type

Dict

ProfileDir.location

Set the profile location directly. This overrides the logic used by the `profile` option.

Trait type

Unicode

CLI option

--profile-dir

BaseFormatter.deferred_printers

No description

Trait type

Dict

BaseFormatter.enabled

No description

Trait type

Bool

Default

True

BaseFormatter.singleton_printers

No description

Trait type

Dict

BaseFormatter.type_printers

No description

Trait type

Dict

`PlainTextFormatter.deferred_printers`

No description

Trait type

Dict

`PlainTextFormatter.float_precision`

No description

Trait type

CUnicode

`PlainTextFormatter.max_seq_length`

Truncate large collections (lists, dicts, tuples, sets) to this size.

Set to 0 to disable truncation.

Trait type

Int

Default

1000

`PlainTextFormatter.max_width`

No description

Trait type

Int

Default

79

`PlainTextFormatter.newline`

No description

Trait type

Unicode

Default

'\\n'

`PlainTextFormatter.pprint`

No description

Trait type

Bool

Default

True

CLI option

--pprint

`PlainTextFormatter.singleton_printers`

No description

Trait type

Dict

`PlainTextFormatter.type_printers`

No description

Trait type

Dict

`PlainTextFormatter.verbose`

No description

Trait type

Bool

Default

False

`Completer.auto_close_dict_keys`

Enable auto-closing dictionary keys.

When enabled string keys will be suffixed with a final quote (matching the opening quote), tuple keys will also receive a separating comma if needed, and keys which are final will receive a closing bracket (`()`).

Trait type

Bool

Default

False

`Completer.backslash_combining_completions`

Enable unicode completions, e.g. `alpha<tab>` . Includes completion of latex commands, unicode names, and expanding unicode characters back to latex commands.

Trait type

Bool

Default

True

`Completer.debug`

Enable debug for the Completer. Mostly print extra information for experimental jedi integration.

Trait type

Bool

Default

False

`Completer.evaluation`

Policy for code evaluation under completion.

Successive options allow to enable more eager evaluation for better completion suggestions, including for nested dictionaries, nested lists, or even results of function calls. Setting `unsafe` or higher can lead to evaluation of arbitrary user code on `Tab` with potentially unwanted or dangerous side effects.

Allowed values are:

- **forbidden**: no evaluation of code is permitted,
- **minimal**: evaluation of literals and access to built-in namespace; no item/attribute evaluation, no access to locals/globals, no evaluation of any operations or comparisons.
- **limited**: access to all namespaces, evaluation of hard-coded methods (for example: `dict.keys`, `object.__getattr__`, `object.__getitem__`) on allow-listed objects (for example: `dict`, `list`, `tuple`, `pandas.Series`),

- **unsafe**: evaluation of all methods and function calls but not of syntax with side-effects like `del x`,
- **dangerous**: completely arbitrary evaluation.

Options

'forbidden', 'minimal', 'limited', 'unsafe', 'dangerous'

Default

'limited'

Completer.greedy

Activate greedy completion.

Не рекомендуется, начиная с версии 8.8: Use `Completer.evaluation` and `Completer.auto_close_dict_keys` instead.

When enabled in IPython 8.8 or newer, changes configuration as follows:

- `Completer.evaluation = 'unsafe'`
- `Completer.auto_close_dict_keys = True`

Trait type

Bool

Default

False

Completer.jedi_compute_type_timeout

Experimental: restrict time (in milliseconds) during which Jedi can compute types. Set to 0 to stop computing types. Non-zero value lower than 100ms may hurt performance by preventing jedi to build its cache.

Trait type

Int

Default

400

Completer.use_jedi

Experimental: Use Jedi to generate autocompletions. Default to True if jedi is installed.

Trait type

Bool

Default

True

IPCompleter.auto_close_dict_keys

Enable auto-closing dictionary keys.

When enabled string keys will be suffixed with a final quote (matching the opening quote), tuple keys will also receive a separating comma if needed, and keys which are final will receive a closing bracket (]).

Trait type

Bool

Default

False

`IPCompleter.backslash_combining_completions`

Enable unicode completions, e.g. `alpha<tab>` . Includes completion of latex commands, unicode names, and expanding unicode characters back to latex commands.

Trait type

Bool

Default

True

`IPCompleter.debug`

Enable debug for the Completer. Mostly print extra information for experimental jedi integration.

Trait type

Bool

Default

False

`IPCompleter.disable_matchers`

List of matchers to disable.

The list should contain matcher identifiers (see *completion_matcher*).

Trait type

List

`IPCompleter.evaluation`

Policy for code evaluation under completion.

Successive options allow to enable more eager evaluation for better completion suggestions, including for nested dictionaries, nested lists, or even results of function calls. Setting **unsafe** or higher can lead to evaluation of arbitrary user code on **Tab** with potentially unwanted or dangerous side effects.

Allowed values are:

- **forbidden**: no evaluation of code is permitted,
- **minimal**: evaluation of literals and access to built-in namespace; no item/attribute evaluation, no access to locals/globals, no evaluation of any operations or comparisons.
- **limited**: access to all namespaces, evaluation of hard-coded methods (for example: `dict.keys`, `object.__getattr__`, `object.__getitem__`) on allow-listed objects (for example: `dict`, `list`, `tuple`, `pandas.Series`),
- **unsafe**: evaluation of all methods and function calls but not of syntax with side-effects like `del x`,
- **dangerous**: completely arbitrary evaluation.

Options

'forbidden', 'minimal', 'limited', 'unsafe', 'dangerous'

Default

'limited'

`IPCompleter.greedy`

Activate greedy completion.

Не рекомендуется, начиная с версии 8.8: Use *Completer.evaluation* and *Completer.auto_close_dict_keys* instead.

When enabled in IPython 8.8 or newer, changes configuration as follows:

- `Completer.evaluation = 'unsafe'`
- `Completer.auto_close_dict_keys = True`

Trait type

Bool

Default

False

`IPCompleter.jedi_compute_type_timeout`

Experimental: restrict time (in milliseconds) during which Jedi can compute types. Set to 0 to stop computing types. Non-zero value lower than 100ms may hurt performance by preventing jedi to build its cache.

Trait type

Int

Default

400

`IPCompleter.limit_to_all__`

DEPRECATED as of version 5.0.

Instruct the completer to use `__all__` for the completion

Specifically, when completing on `object.<tab>`.

When True: only those names in `obj.__all__` will be included.

When False [default]: the `__all__` attribute is ignored

Trait type

Bool

Default

False

`IPCompleter.merge_completions`

Whether to merge completion results into a single list

If False, only the completion results from the first non-empty completer will be returned.

As of version 8.6.0, setting the value to False is an alias for: `IPCompleter.suppress_competing_matchers = True..`

Trait type

Bool

Default

True

`IPCompleter.omit__names`

Instruct the completer to omit private method names

Specifically, when completing on `object.<tab>`.

When 2 [default]: all names that start with „`_`“ will be excluded.

When 1: all „magic“ names (`__foo__`) will be excluded.

When 0: nothing will be excluded.

Options

0, 1, 2

Default

2

`IPCompleter.profile_completions`

If True, emit profiling data for completion subsystem using cProfile.

Trait type

Bool

Default

False

`IPCompleter.profiler_output_dir`

Template for path at which to output profile data for completions.

Trait type

Unicode

Default

'.completion_profiles'

`IPCompleter.suppress_competing_matchers`

Whether to suppress completions from other *Matchers*.

When set to **None** (default) the matchers will attempt to auto-detect whether suppression of other matchers is desirable. For example, at the beginning of a line followed by % we expect a magic completion to be the only applicable option, and after `my_dict['` we usually expect a completion with an existing dictionary key.

If you want to disable this heuristic and see completions from all matchers, set `IPCompleter.suppress_competing_matchers = False`. To disable the heuristic for specific matchers provide a dictionary mapping: `IPCompleter.suppress_competing_matchers = {'IPCompleter.dict_key_matcher': False}`.

Set `IPCompleter.suppress_competing_matchers = True` to limit completions to the set of matchers with the highest priority; this is equivalent to `IPCompleter.merge_completions` and can be beneficial for performance, but will sometimes omit relevant candidates from matchers further down the priority list.

Trait type

Union

`IPCompleter.use_jedi`

Experimental: Use Jedi to generate autocompletions. Default to True if jedi is installed.

Trait type

Bool

Default

True

`ScriptMagics.script_magics`

Extra script cell magics to define

This generates simple wrappers of `%%script foo` as `%%foo`.

If you want to add script magics that aren't on your path, specify them in `script_paths`

Trait type

List

`ScriptMagics.script_paths`

Dict mapping short „ruby“ names to full paths, such as „/opt/secret/bin/ruby“

Only necessary for items in `script_magics` where the default path will not find the right interpreter.**Trait type**

Dict

`LoggingMagics.quiet`

Suppress output of log state when logging is enabled

Trait type

Bool

Default

False

`StoreMagics.autorestore`

If True, any %store-d variables will be automatically restored when IPython starts.

Trait type

Bool

Default

False

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

IPython kernel options

These options can be used in `ipython_kernel_config.py`. The kernel also respects any options in `ipython_config.py`

`ConnectionFileMixin.connection_file`

JSON file in which to store connection info [default: kernel-<pid>.json]

This file will contain the IP, ports, and authentication key needed to connect clients to this kernel. By default, this file will be created in the security dir of the current profile, but can be specified by absolute path.

Trait type

Unicode

`ConnectionFileMixin.control_port`

set the control (ROUTER) port [default: random]

Trait type

Int

Default

0

ConnectionFileMixin.hb_port

set the heartbeat port [default: random]

Trait type

Int

Default

0

ConnectionFileMixin.iopub_port

set the iopub (PUB) port [default: random]

Trait type

Int

Default

0

ConnectionFileMixin.ip

Set the kernel's IP address [default localhost]. If the IP address is something other than localhost, then Consoles on other machines will be able to connect to the Kernel, so be careful!

Trait type

Unicode

ConnectionFileMixin.shell_port

set the shell (ROUTER) port [default: random]

Trait type

Int

Default

0

ConnectionFileMixin.stdin_port

set the stdin (ROUTER) port [default: random]

Trait type

Int

Default

0

ConnectionFileMixin.transport

No description

Options

'tcp', 'ipc'

Default

'tcp'

InteractiveShellApp.code_to_run

Execute the given command string.

Trait type
Unicode

CLI option
-c

`InteractiveShellApp.exec_PYTHONSTARTUP`

Run the file referenced by the PYTHONSTARTUP environment variable at IPython startup.

Trait type
Bool

Default
True

`InteractiveShellApp.exec_files`

List of files to run at IPython startup.

Trait type
List

`InteractiveShellApp.exec_lines`

lines of code to run at IPython startup.

Trait type
List

`InteractiveShellApp.extensions`

A list of dotted module names of IPython extensions to load.

Trait type
List

`InteractiveShellApp.extra_extensions`

Dotted module name(s) of one or more IPython extensions to load.

For specifying extra extensions to load on the command-line.

Добавлено в версии 7.10.

Trait type
List

CLI option
--ext

`InteractiveShellApp.file_to_run`

A file to be run

Trait type
Unicode

`InteractiveShellApp.gui`

Enable GUI event loop integration with any of („asyncio“, „glut“, „gtk“, „gtk2“, „gtk3“, „gtk4“, „osx“, „pyglet“, „qt“, „qt5“, „qt6“, „tk“, „wx“, „gtk2“, „qt4“).

Options

'asyncio', 'glut', 'gtk', 'gtk2', 'gtk3', 'gtk4', 'osx', 'pyglet', 'qt', 'qt5',
'qt6', 'tk', 'wx', 'gtk2', 'qt4'

CLI option
--gui

`InteractiveShellApp.hide_initial_ns`

Should variables loaded at startup (by startup files, `exec_lines`, etc.) be hidden from tools like `%who?`

Trait type

Bool

Default

True

`InteractiveShellApp.ignore_cwd`

If True, IPython will not add the current working directory to `sys.path`. When False, the current working directory is added to `sys.path`, allowing imports of modules defined in the current directory.

Trait type

Bool

Default

False

CLI option

--ignore-cwd

`InteractiveShellApp.matplotlib`

Configure matplotlib for interactive use with the default matplotlib backend.

Options

'auto', 'agg', 'gtk', 'gtk3', 'gtk4', 'inline', 'ipympl', 'nbagg', 'notebook',
'osx', 'pdf', 'ps', 'qt', 'qt4', 'qt5', 'qt6', 'svg', 'tk', 'webagg', 'widget',
'wx'

CLI option

--matplotlib

`InteractiveShellApp.module_to_run`

Run the module as a script.

Trait type

Unicode

CLI option

-m

`InteractiveShellApp.pylab`

Pre-load matplotlib and numpy for interactive use, selecting a particular matplotlib backend and loop integration.

Options

'auto', 'agg', 'gtk', 'gtk3', 'gtk4', 'inline', 'ipympl', 'nbagg', 'notebook',
'osx', 'pdf', 'ps', 'qt', 'qt4', 'qt5', 'qt6', 'svg', 'tk', 'webagg', 'widget',
'wx'

CLI option

--pylab

`InteractiveShellApp.pylab_import_all`

If true, IPython will populate the user namespace with numpy, pylab, etc. and an `import *` is done from numpy and pylab, when using pylab mode.

When False, pylab mode should not import any names into the user namespace.

Trait type

Bool

Default

True

`InteractiveShellApp.reraise_ipython_extension_failures`

Reraise exceptions encountered loading IPython extensions?

Trait type

Bool

Default

False

`Application.log_datefmt`The date format used by logging formatters for `%(asctime)s`**Trait type**

Unicode

Default`'%Y-%m-%d %H:%M:%S'``Application.log_format`

The Logging format template

Trait type

Unicode

Default`'[%s]%(levelname)s %(message)s'``Application.log_level`

Set the log level by value or name.

Options

0, 10, 20, 30, 40, 50, 'DEBUG', 'INFO', 'WARN', 'ERROR', 'CRITICAL'

Default

30

CLI option`--log-level``Application.logging_config`

Configure additional log handlers.

The default stderr logs handler is configured by the `log_level`, `log_datefmt` and `log_format` settings.

This configuration can be used to configure additional handlers (e.g. to output the log to a file) or for finer control over the default handlers.

If provided this should be a logging configuration dictionary, for more information see: <https://docs.python.org/3/library/logging.config.html#logging-config-dictschema>

This dictionary is merged with the base logging configuration which defines the following:

- A logging formatter intended for interactive use called `console`.
- A logging handler that writes to stderr called `console` which uses the formatter `console`.
- A logger with the name of this application set to `DEBUG` level.

This example adds a new handler that writes to a file:

```
c.Application.logging_config = {
    'handlers': {
        'file': {
            'class': 'logging.FileHandler',
            'level': 'DEBUG',
            'filename': '<path/to/file>',
        }
    },
    'loggers': {
        '<application-name>': {
            'level': 'DEBUG',
            # NOTE: if you don't list the default "console"
            # handler here then it will be disabled
            'handlers': ['console', 'file'],
        },
    },
}
```

Trait type

Dict

Application.show_config

Instead of starting the Application, dump configuration to stdout

Trait type

Bool

Default

False

CLI option

--show-config

Application.show_config_json

Instead of starting the Application, dump configuration to stdout (as JSON)

Trait type

Bool

Default

False

CLI option

--show-config-json

BaseIPythonApplication.add_ipython_dir_to_sys_path

No description

Trait type

Bool

Default

False

BaseIPythonApplication.auto_create

Whether to create profile dir if it doesn't exist

Trait type

Bool

Default

False

`BaseIPythonApplication.copy_config_files`

Whether to install the default config files into the profile dir. If a new profile is being created, and IPython contains config files for that profile, then they will be staged into the new directory. Otherwise, default config files will be automatically generated.

Trait type

Bool

Default

False

`BaseIPythonApplication.extra_config_file`

Path to an extra config file to load.

If specified, load this config file in addition to any other IPython config.

Trait type

Unicode

CLI option`--config``BaseIPythonApplication.ipython_dir`

The name of the IPython directory. This directory is used for logging configuration (through profiles), history storage, etc. The default is usually `$HOME/.ipython`. This option can also be specified through the environment variable `IPYTHONDIR`.

Trait type

Unicode

CLI option`--ipython-dir``BaseIPythonApplication.log_datefmt`

The date format used by logging formatters for `%(asctime)s`

Trait type

Unicode

Default`'%Y-%m-%d %H:%M:%S'``BaseIPythonApplication.log_format`

The Logging format template

Trait type

Unicode

Default`'[% (name)s]%(highlevel)s %(message)s'``BaseIPythonApplication.log_level`

Set the log level by value or name.

Options

0, 10, 20, 30, 40, 50, 'DEBUG', 'INFO', 'WARN', 'ERROR', 'CRITICAL'

Default

30

BaseIPythonApplication.logging_config

Configure additional log handlers.

The default stderr logs handler is configured by the `log_level`, `log_datefmt` and `log_format` settings.

This configuration can be used to configure additional handlers (e.g. to output the log to a file) or for finer control over the default handlers.

If provided this should be a logging configuration dictionary, for more information see: <https://docs.python.org/3/library/logging.config.html#logging-config-dictschema>

This dictionary is merged with the base logging configuration which defines the following:

- A logging formatter intended for interactive use called `console`.
- A logging handler that writes to stderr called `console` which uses the formatter `console`.
- A logger with the name of this application set to `DEBUG` level.

This example adds a new handler that writes to a file:

```
c.Application.logging_config = {
    'handlers': {
        'file': {
            'class': 'logging.FileHandler',
            'level': 'DEBUG',
            'filename': '<path/to/file>',
        },
    },
    'loggers': {
        '<application-name>': {
            'level': 'DEBUG',
            # NOTE: if you don't list the default "console"
            # handler here then it will be disabled
            'handlers': ['console', 'file'],
        },
    },
}
```

Trait type

Dict

BaseIPythonApplication.overwrite

Whether to overwrite existing config files when copying

Trait type

Bool

Default

False

BaseIPythonApplication.profile

The IPython profile to use.

Trait type

Unicode

Default`'default'`**CLI option**`--profile``BaseIPythonApplication.show_config`

Instead of starting the Application, dump configuration to stdout

Trait type`Bool`**Default**`False``BaseIPythonApplication.show_config_json`

Instead of starting the Application, dump configuration to stdout (as JSON)

Trait type`Bool`**Default**`False``BaseIPythonApplication.verbose_crash`

Create a massive crash report when IPython encounters what may be an internal error. The default is to append a short message to the usual traceback

Trait type`Bool`**Default**`False``IPKernelApp.add_ipython_dir_to_sys_path`

No description

Trait type`Bool`**Default**`False``IPKernelApp.auto_create`

Whether to create profile dir if it doesn't exist

Trait type`Bool`**Default**`False``IPKernelApp.capture_fd_output`

Attempt to capture and forward low-level output, e.g. produced by Extension libraries.

Trait type`Bool`**Default**`True`

`IPKernelApp.code_to_run`

Execute the given command string.

Trait type

Unicode

`IPKernelApp.connection_file`

JSON file in which to store connection info [default: kernel-<pid>.json]

This file will contain the IP, ports, and authentication key needed to connect clients to this kernel. By default, this file will be created in the security dir of the current profile, but can be specified by absolute path.

Trait type

Unicode

CLI option

-f

`IPKernelApp.control_port`

set the control (ROUTER) port [default: random]

Trait type

Int

Default

0

CLI option

--control

`IPKernelApp.copy_config_files`

Whether to install the default config files into the profile dir. If a new profile is being created, and IPython contains config files for that profile, then they will be staged into the new directory. Otherwise, default config files will be automatically generated.

Trait type

Bool

Default

False

`IPKernelApp.displayhook_class`

The importstring for the DisplayHook factory

Trait type

DottedObjectName

Default

'ipykernel.displayhook.ZMQDisplayHook'

`IPKernelApp.exec_PYTHONSTARTUP`

Run the file referenced by the PYTHONSTARTUP environment variable at IPython startup.

Trait type

Bool

Default

True

`IPKernelApp.exec_files`

List of files to run at IPython startup.

Trait type

List

`IPKernelApp.exec_lines`

lines of code to run at IPython startup.

Trait type

List

`IPKernelApp.extensions`

A list of dotted module names of IPython extensions to load.

Trait type

List

`IPKernelApp.extra_config_file`

Path to an extra config file to load.

If specified, load this config file in addition to any other IPython config.

Trait type

Unicode

`IPKernelApp.extra_extensions`

Dotted module name(s) of one or more IPython extensions to load.

For specifying extra extensions to load on the command-line.

Добавлено в версии 7.10.

Trait type

List

`IPKernelApp.file_to_run`

A file to be run

Trait type

Unicode

`IPKernelApp.gui`

Enable GUI event loop integration with any of („asyncio“, „glut“, „gtk“, „gtk2“, „gtk3“, „gtk4“, „osx“, „pyglet“, „qt“, „qt5“, „qt6“, „tk“, „wx“, „gtk2“, „qt4“).

Options

'asyncio', 'glut', 'gtk', 'gtk2', 'gtk3', 'gtk4', 'osx', 'pyglet', 'qt', 'qt5',
'qt6', 'tk', 'wx', 'gtk2', 'qt4'

`IPKernelApp.hb_port`

set the heartbeat port [default: random]

Trait type

Int

Default

0

CLI option

--hb

`IPKernelApp.hide_initial_ns`

Should variables loaded at startup (by startup files, `exec_lines`, etc.) be hidden from tools like `%who`?

Trait type

Bool

Default

True

`IPKernelApp.ignore_cwd`

If True, IPython will not add the current working directory to `sys.path`. When False, the current working directory is added to `sys.path`, allowing imports of modules defined in the current directory.

Trait type

Bool

Default

False

`IPKernelApp.interrupt`

ONLY USED ON WINDOWS Interrupt this process when the parent is signaled.

Trait type

Int

Default

0

`IPKernelApp.iopub_port`

set the iopub (PUB) port [default: random]

Trait type

Int

Default

0

CLI option

--iopub

`IPKernelApp.ip`

Set the kernel's IP address [default localhost]. If the IP address is something other than localhost, then Consoles on other machines will be able to connect to the Kernel, so be careful!

Trait type

Unicode

CLI option

--ip

`IPKernelApp.ipython_dir`

The name of the IPython directory. This directory is used for logging configuration (through profiles), history storage, etc. The default is usually `$HOME/.ipython`. This option can also be specified through the environment variable `IPYTHONDIR`.

Trait type

Unicode

`IPKernelApp.kernel_class`

The Kernel subclass to be used.

This should allow easy re-use of the IPKernelApp entry point to configure and launch kernels other than IPython's own.

Trait type

Type

Default

'ipykernel.ipkernel.IPythonKernel'

IPKernelApp.log_datefmt

The date format used by logging formatters for %(asctime)s

Trait type

Unicode

Default

'%Y-%m-%d %H:%M:%S'

IPKernelApp.log_format

The Logging format template

Trait type

Unicode

Default

'[% (name)s]%(highlevel)s %(message)s'

IPKernelApp.log_level

Set the log level by value or name.

Options

0, 10, 20, 30, 40, 50, 'DEBUG', 'INFO', 'WARN', 'ERROR', 'CRITICAL'

Default

30

IPKernelApp.logging_config

Configure additional log handlers.

The default stderr logs handler is configured by the log_level, log_datefmt and log_format settings.

This configuration can be used to configure additional handlers (e.g. to output the log to a file) or for finer control over the default handlers.

If provided this should be a logging configuration dictionary, for more information see: <https://docs.python.org/3/library/logging.config.html#logging-config-dictschema>

This dictionary is merged with the base logging configuration which defines the following:

- A logging formatter intended for interactive use called `console`.
- A logging handler that writes to stderr called `console` which uses the formatter `console`.
- A logger with the name of this application set to `DEBUG` level.

This example adds a new handler that writes to a file:

```
c.Application.logging_config = {
    'handlers': {
        'file': {
            'class': 'logging.FileHandler',
            'level': 'DEBUG',
```

(continues on next page)

(продолжение с предыдущей страницы)

```
        'filename': '<path/to/file>',
    },
    'loggers': {
        '<application-name>': {
            'level': 'DEBUG',
            # NOTE: if you don't list the default "console"
            # handler here then it will be disabled
            'handlers': ['console', 'file'],
        },
    },
}
```

Trait type

Dict

IPKernelApp.matplotlib

Configure matplotlib for interactive use with the default matplotlib backend.

Options

```
'auto', 'agg', 'gtk', 'gtk3', 'gtk4', 'inline', 'ipympl', 'nbagg', 'notebook',
'osx', 'pdf', 'ps', 'qt', 'qt4', 'qt5', 'qt6', 'svg', 'tk', 'webagg', 'widget',
'wx'
```

IPKernelApp.module_to_run

Run the module as a script.

Trait type

Unicode

IPKernelApp.no_stderr

redirect stderr to the null device

Trait type

Bool

Default

False

CLI option`--no-stderr`

IPKernelApp.no_stdout

redirect stdout to the null device

Trait type

Bool

Default

False

CLI option`--no-stdout`

IPKernelApp.outstream_class

The importstring for the OutStream factory

Trait type
DottedObjectName

Default
'ipykernel.iostream.OutStream'

IPKernelApp.overwrite

Whether to overwrite existing config files when copying

Trait type
Bool

Default
False

IPKernelApp.parent_handle

kill this process if its parent dies. On Windows, the argument specifies the HANDLE of the parent process, otherwise it is simply boolean.

Trait type
Int

Default
0

IPKernelApp.profile

The IPython profile to use.

Trait type
Unicode

Default
'default'

IPKernelApp.pylab

Pre-load matplotlib and numpy for interactive use, selecting a particular matplotlib backend and loop integration.

Options

'auto', 'agg', 'gtk', 'gtk3', 'gtk4', 'inline', 'ipympl', 'nbagg', 'notebook',
'osx', 'pdf', 'ps', 'qt', 'qt4', 'qt5', 'qt6', 'svg', 'tk', 'webagg', 'widget',
'wx'

IPKernelApp.pylab_import_all

If true, IPython will populate the user namespace with numpy, pylab, etc. and an `import *` is done from numpy and pylab, when using pylab mode.

When False, pylab mode should not import any names into the user namespace.

Trait type
Bool

Default
True

IPKernelApp.quiet

Only send stdout/stderr to output stream

Trait type
Bool

Default

True

IPKernelApp.reraise_ipython_extension_failures

Reraise exceptions encountered loading IPython extensions?

Trait type

Bool

Default

False

IPKernelApp.shell_port

set the shell (ROUTER) port [default: random]

Trait type

Int

Default

0

CLI option

--shell

IPKernelApp.show_config

Instead of starting the Application, dump configuration to stdout

Trait type

Bool

Default

False

IPKernelApp.show_config_json

Instead of starting the Application, dump configuration to stdout (as JSON)

Trait type

Bool

Default

False

IPKernelApp.stdin_port

set the stdin (ROUTER) port [default: random]

Trait type

Int

Default

0

CLI option

--stdin

IPKernelApp.transport

No description

Options

'tcp', 'ipc'

Default

'tcp'

CLI option`--transport``IPKernelApp.trio_loop`

Set main event loop.

Trait type

Bool

Default

False

`IPKernelApp.verbose_crash`

Create a massive crash report when IPython encounters what may be an internal error. The default is to append a short message to the usual traceback

Trait type

Bool

Default

False

`Kernel._darwin_app_nap`

Whether to use appnope for compatibility with OS X App Nap.

Only affects OS X ≥ 10.9 .**Trait type**

Bool

Default

True

`Kernel._execute_sleep`

No description

Trait type

Float

Default

0.0005

`Kernel._poll_interval`

No description

Trait type

Float

Default

0.01

`Kernel.debug_just_my_code`

Set to False if you want to debug python standard and dependent libraries.

Trait type

Bool

Default

True

`Kernel.stop_on_error_timeout`

time (in seconds) to wait for messages to arrive when aborting queued requests after an error.

Requests that arrive within this window after an error will be cancelled.

Increase in the event of unusually slow network causing significant delays, which can manifest as e.g. «Run all» in a notebook aborting some, but not all, messages after an error.

Trait type

Float

Default

0.0

`IPythonKernel._darwin_app_nap`

Whether to use appnope for compatibility with OS X App Nap.

Only affects OS X ≥ 10.9 .

Trait type

Bool

Default

True

`IPythonKernel._execute_sleep`

No description

Trait type

Float

Default

0.0005

`IPythonKernel._poll_interval`

No description

Trait type

Float

Default

0.01

`IPythonKernel.debug_just_my_code`

Set to False if you want to debug python standard and dependent libraries.

Trait type

Bool

Default

True

`IPythonKernel.help_links`

No description

Trait type

List

`IPythonKernel.stop_on_error_timeout`

time (in seconds) to wait for messages to arrive when aborting queued requests after an error.

Requests that arrive within this window after an error will be cancelled.

Increase in the event of unusually slow network causing significant delays, which can manifest as e.g. «Run all» in a notebook aborting some, but not all, messages after an error.

Trait type

Float

Default

0.0

IPythonKernel.use_experimental_completions

Set this flag to False to deactivate the use of experimental IPython completion APIs.

Trait type

Bool

Default

True

InteractiveShell.ast_node_interactivity

„all“, „last“, „last_expr“ or „none“, „last_expr_or_assign“ specifying which nodes should be run interactively (displaying output from expressions).

Options

'all', 'last', 'last_expr', 'none', 'last_expr_or_assign'

Default

'last_expr'

InteractiveShell.ast_transformers

A list of ast.NodeTransformer subclass instances, which will be applied to user input before code is run.

Trait type

List

InteractiveShell.autoawait

Automatically run await statement in the top level repl.

Trait type

Bool

Default

True

InteractiveShell.autocall

Make IPython automatically call any callable object even if you didn't type explicit parentheses. For example, „str 43“ becomes „str(43)“ automatically. The value can be „0“ to disable the feature, „1“ for „smart“ autocall, where it is not applied if there are no more arguments on the line, and „2“ for „full“ autocall, where all callable objects are automatically called (even if no arguments are present).

Options

0, 1, 2

Default

0

CLI option

--autocall

InteractiveShell.autoindent

Autoindent IPython code entered interactively.

Trait type

Bool

Default

True

CLI option`--autoindent`**InteractiveShell.automagic**

Enable magic commands to be called without the leading %.

Trait type

Bool

Default

True

CLI option`--automagic`**InteractiveShell.banner1**

The part of the banner to be printed before the profile

Trait type

Unicode

Default`"Python 3.10.6 | packaged by conda-forge | (main, Aug 22 2022..."`**InteractiveShell.banner2**

The part of the banner to be printed after the profile

Trait type

Unicode

InteractiveShell.cache_size

Set the size of the output cache. The default is 1000, you can change it permanently in your config file. Setting it to 0 completely disables the caching system, and the minimum value accepted is 3 (if you provide a value less than 3, it is reset to 0 and a warning is issued). This limit is defined because otherwise you'll spend more time re-flushing a too small cache than working

Trait type

Int

Default

1000

CLI option`--cache-size`**InteractiveShell.color_info**

Use colors for displaying information about objects. Because this information is passed through a pager (like „less“), and some pagers get confused with color codes, this capability can be turned off.

Trait type

Bool

Default

True

CLI option`--color-info``InteractiveShell.colors`

Set the color scheme (NoColor, Neutral, Linux, or LightBG).

Options`'Neutral', 'NoColor', 'LightBG', 'Linux'`**Default**`'Neutral'`**CLI option**`--colors``InteractiveShell.debug`

No description

Trait type`Bool`**Default**`False``InteractiveShell.disable_failing_post_execute`

Don't call post-execute functions that have failed in the past.

Trait type`Bool`**Default**`False``InteractiveShell.display_page`

If True, anything that would be passed to the pager will be displayed as regular output instead.

Trait type`Bool`**Default**`False``InteractiveShell.enable_html_pager`

(Provisional API) enables html representation in mime bundles sent to pagers.

Trait type`Bool`**Default**`False``InteractiveShell.history_length`

Total length of command history

Trait type`Int`**Default**`10000`

`InteractiveShell.history_load_length`

The number of saved history entries to be loaded into the history buffer at startup.

Trait type

Int

Default

1000

`InteractiveShell.inspector_class`

Class to use to instantiate the shell inspector

Trait type

Type

Default

'IPython.core.oinspect.Inspector'

`InteractiveShell.ipython_dir`

No description

Trait type

Unicode

`InteractiveShell.logappend`

Start logging to the given file in append mode. Use `logfile` to specify a log file to **overwrite** logs to.

Trait type

Unicode

CLI option

--logappend

`InteractiveShell.logfile`

The name of the logfile to use.

Trait type

Unicode

CLI option

--logfile

`InteractiveShell.logstart`

Start logging to the default log file in overwrite mode. Use `logappend` to specify a log file to **append** logs to.

Trait type

Bool

Default

False

`InteractiveShell.loop_runner`

Select the loop runner that will be used to execute top-level asynchronous code

Trait type

Any

Default

'IPython.core.interactiveshell._asyncio_runner'

`InteractiveShell.object_info_string_level`

No description

Options

0, 1, 2

Default

0

`InteractiveShell.pdb`

Automatically call the pdb debugger after every exception.

Trait type

Bool

Default

False

CLI option

--pdb

`InteractiveShell.quiet`

No description

Trait type

Bool

Default

False

`InteractiveShell.separate_in`

No description

Trait type

SeparateUnicode

Default

'\\n'

`InteractiveShell.separate_out`

No description

Trait type

SeparateUnicode

`InteractiveShell.separate_out2`

No description

Trait type

SeparateUnicode

`InteractiveShell.show_rewritten_input`

Show rewritten input, e.g. for autocall.

Trait type

Bool

Default

True

`InteractiveShell.sphinxify_docstring`

Enables rich html representation of docstrings. (This requires the docrepr module).

Trait type

Bool

Default

False

`InteractiveShell.warn_venv`

Warn if running in a virtual environment with no IPython installed (so IPython from the global environment is used).

Trait type

Bool

Default

True

`InteractiveShell.wildcards_case_sensitive`

No description

Trait type

Bool

Default

True

`InteractiveShell.xmode`

Switch modes for the IPython exception handlers.

Options

'Context', 'Plain', 'Verbose', 'Minimal'

Default

'Context'

`ZMQInteractiveShell.ast_node_interactivity`

„all“, „last“, „last_expr“ or „none“, „last_expr_or_assign“ specifying which nodes should be run interactively (displaying output from expressions).

Options

'all', 'last', 'last_expr', 'none', 'last_expr_or_assign'

Default

'last_expr'

`ZMQInteractiveShell.ast_transformers`

A list of ast.NodeTransformer subclass instances, which will be applied to user input before code is run.

Trait type

List

`ZMQInteractiveShell.autoawait`

Automatically run await statement in the top level repl.

Trait type

Bool

Default

True

ZMQInteractiveShell.autocall

Make IPython automatically call any callable object even if you didn't type explicit parentheses. For example, „str 43“ becomes „str(43)“ automatically. The value can be „0“ to disable the feature, „1“ for „smart“ autocall, where it is not applied if there are no more arguments on the line, and „2“ for „full“ autocall, where all callable objects are automatically called (even if no arguments are present).

Options

0, 1, 2

Default

0

ZMQInteractiveShell.automagic

Enable magic commands to be called without the leading %.

Trait type

Bool

Default

True

ZMQInteractiveShell.banner1

The part of the banner to be printed before the profile

Trait type

Unicode

Default

"Python 3.10.6 | packaged by conda-forge | (main, Aug 22 2022..."

ZMQInteractiveShell.banner2

The part of the banner to be printed after the profile

Trait type

Unicode

ZMQInteractiveShell.cache_size

Set the size of the output cache. The default is 1000, you can change it permanently in your config file. Setting it to 0 completely disables the caching system, and the minimum value accepted is 3 (if you provide a value less than 3, it is reset to 0 and a warning is issued). This limit is defined because otherwise you'll spend more time re-flushing a too small cache than working

Trait type

Int

Default

1000

ZMQInteractiveShell.color_info

Use colors for displaying information about objects. Because this information is passed through a pager (like „less“), and some pagers get confused with color codes, this capability can be turned off.

Trait type

Bool

Default

True

ZMQInteractiveShell.colors

Set the color scheme (NoColor, Neutral, Linux, or LightBG).

Options

'Neutral', 'NoColor', 'LightBG', 'Linux'

Default

'Neutral'

`ZMQInteractiveShell.debug`

No description

Trait type

Bool

Default

False

`ZMQInteractiveShell.disable_failing_post_execute`

Don't call post-execute functions that have failed in the past.

Trait type

Bool

Default

False

`ZMQInteractiveShell.display_page`

If True, anything that would be passed to the pager will be displayed as regular output instead.

Trait type

Bool

Default

False

`ZMQInteractiveShell.enable_html_pager`

(Provisional API) enables html representation in mime bundles sent to pagers.

Trait type

Bool

Default

False

`ZMQInteractiveShell.history_length`

Total length of command history

Trait type

Int

Default

10000

`ZMQInteractiveShell.history_load_length`

The number of saved history entries to be loaded into the history buffer at startup.

Trait type

Int

Default

1000

`ZMQInteractiveShell.inspector_class`

Class to use to instantiate the shell inspector

Trait type

Type

Default

'IPython.core.oinspect.Inspector'

`ZMQInteractiveShell.ipython_dir`

No description

Trait type

Unicode

`ZMQInteractiveShell.logappend`

Start logging to the given file in append mode. Use `logfile` to specify a log file to **overwrite** logs to.

Trait type

Unicode

`ZMQInteractiveShell.logfile`

The name of the logfile to use.

Trait type

Unicode

`ZMQInteractiveShell.logstart`

Start logging to the default log file in overwrite mode. Use `logappend` to specify a log file to **append** logs to.

Trait type

Bool

Default

False

`ZMQInteractiveShell.loop_runner`

Select the loop runner that will be used to execute top-level asynchronous code

Trait type

Any

Default

'IPython.core.interactiveshell._asyncio_runner'

`ZMQInteractiveShell.object_info_string_level`

No description

Options

0, 1, 2

Default

0

`ZMQInteractiveShell.pdb`

Automatically call the pdb debugger after every exception.

Trait type

Bool

Default

False

`ZMQInteractiveShell.quiet`

No description

Trait type

Bool

Default

False

`ZMQInteractiveShell.separate_in`

No description

Trait type

SeparateUnicode

Default

'\\n'

`ZMQInteractiveShell.separate_out`

No description

Trait type

SeparateUnicode

`ZMQInteractiveShell.separate_out2`

No description

Trait type

SeparateUnicode

`ZMQInteractiveShell.show_rewritten_input`

Show rewritten input, e.g. for autocall.

Trait type

Bool

Default

True

`ZMQInteractiveShell.sphinxify_docstring`

Enables rich html representation of docstrings. (This requires the docrepr module).

Trait type

Bool

Default

False

`ZMQInteractiveShell.warn_venv`

Warn if running in a virtual environment with no IPython installed (so IPython from the global environment is used).

Trait type

Bool

Default

True

`ZMQInteractiveShell.wildcards_case_sensitive`

No description

Trait type

Bool

Default

True

`ZMQInteractiveShell.xmode`

Switch modes for the IPython exception handlers.

Options

'Context', 'Plain', 'Verbose', 'Minimal'

Default

'Context'

`ProfileDir.location`

Set the profile location directly. This overrides the logic used by the `profile` option.

Trait type

Unicode

CLI option

--profile-dir

`Session.buffer_threshold`

Threshold (in bytes) beyond which an object's buffer should be extracted to avoid pickling.

Trait type

Int

Default

1024

`Session.check_pid`

Whether to check PID to protect against calls after fork.

This check can be disabled if fork-safety is handled elsewhere.

Trait type

Bool

Default

True

`Session.copy_threshold`

Threshold (in bytes) beyond which a buffer should be sent without copying.

Trait type

Int

Default

65536

`Session.debug`

Debug output in the Session

Trait type

Bool

Default

False

Session.digest_history_size

The maximum number of digests to remember.

The digest history will be culled when it exceeds this value.

Trait type

Int

Default

65536

Session.item_threshold

The maximum number of items for a container to be introspected for custom serialization. Containers larger than this are pickled outright.

Trait type

Int

Default

64

Session.key

execution key, for signing messages.

Trait type

CBytes

Default

b''

Session.keyfile

path to file containing execution key.

Trait type

Unicode

CLI option

--keyfile

Session.metadata

Metadata dictionary, which serves as the default top-level metadata dict for each message.

Trait type

Dict

Session.packer

The name of the packer for serializing messages. Should be one of „json“, „pickle“, or an import name for a custom callable serializer.

Trait type

DottedObjectName

Default

'json'

Session.session

The UUID identifying this session.

Trait type
CUnicode

CLI option
--ident

`Session.signature_scheme`

The digest scheme used to construct the message signatures. Must have the form „hmac-HASH“.

Trait type
Unicode

Default
'hmac-sha256'

`Session.unpacker`

The name of the unpacker for unserializing messages. Only used with custom functions for `packer`.

Trait type
DottedObjectName

Default
'json'

`Session.username`

Username for the Session. Default is your system username.

Trait type
Unicode

Default
'username'

CLI option
--user

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.


If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

5.1.3 IPython shortcuts

Shortcuts available in an IPython terminal.

Примечание: This list is automatically generated. Key bindings defined in `prompt_toolkit` may differ between installations depending on the `prompt_toolkit` version.

- Comma-separated keys, e.g. `Esc, f`, indicate a sequence which can be activated by pressing the listed keys in succession.

- Plus-separated keys, e.g. `Esc + f` indicate a combination which requires pressing all keys simultaneously.
- Hover over the  icon in the filter column to see when the shortcut is active.

You can use `TerminalInteractiveShell.shortcuts` configuration to modify, disable or add shortcuts.

Shortcut	Description and identifier	Filter
<code>{</code>	Auto-close braces. <code>IPython:auto_match.braces</code>	
<code>[</code>	Auto-close brackets. <code>IPython:auto_match.brackets</code>	
<code>ctrl + h</code> (or <code>backspace</code>)	Delete auto-closed parenthesis. <code>IPython:auto_match.delete_pair</code>	
<code>ctrl + h</code> (or <code>backspace</code>)	Delete auto-closed parenthesis. <code>IPython:auto_match.delete_pair</code>	
<code>ctrl + h</code> (or <code>backspace</code>)	Delete auto-closed parenthesis. <code>IPython:auto_match.delete_pair</code>	
<code>ctrl + h</code> (or <code>backspace</code>)	Delete auto-closed parenthesis. <code>IPython:auto_match.delete_pair</code>	
<code>ctrl + h</code> (or <code>backspace</code>)	Delete auto-closed parenthesis. <code>IPython:auto_match.delete_pair</code>	
<code>"</code>	Auto-close docstring (double quotes). <code>IPython:auto_match.docstring_double_quotes</code>	
<code>'</code>	Auto-close docstring (single quotes). <code>IPython:auto_match.docstring_single_quotes</code>	
<code>"</code>	Auto-close double quotes. <code>IPython:auto_match.double_quote</code>	
<code>(</code>	Auto-close parenthesis. <code>IPython:auto_match.parenthesis</code>	
<code>{</code>	Auto-close braces in raw strings. <code>IPython:auto_match.raw_string_braces</code>	
<code>[</code>	Auto-close bracker in raw strings. <code>IPython:auto_match.raw_string_bracket</code>	
<code>(</code>	Auto-close parenthesis in raw strings. <code>IPython:auto_match.raw_string_parenthesis</code>	
<code>'</code>	Auto-close single quotes. <code>IPython:auto_match.single_quote</code>	
<code>}</code>	Skip over automatically added parenthesis/quote. <code>IPython:auto_match.skip_over</code>	
<code>]</code>	Skip over automatically added parenthesis/quote. <code>IPython:auto_match.skip_over</code>	
<code>)</code>	Skip over automatically added parenthesis/quote. <code>IPython:auto_match.skip_over</code>	
<code>"</code>	Skip over automatically added parenthesis/quote. <code>IPython:auto_match.skip_over</code>	
<code>'</code>	Skip over automatically added parenthesis/quote. <code>IPython:auto_match.skip_over</code>	
<code>ctrl + f</code>	Accept autosuggestion. <code>IPython:auto_suggest.accept</code>	
<code>right</code>	Accept autosuggestion. <code>IPython:auto_suggest.accept</code>	
<code>escape, down</code>	Accept autosuggestion and keep cursor in place. <code>IPython:auto_suggest.accept_and_keep_cursor</code>	

continues on next page

Таблица 1 – продолжение с предыдущей страницы

Shortcut	Description and identifier	Filter
ctrl + left	Accept autosuggestion and move cursor left in place. IPython:auto_suggest.accept_and_move_cursor_left	
escape, right	Fill partial autosuggestion by character. IPython:auto_suggest.accept_character	
end	Apply autosuggestion or jump to end of line. IPython:auto_suggest.accept_or_jump_to_end	
ctrl + e	Apply autosuggestion or jump to end of line. IPython:auto_suggest.accept_or_jump_to_end	
ctrl + right	Fill partial autosuggestion by token. IPython:auto_suggest.accept_token	
escape, f	Fill partial autosuggestion by word. IPython:auto_suggest.accept_word	
ctrl + h (or backspace)	Resume autosuggestions after deleting last character. IPython:auto_suggest.backspace_and_resume_hint	
escape	Discard autosuggestion. IPython:auto_suggest.discard	
delete	Discard autosuggestion. IPython:auto_suggest.discard	
ctrl + down	Go down and update hint. IPython:auto_suggest.down_and_update_hint	
right	Resume autosuggestions. IPython:auto_suggest.resume_hinting	
ctrl + down	Get previous autosuggestion from history. IPython:auto_suggest.swap_autosuggestion_down	
ctrl + up	Get next autosuggestion from history. IPython:auto_suggest.swap_autosuggestion_up	
ctrl + up	Go up and update hint. IPython:auto_suggest.up_and_update_hint	
ctrl + g	Dismiss completion. IPython:shortcuts.dismiss_completion	
ctrl + m (or enter)	. IPython:shortcuts.handle_return_or_newline_or_execute	
ctrl + i (or tab)	Indent buffer. IPython:shortcuts.indent_buffer	
ctrl + o	Insert a newline after the cursor indented appropriately. IPython:shortcuts.newline_autoindent	
ctrl + n	Control-N in vi edit mode on readline is history previous, unlike default prompt toolkit. IPython:shortcuts.next_history_or_next_completion	
f2	Open code from input in external editor. IPython:shortcuts.open_input_in_editor	
ctrl + p	Control-P in vi edit mode on readline is history next, unlike default prompt toolkit. IPython:shortcuts.previous_history_or_previous_completion	
ctrl + \	Quit application with SIGQUIT if supported or sys.exit otherwise. IPython:shortcuts.quit	
escape, ctrl + m (or enter)	Reformat code and execute it. IPython:shortcuts.reformat_and_execute	
ctrl + c	Reset buffer. IPython:shortcuts.reset_buffer	
ctrl + c	Reset search buffer. IPython:shortcuts.reset_search_buffer	

continues on next page

Таблица 1 – продолжение с предыдущей страницы

Shortcut	Description and identifier	Filter
<code>ctrl + z</code>	Suspend to background. <code>IPython:shortcuts.suspend_to_bg</code>	
<code>ctrl + v</code>	Stub used on other platforms. <code>IPython:shortcuts.win_paste</code>	
<code>right</code>	Accept suggestion. <code>prompt_toolkit:auto_suggest._accept</code>	
<code>ctrl + e</code>	Accept suggestion. <code>prompt_toolkit:auto_suggest._accept</code>	
<code>ctrl + f</code>	Accept suggestion. <code>prompt_toolkit:auto_suggest._accept</code>	
<code>escape, f</code>	Fill partial suggestion. <code>prompt_toolkit:auto_suggest._fill</code>	
<code>ctrl + i</code> (or <code>tab</code>)	Key binding handler for readline-style tab completion. <code>prompt_toolkit:completion.display_completions_like_readline</code>	
<code>ctrl + b</code>	Move back a character. <code>prompt_toolkit:named_commands.backward_char</code>	
<code>ctrl + w</code>	Kills the word before point, using «not a letter nor a digit» as a word boundary. <code>prompt_toolkit:named_commands.backward_kill_word</code>	
<code>escape, h</code>	Kills the word before point, using «not a letter nor a digit» as a word boundary. <code>prompt_toolkit:named_commands.backward_kill_word</code>	
<code>escape, b</code>	Move back to the start of the current or previous word. <code>prompt_toolkit:named_commands.backward_word</code>	
<code>ctrl + a</code>	Move to the start of the current line. <code>prompt_toolkit:named_commands.beginning_of_line</code>	
<code>escape, c</code>	Capitalize the current (or following) word. <code>prompt_toolkit:named_commands.capitalize_word</code>	
<code>escape, l</code>	Lowercase the current (or following) word. <code>prompt_toolkit:named_commands.downcase_word</code>	
<code>ctrl + x, ctrl + e</code>	Invoke an editor on the current command line, and accept the result. <code>prompt_toolkit:named_commands.edit_and_execute</code>	
<code>v</code>	Invoke an editor on the current command line, and accept the result. <code>prompt_toolkit:named_commands.edit_and_execute</code>	
<code>ctrl + x, ctrl + e</code>	Invoke an editor on the current command line, and accept the result. <code>prompt_toolkit:named_commands.edit_and_execute</code>	
<code>ctrl + x, e</code>	Invoke an editor on the current command line, and accept the result. <code>prompt_toolkit:named_commands.edit_and_execute</code>	
<code>ctrl + k</code>	Kill the text from the cursor to the end of the line. <code>prompt_toolkit:named_commands.kill_line</code>	
<code>escape, d</code>	Kill from point to the end of the current word, or if between words, to the end of the next word. <code>prompt_toolkit:named_commands.kill_word</code>	
<code>ctrl + _</code>	Incremental undo. <code>prompt_toolkit:named_commands.undo</code>	
<code>escape, u</code>	Uppercase the current (or following) word. <code>prompt_toolkit:named_commands.uppercase_word</code>	
<code>ctrl + y</code>	Paste before cursor. <code>prompt_toolkit:named_commands.yank</code>	
<code>escape, .</code>	Like <code>yank_nth_arg</code> , but if no argument has been given, yank the last word of each line. <code>prompt_toolkit:named_commands.yank_last_arg</code>	
<code>escape, y</code>	Rotate the kill ring, and yank the new top. <code>prompt_toolkit:named_commands.yank_pop</code>	

continues on next page

Таблица 1 – продолжение с предыдущей страницы

Shortcut	Description and identifier	Filter
<code>ctrl + m</code> (or <code>enter</code>)	Accept input when enter has been pressed. <code>prompt_toolkit:prompt._accept_input</code>	
<code>ctrl + i</code> (or <code>tab</code>)	Display completions (like Readline). <code>prompt_toolkit:prompt._complete_like_readline</code>	
<code>ctrl + d</code>	Exit when Control-D has been pressed. <code>prompt_toolkit:prompt._eof</code>	
<code><sigint></code>	Abort when Control-C has been pressed. <code>prompt_toolkit:prompt._keyboard_interrupt</code>	
<code>ctrl + c</code>	Abort when Control-C has been pressed. <code>prompt_toolkit:prompt._keyboard_interrupt</code>	
<code>ctrl + z</code>	Suspend process to background. <code>prompt_toolkit:prompt._suspend</code>	

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

5.1.4 Specific config details

Custom Prompts

Изменено в версии 5.0.

From IPython 5, prompts are produced as a list of Pygments tokens, which are tuples of (token_type, text). You can customise prompts by writing a method which generates a list of tokens.

There are four kinds of prompt:

- The **in** prompt is shown before the first line of input (default like `In [1]:`).
- The **continuation** prompt is shown before further lines of input (default like `...:`).
- The **rewrite** prompt is shown to highlight how special syntax has been interpreted (default like `---->`).
- The **out** prompt is shown before the result from evaluating the input (default like `Out[1]:`).

Custom prompts are supplied together as a class. If you want to customise only some of the prompts, inherit from `IPython.terminal.prompts.Prompts`, which defines the defaults. The required interface is like this:

```
class MyPrompts(shell)
```

Prompt style definition. *shell* is a reference to the `TerminalInteractiveShell` instance.

```
in_prompt_tokens(cli=None)
```

```
continuation_prompt_tokens(self, cli=None, width=None)
```

```
rewrite_prompt_tokens()
```

```
out_prompt_tokens()
```

Return the respective prompts as lists of `(token_type, text)` tuples.

For continuation prompts, *width* is an integer representing the width of the prompt area in terminal columns.

cli, where used, is the prompt_toolkit `CommandLineInterface` instance. This is mainly for compatibility with the API prompt_toolkit expects.

Here is an example Prompt class that will show the current working directory in the input prompt:

```
from IPython.terminal.prompts import Prompts, Token
import os

class MyPrompt(Prompts):
    def in_prompt_tokens(self, cli=None):
        return [(Token, os.getcwd()),
                (Token.Prompt, ' >>>')]
```

To set the new prompt, assign it to the `prompts` attribute of the IPython shell:

```
In [2]: ip = get_ipython()
...: ip.prompts = MyPrompt(ip)

/home/bob >>> # it works
```

See `IPython/example/utils/cwd_prompt.py` for an example of how to write extensions to customise prompts.

Inside IPython or in a startup script, you can use a custom prompts class by setting `get_ipython().prompts` to an *instance* of the class. In configuration, `TerminalInteractiveShell.prompts_class` may be set to either the class object, or a string of its full importable name.

To include invisible terminal control sequences in a prompt, use `Token.ZeroWidthEscape` as the token type. Tokens with this type are ignored when calculating the width.

Colours in the prompt are determined by the token types and the highlighting style; see below for more details. The tokens used in the default prompts are `Prompt`, `PromptNum`, `OutPrompt` and `OutPromptNum`.

Terminal Colors

Изменено в версии 5.0.

There are two main configuration options controlling colours.

`InteractiveShell.colors` sets the colour of tracebacks and object info (the output from e.g. `zip?`). It may also affect other things if the option below is set to `'legacy'`. It has four case-insensitive values: `'nocolor'`, `'neutral'`, `'linux'`, `'lightbg'`. The default is *neutral*, which should be legible on either dark or light terminal backgrounds. *linux* is optimised for dark backgrounds and *lightbg* for light ones.

`TerminalInteractiveShell.highlighting_style` determines prompt colours and syntax highlighting. It takes the name (as a string) or class (as a subclass of `pygments.style.Style`) of a Pygments style, or the special value `'legacy'` to pick a style in accordance with `InteractiveShell.colors`.

You can see the Pygments styles available on your system by running:

```
import pygments
list(pygments.styles.get_all_styles())
```

Additionally, `TerminalInteractiveShell.highlighting_style_overrides` can override specific styles in the highlighting. It should be a dictionary mapping Pygments token types to strings defining the style. See [Pygments“ documentation](#) for the language used to define styles.

Colors in the pager

On some systems, the default pager has problems with ANSI colour codes. To configure your default pager to allow these:

1. Set the environment `PAGER` variable to `less`.
2. Set the environment `LESS` variable to `-r` (plus any other options you always want to pass to `less` by default). This tells `less` to properly interpret control sequences, which is how color information is given to your terminal.

Editor configuration

IPython can integrate with text editors in a number of different ways:

- Editors (such as (X)Emacs, vim and TextMate) can send code to IPython for execution.
- IPython’s `%edit` magic command can open an editor of choice to edit a code block.

The `%edit` command (and its alias `%ed`) will invoke the editor set in your environment as `EDITOR`. If this variable is not set, it will default to `vi` under Linux/Unix and to `notepad` under Windows. You may want to set this variable properly and to a lightweight editor which doesn’t take too long to start (that is, something other than a new instance of Emacs). This way you can edit multi-line code quickly and with the power of a real editor right inside IPython.

You can also control the editor by setting `TerminalInteractiveShell.editor` in `ipython_config.py`.

Vim

Paul Ivanov’s `vim-ipython` provides powerful IPython integration for vim.

(X)Emacs

If you are a dedicated Emacs user, and want to use Emacs when IPython’s `%edit` magic command is called you should set up the Emacs server so that new requests are handled by the original process. This means that almost no time is spent in handling the request (assuming an Emacs process is already running). For this to work, you need to set your `EDITOR` environment variable to „emacsclient“. The code below, supplied by Francois Pinard, can then be used in your `.emacs` file to enable the server:

```
(defvar server-buffer-clients)
(when (and (fboundp 'server-start) (string-equal (getenv "TERM") 'xterm))
  (server-start)
  (defun fp-kill-server-with-buffer-routine ()
    (and server-buffer-clients (server-done)))
  (add-hook 'kill-buffer-hook 'fp-kill-server-with-buffer-routine))
```

Thanks to the work of Alexander Schmolck and Prabhu Ramachandran, currently (X)Emacs and IPython get along very well in other ways.

With (X)EMacs `>= 24`, You can enable IPython in python-mode with:

```
(require 'python)
(setq python-shell-interpreter "ipython")
```

Keyboard Shortcuts

Добавлено в версии 8.11.

You can modify, disable or modify keyboard shortcuts for IPython Terminal using *TerminalInteractiveShell.shortcuts* traitlet.

The list of shortcuts is available in the Configuring IPython *IPython shortcuts* section.

Advanced configuration

Изменено в версии 5.0.

Creating custom commands requires adding custom code to a *startup file*:

```
from IPython import get_ipython
from prompt_toolkit.enums import DEFAULT_BUFFER
from prompt_toolkit.keys import Keys
from prompt_toolkit.filters import HasFocus, HasSelection, ViInsertMode, EmacsInsertMode

ip = get_ipython()
insert_mode = ViInsertMode() | EmacsInsertMode()

def insert_unexpected(event):
    buf = event.current_buffer
    buf.insert_text('The Spanish Inquisition')
# Register the shortcut if IPython is using prompt_toolkit
if getattr(ip, 'pt_app', None):
    registry = ip.pt_app.key_bindings
    registry.add_binding(Keys.ControlN,
                        filter=(HasFocus(DEFAULT_BUFFER)
                              & ~HasSelection()
                              & insert_mode))(insert_unexpected)
```

Here is a second example that bind the key sequence j, k to switch to VI input mode to Normal when in insert mode:

```
from IPython import get_ipython
from prompt_toolkit.enums import DEFAULT_BUFFER
from prompt_toolkit.filters import HasFocus, ViInsertMode
from prompt_toolkit.key_binding.vi_state import InputMode

ip = get_ipython()

def switch_to_navigation_mode(event):
    vi_state = event.cli.vi_state
    vi_state.input_mode = InputMode.NAVIGATION

if getattr(ip, 'pt_app', None):
```

(continues on next page)

(продолжение с предыдущей страницы)

```
registry = ip.pt_app.key_bindings
registry.add_binding(u'j',u'k',
                    filter=(HasFocus(DEFAULT_BUFFER)
                           & ViInsertMode()))(switch_to_navigation_mode)
```

For more information on filters and what you can do with the `event` object, see the [prompt_toolkit docs](#).

Enter to execute

In the Terminal IPython shell – which by default uses the `prompt_toolkit` interface, the semantic meaning of pressing the **Enter** key can be ambiguous. In some case **Enter** should execute code, and in others it should add a new line. IPython uses heuristics to decide whether to execute or insert a new line at cursor position. For example, if we detect that the current code is not valid Python, then the user is likely editing code and the right behavior is to likely to insert a new line. If the current code is a simple statement like `ord('*')`, then the right behavior is likely to execute. Though the exact desired semantics often varies from users to users.

As the exact behavior of **Enter** is ambiguous, it has been special cased to allow users to completely configure the behavior they like. Hence you can have enter always execute code. If you prefer fancier behavior, you need to get your hands dirty and read the `prompt_toolkit` and IPython documentation though. See [PR #10500](#), set the `c.TerminalInteractiveShell.handle_return` option and get inspiration from the following example that only auto-executes the input if it begins with a bang or a modulo character (! or %). To use the following code, add it to your IPython configuration:

```
def custom_return(shell):

    """This function is required by the API. It takes a reference to
    the shell, which is the same thing `get_ipython()` evaluates to.
    This function must return a function that handles each keypress
    event. That function, named `handle` here, references `shell`
    by closure."""

    def handle(event):

        """This function is called each time `Enter` is pressed,
        and takes a reference to a Prompt Toolkit event object.
        If the current input starts with a bang or modulo, then
        the input is executed, otherwise a newline is entered,
        followed by any spaces needed to auto-indent."""

        # set up a few handy references to nested items...

        buffer = event.current_buffer
        document = buffer.document
        text = document.text

        if text.startswith('!') or text.startswith('%'): # execute the input...

            buffer.accept_action.validate_and_handle(event.cli, buffer)

        else: # insert a newline with auto-indentation...
```

(continues on next page)

(продолжение с предыдущей страницы)

```
if document.line_count > 1: text = text[:document.cursor_position]
indent = shell.check_complete(text)[1]
buffer.insert_text('\n' + indent)

# if you just wanted a plain newline without any indentation, you
# could use `buffer.insert_text('\n')` instead of the lines above

return handle

c.TerminalInteractiveShell.handle_return = custom_return
```

См.также:

Overview of the IPython configuration system

Technical details of the config system.

5.2 Расширение и интеграция с IPython

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

5.2.1 IPython extensions

A level above configuration are IPython extensions, Python modules which modify the behaviour of the shell. They are referred to by an importable module name, and can be placed anywhere you'd normally import from.

Getting extensions

A few important extensions are *bundled with IPython*. Others can be found on the [extensions index](#) on the wiki, and the [Framework :: IPython](#) tag on PyPI.

Extensions on PyPI can be installed using `pip`, like any other Python package.

Using extensions

To load an extension while IPython is running, use the `%load_ext` magic:

```
In [1]: %load_ext myextension
```

To load it each time IPython starts, list it in your configuration file:

```
c.InteractiveShellApp.extensions = [
    'myextension'
]
```

Writing extensions

An IPython extension is an importable Python module that has a couple of special functions to load and unload it. Here is a template:

```
# myextension.py

def load_ipython_extension(ipython):
    # The `ipython` argument is the currently active `InteractiveShell`
    # instance, which can be used in any way. This allows you to register
    # new magics or aliases, for example.

def unload_ipython_extension(ipython):
    # If you want your extension to be unloadable, put that logic here.
```

This `load_ipython_extension()` function is called after your extension is imported, and the currently active *InteractiveShell* instance is passed as the only argument. You can do anything you want with IPython at that point.

`load_ipython_extension()` will not be called again if the users use `%load_extension`. The user has to explicitly ask the extension to be reloaded (with `%reload_extension`). In cases where the user asks the extension to be reloaded, the extension will be unloaded (with `unload_ipython_extension`), and loaded again.

Useful *InteractiveShell* methods include *register_magic_function()*, *push()* (to add variables to the user namespace) and *drop_by_id()* (to remove variables on unloading).

См.также:

Defining custom magics

You can put your extension modules anywhere you want, as long as they can be imported by Python's standard import mechanism.

When your extension is ready for general use, please add it to the [extensions index](#). We also encourage you to upload it to PyPI and use the `Framework :: IPython` classifier, so that users can install it with standard packaging tools.

Extensions bundled with IPython

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

autoreload

`%autoreload`

IPython extension to reload modules before executing user code.

`autoreload` reloads modules automatically before entering the execution of code typed at the IPython prompt.

This makes for example the following workflow possible:

```
In [1]: %load_ext autoreload

In [2]: %autoreload 2

In [3]: from foo import some_function

In [4]: some_function()
Out[4]: 42

In [5]: # open foo.py in an editor and change some_function to return 43

In [6]: some_function()
Out[6]: 43
```

The module was reloaded without reloading it explicitly, and the object imported with `from foo import ...` was also updated.

Usage

The following magic commands are provided:

`%autoreload`, `%autoreload now`

Reload all modules (except those excluded by `%ainport`) automatically now.

`%autoreload 0`, `%autoreload off`

Disable automatic reloading.

`%autoreload 1`, `%autoreload explicit`

Reload all modules imported with `%aimport` every time before executing the Python code typed.

```
%autoreload 2, %autoreload all
```

Reload all modules (except those excluded by `%aimport`) every time before executing the Python code typed.

```
%autoreload 3, %autoreload complete
```

Same as 2/all, but also adds any new objects in the module. See unit test at `IPython/extensions/tests/test_autoreload.py::test_autoload_newly_added_objects`

Adding `--print` or `-p` to the `%autoreload` line will print autoreload activity to standard out. `--log` or `-l` will do it to the log at INFO level; both can be used simultaneously.

```
%aimport
```

List modules which are to be automatically imported or not to be imported.

```
%aimport foo
```

Import module „foo“ and mark it to be autoreloaded for `%autoreload 1`

```
%aimport foo, bar
```

Import modules „foo“, „bar“ and mark them to be autoreloaded for `%autoreload 1`

```
%aimport -foo
```

Mark module „foo“ to not be autoreloaded.

Caveats

Reloading Python modules in a reliable way is in general difficult, and unexpected things may occur. `%autoreload` tries to work around common pitfalls by replacing function code objects and parts of classes previously in the module with new versions. This makes the following things to work:

- Functions and classes imported via „from xxx import foo“ are upgraded to new versions when „xxx“ is reloaded.
- Methods and properties of classes are upgraded on reload, so that calling „c.foo()“ on an object „c“ created before the reload causes the new code for „foo“ to be executed.

Some of the known remaining caveats are:

- Replacing code objects does not always succeed: changing a `@property` in a class to an ordinary method or a method to a member variable can cause problems (but in old objects only).
- Functions that are removed (eg. via monkey-patching) from a module before it is reloaded are not upgraded.
- C extension modules cannot be reloaded, and so cannot be autoreloaded.
- While comparing Enum and Flag, the „is“ Identity Operator is used (even in the case „==“ has been used (Similar to the „None“ keyword)).
- Reloading a module, or importing the same module by a different name, creates new Enums. These may look the same, but are not.

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

storemagic

%store magic for lightweight persistence.

Stores variables, aliases and macros in IPython's database.

To automatically restore stored variables at startup, add this to your `ipython_config.py` file:

```
c.StoreMagics.autorestore = True
```

`StoreMagics.store(parameter_s='')`

Lightweight persistence for python variables.

Example:

```
In [1]: l = ['hello',10,'world']
In [2]: %store l
Stored 'l' (list)
In [3]: exit

(IPython session is closed and started again...)

ville@badger:~$ ipython
In [1]: l
NameError: name 'l' is not defined
In [2]: %store -r
In [3]: l
Out[3]: ['hello', 10, 'world']
```

Usage:

- `%store` - Show list of all variables and their current values
- `%store spam bar` - Store the *current* value of the variables `spam` and `bar` to disk
- `%store -d spam` - Remove the variable and its value from storage
- `%store -z` - Remove all variables from storage
- `%store -r` - Refresh all variables, aliases and directory history from store (overwrite current vals)
- `%store -r spam bar` - Refresh specified variables and aliases from store (delete current val)
- `%store foo >a.txt` - Store value of `foo` to new file `a.txt`
- `%store foo >>a.txt` - Append value of `foo` to file `a.txt`

It should be noted that if you change the value of a variable, you need to `%store` it again if you want to persist the new value.

Note also that the variables will need to be pickleable; most basic python types can be safely `%store`'d.

Also aliases can be `%store`'d across sessions. To remove an alias from the storage, use the `%unalias` magic.

- `octavemagic` used to be bundled, but is now part of `oct2py`. Use `%load_ext oct2py.ipython` to load it.
- `rmagic` is now part of `rpy2`. Use `%load_ext rpy2.ipython` to load it, and see `rpy2.ipython.rmagic` for details of how to use it.
- `cythonmagic` used to be bundled, but is now part of `cython`. Use `%load_ext Cython` to load it.
- `sympyprinting` used to be a bundled extension, but you should now use `sympy.init_printing()` instead.

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

5.2.2 Integrating your objects with IPython

Tab completion

To change the attributes displayed by tab-completing your object, define a `__dir__(self)` method for it. For more details, see the documentation of the built-in `dir()` function.

You can also customise key completions for your objects, e.g. pressing tab after `obj["a`. To do so, define a method `_ipython_key_completions_()`, which returns a list of objects which are possible keys in a subscript expression `obj[key]`.

Добавлено в версии 5.0: Custom key completions

Rich display

Custom methods

IPython can display richer representations of objects. To do this, you can define `_ipython_display_()`, or any of a number of `_repr_*_()` methods. Note that these are surrounded by single, not double underscores.

Таблица 2: Supported `_repr_*_` methods

Format	REPL	Notebook	Qt Console
<code>_repr_pretty_</code>	yes	yes	yes
<code>_repr_svg_</code>	no	yes	yes
<code>_repr_png_</code>	no	yes	yes
<code>_repr_jpeg_</code>	no	yes	yes
<code>_repr_html_</code>	no	yes	no
<code>_repr_javascript_</code>	no	yes	no
<code>_repr_markdown_</code>	no	yes	no
<code>_repr_latex_</code>	no	yes	no
<code>_repr_mimebundle_</code>	no	?	?

If the methods don't exist, the standard `repr()` is used. If a method exists and returns `None`, it is treated the same as if it does not exist. In general, *all* available formatters will be called when an object is displayed, and it is up to the UI to select which to display. A given formatter should not generally change its output based on what other formats are available - that should be handled at a different level, such as the *DisplayFormatter*, or configuration.

`_repr_*_` methods should *return* data of the expected format and have no side effects. For example, `_repr_html_` should return HTML as a `str` and `_repr_png_` should return PNG data as `bytes`.

If you wish to take control of display via your own side effects, use `_ipython_display_()`.

For example:

```
class Shout(object):
    def __init__(self, text):
        self.text = text

    def _repr_html_(self):
        return "<h1>" + self.text + "</h1>"
```

Special methods

Pretty printing

To customize how your object is pretty-printed, add a `_repr_pretty_` method to the class. The method should accept a pretty printer, and a boolean that indicates whether the printer detected a cycle. The method should act on the printer to produce your customized pretty output. Here is an example:

```
class MyObject(object):

    def _repr_pretty_(self, p, cycle):
        if cycle:
            p.text('MyObject(...)')
        else:
            p.text('MyObject[...]')
```

For details on how to use the pretty printer, see *IPython.lib.pretty*.

More powerful methods

```
class MyObject
```

```
    _repr_mimebundle_(include=None, exclude=None)
```

Should return a dictionary of multiple formats, keyed by mimetype, or a tuple of two dictionaries: *data*, *metadata* (see [Distribution metadata](#)). If this returns something, other `_repr_*_` methods are ignored. The method should take keyword arguments `include` and `exclude`, though it is not required to respect them.

```
    _ipython_display_()
```

Displays the object as a side effect; the return value is ignored. If this is defined, all other display methods are ignored.

Metadata

We often want to provide frontends with guidance on how to display the data. To support this, `_repr_*_()` methods (except `_repr_pretty_?`) can also return a `(data, metadata)` tuple where `metadata` is a dictionary containing arbitrary key-value pairs for the frontend to interpret. An example use case is `_repr_jpeg_()`, which can be set to return a jpeg image and a `{'height': 400, 'width': 600}` dictionary to inform the frontend how to size the image.

Formatters for third-party types

The user can also register formatters for types without modifying the class:

```
from bar.baz import Foo

def foo_html(obj):
    return '<marquee>Foo object %s</marquee>' % obj.name

html_formatter = get_ipython().display_formatter.formatters['text/html']
html_formatter.for_type(Foo, foo_html)

# Or register a type without importing it - this does the same as above:
html_formatter.for_type_by_name('bar.baz', 'Foo', foo_html)
```

Custom exception tracebacks

Rarely, you might want to display a custom traceback when reporting an exception. To do this, define the custom traceback using `_render_traceback_(self)` method which returns a list of strings, one string for each line of the traceback. For example, the `ipyparallel` a parallel computing framework for IPython, does this to display errors from multiple engines.

Please be conservative in using this feature; by replacing the default traceback you may hide important information from the user.

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

5.2.3 Defining custom magics

There are two main ways to define your own magic functions: from standalone functions and by inheriting from a base class provided by IPython: `IPython.core.magic.Magics`. Below we show code you can place in a file that you load from your configuration, such as any file in the `startup` subdirectory of your default IPython profile.

First, let us see the simplest case. The following shows how to create a line magic, a cell one and one that works in both modes, using just plain functions:

```
from IPython.core.magic import (register_line_magic, register_cell_magic,
                                register_line_cell_magic)

@register_line_magic
def lmagic(line):
    "my line magic"
    return line

@register_cell_magic
def cmagic(line, cell):
    "my cell magic"
    return line, cell

@register_line_cell_magic
def lcmagic(line, cell=None):
    "Magic that works both as %lcmagic and as %%lcmagic"
    if cell is None:
        print("Called as line magic")
        return line
    else:
        print("Called as cell magic")
        return line, cell

# In an interactive session, we need to delete these to avoid
# name conflicts for automagic to work on line magics.
del lmagic, lcmagic
```

You can also create magics of all three kinds by inheriting from the `IPython.core.magic.Magics` class. This lets you create magics that can potentially hold state in between calls, and that have full access to the main IPython object:

```
# This code can be put in any Python module, it does not require IPython
# itself to be running already. It only creates the magics subclass but
# doesn't instantiate it yet.
from __future__ import print_function
from IPython.core.magic import (Magics, magics_class, line_magic,
```

(continues on next page)

(продолжение с предыдущей страницы)

```

cell_magic, line_cell_magic)

# The class MUST call this class decorator at creation time
@magics_class
class MyMagics(Magics):

    @line_magic
    def lmagic(self, line):
        "my line magic"
        print("Full access to the main IPython object:", self.shell)
        print("Variables in the user namespace:", list(self.shell.user_ns.keys()))
        return line

    @cell_magic
    def cmagic(self, line, cell):
        "my cell magic"
        return line, cell

    @line_cell_magic
    def lcmagic(self, line, cell=None):
        "Magic that works both as %lcmagic and as %%lcmagic"
        if cell is None:
            print("Called as line magic")
            return line
        else:
            print("Called as cell magic")
            return line, cell

# In order to actually use these magics, you must register them with a
# running IPython.

def load_ipython_extension(ipython):
    """
    Any module file that define a function named `load_ipython_extension`
    can be loaded via `%load_ext module.path` or be configured to be
    autoloaded by IPython at startup time.
    """
    # You can register the class itself without instantiating it. IPython will
    # call the default constructor on it.
    ipython.register_magics(MyMagics)

```

If you want to create a class with a different constructor that holds additional state, then you should always call the parent constructor and instantiate the class yourself before registration:

```

@magics_class
class StatefulMagics(Magics):
    "Magics that hold additional state"

    def __init__(self, shell, data):
        # You must call the parent constructor
        super(StatefulMagics, self).__init__(shell)

```

(continues on next page)

(продолжение с предыдущей страницы)

```

        self.data = data

    # etc...

def load_ipython_extension(ipython):
    """
    Any module file that define a function named `load_ipython_extension`
    can be loaded via `%load_ext module.path` or be configured to be
    autoloaded by IPython at startup time.
    """
    # This class must then be registered with a manually created instance,
    # since its constructor has different arguments from the default:
    magics = StatefulMagics(ipython, some_data)
    ipython.register_magics(magics)

```

Примечание: In early IPython versions 0.12 and before the line magics were created using a `define_magic()` API function. This API has been replaced with the above in IPython 0.13 and then completely removed in IPython 5. Maintainers of IPython extensions that still use the `define_magic()` function are advised to adjust their code for the current API.

5.2.4 Accessing user namespace and local scope

When creating line magics, you may need to access surrounding scope to get user variables (e.g when called inside functions). IPython provides the `@needs_local_scope` decorator that can be imported from `IPython.core.magics`. When decorated with `@needs_local_scope` a magic will be passed `local_ns` as an argument. As a convenience `@needs_local_scope` can also be applied to cell magics even if cell magics cannot appear at local scope context.

5.2.5 Silencing the magic output

Sometimes it may be useful to define a magic that can be silenced the same way that non-magic expressions can, i.e., by appending a semicolon at the end of the Python code to be executed. That can be achieved by decorating the magic function with the decorator `@output_can_be_silenced` that can be imported from `IPython.core.magics`. When this decorator is used, IPython will parse the Python code used by the magic and, if the last token is a `;`, the output created by the magic will not show up on the screen. If you want to see an example of this decorator in action, take a look on the `time` magic defined in `IPython.core.magics.execution.py`.

5.2.6 Complete Example

Here is a full example of a magic package. You can distribute magics using `setuptools`, `distutils`, or any other distribution tools like `flit` for pure Python packages.

When distributing magics as part of a package, recommended best practice is to execute the registration inside the `load_ipython_extension` as demonstrated in the example below, instead of directly in the module (as in the initial example with the `@register_*` decorators). This means a user will need to explicitly choose to load your magic with `%load_ext`, instead implicitly getting it when importing the module. This is particularly relevant if loading your magic has side effects, if it is slow to load, or if it might override another magic with the same name.

```

.
├── example_magic
│   ├── __init__.py
│   └── abracadabra.py
└── setup.py

```

```

$ cat example_magic/__init__.py
"""An example magic"""
__version__ = '0.0.1'

from .abracadabra import Abracadabra

def load_ipython_extension(ipython):
    ipython.register_magics(Abracadabra)

```

```

$ cat example_magic/abracadabra.py
from IPython.core.magic import (Magics, magics_class, line_magic, cell_magic)

@magics_class
class Abracadabra(Magics):

    @line_magic
    def abra(self, line):
        return line

    @cell_magic
    def cadabra(self, line, cell):
        return line, cell

```

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

5.2.7 Mime Renderer Extensions

Like it's cousins, Jupyter Notebooks and JupyterLab, Terminal IPython can be thought to render a number of mimetypes in the shell. This can be used to either display inline images if your terminal emulator supports it; or open some display results with external file viewers.

Registering new mimetype handlers can so far only be done by extensions and requires 4 steps:

- Define a callable that takes 2 parameters: `data` and `metadata`; return value of the callable is so far ignored. This callable is responsible for «displaying» the given mimetype. Which can be sending the right escape sequences and bytes to the current terminal; or open an external program. -

- Appending the right mimetype to `ipython.display_formatter.active_types` for IPython to know it should not ignore those mimetypes.
- Enabling the given mimetype: `ipython.display_formatter.formatters[mime].enabled = True`
- Registering above callable with mimetype handler: `ipython.mime_renderers[mime] = handler`

Here is a complete IPython extension to display images inline and convert math to png, before displaying it inline for `term2` on macOS

```
from base64 import encodebytes
from IPython.lib.latextools import latex_to_png

def mathcat(data, meta):
    png = latex_to_png(f'${data}$'.replace('\displaystyle', '').replace('$$$', '$$'))
    imcat(png, meta)

IMAGE_CODE = '\033]1337;File=name=name;inline=true;:{a}'

def imcat(image_data, metadata):
    try:
        print(IMAGE_CODE.format(encodebytes(image_data).decode()))
        # bug workaround
    except:
        print(IMAGE_CODE.format(image_data))

def register_mimerenderer(ipython, mime, handler):
    ipython.display_formatter.active_types.append(mime)
    ipython.display_formatter.formatters[mime].enabled = True
    ipython.mime_renderers[mime] = handler

def load_ipython_extension(ipython):
    register_mimerenderer(ipython, 'image/png', imcat)
    register_mimerenderer(ipython, 'image/jpeg', imcat)
    register_mimerenderer(ipython, 'text/latex', mathcat)
```

This example only work for `term2` on macOS and skip error handling for brevity. One could also invoke an external viewer with `subprocess.run()` and a temporary file, which is left as an exercise.

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

5.2.8 Custom input transformation

IPython extends Python syntax to allow things like magic commands, and help with the `?` syntax. There are several ways to customise how the user's input is processed into Python code to be executed.

These hooks are mainly for other projects using IPython as the core of their interactive interface. Using them carelessly can easily break IPython!

String based transformations

When the user enters code, it is first processed as a string. By the end of this stage, it must be valid Python syntax.

Изменено в версии 7.0: The API for string and token-based transformations has been completely redesigned. Any third party code extending input transformation will need to be rewritten. The new API is, hopefully, simpler.

String based transformations are functions which accept a list of strings: each string is a single line of the input cell, including its line ending. The transformation function should return output in the same structure.

These transformations are in two groups, accessible as attributes of the `InteractiveShell` instance. Each group is a list of transformation functions.

- `input_transformers_cleanup` run first on input, to do things like stripping prompts and leading indents from copied code. It may not be possible at this stage to parse the input as valid Python code.
- Then IPython runs its own transformations to handle its special syntax, like `%magics` and `!system` commands. This part does not expose extension points.
- `input_transformers_post` run as the last step, to do things like converting float literals into decimal objects. These may attempt to parse the input as Python code.

These transformers may raise `SyntaxError` if the input code is invalid, but in most cases it is clearer to pass unrecognised code through unmodified and let Python's own parser decide whether it is valid.

For example, imagine we want to obfuscate our code by reversing each line, so we'd write `)5(f += a` instead of `a += f(5)`. Here's how we could swap it back the right way before IPython tries to run it:

```
def reverse_line_chars(lines):
    new_lines = []
    for line in lines:
        chars = line[:-1] # the newline needs to stay at the end
        new_lines.append(chars[::-1] + '\n')
    return new_lines
```

To start using this:

```
ip = get_ipython()
ip.input_transformers_cleanup.append(reverse_line_chars)
```

Добавлено в версии 7.17: `input_transformers` can now have an attribute `has_side_effects` set to `True`, which will prevent the transformers from being ran when IPython is trying to guess whether the user input is complete.

AST transformations

After the code has been parsed as Python syntax, you can use Python's powerful *Abstract Syntax Tree* tools to modify it. Subclass `ast.NodeTransformer`, and add an instance to `shell.ast_transformers`.

This example wraps integer literals in an `Integer` class, which is useful for mathematical frameworks that want to handle e.g. $1/3$ as a precise fraction:

```
class IntegerWrapper(ast.NodeTransformer):
    """Wraps all integers in a call to Integer()"""
    def visit_Num(self, node):
        if isinstance(node.n, int):
            return ast.Call(func=ast.Name(id='Integer', ctx=ast.Load()),
                            args=[node], keywords=[])
        return node
```

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

5.2.9 IPython Events

Extension code can register callbacks functions which will be called on specific events within the IPython code. You can see the current list of available callbacks, and the parameters that will be passed with each, in the callback prototype functions defined in *IPython.core.events*.

To register callbacks, use *IPython.core.events.EventManager.register()*. For example:

```
class VarWatcher(object):
    def __init__(self, ip):
        self.shell = ip
        self.last_x = None

    def pre_execute(self):
        self.last_x = self.shell.user_ns.get('x', None)

    def pre_run_cell(self, info):
        print('info.raw_cell =', info.raw_cell)
        print('info.store_history =', info.store_history)
        print('info.silent =', info.silent)
        print('info.shell_futures =', info.shell_futures)
        print('info.cell_id =', info.cell_id)
        print(dir(info))

    def post_execute(self):
```

(continues on next page)

(продолжение с предыдущей страницы)

```

        if self.shell.user_ns.get('x', None) != self.last_x:
            print("x changed!")

    def post_run_cell(self, result):
        print('result.execution_count = ', result.execution_count)
        print('result.error_before_exec = ', result.error_before_exec)
        print('result.error_in_exec = ', result.error_in_exec)
        print('result.info = ', result.info)
        print('result.result = ', result.result)

def load_ipython_extension(ip):
    vw = VarWatcher(ip)
    ip.events.register('pre_execute', vw.pre_execute)
    ip.events.register('pre_run_cell', vw.pre_run_cell)
    ip.events.register('post_execute', vw.post_execute)
    ip.events.register('post_run_cell', vw.post_run_cell)

```

Добавлено в версии 8.3: Since IPython 8.3 and ipykernel 6.12.1, the `info` objects in the callback now have a the `cell_id` that will be set to the value sent by the frontened, when those send it.

Events

These are the events IPython will emit. Callbacks will be passed no arguments, unless otherwise specified.

shell_initialized

```

def shell_initialized(ipython):
    ...

```

This event is triggered only once, at the end of setting up IPython. Extensions registered to load by default as part of configuration can use this to execute code to finalize setup. Callbacks will be passed the `InteractiveShell` instance.

pre_run_cell

`pre_run_cell` fires prior to interactive execution (e.g. a cell in a notebook). It can be used to note the state prior to execution, and keep track of changes. An object containing information used for the code execution is provided as an argument.

pre_execute

`pre_execute` is like `pre_run_cell`, but is triggered prior to *any* execution. Sometimes code can be executed by libraries, etc. which skipping the history/display mechanisms, in which cases `pre_run_cell` will not fire.

post_run_cell

`post_run_cell` runs after interactive execution (e.g. a cell in a notebook). It can be used to cleanup or notify or perform operations on any side effects produced during execution. For instance, the inline matplotlib backend uses this event to display any figures created but not explicitly displayed during the course of the cell. The object which will be returned as the execution result is provided as an argument.

post_execute

The same as `pre_execute`, `post_execute` is like `post_run_cell`, but fires for *all* executions, not just interactive ones.

См.также:

Module *IPython.core.hooks*

The older „hooks“ system allows end users to customise some parts of IPython’s behaviour.

Custom input transformation

By registering input transformers that don’t change code, you can monitor what is being executed.

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

5.2.10 Integrating with GUI event loops

When the user types `%gui qt`, IPython integrates itself with the Qt event loop, so you can use both a GUI and an interactive prompt together. IPython supports a number of common GUI toolkits, but from IPython 3.0, it is possible to integrate other event loops without modifying IPython itself.

Supported event loops include `qt5`, `qt6`, `gtk2`, `gtk3`, `gtk4`, `wx`, `osx` and `tk`. Make sure the event loop you specify matches the GUI toolkit used by your own code.

To make IPython GUI event loop integration occur automatically at every startup, set the `c.InteractiveShellApp.gui` configuration key in your IPython profile (see *Setting configurable options*).

If the event loop you use is supported by IPython, turning on event loop integration follows the steps just described whether you use Terminal IPython or an IPython kernel.

However, the way Terminal IPython handles event loops is very different from the way IPython kernel does, so if you need to integrate with a new kind of event loop, different steps are needed to integrate with each.

Integrating with a new event loop in the terminal

Изменено в версии 5.0: There is a new API for event loop integration using `prompt_toolkit`.

In the terminal, IPython uses `prompt_toolkit` to prompt the user for input. `prompt_toolkit` provides hooks to integrate with an external event loop.

To integrate an event loop, define a function which runs the GUI event loop until there is input waiting for `prompt_toolkit` to process. There are two ways to detect this condition:

```
# Polling for input.
def inpuhook(context):
    while not context.input_is_ready():
        # Replace this with the appropriate call for the event loop:
        iterate_loop_once()

# Using a file descriptor to notify the event loop to stop.
def inpuhook2(context):
    fd = context.fileno()
    # Replace the functions below with those for the event loop.
    add_file_reader(fd, callback=stop_the_loop)
    run_the_loop()
```

Once you have defined this function, register it with IPython:

```
IPython.terminal.pt_inpuhooks.register(name, inpuhook)
```

Register the function `inpuhook` as the event loop integration for the GUI `name`. If `name='foo'`, then the user can enable this integration by running `%gui foo`.

Integrating with a new event loop in the kernel

The kernel runs its own event loop, so it's simpler to integrate with others. IPython allows the other event loop to take control, but it must call `IPython.kernel.zmq.kernelbase.Kernel.do_one_iteration()` periodically.

To integrate with this, write a function that takes a single argument, the IPython kernel instance, arranges for your event loop to call `kernel.do_one_iteration()` at least every `kernel._poll_interval` seconds, and starts the event loop.

Decorate this function with `IPython.kernel.zmq.eventloops.register_integration()`, passing in the names you wish to register it for. Here is a slightly simplified version of the Tkinter integration already included in IPython:

```
@register_integration('tk')
def loop_tk(kernel):
    """Start a kernel with the Tk event loop."""
    from tkinter import Tk

    # Tk uses milliseconds
    poll_interval = int(1000*kernel._poll_interval)
    # For Tkinter, we create a Tk object and call its withdraw method.
    class Timer(object):
        def __init__(self, func):
            self.app = Tk()
            self.app.withdraw()
```

(continues on next page)

(продолжение с предыдущей страницы)

```
self.func = func

def on_timer(self):
    self.func()
    self.app.after(poll_interval, self.on_timer)

def start(self):
    self.on_timer() # Call it once to get things going.
    self.app.mainloop()

kernel.timer = Timer(kernel.do_one_iteration)
kernel.timer.start()
```

Some event loops can go one better, and integrate checking for messages on the kernel's ZMQ sockets, making the kernel more responsive than plain polling. How to do this is outside the scope of this document; if you are interested, look at the integration with Qt in `IPython.kernel.zmq.eventloops`.

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

Developer's guide for third party tools and libraries

Важно: This guide contains information for developers of third party tools and libraries that use IPython. Alternatively, documentation for core **IPython** development can be found in the [Guide for IPython core Developers](#).

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

6.1 How IPython works

6.1.1 Terminal IPython

When you type `ipython`, you get the original IPython interface, running in the terminal. It does something like this:

```
while True:
    code = input(">>> ")
    exec(code)
```


Of course, it's much more complex, because it has to deal with multi-line code, tab completion using `readline`, magic commands, and so on. But the model is like that: prompt the user for some code, and

when they've entered it, exec it in the same process. This model is often called a REPL, or Read-Eval-Print-Loop.

6.1.2 The IPython Kernel

All the other interfaces—the Notebook, the Qt console, `ipython console` in the terminal, and third party interfaces—use the IPython Kernel. This is a separate process which is responsible for running user code, and things like computing possible completions. Frontends communicate with it using JSON messages sent over [ZeroMQ](#) sockets; the protocol they use is described in [Messaging in Jupyter](#).


The core execution machinery for the kernel is shared with terminal IPython:



A kernel process can be connected to more than one frontend simultaneously. In this case, the different frontends will have access to the same variables.

This design was intended to allow easy development of different frontends based on the same kernel, but it also made it possible to support new languages in the same frontends, by developing kernels in those languages, and we are refining IPython to make that more practical.

Today, there are two ways to develop a kernel for another language. Wrapper kernels reuse the communications machinery from IPython, and implement only the core execution part. Native kernels implement execution and communications in the target language:



Wrapper kernels are easier to write quickly for languages that have good Python wrappers, like `octave_kernel`, or languages where it's impractical to implement the communications machinery, like `bash_kernel`. Native kernels are likely to be better maintained by the community using them, like `IJulia` or `IHaskell`.

См. также:

[Making kernels for Jupyter](#)

[Making simple Python wrapper kernels](#)

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

6.2 Making simple Python wrapper kernels

Добавлено в версии 3.0.

You can now re-use the kernel machinery in IPython to easily make new kernels. This is useful for languages that have Python bindings, such as [Octave](#) (via [Oct2Py](#)), or languages where the REPL can be controlled in a tty using [pexpect](#), such as `bash`.

См.также:

`bash_kernel`

A simple kernel for `bash`, written using this machinery

6.2.1 Required steps

Subclass `ipykernel.kernelbase.Kernel`, and implement the following methods and attributes:

```
class MyKernel
```

```
    implementation
```

```
    implementation_version
```

```
    language
```

```
    language_version
```

```
    banner
```

Information for [Kernel info](#) replies. „Implementation“ refers to the kernel (e.g. IPython), and „language“ refers to the language it interprets (e.g. Python). The „banner“ is displayed to the user in console UIs before the first prompt. All of these values are strings.

```
    language_info
```

Language information for [Kernel info](#) replies, in a dictionary. This should contain the key `mimetype` with the mimetype of code in the target language (e.g. `'text/x-python'`), and `file_extension` (e.g. `'py'`). It may also contain keys `codemirror_mode` and `pygments_lexer` if they need to differ from `language`.

Other keys may be added to this later.

```
    do_execute(code, silent, store_history=True, user_expressions=None, allow_stdin=False)
```

Execute user code.

Параметры

- `code` (*str*) – The code to be executed.
- `silent` (*bool*) – Whether to display output.
- `store_history` (*bool*) – Whether to record this code in history and increase the execution count. If `silent` is `True`, this is implicitly `False`.

- `user_expressions` (*dict*) – Mapping of names to expressions to evaluate after the code has run. You can ignore this if you need to.
- `allow_stdin` (*bool*) – Whether the frontend can provide input on request (e.g. for Python's `raw_input()`).

Your method should return a dict containing the fields described in [Execution results](#). To display output, it can send messages using `send_response()`. See messaging for details of the different message types.

To launch your kernel, add this at the end of your module:

```
if __name__ == '__main__':
    from ipykernel.kernelapp import IPKernelApp
    IPKernelApp.launch_instance(kernel_class=MyKernel)
```

6.2.2 Example

`echokernel.py` will simply echo any input it's given to stdout:

```
from ipykernel.kernelbase import Kernel

class EchoKernel(Kernel):
    implementation = 'Echo'
    implementation_version = '1.0'
    language = 'no-op'
    language_version = '0.1'
    language_info = {'mimetype': 'text/plain'}
    banner = "Echo kernel - as useful as a parrot"

    def do_execute(self, code, silent, store_history=True, user_expressions=None,
                  allow_stdin=False):
        if not silent:
            stream_content = {'name': 'stdout', 'text': code}
            self.send_response(self.iopub_socket, 'stream', stream_content)

        return {'status': 'ok',
                # The base class increments the execution count
                'execution_count': self.execution_count,
                'payload': [],
                'user_expressions': {}},

if __name__ == '__main__':
    from ipykernel.kernelapp import IPKernelApp
    IPKernelApp.launch_instance(kernel_class=EchoKernel)
```

Here's the Kernel spec `kernel.json` file for this:

```
{
  "argv": ["python", "-m", "echokernel", "-f", "{connection_file}"],
  "display_name": "Echo"
}
```

6.2.3 Optional steps

You can override a number of other methods to improve the functionality of your kernel. All of these methods should return a dictionary as described in the relevant section of the messaging spec.

`class MyBetterKernel`

`do_complete(code, cursor_pos)`

Code completion

Параметры

- `code` (*str*) – The code already present
- `cursor_pos` (*int*) – The position in the code where completion is requested

См.также:

Completion messages

`do_inspect(code, cursor_pos, detail_level=0)`

Object introspection

Параметры

- `code` (*str*) – The code
- `cursor_pos` (*int*) – The position in the code where introspection is requested
- `detail_level` (*int*) – 0 or 1 for more or less detail. In IPython, 1 gets the source code.

См.также:

Introspection messages

`do_history(hist_access_type, output, raw, session=None, start=None, stop=None, n=None, pattern=None, unique=False)`

History access. Only the relevant parameters for the type of history request concerned will be passed, so your method definition must have defaults for all the arguments shown with defaults here.

См.также:

History messages

`do_is_complete(code)`

Is code entered in a console-like interface complete and ready to execute, or should a continuation prompt be shown?

Параметры

- `code` (*str*) – The code entered so far - possibly multiple lines

См.также:

Code completeness messages

`do_shutdown(restart)`

Shutdown the kernel. You only need to handle your own clean up - the kernel machinery will take care of cleaning up its own things before stopping.

Параметры

- `restart` (*bool*) – Whether the kernel will be started again afterwards

См.также:

[Kernel shutdown](#) messages

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

6.3 Execution of cells in the IPython kernel

When IPython kernel receives `execute_request` with user code, it processes the message in the following phases:

1. Fire the `pre_execute` event.
2. Fire the `pre_run_cell` event unless `silent` is `True`.
3. Execute `run_cell` method to preprocess `code`, compile and run it, see below for details.
4. If execution succeeds, expressions in `user_expressions` are computed. This ensures that any error in the expressions don't affect the main code execution.
5. Fire the `post_execute` event.
6. Fire the `post_run_cell` event unless `silent` is `True`.

См.также:

[IPython Events](#)

6.4 Running user code

First, the code cell is transformed to expand `%magic` and `!system` commands by `IPython.core.inputtransformer2`. Then expanded cell is compiled using standard Python `compile()` function and executed.

Python `compile()` function provides `mode` argument to select one of three ways of compiling code:

single

Valid for a single interactive statement (though the source can contain multiple lines, such as a for loop). When compiled in this mode, the generated bytecode contains special instructions that trigger the calling of `sys.displayhook()` for any expression in the block that returns a value. This means that a single statement can actually produce multiple calls to `sys.displayhook()`, if for example it contains a loop where each iteration computes an unassigned expression would generate 10 calls:

```
for i in range(10):
    i**2
```

exec

An arbitrary amount of source code, this is how modules are compiled. `sys.displayhook()` is *never* implicitly called.

eval

A single expression that returns a value. `sys.displayhook()` is *never* implicitly called.

The `code` field is split into individual blocks each of which is valid for execution in „single“ mode, and then:

- If there is only a single block: it is executed in „single“ mode.
- If there is more than one block:
 - if the last block is a single line long, run all but the last in „exec“ mode and the very last one in „single“ mode. This makes it easy to type simple expressions at the end to see computed values.
 - if the last block is no more than two lines long, run all but the last in „exec“ mode and the very last one in „single“ mode. This makes it easy to type simple expressions at the end to see computed values. - otherwise (last one is also multiline), run all in „exec“ mode
 - otherwise (last block is also multiline), run all in „exec“ mode as a single unit.

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

6.5 New IPython Console Lexer

Добавлено в версии 2.0.0.

The IPython console lexer has been rewritten and now supports tracebacks and customized input/output prompts. An entire suite of lexers is now available at [IPython.lib.lexers](#). These include:

IPythonLexer & IPython3Lexer

Lexers for pure IPython (python + magic/shell commands)

IPythonPartialTracebackLexer & IPythonTracebackLexer

Supports 2.x and 3.x via the keyword `python3`. The partial traceback lexer reads everything but the Python code appearing in a traceback. The full lexer combines the partial lexer with an IPython lexer.

IPythonConsoleLexer

A lexer for IPython console sessions, with support for tracebacks. Supports 2.x and 3.x via the keyword `python3`.

IPyLexer

A friendly lexer which examines the first line of text and from it, decides whether to use an IPython lexer or an IPython console lexer. Supports 2.x and 3.x via the keyword `python3`.

Previously, the `IPythonConsoleLexer` class was available at `IPython.sphinxext.ipython_console_highlight`. It was inserted into Pygments“ list of available lexers under the name

`ipython`. It should be mentioned that this name is inaccurate, since an IPython console session is not the same as IPython code (which itself is a superset of the Python language).

Now, the Sphinx extension inserts two console lexers into Pygments' list of available lexers. Both are IPyLexer instances under the names: `ipython` and `ipython3`. Although the names can be confusing (as mentioned above), their continued use is, in part, to maintain backwards compatibility and to aid typical usage. If a project needs to make Pygments aware of more than just the IPyLexer class, then one should not make the IPyLexer class available under the name `ipython` and use `ipy` or some other non-conflicting value.

Code blocks such as:

```
.. code-block:: ipython
```

```
In [1]: 2**2
Out[1]: 4
```

will continue to work as before, but now, they will also properly highlight tracebacks. For pure IPython code, the same lexer will also work:

```
.. code-block:: ipython
```

```
x = ''.join(map(str, range(10)))
!echo $x
```

Since the first line of the block did not begin with a standard IPython console prompt, the entire block is assumed to consist of IPython code instead.

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

6.6 Overview of the IPython configuration system

This section describes the IPython configuration system. This is based on `traitlets.config`; see that documentation for more information about the overall architecture.

6.6.1 Configuration file location

So where should you put your configuration files? IPython uses «profiles» for configuration, and by default, all profiles will be stored in the so called «IPython directory». The location of this directory is determined by the following algorithm:

- If the `ipython-dir` command line flag is given, its value is used.
- If not, the value returned by `IPython.paths.get_ipython_dir()` is used. This function will first look at the `IPYTHONDIR` environment variable and then default to `~/.ipython`. Historical support for the `IPYTHON_DIR` environment variable will be removed in a future release.

For most users, the configuration directory will be `~/.ipython`.

Previous versions of IPython on Linux would use the XDG config directory, creating `~/.config/ipython` by default. We have decided to go back to `~/.ipython` for consistency among systems. IPython will issue a warning if it finds the XDG location, and will move it to the new location if there isn't already a directory there.

Once the location of the IPython directory has been determined, you need to know which profile you are using. For users with a single configuration, this will simply be „default“, and will be located in `<IPYTHONDIR>/profile_default`.

The next thing you need to know is what to call your configuration file. The basic idea is that each application has its own default configuration filename. The default named used by the `ipython` command line program is `ipython_config.py`, and *all* IPython applications will use this file. The IPython kernel will load its own config file *after* `ipython_config.py`. To load a particular configuration file instead of the default, the name can be overridden by the `config_file` command line flag.

To generate the default configuration files, do:

```
$ ipython profile create
```

and you will have a default `ipython_config.py` in your IPython directory under `profile_default`.

Примечание: IPython configuration options are case sensitive, and IPython cannot catch misnamed keys or invalid values.

By default IPython will also ignore any invalid configuration files.

Добавлено в версии 5.0: IPython can be configured to abort in case of invalid configuration file. To do so set the environment variable `IPYTHON_SUPPRESS_CONFIG_ERRORS` to `'1'` or `'true'`

Locating these files

From the command-line, you can quickly locate the IPYTHONDIR or a specific profile with:

```
$ ipython locate
/home/you/.ipython

$ ipython locate profile foo
/home/you/.ipython/profile_foo
```

These map to the utility functions: `IPython.paths.get_ipython_dir()` and `IPython.paths.locate_profile()` respectively.

6.6.2 Profiles

A profile is a directory containing configuration and runtime files, such as logs, connection info for the parallel apps, and your IPython command history.

The idea is that users often want to maintain a set of configuration files for different purposes: one for doing numerical computing with NumPy and SciPy and another for doing symbolic computing with SymPy. Profiles make it easy to keep a separate configuration files, logs, and histories for each of these purposes.

Let's start by showing how a profile is used:

```
$ ipython --profile=sympy
```

This tells the `ipython` command line program to get its configuration from the «sympy» profile. The file names for various profiles do not change. The only difference is that profiles are named in a special way. In the case above, the «sympy» profile means looking for `ipython_config.py` in `<IPYTHONDIR>/profile_sympy`.

The general pattern is this: simply create a new profile with:

```
$ ipython profile create <name>
```

which adds a directory called `profile_<name>` to your IPython directory. Then you can load this profile by adding `--profile=<name>` to your command line options. Profiles are supported by all IPython applications.

IPython extends the config loader for Python files so that you can inherit config from another profile. To do this, use a line like this in your Python config file:

```
load_subconfig('ipython_config.py', profile='default')
```

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

6.7 IPython GUI Support Notes

IPython allows GUI event loops to be run in an interactive IPython session. This is done using Python's `PyOS_InputHook` hook which Python calls when the `raw_input()` function is called and waiting for user input. IPython has versions of this hook for `wx`, `pyqt4` and `pygtk`.

When a GUI program is used interactively within IPython, the event loop of the GUI should *not* be started. This is because, the `PyOS_Inputhook` itself is responsible for iterating the GUI event loop.

IPython has facilities for installing the needed input hook for each GUI toolkit and for creating the needed main GUI application object. Usually, these main application objects should be created only once and for some GUI toolkits, special options have to be passed to the application object to enable it to function properly in IPython.

We need to answer the following questions:

- Who is responsible for creating the main GUI application object, IPython or third parties (`matplotlib`, `enthought.traits`, etc.)?
- What is the proper way for third party code to detect if a GUI application object has already been created? If one has been created, how should the existing instance be retrieved?
- In a GUI application object has been created, how should third party code detect if the GUI event loop is running. It is not sufficient to call the relevant function methods in the GUI toolkits (like `IsMainLoopRunning`) because those don't know if the GUI event loop is running through the input hook.
- We might need a way for third party code to determine if it is running in IPython or not. Currently, the only way of running GUI code in IPython is by using the input hook, but eventually, GUI based versions of IPython will allow the GUI event loop in the more traditional manner. We will need a way for third party code to distinguish between these two cases.

Here is some sample code I have been using to debug this issue:

```
from matplotlib import pyplot as plt

from enthought.traits import api as traits

class Foo(traits.HasTraits):
    a = traits.Float()

f = Foo()
f.configure_traits()

plt.plot(range(10))
```

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

Guide for IPython core Developers

This guide documents the development of IPython itself. Alternatively, developers of third party tools and libraries that use IPython should see the *Developer's guide for third party tools and libraries*.

For instructions on how to make a developer install see *Installing the development version*.

7.1 Backporting Pull requests

All pull requests should usually be made against `main`, if a Pull Request need to be backported to an earlier release; then it should be tagged with the correct `milestone`.

If you tag a pull request with a milestone **before** merging the pull request, and the base ref is `main`, then our backport bot should automatically create a corresponding pull-request that backport on the correct branch.

If you have write access to the IPython repository you can also just mention the **backport bot** to do the work for you. The bot is evolving so instructions may be different. At the time of this writing you can use:

```
@meeseeksdev[bot] backport [to] <branchname>
```

The bot will attempt to backport the current pull-request and issue a PR if possible.

Примечание: The `@` and `[bot]` when mentioning the bot should be optional and can be omitted.

If the pull request cannot be automatically backported, the bot should tell you so on the PR and apply a «Need manual backport» tag to the origin PR.

7.2 IPython release process

This document contains the process that is used to create an IPython release.

Conveniently, the `release` script in the `tools` directory of the IPython repository automates most of the release process. This document serves as a handy reminder and checklist for the release manager.

During the release process, you might need the extra following dependencies:

- `keyring` to access your GitHub authentication tokens
- `graphviz` to generate some graphs in the documentation
- `ghpro` to generate the stats

Make sure you have all the required dependencies to run the tests as well.

You can try to `source tools/release_helper.sh` when releasing via bash, it should guide you through most of the process.

7.2.1 1. Set Environment variables

Set environment variables to document previous release tag, current release milestone, current release version, and git tag.

These variables may be used later to copy/paste as answers to the script questions instead of typing the appropriate command when the time comes. These variables are not used by the scripts directly; therefore, there is no need to `export` them. The format for bash is as follows, but note that these values are just an example valid only for the 5.0 release; you'll need to update them for the release you are actually making:

```
PREV_RELEASE=4.2.1
MILESTONE=5.0
VERSION=5.0.0
BRANCH=main
```

For [reproducibility of builds](#), we recommend setting `SOURCE_DATE_EPOCH` prior to running the build; record the used value of `SOURCE_DATE_EPOCH` as it may not be available from build artifact. You should be able to use `date +%s` to get a formatted timestamp:

```
SOURCE_DATE_EPOCH=$(date +%s)
```

7.2.2 2. Create GitHub stats and finish release note

Примечание: This step is optional if making a Beta or RC release.

Примечание: Before generating the GitHub stats, verify that all closed issues and pull requests have [appropriate milestones](#). [This search](#) should return no results before creating the GitHub stats.

If a major release:

- merge any pull request notes into what's new:

```
python tools/update_whatsnew.py
```

- update `docs/source/whatsnew/development.rst`, to ensure it covers the major release features
- move the contents of `development.rst` to `versionX.rst` where `X` is the numerical release version
- generate summary of GitHub contributions, which can be done with:

```
python tools/github_stats.py --milestone $MILESTONE > stats.rst
```

which may need some manual cleanup of `stats.rst`. Add the cleaned `stats.rst` results to `docs/source/whatsnew/github-stats-X.rst` where `X` is the numerical release version (don't forget to add it to the git repository as well). If creating a major release, make a new `github-stats-X.rst` file; if creating a minor release, the content from `stats.rst` may simply be added to the top of an existing `github-stats-X.rst` file.

- Edit `docs/source/whatsnew/index.rst` to list the new `github-stats-X` file you just created.
- You do not need to temporarily remove the first entry called `development`, nor re-add it after the release, it will automatically be hidden when releasing a stable version of IPython (if `_version_extra` in `release.py` is an empty string).

Make sure that the stats file has a header or it won't be rendered in the final documentation.

To find duplicates and update `.mailmap`, use:

```
git log --format="%aN <%aE>" $PREV_RELEASE... | sort -u -f
```

If a minor release you might need to do some of the above points manually, and forward port the changes.

7.2.3 3. Make sure the repository is clean

of any file that could be problematic.

Remove all non-tracked files with:

```
git clean -xdi
```

This will ask for confirmation before removing all untracked files. Make sure the `dist/` folder is clean to avoid any stale builds from previous build attempts.

7.2.4 4. Update the release version number

Edit `IPython/core/release.py` to have the current version.

in particular, update version number and `_version_extra` content in `IPython/core/release.py`.

Step 5 will validate your changes automatically, but you might still want to make sure the version number matches pep440.

In particular, `rc` and `beta` are not separated by `.` or the `sdist` and `bdist` will appear as different releases. For example, a valid version number for a release candidate (`rc`) release is: `1.3rc1`. Notice that there is no separator between the „3“ and the „r“. Check the environment variable `$VERSION` as well.

You will likely just have to modify/comment/uncomment one of the lines setting `_version_extra`

7.2.5 5. Run the tools/build_release script

Running `tools/build_release` does all the file checking and building that the real release script will do. This makes test installations, checks that the build procedure runs OK, and tests other steps in the release process.

The `build_release` script will in particular verify that the version number match PEP 440, in order to avoid surprise at the time of build upload.

We encourage creating a test build of the docs as well.

7.2.6 6. Create and push the new tag

Commit the changes to `release.py`:

```
git commit -am "release $VERSION" -S
git push origin $BRANCH
```

(omit the `-S` if you are no signing the package)

Create and push the tag:

```
git tag -am "release $VERSION" "$VERSION" -s
git push origin $VERSION
```

(omit the `-s` if you are no signing the package)

Update `release.py` back to `x.y-dev` or `x.y-maint` commit and push:

```
git commit -am "back to development" -S
git push origin $BRANCH
```

(omit the `-S` if you are no signing the package)

Now checkout the tag we just made:

```
git checkout $VERSION
```

7.2.7 7. Run the release script

Run the `release` script, this step requires having a current wheel, Python ≥ 3.4 and Python 2.7.:

```
./tools/release
```

This makes the tarballs and wheels, and puts them under the `dist/` folder. Be sure to test the `wheels` and the `sdist` locally before uploading them to PyPI. We do not use an universal wheel as each wheel installs an `ipython2` or `ipython3` script, depending on the version of Python it is built for. Using an universal wheel would prevent this.

Check the shasum of files with:

```
shasum -a 256 dist/*
```

and takes notes of them you might need them to update the conda-forge recipes. Rerun the command and check the hash have not changed:

```
./tools/release  
shasum -a 256 dist/*
```

Use the following to actually upload the result of the build:

```
./tools/release upload
```

It should posts them to `archive.ipython.org` and to PyPI.

PyPI/Warehouse will automatically hide previous releases. If you are uploading a non-stable version, make sure to log-in to PyPI and un-hide previous version.

7.2.8 8. Draft a short release announcement

The announcement should include:

- release highlights
- a link to the html version of the *What's new* section of the documentation
- a link to upgrade or installation tips (if necessary)

Post the announcement to the mailing list and or blog, and link from Twitter.

Примечание: If you are doing a RC or Beta, you can likely skip the next steps.

7.2.9 9. Update milestones on GitHub

These steps will bring milestones up to date:

- close the just released milestone
- open a new milestone for the next release (x, y+1), if the milestone doesn't exist already

7.2.10 10. Update the IPython website

The IPython website should document the new release:

- add release announcement (news, announcements)
- update current version and download links
- update links on the documentation page (especially if a major release)

7.2.11 11. Update readthedocs

Make sure to update readthedocs and set the latest tag as stable, as well as checking that previous release is still building under its own tag.

7.2.12 12. Update the Conda-Forge feedstock

Follow the instructions on [the repository](#)

7.2.13 13. Celebrate!

Celebrate the release and please thank the contributors for their work. Great job!

7.3 Old Documentation

Out of date documentation is still available and have been kept for archival purposes.

Примечание: Developers documentation used to be on the IPython wiki, but are now out of date. The wiki is though still available for historical reasons: [Old IPython GitHub Wiki](#).

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

The IPython API

<i>IPython</i>	IPython: tools for interactive and parallel computing in Python.
<i>IPython.core.alias</i>	System command aliases.
<i>IPython.core.application</i>	An application for IPython.
<i>IPython.core.async_helpers</i>	Async helper function that are invalid syntax on Python 3.5 and below.
<i>IPython.core.autocall</i>	Autocall capabilities for IPython.core.
<i>IPython.core.builtin_trap</i>	A context manager for managing things injected into <code>builtins</code> .
<i>IPython.core.compilerop</i>	Compiler tools with improved interactive support.
<i>IPython.core.completer</i>	Completion for IPython.
<i>IPython.core.completerlib</i>	Implementations for various useful completers.
<i>IPython.core.crashhandler</i>	sys.excepthook for IPython itself, leaves a detailed report on disk.
<i>IPython.core.debugger</i>	Pdb debugger class.
<i>IPython.core.error</i>	Global exception classes for IPython.core.
<i>IPython.core.events</i>	Infrastructure for registering and firing callbacks on application events.
<i>IPython.core.excolors</i>	Color schemes for exception handling code in IPython.
<i>IPython.core.extensions</i>	A class for managing IPython extensions.
<i>IPython.core.formatters</i>	Display formatters.
<i>IPython.core.getipython</i>	Simple function to call to get the current InteractiveShell instance
<i>IPython.core.guarded_eval</i>	
<i>IPython.core.history</i>	History related magics and functionality
<i>IPython.core.historyapp</i>	An application for managing IPython history.
<i>IPython.core.hooks</i>	Hooks for IPython.

continues on next page

Таблица 1 – продолжение с предыдущей страницы

<i>IPython.core.inputsplitter</i>	DEPRECATED: Input handling and transformation machinery.
<i>IPython.core.inputtransformer</i>	DEPRECATED: Input transformer classes to support IPython special syntax.
<i>IPython.core.inputtransformer2</i>	Input transformer machinery to support IPython special syntax.
<i>IPython.core.interactiveshell</i>	Main IPython class.
<i>IPython.core.logger</i>	Logger class for IPython's logging facilities.
<i>IPython.core.macro</i>	Support for interactive macros in IPython
<i>IPython.core.magic</i>	Magic functions for InteractiveShell.
<i>IPython.core.magic_arguments</i>	A decorator-based method of constructing IPython magics with <code>argparse</code> option handling.
<i>IPython.core.oinspect</i>	Tools for inspecting Python objects.
<i>IPython.core.page</i>	Paging capabilities for IPython.core
<i>IPython.core.payload</i>	Payload system for IPython.
<i>IPython.core.payloadpage</i>	A payload based version of page.
<i>IPython.core.prefilter</i>	Prefiltering components.
<i>IPython.core.profileapp</i>	An application for managing IPython profiles.
<i>IPython.core.profiledir</i>	An object for managing IPython profile directories.
<i>IPython.core.prompts</i>	Being removed
<i>IPython.core.pylabtools</i>	Pylab (matplotlib) support utilities.
<i>IPython.core.shellapp</i>	A mixin for <code>Application</code> classes that launch InteractiveShell instances, load extensions, etc.
<i>IPython.core.splitinput</i>	Simple utility for splitting user input.
<i>IPython.core.ultratb</i>	Verbose and colourful traceback formatting.
<i>IPython.display</i>	Public API for display tools in IPython.
<i>IPython.lib.backgroundjobs</i>	Manage background (threaded) jobs conveniently from an interactive shell.
<i>IPython.lib.clipboard</i>	Utilities for accessing the platform's clipboard.
<i>IPython.lib.deepreload</i>	Provides a <code>reload()</code> function that acts recursively.
<i>IPython.lib.demo</i>	Module for interactive demos using IPython.
<i>IPython.lib.editorhooks</i>	'editor' hooks for common editors that work well with <code>ipython</code>
<i>IPython.lib.guisupport</i>	Support for creating GUI apps and starting event loops.
<i>IPython.lib.latextools</i>	Tools for handling LaTeX.
<i>IPython.lib.lexers</i>	Defines a variety of Pygments lexers for highlighting IPython code.
<i>IPython.lib.pretty</i>	Python advanced pretty printer.
<i>IPython.paths</i>	Find files and directories which IPython uses.
<i>IPython.terminal.debugger</i>	
<i>IPython.terminal.embed</i>	An embedded IPython shell.
<i>IPython.terminal.interactiveshell</i>	IPython terminal interface using <code>prompt_toolkit</code>
<i>IPython.terminal.ipapp</i>	The <code>Application</code> object for the command line <code>ipython</code> program.
<i>IPython.terminal.magics</i>	Extra magics for terminal use.
<i>IPython.terminal.prompts</i>	Terminal input and output prompts.
<i>IPython.terminal.shortcuts</i>	Module to define and register Terminal IPython shortcuts with <code>prompt_toolkit</code>

continues on next page

Таблица 1 – продолжение с предыдущей страницы

<i>IPython.terminal.shortcuts.auto_match</i>	Utilities function for keybinding with prompt toolkit.
<i>IPython.terminal.shortcuts.auto_suggest</i>	
<i>IPython.terminal.shortcuts.filters</i>	Filters restricting scope of IPython Terminal shortcuts.
<i>IPython.testing.ipunittest</i>	Experimental code for cleaner support of IPython syntax with unittest.
<i>IPython.testing.skipdoctest</i>	Decorators marks that a doctest should be skipped.
<i>IPython.utils.PyColorize</i>	Class and program to colorize python source code for ANSI terminals.
<i>IPython.utils.capture</i>	IO capturing utilities.
<i>IPython.utils.colorable</i>	Color managing related utilities
<i>IPython.utils.coloransi</i>	Tools for coloring text in ANSI terminals.
<i>IPython.utils.contexts</i>	Miscellaneous context managers.
<i>IPython.utils.data</i>	Utilities for working with data structures like lists, dicts and tuples.
<i>IPython.utils.decorators</i>	Decorators that don't go anywhere else.
<i>IPython.utils.dir2</i>	A fancy version of Python's builtin <code>dir()</code> function.
<i>IPython.utils.encoding</i>	Utilities for dealing with text encodings
<i>IPython.utils.frame</i>	Utilities for working with stack frames.
<i>IPython.utils.generics</i>	Generic functions for extending IPython.
<i>IPython.utils.importstring</i>	A simple utility to import something by its string name.
<i>IPython.utils.io</i>	IO related utilities.
<i>IPython.utils.ipstruct</i>	A dict subclass that supports attribute style access.
<i>IPython.utils.module_paths</i>	Utility functions for finding modules
<i>IPython.utils.openpy</i>	Tools to open .py files as Unicode, using the encoding specified within the file, as per PEP 263.
<i>IPython.utils.path</i>	Utilities for path handling.
<i>IPython.utils.process</i>	Utilities for working with external processes.
<i>IPython.utils.sentinel</i>	Sentinel class for constants with useful reprs
<i>IPython.utils.shimmodule</i>	A shim module for deprecated imports
<i>IPython.utils.strdispatch</i>	String dispatch class to match regexps and dispatch commands.
<i>IPython.utils.sysinfo</i>	Utilities for getting information about IPython and the system it's running in.
<i>IPython.utils.syspathcontext</i>	Context managers for adding things to sys.path temporarily.
<i>IPython.utils.tempdir</i>	This module contains classes - <code>NamedFileInTemporaryDirectory</code> , <code>TemporaryWorkingDirectory</code> .
<i>IPython.utils.terminal</i>	Utilities for working with terminals.
<i>IPython.utils.text</i>	Utilities for working with strings and text.
<i>IPython.utils.timing</i>	Utilities for timing code execution.
<i>IPython.utils.tokenutil</i>	Token-related utilities
<i>IPython.utils.tz</i>	Timezone utilities
<i>IPython.utils.ulinecache</i>	This module has been deprecated since IPython 6.0.
<i>IPython.utils.wildcard</i>	Support for wildcard pattern matching in object inspection.

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

8.1 IPython

IPython: tools for interactive and parallel computing in Python.

<https://ipython.org>

8.1.1 4 Functions

`IPython.embed(*, header='', compile_flags=None, **kwargs)`

Call this to embed IPython at the current point in your program.

The first invocation of this will create a `terminal.embed.InteractiveShellEmbed` instance and then call it. Consecutive calls just call the already created instance.

If you don't want the kernel to initialize the namespace from the scope of the surrounding function, and/or you want to load full IPython configuration, you probably want `IPython.start_ipython()` instead.

Here is a simple example:

```
from IPython import embed
a = 10
b = 20
embed(header='First time')
c = 30
d = 40
embed()
```

Параметры

- `header` (*str*) – Optional header string to print at startup.
- `compile_flags` – Passed to the `compile_flags` parameter of `terminal.embed.InteractiveShellEmbed.mainloop()`, which is called when the `terminal.embed.InteractiveShellEmbed` instance is called.
- `**kwargs` (*various, optional*) – Any other kwargs will be passed to the `terminal.embed.InteractiveShellEmbed` constructor. Full customization can be done by passing a traitlets `Config` in as the `config` argument (see *Running IPython from Python* and *Terminal IPython options*).

`IPython.embed_kernel(module=None, local_ns=None, **kwargs)`

Embed and start an IPython kernel in a given scope.

If you don't want the kernel to initialize the namespace from the scope of the surrounding function, and/or you want to load full IPython configuration, you probably want `IPython.start_kernel()` instead.

Параметры

- `module` (*types.ModuleType*, *optional*) – The module to load into IPython globals (default: caller)
- `local_ns` (*dict*, *optional*) – The namespace to load into IPython user namespace (default: caller)
- `**kwargs` (*various*, *optional*) – Further keyword args are relayed to the `IPKernelApp` constructor, such as `config`, a traitlets `Config` object (see [Running IPython from Python](#)), allowing configuration of the kernel (see [IPython kernel options](#)). Will only have an effect on the first `embed_kernel` call for a given process.

`IPython.start_ipython(argv=None, **kwargs)`

Launch a normal IPython instance (as opposed to embedded)

`IPython.embed()` puts a shell in a particular calling scope, such as a function or method for debugging purposes, which is often not desirable.

`start_ipython()` does full, regular IPython initialization, including loading startup files, configuration, etc. much of which is skipped by `embed()`.

This is a public API method, and will survive implementation changes.

Параметры

- `argv` (*list or None*, *optional*) – If unspecified or `None`, IPython will parse command-line options from `sys.argv`. To prevent any command-line parsing, pass an empty list: `argv=[]`.
- `user_ns` (*dict*, *optional*) – specify this dictionary to initialize the IPython user namespace with particular values.
- `**kwargs` (*various*, *optional*) – Any other kwargs will be passed to the Application constructor, such as `config`, a traitlets `Config` object (see [Running IPython from Python](#)), allowing configuration of the instance (see [Terminal IPython options](#)).

`IPython.start_kernel(argv=None, **kwargs)`

Launch a normal IPython kernel instance (as opposed to embedded)

`IPython.embed_kernel()` puts a shell in a particular calling scope, such as a function or method for debugging purposes, which is often not desirable.

`start_kernel()` does full, regular IPython initialization, including loading startup files, configuration, etc. much of which is skipped by `embed_kernel()`.

Параметры

- `argv` (*list or None*, *optional*) – If unspecified or `None`, IPython will parse command-line options from `sys.argv`. To prevent any command-line parsing, pass an empty list: `argv=[]`.
- `user_ns` (*dict*, *optional*) – specify this dictionary to initialize the IPython user namespace with particular values.

- ****kwargs** (*various, optional*) – Any other kwargs will be passed to the Application constructor, such as `config`, a traitlets `Config` object (see [Running IPython from Python](#)), allowing configuration of the kernel (see [IPython kernel options](#)).

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

8.2 Module: `core.alias`

System command aliases.

Authors:

- Fernando Perez
- Brian Granger

8.2.1 4 Classes

```
class IPython.core.alias.AliasError
```

Базовые классы: `Exception`

```
class IPython.core.alias.InvalidAliasError
```

Базовые классы: `AliasError`

```
class IPython.core.alias.Alias(shell, name, cmd)
```

Базовые классы: `object`

Callable object storing the details of one alias.

Instances are registered as magic functions to allow use of aliases.

```
__init__(shell, name, cmd)
```

```
validate()
```

Validate the alias, and return the number of arguments.

```
class IPython.core.alias.AliasManager(**kwargs: Any)
```

Базовые классы: `Configurable`

```
__init__(shell=None, **kwargs)
```

Create a configurable given a config config.

Параметры

- `config` (*Config*) – If this is empty, default values are used. If `config` is a `Config` instance, it will be used to configure the instance.
- `parent` (*Configurable instance, optional*) – The parent `Configurable` instance of this object.

Заметки

Subclasses of `Configurable` must call the `__init__()` method of `Configurable` *before* doing anything else and using `super()`:

```
class MyConfigurable(Configurable):
    def __init__(self, config=None):
        super(MyConfigurable, self).__init__(config=config)
        # Then any other code you need to finish initialization.
```

This ensures that instances will be configured properly.

`define_alias(name, cmd)`

Define a new alias after validating it.

This will raise an *AliasError* if there are validation problems.

`get_alias(name)`

Return an alias, or None if no alias by that name exists.

`is_alias(name)`

Return whether or not a given name has been defined as an alias

`retrieve_alias(name)`

Retrieve the command to which an alias expands.

`soft_define_alias(name, cmd)`

Define an alias, but don't raise on an *AliasError*.

8.2.2 1 Function

`IPython.core.alias.default_aliases()`

Return list of shell aliases to auto-define.

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

8.3 Module: `core.application`

An application for IPython.

All top-level applications should use the classes in this module for handling configuration and creating configurables.

The job of an `Application` is to create the master configuration object and then create the configurable objects, passing the config to them.

8.3.1 2 Classes

```
class IPython.core.application.ProfileAwareConfigLoader(filename, path=None, **kw)
```

Базовые классы: `PyFileConfigLoader`

A Python file config loader that is aware of IPython profiles.

```
load_subconfig(fname, path=None, profile=None)
```

Injected into config file namespace as `load_subconfig`

```
class IPython.core.application.BaseIPythonApplication(**kwargs: Any)
```

Базовые классы: `Application`

```
__init__(**kwargs)
```

Create a configurable given a config config.

Параметры

- `config` (*Config*) – If this is empty, default values are used. If config is a `Config` instance, it will be used to configure the instance.
- `parent` (*Configurable instance, optional*) – The parent `Configurable` instance of this object.

Заметки

Subclasses of `Configurable` must call the `__init__()` method of `Configurable` *before* doing anything else and using `super()`:

```
class MyConfigurable(Configurable):
    def __init__(self, config=None):
        super(MyConfigurable, self).__init__(config=config)
        # Then any other code you need to finish initialization.
```

This ensures that instances will be configured properly.

`auto_create`

Whether to create profile dir if it doesn't exist

`copy_config_files`

Whether to install the default config files into the profile dir. If a new profile is being created, and IPython contains config files for that profile, then they will be staged into the new directory. Otherwise, default config files will be automatically generated.

`excepthook(etype, eval, tb)`

this is `sys.excepthook` after `init_crashhandler`

set `self.verbose_crash=True` to use our full crashhandler, instead of a regular traceback with a short message (`crash_handler_lite`)

`extra_config_file`

Path to an extra config file to load.

If specified, load this config file in addition to any other IPython config.

`init_config_files()`

[optionally] copy default config files into profile dir.

`init_crash_handler()`

Create a crash handler, typically setting `sys.excepthook` to it.

`init_profile_dir()`

initialize the profile dir

`initialize(argv=None)`

Do the basic steps to configure me.

Override in subclasses.

`ipython_dir`

The name of the IPython directory. This directory is used for logging configuration (through profiles), history storage, etc. The default is usually `$HOME/.ipython`. This option can also be specified through the environment variable `IPYTHONDIR`.

`load_config_file(suppress_errors=None)`

Load the config file.

By default, errors in loading config are handled, and a warning printed on screen. For testing, the `suppress_errors` option is set to `False`, so errors will make tests fail.

`suppress_errors` default value is to be `None` in which case the behavior default to the one of `traitlets.Application`.

The default value can be set :

- to `False` by setting „`IPYTHON_SUPPRESS_CONFIG_ERRORS`“ environment variable to „0“, or „false“ (case insensitive).
- to `True` by setting „`IPYTHON_SUPPRESS_CONFIG_ERRORS`“ environment variable to „1“ or „true“ (case insensitive).
- to `None` by setting „`IPYTHON_SUPPRESS_CONFIG_ERRORS`“ environment variable to „“ (empty string) or leaving it unset.

Any other value are invalid, and will make IPython exit with a non-zero return code.

`overwrite`

Whether to overwrite existing config files when copying

`profile`

The IPython profile to use.

`python_config_loader_class`

alias of *ProfileAwareConfigLoader*

`stage_default_config_file()`

auto generate default config file, and stage it into the profile.

`verbose_crash`

Create a massive crash report when IPython encounters what may be an internal error. The default is to append a short message to the usual traceback

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

8.4 Module: `core.async_helpers`

Async helper function that are invalid syntax on Python 3.5 and below.

This code is best effort, and may have edge cases not behaving as expected. In particular it contain a number of heuristics to detect whether code is effectively async and need to run in an event loop or not.

Some constructs (like top-level `return`, or `yield`) are taken care of explicitly to actually raise a `SyntaxError` and stay as close as possible to Python semantics.

8.4.1 1 Function

`IPython.core.async_helpers.get_asyncio_loop()`

asyncio has deprecated `get_event_loop`

Replicate it here, with our desired semantics:

- always returns a valid, not-closed loop
- not thread-local like asyncio's, because we only want one loop for IPython
- if called from inside a coroutine (e.g. in `ipykernel`), return the running loop

Добавлено в версии 8.0.

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

8.5 Module: `core.autocall`

Autocall capabilities for IPython.core.

Authors:

- Brian Granger
- Fernando Perez
- Thomas Kluyver

Заметки

8.5.1 3 Classes

`class IPython.core.autocall.IPyAutocall(ip=None)`

Базовые классы: `object`

Instances of this class are always autocalled

This happens regardless of „autocall“ variable state. Use this to develop macro-like mechanisms.

`__init__(ip=None)`

`set_ip(ip)`

Will be used to set `_ip` point to current ipython instance b/f call

Override this method if you don't want this to happen.

`class IPython.core.autocall.ExitAutocall(ip=None)`

Базовые классы: `IPyAutocall`

An autocallable object which will be added to the user namespace so that `exit`, `exit()`, `quit` or `quit()` are all valid ways to close the shell.

`class IPython.core.autocall.ZMQExitAutocall(ip=None)`

Базовые классы: `ExitAutocall`

Exit IPython. Autocallable, so it needn't be explicitly called.

Параметры

`keep_kernel (bool)` – If True, leave the kernel alive. Otherwise, tell the kernel to exit too (default).

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

8.6 Module: `core.builtin_trap`

A context manager for managing things injected into `builtins`.

8.6.1 1 Class

```
class IPython.core.builtin_trap.BuiltinTrap(**kwargs: Any)
```

Базовые классы: `Configurable`

```
__init__(shell=None)
```

Create a configurable given a config config.

Параметры

- `config` (*Config*) – If this is empty, default values are used. If config is a `Config` instance, it will be used to configure the instance.
- `parent` (*Configurable instance, optional*) – The parent `Configurable` instance of this object.

Заметки

Subclasses of `Configurable` must call the `__init__()` method of `Configurable` *before* doing anything else and using `super()`:

```
class MyConfigurable(Configurable):
    def __init__(self, config=None):
        super(MyConfigurable, self).__init__(config=config)
        # Then any other code you need to finish initialization.
```

This ensures that instances will be configured properly.

```
activate()
```

Store ipython references in the `__builtin__` namespace.

```
add_builtin(key, value)
```

Add a builtin and save the original.

```
deactivate()
```

Remove any builtins which might have been added by `add_builtins`, or restore overwritten ones to their previous values.

```
remove_builtin(key, orig)
```

Remove an added builtin and re-set the original.

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

8.7 Module: `core.compilerop`

Compiler tools with improved interactive support.

Provides compilation machinery similar to `codeop`, but with caching support so we can provide interactive tracebacks.

8.7.1 Authors

- Robert Kern
- Fernando Perez
- Thomas Kluyver

8.7.2 1 Class

`class IPython.core.compilerop.CachingCompiler`

Базовые классы: `Compile`

A compiler that caches code compiled from interactive statements.

`__init__()`

`ast_parse(source, filename='<unknown>', symbol='exec')`

Parse code to an AST with the current compiler flags active.

Arguments are exactly the same as `ast.parse` (in the standard library), and are passed to the built-in compile function.

`cache(transformed_code, number=0, raw_code=None)`

Make a name for a block of code, and cache the code.

Параметры

- `transformed_code` (*str*) – The executable Python source code to cache and compile.
- `number` (*int*) – A number which forms part of the code's name. Used for the execution counter.
- `raw_code` (*str*) – The raw code before transformation, if None, set to `transformed_code`.

Результат

- *The name of the cached code (as a string). Pass this as the filename*
- *argument to compilation, so that tracebacks are correctly hooked up.*

property `compiler_flags`

Flags currently active in the compilation process.

`format_code_name(name)`

Return a user-friendly label and name for a code block.

Параметры

`name` (*str*) – The name for the code block returned from `get_code_name`

Тип результата

A (label, name) pair that can be used in tracebacks, or None if the default formatting should be used.

`get_code_name(raw_code, transformed_code, number)`

Compute filename given the code, and the cell number.

Параметры

- `raw_code` (*str*) – The raw cell code.
- `transformed_code` (*str*) – The executable Python source code to cache and compile.
- `number` (*int*) – A number which forms part of the code's name. Used for the execution counter.

Тип результата

The computed filename.

`reset_compiler_flags()`

Reset compiler flags to default state.

8.7.3 2 Functions

`IPython.core.compilerop.code_name(code, number=0)`

Compute a (probably) unique name for code for caching.

This now expects code to be unicode.

`IPython.core.compilerop.check_linecache_ipython(*args)`

Deprecated since IPython 8.6. Call `linecache.checkcache()` directly.

It was already not necessary to call this function directly. If no `CachingCompiler` had been created, this function would fail badly. If an instance had been created, this function would've been monkeypatched into place.

As of IPython 8.6, the monkeypatching has gone away entirely. But there were still internal callers of this function, so maybe external callers also existed?

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

8.8 Module: `core.completer`

Completion for IPython.

This module started as fork of the `rlcompleter` module in the Python standard library. The original enhancements made to `rlcompleter` have been sent upstream and were accepted as of Python 2.3,

This module now support a wide variety of completion mechanism both available for normal classic Python code, as well as completer for IPython specific Syntax like magics.

8.8.1 Latex and Unicode completion

IPython and compatible frontends not only can complete your code, but can help you to input a wide range of characters. In particular we allow you to insert a unicode character using the tab completion mechanism.

Forward latex/unicode completion

Forward completion allows you to easily type a unicode character using its latex name, or unicode long description. To do so type a backslash follow by the relevant name and press tab:

Using latex completion:

```
\alpha<tab>
```

or using unicode completion:

```
\GREEK SMALL LETTER ALPHA<tab>
```

Only valid Python identifiers will complete. Combining characters (like arrow or dots) are also available, unlike latex they need to be put after the their counterpart that is to say, `F\\vec<tab>` is correct, not `\\vec<tab>F`.

Some browsers are known to display combining characters incorrectly.

Backward latex completion

It is sometime challenging to know how to type a character, if you are using IPython, or any compatible frontend you can prepend backslash to the character and press **Tab** to expand it to its latex form.

```
\<tab>
\alpha
```

Both forward and backward completions can be deactivated by setting the `Completer.backslash_combining_completions` option to `False`.

8.8.2 Experimental

Starting with IPython 6.0, this module can make use of the Jedi library to generate completions both using static analysis of the code, and dynamically inspecting multiple namespaces. Jedi is an autocompletion and static analysis for Python. The APIs attached to this new mechanism is unstable and will raise unless use in an *provisionalcompleter* context manager.

You will find that the following are experimental:

- *provisionalcompleter*
- *IPCompleter.completions*
- *Completion*
- *rectify_completions*

Примечание: better name for *rectify_completions* ?

We welcome any feedback on these new API, and we also encourage you to try this module in debug mode (start IPython with `--Completer.debug=True`) in order to have extra logging information if *jedi* is crashing, or if current IPython completer pending deprecations are returning results not yet handled by *jedi*

Using Jedi for tab completion allow snippets like the following to work without having to execute any code:

```
>>> myvar = ['hello', 42]
... myvar[1].bi<tab>
```

Tab completion will be able to infer that `myvar[1]` is a real number without executing almost any code unlike the deprecated *IPCompleter.greedy* option.

Be sure to update *jedi* to the latest stable version or to try the current development version to get better completions.

8.8.3 Matchers

All completions routines are implemented using unified *Matchers* API. The matchers API is provisional and subject to change without notice.

The built-in matchers include:

- *IPCompleter.dict_key_matcher*: dictionary key completions,
- *IPCompleter.magic_matcher*: completions for magics,
- *IPCompleter.unicode_name_matcher*, *IPCompleter.fwd_unicode_matcher* and *IPCompleter.latex_name_matcher*: see *Forward latex/unicode completion*,
- *back_unicode_name_matcher* and *back_latex_name_matcher*: see *Backward latex completion*,
- *IPCompleter.file_matcher*: paths to files and directories,
- *IPCompleter.python_func_kw_matcher* - function keywords,
- *IPCompleter.python_matches* - globals and attributes (v1 API),
- *IPCompleter.jedi_matcher* - static analysis with Jedi,
- *IPCompleter.custom_completer_matcher* - pluggable completer with a default implementation in *InteractiveShell* which uses IPython hooks system (`complete_command`) with string dispatch

(including regular expressions). Differently to other matchers, `custom_completer_matcher` will not suppress Jedi results to match behaviour in earlier IPython versions.

Custom matchers can be added by appending to `IPCompleter.custom_matchers` list.

Matcher API

Simplifying some details, the `Matcher` interface can be described as

```
MatcherAPIv1 = Callable[[str], list[str]]
MatcherAPIv2 = Callable[[CompletionContext], SimpleMatcherResult]

Matcher = MatcherAPIv1 | MatcherAPIv2
```

The `MatcherAPIv1` reflects the matcher API as available prior to IPython 8.6.0 and remains supported as a simplest way for generating completions. This is also currently the only API supported by the IPython hooks system `complete_command`.

To distinguish between matcher versions `matcher_api_version` attribute is used. More precisely, the API allows to omit `matcher_api_version` for v1 Matchers, and requires a literal 2 for v2 Matchers.

Once the API stabilises future versions may relax the requirement for specifying `matcher_api_version` by switching to `functools singledispatch`, therefore please do not rely on the presence of `matcher_api_version` for any purposes.

Suppression of competing matchers

By default results from all matchers are combined, in the order determined by their priority. Matchers can request to suppress results from subsequent matchers by setting `suppress` to `True` in the `MatcherResult`.

When multiple matchers simultaneously request suppression, the results from of the matcher with higher priority will be returned.

Sometimes it is desirable to suppress most but not all other matchers; this can be achieved by adding a set of identifiers of matchers which should not be suppressed to `MatcherResult` under `do_not_suppress` key.

The suppression behaviour can be user-configurable via `IPCompleter.suppress_competing_matchers`.

8.8.4 9 Classes

`class IPython.core.completer.ProvisionalCompleterWarning`

Базовые классы: `FutureWarning`

Exception raised by an experimental feature in this module.

Wrap code in `provisionalcompleter` context manager if you are certain you want to use an unstable feature.

`class IPython.core.completer.Completion(start: int, end: int, text: str, *, type: Optional[str] = None, _origin='', signature='')`

Базовые классы: `object`

Completion object used and returned by IPython completers.

Предупреждение: Unstable

This function is unstable, API may change without warning. It will also raise unless use in proper context manager.

This act as a middle ground *Completion* object between the `jedi.api.classes.Completion` object and the Prompt Toolkit completion object. While Jedi need a lot of information about evaluator and how the code should be ran/inspected, PromptToolkit (and other frontend) mostly need user facing information.

- Which range should be replaced replaced by what.
- Some metadata (like completion type), or meta information to displayed to the use user.

For debugging purpose we can also store the origin of the completion (`jedi`, `IPython.python_matches`, `IPython.magics_matches...`).

```
__init__(start: int, end: int, text: str, *, type: Optional[str] = None, _origin='', signature='') → None
```

```
class IPython.core.completer.SimpleCompletion(text: str, *, type: Optional[str] = None)
```

Базовые классы: `object`

Completion item to be included in the dictionary returned by new-style Matcher (API v2).

Предупреждение: Provisional

This class is used to describe the currently supported attributes of simple completion items, and any additional implementation details should not be relied on. Additional attributes may be included in future versions, and meaning of text disambiguated from the current dual meaning of «text to insert» and «text to used as a label».

```
__init__(text: str, *, type: Optional[str] = None)
```

```
class IPython.core.completer.SimpleMatcherResult
```

Базовые классы: `_MatcherResultBase`, `Dict`

Result of new-style completion matcher.

```
completions: Union[Sequence[SimpleCompletion], Iterator[SimpleCompletion]]
```

List of candidate completions

```
class IPython.core.completer.CompletionContext(token: str, full_text: str, cursor_position: int, cursor_line: int, limit: Optional[int])
```

Базовые классы: `object`

Completion context provided as an argument to matchers in the Matcher API v2.

```
cursor_line: int
```

Cursor line in `full_text`.

```
cursor_position: int
```

Cursor position in the line (the same for `full_text` and `text`).

```
full_text: str
```

The full available content of the editor or buffer

`token: str`

Relevant fragment of code directly preceding the cursor. The extraction of token is implemented via splitter heuristic (following readline behaviour for legacy reasons), which is user configurable (by switching the greedy mode).

`class IPython.core.completer.MatcherAPIv2`

Базовые классы: `object`

Protocol describing Matcher API v2.

`matcher_api_version: Literal[2] = 2`

API version

`class IPython.core.completer.CompletionSplitter(delims=None)`

Базовые классы: `object`

An object to split an input line in a manner similar to readline.

By having our own implementation, we can expose readline-like completion in a uniform manner to all frontends. This object only needs to be given the line of text to be split and the cursor position on said line, and it returns the „word“ to be completed on at the cursor after splitting the entire line.

What characters are used as splitting delimiters can be controlled by setting the `delims` attribute (this is a property that internally automatically builds the necessary regular expression)

`__init__(delims=None)`

property `delims`

Return the string of delimiter characters.

`split_line(line, cursor_pos=None)`

Split a line of text with a cursor at the given position.

`class IPython.core.completer.Completer(**kwargs: Any)`

Базовые классы: `Configurable`

`__init__(namespace=None, global_namespace=None, **kwargs)`

Create a new completer for the command line.

`Completer(namespace=ns, global_namespace=ns2) -> completer instance.`

If unspecified, the default namespace where completions are performed is `__main__` (technically, `__main__.__dict__`). Namespaces should be given as dictionaries.

An optional second namespace can be given. This allows the completer to handle cases where both the local and global scopes need to be distinguished.

`attr_matches(text)`

Compute matches when text contains a dot.

Assuming the text is of the form `NAME.NAME...[NAME]`, and is evaluable in `self.namespace` or `self.global_namespace`, it will be evaluated and its attributes (as revealed by `dir()`) are used as possible completions. (For class instances, class members are also considered.)

WARNING: this can still invoke arbitrary C code, if an object with a `__getattr__` hook is evaluated.

property `auto_close_dict_keys`

Enable auto-closing dictionary keys.

When enabled string keys will be suffixed with a final quote (matching the opening quote), tuple keys will also receive a separating comma if needed, and keys which are final will receive a closing bracket (]).

`backslash_combining_completions`

Enable unicode completions, e.g. `alpha<tab>` . Includes completion of latex commands, unicode names, and expanding unicode characters back to latex commands.

`complete(text, state)`

Return the next possible completion for „text“.

This is called successively with `state == 0, 1, 2, ...` until it returns `None`. The completion should begin with „text“.

`debug`

Enable debug for the Completer. Mostly print extra information for experimental jedi integration.

`evaluation`

Policy for code evaluation under completion.

Successive options allow to enable more eager evaluation for better completion suggestions, including for nested dictionaries, nested lists, or even results of function calls. Setting `unsafe` or higher can lead to evaluation of arbitrary user code on `Tab` with potentially unwanted or dangerous side effects.

Allowed values are:

- `forbidden`: no evaluation of code is permitted,
- `minimal`: evaluation of literals and access to built-in namespace; no item/attribute evaluation, no access to locals/globals, no evaluation of any operations or comparisons.
- `limited`: access to all namespaces, evaluation of hard-coded methods (for example: `dict.keys`, `object.__getattr__`, `object.__getitem__`) on allow-listed objects (for example: `dict`, `list`, `tuple`, `pandas.Series`),
- `unsafe`: evaluation of all methods and function calls but not of syntax with side-effects like `del x`,
- `dangerous`: completely arbitrary evaluation.

`global_matches(text)`

Compute matches when text is a simple name.

Return a list of all keywords, built-in functions and names currently defined in `self.namespace` or `self.global_namespace` that match.

`greedy`

Activate greedy completion.

Не рекомендуется, начиная с версии 8.8: Use `Completer.evaluation` and `Completer.auto_close_dict_keys` instead.

When enabled in IPython 8.8 or newer, changes configuration as follows:

- `Completer.evaluation = 'unsafe'`
- `Completer.auto_close_dict_keys = True`

`jedi_compute_type_timeout`

restrict time (in milliseconds) during which Jedi can compute types. Set to 0 to stop computing types. Non-zero value lower than 100ms may hurt performance by preventing jedi to build its cache.

Type

Experimental

`use_jedi`

Use Jedi to generate autocompletions. Default to True if jedi is installed.

Type

Experimental

`class IPython.core.completer.IPCompleter(**kwargs: Any)`Базовые классы: *Completer*

Extension of the completer class with IPython-specific features

`__init__(shell=None, namespace=None, global_namespace=None, config=None, **kwargs)`

IPCompleter() -> completer

Return a completer object.

Параметры

- `shell` – a pointer to the ipython shell itself. This is needed because this completer knows about magic functions, and those can only be accessed via the ipython instance.
- `namespace` (*dict*, *optional*) – an optional dict where completions are performed.
- `global_namespace` (*dict*, *optional*) – secondary optional dict for completions, to handle cases (such as IPython embedded inside functions) where both Python scopes are visible.
- `config` (*Config*) – traitlet’s config object
- `**kwargs` – passed to super class unmodified.

`all_completions(text: str) → List[str]`

Wrapper around the completion methods for the benefit of emacs.

`complete(text=None, line_buffer=None, cursor_pos=None) → Tuple[str, Sequence[str]]`

Find completions for the given text and line context.

Note that both the text and the line_buffer are optional, but at least one of them must be given.

Параметры

- `text` (*string*, *optional*) – Text to perform the completion on. If not given, the line buffer is split using the instance’s CompletionSplitter object.
- `line_buffer` (*string*, *optional*) – If not given, the completer attempts to obtain the current line buffer via readline. This keyword allows clients which are requesting for text completions in non-readline contexts to inform the completer of the entire text.
- `cursor_pos` (*int*, *optional*) – Index of the cursor in the full line buffer. Should be provided by remote frontends where kernel has no access to frontend state.

Результат

- *Tuple of two items*
- `text` (*str*) – Text that was actually used in the completion.
- `matches` (*list*) – A list of completion matches.

Заметки

This API is likely to be deprecated and replaced by *IPCompleter.completions* in the future.

`completions(text: str, offset: int) → Iterator[Completion]`

Returns an iterator over the possible completions

Предупреждение: Unstable

This function is unstable, API may change without warning. It will also raise unless use in proper context manager.

Параметры

- `text` (*str*) – Full text of the current input, multi line string.
- `offset` (*int*) – Integer representing the position of the cursor in `text`. Offset is 0-based indexed.

Yields

Completion

Заметки

The cursor on a text can either be seen as being «in between» characters or «On» a character depending on the interface visible to the user. For consistency the cursor being on «in between» characters X and Y is equivalent to the cursor being «on» character Y, that is to say the character the cursor is on is considered as being after the cursor.

Combining characters may span more than one position in the text.

Примечание: If `IPCompleter.debug` is `True` will yield a `--jedi/ipython--` fake Completion token to distinguish completion returned by Jedi and usual IPython completion.

Примечание: Completions are not completely deduplicated yet. If identical completions are coming from different sources this function does not ensure that each completion object will only be present once.

`custom_completer_matcher(context)`

Dispatch custom completer.

If a match is found, suppresses all other matchers except for Jedi.

`dict_key_matcher(context: CompletionContext) → SimpleMatcherResult`

Match string keys in a dictionary, after e.g. `foo[`.

`dict_key_matches(text: str) → List[str]`

Match string keys in a dictionary, after e.g. `foo[`.

Не рекомендуется, начиная с версии 8.6: You can use `dict_key_matcher()` instead.

`dict_keys_only`

Whether to show dict key matches only.

(disables all matchers except for `IPCompleter.dict_key_matcher`).

`disable_matchers`

List of matchers to disable.

The list should contain matcher identifiers (see `completion_matcher`).

`dispatch_custom_completer(text)`

Не рекомендуется, начиная с версии 8.6: You can use `custom_completer_matcher()` instead.

`file_matcher(context: CompletionContext) → SimpleMatcherResult`

Same as `file_matches`, but adopted to new Matcher API.

`file_matches(text: str) → List[str]`

Match filenames, expanding `~USER` type strings.

Most of the seemingly convoluted logic in this completer is an attempt to handle filenames with spaces in them. And yet it's not quite perfect, because Python's readline doesn't expose all of the GNU readline details needed for this to be done correctly.

For a filename with a space in it, the printed completions will be only the parts after what's already been typed (instead of the full completions, as is normally done). I don't think with the current (as of Python 2.3) Python readline it's possible to do better.

Не рекомендуется, начиная с версии 8.6: You can use `file_matcher()` instead.

`fwd_unicode_match(text: str) → Tuple[str, Sequence[str]]`

Forward match a string starting with a backslash with a list of potential Unicode completions.

Will compute list of Unicode character names on first call and cache it.

Не рекомендуется, начиная с версии 8.6: You can use `fwd_unicode_matcher()` instead.

Результат

- matched text (empty if no matches)
- list of potential completions, empty tuple otherwise)

Тип результата

At tuple with

`fwd_unicode_matcher(context: CompletionContext)`

Same as `fwd_unicode_match`, but adopted to new Matcher API.

`latex_matches(text: str) → Tuple[str, Sequence[str]]`

Match Latex syntax for unicode characters.

This does both `\alp -> \alpha` and `\alpha ->`

Не рекомендуется, начиная с версии 8.6: You can use `latex_name_matcher()` instead.

`latex_name_matcher(context: CompletionContext)`

Match Latex syntax for unicode characters.

This does both `\alp -> \alpha` and `\alpha ->`

`limit_to__all__`

DEPRECATED as of version 5.0.

Instruct the completer to use `__all__` for the completion

Specifically, when completing on `object.<tab>`.

When True: only those names in `obj.__all__` will be included.

When False [default]: the `__all__` attribute is ignored

`magic_color_matcher(context: CompletionContext) → SimpleMatcherResult`

Match color schemes for `%colors` magic.

`magic_color_matches(text: str) → List[str]`

Match color schemes for `%colors` magic.

He рекомендуется, начиная с версии 8.6: You can use `magic_color_matcher()` instead.

`magic_config_matcher(context: CompletionContext) → SimpleMatcherResult`

Match class names and attributes for `%config` magic.

`magic_config_matches(text: str) → List[str]`

Match class names and attributes for `%config` magic.

He рекомендуется, начиная с версии 8.6: You can use `magic_config_matcher()` instead.

`magic_matcher(context: CompletionContext) → SimpleMatcherResult`

Match magics.

`magic_matches(text: str)`

Match magics.

He рекомендуется, начиная с версии 8.6: You can use `magic_matcher()` instead.

`property matchers: List[IPython.core.completer.Matcher]`

All active matcher routines for completion

`merge_completions`

Whether to merge completion results into a single list

If False, only the completion results from the first non-empty completer will be returned.

As of version 8.6.0, setting the value to `False` is an alias for: `IPCompleter.suppress_competing_matchers = True..`

`omit__names`

Instruct the completer to omit private method names

Specifically, when completing on `object.<tab>`.

When 2 [default]: all names that start with „`_`“ will be excluded.

When 1: all „magic“ names (`__foo__`) will be excluded.

When 0: nothing will be excluded.

`profile_completions`

If True, emit profiling data for completion subsystem using `cProfile`.

`profiler_output_dir`

Template for path at which to output profile data for completions.

`python_func_kw_matcher(context: CompletionContext) → SimpleMatcherResult`

Match named parameters (kwargs) of the last open function.

`python_func_kw_matches(text)`

Match named parameters (kwargs) of the last open function.

Не рекомендуется, начиная с версии 8.6: You can use `python_func_kw_matcher()` instead.

`python_matches(text: str) → Iterable[str]`

Match attributes or global python names

`suppress_competing_matchers`

Whether to suppress completions from other *Matchers*.

When set to `None` (default) the matchers will attempt to auto-detect whether suppression of other matchers is desirable. For example, at the beginning of a line followed by `%` we expect a magic completion to be the only applicable option, and after `my_dict['` we usually expect a completion with an existing dictionary key.

If you want to disable this heuristic and see completions from all matchers, set `IPCompleter.suppress_competing_matchers = False`. To disable the heuristic for specific matchers provide a dictionary mapping: `IPCompleter.suppress_competing_matchers = {'IPCompleter.dict_key_matcher': False}`.

Set `IPCompleter.suppress_competing_matchers = True` to limit completions to the set of matchers with the highest priority; this is equivalent to `IPCompleter.merge_completions` and can be beneficial for performance, but will sometimes omit relevant candidates from matchers further down the priority list.

`unicode_name_matcher(context: CompletionContext)`

Same as `unicode_name_matches`, but adopted to new Matcher API.

`static unicode_name_matches(text: str) → Tuple[str, List[str]]`

Match Latex-like syntax for unicode characters base on the name of the character.

This does `\GREEK SMALL LETTER ETA ->`

Works only on valid python 3 identifier, or on combining characters that will combine to form a valid identifier.

property `unicode_names: List[str]`

List of names of unicode code points that can be completed.

The list is lazily initialized on first access.

8.8.5 18 Functions

`IPython.core.completer.cast(type_, obj)`

Workaround for `TypeError: MatcherAPIv2() takes no arguments`

`IPython.core.completer.provisionalcompleter(action='ignore')`

This context manager has to be used in any place where unstable completer behavior and API may be called.

```
>>> with provisionalcompleter():
...     completer.do_experimental_things() # works
```

```
>>> completer.do_experimental_things() # raises.
```

Примечание: Unstable

By using this context manager you agree that the API in use may change without warning, and that you won't complain if they do so.

You also understand that, if the API is not to your liking, you should report a bug to explain your use case upstream.

We'll be happy to get your feedback, feature requests, and improvements on any of the unstable APIs!

`IPython.core.completer.has_open_quotes(s)`

Return whether a string has open quotes.

This simply counts whether the number of quote characters of either type in the string is odd.

Результат

- If there is an open quote, the quote character is returned. Else, return
- `False`.

`IPython.core.completer.protect_filename(s, protectables='()[]{}?=\|/;:\'#"^&')`

Escape a string to protect certain characters.

`IPython.core.completer.expand_user(path: str) → Tuple[str, bool, str]`

Expand ~-style usernames in strings.

This is similar to `os.path.expanduser()`, but it computes and returns extra information that will be useful if the input was being used in computing completions, and you wish to return the completions with the original „~“ instead of its expanded value.

Параметры

`path (str)` – String to be expanded. If no ~ is present, the output is the same as the input.

Результат

- `newpath (str)` – Result of ~ expansion in the input path.
- `tilde_expand (bool)` – Whether any expansion was performed or not.
- `tilde_val (str)` – The value that ~ was replaced with.

`IPython.core.completer.compress_user(path: str, tilde_expand: bool, tilde_val: str) → str`

Does the opposite of `expand_user`, with its outputs.

`IPython.core.completer.completions_sorting_key(word)`

key for sorting completions

This does several things:

- Demote any completions starting with underscores to the end
- Insert any %magic and %%cellmagic completions in the alphabetical order by their name

`IPython.core.completer.has_any_completions(result: Union[SimpleMatcherResult, _JediMatcherResult]) → bool`

Check if any result includes any completions.


```
IPython.core.completer.completion_matcher(*, priority: Optional[float] = None, identifier:
                                          Optional[str] = None, api_version: int = 1)
```

Adds attributes describing the matcher.

Параметры

- `priority` (*Optional* [float]) – The priority of the matcher, determines the order of execution of matchers. Higher priority means that the matcher will be executed first. Defaults to 0.
- `identifier` (*Optional* [str]) – identifier of the matcher allowing users to modify the behaviour via traitlets, and also used to for debugging (will be passed as `origin` with the completions).

Defaults to matcher function's `__qualname__` (for example, `IPCompleter.file_matcher` for the built-in matched defined as a `file_matcher` method of the `IPCompleter` class).

- `api_version` (*Optional* [int]) – version of the Matcher API used by this matcher. Currently supported values are 1 and 2. Defaults to 1.

```
IPython.core.completer.rectify_completions(text: str, completions: Iterable[Completion], *, _debug:
                                          bool = False) → Iterable[Completion]
```

Rectify a set of completions to all have the same `start` and `end`

Предупреждение: Unstable

This function is unstable, API may change without warning. It will also raise unless use in proper context manager.

Параметры

- `text` (str) – text that should be completed.
- `completions` (*Iterator* [Completion]) – iterator over the completions to rectify
- `_debug` (bool) – Log failed completion

Заметки

`jedi.api.classes.Completion`s returned by Jedi may not have the same `start` and `end`, though the Jupyter Protocol requires them to behave like so. This will readjust the completion to have the same `start` and `end` by padding both extremities with surrounding text.

During stabilisation should support a `_debug` option to log which completion are return by the IPython completer and not found in Jedi in order to make upstream bug report.

```
IPython.core.completer.get_all_entries(obj)
```

returns the strings in the `__all__` attribute

```
IPython.core.completer.match_dict_keys(keys: List[Union[str, bytes, Tuple[Union[str, bytes], ...]]],
                                       prefix: str, delims: str, extra_prefix:
                                       Optional[Tuple[Union[str, bytes], ...]] = None) → Tuple[str,
                                       int, Dict[str, _DictKeyState]]
```

Used by `dict_key_matches`, matching the prefix to a list of keys

Параметры

- `keys` – list of keys in dictionary currently being completed.
- `prefix` – Part of the text already typed by the user. E.g. `mydict[b'fo`
- `delims` – String of delimiters to consider when finding the current key.
- `extra_prefix` (*optional*) – Part of the text already typed in multi-key index cases. E.g. for `mydict['foo', "bar", 'b`, this would be `('foo', 'bar')`.

Результат

- A tuple of three elements (`quote`, `token_start`, `matched`, `with`)
- `quote` being the quote that need to be used to close current string.
- `token_start` the position where the replacement should start occurring,
- `matches` a dictionary of replacement/completion keys on keys and values – indicating whether the state.

`IPython.core.completer.cursor_to_position(text: str, line: int, column: int) → int`

Convert the (line,column) position of the cursor in text to an offset in a string.

Параметры

- `text` (*str*) – The text in which to calculate the cursor offset
- `line` (*int*) – Line of the cursor; 0-indexed
- `column` (*int*) – Column of the cursor 0-indexed

Тип результата

Position of the cursor in `text`, 0-indexed.

См.также:

position_to_cursor

reciprocal of this function

`IPython.core.completer.position_to_cursor(text: str, offset: int) → Tuple[int, int]`

Convert the position of the cursor in text (0 indexed) to a line number(0-indexed) and a column number (0-indexed) pair

Position should be a valid position in `text`.

Параметры

- `text` (*str*) – The text in which to calculate the cursor offset
- `offset` (*int*) – Position of the cursor in `text`, 0-indexed.

Результат

(`line`, `column`) – Line of the cursor; 0-indexed, column of the cursor 0-indexed

Тип результата

(*int*, *int*)

См.также:

cursor_to_position

reciprocal of this function

`IPython.core.completer.back_unicode_name_matcher(context: CompletionContext)`

Match Unicode characters back to Unicode name

Same as `back_unicode_name_matches`, but adopted to new Matcher API.

`IPython.core.completer.back_unicode_name_matches(text: str) → Tuple[str, Sequence[str]]`

Match Unicode characters back to Unicode name

This does `-> \snowman`

Note that snowman is not a valid python3 combining character but will be expanded. Though it will not recombine back to the snowman character by the completion machinery.

This will not either back-complete standard sequences like `n`, `b` ...

Не рекомендуется, начиная с версии 8.6: You can use `back_unicode_name_matcher()` instead.

Результат

- *Return a tuple with two elements*
- *- The Unicode character that was matched (preceded with a backslash), or – empty string,*
- *- a sequence (of 1), name for the match Unicode character, preceded by – backslash, or empty if no match.*

`IPython.core.completer.back_latex_name_matcher(context: CompletionContext)`

Match latex characters back to unicode name

Same as `back_latex_name_matches`, but adopted to new Matcher API.

`IPython.core.completer.back_latex_name_matches(text: str) → Tuple[str, Sequence[str]]`

Match latex characters back to unicode name

This does `\ -> \aleph`

Не рекомендуется, начиная с версии 8.6: You can use `back_latex_name_matcher()` instead.

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

8.9 Module: `core.completerlib`

Implementations for various useful completers.

These are all loaded by default by IPython.

8.9.1 11 Functions

`IPython.core.completerlib.module_list(path)`

Return the list containing the names of the modules available in the given folder.

`IPython.core.completerlib.get_root_modules()`

Returns a list containing the names of all the modules available in the folders of the `pythonpath`.

`ip.db[„rootmodules_cache“]` maps `sys.path` entries to list of modules.

`IPython.core.completerlib.is_importable(module, attr, only_modules)`

`IPython.core.completerlib.is_possible_submodule(module, attr)`

`IPython.core.completerlib.try_import(mod: str, only_modules=False) → List[str]`

Try to import given module and return list of potential completions.

`IPython.core.completerlib.quick_completer(cmd, completions)`

Easily create a trivial completer for a command.

Takes either a list of completions, or all completions in string (that will be split on whitespace).

Example:

```
[d:\ipython] |1> import ipy_completers
[d:\ipython] |2> ipy_completers.quick_completer('foo', ['bar', 'baz'])
[d:\ipython] |3> foo b<TAB>
bar baz
[d:\ipython] |3> foo ba
```

`IPython.core.completerlib.module_completion(line)`

Returns a list containing the completion possibilities for an import line.

The line looks like this : „import xml.d“ „from xml.dom import“

`IPython.core.completerlib.module_completer(self, event)`

Give completions after user has typed „import ...“ or „from ...“

`IPython.core.completerlib.magic_run_completer(self, event)`

Complete files that end in `.py` or `.ipy` or `.ipynb` for the `%run` command.

`IPython.core.completerlib.cd_completer(self, event)`

Completer function for `cd`, which only returns directories.

`IPython.core.completerlib.reset_completer(self, event)`

A completer for `%reset` magic

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

8.10 Module: `core.crashhandler`

`sys.excepthook` for IPython itself, leaves a detailed report on disk.

Authors:

- Fernando Perez
- Brian E. Granger

8.10.1 1 Class

```
class IPython.core.crashhandler.CrashHandler(app, contact_name: Optional[str] = None,
                                             contact_email: Optional[str] = None, bug_tracker:
                                             Optional[str] = None, show_crash_traceback: bool =
                                             True, call_pdb: bool = False)
```

Базовые классы: `object`

Customizable crash handlers for IPython applications.

Instances of this class provide a `__call__()` method which can be used as a `sys.excepthook`. The `__call__()` signature is:

```
def __call__(self, etype, evalue, etb)
```

```
__init__(app, contact_name: Optional[str] = None, contact_email: Optional[str] = None,
         bug_tracker: Optional[str] = None, show_crash_traceback: bool = True, call_pdb: bool =
         False)
```

Create a new crash handler

Параметры

- `app` (*Application*) – A running `Application` instance, which will be queried at crash time for internal information.
- `contact_name` (*str*) – A string with the name of the person to contact.
- `contact_email` (*str*) – A string with the email address of the contact.
- `bug_tracker` (*str*) – A string with the URL for your project's bug tracker.
- `show_crash_traceback` (*bool*) – If false, don't print the crash traceback on stderr, only generate the on-disk report
- `call_pdb` – Whether to call `pdb` on crash

These instances contain some non-argument attributes which allow for further customization of the crash handler's behavior. Please see the

source for further details.

`make_report(traceback)`

Return a string containing a crash report.

8.10.2 1 Function

`IPython.core.crashhandler.crash_handler_lite(etype, evaluable, tb)`
a light excepthook, adding a small message to the usual traceback

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

8.11 Module: `core.debugger`

Pdb debugger class.

This is an extension to PDB which adds a number of new features. Note that there is also the `IPython.terminal.debugger` class which provides UI improvements.

We also strongly recommend to use this via the `ipdb` package, which provides extra configuration options.

Among other things, this subclass of PDB:

- supports many IPython magics like `pdf/psource`
- hide frames in tracebacks based on `__tracebackhide__`
- allows to skip frames based on `__debuggerskip__`

The skipping and hiding frames are configurable via the `skip_predicates` command.

By default, frames from readonly files will be hidden, frames containing `__tracebackhide__=True` will be hidden.

Frames containing `__debuggerskip__` will be stepped over, frames who's parent frames value of `__debuggerskip__` is True will be skipped.

```
>>> def helpers_helper():
...     pass
...
... def helper_1():
...     print("don't step in me")
...     helpers_helpers() # will be stepped over unless breakpoint set.
...
... 
```

(continues on next page)

(продолжение с предыдущей страницы)

```
... def helper_2():
...     print("in me neither")
...
```

One can define a decorator that wraps a function between the two helpers:

```
>>> def pdb_skipped_decorator(function):
...
...
...     def wrapped_fn(*args, **kwargs):
...         __debuggerskip__ = True
...         helper_1()
...         __debuggerskip__ = False
...         result = function(*args, **kwargs)
...         __debuggerskip__ = True
...         helper_2()
...         # setting __debuggerskip__ to False again is not necessary
...         return result
...
...     return wrapped_fn
```

When decorating a function, ipdb will directly step into `bar()` by default:

```
>>> @foo_decorator
... def bar(x, y):
...     return x * y
```

You can toggle the behavior with

```
ipdb> skip_predicates debuggerskip false
```

or configure it in your `.pdbrc`

8.11.1 License

Modified from the standard `pdb.Pdb` class to avoid including `readline`, so that the command line completion of other programs which include this isn't damaged.

In the future, this class will be expanded with improvements over the standard `pdb`.

The original code in this file is mainly lifted out of `cmd.py` in Python 2.2, with minor changes. Licensing should therefore be under the standard Python terms. For details on the PSF (Python Software Foundation) standard license, see:

<https://docs.python.org/2/license.html>

All the changes since then are under the same license as IPython.

8.11.2 2 Classes

`class IPython.core.debugger.Pdb(completekey=None, stdin=None, stdout=None, context=5, **kwargs)`

Базовые классы: `Pdb`

Modified Pdb class, does not load readline.

for a standalone version that uses `prompt_toolkit`, see `IPython.terminal.debugger.TerminalPdb` and `IPython.terminal.debugger.set_trace()`

This debugger can hide and skip frames that are tagged according to some predicates. See the `skip_predicates` commands.

`__init__`(*completekey=None, stdin=None, stdout=None, context=5, **kwargs*)

Create a new IPython debugger.

Параметры

- `completekey` (*default None*) – Passed to `pdb.Pdb`.
- `stdin` (*default None*) – Passed to `pdb.Pdb`.
- `stdout` (*default None*) – Passed to `pdb.Pdb`.
- `context` (*int*) – Number of lines of source code context to show when displaying stacktrace information.
- `**kwargs` – Passed to `pdb.Pdb`.

Заметки

The possibilities are python version dependent, see the python docs for more info.

`break_anywhere(frame)`

`_stop_in_decorator_internals` is overly restrictive, as we may still want to trace function calls, so we need to also update `break_anywhere` so that is we don't `stop_here`, because of debugger skip, we may still stop at any point inside the function

`do_context(context)`

`context` `number_of_lines` Set the number of lines of source code to show when displaying stacktrace information.

`do_d(arg)`

`d(own)` [`count`] Move the current frame count (default one) levels down in the stack trace (to a newer frame).

Will skip hidden frames.

`do_debug(arg)`

`debug code` Enter a recursive debugger that steps through the code argument (which is an arbitrary expression or statement to be executed in the current environment).

`do_down(arg)`

`d(own)` [`count`] Move the current frame count (default one) levels down in the stack trace (to a newer frame).

Will skip hidden frames.

`do_l(arg)`

Print lines of code from the current stack frame

`do_list(arg)`
 Print lines of code from the current stack frame

`do_ll(arg)`
 Print lines of code from the current stack frame.
 Shows more lines than „list“ does.

`do_longlist(arg)`
 Print lines of code from the current stack frame.
 Shows more lines than „list“ does.

`do_pdef(arg)`
 Print the call signature for any callable object.
 The debugger interface to `%pdef`

`do_pdoc(arg)`
 Print the docstring for an object.
 The debugger interface to `%pdoc`.

`do_pfile(arg)`
 Print (or run through pager) the file where an object is defined.
 The debugger interface to `%pfile`.

`do_pinfo(arg)`
 Provide detailed information about an object.
 The debugger interface to `%pinfo`, i.e., `obj?`.

`do_pinfo2(arg)`
 Provide extra detailed information about an object.
 The debugger interface to `%pinfo2`, i.e., `obj??`.

`do_psource(arg)`
 Print (or run through pager) the source code for an object.

`do_q(**kw)`
`q(uit)` exit Quit from the debugger. The program being executed is aborted.

`do_quit(**kw)`
`q(uit)` exit Quit from the debugger. The program being executed is aborted.

`do_skip_hidden(arg)`
 Change whether or not we should skip frames with the `__tracebackhide__` attribute.

`do_skip_predicates(args)`
 Turn on/off individual predicates as to whether a frame should be hidden/skip.
 The global option to skip (or not) hidden frames is set with `skip_hidden`
 To change the value of a predicate
 `skip_predicates` key [true/false]
 Call without arguments to see the current values.
 To permanently change the value of an option add the corresponding command to your `~/ .pdbrc` file. If you are programmatically using the `Pdb` instance you can also change the `default_predicates` class attribute.

`do_u(arg)`

`u(p) [count]` Move the current frame count (default one) levels up in the stack trace (to an older frame).

Will skip hidden frames.

`do_up(arg)`

`u(p) [count]` Move the current frame count (default one) levels up in the stack trace (to an older frame).

Will skip hidden frames.

`do_w(arg)`

`w(here)` Print a stack trace, with the most recent frame at the bottom. An arrow indicates the «current frame», which determines the context of most commands. „bt“ is an alias for this command.

Take a number as argument as an (optional) number of context line to print

`do_where(arg)`

`w(here)` Print a stack trace, with the most recent frame at the bottom. An arrow indicates the «current frame», which determines the context of most commands. „bt“ is an alias for this command.

Take a number as argument as an (optional) number of context line to print

`format_stack_entry(frame_lineno, lprefix=': ', context=None)`

Return a string with information about a stack entry.

The stack entry `frame_lineno` is a (frame, lineno) tuple. The return string contains the canonical filename, the function name or „<lambda>“, the input arguments, the return value, and the line of code (if it exists).

`hidden_frames(stack)`

Given an index in the stack return whether it should be skipped.

This is used in up/down and where to skip frames.

`new_do_restart(arg)`

Restart command. In the context of ipython this is exactly the same thing as „quit“.

`precmd(line)`

Perform useful escapes on the command before it is executed.

`print_list_lines(filename, first, last)`

The printing (as opposed to the parsing part of a „list“ command).

`set_colors(scheme)`

Shorthand access to the color table scheme selector method.

`set_trace(frame=None)`

Start debugging from frame.

If frame is not specified, debugging starts from caller’s frame.

`stop_here(frame)`

Return True if frame is below the starting frame in the stack.

```
class IPython.core.debugger.InterruptiblePdb(completekey=None, stdin=None, stdout=None,  
                                             context=5, **kwargs)
```

Базовые классы: *Pdb*

Version of debugger where KeyboardInterrupt exits the debugger altogether.

```
cmdloop(intro=None)
```

Wrap cmdloop() such that KeyboardInterrupt stops the debugger.

8.11.3 6 Functions

```
IPython.core.debugger.make_arrow(pad)
```

generate the leading arrow in front of traceback or debugger

```
IPython.core.debugger.BdbQuit_excepthook(et, ev, tb, excepthook=None)
```

Exception hook which handles BdbQuit exceptions.

All other exceptions are processed using the `excepthook` parameter.

```
IPython.core.debugger.BdbQuit_IPython_excepthook(self, et, ev, tb, tb_offset=None)
```

```
IPython.core.debugger.strip_indentation(multiline_string)
```

```
IPython.core.debugger.decorate_fn_with_doc(new_fn, old_fn, additional_text='')
```

Make `new_fn` have `old_fn`'s doc string. This is particularly useful for the `do...` commands that hook into the help system. Adapted from from a `comp.lang.python` posting by Duncan Booth.

```
IPython.core.debugger.set_trace(frame=None)
```

Start debugging from `frame`.

If `frame` is not specified, debugging starts from caller's frame.

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

8.12 Module: `core.error`

Global exception classes for IPython.core.

Authors:

- Brian Granger
- Fernando Perez
- Min Ragan-Kelley

Заметки

8.12.1 5 Classes

`class IPython.core.error.IPythonCoreError`

Базовые классы: `Exception`

`class IPython.core.error.TryNext`

Базовые классы: `IPythonCoreError`

Try next hook exception.

Raise this in your hook function to indicate that the next hook handler should be used to handle the operation.

`class IPython.core.error.UsageError`

Базовые классы: `IPythonCoreError`

Error in magic function arguments, etc.

Something that probably won't warrant a full traceback, but should nevertheless interrupt a macro / batch file.

`class IPython.core.error.StdinNotImplementedError`

Базовые классы: `IPythonCoreError`, `NotImplementedError`

`raw_input` was requested in a context where it is not supported

For use in IPython kernels, where only some frontends may support stdin requests.

`class IPython.core.error.InputRejected`

Базовые классы: `Exception`

Input rejected by ast transformer.

Raise this in your NodeTransformer to indicate that InteractiveShell should not execute the supplied input.

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

8.13 Module: `core.events`

Infrastructure for registering and firing callbacks on application events.

Unlike `IPython.core.hooks`, which lets end users set single functions to be called at specific times, or a collection of alternative methods to try, callbacks are designed to be used by extension authors. A number of callbacks can be registered for the same event without needing to be aware of one another.

The functions defined in this module are no-ops indicating the names of available events and the arguments which will be passed to them.

Примечание: This API is experimental in IPython 2.0, and may be revised in future versions.

8.13.1 1 Class

```
class IPython.core.events.EventManager(shell, available_events)
```

Базовые классы: `object`

Manage a collection of events and a sequence of callbacks for each.

This is attached to `InteractiveShell` instances as an `events` attribute.

Примечание: This API is experimental in IPython 2.0, and may be revised in future versions.

```
__init__(shell, available_events)
```

Initialise the `CallbackManager`.

Параметры

- `shell` – The `InteractiveShell` instance
- `available_events` – An iterable of names for callback events.

```
register(event, function)
```

Register a new event callback.

Параметры

- `event` (*str*) – The event for which to register this callback.
- `function` (*callable*) – A function to be called on the given event. It should take the same parameters as the appropriate callback prototype.

Исключение

- `TypeError` – If `function` is not callable.
- `KeyError` – If `event` is not one of the known events.

```
trigger(event, *args, **kwargs)
```

Call callbacks for `event`.

Any additional arguments are passed to all callbacks registered for this event. Exceptions raised by callbacks are caught, and a message printed.

```
unregister(event, function)
```

Remove a callback from the given event.

8.13.2 5 Functions

`IPython.core.events.pre_execute()`

Fires before code is executed in response to user/frontend action.

This includes comm and widget messages and silent execution, as well as user code cells.

`IPython.core.events.pre_run_cell(info)`

Fires before user-entered code runs.

Параметры

`info` (*ExecutionInfo*) – An object containing information used for the code execution.

`IPython.core.events.post_execute()`

Fires after code is executed in response to user/frontend action.

This includes comm and widget messages and silent execution, as well as user code cells.

`IPython.core.events.post_run_cell(result)`

Fires after user-entered code runs.

Параметры

`result` (*ExecutionResult*) – The object which will be returned as the execution result.

`IPython.core.events.shell_initialized(ip)`

Fires after initialisation of *InteractiveShell*.

This is before extensions and startup scripts are loaded, so it can only be set by subclassing.

Параметры

`ip` (*InteractiveShell*) – The newly initialised shell.

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

8.14 Module: `core.excolors`

Color schemes for exception handling code in IPython.

8.14.1 1 Function

`IPython.core.excolors.exception_colors()`

Return a color table with fields for exception reporting.

The table is an instance of `ColorSchemeTable` with schemes added for „Neutral“, „Linux“, „LightBG“ and „NoColor“ and fields for exception handling filled in.

Examples:

```
>>> ec = exception_colors()
>>> ec.active_scheme_name
''
>>> print(ec.active_colors)
None
```

Now we activate a color scheme: `>>> ec.set_active_scheme('NoColor')` `>>> ec.active_scheme_name` „NoColor“ `>>> sorted(ec.active_colors.keys())` [„Normal“, „caret“, „em“, „excName“, „filename“, „filenameEm“, „line“, „lineno“, „linenoEm“, „name“, „nameEm“, „normalEm“, „topline“, „vName“, „val“, „valEm“]

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

8.15 Module: `core.extensions`

A class for managing IPython extensions.

8.15.1 1 Class

`class IPython.core.extensions.ExtensionManager(**kwargs: Any)`

Базовые классы: `Configurable`

A class to manage IPython extensions.

An IPython extension is an importable Python module that has a function with the signature:

```
def load_ipython_extension(ipython):
    # Do things with ipython
```

This function is called after your extension is imported and the currently active `InteractiveShell` instance is passed as the only argument. You can do anything you want with IPython at that point, including defining new magic and aliases, adding new components, etc.

You can also optionally define an `unload_ipython_extension(ipython)()` function, which will be called if the user unloads or reloads the extension. The extension manager will only call `load_ipython_extension()` again if the extension is reloaded.

You can put your extension modules anywhere you want, as long as they can be imported by Python's standard import mechanism. However, to make it easy to write extensions, you can also put your extensions in `os.path.join(self.ipython_dir, 'extensions')`. This directory is added to `sys.path` automatically.

```
__init__(shell=None, **kwargs)
```

Create a configurable given a config config.

Параметры

- `config (Config)` – If this is empty, default values are used. If config is a `Config` instance, it will be used to configure the instance.
- `parent (Configurable instance, optional)` – The parent `Configurable` instance of this object.

Заметки

Subclasses of `Configurable` must call the `__init__()` method of `Configurable` *before* doing anything else and using `super()`:

```
class MyConfigurable(Configurable):
    def __init__(self, config=None):
        super(MyConfigurable, self).__init__(config=config)
        # Then any other code you need to finish initialization.
```

This ensures that instances will be configured properly.

```
load_extension(module_str: str)
```

Load an IPython extension by its module name.

Returns the string «already loaded» if the extension is already loaded, «no load function» if the module doesn't have a `load_ipython_extension` function, or `None` if it succeeded.

```
reload_extension(module_str: str)
```

Reload an IPython extension by calling `reload`.

If the module has not been loaded before, `InteractiveShell.load_extension()` is called. Otherwise `reload()` is called and then the `load_ipython_extension()` function of the module, if it exists is called.

```
unload_extension(module_str: str)
```

Unload an IPython extension by its module name.

This function looks up the extension's name in `sys.modules` and simply calls `mod.unload_ipython_extension(self)`.

Returns the string «no unload function» if the extension doesn't define a function to unload itself, «not loaded» if the extension isn't loaded, otherwise `None`.

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.


Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

8.16 Module: `core.formatters`

Display formatters.

Inheritance diagram:



8.16.1 16 Classes

`class IPython.core.formatters.DisplayFormatter(**kwargs: Any)`

Базовые классы: `Configurable`

`active_types`

List of currently active mime-types to display. You can use this to set a white-list for formats to display.

Most users will not need to change this value.

`format(obj, include=None, exclude=None)`

Return a format data dict for an object.

By default all format types will be computed.

The following MIME types are usually implemented:

- `text/plain`
- `text/html`

- text/markdown
- text/latex
- application/json
- application/javascript
- application/pdf
- image/png
- image/jpeg
- image/svg+xml

Параметры

- `obj` (*object*) – The Python object whose format data will be computed.
- `include` (*list, tuple or set; optional*) – A list of format type strings (MIME types) to include in the format data dict. If this is set *only* the format types included in this list will be computed.
- `exclude` (*list, tuple or set; optional*) – A list of format type string (MIME types) to exclude in the format data dict. If this is set all format types will be computed, except for those included in this argument. Mimeypes present in exclude will take precedence over the ones in include

Результат

(`format_dict`, `metadata_dict`) – `format_dict` is a dictionary of key/value pairs, one of each format that was generated for the object. The keys are the format types, which will usually be MIME type strings and the values and JSON'able data structure containing the raw data for the representation in that format.

`metadata_dict` is a dictionary of metadata about each mime-type output. Its keys will be a strict subset of the keys in `format_dict`.

Тип результата

tuple of two dicts

Заметки

If an object implement `_repr_mimebundle_` as well as various `_repr_*_`, the data returned by `_repr_mimebundle_` will take precedence and the corresponding `_repr_*_` for this mimetype will not be called.

property `format_types`

Return the format types (MIME types) of the active formatters.

```
class IPython.core.formatters.FormatterWarning
```

Базовые классы: `UserWarning`

Warning class for errors in formatters

```
class IPython.core.formatters.FormatterABC
```

Базовые классы: `object`

Abstract base class for Formatters.

A formatter is a callable class that is responsible for computing the raw format data for a particular format type (MIME type). For example, an HTML formatter would have a format type of `text/html` and would return the HTML representation of the object when called.

```
class IPython.core.formatters.BaseFormatter(**kwargs: Any)
```

Базовые классы: `Configurable`

A base formatter class that is configurable.

This formatter should usually be used as the base class of all formatters. It is a traitled `Configurable` class and includes an extensible API for users to determine how their objects are formatted. The following logic is used to find a function to format an given object.

1. The object is introspected to see if it has a method with the name `print_method`. If it does, that object is passed to that method for formatting.
2. If no print method is found, three internal dictionaries are consulted to find print method: `singleton_printers`, `type_printers` and `deferred_printers`.

Users should use these dictionaries to register functions that will be used to compute the format data for their objects (if those objects don't have the special print methods). The easiest way of using these dictionaries is through the `for_type()` and `for_type_by_name()` methods.

If no function/callable is found to compute the format data, `None` is returned and this format type is not used.

```
for_type(typ, func=None)
```

Add a format function for a given type.

Параметры

- `typ` (*type* or `'__module__'...` string for a type) – The class of the object that will be formatted using `func`.
- `func` (*callable*) – A callable for computing the format data. `func` will be called with the object to be formatted, and will return the raw data in this formatter's format. Subclasses may use a different call signature for the `func` argument.

If `func` is `None` or not specified, there will be no change, only returning the current value.

Результат

oldfunc – The currently registered callable. If you are registering a new formatter, this will be the previous value (to enable restoring later).

Тип результата

callable

```
for_type_by_name(type_module, type_name, func=None)
```

Add a format function for a type specified by the full dotted module and name of the type, rather than the type of the object.

Параметры

- `type_module` (*str*) – The full dotted name of the module the type is defined in, like `numpy`.
- `type_name` (*str*) – The name of the type (the class name), like `dtype`
- `func` (*callable*) – A callable for computing the format data. `func` will be called with the object to be formatted, and will return the raw data in this formatter's format. Subclasses may use a different call signature for the `func` argument.

If `func` is `None` or unspecified, there will be no change, only returning the current value.

Результат

oldfunc – The currently registered callable. If you are registering a new formatter, this will be the previous value (to enable restoring later).

Тип результата

callable

`lookup(obj)`

Look up the formatter for a given instance.

Параметры

`obj` (*object instance*) –

Результат

`f` – The registered formatting callable for the type.

Тип результата

callable

Исключение

`KeyError` if the type has not been registered. –

`lookup_by_type(typ)`

Look up the registered formatter for a type.

Параметры

`typ` (*type or '.__module__.__name__' string for a type*) –

Результат

`f` – The registered formatting callable for the type.

Тип результата

callable

Исключение

`KeyError` if the type has not been registered. –

`pop(typ, default=IPython.core.formatters._raise_key_error)`

Pop a formatter for the given type.

Параметры

- `typ` (*type or '.__module__.__name__' string for a type*) –
- `default` (*object*) – value to be returned if no formatter is registered for `typ`.

Результат

`obj` – The last registered object for the type.

Тип результата

object

Исключение

`KeyError` if the type is not registered and default is not specified. –

`class IPython.core.formatters.PlainTextFormatter(**kwargs: Any)`

Базовые классы: *BaseFormatter*

The default pretty-printer.

This uses `IPython.lib.pretty` to compute the format data of the object. If the object cannot be pretty printed, `repr()` is used. See the documentation of `IPython.lib.pretty` for details on how to write pretty printers. Here is a simple example:

```
def dtype_pprinter(obj, p, cycle):
    if cycle:
        return p.text('dtype(...)')
    if hasattr(obj, 'fields'):
        if obj.fields is None:
            p.text(repr(obj))
        else:
            p.begin_group(7, 'dtype([')
            for i, field in enumerate(obj.descr):
                if i > 0:
                    p.text(',')
                    p.breakable()
                p.pretty(field)
            p.end_group(7, '])')
```

`max_seq_length`

Truncate large collections (lists, dicts, tuples, sets) to this size.

Set to 0 to disable truncation.

`class IPython.core.formatters.HTMLFormatter(**kwargs: Any)`

Базовые классы: `BaseFormatter`

An HTML formatter.

To define the callables that compute the HTML representation of your objects, define a `_repr_html_()` method or use the `for_type()` or `for_type_by_name()` methods to register functions that handle this.

The return value of this formatter should be a valid HTML snippet that could be injected into an existing DOM. It should *not* include the `<html>` or `<body>` tags.

`class IPython.core.formatters.MarkdownFormatter(**kwargs: Any)`

Базовые классы: `BaseFormatter`

A Markdown formatter.

To define the callables that compute the Markdown representation of your objects, define a `_repr_markdown_()` method or use the `for_type()` or `for_type_by_name()` methods to register functions that handle this.

The return value of this formatter should be a valid Markdown.

`class IPython.core.formatters.SVGFormatter(**kwargs: Any)`

Базовые классы: `BaseFormatter`

An SVG formatter.

To define the callables that compute the SVG representation of your objects, define a `_repr_svg_()` method or use the `for_type()` or `for_type_by_name()` methods to register functions that handle this.

The return value of this formatter should be valid SVG enclosed in `<svg>` tags, that could be injected into an existing DOM. It should *not* include the `<html>` or `<body>` tags.

`class IPython.core.formatters.PNGFormatter(**kwargs: Any)`

Базовые классы: `BaseFormatter`

A PNG formatter.

To define the callables that compute the PNG representation of your objects, define a `_repr_png_()` method or use the `for_type()` or `for_type_by_name()` methods to register functions that handle this.

The return value of this formatter should be raw PNG data, *not* base64 encoded.

```
class IPython.core.formatters.JPEGFormatter(**kwargs: Any)
```

Базовые классы: `BaseFormatter`

A JPEG formatter.

To define the callables that compute the JPEG representation of your objects, define a `_repr_jpeg_()` method or use the `for_type()` or `for_type_by_name()` methods to register functions that handle this.

The return value of this formatter should be raw JPEG data, *not* base64 encoded.

```
class IPython.core.formatters.LatexFormatter(**kwargs: Any)
```

Базовые классы: `BaseFormatter`

A LaTeX formatter.

To define the callables that compute the LaTeX representation of your objects, define a `_repr_latex_()` method or use the `for_type()` or `for_type_by_name()` methods to register functions that handle this.

The return value of this formatter should be a valid LaTeX equation, enclosed in either ``$``, ``$$`` or another LaTeX equation environment.

```
class IPython.core.formatters.JSONFormatter(**kwargs: Any)
```

Базовые классы: `BaseFormatter`

A JSON string formatter.

To define the callables that compute the JSONable representation of your objects, define a `_repr_json_()` method or use the `for_type()` or `for_type_by_name()` methods to register functions that handle this.

The return value of this formatter should be a JSONable list or dict. JSON scalars (None, number, string) are not allowed, only dict or list containers.

```
class IPython.core.formatters.JavascriptFormatter(**kwargs: Any)
```

Базовые классы: `BaseFormatter`

A Javascript formatter.

To define the callables that compute the Javascript representation of your objects, define a `_repr_javascript_()` method or use the `for_type()` or `for_type_by_name()` methods to register functions that handle this.

The return value of this formatter should be valid Javascript code and should *not* be enclosed in `<script>` tags.

```
class IPython.core.formatters.PDFFormatter(**kwargs: Any)
```

Базовые классы: `BaseFormatter`

A PDF formatter.

To define the callables that compute the PDF representation of your objects, define a `_repr_pdf_()` method or use the `for_type()` or `for_type_by_name()` methods to register functions that handle this.

The return value of this formatter should be raw PDF data, *not* base64 encoded.

```
class IPython.core.formatters.IPythonDisplayFormatter(**kwargs: Any)
```

Базовые классы: *BaseFormatter*

An escape-hatch Formatter for objects that know how to display themselves.

To define the callables that compute the representation of your objects, define a `_ipython_display_()` method or use the `for_type()` or `for_type_by_name()` methods to register functions that handle this. Unlike mime-type displays, this method should not return anything, instead calling any appropriate display methods itself.

This display formatter has highest priority. If it fires, no other display formatter will be called.

Prior to IPython 6.1, `_ipython_display_` was the only way to display custom mime-types without registering a new Formatter.

IPython 6.1 introduces `_repr_mimebundle_` for displaying custom mime-types, so `_ipython_display_` should only be used for objects that require unusual display patterns, such as multiple display calls.

```
class IPython.core.formatters.MimeBundleFormatter(**kwargs: Any)
```

Базовые классы: *BaseFormatter*

A Formatter for arbitrary mime-types.

Unlike other `_repr_<mime-type>_` methods, `_repr_mimebundle_` should return mime-bundle data, either the mime-keyed `data` dictionary or the tuple `(data, metadata)`. Any mime-type is valid.

To define the callables that compute the mime-bundle representation of your objects, define a `_repr_mimebundle_()` method or use the `for_type()` or `for_type_by_name()` methods to register functions that handle this.

Добавлено в версии 6.1.

8.16.2 2 Functions

```
IPython.core.formatters.catch_format_error(method, self)
```

show traceback on failed format call

```
IPython.core.formatters.format_display_data(obj, include=None, exclude=None)
```

Return a format data dict for an object.

By default all format types will be computed.

Параметры

`obj` (*object*) – The Python object whose format data will be computed.

Результат

- **format_dict** (*dict*) – A dictionary of key/value pairs, one or each format that was generated for the object. The keys are the format types, which will usually be MIME type strings and the values and JSON'able data structure containing the raw data for the representation in that format.
- **include** (*list or tuple, optional*) – A list of format type strings (MIME types) to include in the format data dict. If this is set *only* the format types included in this list will be computed.
- **exclude** (*list or tuple, optional*) – A list of format type string (MIME types) to exclude in the format data dict. If this is set all format types will be computed, except for those included in this argument.

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

8.17 Module: `core.getipython`

Simple function to call to get the current InteractiveShell instance

8.17.1 1 Function

`IPython.core.getipython.get_ipython()`

Get the global InteractiveShell instance.

Returns None if no InteractiveShell instance is registered.

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

8.18 Module: `core.guarded_eval`

8.18.1 2 Classes

`class IPython.core.guarded_eval.EvaluationContext(locals, globals, evaluation, in_subscript)`

Базовые классы: `NamedTuple`

`evaluation: Literal['forbidden', 'minimal', 'limited', 'unsafe', 'dangerous']`

Evaluation policy identifier

`globals: dict`

Global namespace

`in_subscript: bool`

Whether the evaluation of code takes place inside of a subscript. Useful for evaluating `:-1, 'col'` in `df[:-1, 'col']`.

`locals: dict`

Local namespace

`class IPython.core.guarded_eval.GuardRejection`

Базовые классы: `Exception`

Exception raised when guard rejects evaluation attempt.

8.18.2 2 Functions

`IPython.core.guarded_eval.guarded_eval(code: str, context: EvaluationContext)`

Evaluate provided code in the evaluation context.

If evaluation policy given by context is set to `forbidden` no evaluation will be performed; if it is set to `dangerous` standard `eval()` will be used; finally, for any other, policy `eval_node()` will be called on parsed AST.

`IPython.core.guarded_eval.eval_node(node: Optional[AST], context: EvaluationContext)`

Evaluate AST node in provided context.

Applies evaluation restrictions defined in the context. Currently does not support evaluation of functions with keyword arguments.

Does not evaluate actions that always have side effects:

- class definitions (`class sth: ...`)
- function definitions (`def sth: ...`)
- variable assignments (`x = 1`)
- augmented assignments (`x += 1`)
- deletions (`del x`)

Does not evaluate operations which do not return values:

- assertions (`assert x`)
- pass (`pass`)
- imports (`import x`)
- control flow:
 - conditionals (`if x:`) except for ternary `IfExp (a if x else b)`
 - loops (`for` and `while`)
 - exception handling

The purpose of this function is to guard against unwanted side-effects; it does not give guarantees on protection from malicious code execution.

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

8.19 Module: `core.history`

History related magics and functionality

8.19.1 4 Classes

```
class IPython.core.history.HistoryAccessorBase(**kwargs: Any)
```

Базовые классы: `LoggingConfigurable`

An abstract class for History Accessors

```
class IPython.core.history.HistoryAccessor(**kwargs: Any)
```

Базовые классы: `HistoryAccessorBase`

Access the history database without adding to it.

This is intended for use by standalone history tools. IPython shells use `HistoryManager`, below, which is a subclass of this.

```
__init__(profile='default', hist_file='', **traits)
```

Create a new history accessor.

Параметры

- `profile` (*str*) – The name of the profile from which to open history.
- `hist_file` (*str*) – Path to an SQLite history database stored by IPython. If specified, `hist_file` overrides `profile`.
- `config` (`Config`) – Config object. `hist_file` can also be set through this.

```
connection_options
```

Options for configuring the SQLite connection

These options are passed as keyword args to `sqlite3.connect` when establishing database connections.

```
enabled
```

enable the SQLite history

set `enabled=False` to disable the SQLite history, in which case there will be no stored history, no SQLite connection, and no background saving thread. This may be necessary in some threaded environments where IPython is embedded.

```
get_last_session_id()
```

Get the last session ID currently in the database.

Within IPython, this should be the same as the value stored in `HistoryManager.session_number`.

`get_range(session, start=1, stop=None, raw=True, output=False)`

Retrieve input by session.

Параметры

- `session` (*int*) – Session number to retrieve.
- `start` (*int*) – First line to retrieve.
- `stop` (*int*) – End of line range (excluded from output itself). If None, retrieve to the end of the session.
- `raw` (*bool*) – If True, return untranslated input
- `output` (*bool*) – If True, attempt to include output. This will be „real“ Python objects for the current session, or text reprs from previous sessions if `db_log_output` was enabled at the time. Where no output is found, None is used.

Результат

An iterator over the desired lines. Each line is a 3-tuple, either (session, line, input) if output is False, or (session, line, (input, output)) if output is True.

Тип результата

entries

`get_range_by_str(rangestr, raw=True, output=False)`

Get lines of history from a string of ranges, as used by magic commands `%hist`, `%save`, `%macro`, etc.

Параметры

- `rangestr` (*str*) – A string specifying ranges, e.g. «5 ~2/1-4». If empty string is used, this will return everything from current session's history.

See the documentation of `%history()` for the full details.

- `raw` (*bool*) – As `get_range()`
- `output` (*bool*) – As `get_range()`

Тип результата

Tuples as `get_range()`

`get_session_info(session)`

Get info about a session.

Параметры

- `session` (*int*) – Session number to retrieve.

Результат

- `session_id` (*int*) – Session ID number
- `start` (*datetime*) – Timestamp for the start of the session.
- `end` (*datetime*) – Timestamp for the end of the session, or None if IPython crashed.
- `num_cmds` (*int*) – Number of commands run, or None if IPython crashed.
- `remark` (*unicode*) – A manually set description.

`get_tail(n=10, raw=True, output=False, include_latest=False)`

Get the last n lines from the history database.

Параметры

- `n` (*int*) – The number of lines to get
- `raw` (*bool*) – See `get_range()`
- `output` (*bool*) – See `get_range()`
- `include_latest` (*bool*) – If False (default), `n+1` lines are fetched, and the latest one is discarded. This is intended to be used where the function is called by a user command, which it should not return.

Тип результата

Tuples as `get_range()`

`hist_file`

Path to file to use for SQLite history database.

By default, IPython will put the history database in the IPython profile directory. If you would rather share one history among profiles, you can set this value in each, so that they are consistent.

Due to an issue with `fcntl`, SQLite is known to misbehave on some NFS mounts. If you see IPython hanging, try setting this to something on a local disk, e.g:

```
ipython --HistoryManager.hist_file=/tmp/ipython_hist.sqlite
```

you can also use the specific value `:memory:` (including the colon at both end but not the back ticks), to avoid creating an history file.

`init_db()`

Connect to the database, and create tables if necessary.

`search(pattern='*', raw=True, search_raw=True, output=False, n=None, unique=False)`

Search the database using unix glob-style matching (wildcards `*` and `?`).

Параметры

- `pattern` (*str*) – The wildcarded pattern to match when searching
- `search_raw` (*bool*) – If True, search the raw input, otherwise, the parsed input
- `raw` (*bool*) – See `get_range()`
- `output` (*bool*) – See `get_range()`
- `n` (*None or int*) – If an integer is given, it defines the limit of returned entries.
- `unique` (*bool*) – When it is true, return only unique entries.

Тип результата

Tuples as `get_range()`

`writeout_cache()`

Overridden by `HistoryManager` to dump the cache before certain database lookups.

`class IPython.core.history.HistoryManager(**kwargs: Any)`

Базовые классы: `HistoryAccessor`

A class to organize all history-related functionality in one place.

`__init__(shell=None, config=None, **traits)`

Create a new history manager associated with a shell instance.

`db_cache_size`

Write to database every x commands (higher values save disk access & power). Values of 1 or less effectively disable caching.

`db_log_output`

no)

Типе

Should the history database include output? (default

`end_session()`

Close the database session, filling in the end time and line count.

`get_range(session=0, start=1, stop=None, raw=True, output=False)`

Retrieve input by session.

Параметры

- `session` (*int*) – Session number to retrieve. The current session is 0, and negative numbers count back from current session, so -1 is previous session.
- `start` (*int*) – First line to retrieve.
- `stop` (*int*) – End of line range (excluded from output itself). If None, retrieve to the end of the session.
- `raw` (*bool*) – If True, return untranslated input
- `output` (*bool*) – If True, attempt to include output. This will be „real“ Python objects for the current session, or text reprs from previous sessions if `db_log_output` was enabled at the time. Where no output is found, None is used.

Результат

An iterator over the desired lines. Each line is a 3-tuple, either (session, line, input) if output is False, or (session, line, (input, output)) if output is True.

Тип результата

entries

`get_session_info(session=0)`

Get info about a session.

Параметры

`session` (*int*) – Session number to retrieve. The current session is 0, and negative numbers count back from current session, so -1 is the previous session.

Результат

- `session_id` (*int*) – Session ID number
- `start` (*datetime*) – Timestamp for the start of the session.
- `end` (*datetime*) – Timestamp for the end of the session, or None if IPython crashed.
- `num_cmds` (*int*) – Number of commands run, or None if IPython crashed.
- `remark` (*unicode*) – A manually set description.

`get_tail(n=10, raw=True, output=False, include_latest=False)`

Get the last n lines from the history database.

Most recent entry last.

Completion will be reordered so that that the last ones are when possible from current session.

Параметры

- `n` (*int*) – The number of lines to get
- `raw` (*bool*) – See `get_range()`
- `output` (*bool*) – See `get_range()`
- `include_latest` (*bool*) – If False (default), `n+1` lines are fetched, and the latest one is discarded. This is intended to be used where the function is called by a user command, which it should not return.

Тип результата

Tuples as `get_range()`

`name_session(name)`

Give the current session a name in the history database.

`new_session(conn=None)`

Get a new session number.

`reset(new_session=True)`

Clear the session history, releasing all object references, and optionally open a new session.

`store_inputs(line_num, source, source_raw=None)`

Store source and raw input in history and create input cache variables `_i*`.

Параметры

- `line_num` (*int*) – The prompt number of this input.
- `source` (*str*) – Python input.
- `source_raw` (*str*, *optional*) – If given, this is the raw input without any IPython transformations applied to it. If not given, `source` is used.

`store_output(line_num)`

If database output logging is enabled, this saves all the outputs from the indicated prompt number to the database. It's called by `run_cell` after code has been executed.

Параметры

`line_num` (*int*) – The line number from which to save outputs

`writeout_cache(conn=None)`

Write any entries in the cache to the database.

`class IPython.core.history.HistorySavingThread(history_manager)`

Базовые классы: `Thread`

This thread takes care of writing history to the database, so that the UI isn't held up while that happens.

It waits for the `HistoryManager`'s `save_flag` to be set, then writes out the history cache. The main thread is responsible for setting the flag when the cache size reaches a defined threshold.

`__init__(history_manager)`

This constructor should always be called with keyword arguments. Arguments are:

`group` should be `None`; reserved for future extension when a `ThreadGroup` class is implemented.

`target` is the callable object to be invoked by the `run()` method. Defaults to `None`, meaning nothing is called.

name is the thread name. By default, a unique name is constructed of the form «Thread-N» where N is a small decimal number.

args is the argument tuple for the target invocation. Defaults to ().

kwargs is a dictionary of keyword arguments for the target invocation. Defaults to {}.

If a subclass overrides the constructor, it must make sure to invoke the base class constructor (Thread.__init__()) before doing anything else to the thread.

run()

Method representing the thread's activity.

You may override this method in a subclass. The standard run() method invokes the callable object passed to the object's constructor as the target argument, if any, with sequential and keyword arguments taken from the args and kwargs arguments, respectively.

stop()

This can be called from the main thread to safely stop this thread.

Note that it does not attempt to write out remaining history before exiting. That should be done by calling the HistoryManager's end_session method.

8.19.2 3 Functions

`IPython.core.history.only_when_enabled(f, self)`

Decorator: return an empty list in the absence of sqlite.

`IPython.core.history.catch_corrupt_db(f, self)`

A decorator which wraps HistoryAccessor method calls to catch errors from a corrupt SQLite database, move the old database out of the way, and create a new one.

We avoid clobbering larger databases because this may be triggered due to filesystem issues, not just a corrupt file.

`IPython.core.history.extract_hist_ranges(ranges_str)`

Turn a string of history ranges into 3-tuples of (session, start, stop).

Empty string results in a [(0, 1, None)], i.e. «everything from current session».

Примеры

```
>>> list(extract_hist_ranges("~8/5-~7/4 2"))
[(-8, 5, None), (-7, 1, 5), (0, 2, 3)]
```

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

8.20 Module: `core.historyapp`

An application for managing IPython history.

To be invoked as the `ipython history` subcommand.

8.20.1 3 Classes

```
class IPython.core.historyapp.HistoryTrim(**kwargs: Any)
```

Базовые классы: `BaseIPythonApplication`

`backup`

Keep the old history file as `history.sqlite.<N>`

`keep`

Number of recent lines to keep in the database.

`start()`

Start the app mainloop.

Override in subclasses.

```
class IPython.core.historyapp.HistoryClear(**kwargs: Any)
```

Базовые классы: `HistoryTrim`

`force`

Don't prompt user for confirmation

`keep`

Number of recent lines to keep in the database.

`start()`

Start the app mainloop.

Override in subclasses.

```
class IPython.core.historyapp.HistoryApp(**kwargs: Any)
```

Базовые классы: `Application`

`start()`

Start the app mainloop.

Override in subclasses.

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

8.21 Module: core.hooks

Hooks for IPython.

In Python, it is possible to overwrite any method of any object if you really want to. But IPython exposes a few „hooks“, methods which are *designed* to be overwritten by users for customization purposes. This module defines the default versions of all such hooks, which get used by IPython if not overridden by the user.

Hooks are simple functions, but they should be declared with **self** as their first argument, because when activated they are registered into IPython as instance methods. The self argument will be the IPython running instance itself, so hooks have full access to the entire IPython object.

If you wish to define a new hook and activate it, you can make an *extension* or a *startup script*. For example, you could use a startup file like this:

```
import os

def calljed(self,filename, lineno):
    "My editor hook calls the jed editor directly."
    print "Calling my own editor, jed ..."
    if os.system('jed +%d %s' % (lineno,filename)) != 0:
        raise TryNext()

def load_ipython_extension(ip):
    ip.set_hook('editor', calljed)
```

8.21.1 1 Class

`class IPython.core.hooks.CommandChainDispatcher(commands=None)`

Базовые классы: `object`

Dispatch calls to a chain of commands until some func can handle it

Usage: instantiate, execute «add» to add commands (with optional priority), execute normally via f() calling mechanism.

`__init__(commands=None)`

`add(func, priority=0)`

Add a func to the cmd chain with given priority

8.21.2 5 Functions

`IPython.core.hooks.editor(self, filename, lineno=None, wait=True)`

Open the default editor at the given filename and linenumber.

This is IPython's default editor hook, you can use it as an example to write your own modified one. To set your own editor function as the new editor hook, call `ip.set_hook(„editor“,yourfunc)`.

`IPython.core.hooks.synchronize_with_editor(self, filename, lineno, column)`

`IPython.core.hooks.show_in_pager(self, data, start, screen_lines)`

Run a string through pager

```
IPython.core.hooks.pre_prompt_hook(self)
```

Run before displaying the next prompt

Use this e.g. to display output from asynchronous operations (in order to not mess up text entry)

```
IPython.core.hooks.clipboard_get(self)
```

Get text from the clipboard.

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

8.22 Module: `core.inputsplitter`

DEPRECATED: Input handling and transformation machinery.

This module was deprecated in IPython 7.0, in favour of `inputtransformer2`.

The first class in this module, *InputSplitter*, is designed to tell when input from a line-oriented frontend is complete and should be executed, and when the user should be prompted for another line of code instead. The name „input splitter“ is largely for historical reasons.

A companion, *IPythonInputSplitter*, provides the same functionality but with full support for the extended IPython syntax (magics, system calls, etc). The code to actually do these transformations is in *IPython.core.inputtransformer*. *IPythonInputSplitter* feeds the raw code to the transformers in order and stores the results.

For more details, see the class docstrings below.

8.22.1 4 Classes

```
class IPython.core.inputsplitter.IncompleteString(s, start, end, line)
```

Базовые классы: `object`

```
__init__(s, start, end, line)
```

```
class IPython.core.inputsplitter.InMultilineStatement(pos, line)
```

Базовые классы: `object`

```
__init__(pos, line)
```

```
class IPython.core.inputsplitter.InputSplitter
```

Базовые классы: `object`

An object that can accumulate lines of Python source before execution.

This object is designed to be fed python source line-by-line, using *push()*. It will return on each push whether the currently pushed code could be executed already. In addition, it provides a method called

`push_accepts_more()` that can be used to query whether more input can be pushed into a single interactive block.

This is a simple example of how an interactive terminal-based client can use this tool:

```
isp = InputSplitter()
while isp.push_accepts_more():
    indent = ' '*isp.indent_spaces
    prompt = '>>> ' + indent
    line = indent + raw_input(prompt)
    isp.push(line)
print 'Input source was:\n', isp.source_reset(),
```

`__init__()` → `None`

Create a new `InputSplitter` instance.

`check_complete(source)`

Return whether a block of code is ready to execute, or should be continued

This is a non-stateful API, and will reset the state of this `InputSplitter`.

Параметры

`source` (*string*) – Python input code, which can be multiline.

Результат

- **status** (*str*) – One of „complete“, „incomplete“, or „invalid“ if source is not a prefix of valid code.
- **indent_spaces** (*int or None*) – The number of spaces by which to indent the next line of code. If status is not „incomplete“, this is `None`.

`push(lines: str) → bool`

Push one or more lines of input.

This stores the given lines and returns a status code indicating whether the code forms a complete Python block or not.

Any exceptions generated in compilation are swallowed, but if an exception was produced, the method returns `True`.

Параметры

`lines` (*string*) – One or more lines of Python input.

Результат

is_complete – `True` if the current input source (the result of the current input plus prior inputs) forms a complete Python execution block. Note that this value is also stored as a private attribute (`_is_complete`), so it can be queried at any time.

Тип результата

boolean

`push_accepts_more()`

Return whether a block of interactive input can accept more input.

This method is meant to be used by line-oriented frontends, who need to guess whether a block is complete or not based solely on prior and current input lines. The `InputSplitter` considers it has a complete interactive block and will not accept more input when either:

- A `SyntaxError` is raised
- The code is complete and consists of a single line or a single non-compound statement

- The code is complete and has a blank line at the end

If the current input produces a syntax error, this method immediately returns False but does *not* raise the syntax error exception, as typically clients will want to send invalid syntax to an execution backend which might convert the invalid syntax into valid Python via one of the dynamic IPython mechanisms.

`reset()`

Reset the input buffer and associated state.

`source_reset()`

Return the input source and perform a full reset.

```
class IPython.core.inputsplitter.IPythonInputSplitter(line_input_checker=True,
                                                       physical_line_transforms=None,
                                                       logical_line_transforms=None,
                                                       python_line_transforms=None)
```

Базовые классы: *InputSplitter*

An input splitter that recognizes all of IPython's special syntax.

```
__init__(line_input_checker=True, physical_line_transforms=None,
         logical_line_transforms=None, python_line_transforms=None)
```

Create a new InputSplitter instance.

`push(lines: str) → bool`

Push one or more lines of IPython input.

This stores the given lines and returns a status code indicating whether the code forms a complete Python block or not, after processing all input lines for special IPython syntax.

Any exceptions generated in compilation are swallowed, but if an exception was produced, the method returns True.

Параметры

`lines (string)` – One or more lines of Python input.

Результат

`is_complete` – True if the current input source (the result of the current input plus prior inputs) forms a complete Python execution block. Note that this value is also stored as a private attribute (`_is_complete`), so it can be queried at any time.

Тип результата

boolean

`push_accepts_more()`

Return whether a block of interactive input can accept more input.

This method is meant to be used by line-oriented frontends, who need to guess whether a block is complete or not based solely on prior and current input lines. The InputSplitter considers it has a complete interactive block and will not accept more input when either:

- A SyntaxError is raised
- The code is complete and consists of a single line or a single non-compound statement
- The code is complete and has a blank line at the end

If the current input produces a syntax error, this method immediately returns False but does *not* raise the syntax error exception, as typically clients will want to send invalid syntax to an execution backend which might convert the invalid syntax into valid Python via one of the dynamic IPython mechanisms.

`raw_reset()`

Return raw input only and perform a full reset.

`reset()`

Reset the input buffer and associated state.

`source_reset()`

Return the input source and perform a full reset.

`transform_cell(cell)`

Process and translate a cell of input.

`property transforms`

Quick access to all transformers.

`property transforms_in_use`

Transformers, excluding logical line transformers if we're in a Python line.

8.22.2 7 Functions

`IPython.core.inputsplitter.num_ini_spaces(s)`

Return the number of initial spaces in a string.

Note that tabs are counted as a single space. For now, we do *not* support mixing of tabs and spaces in the user's input.

Параметры

s (*string*) –

Результат

n

Тип результата

int

`IPython.core.inputsplitter.partial_tokens(s)`

Iterate over tokens from a possibly-incomplete string of code.

This adds two special token types: `INCOMPLETE_STRING` and `IN_MULTILINE_STATEMENT`. These can only occur as the last token yielded, and represent the two main ways for code to be incomplete.

`IPython.core.inputsplitter.find_next_indent(code)`

Find the number of spaces for the next line of indentation

`IPython.core.inputsplitter.last_blank(src)`

Determine if the input source ends in a blank.

A blank is either a newline or a line consisting of whitespace.

Параметры

src (*string*) – A single or multiline string.

`IPython.core.inputsplitter.last_two_blanks(src)`

Determine if the input source ends in two blanks.

A blank is either a newline or a line consisting of whitespace.

Параметры

src (*string*) – A single or multiline string.

```
IPython.core.inputsplitter.remove_comments(src)
```

Remove all comments from input source.

Note: comments are NOT recognized inside of strings!

Параметры

src (*string*) – A single or multiline input string.

Тип результата

String with all Python comments removed.

```
IPython.core.inputsplitter.get_input_encoding()
```

Return the default standard input encoding.

If sys.stdin has no encoding, „ascii“ is returned.

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

8.23 Module: `core.inputtransformer`

DEPRECATED: Input transformer classes to support IPython special syntax.

This module was deprecated in IPython 7.0, in favour of `inputtransformer2`.

This includes the machinery to recognise and transform `%magic` commands, `!system` commands, `help?` querying, prompt stripping, and so forth.

8.23.1 5 Classes

```
class IPython.core.inputtransformer.InputTransformer
```

Базовые классы: `object`

Abstract base class for line-based input transformers.

```
abstract push(line)
```

Send a line of input to the transformer, returning the transformed input or None if the transformer is waiting for more input.

Must be overridden by subclasses.

Implementations may raise `SyntaxError` if the input is invalid. No other exceptions may be raised.

```
abstract reset()
```

Return, transformed any lines that the transformer has accumulated, and reset its internal state.

Must be overridden by subclasses.

`classmethod wrap(func)`

Can be used by subclasses as a decorator, to return a factory that will allow instantiation with the decorated object.

`class IPython.core.inputtransformer.StatelessInputTransformer(func)`

Базовые классы: *InputTransformer*

Wrapper for a stateless input transformer implemented as a function.

`__init__(func)`

`push(line)`

Send a line of input to the transformer, returning the transformed input.

`reset()`

No-op - exists for compatibility.

`class IPython.core.inputtransformer.CoroutineInputTransformer(coro, **kwargs)`

Базовые классы: *InputTransformer*

Wrapper for an input transformer implemented as a coroutine.

`__init__(coro, **kwargs)`

`push(line)`

Send a line of input to the transformer, returning the transformed input or None if the transformer is waiting for more input.

`reset()`

Return, transformed any lines that the transformer has accumulated, and reset its internal state.

`class IPython.core.inputtransformer.TokenInputTransformer(func)`

Базовые классы: *InputTransformer*

Wrapper for a token-based input transformer.

func should accept a list of tokens (5-tuples, see tokenize docs), and return an iterable which can be passed to tokenize.untokenize().

`__init__(func)`

`push(line)`

Send a line of input to the transformer, returning the transformed input or None if the transformer is waiting for more input.

Must be overridden by subclasses.

Implementations may raise `SyntaxError` if the input is invalid. No other exceptions may be raised.

`reset()`

Return, transformed any lines that the transformer has accumulated, and reset its internal state.

Must be overridden by subclasses.

`class IPython.core.inputtransformer.assemble_python_lines`

Базовые классы: *TokenInputTransformer*

`__init__()`

8.23.2 11 Functions

`IPython.core.inputtransformer.assemble_logical_lines()`

Join lines following explicit line continuations ()

`IPython.core.inputtransformer.escaped_commands(line)`

Transform escaped commands - %magic, !system, ?help + various autocalls.

`IPython.core.inputtransformer.has_comment(src)`

Indicate whether an input line has (i.e. ends in, or is) a comment.

This uses tokenize, so it can distinguish comments from # inside strings.

Параметры

src (*string*) – A single line input string.

Результат

comment – True if source has a comment.

Тип результата

`bool`

`IPython.core.inputtransformer.ends_in_comment_or_string(src)`

Indicates whether or not an input line ends in a comment or within a multiline string.

Параметры

src (*string*) – A single line input string.

Результат

comment – True if source ends in a comment or multiline string.

Тип результата

`bool`

`IPython.core.inputtransformer.help_end(line)`

Translate lines with ?/? at the end

`IPython.core.inputtransformer.cellmagic(end_on_blank_line=False)`

Captures & transforms cell magics.

After a cell magic is started, this stores up any lines it gets until it is reset (sent None).

`IPython.core.inputtransformer.classic_prompt()`

Strip the >>>/... prompts of the Python interactive shell.

`IPython.core.inputtransformer.ipy_prompt()`

Strip IPython's In [1]:/...: prompts.

`IPython.core.inputtransformer.leading_indent()`

Remove leading indentation.

If the first line starts with a spaces or tabs, the same whitespace will be removed from each following line until it is reset.

`IPython.core.inputtransformer.assign_from_system(line)`

Transform assignment from system commands (e.g. files = !ls)

`IPython.core.inputtransformer.assign_from_magic(line)`

Transform assignment from magic commands (e.g. a = %who_ls)

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

8.24 Module: `core.inputtransformer2`

Input transformer machinery to support IPython special syntax.

This includes the machinery to recognise and transform `%magic` commands, `!system` commands, `help?` querying, prompt stripping, and so forth.

Added: IPython 7.0. Replaces `inputsplitter` and `inputtransformer` which were deprecated in 7.0.

8.24.1 9 Classes

```
class IPython.core.inputtransformer2.PromptStripper(prompt_re, initial_re=None)
```

Базовые классы: `object`

Remove matching input prompts from a block of input.

Параметры

- `prompt_re` (*regular expression*) – A regular expression matching any input prompt (including continuation, e.g. `...`)
- `initial_re` (*regular expression, optional*) – A regular expression matching only the initial prompt, but not continuation. If no initial expression is given, `prompt_re` will be used everywhere. Used mainly for plain Python prompts (`>>>`), where the continuation prompt `...` is a valid Python expression in Python 3, so shouldn't be stripped.

Заметки

If `initial_re` and `prompt_re` differ, only `initial_re` will be tested against the first line. If any prompt is found on the first two lines, prompts will be stripped from the rest of the block.

```
__init__(prompt_re, initial_re=None)
```

```
class IPython.core.inputtransformer2.TokenTransformBase(start)
```

Базовые классы: `object`

Base class for transformations which examine tokens.

Special syntax should not be transformed when it occurs inside strings or comments. This is hard to reliably avoid with regexes. The solution is to tokenise the code as Python, and recognise the special syntax in the tokens.

IPython's special syntax is not valid Python syntax, so tokenising may go wrong after the special syntax starts. These classes therefore find and transform *one* instance of special syntax at a time into regular Python syntax. After each transformation, tokens are regenerated to find the next piece of special syntax.

Subclasses need to implement one class method (`find`) and one regular method (`transform`).

The priority attribute can select which transformation to apply if multiple transformers match in the same place. Lower numbers have higher priority. This allows «%magic?» to be turned into a help call rather than a magic call.

```
__init__(start)
```

```
classmethod find(tokens_by_line)
```

Find one instance of special syntax in the provided tokens.

Tokens are grouped into logical lines for convenience, so it is easy to e.g. look at the first token of each line. `tokens_by_line` is a list of lists of `tokenize.TokenInfo` objects.

This should return an instance of its class, pointing to the start position it has found, or `None` if it found no match.

```
transform(lines: List[str])
```

Transform one instance of special syntax found by `find()`

Takes a list of strings representing physical lines, returns a similar list of transformed lines.

```
class IPython.core.inputtransformer2.MagicAssign(start)
```

Базовые классы: `TokenTransformBase`

Transformer for assignments from magics (`a = %foo`)

```
classmethod find(tokens_by_line)
```

Find the first magic assignment (`a = %foo`) in the cell.

```
transform(lines: List[str])
```

Transform a magic assignment found by the `find()` classmethod.

```
class IPython.core.inputtransformer2.SystemAssign(start)
```

Базовые классы: `TokenTransformBase`

Transformer for assignments from system commands (`a = !foo`)

```
classmethod find(tokens_by_line)
```

Find the first system assignment (`a = !foo`) in the cell.

```
transform(lines: List[str])
```

Transform a system assignment found by the `find()` classmethod.

```
class IPython.core.inputtransformer2.EscapedCommand(start)
```

Базовые классы: `TokenTransformBase`

Transformer for escaped commands like `%foo`, `!foo`, or `/foo`

```
classmethod find(tokens_by_line)
```

Find the first escaped command (`%foo`, `!foo`, etc.) in the cell.

```
transform(lines)
```

Transform an escaped line found by the `find()` classmethod.

```
class IPython.core.inputtransformer2.HelpEnd(start, q_locn)
```

Базовые классы: `TokenTransformBase`

Transformer for help syntax: obj? and obj??

```
__init__(start, q_locn)
```

```
classmethod find(tokens_by_line)
```

Find the first help command (foo?) in the cell.

```
transform(lines)
```

Transform a help command found by the `find()` classmethod.

```
class IPython.core.inputtransformer2.TransformerManager
```

Базовые классы: `object`

Applies various transformations to a cell or code block.

The key methods for external use are `transform_cell()` and `check_complete()`.

```
__init__()
```

```
check_complete(cell: str)
```

Return whether a block of code is ready to execute, or should be continued

Параметры

`cell (string)` – Python input code, which can be multiline.

Результат

- **status** (`str`) – One of „complete“, „incomplete“, or „invalid“ if source is not a prefix of valid code.
- **indent_spaces** (`int or None`) – The number of spaces by which to indent the next line of code. If status is not „incomplete“, this is None.

```
do_one_token_transform(lines)
```

Find and run the transform earliest in the code.

Returns (changed, lines).

This method is called repeatedly until `changed` is False, indicating that all available transformations are complete.

The tokens following IPython special syntax might not be valid, so the transformed code is retokenised every time to identify the next piece of special syntax. Hopefully long code cells are mostly valid Python, not using lots of IPython special syntax, so this shouldn't be a performance issue.

```
transform_cell(cell: str) → str
```

Transforms a cell of input code

```
class IPython.core.inputtransformer2.MaybeAsyncCompile(extra_flags=0)
```

Базовые классы: `Compile`

```
__init__(extra_flags=0)
```

```
class IPython.core.inputtransformer2.MaybeAsyncCommandCompiler(extra_flags=0)
```

Базовые классы: `CommandCompiler`

```
__init__(extra_flags=0)
```

8.24.2 9 Functions

`IPython.core.inputtransformer2.leading_empty_lines(lines)`

Remove leading empty lines

If the leading lines are empty or contain only whitespace, they will be removed.

`IPython.core.inputtransformer2.leading_indent(lines)`

Remove leading indentation.

If the first line starts with a spaces or tabs, the same whitespace will be removed from each following line in the cell.

`IPython.core.inputtransformer2.cell_magic(lines)`

`IPython.core.inputtransformer2.find_end_of_continued_line(lines, start_line: int)`

Find the last line of a line explicitly extended using backslashes.

Uses 0-indexed line numbers.

`IPython.core.inputtransformer2.assemble_continued_line(lines, start: Tuple[int, int], end_line: int)`

Assemble a single line from multiple continued line pieces

Continued lines are lines ending in \, and the line following the last \ in the block.

For example, this code continues over multiple lines:

```
if (assign_ix is not None) \
    and (len(line) >= assign_ix + 2) \
    and (line[assign_ix+1].string == '%') \
    and (line[assign_ix+2].type == tokenize.NAME):
```

This statement contains four continued line pieces. Assembling these pieces into a single line would give:

```
if (assign_ix is not None) and (len(line) >= assign_ix + 2) and (line[...
```

This uses 0-indexed line numbers. *start* is (lineno, colno).

Used to allow `%magic` and `!system` commands to be continued over multiple lines.

`IPython.core.inputtransformer2.make_tokens_by_line(lines: List[str])`

Tokenize a series of lines and group tokens by line.

The tokens for a multiline Python string or expression are grouped as one line. All lines except the last lines should keep their line ending (“\n“, “\r\n“) for this to properly work. Use `.splitlines(keeplineending=True)` for example when passing block of text to this function.

`IPython.core.inputtransformer2.has_sunken_brackets(tokens: List[TokenInfo])`

Check if the depth of brackets in the list of tokens drops below 0

`IPython.core.inputtransformer2.show_linewise_tokens(s: str)`

For investigation and debugging

`IPython.core.inputtransformer2.find_last_indent(lines)`

<p>Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.</p>
--

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

8.25 Module: `core.interactiveshell`

Main IPython class.

8.25.1 7 Classes

```
class IPython.core.interactiveshell.ProvisionalWarning
```

Базовые классы: `DeprecationWarning`

Warning class for unstable features

```
class IPython.core.interactiveshell.SpaceInInput
```

Базовые классы: `Exception`

```
class IPython.core.interactiveshell.SeparateUnicode(default_value=traitlets.Undefined,
                                                    allow_none=False, read_only=None,
                                                    help=None, config=None, **kwargs)
```

Базовые классы: `Unicode`

A Unicode subclass to validate `separate_in`, `separate_out`, etc.

This is a Unicode based trait that converts „0“->““ and ‘\n’->‘\n’.

```
class IPython.core.interactiveshell.ExecutionInfo(raw_cell, store_history, silent, shell_futures,
                                                  cell_id)
```

Базовые классы: `object`

The arguments used for a call to `InteractiveShell.run_cell()`

Stores information about what is going to happen.

```
__init__(raw_cell, store_history, silent, shell_futures, cell_id)
```

```
class IPython.core.interactiveshell.ExecutionResult(info)
```

Базовые классы: `object`

The result of a call to `InteractiveShell.run_cell()`

Stores information about what took place.

```
__init__(info)
```

```
raise_error()
```

Reraises error if `success` is `False`, otherwise does nothing

```
class IPython.core.interactiveshell.InteractiveShell(**kwargs: Any)
```

Базовые классы: `SingletonConfigurable`

An enhanced, interactive shell for Python.

```
__init__(ipython_dir=None, profile_dir=None, user_module=None, user_ns=None,
         custom_exceptions=(), None), **kwargs)
```

Create a configurable given a config config.

Параметры

- **config** (*Config*) – If this is empty, default values are used. If config is a **Config** instance, it will be used to configure the instance.
- **parent** (*Configurable instance, optional*) – The parent Configurable instance of this object.

Заметки

Subclasses of Configurable must call the `__init__()` method of **Configurable** *before* doing anything else and using `super()`:

```
class MyConfigurable(Configurable):
    def __init__(self, config=None):
        super(MyConfigurable, self).__init__(config=config)
        # Then any other code you need to finish initialization.
```

This ensures that instances will be configured properly.

property all_ns_refs

Get a list of references to all the namespace dictionaries in which IPython might store a user-created object.

Note that this does not include the displayhook, which also caches objects from the output.

ast_node_interactivity

„all“, „last“, „last_expr“ or „none“, „last_expr_or_assign“ specifying which nodes should be run interactively (displaying output from expressions).

ast_transformers

A list of ast.NodeTransformer subclass instances, which will be applied to user input before code is run.

atexit_operations()

This will be executed at the time of exit.

Cleanup operations and saving of persistent data that is done unconditionally by IPython should be performed here.

For things that may depend on startup flags or platform specifics (such as having readline or not), register a separate atexit function in the code that has the appropriate information, rather than trying to clutter

auto_rewrite_input(cmd)

Print to the screen the rewritten form of the user's command.

This shows visual feedback by rewriting input lines that cause automatic calling to kick in, like:

```
/f x
```

into:

```
-----> f(x)
```

after the user's input prompt. This helps the user understand that the input line was transformed automatically by IPython.

autoawait

Automatically run await statement in the top level repl.

autocall

Make IPython automatically call any callable object even if you didn't type explicit parentheses. For example, „str 43“ becomes „str(43)“ automatically. The value can be „0“ to disable the feature, „1“ for „smart“ autocall, where it is not applied if there are no more arguments on the line, and „2“ for „full“ autocall, where all callable objects are automatically called (even if no arguments are present).

autoindent

Autoindent IPython code entered interactively.

automagic

Enable magic commands to be called without the leading %.

banner1

The part of the banner to be printed before the profile

banner2

The part of the banner to be printed after the profile

cache_size

Set the size of the output cache. The default is 1000, you can change it permanently in your config file. Setting it to 0 completely disables the caching system, and the minimum value accepted is 3 (if you provide a value less than 3, it is reset to 0 and a warning is issued). This limit is defined because otherwise you'll spend more time re-flushing a too small cache than working

property call_pdb

Control auto-activation of pdb at exceptions

check_complete(*code: str*) → Tuple[str, str]

Return whether a block of code is ready to execute, or should be continued

Параметры

code (*string*) – Python input code, which can be multiline.

Результат

- **status** (*str*) – One of „complete“, „incomplete“, or „invalid“ if source is not a prefix of valid code.
- **indent** (*str*) – When status is „incomplete“, this is some whitespace to insert on the next line of the prompt.

clear_main_mod_cache()

Clear the cache of main modules.

Mainly for use by utilities like %reset.

Примеры

```
In [15]: import IPython
```

```
In [16]: m = _ip.new_main_mod(IPython.__file__, „IPython“)
```

```
In [17]: len(_ip._main_mod_cache) > 0 Out[17]: True
```

```
In [18]: _ip.clear_main_mod_cache()
```

```
In [19]: len(_ip._main_mod_cache) == 0 Out[19]: True
```

color_info

Use colors for displaying information about objects. Because this information is passed through a pager (like „less“), and some pagers get confused with color codes, this capability can be turned off.

colors

Set the color scheme (NoColor, Neutral, Linux, or LightBG).

complete(text, line=None, cursor_pos=None)

Return the completed text and a list of completions.

Параметры

- **text** (*string*) – A string of text to be completed on. It can be given as empty and instead a line/position pair are given. In this case, the completer itself will split the line like readline does.
- **line** (*string*, *optional*) – The complete line that text is part of.
- **cursor_pos** (*int*, *optional*) – The position of the cursor on the input line.

Результат

- **text** (*string*) – The actual text that was completed.
- **matches** (*list*) – A sorted list with all possible completions.

Заметки

The optional arguments allow the completion to take more context into account, and are part of the low-level completion API.

This is a wrapper around the completion mechanism, similar to what readline does at the command line when the TAB key is hit. By exposing it as a method, it can be used by other non-readline environments (such as GUIs) for text completion.

Примеры

```
In [1]: x = „hello“
```

```
In [2]: _ip.complete(„x.l“) Out[2]: („x.l“, [„x.ljust“, „x.lower“, „x.lstrip“])
```

debugger(force=False)

Call the pdb debugger.

Keywords:

- `force(False)`: by default, this routine checks the instance call `_pdb` flag and does not actually invoke the debugger if the flag is false. The „force“ option forces the debugger to activate even if the flag is false.

`debugger_cls`

alias of `InterruptiblePdb`

`define_macro(name, themacro)`

Define a new macro

Параметры

- `name (str)` – The name of the macro.
- `themacro (str or Macro)` – The action to do upon invoking the macro. If a string, a new Macro object is created by passing the string to it.

`del_var(varname, by_name=False)`

Delete a variable from the various namespaces, so that, as far as possible, we're not keeping any hidden references to it.

Параметры

- `varname (str)` – The name of the variable to delete.
- `by_name (bool)` – If True, delete variables with the given name in each namespace. If False (default), find the variable in the user namespace, and delete references to it.

`disable_failing_post_execute`

Don't call post-execute functions that have failed in the past.

`display_page`

If True, anything that would be passed to the pager will be displayed as regular output instead.

`drop_by_id(variables)`

Remove a dict of variables from the user namespace, if they are the same as the values in the dictionary.

This is intended for use by extensions: variables that they've added can be taken back out if they are unloaded, without removing any that the user has overwritten.

Параметры

`variables (dict)` – A dictionary mapping object names (as strings) to the objects.

`enable_html_pager`

(Provisional API) enables html representation in mime bundles sent to pagers.

`enable_matplotlib(gui=None)`

Enable interactive matplotlib and inline figure support.

This takes the following steps:

1. select the appropriate eventloop and matplotlib backend
2. set up matplotlib for interactive use with that backend
3. configure formatters for inline figure display
4. enable the selected gui eventloop

Параметры

`gui` (*optional*, *string*) – If given, dictates the choice of matplotlib GUI backend to use (should be one of IPython’s supported backends, „qt“, „osx“, „tk“, „gtk“, „wx“ or „inline“), otherwise we use the default chosen by matplotlib (as dictated by the matplotlib build-time options plus the user’s matplotlibrc configuration file). Note that not all backends make sense in all contexts, for example a terminal ipython can’t display figures inline.

`enable_pylab(gui=None, import_all=True, welcome_message=False)`

Activate pylab support at runtime.

This turns on support for matplotlib, preloads into the interactive namespace all of numpy and pylab, and configures IPython to correctly interact with the GUI event loop. The GUI backend to be used can be optionally selected with the optional `gui` argument.

This method only adds preloading the namespace to InteractiveShell.enable_matplotlib.

Параметры

- `gui` (*optional*, *string*) – If given, dictates the choice of matplotlib GUI backend to use (should be one of IPython’s supported backends, „qt“, „osx“, „tk“, „gtk“, „wx“ or „inline“), otherwise we use the default chosen by matplotlib (as dictated by the matplotlib build-time options plus the user’s matplotlibrc configuration file). Note that not all backends make sense in all contexts, for example a terminal ipython can’t display figures inline.
- `import_all` (*optional*, *bool*, *default: True*) – Whether to do `from numpy import *` and `from pylab import *` in addition to module imports.
- `welcome_message` (*deprecated*) – This argument is ignored, no welcome message will be displayed.

`ev(expr)`

Evaluate python expression `expr` in user namespace.

Returns the result of evaluation

`ex(cmd)`

Execute a normal python statement in user namespace.

`excepthook(etype, value, tb)`

One more defense for GUI apps that call `sys.excepthook`.

GUI frameworks like wxPython trap exceptions and call `sys.excepthook` themselves. I guess this is a feature that enables them to keep running after exceptions that would otherwise kill their mainloop. This is a bother for IPython which expects to catch all of the program exceptions with a `try: except: statement`.

Normally, IPython sets `sys.excepthook` to a `CrashHandler` instance, so if any app directly invokes `sys.excepthook`, it will look to the user like IPython crashed. In order to work around this, we can disable the `CrashHandler` and replace it with this `excepthook` instead, which prints a regular traceback using our `InteractiveTB`. In this fashion, apps which call `sys.excepthook` will generate a regular-looking exception from IPython, and the `CrashHandler` will only be triggered by real IPython crashes.

This hook should be used sparingly, only in places which are not likely to be true IPython errors.

`extract_input_lines(range_str, raw=False)`

Return as a string a set of input history slices.

Параметры

- `range_str (str)` – The set of slices is given as a string, like «~5/6-~4/2 4:8 9», since this function is for use by magic functions which get their arguments as strings. The number before the / is the session number: ~n goes n back from the current session.

If empty string is given, returns history of current session without the last input.

- `raw (bool, optional)` – By default, the processed input is used. If this is true, the raw input history is used instead.

Заметки

Slices can be described with two notations:

- `N:M ->` standard python form, means including items `N... (M-1)`.
- `N-M ->` include items `N..M` (closed endpoint).

`find_cell_magic(magic_name)`

Find and return a cell magic by name.

Returns None if the magic isn't found.

`find_line_magic(magic_name)`

Find and return a line magic by name.

Returns None if the magic isn't found.

`find_magic(magic_name, magic_kind='line')`

Find and return a magic of the given type by name.

Returns None if the magic isn't found.

`find_user_code(target, raw=True, py_only=False, skip_encoding_cookie=True, search_ns=False)`

Get a code string from history, file, url, or a string or macro.

This is mainly used by magic functions.

Параметры

- `target (str)` – A string specifying code to retrieve. This will be tried respectively as: ranges of input history (see %history for syntax), url, corresponding .py file, filename, or an expression evaluating to a string or Macro in the user namespace.

If empty string is given, returns complete history of current session, without the last line.

- `raw (bool)` – If true (default), retrieve raw history. Has no effect on the other retrieval mechanisms.
- `py_only (bool (default False))` – Only try to fetch python code, do not try alternative methods to decode file if unicode fails.

Результат

- *A string of code.*
- *ValueError is raised if nothing is found, and TypeError if it evaluates*
- *to an object of another type. In each case, .args[0] is a printable*
- *message.*

`get_exception_only(exc_tuple=None)`

Return as a string (ending with a newline) the exception that just occurred, without any traceback.

`get_ipython()`

Return the currently running IPython instance.

`get_local_scope(stack_depth)`

Get local scope at given stack depth.

Параметры

`stack_depth (int)` – Depth relative to calling frame

`static get_path_links(p: Path)`

Gets path links including all symlinks

Примеры

In [1]: from IPython.core.interactiveshell import InteractiveShell

In [2]: import sys, pathlib

In [3]: paths = InteractiveShell.get_path_links(pathlib.Path(sys.executable))

In [4]: len(paths) == len(set(paths)) Out[4]: True

In [5]: bool(paths) Out[5]: True

`getoutput(cmd, split=True, depth=0)`

Get output (possibly including stderr) from a subprocess.

Параметры

- `cmd (str)` – Command to execute (can not end in „&“, as background processes are not supported).
- `split (bool, optional)` – If True, split the output into an IPython SList. Otherwise, an IPython LSString is returned. These are objects similar to normal lists and strings, with a few convenience attributes for easier manipulation of line-based output. You can use „?“ on them for details.
- `depth (int, optional)` – How many frames above the caller are the local variables which should be expanded in the command string? The default (0) assumes that the expansion variables are in the stack frame calling this function.

`history_length`

Total length of command history

`history_load_length`

The number of saved history entries to be loaded into the history buffer at startup.

`init_completer()`

Initialize the completion machinery.

This creates completion machinery that can be used by client code, either interactively in-process (typically triggered by the readline library), programmatically (such as in test suites) or out-of-process (typically over the network by remote frontends).

`init_environment()`

Any changes we need to make to the user's environment.

`init_history()`

Sets up the command history, and starts regular autosaves.

`init_logstart()`

Initialize logging in case it was requested at the command line.

`init_user_ns()`

Initialize all user-visible namespaces to their minimum defaults.

Certain history lists are also initialized here, as they effectively act as user namespaces.

Заметки

All data structures here are only filled in, they are NOT reset by this method. If they were not empty before, data will simply be added to them.

`init_virtualenv()`

Add the current virtualenv to `sys.path` so the user can import modules from it. This isn't perfect: it doesn't use the Python interpreter with which the virtualenv was built, and it ignores the `--no-site-packages` option. A warning will appear suggesting the user installs IPython in the virtualenv, but for many cases, it probably works well enough.

Adapted from code snippets online.

<http://blog.ufsoft.org/2009/1/29/ipython-and-virtualenv>

`property input_splitter`

Make this available for backward compatibility (pre-7.0 release) with existing code.

For example, ipykernel currently uses `shell.input_splitter.check_complete`

`input_transformers_post`

A list of string input transformers, to be applied after IPython's own input transformations.

`inspector_class`

Class to use to instantiate the shell inspector

`last_execution_result`

Result of executing the last command

`last_execution_succeeded`

Did last executed command succeeded

`logappend`

Start logging to the given file in append mode. Use `logfile` to specify a log file to **overwrite** logs to.

`logfile`

The name of the logfile to use.

`logstart`

Start logging to the default log file in overwrite mode. Use `logappend` to specify a log file to **append** logs to.

`loop_runner`

Select the loop runner that will be used to execute top-level asynchronous code

`magic(arg_s)`

DEPRECATED

Deprecated since IPython 0.13 (warning added in 8.1), use `run_line_magic(magic_name, parameter_s)`.

Call a magic function by name.

Input: a string containing the name of the magic function to call and any additional arguments to be passed to the magic.

`magic(„name -opt foo bar“)` is equivalent to typing at the ipython prompt:

In[1]: `%name -opt foo bar`

To call a magic without arguments, simply use `magic(„name“)`.

This provides a proper Python function to call IPython’s magics in any valid Python code you can type at the interpreter, including loops and compound statements.

`mktempfile(data=None, prefix='ipython_edit_')`

Make a new tempfile and return its filename.

This makes a call to `tempfile.mkstemp` (created in a `tempfile.mkdtemp`), but it registers the created filename internally so ipython cleans it up at exit time.

Optional inputs:

- `data(None)`: if data is given, it gets written out to the temp file immediately, and the file is closed again.

`new_main_mod(filename, modname)`

Return a new „main“ module object for user code execution.

`filename` should be the path of the script which will be run in the module. Requests with the same filename will get the same module, with its namespace cleared.

`modname` should be the module name - normally either „`__main__`“ or the basename of the file without the extension.

When scripts are executed via `%run`, we must keep a reference to their `__main__` module around so that Python doesn’t clear it, rendering references to module globals useless.

This method keeps said reference in a private dict, keyed by the absolute path of the script. This way, for multiple executions of the same script we only keep one copy of the namespace (the last one), thus preventing memory leaks from old references while allowing the objects from the last execution to be accessible.

`object_inspect(oname, detail_level=0)`

Get object info about oname

`object_inspect_mime(oname, detail_level=0, omit_sections=())`

Get object info as a mimebundle of formatted representations.

A mimebundle is a dictionary, keyed by mime-type. It must always have the key `'text/plain'`.

`object_inspect_text(oname, detail_level=0)`

Get object info as formatted text

`pdb`

Automatically call the `pdb` debugger after every exception.

`prepare_user_module(user_module=None, user_ns=None)`

Prepare the module and namespace in which user code will be run.

When IPython is started normally, both parameters are None: a new module is created automatically, and its `__dict__` used as the namespace.

If only `user_module` is provided, its `__dict__` is used as the namespace. If only `user_ns` is provided, a dummy module is created, and `user_ns` becomes the global namespace. If both are provided (as they may be when embedding), `user_ns` is the local namespace, and `user_module` provides the global namespace.

Параметры

- `user_module` (*module*, *optional*) – The current user module in which IPython is being run. If None, a clean module will be created.
- `user_ns` (*dict*, *optional*) – A namespace in which to run interactive commands.

Тип результата

A tuple of `user_module` and `user_ns`, each properly initialised.

`push(variables, interactive=True)`

Inject a group of variables into the IPython user namespace.

Параметры

- `variables` (*dict*, *str* or *list/tuple of str*) – The variables to inject into the user's namespace. If a dict, a simple update is done. If a str, the string is assumed to have variable names separated by spaces. A list/tuple of str can also be used to give the variable names. If just the variable names are give (list/tuple/str) then the variable values looked up in the callers frame.
- `interactive` (*bool*) – If True (default), the variables will be listed with the `who` magic.

`register_magic_function(func, magic_kind='line', magic_name=None)`

Expose a standalone function as magic function for IPython.

This will create an IPython magic (line, cell or both) from a standalone function. The functions should have the following signatures:

- For line magics: `def f(line)`
- For cell magics: `def f(line, cell)`
- For a function that does both: `def f(line, cell=None)`

In the latter case, the function will be called with `cell==None` when invoked as `%f`, and with `cell` as a string when invoked as `%%f`.

Параметры

- `func` (*callable*) – Function to be registered as a magic.
- `magic_kind` (*str*) – Kind of magic, one of „line“, „cell“ or „line_cell“
- `magic_name` (*optional str*) – If given, the name the magic will have in the IPython namespace. By default, the name of the function itself is used.

`register_post_execute(func)`

DEPRECATED: Use `ip.events.register(„post_run_cell“, func)`

Register a function for calling after code execution.

`reset(new_session=True, aggressive=False)`

Clear all internal namespaces, and attempt to release references to user objects.

If `new_session` is `True`, a new history session will be opened.

`reset_selective(regex=None)`

Clear selective variables from internal namespaces based on a specified regular expression.

Параметры

`regex` (*string or compiled pattern, optional*) – A regular expression pattern that will be used in searching variable names in the users namespaces.

`restore_sys_module_state()`

Restore the state of the `sys` module.

`async run_ast_nodes(nodelist: ~typing.List[~ast.stmt], cell_name: str, interactivity='last_expr', compiler=<built-in function compile>, result=None)`

Run a sequence of AST nodes. The execution mode depends on the `interactivity` parameter.

Параметры

- `nodelist` (*list*) – A sequence of AST nodes to run.
- `cell_name` (*str*) – Will be passed to the compiler as the filename of the cell. Typically the value returned by `ip.compile.cache(cell)`.
- `interactivity` (*str*) – „all“, „last“, „last_expr“, „last_expr_or_assign“ or „none“, specifying which nodes should be run interactively (displaying output from expressions). „last_expr“ will run the last node interactively only if it is an expression (i.e. expressions in loops or other blocks are not displayed) „last_expr_or_assign“ will run the last expression or the last assignment. Other values for this parameter will raise a `ValueError`.
- `compiler` (*callable*) – A function with the same interface as the built-in `compile()`, to turn the AST nodes into code objects. Default is the built-in `compile()`.
- `result` (`ExecutionResult`, *optional*) – An object to store exceptions that occur during execution.

Результат

- *True if an exception occurred while running code, False if it finished*
- *running.*

`run_cell(raw_cell, store_history=False, silent=False, shell_futures=True, cell_id=None)`

Run a complete IPython cell.

Параметры

- `raw_cell` (*str*) – The code (including IPython code such as `%magic` functions) to run.
- `store_history` (*bool*) – If `True`, the raw and translated cell will be stored in IPython’s history. For user code calling back into IPython’s machinery, this should be set to `False`.
- `silent` (*bool*) – If `True`, avoid side-effects, such as implicit displayhooks and and logging. `silent=True` forces `store_history=False`.

- `shell_futures` (*bool*) – If True, the code will share future statements with the interactive shell. It will both be affected by previous `__future__` imports, and any `__future__` imports in the code will affect the shell. If False, `__future__` imports are not shared in either direction.

Результат`result`**Тип результата***ExecutionResult*

```
async run_cell_async(raw_cell: str, store_history=False, silent=False, shell_futures=True, *,
                    transformed_cell: Optional[str] = None, preprocessing_exc_tuple:
                    Optional[Any] = None, cell_id=None) → ExecutionResult
```

Run a complete IPython cell asynchronously.

Параметры

- `raw_cell` (*str*) – The code (including IPython code such as `%magic` functions) to run.
- `store_history` (*bool*) – If True, the raw and translated cell will be stored in IPython’s history. For user code calling back into IPython’s machinery, this should be set to False.
- `silent` (*bool*) – If True, avoid side-effects, such as implicit displayhooks and logging. `silent=True` forces `store_history=False`.
- `shell_futures` (*bool*) – If True, the code will share future statements with the interactive shell. It will both be affected by previous `__future__` imports, and any `__future__` imports in the code will affect the shell. If False, `__future__` imports are not shared in either direction.
- `transformed_cell` (*str*) – cell that was passed through transformers
- `preprocessing_exc_tuple` – trace if the transformation failed.

Результат

- `result` (*ExecutionResult*)
- `.. versionadded:: 7.0`

```
run_cell_magic(magic_name, line, cell)
```

Execute the given cell magic.

Параметры

- `magic_name` (*str*) – Name of the desired magic function, without „`%`“ prefix.
- `line` (*str*) – The rest of the first input line as a single string.
- `cell` (*str*) – The body of the cell as a (possibly multiline) string.

```
async run_code(code_obj, result=None, *, async_=False)
```

Execute a code object.

When an exception occurs, `self.showtraceback()` is called to display a traceback.

Параметры

- `code_obj` (*code object*) – A compiled code object, to be executed
- `result` (*ExecutionResult*, *optional*) – An object to store exceptions that occur during execution.

- `async` (*Bool (Experimental)*) – Attempt to run top-level asynchronous code in a default loop.

Результат

- `False` (*successful execution.*)
- `True` (*an error occurred.*)

`run_line_magic(magic_name: str, line, _stack_depth=1)`

Execute the given line magic.

Параметры

- `magic_name` (*str*) – Name of the desired magic function, without „%“ prefix.
- `line` (*str*) – The rest of the input line as a single string.
- `_stack_depth` (*int*) – If `run_line_magic()` is called from `magic()` then `_stack_depth=2`. This is added to ensure backward compatibility for use of `„get_ipython().magic()“`

`async runcode(code_obj, result=None, *, async_=False)`

Execute a code object.

When an exception occurs, `self.showtraceback()` is called to display a traceback.

Параметры

- `code_obj` (*code object*) – A compiled code object, to be executed
- `result` (*ExecutionResult, optional*) – An object to store exceptions that occur during execution.
- `async` (*Bool (Experimental)*) – Attempt to run top-level asynchronous code in a default loop.

Результат

- `False` (*successful execution.*)
- `True` (*an error occurred.*)

`safe_execfile(fname, *where, exit_ignore=False, raise_exceptions=False, shell_futures=False)`

A safe version of the builtin `execfile()`.

This version will never throw an exception, but instead print helpful error messages to the screen. This only works on pure Python files with the `.py` extension.

Параметры

- `fname` (*string*) – The name of the file to be executed.
- `*where` (*tuple*) – One or two namespaces, passed to `execfile()` as `(globals,locals)`. If only one is given, it is passed as both.
- `exit_ignore` (*bool (False)*) – If `True`, then silence `SystemExit` for non-zero status (it is always silenced for zero status, as it is so common).
- `raise_exceptions` (*bool (False)*) – If `True` raise exceptions everywhere. Meant for testing.
- `shell_futures` (*bool (False)*) – If `True`, the code will share future statements with the interactive shell. It will both be affected by previous `__future__` imports, and any `__future__` imports in the code will affect the shell. If `False`, `__future__` imports are not shared in either direction.

`safe_execfile_ipy(fname, shell_futures=False, raise_exceptions=False)`

Like `safe_execfile`, but for `.ipy` or `.ipynb` files with IPython syntax.

Параметры

- `fname` (*str*) – The name of the file to execute. The filename must have a `.ipy` or `.ipynb` extension.
- `shell_futures` (*bool* (`False`)) – If True, the code will share future statements with the interactive shell. It will both be affected by previous `__future__` imports, and any `__future__` imports in the code will affect the shell. If False, `__future__` imports are not shared in either direction.
- `raise_exceptions` (*bool* (`False`)) – If True raise exceptions everywhere. Meant for testing.

`safe_run_module(mod_name, where)`

A safe version of `runpy.run_module()`.

This version will never throw an exception, but instead print helpful error messages to the screen.

`SystemExit` exceptions with status code 0 or None are ignored.

Параметры

- `mod_name` (*string*) – The name of the module to be executed.
- `where` (*dict*) – The globals namespace.

`save_sys_module_state()`

Save the state of hooks in the `sys` module.

This has to be called after `self.user_module` is created.

`set_autoindent(value=None)`

Set the autoindent flag.

If called with no arguments, it acts as a toggle.

`set_completer_frame(frame=None)`

Set the frame of the completer.

`set_custom_completer(completer, pos=0) → None`

Adds a new custom completer function.

The position argument (defaults to 0) is the index in the completers list where you want the completer to be inserted.

`completer` should have the following signature:

```
def completion(self: Completer, text: string) -> List[str]:
    raise NotImplementedError
```

It will be bound to the current `Completer` instance and pass some text and return a list with current completions to suggest to the user.

`set_custom_exc(exc_tuple, handler)`

Set a custom exception handler, which will be called if any of the exceptions in `exc_tuple` occur in the mainloop (specifically, in the `run_code()` method).

Параметры

- `exc_tuple` (*tuple of exception classes*) – A *tuple* of exception classes, for which to call the defined handler. It is very important that you use a tuple, and NOT A LIST here, because of the way Python’s `except` statement works. If you only want to trap a single exception, use a singleton tuple:

```
exc_tuple == (MyCustomException,)
```

- `handler` (*callable*) – handler must have the following signature:

```
def my_handler(self, etype, value, tb, tb_offset=None):  
    ...  
    return structured_traceback
```

Your handler must return a structured traceback (a list of strings), or `None`.

This will be made into an instance method (via `types.MethodType`) of IPython itself, and it will be called if any of the exceptions listed in the `exc_tuple` are caught. If the handler is `None`, an internal basic one is used, which just prints basic info.

To protect IPython from crashes, if your handler ever raises an exception or returns an invalid result, it will be immediately disabled.

Заметки

WARNING: by putting in your own exception handler into IPython’s main execution loop, you run a very good chance of nasty crashes. This facility should only be used if you really know what you are doing.

`set_hook(name, hook)` → sets an internal IPython hook.

IPython exposes some of its internal API as user-modifiable hooks. By adding your function to one of these hooks, you can modify IPython’s behavior to call at runtime your own routines.

`set_next_input(s, replace=False)`

Sets the „default“ input string for the next command line.

Example:

```
In [1]: _ip.set_next_input("Hello Word")  
In [2]: Hello Word_   # cursor is here
```

`should_run_async(raw_cell: str, *, transformed_cell=None, preprocessing_exc_tuple=None) → bool`

Return whether a cell should be run asynchronously via a coroutine runner

Параметры

`raw_cell` (*str*) – The code to be executed

Результат

- **result** (*bool*) – Whether the code needs to be run with a coroutine runner or not
- .. *versionadded:: 7.0*

`show_rewritten_input`

Show rewritten input, e.g. for autocall.

`show_usage()`

Show a usage message

`show_usage_error(exc)`

Show a short message for UsageErrors

These are special exceptions that shouldn't show a traceback.

`showindentationerror()`

Called by `_run_cell` when there's an IndentationError in code entered at the prompt.

This is overridden in TerminalInteractiveShell to show a message about the `%paste` magic.

`showsyntaxerror(filename=None, running_compiled_code=False)`

Display the syntax error that just occurred.

This doesn't display a stack trace because there isn't one.

If a filename is given, it is stuffed in the exception instead of what was there before (because Python's parser always uses `<<string>>` when reading from a string).

If the syntax error occurred when running a compiled code (i.e. `running_compile_code=True`), longer stack trace will be displayed.

`showtraceback(exc_tuple=None, filename=None, tb_offset=None, exception_only=False, running_compiled_code=False)`

Display the exception that just occurred.

If nothing is known about the exception, this is the method which should be used throughout the code for presenting user tracebacks, rather than directly invoking the InteractiveTB object.

A specific `showsyntaxerror()` also exists, but this method can take care of calling it if needed, so unless you are explicitly catching a SyntaxError exception, don't try to analyze the stack manually and simply call this method.

`sphinxify_docstring`

Enables rich html representation of docstrings. (This requires the `docrepr` module).

`system(cmd)`

Call the given `cmd` in a subprocess, piping stdout/err

Параметры

`cmd` (*str*) – Command to execute (can not end in `„&“`, as background processes are not supported. Should not be a command that expects input other than simple text.

`system_piped(cmd)`

Call the given `cmd` in a subprocess, piping stdout/err

Параметры

`cmd` (*str*) – Command to execute (can not end in `„&“`, as background processes are not supported. Should not be a command that expects input other than simple text.

`system_raw(cmd)`

Call the given `cmd` in a subprocess using `os.system` on Windows or `subprocess.call` using the system shell on other platforms.

Параметры

`cmd` (*str*) – Command to execute.

`transform_ast(node)`

Apply the AST transformations from `self.ast_transformers`

Параметры

`node` (*ast.Node*) – The root node to be transformed. Typically called with the `ast.Module` produced by parsing user input.

Результат

- *An ast.Node corresponding to the node it was called with. Note that it*
- *may also modify the passed object, so don't rely on references to the*
- *original AST.*

`transform_cell(raw_cell)`

Transform an input cell before parsing it.

Static transformations, implemented in `IPython.core.inputtransformer2`, deal with things like `%magic` and `!system` commands. These run on all input. Dynamic transformations, for things like unescaped magics and the exit autocall, depend on the state of the interpreter. These only apply to single line inputs.

These string-based transformations are followed by AST transformations; see [`transform_ast\(\)`](#).

`user_expressions(expressions)`

Evaluate a dict of expressions in the user's namespace.

Параметры

`expressions` (*dict*) – A dict with string keys and string values. The expression values should be valid Python expressions, each of which will be evaluated in the user namespace.

Результат

- *A dict, keyed like the input expressions dict, with the rich mime-typed*
- *display_data of each value.*

`var_expand(cmd, depth=0, formatter=<DollarFormatter>)`

Expand python variables in a string.

The `depth` argument indicates how many frames above the caller should be walked to look for the local namespace where to expand variables.

The global namespace for expansion is always the user's interactive namespace.

`warn_venv`

Warn if running in a virtual environment with no IPython installed (so IPython from the global environment is used).

`xmode`

Switch modes for the IPython exception handlers.

`class IPython.core.interactiveshell.InteractiveShellABC`

Базовые классы: `object`

An abstract base class for `InteractiveShell`.

8.25.2 2 Functions

`IPython.core.interactiveshell.sphinxify(oinfo)`

`IPython.core.interactiveshell.is_integer_string(s: str)`

Variant of «`str.isnumeric()`» that allow negative values and other ints.

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

8.26 Module: `core.logger`

Logger class for IPython's logging facilities.

8.26.1 1 Class

`class IPython.core.logger.Logger(home_dir, logfname='Logger.log', loghead='', logmode='over')`

Базовые классы: `object`

A Logfile class with different policies for file creation

`__init__`(*home_dir*, *logfname*='Logger.log', *loghead*='', *logmode*='over')

`close_log()`

Fully stop logging and close log file.

In order to start logging again, a new `logstart()` call needs to be made, possibly (though not necessarily) with a new filename, mode and other options.

`log(line_mod, line_ori)`

Write the sources to a log.

Inputs:

- `line_mod`: possibly modified input, such as the transformations made by input prefilters or input handlers of various kinds. This should always be valid Python.
- `line_ori`: unmodified input line from the user. This is not necessarily valid Python.

`log_write(data, kind='input')`

Write data to the log file, if active

`logstart(logfname=None, loghead=None, logmode=None, log_output=False, timestamp=False, log_raw_input=False)`

Generate a new log-file with a default header.

Raises `RuntimeError` if the log has already been started

`logstate()`

Print a status message about the logger.

`logstop()`

Fully stop logging and close log file.

In order to start logging again, a new `logstart()` call needs to be made, possibly (though not necessarily) with a new filename, mode and other options.

`switch_log(val)`

Switch logging on/off. `val` should be ONLY a boolean.

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

8.27 Module: `core.macro`

Support for interactive macros in IPython

8.27.1 1 Class

`class IPython.core.macro.Macro(code)`

Базовые классы: `object`

Simple class to store the value of macros as strings.

Macro is just a callable that executes a string of IPython input when called.

`__init__(code)`

store the macro value, as a single string which can be executed

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

8.28 Module: `core.magic`

Magic functions for InteractiveShell.

8.28.1 4 Classes

`class IPython.core.magic.Bunch`

Базовые классы: `object`

`class IPython.core.magic.MagicsManager(**kwargs: Any)`

Базовые классы: `Configurable`

Object that handles all magic-related functionality for IPython.

`__init__(shell=None, config=None, user_magics=None, **traits)`

Create a configurable given a config config.

Параметры

- `config (Config)` – If this is empty, default values are used. If config is a `Config` instance, it will be used to configure the instance.
- `parent (Configurable instance, optional)` – The parent `Configurable` instance of this object.

Заметки

Subclasses of `Configurable` must call the `__init__()` method of `Configurable` *before* doing anything else and using `super()`:

```
class MyConfigurable(Configurable):
    def __init__(self, config=None):
        super(MyConfigurable, self).__init__(config=config)
        # Then any other code you need to finish initialization.
```

This ensures that instances will be configured properly.

`auto_magic`

Automatically call line magics without requiring explicit `%` prefix

`auto_status()`

Return descriptive string with automagic status.

`lazy_magics`

Mapping from magic names to modules to load.

This can be used in IPython/IPykernel configuration to declare lazy magics that will only be imported/registered on first use.

For example:

```
c.MagicsManager.lazy_magics = {
    "my_magic": "slow.to.import",
    "my_other_magic": "also.slow",
}
```

On first invocation of `%my_magic`, `%%my_magic`, `%%my_other_magic` or `%%my_other_magic`, the corresponding module will be loaded as an ipython extensions as if you had previously done `%load_ext ipython`.

Magics names should be without percent(s) as magics can be both cell and line magics.

Lazy loading happen relatively late in execution process, and complex extensions that manipulate Python/IPython internal state or global state might not support lazy loading.

`lsmagic()`

Return a dict of currently available magic functions.

The return dict has the keys „line“ and „cell“, corresponding to the two types of magics we support. Each value is a list of names.

`lsmagic_docs(brief=False, missing='')`

Return dict of documentation of magic functions.

The return dict has the keys „line“ and „cell“, corresponding to the two types of magics we support. Each value is a dict keyed by magic name whose value is the function docstring. If a docstring is unavailable, the value of `missing` is used instead.

If `brief` is `True`, only the first line of each docstring will be returned.

`register(*magic_objects)`

Register one or more instances of Magics.

Take one or more classes or instances of classes that subclass the main `core.Magic` class, and register them with IPython to use the magic functions they provide. The registration process will then ensure that any methods that have decorated to provide line and/or cell magics will be recognized with the `%x/%%x` syntax as a line/cell magic respectively.

If classes are given, they will be instantiated with the default constructor. If your classes need a custom constructor, you should instantiate them first and pass the instance.

The provided arguments can be an arbitrary mix of classes and instances.

Параметры

`*magic_objects` (*one or more classes or instances*) –

`register_alias(alias_name, magic_name, magic_kind='line', magic_params=None)`

Register an alias to a magic function.

The alias is an instance of `MagicAlias`, which holds the name and kind of the magic it should call. Binding is done at call time, so if the underlying magic function is changed the alias will call the new function.

Параметры

- `alias_name` (*str*) – The name of the magic to be registered.
- `magic_name` (*str*) – The name of an existing magic.
- `magic_kind` (*str*) – Kind of magic, one of „line“ or „cell“

`register_function(func, magic_kind='line', magic_name=None)`

Expose a standalone function as magic function for IPython.

This will create an IPython magic (line, cell or both) from a standalone function. The functions should have the following signatures:

- For line magics: `def f(line)`
- For cell magics: `def f(line, cell)`

- For a function that does both: `def f(line, cell=None)`

In the latter case, the function will be called with `cell==None` when invoked as `%f`, and with `cell` as a string when invoked as `%%f`.

Параметры

- `func` (*callable*) – Function to be registered as a magic.
- `magic_kind` (*str*) – Kind of magic, one of „line“, „cell“ or „line_cell“
- `magic_name` (*optional str*) – If given, the name the magic will have in the IPython namespace. By default, the name of the function itself is used.

`register_lazy(name: str, fully_qualified_name: str)`

Lazily register a magic via an extension.

Параметры

- `name` (*str*) – Name of the magic you wish to register.
- `fully_qualified_name` – Fully qualified name of the module/submodule that should be loaded as an extensions when the magic is first called. It is assumed that loading this extensions will register the given magic.

`class IPython.core.magic.Magics(**kwargs: Any)`

Базовые классы: `Configurable`

Base class for implementing magic functions.

Shell functions which can be reached as `%function_name`. All magic functions should accept a string, which they can parse for their own needs. This can make some functions easier to type, eg `%cd ../` vs. `%cd("../")`

Classes providing magic functions need to subclass this class, and they MUST:

- Use the method decorators `@line_magic` and `@cell_magic` to decorate individual methods as magic functions, AND
- Use the class decorator `@magics_class` to ensure that the magic methods are properly registered at the instance level upon instance initialization.

See `magic_functions` for examples of actual implementation classes.

`__init__(shell=None, **kwargs)`

Create a configurable given a config config.

Параметры

- `config` (*Config*) – If this is empty, default values are used. If config is a `Config` instance, it will be used to configure the instance.
- `parent` (*Configurable instance, optional*) – The parent `Configurable` instance of this object.

Заметки

Subclasses of `Configurable` must call the `__init__()` method of `Configurable` *before* doing anything else and using `super()`:

```
class MyConfigurable(Configurable):
    def __init__(self, config=None):
        super(MyConfigurable, self).__init__(config=config)
        # Then any other code you need to finish initialization.
```

This ensures that instances will be configured properly.

`arg_err(func)`

Print docstring if incorrect arguments were passed

`default_option(fn, optstr)`

Make an entry in the `options_table` for `fn`, with value `optstr`

`format_latex(string)`

Format a string for latex inclusion.

`parse_options(arg_str, opt_str, *long_opts, **kw)`

Parse options passed to an argument string.

The interface is similar to that of `getopt.getopt()`, but it returns a `Struct` with the options as keys and the stripped argument string still as a string.

`arg_str` is quoted as a true `sys.argv` vector by using `shlex.split`. This allows us to easily expand variables, glob files, quote arguments, etc.

Параметры

- `arg_str (str)` – The arguments to parse.
- `opt_str (str)` – The options specification.
- `mode (str, default 'string')` – If given as „list“, the argument string is returned as a list (split on whitespace) instead of a string.
- `list_all (bool, default False)` – Put all option values in lists. Normally only options appearing more than once are put in a list.
- `posix (bool, default True)` – Whether to split the input line in POSIX mode or not, as per the conventions outlined in the `shlex` module from the standard library.

```
class IPython.core.magic.MagicAlias(shell, magic_name, magic_kind, magic_params=None)
```

Базовые классы: `object`

An alias to another magic function.

An alias is determined by its magic name and magic kind. Lookup is done at call time, so if the underlying magic changes the alias will call the new function.

Use the `MagicsManager.register_alias()` method or the `%alias_magic` magic function to create and register a new alias.

```
__init__(shell, magic_name, magic_kind, magic_params=None)
```

8.28.2 8 Functions

`IPython.core.magic.on_off(tag)`

Return an ON/OFF string for a 1/0 input. Simple utility function.

`IPython.core.magic.compress_dhist(dh)`

Compress a directory history into a new one with at most 20 entries.

Return a new list made from the first and last 10 elements of dhist after removal of duplicates.

`IPython.core.magic.needs_local_scope(func)`

Decorator to mark magic functions which need to local scope to run.

`IPython.core.magic.magics_class(cls)`

Class decorator for all subclasses of the main Magics class.

Any class that subclasses Magics *must* also apply this decorator, to ensure that all the methods that have been decorated as line/cell magics get correctly registered in the class instance. This is necessary because when method decorators run, the class does not exist yet, so they temporarily store their information into a module global. Application of this class decorator copies that global data to the class instance and clears the global.

Obviously, this mechanism is not thread-safe, which means that the *creation* of subclasses of Magic should only be done in a single-thread context. Instantiation of the classes has no restrictions. Given that these classes are typically created at IPython startup time and before user application code becomes active, in practice this should not pose any problems.

`IPython.core.magic.record_magic(dct, magic_kind, magic_name, func)`

Utility function to store a function as a magic of a specific kind.

Параметры

- `dct` (*dict*) – A dictionary with „line“ and „cell“ subdicts.
- `magic_kind` (*str*) – Kind of magic to be stored.
- `magic_name` (*str*) – Key to store the magic as.
- `func` (*function*) – Callable object to store.

`IPython.core.magic.validate_type(magic_kind)`

Ensure that the given magic_kind is valid.

Check that the given magic_kind is one of the accepted spec types (stored in the global `magic_spec`), raise `ValueError` otherwise.

`IPython.core.magic.no_var_expand(magic_func)`

Mark a magic function as not needing variable expansion

By default, IPython interprets `{a}` or `$a` in the line passed to magics as variables that should be interpolated from the interactive namespace before passing the line to the magic function. This is not always desirable, e.g. when the magic executes Python code (`%timeit`, `%time`, etc.). Decorate magics with `@no_var_expand` to opt-out of variable expansion.

Добавлено в версии 7.3.

`IPython.core.magic.output_can_be_silenced(magic_func)`

Mark a magic function so its output may be silenced.

The output is silenced if the Python code used as a parameter of the magic ends in a semicolon, not counting a Python comment that can follow it.

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

8.29 Module: `core.magic_arguments`

A decorator-based method of constructing IPython magics with `argparse` option handling.

New magic functions can be defined like so:

```
from IPython.core.magic_arguments import (argument, magic_arguments,
    parse_argstring)

@magic_arguments()
@argument('-o', '--option', help='An optional argument.')
@argument('arg', type=int, help='An integer positional argument.')
def magic_cool(self, arg):
    """ A really cool magic command.

    """
    args = parse_argstring(magic_cool, arg)
    ...
```

The `@magic_arguments` decorator marks the function as having `argparse` arguments. The `@argument` decorator adds an argument using the same syntax as `argparse`'s `add_argument()` method. More sophisticated uses may also require the `@argument_group` or `@kwds` decorator to customize the formatting and the parsing.

Help text for the magic is automatically generated from the docstring and the arguments:

```
In[1]: %cool?
      %cool [-o OPTION] arg

      A really cool magic command.

      positional arguments:
        arg                An integer positional argument.

      optional arguments:
        -o OPTION, --option OPTION
                           An optional argument.
```

Here is an elaborated example that uses default parameters in `argument` and calls the `args` in the cell magic:

```

from IPython.core.magic import register_cell_magic
from IPython.core.magic_arguments import (argument, magic_arguments,
                                          parse_argstring)

@magic_arguments()
@argument(
    "--option",
    "-o",
    help="Add an option here"),
)
@argument(
    "--style",
    "-s",
    default="foo",
    help="Add some style arguments"),
)
@register_cell_magic
def my_cell_magic(line, cell):
    args = parse_argstring(my_cell_magic, line)
    print(f"{args.option=} ")
    print(f"{args.style=} ")
    print(f"{cell=} ")

```


In a jupyter notebook, this cell magic can be executed like this:

```

%%my_cell_magic -o Hello
print("bar")
i = 42

```

Inheritance diagram:



8.29.1 8 Classes

```
class IPython.core.magic_arguments.MagicArgumentParser(prog=None, usage=None,
                                                         description=None, epilog=None,
                                                         parents=None, formatter_class=<class
                                                         'IPython.core.magic_arguments.MagicHelpFormatter'>,
                                                         prefix_chars='-',
                                                         argument_default=None,
                                                         conflict_handler='error',
                                                         add_help=False)
```

Базовые классы: [ArgumentParser](#)

An ArgumentParser tweaked for use by IPython magics.

```
__init__(prog=None, usage=None, description=None, epilog=None, parents=None,
          formatter_class=<class 'IPython.core.magic_arguments.MagicHelpFormatter'>,
          prefix_chars='-', argument_default=None, conflict_handler='error', add_help=False)
```

`error(message)`

Raise a catchable error instead of exiting.

`parse_argstring(argstring)`

Split a string into an argument list and parse that argument list.

```
class IPython.core.magic_arguments.ArgDecorator
```

Базовые классы: [object](#)

Base class for decorators to add ArgumentParser information to a method.

`add_to_parser(parser, group)`

Add this object's information to the parser, if necessary.

```
class IPython.core.magic_arguments.magic_arguments(name=None)
```

Базовые классы: [ArgDecorator](#)

Mark the magic as having argparse arguments and possibly adjust the name.

```
__init__(name=None)
```

```
class IPython.core.magic_arguments.ArgMethodWrapper(*args, **kws)
```

Базовые классы: [ArgDecorator](#)

Base class to define a wrapper for ArgumentParser method.

Child class must define either `_method_name` or `add_to_parser`.

```
__init__(*args, **kws)
```

`add_to_parser(parser, group)`

Add this object's information to the parser.

```
class IPython.core.magic_arguments.argument(*args, **kws)
```

Базовые классы: [ArgMethodWrapper](#)

Store arguments and keywords to pass to `add_argument()`.

Instances also serve to decorate command methods.


```
class IPython.core.magic_arguments.defaults(*args, **kws)
    Базовые классы: ArgMethodWrapper

    Store arguments and keywords to pass to set_defaults().

    Instances also serve to decorate command methods.

class IPython.core.magic_arguments.argument_group(*args, **kws)
    Базовые классы: ArgMethodWrapper

    Store arguments and keywords to pass to add_argument_group().

    Instances also serve to decorate command methods.

    add_to_parser(parser, group)
        Add this object's information to the parser.

class IPython.core.magic_arguments.kwds(**kws)
    Базовые классы: ArgDecorator

    Provide other keywords to the sub-parser constructor.

    __init__(**kws)
```

8.29.2 3 Functions

```
IPython.core.magic_arguments.construct_parser(magic_func)
    Construct an argument parser using the function decorations.

IPython.core.magic_arguments.parse_argstring(magic_func, argstring)
    Parse the string of arguments for the given magic function.

IPython.core.magic_arguments.real_name(magic_func)
    Find the real name of the magic.
```

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7. If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

8.30 Module: `core.oinspect`

Tools for inspecting Python objects.

Uses syntax highlighting for presenting the various information elements.

Similar in spirit to the `inspect` module, but all calls take a name argument to reference the name under which an object is being read.

8.30.1 2 Classes

```
class IPython.core.oinspect.OInfo(ismagic: bool, isalias: bool, found: bool, namespace: Optional[str],
                                   parent: Any, obj: Any)
```

Базовые классы: `object`

`get(field)`

Get a field from the object for backward compatibility with before 8.12

see <https://github.com/h5py/h5py/issues/2253>

```
class IPython.core.oinspect.Inspector(**kwargs: Any)
```

Базовые классы: `Colorable`

```
__init__(color_table={'': <IPython.utils.coloransi.ColorScheme object>, 'LightBG':
<IPython.utils.coloransi.ColorScheme object>, 'Linux':
<IPython.utils.coloransi.ColorScheme object>, 'Neutral':
<IPython.utils.coloransi.ColorScheme object>, 'NoColor':
<IPython.utils.coloransi.ColorScheme object>}, code_color_table={'':
<IPython.utils.coloransi.ColorScheme object>, 'LightBG':
<IPython.utils.coloransi.ColorScheme object>, 'Linux':
<IPython.utils.coloransi.ColorScheme object>, 'Neutral':
<IPython.utils.coloransi.ColorScheme object>, 'NoColor':
<IPython.utils.coloransi.ColorScheme object>}, scheme=None, str_detail_level=0,
parent=None, config=None)
```

Create a configurable given a config config.

Параметры

- `config (Config)` – If this is empty, default values are used. If config is a `Config` instance, it will be used to configure the instance.
- `parent (Configurable instance, optional)` – The parent `Configurable` instance of this object.

Заметки

Subclasses of `Configurable` must call the `__init__()` method of `Configurable` *before* doing anything else and using `super()`:

```
class MyConfigurable(Configurable):
    def __init__(self, config=None):
        super(MyConfigurable, self).__init__(config=config)
        # Then any other code you need to finish initialization.
```

This ensures that instances will be configured properly.

`format_mime(bundle: Dict[str, List[Tuple[str, str]]]) → Dict[str, str]`

Format a mimebundle being created by `_make_info_unformatted` into a real mimebundle

`info(obj, oname='', info=None, detail_level=0) → Dict[str, Any]`

Compute a dict with detailed information about an object.

Параметры

- `obj` (*any*) – An object to find information about
- `oname` (*str* (`default: ''`)) – Name of the variable pointing to `obj`.
- `info` (*((default: None))*) – A struct (dict like with attr access) with some information fields which may have been precomputed already.
- `detail_level` (*int* (`default: 0`)) – If set to 1, more information is given.

Результат

- An object info dict with known fields from `info_fields`. Keys are
- *strings, values are string or None.*

`noinfo(msg, oname)`

Generic message when no information is found.

`pdef(obj, oname='')`

Print the call signature for any callable object.

If the object is a class, print the constructor information.

`pdoc(obj, oname='', formatter=None)`

Print the docstring for any object.

Optional: `-formatter`: a function to run the docstring through for specially formatted docstrings.

Примеры

In [1]: class NoInit:

...: pass

In [2]: class NoDoc:

...: def __init__(self): ...: pass

In [3]: %pdoc NoDoc No documentation found for NoDoc

In [4]: %pdoc NoInit No documentation found for NoInit

In [5]: obj = NoInit()

In [6]: %pdoc obj No documentation found for obj

In [5]: obj2 = NoDoc()

In [6]: %pdoc obj2 No documentation found for obj2

`pfile(obj, oname='')`

Show the whole file where an object was defined.

```
pinfo(obj, oname='', formatter=None, info: Optional[OInfo] = None, detail_level=0,
      enable_html_pager=True, omit_sections=())
```

Show detailed information about an object.

Optional arguments:

- **oname**: name of the variable pointing to the object.

- **formatter: callable (optional)**

A special formatter for docstrings.

The formatter is a callable that takes a string as an input and returns either a formatted string or a mime type bundle in the form of a dictionary.

Although the support of custom formatter returning a string instead of a mime type bundle is deprecated.

- **info**: a structure with some information fields which may have been precomputed already.
- **detail_level**: if set to 1, more information is given.
- **omit_sections**: set of section keys and titles to omit

```
psearch(pattern, ns_table, ns_search=[], ignore_case=False, show_all=False, *, list_types=False)
```

Search namespaces with wildcards for objects.

Arguments:

- **pattern**: string containing shell-like wildcards to use in namespace searches and optionally a type specification to narrow the search to objects of that type.
- **ns_table**: dict of name->namespaces for search.

Optional arguments:

- **ns_search**: list of namespace names to include in search.
- **ignore_case(False)**: make the search case-insensitive.
- **show_all(False)**: show all names, including those starting with underscores.
- **list_types(False)**: list all available object types for object matching.

```
psource(obj, oname='')
```

Print the source code for an object.

8.30.2 8 Functions

```
IPython.core.oinspect.pylight(code)
```

```
IPython.core.oinspect.object_info(**kw)
```

Make an object info dict with all fields present.

```
IPython.core.oinspect.get_encoding(obj)
```

Get encoding for python source file defining obj

Returns None if obj is not defined in a sourcefile.

`IPython.core.oinspect.getdoc(obj) → Optional[str]`

Stable wrapper around `inspect.getdoc`.

This can't crash because of attribute problems.

It also attempts to call a `getdoc()` method on the given object. This allows objects which provide their docstrings via non-standard mechanisms (like Pyro proxies) to still be inspected by `ipython's ?` system.

`IPython.core.oinspect.getsource(obj, oname='') → Optional[str]`

Wrapper around `inspect.getsource`.

This can be modified by other projects to provide customized source extraction.

Параметры

- `obj` (*object*) – an object whose source code we will attempt to extract
- `oname` (*str*) – (optional) a name under which the object is known

Результат

`src`

Тип результата

unicode or None

`IPython.core.oinspect.is_simple_callable(obj)`

True if `obj` is a function ()

`IPython.core.oinspect.find_file(obj) → str`

Find the absolute path to the file where an object was defined.

This is essentially a robust wrapper around `inspect.getabsfile`.

Returns None if no file can be found.

Параметры

`obj` (*any Python object*) –

Результат

`fname` – The absolute path to the file where the object was defined.

Тип результата

`str`

`IPython.core.oinspect.find_source_lines(obj)`

Find the line number in a file where an object was defined.

This is essentially a robust wrapper around `inspect.getsourcelines`.

Returns None if no file can be found.

Параметры

`obj` (*any Python object*) –

Результат

`lineno` – The line number where the object definition starts.

Тип результата

`int`

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

8.31 Module: `core.page`

Paging capabilities for IPython.core

Заметки

For now this uses IPython hooks, so it can't be in IPython.utils. If we can get rid of that dependency, we could move it there. —

8.31.1 9 Functions

`IPython.core.page.display_page(strng, start=0, screen_lines=25)`

Just display, no paging. `screen_lines` is ignored.

`IPython.core.page.as_hook(page_func)`

Wrap a pager func to strip the `self` arg

so it can be called as a hook.

`IPython.core.page.page_dumb(strng, start=0, screen_lines=25)`

Very dumb „pager“ in Python, for when nothing else works.

Only moves forward, same interface as `page()`, except for `pager_cmd` and `mode`.

`IPython.core.page.pager_page(strng, start=0, screen_lines=0, pager_cmd=None)`

Display a string, piping through a pager after a certain length.

`strng` can be a mime-bundle dict, supplying multiple representations, keyed by mime-type.

The `screen_lines` parameter specifies the number of *usable* lines of your terminal screen (total lines minus lines you need to reserve to show other information).

If you set `screen_lines` to a number ≤ 0 , `page()` will try to auto-determine your screen size and will only use up to $(\text{screen_size} + \text{screen_lines})$ for printing, paging after that. That is, if you want auto-detection but need to reserve the bottom 3 lines of the screen, use `screen_lines = -3`, and for auto-detection without any lines reserved simply use `screen_lines = 0`.

If a string won't fit in the allowed lines, it is sent through the specified pager command. If none given, look for `PAGER` in the environment, and ultimately default to `less`.

If no system pager works, the string is sent through a „dumb pager“ written in python, very simplistic.

`IPython.core.page.page(data, start=0, screen_lines=0, pager_cmd=None)`

Display content in a pager, piping through a pager after a certain length.

`data` can be a mime-bundle dict, supplying multiple representations, keyed by mime-type, or text.

Pager is dispatched via the `show_in_pager` IPython hook. If no hook is registered, `pager_page` will be used.

`IPython.core.page.page_file(fname, start=0, pager_cmd=None)`

Page a file, using an optional pager command and starting line.

`IPython.core.page.get_pager_cmd(pager_cmd=None)`

Return a pager command.

Makes some attempts at finding an OS-correct one.

`IPython.core.page.get_pager_start(pager, start)`

Return the string for paging files with an offset.

This is the „+N“ argument which less and more (under Unix) accept.

`IPython.core.page.page_more()`

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

8.32 Module: `core.payload`

Payload system for IPython.

Authors:

- Fernando Perez
- Brian Granger

8.32.1 1 Class

`class IPython.core.payload.PayloadManager(**kwargs: Any)`

Базовые классы: `Configurable`

`write_payload(data, single=True)`

Include or update the specified `data` payload in the `PayloadManager`.

If a previous payload with the same source exists and `single` is `True`, it will be overwritten with the new one.

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

8.33 Module: `core.payloadpage`

A payload based version of `page`.

8.33.1 2 Functions

`IPython.core.payloadpage.page(strng, start=0, screen_lines=0, pager_cmd=None)`

Print a string, piping through a pager.

This version ignores the `screen_lines` and `pager_cmd` arguments and uses IPython's payload system instead.

Параметры

- `strng` (*str* or *mime-dict*) – Text to page, or a mime-type keyed dict of already formatted data.
- `start` (*int*) – Starting line at which to place the display.

`IPython.core.payloadpage.install_payload_page()`

DEPRECATED, use `show_in_pager` hook

Install this version of `page` as `IPython.core.page.page`.

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

8.34 Module: `core.prefilter`

Prefiltering components.

Prefilters transform user input before it is exec'd by Python. These transforms are used to implement additional syntax such as `!ls` and `%magic`.

8.34.1 16 Classes

`class IPython.core.prefilter.PrefilterError`

Базовые классы: `Exception`

`class IPython.core.prefilter.PrefilterManager(**kwargs: Any)`

Базовые классы: `Configurable`

Main prefilter component.

The IPython prefilter is run on all user input before it is run. The prefilter consumes lines of input and produces transformed lines of input.

The implementation consists of two phases:

1. Transformers
2. Checkers and handlers

Over time, we plan on deprecating the checkers and handlers and doing everything in the transformers.

The transformers are instances of `PrefilterTransformer` and have a single method `transform()` that takes a line and returns a transformed line. The transformation can be accomplished using any tool, but our current ones use regular expressions for speed.

After all the transformers have been run, the line is fed to the checkers, which are instances of `PrefilterChecker`. The line is passed to the `check()` method, which either returns `None` or a `PrefilterHandler` instance. If `None` is returned, the other checkers are tried. If an `PrefilterHandler` instance is returned, the line is passed to the `handle()` method of the returned handler and no further checkers are tried.

Both transformers and checkers have a `priority` attribute, that determines the order in which they are called. Smaller priorities are tried first.

Both transformers and checkers also have `enabled` attribute, which is a boolean that determines if the instance is used.

Users or developers can change the priority or enabled attribute of transformers or checkers, but they must call the `sort_checkers()` or `sort_transformers()` method after changing the priority.

`__init__(shell=None, **kwargs)`

Create a configurable given a config config.

Параметры

- `config (Config)` – If this is empty, default values are used. If config is a `Config` instance, it will be used to configure the instance.
- `parent (Configurable instance, optional)` – The parent `Configurable` instance of this object.

Заметки

Subclasses of Configurable must call the `__init__()` method of Configurable *before* doing anything else and using `super()`:

```
class MyConfigurable(Configurable):
    def __init__(self, config=None):
        super(MyConfigurable, self).__init__(config=config)
        # Then any other code you need to finish initialization.
```

This ensures that instances will be configured properly.

property checkers

Return a list of checkers, sorted by priority.

find_handler(line_info)

Find a handler for the line_info by trying checkers.

get_handler_by_esc(esc_str)

Get a handler by its escape string.

get_handler_by_name(name)

Get a handler by its name.

property handlers

Return a dict of all the handlers.

init_checkers()

Create the default checkers.

init_handlers()

Create the default handlers.

prefilter_line(line, continue_prompt=False)

Prefilter a single input line as text.

This method prefilters a single line of text by calling the transformers and then the checkers/handlers.

prefilter_line_info(line_info)

Prefilter a line that has been converted to a LineInfo object.

This implements the checker/handler part of the prefilter pipe.

prefilter_lines(lines, continue_prompt=False)

Prefilter multiple input lines of text.

This is the main entry point for prefiltering multiple lines of input. This simply calls `prefilter_line()` for each line of input.

This covers cases where there are multiple lines in the user entry, which is the case when the user goes back to a multiline history entry and presses enter.

register_checker(checker)

Register a checker instance.

register_handler(name, handler, esc_strings)

Register a handler instance by name with esc_strings.

`register_transformer(transformer)`

Register a transformer instance.

`sort_checkers()`

Sort the checkers by priority.

This must be called after the priority of a checker is changed. The `register_checker()` method calls this automatically.

`sort_transformers()`

Sort the transformers by priority.

This must be called after the priority of a transformer is changed. The `register_transformer()` method calls this automatically.

`transform_line(line, continue_prompt)`

Calls the enabled transformers in order of increasing priority.

property `transformers`

Return a list of checkers, sorted by priority.

`unregister_checker(checker)`

Unregister a checker instance.

`unregister_handler(name, handler, esc_strings)`

Unregister a handler instance by name with `esc_strings`.

`unregister_transformer(transformer)`

Unregister a transformer instance.

`class IPython.core.prefilter.PrefilterTransformer(**kwargs: Any)`

Базовые классы: `Configurable`

Transform a line of user input.

`__init__(shell=None, prefilter_manager=None, **kwargs)`

Create a configurable given a config config.

Параметры

- `config (Config)` – If this is empty, default values are used. If config is a `Config` instance, it will be used to configure the instance.
- `parent (Configurable instance, optional)` – The parent `Configurable` instance of this object.

Заметки

Subclasses of `Configurable` must call the `__init__()` method of `Configurable` *before* doing anything else and using `super()`:

```
class MyConfigurable(Configurable):
    def __init__(self, config=None):
        super(MyConfigurable, self).__init__(config=config)
        # Then any other code you need to finish initialization.
```

This ensures that instances will be configured properly.

```
transform(line, continue_prompt)
```

Transform a line, returning the new one.

```
class IPython.core.prefilter.PrefilterChecker(**kwargs: Any)
```

Базовые классы: [Configurable](#)

Inspect an input line and return a handler for that line.

```
__init__(shell=None, prefilter_manager=None, **kwargs)
```

Create a configurable given a config config.

Параметры

- `config` (*Config*) – If this is empty, default values are used. If config is a `Config` instance, it will be used to configure the instance.
- `parent` (*Configurable instance, optional*) – The parent `Configurable` instance of this object.

Заметки

Subclasses of `Configurable` must call the `__init__()` method of `Configurable` *before* doing anything else and using `super()`:

```
class MyConfigurable(Configurable):
    def __init__(self, config=None):
        super(MyConfigurable, self).__init__(config=config)
        # Then any other code you need to finish initialization.
```

This ensures that instances will be configured properly.

```
check(line_info)
```

Inspect `line_info` and return a handler instance or `None`.

```
class IPython.core.prefilter.EmacsChecker(**kwargs: Any)
```

Базовые классы: [PrefilterChecker](#)

```
check(line_info)
```

Emacs ipython-mode tags certain input lines.

```
class IPython.core.prefilter.MacroChecker(**kwargs: Any)
```

Базовые классы: [PrefilterChecker](#)

```
check(line_info)
```

Inspect `line_info` and return a handler instance or `None`.

```
class IPython.core.prefilter.IPyAutocallChecker(**kwargs: Any)
```

Базовые классы: [PrefilterChecker](#)

```
check(line_info)
```

Instances of `IPyAutocall` in `user_ns` get autocalled immediately

```
class IPython.core.prefilter.AssignmentChecker(**kwargs: Any)
```

Базовые классы: [PrefilterChecker](#)

`check(line_info)`

Check to see if user is assigning to a var for the first time, in which case we want to avoid any sort of automagic / autocall games.

This allows users to assign to either alias or magic names true python variables (the magic/alias systems always take second seat to true python code). E.g. `ls="hi"`, or `ls,that=1,2`

`class IPython.core.prefilter.AutoMagicChecker(**kwargs: Any)`

Базовые классы: *PrefilterChecker*

`check(line_info)`

If the ifun is magic, and automagic is on, run it. Note: normal, non-auto magic would already have been triggered via „%“ in `check_esc_chars`. This just checks for automagic. Also, before triggering the magic handler, make sure that there is nothing in the user namespace which could shadow it.

`class IPython.core.prefilter.PythonOpsChecker(**kwargs: Any)`

Базовые классы: *PrefilterChecker*

`check(line_info)`

If the „rest“ of the line begins with a function call or pretty much any python operator, we should simply execute the line (regardless of whether or not there's a possible autocall expansion). This avoids spurious (and very confusing) `getattr()` accesses.

`class IPython.core.prefilter.AutocallChecker(**kwargs: Any)`

Базовые классы: *PrefilterChecker*

`check(line_info)`

Check if the initial word/function is callable and autocall is on.

`exclude_regexp`

RegExp to exclude strings with this start from autocalling.

`function_name_regexp`

RegExp to identify potential function names.

`class IPython.core.prefilter.PrefilterHandler(**kwargs: Any)`

Базовые классы: *Configurable*

`__init__(shell=None, prefilter_manager=None, **kwargs)`

Create a configurable given a config config.

Параметры

- `config (Config)` – If this is empty, default values are used. If config is a *Config* instance, it will be used to configure the instance.
- `parent (Configurable instance, optional)` – The parent *Configurable* instance of this object.

Заметки

Subclasses of `Configurable` must call the `__init__()` method of `Configurable` *before* doing anything else and using `super()`:

```
class MyConfigurable(Configurable):
    def __init__(self, config=None):
        super(MyConfigurable, self).__init__(config=config)
        # Then any other code you need to finish initialization.
```

This ensures that instances will be configured properly.

`handle(line_info)`

Handle normal input lines. Use as a template for handlers.

```
class IPython.core.prefilter.MacroHandler(**kwargs: Any)
```

Базовые классы: `PrefilterHandler`

`handle(line_info)`

Handle normal input lines. Use as a template for handlers.

```
class IPython.core.prefilter.MagicHandler(**kwargs: Any)
```

Базовые классы: `PrefilterHandler`

`handle(line_info)`

Execute magic functions.

```
class IPython.core.prefilter.AutoHandler(**kwargs: Any)
```

Базовые классы: `PrefilterHandler`

`handle(line_info)`

Handle lines which can be auto-executed, quoting if requested.

```
class IPython.core.prefilter.EmacsHandler(**kwargs: Any)
```

Базовые классы: `PrefilterHandler`

`handle(line_info)`

Handle input lines marked by python-mode.

8.34.2 1 Function

```
IPython.core.prefilter.is_shadowed(identifier, ip)
```

Is the given identifier defined in one of the namespaces which shadow the alias and magic namespaces?

Note that an identifier is different than ifun, because it can not contain a „“ character.

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

8.35 Module: `core.profileapp`

An application for managing IPython profiles.

To be invoked as the `ipython profile` subcommand.

Authors:

- Min RK

8.35.1 4 Classes

```
class IPython.core.profileapp.ProfileLocate(**kwargs: Any)
```

Базовые классы: `BaseIPythonApplication`

`parse_command_line(argv=None)`

Parse the command line arguments.

`start()`

Start the app mainloop.

Override in subclasses.

```
class IPython.core.profileapp.ProfileList(**kwargs: Any)
```

Базовые классы: `Application`

`ipython_dir`

The name of the IPython directory. This directory is used for logging configuration (through profiles), history storage, etc. The default is usually `$HOME/.ipython`. This options can also be specified through the environment variable `IPYTHONDIR`.

`start()`

Start the app mainloop.

Override in subclasses.

```
class IPython.core.profileapp.ProfileCreate(**kwargs: Any)
```

Базовые классы: `BaseIPythonApplication`

`init_config_files()`

[optionally] copy default config files into profile dir.

`parallel`

whether to include parallel computing config files

`parse_command_line(argv)`

Parse the command line arguments.

`stage_default_config_file()`

auto generate default config file, and stage it into the profile.

```
class IPython.core.profileapp.ProfileApp(**kwargs: Any)
```

Базовые классы: `Application`

`start()`

Start the app mainloop.

Override in subclasses.

8.35.2 2 Functions

`IPython.core.profileapp.list_profiles_in(path)`

list profiles in a given root directory

`IPython.core.profileapp.list_bundled_profiles()`

list profiles that are bundled with IPython.

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

8.36 Module: `core.profiledir`

An object for managing IPython profile directories.

8.36.1 2 Classes

`class IPython.core.profiledir.ProfileDirError`

Базовые классы: `Exception`

`class IPython.core.profiledir.ProfileDir(**kwargs: Any)`

Базовые классы: `LoggingConfigurable`

An object to manage the profile directory and its resources.

The profile directory is used by all IPython applications, to manage configuration, logging and security.

This object knows how to find, create and manage these directories. This should be used by any code that wants to handle profiles.

`copy_config_file(config_file: str, path: Path, overwrite=False) → bool`

Copy a default config file into the active profile directory.

Default configuration files are kept in `IPython.core.profile`. This function moves these from that location to the working profile directory.

`classmethod create_profile_dir(profile_dir, config=None)`

Create a new profile directory given a full path.

Параметры

`profile_dir (str)` – The full path to the profile directory. If it does exist, it will be used. If not, it will be created.


```
classmethod create_profile_dir_by_name(path, name='default', config=None)
```

Create a profile dir by profile name and path.

Параметры

- `path` (*unicode*) – The path (directory) to put the profile directory in.
- `name` (*unicode*) – The name of the profile. The name of the profile directory will be «profile_<profile>».

```
classmethod find_profile_dir(profile_dir, config=None)
```

Find/create a profile dir and return its ProfileDir.

This will create the profile directory if it doesn't exist.

Параметры

`profile_dir` (*unicode or str*) – The path of the profile directory.

```
classmethod find_profile_dir_by_name(ipython_dir, name='default', config=None)
```

Find an existing profile dir by profile name, return its ProfileDir.

This searches through a sequence of paths for a profile dir. If it is not found, a *ProfileDirError* exception will be raised.

The search path algorithm is: 1. `os.getcwd()` # removed for security reason. 2. `ipython_dir`

Параметры

- `ipython_dir` (*unicode or str*) – The IPython directory to use.
- `name` (*unicode or str*) – The name of the profile. The name of the profile directory will be «profile_<profile>».

`location`

Set the profile location directly. This overrides the logic used by the `profile` option.

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

8.37 Module: `core.prompts`

Being removed

8.37.1 1 Class

```
class IPython.core.prompts.LazyEvaluate(func, *args, **kwargs)
```

Базовые классы: `object`

This is used for formatting strings with values that need to be updated at that time, such as the current time or working directory.

```
__init__(func, *args, **kwargs)
```

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

8.38 Module: `core.pylabtools`

Pylab (matplotlib) support utilities.

8.38.1 10 Functions

```
IPython.core.pylabtools.getfigs(*fig_nums)
```

Get a list of matplotlib figures by figure numbers.

If no arguments are given, all available figures are returned. If the argument list contains references to invalid figures, a warning is printed but the function continues pasting further figures.

Параметры

`figs (tuple)` – A tuple of ints giving the figure numbers of the figures to return.

```
IPython.core.pylabtools.figure(figsize=(size_x, size_y))
```

Set the default figure size to be [size_x, size_y].

This is just an easy to remember, convenience wrapper that sets:

```
matplotlib.rcParams['figure.figsize'] = [size_x, size_y]
```

```
IPython.core.pylabtools.print_figure(fig, fmt='png', bbox_inches='tight', base64=False, **kwargs)
```

Print a figure to an image, and return the resulting file data

Returned data will be bytes unless `fmt='svg'`, in which case it will be unicode.

Any keyword args are passed to `fig.canvas.print_figure`, such as `quality` or `bbox_inches`.

If `base64` is True, return base64-encoded str instead of raw bytes for binary-encoded image formats

Добавлено в версии 7.29: `base64` argument

`IPython.core.pylabtools.retina_figure(fig, base64=False, **kwargs)`

format a figure as a pixel-doubled (retina) PNG

If `base64` is `True`, return base64-encoded str instead of raw bytes for binary-encoded image formats

Добавлено в версии 7.29: `base64` argument

`IPython.core.pylabtools.mpl_runner(safe_execfile)`

Factory to return a matplotlib-enabled runner for `%run`.

Параметры

`safe_execfile` (*function*) – This must be a function with the same interface as the `safe_execfile()` method of IPython.

Результат

- A function suitable for use as the `runner` argument of the `%run` magic
- *function*.

`IPython.core.pylabtools.select_figure_formats(shell, formats, **kwargs)`

Select figure formats for the inline backend.

Параметры

- `shell` (`InteractiveShell`) – The main IPython instance.
- `formats` (*str or set*) – One or a set of figure formats to enable: „png“, „retina“, „jpeg“, „svg“, „pdf“.
- `**kwargs` (*any*) – Extra keyword arguments to be passed to `fig.canvas.print_figure`.

`IPython.core.pylabtools.find_gui_and_backend(gui=None, gui_select=None)`

Given a gui string return the gui and mpl backend.

Параметры

- `gui` (*str*) – Can be one of („tk“, „gtk“, „wx“, „qt“, „qt4“, „inline“, „agg“).
- `gui_select` (*str*) – Can be one of („tk“, „gtk“, „wx“, „qt“, „qt4“, „inline“). This is any gui already selected by the shell.

Результат

- A tuple of (*gui*, *backend*) where *backend* is one of („TkAgg“, „GTKAgg“, „WXAgg“, „Qt4Agg“, „module (//matplotlib_inline.backend_inline“, „agg“).

`IPython.core.pylabtools.activate_matplotlib(backend)`

Activate the given backend and set interactive to `True`.

`IPython.core.pylabtools.import_pylab(user_ns, import_all=True)`

Populate the namespace with pylab-related values.

Imports matplotlib, pylab, numpy, and everything from pylab and numpy.

Also imports a few names from IPython (figsize, display, getfigs)

`IPython.core.pylabtools.configure_inline_support(shell, backend)`

Не рекомендуется, начиная с версии 7.23: use `matplotlib_inline.backend_inline.configure_inline_support()`

Configure an IPython shell object for matplotlib use.

Параметры

- `shell` (*InteractiveShell instance*) –
- `backend` (*matplotlib backend*) –

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

8.39 Module: `core.shellapp`

A mixin for `Application` classes that launch `InteractiveShell` instances, load extensions, etc.

8.39.1 1 Class

`class IPython.core.shellapp.InteractiveShellApp(**kwargs: Any)`

Базовые классы: `Configurable`

A Mixin for applications that start `InteractiveShell` instances.

Provides configurables for loading extensions and executing files as part of configuring a Shell environment.

The following methods should be called by the `initialize()` method of the subclass:

- `init_path()`
- `init_shell()` (to be implemented by the subclass)
- `init_gui_pylab()`
- `init_extensions()`
- `init_code()`

`code_to_run`

Execute the given command string.

`exec_PYTHONSTARTUP`

Run the file referenced by the `PYTHONSTARTUP` environment variable at IPython startup.

`exec_files`

List of files to run at IPython startup.

`exec_lines`

lines of code to run at IPython startup.

`extensions`

A list of dotted module names of IPython extensions to load.

extra_extensions

Dotted module name(s) of one or more IPython extensions to load.

For specifying extra extensions to load on the command-line.

Добавлено в версии 7.10.

file_to_run

A file to be run

gui

Enable GUI event loop integration with any of („asyncio“, „glut“, „gtk“, „gtk2“, „gtk3“, „gtk4“, „osx“, „pyglet“, „qt“, „qt5“, „qt6“, „tk“, „wx“, „gtk2“, „qt4“).

hide_initial_ns

Should variables loaded at startup (by startup files, `exec_lines`, etc.) be hidden from tools like `%who`?

ignore_cwd

If True, IPython will not add the current working directory to `sys.path`. When False, the current working directory is added to `sys.path`, allowing imports of modules defined in the current directory.

init_code()

run the pre-flight code, specified via `exec_lines`

init_extensions()

Load all IPython extensions in `IPythonApp.extensions`.

This uses the `ExtensionManager.load_extensions()` to load all the extensions listed in `self.extensions`.

init_gui_pylab()

Enable GUI event loop integration, taking pylab into account.

init_path()

Add current working directory, „“, to `sys.path`

Unlike Python’s default, we insert before the first `site-packages` or `dist-packages` directory, so that it is after the standard library.

Изменено в версии 7.2: Try to insert after the standard library, instead of first.

Изменено в версии 8.0: Allow optionally not including the current directory in `sys.path`

matplotlib

Configure matplotlib for interactive use with the default matplotlib backend.

module_to_run

Run the module as a script.

pylab

Pre-load matplotlib and numpy for interactive use, selecting a particular matplotlib backend and loop integration.

pylab_import_all

If true, IPython will populate the user namespace with numpy, pylab, etc. and an `import *` is done from numpy and pylab, when using pylab mode.

When False, pylab mode should not import any names into the user namespace.

```
reraise_ipython_extension_failures
```

Reraise exceptions encountered loading IPython extensions?

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

8.40 Module: `core.splitinput`

Simple utility for splitting user input. This is used by both `inputsplitter` and `prefilter`.

Authors:

- Brian Granger
- Fernando Perez

8.40.1 1 Class

```
class IPython.core.splitinput.LineInfo(line, continue_prompt=False)
```

Базовые классы: `object`

A single line of input and associated info.

Includes the following as properties:

line

The original, raw line

continue_prompt

Is this line a continuation in a sequence of multiline input?

pre

Any leading whitespace.

esc

The escape character(s) in pre or the empty string if there isn't one. Note that „!!“ and „??“ are possible values for esc. Otherwise it will always be a single character.

ifun

The „function part“, which is basically the maximal initial sequence of valid python identifiers and the „“ character. This is what is checked for alias and magic transformations, used for auto-calling, etc. In contrast to Python identifiers, it may start with «%» and contain «*».

the_rest

Everything else on the line.

```
__init__(line, continue_prompt=False)
```

`ofind(ip) → OInfo`

Do a full, attribute-walking lookup of the ifun in the various namespaces for the given IPython InteractiveShell instance.

Return a dict with keys: {found, obj, ospace, ismagic}

Note: can cause state changes because of calling getattr, but should only be run if autocall is on and if the line hasn't matched any other, less dangerous handlers.

Does cache the results of the call, so can be called multiple times without worrying about *further* damaging state.

8.40.2 1 Function

`IPython.core.splitinput.split_user_input(line, pattern=None)`

Split user input into initial whitespace, escape character, function part and the rest.

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

8.41 Module: `core.ultratb`

Verbose and colourful traceback formatting.

ColorTB

I've always found it a bit hard to visually parse tracebacks in Python. The ColorTB class is a solution to that problem. It colors the different parts of a traceback in a manner similar to what you would expect from a syntax-highlighting text editor.

Installation instructions for ColorTB:

```
import sys,ultratb
sys.excepthook = ultratb.ColorTB()
```

VerboseTB

I've also included a port of Ka-Ping Yee's «cgitb.py» that produces all kinds of useful info when a traceback occurs. Ping originally had it spit out HTML and intended it for CGI programmers, but why should they have all the fun? I altered it to spit out colored text to the terminal. It's a bit overwhelming, but kind of neat, and maybe useful for long-running programs that you believe are bug-free. If a crash *does* occur in that type of program you want details. Give it a shot—you'll love it or you'll hate it.

Примечание: The Verbose mode prints the variables currently visible where the exception happened (shortening their strings if too long). This can potentially be very slow, if you happen to have a huge data

structure whose string representation is complex to compute. Your computer may appear to freeze for a while with cpu usage at 100%. If this occurs, you can cancel the traceback with Ctrl-C (maybe hitting it more than once).

If you encounter this kind of situation often, you may want to use the `Verbose_novars` mode instead of the regular `Verbose`, which avoids formatting variables (but otherwise includes the information and context given by `Verbose`).

Примечание: The verbose mode print all variables in the stack, which means it can potentially leak sensitive information like access keys, or unencrypted password.

Installation instructions for `VerboseTB`:

```
import sys,ultratb
sys.excepthook = ultratb.VerboseTB()
```

Note: Much of the code in this module was lifted verbatim from the standard library module „`traceback.py`“ and Ka-Ping Yee’s „`cgitb.py`“.

8.41.1 Color schemes

The colors are defined in the class `TBTools` through the use of the `ColorSchemeTable` class. Currently the following exist:

- `NoColor`: allows all of this module to be used in any terminal (the color escapes are just dummy blank strings).
- `Linux`: is meant to look good in a terminal like the Linux console (black or very dark background).
- `LightBG`: similar to `Linux` but swaps dark/light colors to be more readable in light background terminals.
- `Neutral`: a neutral color scheme that should be readable on both light and dark background

You can implement other color schemes easily, the syntax is fairly self-explanatory. Please send back new schemes you develop to the author for possible inclusion in future releases.

Inheritance diagram:



8.41.2 8 Classes

`class IPython.core.ultratb.TBTools(**kwargs: Any)`

Базовые классы: *Colorable*

Basic tools used by all traceback printer classes.

`__init__(color_scheme='NoColor', call_pdb=False, ostream=None, parent=None, config=None, *, debugger_cls=None)`

Create a configurable given a config config.

Параметры

- `config` (*Config*) – If this is empty, default values are used. If config is a *Config* instance, it will be used to configure the instance.
- `parent` (*Configurable instance, optional*) – The parent *Configurable* instance of this object.

Заметки

Subclasses of *Configurable* must call the `__init__()` method of *Configurable* *before* doing anything else and using `super()`:

```
class MyConfigurable(Configurable):
    def __init__(self, config=None):
        super(MyConfigurable, self).__init__(config=config)
        # Then any other code you need to finish initialization.
```

This ensures that instances will be configured properly.

`color_toggle()`

Toggle between the currently active color scheme and NoColor.

property `ostream`

Output stream that exceptions are written to.

Valid values are:

- None: the default, which means that IPython will dynamically resolve to `sys.stdout`. This ensures compatibility with most tools, including Windows (where plain `stdout` doesn't recognize ANSI escapes).
- Any object with „write“ and „flush“ attributes.

`set_colors(*args, **kw)`

Shorthand access to the color table scheme selector method.

`stb2text(stb)`

Convert a structured traceback (a list) to a string.

`structured_traceback(etype: type, evalue: Optional[BaseException], etb: Optional[TracebackType] = None, tb_offset: Optional[int] = None, number_of_lines_of_context: int = 5)`

Return a list of traceback frames.

Must be implemented by each class.

`text(etype, value, tb, tb_offset: Optional[int] = None, context=5)`

Return formatted traceback.

Subclasses may override this if they add extra arguments.

`class IPython.core.ultratb.ListTB(**kwargs: Any)`

Базовые классы: *TBTools*

Print traceback information from a traceback list, with optional color.

Calling requires 3 arguments: (etype, evalue, elist) as would be obtained by:

```
etype, evalue, tb = sys.exc_info()
if tb:
    elist = traceback.extract_tb(tb)
else:
    elist = None
```

It can thus be used by programs which need to process the traceback before printing (such as console replacements based on the code module from the standard library).

Because they are meant to be called without a full traceback (only a list), instances of this class can't call the interactive pdb debugger.

`get_exception_only(etype, value)`

Only print the exception type and message, without a traceback.

Параметры

- `etype` (*exception type*) –
- `value` (*exception value*) –

`show_exception_only(etype, value)`

Only print the exception type and message, without a traceback.

Параметры

- `etype` (*exception type*) –
- `evalue` (*exception value*) –

`structured_traceback(etype: type, evalue: Optional[BaseException], etb: Optional[TracebackType] = None, tb_offset: Optional[int] = None, context=5)`

Return a color formatted string with the traceback info.

Параметры

- `etype` (*exception type*) – Type of the exception raised.
- `evalue` (*object*) – Data stored in the exception
- `etb` (*list / TracebackType / None*) – If list: List of frames, see class docstring for details. If Traceback: Traceback of the exception.
- `tb_offset` (*int, optional*) – Number of frames in the traceback to skip. If not given, the instance evalue is used (set in constructor).
- `context` (*int, optional*) – Number of lines of context information to print.

Тип результата

String with formatted exception.

```
class IPython.core.ultratb.FrameInfo(description: Optional[str], filename: str, lineno: Tuple[int],
                                   frame, code, *, sd=None, context=None)
```

Базовые классы: `object`

Mirror of stack data's FrameInfo, but so that we can bypass highlighting on really long frames.

```
__init__(description: Optional[str], filename: str, lineno: Tuple[int], frame, code, *, sd=None,
         context=None)
```

```
class IPython.core.ultratb.VerboseTB(**kwargs: Any)
```

Базовые классы: `TBTools`

A port of Ka-Ping Yee's `cgith.py` module that outputs color text instead of HTML. Requires `inspect` and `pydoc`. Crazy, man.

Modified version which optionally strips the topmost entries from the traceback, to be used with alternate interpreters (because their own code would appear in the traceback).

```
__init__(color_scheme: str = 'Linux', call_pdb: bool = False, ostream=None, tb_offset: int = 0,
         long_header: bool = False, include_vars: bool = True, check_cache=None,
         debugger_cls=None, parent=None, config=None)
```

Specify traceback offset, headers and color scheme.

Define how many frames to drop from the tracebacks. Calling it with `tb_offset=1` allows use of this handler in interpreters which will have their own code at the top of the traceback (VerboseTB will first remove that frame before printing the traceback info).

```
debugger(force: bool = False)
```

Call up the `pdb` debugger if desired, always clean up the `tb` reference.

Keywords:

- `force(False)`: by default, this routine checks the instance `call_pdb` flag and does not actually invoke the debugger if the flag is false. The „force“ option forces the debugger to activate even if the flag is false.

If the `call_pdb` flag is set, the `pdb` interactive debugger is invoked. In all cases, the `self.tb` reference to the current traceback is deleted to prevent lingering references which hamper memory management.

Note that each call to `pdb()` does an „import readline“, so if your app requires a special setup for the readline completers, you'll have to fix that by hand after invoking the exception handler.

```
format_exception_as_a_whole(etype: type, value: Optional[BaseException], etb:
                           Optional[TracebackType], number_of_lines_of_context, tb_offset:
                           Optional[int])
```

Formats the header, traceback and exception message for a single exception.

This may be called multiple times by Python 3 exception chaining (PEP 3134).

```
format_record(frame_info: FrameInfo)
```

Format a single stack frame

```
structured_traceback(etype: type, value: Optional[BaseException], etb: Optional[TracebackType] =
                     None, tb_offset: Optional[int] = None, number_of_lines_of_context: int =
                     5)
```

Return a nice text document describing the traceback.

```
class IPython.core.ultratb.FormattedTB(**kwargs: Any)
```

Базовые классы: *VerboseTB*, *ListTB*

Subclass ListTB but allow calling with a traceback.

It can thus be used as a sys.excepthook for Python > 2.1.

Also adds „Context“ and „Verbose“ modes, not available in ListTB.

Allows a tb_offset to be specified. This is useful for situations where one needs to remove a number of topmost frames from the traceback (such as occurs with python programs that themselves execute other python code, like Python shells).

```
__init__(mode='Plain', color_scheme='Linux', call_pdb=False, ostream=None, tb_offset=0,
         long_header=False, include_vars=False, check_cache=None, debugger_cls=None,
         parent=None, config=None)
```

Specify traceback offset, headers and color scheme.

Define how many frames to drop from the tracebacks. Calling it with tb_offset=1 allows use of this handler in interpreters which will have their own code at the top of the traceback (VerboseTB will first remove that frame before printing the traceback info).

```
set_mode(mode: Optional[str] = None)
```

Switch to the desired mode.

If mode is not specified, cycles through the available modes.

```
stb2text(stb)
```

Convert a structured traceback (a list) to a string.

```
structured_traceback(etype, value, tb, tb_offset=None, number_of_lines_of_context=5)
```

Return a nice text document describing the traceback.

```
class IPython.core.ultratb.AutoFormattedTB(**kwargs: Any)
```

Базовые классы: *FormattedTB*

A traceback printer which can be called on the fly.

It will find out about exceptions by itself.

A brief example:

```
AutoTB = AutoFormattedTB(mode = 'Verbose',color_scheme='Linux')
try:
    ...
except:
    AutoTB() # or AutoTB(out=logfile) where logfile is an open file object
```

```
structured_traceback(etype: type, value: Optional[BaseException], etb: Optional[TracebackType] =
                     None, tb_offset: Optional[int] = None, number_of_lines_of_context: int =
                     5)
```

Return a nice text document describing the traceback.

```
class IPython.core.ultratb.ColorTB(**kwargs: Any)
```

Базовые классы: *FormattedTB*

Shorthand to initialize a FormattedTB in Linux colors mode.

```
__init__(color_scheme='Linux', call_pdb=0, **kwargs)
```

Specify traceback offset, headers and color scheme.

Define how many frames to drop from the tracebacks. Calling it with `tb_offset=1` allows use of this handler in interpreters which will have their own code at the top of the traceback (VerboseTB will first remove that frame before printing the traceback info).

```
class IPython.core.ultratb.SyntaxTB(**kwargs: Any)
```

Базовые классы: *ListTB*

Extension which holds some state: the last exception value

```
__init__(color_scheme='NoColor', parent=None, config=None)
```

Create a configurable given a config config.

Параметры

- `config` (*Config*) – If this is empty, default values are used. If config is a *Config* instance, it will be used to configure the instance.
- `parent` (*Configurable instance, optional*) – The parent *Configurable* instance of this object.

Заметки

Subclasses of *Configurable* must call the `__init__()` method of *Configurable* *before* doing anything else and using `super()`:

```
class MyConfigurable(Configurable):
    def __init__(self, config=None):
        super(MyConfigurable, self).__init__(config=config)
        # Then any other code you need to finish initialization.
```

This ensures that instances will be configured properly.

```
clear_err_state()
```

Return the current error state and clear it

```
stb2text(stb)
```

Convert a structured traceback (a list) to a string.

```
structured_traceback(etype, value, elist, tb_offset=None, context=5)
```

Return a color formatted string with the traceback info.

Параметры

- `etype` (*exception type*) – Type of the exception raised.
- `eval` (*object*) – Data stored in the exception
- `etb` (*list / TracebackType / None*) – If list: List of frames, see class docstring for details. If *Traceback*: *Traceback* of the exception.
- `tb_offset` (*int, optional*) – Number of frames in the traceback to skip. If not given, the instance `eval` is used (set in constructor).
- `context` (*int, optional*) – Number of lines of context information to print.

Тип результата

String with formatted exception.

8.41.3 5 Functions

`IPython.core.ultratb.count_lines_in_py_file(filename: str) → int`

Given a filename, returns the number of lines in the file if it ends with the extension «.py». Otherwise, returns 0.

`IPython.core.ultratb.get_line_number_of_frame(frame: frame) → int`

Given a frame object, returns the total number of lines in the file containing the frame's code object, or the number of lines in the frame's source code if the file is not available.

Параметры

`frame (FrameType)` – The frame object whose line number is to be determined.

Результат

The total number of lines in the file containing the frame's code object, or the number of lines in the frame's source code if the file is not available.

Тип результата

`int`

`IPython.core.ultratb.text_repr(value)`

Hopefully pretty robust repr equivalent.

`IPython.core.ultratb.eqrepr(value, repr=<function text_repr>)`

`IPython.core.ultratb.nullrepr(value, repr=<function text_repr>)`

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

8.42 Module: display

Public API for display tools in IPython.

8.42.1 23 Classes

`class IPython.display.Audio(data=None, filename=None, url=None, embed=None, rate=None, autoplay=False, normalize=True, *, element_id=None)`

Базовые классы: `DisplayObject`

Create an audio object.

When this object is returned by an input cell or passed to the display function, it will result in Audio controls being displayed in the frontend (only works in the notebook).

Параметры

- `data` (*numpy array, list, unicode, str or bytes*) – Can be one of
 - Numpy 1d array containing the desired waveform (mono)
 - Numpy 2d array containing waveforms for each channel. Shape=(NCHAN, NSAMPLES). For the standard channel order, see [http://msdn.microsoft.com/en-us/library/windows/hardware/dn653308\(v=vs.85\).aspx](http://msdn.microsoft.com/en-us/library/windows/hardware/dn653308(v=vs.85).aspx)
 - List of float or integer representing the waveform (mono)
 - String containing the filename
 - Bytestring containing raw PCM data or
 - URL pointing to a file on the web.

If the array option is used, the waveform will be normalized.

If a filename or url is used, the format support will be browser dependent.

- `url` (*unicode*) – A URL to download the data from.
 - `filename` (*unicode*) – Path to a local file to load the data from.
 - `embed` (*boolean*) – Should the audio data be embedded using a data URI (True) or should the original source be referenced. Set this to True if you want the audio to playable later with no internet connection in the notebook.
- Default is `True`, unless the keyword argument `url` is set, then default value is `False`.
- `rate` (*integer*) – The sampling rate of the raw data. Only required when `data` parameter is being used as an array
 - `autoplay` (*bool*) – Set to True if the audio should immediately start playing. Default is `False`.
 - `normalize` (*bool*) – Whether audio should be normalized (rescaled) to the maximum possible range. Default is `True`. When set to `False`, `data` must be between -1 and 1 (inclusive), otherwise an error is raised. Applies only when `data` is a list or array of samples; other types of audio are never normalized.

Примеры

```
>>> import pytest
>>> np = pytest.importorskip("numpy")
```

Generate a sound

```
>>> import numpy as np
>>> framerate = 44100
>>> t = np.linspace(0,5,framerate*5)
>>> data = np.sin(2*np.pi*220*t) + np.sin(2*np.pi*224*t)
>>> Audio(data, rate=framerate)
<IPython.lib.display.Audio object>
```

Can also do stereo or more channels

```
>>> dataleft = np.sin(2*np.pi*220*t)
>>> dataright = np.sin(2*np.pi*224*t)
```

(continues on next page)

(продолжение с предыдущей страницы)

```
>>> Audio([dataleft, dataright], rate=framerate)
<IPython.lib.display.Audio object>
```

From URL:

```
>>> Audio("http://www.nch.com.au/acm/8k16bitpcm.wav")
>>> Audio(url="http://www.w3schools.com/html/horse.ogg")
```

From a File:

```
>>> Audio('IPython/lib/tests/test.wav')
>>> Audio(filename='IPython/lib/tests/test.wav')
```

From Bytes:

```
>>> Audio(b'RAW_WAV_DATA..')
>>> Audio(data=b'RAW_WAV_DATA..')
```

См.также:

`ipywidgets.Audio`

Audio widget with more more flexibility and options.

```
__init__(data=None, filename=None, url=None, embed=None, rate=None, autoplay=False,
         normalize=True, *, element_id=None)
```

Create a display object given raw data.

When this object is returned by an expression or passed to the display function, it will result in the data being displayed in the frontend. The MIME type of the data should match the subclasses used, so the Png subclass should be used for „image/png“ data. If the data is a URL, the data will first be downloaded and then displayed. If

Параметры

- `data` (*unicode*, *str* or *bytes*) – The raw data or a URL or file to load the data from
- `url` (*unicode*) – A URL to download the data from.
- `filename` (*unicode*) – Path to a local file to load the data from.
- `metadata` (*dict*) – Dict of metadata associated to be the object when displayed

`reload()`

Reload the raw data from file or URL.

```
class IPython.display.Code(data=None, url=None, filename=None, language=None)
```

Базовые классы: *TextDisplayObject*

Display syntax-highlighted source code.

This uses Pygments to highlight the code for HTML and Latex output.

Параметры

- `data` (*str*) – The code as a string
- `url` (*str*) – A URL to fetch the code from

- `filename` (*str*) – A local filename to load the code from
- `language` (*str*) – The short name of a Pygments lexer to use for highlighting. If not specified, it will guess the lexer based on the filename or the code. Available lexers: <http://pygments.org/docs/lexers/>

`__init__(data=None, url=None, filename=None, language=None)`

Create a display object given raw data.

When this object is returned by an expression or passed to the display function, it will result in the data being displayed in the frontend. The MIME type of the data should match the subclasses used, so the Png subclass should be used for „image/png“ data. If the data is a URL, the data will first be downloaded and then displayed. If

Параметры

- `data` (*unicode*, *str* or *bytes*) – The raw data or a URL or file to load the data from
- `url` (*unicode*) – A URL to download the data from.
- `filename` (*unicode*) – Path to a local file to load the data from.
- `metadata` (*dict*) – Dict of metadata associated to be the object when displayed

`class IPython.display.DisplayHandle(display_id=None)`

Базовые классы: `object`

A handle on an updatable display

Call `.update(obj)` to display a new object.

Call `.display(obj)` to add a new instance of this display, and update existing instances.

`__init__(display_id=None)`

`display(obj, **kwargs)`

Make a new display with my id, updating existing instances.

Параметры

- `obj` – object to display
- `**kwargs` – additional keyword arguments passed to display

`update(obj, **kwargs)`

Update existing displays with my id

Параметры

- `obj` – object to display
- `**kwargs` – additional keyword arguments passed to `update_display`

`class IPython.display.DisplayObject(data=None, url=None, filename=None, metadata=None)`

Базовые классы: `object`

An object that wraps data to be displayed.

`__init__(data=None, url=None, filename=None, metadata=None)`

Create a display object given raw data.

When this object is returned by an expression or passed to the display function, it will result in the data being displayed in the frontend. The MIME type of the data should match the subclasses

used, so the Png subclass should be used for „image/png“ data. If the data is a URL, the data will first be downloaded and then displayed. If

Параметры

- `data` (*unicode*, *str* or *bytes*) – The raw data or a URL or file to load the data from
- `url` (*unicode*) – A URL to download the data from.
- `filename` (*unicode*) – Path to a local file to load the data from.
- `metadata` (*dict*) – Dict of metadata associated to be the object when displayed

`reload()`

Reload the raw data from file or URL.

```
class IPython.display.FileLink(path, url_prefix='', result_html_prefix='',
                               result_html_suffix='<br>')
```

БАЗОВЫЕ КЛАССЫ: `object`

Class for embedding a local file link in an IPython session, based on path

e.g. to embed a link that was generated in the IPython notebook as my/data.txt

you would do:

```
local_file = FileLink("my/data.txt")
display(local_file)
```

or in the HTML notebook, just:

```
FileLink("my/data.txt")
```

```
__init__(path, url_prefix='', result_html_prefix='', result_html_suffix='<br>')
```

Параметры

- `path` (*str*) – path to the file or directory that should be formatted
- `url_prefix` (*str*) – prefix to be prepended to all files to form a working link [default: „"]
- `result_html_prefix` (*str*) – text to append to beginning to link [default: „"]
- `result_html_suffix` (*str*) – text to append at the end of link [default: „
"]

```
class IPython.display.FileLinks(path, url_prefix='', included_suffixes=None, result_html_prefix='',
                                result_html_suffix='<br>', notebook_display_formatter=None,
                                terminal_display_formatter=None, recursive=True)
```

БАЗОВЫЕ КЛАССЫ: `FileLink`

Class for embedding local file links in an IPython session, based on path

e.g. to embed links to files that were generated in the IPython notebook under my/data, you would do:

```
local_files = FileLinks("my/data")
display(local_files)
```

or in the HTML notebook, just:

```
FileLinks("my/data")
```

```
__init__(path, url_prefix='', included_suffixes=None, result_html_prefix='',
         result_html_suffix='<br>', notebook_display_formatter=None,
         terminal_display_formatter=None, recursive=True)
```

See [FileLink](#) for the `path`, `url_prefix`, `result_html_prefix` and `result_html_suffix` parameters.

included_suffixes

[list] Filename suffixes to include when formatting output [default: include all files]

notebook_display_formatter

[function] Used to format links for display in the notebook. See discussion of formatter functions below.

terminal_display_formatter

[function] Used to format links for display in the terminal. See discussion of formatter functions below.

Formatter functions must be of the form:

```
f(dirname, fnames, included_suffixes)
```

dirname

[str] The name of a directory

fnames

[list] The files in that directory

included_suffixes

[list] The file suffixes that should be included in the output (passing None means to include all suffixes in the output in the built-in formatters)

recursive

[boolean] Whether to recurse into subdirectories. Default is True.

The function should return a list of lines that will be printed in the notebook (if passing `notebook_display_formatter`) or the terminal (if passing `terminal_display_formatter`). This function is iterated over for each directory in `self.path`. Default formatters are in place, can be passed here to support alternative formatting.

```
class IPython.display.GeoJSON(*args, **kwargs)
```

Базовые классы: [JSON](#)

GeoJSON expects JSON-able dict

not an already-serialized JSON string.

Scalar types (None, number, string) are not allowed, only dict containers.

```
__init__(*args, **kwargs)
```

Create a GeoJSON display object given raw data.

Параметры

- **data** (*dict or list*) – VegaLite data. Not an already-serialized JSON string. Scalar types (None, number, string) are not allowed, only dict or list containers.
- **url_template** (*string*) – Leaflet TileLayer URL template: <http://leafletjs.com/reference.html#url-template>
- **layer_options** (*dict*) – Leaflet TileLayer options: <http://leafletjs.com/reference.html#tilelayer-options>

- `url` (*unicode*) – A URL to download the data from.
- `filename` (*unicode*) – Path to a local file to load the data from.
- `metadata` (*dict*) – Specify extra metadata to attach to the json display object.

Примеры

The following will display an interactive map of Mars with a point of interest on frontend that do support GeoJSON display.

```
>>> from IPython.display import GeoJSON
```

```
>>> GeoJSON(data={
...     "type": "Feature",
...     "geometry": {
...         "type": "Point",
...         "coordinates": [-81.327, 296.038]
...     }
... },
... url_template="http://s3-eu-west-1.amazonaws.com/whereonmars.cartodb.net/
↪{basemap_id}/{z}/{x}/{y}.png",
... layer_options={
...     "basemap_id": "celestia_mars-shaded-16k_global",
...     "attribution" : "Celestia/praesepe",
...     "minZoom" : 0,
...     "maxZoom" : 18,
... })
<IPython.core.display.GeoJSON object>
```

In the terminal IPython, you will only see the text representation of the GeoJSON object.

```
class IPython.display.HTML(data=None, url=None, filename=None, metadata=None)
```

Базовые классы: *TextDisplayObject*

```
__init__(data=None, url=None, filename=None, metadata=None)
```

Create a display object given raw data.

When this object is returned by an expression or passed to the display function, it will result in the data being displayed in the frontend. The MIME type of the data should match the subclasses used, so the Png subclass should be used for „image/png“ data. If the data is a URL, the data will first be downloaded and then displayed. If

Параметры

- `data` (*unicode*, *str* or *bytes*) – The raw data or a URL or file to load the data from
- `url` (*unicode*) – A URL to download the data from.
- `filename` (*unicode*) – Path to a local file to load the data from.
- `metadata` (*dict*) – Dict of metadata associated to be the object when displayed

```
class IPython.display.IFrame(src, width, height, extras: Optional[Iterable[str]] = None, **kwargs)
```

Базовые классы: *object*

Generic class to embed an iframe in an IPython notebook

```
__init__(src, width, height, extras: Optional[Iterable[str]] = None, **kwargs)

class IPython.display.Image(data=None, url=None, filename=None, format=None, embed=None,
                             width=None, height=None, retina=False, unconfined=False,
                             metadata=None, alt=None)
```

Базовые классы: *DisplayObject*

```
__init__(data=None, url=None, filename=None, format=None, embed=None, width=None,
          height=None, retina=False, unconfined=False, metadata=None, alt=None)
```

Create a PNG/JPEG/GIF image object given raw data.

When this object is returned by an input cell or passed to the display function, it will result in the image being displayed in the frontend.

Параметры

- **data** (*unicode*, *str* or *bytes*) – The raw image data or a URL or filename to load the data from. This always results in embedded image data.
- **url** (*unicode*) – A URL to download the data from. If you specify **url=**, the image data will not be embedded unless you also specify **embed=True**.
- **filename** (*unicode*) – Path to a local file to load the data from. Images from a file are always embedded.
- **format** (*unicode*) – The format of the image data (png/jpeg/jpg/gif). If a filename or URL is given for format will be inferred from the filename extension.
- **embed** (*bool*) – Should the image data be embedded using a data URI (True) or be loaded using an `` tag. Set this to True if you want the image to be viewable later with no internet connection in the notebook.

Default is **True**, unless the keyword argument **url** is set, then default value is **False**.

Note that QtConsole is not able to display images if **embed** is set to **False**

- **width** (*int*) – Width in pixels to which to constrain the image in html
- **height** (*int*) – Height in pixels to which to constrain the image in html
- **retina** (*bool*) – Automatically set the width and height to half of the measured width and height. This only works for embedded images because it reads the width/height from image data. For non-embedded images, you can just set the desired display width and height directly.
- **unconfined** (*bool*) – Set **unconfined=True** to disable max-width confinement of the image.
- **metadata** (*dict*) – Specify extra metadata to attach to the image.
- **alt** (*unicode*) – Alternative text for the image, for use by screen readers.

Примеры

embedded image data, works in qtconsole and notebook when passed positionally, the first arg can be any of raw image data, a URL, or a filename from which to load image data. The result is always embedding image data for inline images.

```
>>> Image('https://www.google.fr/images/srpr/logo3w.png')
<IPython.core.display.Image object>
```

```
>>> Image('/path/to/image.jpg')
<IPython.core.display.Image object>
```

```
>>> Image(b'RAW_PNG_DATA...')
<IPython.core.display.Image object>
```

Specifying Image(url=...) does not embed the image data, it only generates tag with a link to the source. This will not work in the qtconsole or offline.

```
>>> Image(url='https://www.google.fr/images/srpr/logo3w.png')
<IPython.core.display.Image object>
```

reload()

Reload the raw data from file or URL.

```
class IPython.display.JSON(data=None, url=None, filename=None, expanded=False, metadata=None,
                           root='root', **kwargs)
```

Базовые классы: *DisplayObject*

JSON expects a JSON-able dict or list

not an already-serialized JSON string.

Scalar types (None, number, string) are not allowed, only dict or list containers.

```
__init__(data=None, url=None, filename=None, expanded=False, metadata=None, root='root',
          **kwargs)
```

Create a JSON display object given raw data.

Параметры

- *data* (*dict* or *list*) – JSON data to display. Not an already-serialized JSON string. Scalar types (None, number, string) are not allowed, only dict or list containers.
- *url* (*unicode*) – A URL to download the data from.
- *filename* (*unicode*) – Path to a local file to load the data from.
- *expanded* (*boolean*) – Metadata to control whether a JSON display component is expanded.
- *metadata* (*dict*) – Specify extra metadata to attach to the json display object.
- *root* (*str*) – The name of the root element of the JSON tree

```
class IPython.display.Javascript(data=None, url=None, filename=None, lib=None, css=None)
```

Базовые классы: *TextDisplayObject*

```
__init__(data=None, url=None, filename=None, lib=None, css=None)
```

Create a Javascript display object given raw data.

When this object is returned by an expression or passed to the display function, it will result in the data being displayed in the frontend. If the data is a URL, the data will first be downloaded and then displayed.

In the Notebook, the containing element will be available as `element`, and jQuery will be available. Content appended to `element` will be visible in the output area.

Параметры

- `data` (*unicode*, *str* or *bytes*) – The Javascript source code or a URL to download it from.
- `url` (*unicode*) – A URL to download the data from.
- `filename` (*unicode*) – Path to a local file to load the data from.
- `lib` (*list* or *str*) – A sequence of Javascript library URLs to load asynchronously before running the source code. The full URLs of the libraries should be given. A single Javascript library URL can also be given as a string.
- `css` (*list* or *str*) – A sequence of css files to load before running the source code. The full URLs of the css files should be given. A single css URL can also be given as a string.

```
class IPython.display.Latex(data=None, url=None, filename=None, metadata=None)
```

Базовые классы: *TextDisplayObject*

```
class IPython.display.Markdown(data=None, url=None, filename=None, metadata=None)
```

Базовые классы: *TextDisplayObject*

```
class IPython.display.Math(data=None, url=None, filename=None, metadata=None)
```

Базовые классы: *TextDisplayObject*

```
class IPython.display.Pretty(data=None, url=None, filename=None, metadata=None)
```

Базовые классы: *TextDisplayObject*

```
class IPython.display.ProgressBar(total)
```

Базовые классы: *DisplayObject*

Progressbar supports displaying a progressbar like element

```
__init__(total)
```

Creates a new progressbar

Параметры

`total` (*int*) – maximum size of the progressbar

```
class IPython.display.SVG(data=None, url=None, filename=None, metadata=None)
```

Базовые классы: *DisplayObject*

Embed an SVG into the display.

Note if you just want to view a svg image via a URL use `:class:Image` with a `url=URL` keyword argument.

```
class IPython.display.ScribdDocument(id, width=400, height=300, **kwargs)
```

Базовые классы: *IFrame*

Class for embedding a Scribd document in an IPython session

Use the `start_page` params to specify a starting point in the document Use the `view_mode` params to specify display type one off scroll | slideshow | book

e.g to Display Wes“ foundational paper about PANDAS in book mode from page 3

```
ScribdDocument(71048089, width=800, height=400, start_page=3, view_mode=»book«)
```

```
__init__(id, width=400, height=300, **kwargs)
```

```
class IPython.display.TextDisplayObject(data=None, url=None, filename=None, metadata=None)
```

Базовые классы: [DisplayObject](#)

Create a text display object given raw data.

Параметры

- `data` (*str or unicode*) – The raw data or a URL or file to load the data from.
- `url` (*unicode*) – A URL to download the data from.
- `filename` (*unicode*) – Path to a local file to load the data from.
- `metadata` (*dict*) – Dict of metadata associated to be the object when displayed

```
class IPython.display.Video(data=None, url=None, filename=None, embed=False, mimetype=None, width=None, height=None, html_attributes='controls')
```

Базовые классы: [DisplayObject](#)

```
__init__(data=None, url=None, filename=None, embed=False, mimetype=None, width=None, height=None, html_attributes='controls')
```

Create a video object given raw data or an URL.

When this object is returned by an input cell or passed to the display function, it will result in the video being displayed in the frontend.

Параметры

- `data` (*unicode, str or bytes*) – The raw video data or a URL or filename to load the data from. Raw data will require passing `embed=True`.
- `url` (*unicode*) – A URL for the video. If you specify `url=`, the image data will not be embedded.
- `filename` (*unicode*) – Path to a local file containing the video. Will be interpreted as a local URL unless `embed=True`.
- `embed` (*bool*) – Should the video be embedded using a data URI (True) or be loaded using a `<video>` tag (False).

Since videos are large, embedding them should be avoided, if possible. You must confirm embedding as your intention by passing `embed=True`.

Local files can be displayed with URLs without embedding the content, via:

```
Video('./video.mp4')
```

- `mimetype` (*unicode*) – Specify the mimetype for embedded videos. Default will be guessed from file extension, if available.
- `width` (*int*) – Width in pixels to which to constrain the video in HTML. If not supplied, defaults to the width of the video.
- `height` (*int*) – Height in pixels to which to constrain the video in html. If not supplied, defaults to the height of the video.

- `html_attributes` (*str*) – Attributes for the HTML `<video>` block. Default: `"controls"` to get video controls. Other examples: `"controls muted"` for muted video with controls, `"loop autoplay"` for looping autoplaying video without controls.

Примеры

```
Video('https://archive.org/download/Sita_Sings_the_Blues/Sita_Sings_the_Blues_
↪small.mp4')
Video('path/to/video.mp4')
Video('path/to/video.mp4', embed=True)
Video('path/to/video.mp4', embed=True, html_attributes="controls muted autoplay
↪")
Video(b'raw-videodata', embed=True)
```

`reload()`

Reload the raw data from file or URL.

```
class IPython.display.VimeoVideo(id, width=400, height=300, **kwargs)
```

Базовые классы: *IFrame*

Class for embedding a Vimeo video in an IPython session, based on its video id.

```
__init__(id, width=400, height=300, **kwargs)
```

```
class IPython.display.YouTubeVideo(id, width=400, height=300, allow_autoplay=False, **kwargs)
```

Базовые классы: *IFrame*

Class for embedding a YouTube Video in an IPython session, based on its video id.

e.g. to embed the video from <https://www.youtube.com/watch?v=foo> , you would do:

```
vid = YouTubeVideo("foo")
display(vid)
```

To start from 30 seconds:

```
vid = YouTubeVideo("abc", start=30)
display(vid)
```

To calculate seconds from time as hours, minutes, seconds use `datetime.timedelta`:

```
start=int(timedelta(hours=1, minutes=46, seconds=40).total_seconds())
```

Other parameters can be provided as documented at https://developers.google.com/youtube/player_parameters#Parameters

When converting the notebook using `nbconvert`, a jpeg representation of the video will be inserted in the document.

```
__init__(id, width=400, height=300, allow_autoplay=False, **kwargs)
```

8.42.2 16 Functions

`IPython.display.clear_output(wait=False)`

Clear the output of the current cell receiving output.

Параметры

`wait` (*bool* [*default: false*]) – Wait to clear the output until new output is available to replace it.

`IPython.display.display(*objs, include=None, exclude=None, metadata=None, transient=None, display_id=None, raw=False, clear=False, **kwargs)`

Display a Python object in all frontends.

By default all representations will be computed and sent to the frontends. Frontends can decide which representation is used and how.

In terminal IPython this will be similar to using `print()`, for use in richer frontends see Jupyter notebook examples with rich display logic.

Параметры

- `*objs` (*object*) – The Python objects to display.
- `raw` (*bool*, *optional*) – Are the objects to be displayed already mimetype-keyed dicts of raw display data, or Python objects that need to be formatted before display? [default: False]
- `include` (*list*, *tuple or set*, *optional*) – A list of format type strings (MIME types) to include in the format data dict. If this is set *only* the format types included in this list will be computed.
- `exclude` (*list*, *tuple or set*, *optional*) – A list of format type strings (MIME types) to exclude in the format data dict. If this is set all format types will be computed, except for those included in this argument.
- `metadata` (*dict*, *optional*) – A dictionary of metadata to associate with the output. mime-type keys in this dictionary will be associated with the individual representation formats, if they exist.
- `transient` (*dict*, *optional*) – A dictionary of transient data to associate with the output. Data in this dict should not be persisted to files (e.g. notebooks).
- `display_id` (*str*, *bool optional*) – Set an id for the display. This id can be used for updating this display area later via `update_display`. If given as `True`, generate a new `display_id`
- `clear` (*bool*, *optional*) – Should the output area be cleared before displaying anything? If `True`, this will wait for additional output before clearing. [default: False]
- `**kwargs` (*additional keyword-args*, *optional*) – Additional keyword-arguments are passed through to the display publisher.

Результат

`handle` – Returns a handle on updatable displays for use with `update_display()`, if `display_id` is given. Returns `None` if no `display_id` is given (default).

Тип результата

DisplayHandle

Примеры

```
>>> class Json(object):
...     def __init__(self, json):
...         self.json = json
...     def _repr_pretty_(self, pp, cycle):
...         import json
...         pp.text(json.dumps(self.json, indent=2))
...     def __repr__(self):
...         return str(self.json)
... 
```

```
>>> d = Json({1:2, 3: {4:5}})
```

```
>>> print(d)
{1: 2, 3: {4: 5}}
```

```
>>> display(d)
{
  "1": 2,
  "3": {
    "4": 5
  }
}
```

```
>>> def int_formatter(integer, pp, cycle):
...     pp.text('I'*integer)
```

```
>>> plain = get_ipython().display_formatter.formatters['text/plain']
>>> plain.for_type(int, int_formatter)
<function _repr_pprint at 0x...>
>>> display(7-5)
II
```

```
>>> del plain.type_printers[int]
>>> display(7-5)
2
```

См.также:

update_display()

Заметки

In Python, objects can declare their textual representation using the `__repr__` method. IPython expands on this idea and allows objects to declare other, rich representations including:

- HTML
- JSON
- PNG
- JPEG

- SVG
- LaTeX

A single object can declare some or all of these representations; all are handled by IPython's display system.

The main idea of the first approach is that you have to implement special display methods when you define your class, one for each representation you want to use. Here is a list of the names of the special methods and the values they must return:

- `_repr_html_`: return raw HTML as a string, or a tuple (see below).
- `_repr_json_`: return a JSONable dict, or a tuple (see below).
- `_repr_jpeg_`: return raw JPEG data, or a tuple (see below).
- `_repr_png_`: return raw PNG data, or a tuple (see below).
- `_repr_svg_`: return raw SVG data as a string, or a tuple (see below).
- `_repr_latex_`: return LaTeX commands in a string surrounded by «\$», or a tuple (see below).
- `_repr_mimebundle_`: return a full mimebundle containing the mapping from all mimetypes to data. Use this for any mime-type not listed above.

The above functions may also return the object's metadata alongside the data. If the metadata is available, the functions will return a tuple containing the data and metadata, in that order. If there is no metadata available, then the functions will return the data only.

When you are directly writing your own classes, you can adapt them for display in IPython by following the above approach. But in practice, you often need to work with existing classes that you can't easily modify.

You can refer to the documentation on integrating with the display system in order to register custom formatters for already existing types (*Rich display*).

Добавлено в версии 5.4: display available without import

Добавлено в версии 6.1: display available without import

Since IPython 5.4 and 6.1 `display()` is automatically made available to the user without import. If you are using display in a document that might be used in a pure python context or with older version of IPython, use the following import at the top of your file:

```
from IPython.display import display
```

`IPython.display.display_html(*objs, **kwargs)`

Display the HTML representation of an object.

Note: If `raw=False` and the object does not have a HTML representation, no HTML will be shown.

Параметры

- `*objs` (*object*) – The Python objects to display, or if `raw=True` raw HTML data to display.
- `raw` (*bool*) – Are the data objects raw data or Python objects that need to be formatted before display? [default: False]
- `metadata` (*dict (optional)*) – Metadata to be associated with the specific mimetype output.

`IPython.display.display_javascript(*objs, **kwargs)`

Display the Javascript representation of an object.

Параметры

- `*objs` (*object*) – The Python objects to display, or if `raw=True` raw javascript data to display.
- `raw` (*bool*) – Are the data objects raw data or Python objects that need to be formatted before display? [default: False]
- `metadata` (*dict (optional)*) – Metadata to be associated with the specific mimetype output.

`IPython.display.display_jpeg(*objs, **kwargs)`

Display the JPEG representation of an object.

Параметры

- `*objs` (*object*) – The Python objects to display, or if `raw=True` raw JPEG data to display.
- `raw` (*bool*) – Are the data objects raw data or Python objects that need to be formatted before display? [default: False]
- `metadata` (*dict (optional)*) – Metadata to be associated with the specific mimetype output.

`IPython.display.display_json(*objs, **kwargs)`

Display the JSON representation of an object.

Note that not many frontends support displaying JSON.

Параметры

- `*objs` (*object*) – The Python objects to display, or if `raw=True` raw json data to display.
- `raw` (*bool*) – Are the data objects raw data or Python objects that need to be formatted before display? [default: False]
- `metadata` (*dict (optional)*) – Metadata to be associated with the specific mimetype output.

`IPython.display.display_latex(*objs, **kwargs)`

Display the LaTeX representation of an object.

Параметры

- `*objs` (*object*) – The Python objects to display, or if `raw=True` raw latex data to display.
- `raw` (*bool*) – Are the data objects raw data or Python objects that need to be formatted before display? [default: False]
- `metadata` (*dict (optional)*) – Metadata to be associated with the specific mimetype output.

`IPython.display.display_markdown(*objs, **kwargs)`

Displays the Markdown representation of an object.

Параметры

- `*objs` (*object*) – The Python objects to display, or if `raw=True` raw markdown data to display.
- `raw` (*bool*) – Are the data objects raw data or Python objects that need to be formatted before display? [default: False]
- `metadata` (*dict (optional)*) – Metadata to be associated with the specific mimetype output.

`IPython.display.display_pdf(*objs, **kwargs)`

Display the PDF representation of an object.

Параметры

- `*objs` (*object*) – The Python objects to display, or if `raw=True` raw javascript data to display.
- `raw` (*bool*) – Are the data objects raw data or Python objects that need to be formatted before display? [default: False]
- `metadata` (*dict (optional)*) – Metadata to be associated with the specific mimetype output.

`IPython.display.display_png(*objs, **kwargs)`

Display the PNG representation of an object.

Параметры

- `*objs` (*object*) – The Python objects to display, or if `raw=True` raw png data to display.
- `raw` (*bool*) – Are the data objects raw data or Python objects that need to be formatted before display? [default: False]
- `metadata` (*dict (optional)*) – Metadata to be associated with the specific mimetype output.

`IPython.display.display_pretty(*objs, **kwargs)`

Display the pretty (default) representation of an object.

Параметры

- `*objs` (*object*) – The Python objects to display, or if `raw=True` raw text data to display.
- `raw` (*bool*) – Are the data objects raw data or Python objects that need to be formatted before display? [default: False]
- `metadata` (*dict (optional)*) – Metadata to be associated with the specific mimetype output.

`IPython.display.display_svg(*objs, **kwargs)`

Display the SVG representation of an object.

Параметры

- `*objs` (*object*) – The Python objects to display, or if `raw=True` raw svg data to display.
- `raw` (*bool*) – Are the data objects raw data or Python objects that need to be formatted before display? [default: False]
- `metadata` (*dict (optional)*) – Metadata to be associated with the specific mimetype output.

```
IPython.display.publish_display_data(data, metadata=None, source=<deprecated>, *,
                                     transient=None, **kwargs)
```

Publish data and metadata to all frontends.

See the `display_data` message in the messaging documentation for more details about this message type.

Keys of data and metadata can be any mime-type.

Параметры

- `data` (*dict*) – A dictionary having keys that are valid MIME types (like „text/plain“ or „image/svg+xml“) and values that are the data for that MIME type. The data itself must be a JSON’able data structure. Minimally all data should have the „text/plain“ data, which can be displayed by all frontends. If more than the plain text is given, it is up to the frontend to decide which representation to use.
- `metadata` (*dict*) – A dictionary for metadata related to the data. This can contain arbitrary key, value pairs that frontends can use to interpret the data. mime-type keys matching those in data can be used to specify metadata about particular representations.
- `source` (*str*, *deprecated*) – Unused.
- `transient` (*dict*, *keyword-only*) – A dictionary of transient data, such as `display_id`.

```
IPython.display.set_matplotlib_close(close=True)
```

Не рекомендуется, начиная с версии 7.23: use `matplotlib_inline.backend_inline.set_matplotlib_close()`

Set whether the inline backend closes all figures automatically or not.

By default, the inline backend used in the IPython Notebook will close all matplotlib figures automatically after each cell is run. This means that plots in different cells won’t interfere. Sometimes, you may want to make a plot in one cell and then refine it in later cells. This can be accomplished by:

```
In [1]: set_matplotlib_close(False)
```

To set this in your config files use the following:

```
c.InlineBackend.close_figures = False
```

Параметры

- `close` (*bool*) – Should all matplotlib figures be automatically closed after each cell is run?

```
IPython.display.set_matplotlib_formats(*formats, **kwargs)
```

Не рекомендуется, начиная с версии 7.23: use `matplotlib_inline.backend_inline.set_matplotlib_formats()`

Select figure formats for the inline backend. Optionally pass quality for JPEG.

For example, this enables PNG and JPEG output with a JPEG quality of 90%:

```
In [1]: set_matplotlib_formats('png', 'jpeg', quality=90)
```

To set this in your config files use the following:

```
c.InlineBackend.figure_formats = {'png', 'jpeg'}
c.InlineBackend.print_figure_kwargs.update({'quality' : 90})
```

Параметры

- ***formats** (*strs*) – One or more figure formats to enable: „png“, „retina“, „jpeg“, „svg“, „pdf“.
- ****kwargs** – Keyword args will be relayed to `figure.canvas.print_figure`.

`IPython.display.update_display(obj, *, display_id, **kwargs)`

Update an existing display by id

Параметры

- **obj** – The object with which to update the display
- **display_id** (*keyword-only*) – The id of the display to update

См.также:

`display()`

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

8.43 Module: `lib.backgroundjobs`

Manage background (threaded) jobs conveniently from an interactive shell.

This module provides a `BackgroundJobManager` class. This is the main class meant for public usage, it implements an object which can create and manage new background jobs.

It also provides the actual job classes managed by these `BackgroundJobManager` objects, see their docstrings below.

This system was inspired by discussions with B. Granger and the `BackgroundCommand` class described in the book *Python Scripting for Computational Science*, by H. P. Langtangen:

<http://folk.uio.no/hpl/scripting>

(although ultimately no code from this text was used, as IPython’s system is a separate implementation).

An example notebook is provided in our documentation illustrating interactive use of the system.

8.43.1 4 Classes

`class IPython.lib.backgroundjobs.BackgroundJobManager`

Базовые классы: `object`

Class to manage a pool of backgrounded threaded jobs.

Below, we assume that „jobs“ is a BackgroundJobManager instance.

Usage summary (see the method docstrings for details):

```
jobs.new(...) -> start a new job
jobs() or jobs.status() -> print status summary of all jobs
jobs[N] -> returns job number N.
foo = jobs[N].result -> assign to variable foo the result of job N
jobs[N].traceback() -> print the traceback of dead job N
jobs.remove(N) -> remove (finished) job N
jobs.flush() -> remove all finished jobs
```

As a convenience feature, BackgroundJobManager instances provide the utility result and traceback methods which retrieve the corresponding information from the jobs list:

```
jobs.result(N) <-> jobs[N].result jobs.traceback(N) <-> jobs[N].traceback()
```

While this appears minor, it allows you to use tab completion interactively on the job manager instance.

`__init__()`

`flush()`

Flush all finished jobs (completed and dead) from lists.

Running jobs are never flushed.

It first calls `_status_new()`, to update info. If any jobs have completed since the last `_status_new()` call, the flush operation aborts.

`new(func_or_exp, *args, **kwargs)`

Add a new background job and start it in a separate thread.

There are two types of jobs which can be created:

1. Jobs based on expressions which can be passed to an `eval()` call. The expression must be given as a string. For example:

```
job_manager.new(„myfunc(x,y,z=1)“,[glob[,loc]])
```

The given expression is passed to `eval()`, along with the optional global/local dicts provided. If no dicts are given, they are extracted automatically from the caller's frame.

A Python statement is NOT a valid `eval()` expression. Basically, you can only use as an `eval()` argument something which can go on the right of an „=“ sign and be assigned to a variable.

For example, »print „hello“« is not valid, but „2+3“ is.

2. Jobs given a function object, optionally passing additional positional arguments:

```
job_manager.new(myfunc, x, y)
```

The function is called with the given arguments.

If you need to pass keyword arguments to your function, you must supply them as a dict named `kw`:

```
job_manager.new(myfunc, x, y, kw=dict(z=1))
```

The reason for this asymmetry is that the `new()` method needs to maintain access to its own keywords, and this prevents name collisions between arguments to `new()` and arguments to your own functions.

In both cases, the result is stored in the `job.result` field of the background job object.

You can set `daemon` attribute of the thread by giving the keyword argument `daemon`.

Notes and caveats:

1. All threads running share the same standard output. Thus, if your background jobs generate output, it will come out on top of whatever you are currently writing. For this reason, background jobs are best used with silent functions which simply return their output.
2. Threads also all work within the same global namespace, and this system does not lock interactive variables. So if you send job to the background which operates on a mutable object for a long time, and start modifying that same mutable object interactively (or in another backgrounded job), all sorts of bizarre behaviour will occur.
3. If a background job is spending a lot of time inside a C extension module which does not release the Python Global Interpreter Lock (GIL), this will block the IPython prompt. This is simply because the Python interpreter can only switch between threads at Python bytecodes. While the execution is inside C code, the interpreter must simply wait unless the extension module releases the GIL.
4. There is no way, due to limitations in the Python threads library, to kill a thread once it has started.

`remove(num)`

Remove a finished (completed or dead) job.

`result(N)` → return the result of job N.

`status(verbose=0)`

Print a status of all jobs currently being managed.

`class IPython.lib.backgroundjobs.BackgroundJobBase`

Базовые классы: [Thread](#)

Base class to build BackgroundJob classes.

The derived classes must implement:

- Their own `__init__`, since the one here raises `NotImplementedError`. The derived constructor must call `self._init()` at the end, to provide common initialization.
- A `str`form attribute used in calls to `__str__`.
- A `call()` method, which will make the actual execution call and must return a value to be held in the „result“ field of the job object.

`__init__()`

Must be implemented in subclasses.

Subclasses must call `_init()` for standard initialisation.

`run()`

Method representing the thread's activity.

You may override this method in a subclass. The standard `run()` method invokes the callable object passed to the object's constructor as the target argument, if any, with sequential and keyword arguments taken from the `args` and `kwargs` arguments, respectively.

```
class IPython.lib.backgroundjobs.BackgroundJobExpr(expression, glob=None, loc=None)
```

Базовые классы: [BackgroundJobBase](#)

Evaluate an expression as a background job (uses a separate thread).

```
__init__(expression, glob=None, loc=None)
```

Create a new job from a string which can be fed to `eval()`.

global/locals dicts can be provided, which will be passed to the `eval` call.

```
class IPython.lib.backgroundjobs.BackgroundJobFunc(func, *args, **kwargs)
```

Базовые классы: [BackgroundJobBase](#)

Run a function call as a background job (uses a separate thread).

```
__init__(func, *args, **kwargs)
```

Create a new job from a callable object.

Any positional arguments and keyword args given to this constructor after the initial callable are passed directly to it.

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

8.44 Module: `lib.clipboard`

Utilities for accessing the platform's clipboard.

8.44.1 1 Class

```
class IPython.lib.clipboard.ClipboardEmpty
```

Базовые классы: [ValueError](#)

8.44.2 4 Functions

`IPython.lib.clipboard.win32_clipboard_get()`

Get the current clipboard's text on Windows.

Requires Mark Hammond's `pywin32` extensions.

`IPython.lib.clipboard.osx_clipboard_get()` → `str`

Get the clipboard's text on OS X.

`IPython.lib.clipboard.tkinter_clipboard_get()`

Get the clipboard's text using Tkinter.

This is the default on systems that are not Windows or OS X. It may interfere with other UI toolkits and should be replaced with an implementation that uses that toolkit.

`IPython.lib.clipboard.wayland_clipboard_get()`

Get the clipboard's text under Wayland using `wl-paste` command.

This requires Wayland and `wl-clipboard` installed and running.

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

8.45 Module: `lib.deepreload`

Provides a `reload()` function that acts recursively.

Python's normal `python:reload()` function only reloads the module that it's passed. The `reload()` function in this module also reloads everything imported from that module, which is useful when you're changing files deep inside a package.

To use this as your default reload function, type this:

```
import builtins
from IPython.lib import deepreload
builtins.reload = deepreload.reload
```

A reference to the original `python:reload()` is stored in this module as `original_reload`, so you can restore it later.

This code is almost entirely based on `knee.py`, which is a Python re-implementation of hierarchical module import.

8.45.1 9 Functions

`IPython.lib.deepreload.replace_import_hook(new_import)`

`IPython.lib.deepreload.get_parent(globals, level)`

parent, name = get_parent(globals, level)

Return the package that an import is being performed in. If `globals` comes from the module `foo.bar.bat` (not itself a package), this returns the `sys.modules` entry for `foo.bar`. If `globals` is from a package's `__init__.py`, the package's entry in `sys.modules` is returned.

If `globals` doesn't come from a package or a module in a package, or a corresponding entry is not found in `sys.modules`, `None` is returned.

`IPython.lib.deepreload.load_next(mod, altmod, name, buf)`

mod, name, buf = load_next(mod, altmod, name, buf)

altmod is either `None` or same as `mod`

`IPython.lib.deepreload.import_submodule(mod, subname, fullname)`

m = import_submodule(mod, subname, fullname)

`IPython.lib.deepreload.add_submodule(mod, submod, fullname, subname)`

mod.{subname} = submod

`IPython.lib.deepreload.ensure_fromlist(mod, fromlist, buf, recursive)`

Handle „from module import a, b, c“ imports.

`IPython.lib.deepreload.deep_import_hook(name, globals=None, locals=None, fromlist=None, level=-1)`

Replacement for `__import__()`

`IPython.lib.deepreload.deep_reload_hook(m)`

Replacement for `reload()`.

`IPython.lib.deepreload.reload(module, exclude=('_abc', '_ast', '_codecs', '_collections', '_functools', '_imp', '_io', '_locale', '_operator', '_signal', '_sre', '_stat', '_string', '_symtable', '_thread', '_tracemalloc', '_warnings', '_weakref', 'atexit', 'builtins', 'errno', 'faulthandler', 'gc', 'itertools', 'marshal', 'posix', 'pwd', 'sys', 'time', 'xxsubtype', 'sys', 'os.path', 'builtins', '__main__', 'numpy', 'numpy._globals'))`

Recursively reload all modules used in the given module. Optionally takes a list of modules to exclude from reloading. The default exclude list contains modules listed in `sys.builtin_module_names` with additional `sys`, `os.path`, `builtins` and `__main__`, to prevent, e.g., resetting display, exception, and io hooks.

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

8.46 Module: `lib.demo`

Module for interactive demos using IPython.


This module implements a few classes for running Python scripts interactively in IPython for demonstrations. With very simple markup (a few tags in comments), you can control points where the script stops executing and returns control to IPython.

8.46.1 Provided classes

The classes are (see their docstrings for further details):

- `Demo`: pure python demos
- `IPythonDemo`: demos with input to be processed by IPython as if it had been typed interactively (so magics work, as well as any other special syntax you may have added via input prefilters).
- `LineDemo`: single-line version of the `Demo` class. These demos are executed one line at a time, and require no markup.
- `IPythonLineDemo`: IPython version of the `LineDemo` class (the demo is executed a line at a time, but processed via IPython).
- `ClearMixin`: mixin to make `Demo` classes with less visual clutter. It declares an empty `marquee` and a `pre_cmd` that clears the screen before each block (see Subclassing below).
- `ClearDemo`, `ClearIPDemo`: mixin-enabled versions of the `Demo` and `IPythonDemo` classes.

Inheritance diagram:



8.46.2 Subclassing

The classes here all include a few methods meant to make customization by subclassing more convenient. Their docstrings below have some more details:

- `highlight()`: format every block and optionally highlight comments and docstring content.
- `marquee()`: generates a marquee to provide visible on-screen markers at each block start and end.
- `pre_cmd()`: run right before the execution of each block.
- `post_cmd()`: run right after the execution of each block. If the block raises an exception, this is NOT called.

8.46.3 Operation

The file is run in its own empty namespace (though you can pass it a string of arguments as if in a command line environment, and it will see those as `sys.argv`). But at each stop, the global IPython namespace is updated with the current internal demo namespace, so you can work interactively with the data accumulated so far.

By default, each block of code is printed (with syntax highlighting) before executing it and you have to confirm execution. This is intended to show the code to an audience first so you can discuss it, and only proceed with execution once you agree. There are a few tags which allow you to modify this behavior.

The supported tags are:

`# <demo> stop`

Defines block boundaries, the points where IPython stops execution of the file and returns to the interactive prompt.

You can optionally mark the stop tag with extra dashes before and after the word „stop“, to help visually distinguish the blocks in a text editor:

`# <demo> – stop –`

`# <demo> silent`

Make a block execute silently (and hence automatically). Typically used in cases where you have some boilerplate or initialization code which you need executed but do not want to be seen in the demo.

`# <demo> auto`

Make a block execute automatically, but still being printed. Useful for simple code which does not warrant discussion, since it avoids the extra manual confirmation.

`# <demo> auto_all`

This tag can `_only_` be in the first block, and if given it overrides the individual auto tags to make the whole demo fully automatic (no block asks for confirmation). It can also be given at creation time (or the attribute set later) to override what's in the file.

While `_any_` python file can be run as a Demo instance, if there are no stop tags the whole file will run in a single block (no different that calling first `%pycat` and then `%run`). The minimal markup to make this useful is to place a set of stop tags; the other tags are only there to let you fine-tune the execution.

This is probably best explained with the simple example file below. You can copy this into a file named `ex_demo.py`, and try running it via:

```
from IPython.lib.demo import Demo
d = Demo('ex_demo.py')
d()
```

Each time you call the demo object, it runs the next block. The demo object has a few useful methods for navigation, like `again()`, `edit()`, `jump()`, `seek()` and `back()`. It can be reset for a new run via `reset()` or reloaded from disk (in case you've edited the source) via `reload()`. See their docstrings below.

Note: To make this simpler to explore, a file called «demo-exercizer.py» has been added to the «docs/examples/core» directory. Just `cd` to this directory in an IPython session, and type:

```
%run demo-exercizer.py
```

and then follow the directions.

Пример

The following is a very simple example of a valid demo file.

```
##### EXAMPLE DEMO <ex_demo.py> #####
'''A simple interactive demo to illustrate the use of IPython's Demo class.'''

print('Hello, welcome to an interactive IPython demo.')

# The mark below defines a block boundary, which is a point where IPython will
# stop execution and return to the interactive prompt. The dashes are actually
# optional and used only as a visual aid to clearly separate blocks while
# editing the demo code.
# <demo> stop

x = 1
y = 2

# <demo> stop

# the mark below makes this block as silent
# <demo> silent

print('This is a silent block, which gets executed but not printed.')

# <demo> stop
# <demo> auto
print('This is an automatic block.')
print('It is executed without asking for confirmation, but printed.')
z = x + y

print('z =', x)

# <demo> stop
# This is just another normal block.
print('z is now:', z)
```

(continues on next page)

(продолжение с предыдущей страницы)

```
print('bye!')
##### END EXAMPLE DEMO <ex_demo.py> #####
```

8.46.4 8 Classes

```
class IPython.lib.demo.DemoError
```

Базовые классы: `Exception`

```
class IPython.lib.demo.Demo(src, title='', arg_str='', auto_all=None, format_rst=False,
                             formatter='terminal', style='default')
```

Базовые классы: `object`

```
__init__(src, title='', arg_str='', auto_all=None, format_rst=False, formatter='terminal',
          style='default')
```

Make a new demo object. To run the demo, simply call the object.

See the module docstring for full details and an example (you can use `IPython.Demo?` in IPython to see it).

Inputs:

- **src is either a file, or file-like object, or a** string that can be resolved to a filename.

Optional inputs:

- **title:** a string to use as the demo name. Of most use when the demo you are making comes from an object that has no filename, or if you want an alternate denotation distinct from the filename.
- **arg_str(„“):** a string of arguments, internally converted to a list just like `sys.argv`, so the demo script can see a similar environment.
- **auto_all(None):** global flag to run all blocks automatically without confirmation. This attribute overrides the block-level tags and applies to the whole demo. It is an attribute of the object, and can be changed at runtime simply by reassigning it to a boolean value.
- **format_rst(False):** a bool to enable comments and doc strings formatting with pygments rst lexer
- **formatter(„terminal“):** a string of pygments formatter name to be used. Useful values for terminals: `terminal`, `terminal256`, `terminal16m`
- **style(„default“):** a string of pygments style name to be used.

`again()`

Move the seek pointer back one block and re-execute.

`back(num=1)`

Move the seek pointer back num blocks (default is 1).

`edit(index=None)`

Edit a block.

If no number is given, use the last block executed.

This edits the in-memory copy of the demo, it does NOT modify the original source file. If you want to do that, simply open the file in an editor and use `reload()` when you make changes to

the file. This method is meant to let you change a block during a demonstration for explanatory purposes, without damaging your original script.

`fload()`

Load file object.

`highlight(block)`

Method called on each block to highlight its content

`jump(num=1)`

Jump a given number of blocks relative to the current one.

The offset can be positive or negative, defaults to 1.

`marquee(txt='', width=78, mark='*')`

Return the input string centered in a „marquee“.

`post_cmd()`

Method called after executing each block.

`pre_cmd()`

Method called before executing each block.

`reload()`

Reload source from disk and initialize state.

`reset()`

Reset the namespace and seek pointer to restart the demo

`run_cell(source)`

Execute a string with one or more lines of code

`seek(index)`

Move the current seek pointer to the given block.

You can use negative indices to seek from the end, with identical semantics to those of Python lists.

`show(index=None)`

Show a single block on screen

`show_all()`

Show entire demo on screen, block by block

```
class IPython.lib.demo.IPythonDemo(src, title='', arg_str='', auto_all=None, format_rst=False,
                                   formatter='terminal', style='default')
```

Базовые классы: [Demo](#)

Class for interactive demos with IPython's input processing applied.

This subclasses `Demo`, but instead of executing each block by the Python interpreter (via `exec`), it actually calls `IPython` on it, so that any input filters which may be in place are applied to the input block.

If you have an interactive environment which exposes special input processing, you can use this class instead to write demo scripts which operate exactly as if you had typed them interactively. The default `Demo` class requires the input to be valid, pure Python code.

`run_cell(source)`

Execute a string with one or more lines of code

```
class IPython.lib.demo.LineDemo(src, title='', arg_str='', auto_all=None, format_rst=False,
                               formatter='terminal', style='default')
```

Базовые классы: [Demo](#)

Demo where each line is executed as a separate block.

The input script should be valid Python code.

This class doesn't require any markup at all, and it's meant for simple scripts (with no nesting or any kind of indentation) which consist of multiple lines of input to be executed, one at a time, as if they had been typed in the interactive prompt.

Note: the input can not have *any* indentation, which means that only single-lines of input are accepted, not even function definitions are valid.

```
reload()
```

Reload source from disk and initialize state.

```
class IPython.lib.demo.IPythonLineDemo(src, title='', arg_str='', auto_all=None, format_rst=False,
                                       formatter='terminal', style='default')
```

Базовые классы: [IPythonDemo](#), [LineDemo](#)

Variant of the LineDemo class whose input is processed by IPython.

```
class IPython.lib.demo.ClearMixin
```

Базовые классы: [object](#)

Use this mixin to make Demo classes with less visual clutter.

Demos using this mixin will clear the screen before every block and use blank marquees.

Note that in order for the methods defined here to actually override those of the classes it's mixed with, it must go /first/ in the inheritance tree. For example:

```
class ClearIPDemo(ClearMixin,IPythonDemo): pass
```

will provide an IPythonDemo class with the mixin's features.

```
marquee(txt='', width=78, mark='*')
```

Blank marquee that returns „“ no matter what the input.

```
pre_cmd()
```

Method called before executing each block.

This one simply clears the screen.

```
class IPython.lib.demo.ClearDemo(src, title='', arg_str='', auto_all=None, format_rst=False,
                                 formatter='terminal', style='default')
```

Базовые классы: [ClearMixin](#), [Demo](#)

```
class IPython.lib.demo.ClearIPDemo(src, title='', arg_str='', auto_all=None, format_rst=False,
                                   formatter='terminal', style='default')
```

Базовые классы: [ClearMixin](#), [IPythonDemo](#)

8.46.5 2 Functions

```
IPython.lib.demo.re_mark(mark)
```

```
IPython.lib.demo.slide(file_path, noclear=False, format_rst=True, formatter='terminal',
                        style='native', auto_all=False, delimiter='...')
```

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

8.47 Module: lib.editorhooks

„editor“ hooks for common editors that work well with ipython

They should honor the line number argument, at least.

Contributions are *very* welcome.

8.47.1 11 Functions

```
IPython.lib.editorhooks.install_editor(template, wait=False)
```

Installs the editor that is called by IPython for the %edit magic.

This overrides the default editor, which is generally set by your EDITOR environment variable or is notepad (windows) or vi (linux). By supplying a template string `run_template`, you can control how the editor is invoked by IPython – (e.g. the format in which it accepts command line options)

Параметры

- `template` (*basestring*) – `run_template` acts as a template for how your editor is invoked by the shell. It should contain „{filename}“, which will be replaced on invocation with the file name, and „{line}“, \$line by line number (or 0) to invoke the file with.
- `wait` (*bool*) – If `wait` is true, wait until the user presses enter before returning, to facilitate non-blocking editors that exit immediately after the call.

```
IPython.lib.editorhooks.komodo(exe='komodo')
```

Activestate Komodo [Edit]

```
IPython.lib.editorhooks.scite(exe='scite')
```

SciTE or Sc1

```
IPython.lib.editorhooks.notepadplusplus(exe='notepad++')
```

Notepad++ <http://notepad-plus.sourceforge.net>

```
IPython.lib.editorhooks.jed(exe='jed')
```

JED, the lightweight emacsish editor

```
IPython.lib.editorhooks.idle(exe='idle')
```

Idle, the editor bundled with python

Параметры

`exe` (*str*, *None*) – If none, should be pretty smart about finding the executable.

```
IPython.lib.editorhooks.mate(exe='mate')
```

TextMate, the missing editor

```
IPython.lib.editorhooks.emacs(exe='emacs')
```

```
IPython.lib.editorhooks.gnuclient(exe='gnuclient')
```

```
IPython.lib.editorhooks.crimson_editor(exe='cedt.exe')
```

```
IPython.lib.editorhooks.kate(exe='kate')
```

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

8.48 Module: `lib.guisupport`

Support for creating GUI apps and starting event loops.

IPython's GUI integration allows interactive plotting and GUI usage in IPython session. IPython has two different types of GUI integration:

1. The terminal based IPython supports GUI event loops through Python's `PyOS_InputHook`. `PyOS_InputHook` is a hook that Python calls periodically whenever `raw_input` is waiting for a user to type code. We implement GUI support in the terminal by setting `PyOS_InputHook` to a function that iterates the event loop for a short while. It is important to note that in this situation, the real GUI event loop is NOT run in the normal manner, so you can't use the normal means to detect that it is running.
2. In the two process IPython kernel/frontend, the GUI event loop is run in the kernel. In this case, the event loop is run in the normal manner by calling the function or method of the GUI toolkit that starts the event loop.

In addition to starting the GUI event loops in one of these two ways, IPython will *always* create an appropriate GUI application object when GUI integration is enabled.

If you want your GUI apps to run in IPython you need to do two things:

1. Test to see if there is already an existing main application object. If there is, you should use it. If there is not an existing application object you should create one.

2. Test to see if the GUI event loop is running. If it is, you should not start it. If the event loop is not running you may start it.

This module contains functions for each toolkit that perform these things in a consistent manner. Because of how PyOS_InputHook runs the event loop you cannot detect if the event loop is running using the traditional calls (such as `wx.GetApp.IsMainLoopRunning()` in `wxPython`). If `PyOS_InputHook` is set These methods will return a false negative. That is, they will say the event loop is not running, when is actually is. To work around this limitation we proposed the following informal protocol:

- Whenever someone starts the event loop, they *must* set the `_in_event_loop` attribute of the main application object to `True`. This should be done regardless of how the event loop is actually run.
- Whenever someone stops the event loop, they *must* set the `_in_event_loop` attribute of the main application object to `False`.
- If you want to see if the event loop is running, you *must* use `hasattr` to see if `_in_event_loop` attribute has been set. If it is set, you *must* use its value. If it has not been set, you can query the toolkit in the normal manner.
- If you want GUI support and no one else has created an application or started the event loop you *must* do this. We don't want projects to attempt to defer these things to someone else if they themselves need it.

The functions below implement this logic for each GUI toolkit. If you need to create custom application subclasses, you will likely have to modify this code for your own purposes. This code can be copied into your own project so you don't have to depend on IPython.

8.48.1 6 Functions

```
IPython.lib.guisupport.get_app_wx(*args, **kwargs)
```

Create a new wx app or return an exiting one.

```
IPython.lib.guisupport.is_event_loop_running_wx(app=None)
```

Is the wx event loop running.

```
IPython.lib.guisupport.start_event_loop_wx(app=None)
```

Start the wx event loop in a consistent manner.

```
IPython.lib.guisupport.get_app_qt4(*args, **kwargs)
```

Create a new Qt app or return an existing one.

```
IPython.lib.guisupport.is_event_loop_running_qt4(app=None)
```

Is the qt event loop running.

```
IPython.lib.guisupport.start_event_loop_qt4(app=None)
```

Start the qt event loop in a consistent manner.

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

8.49 Module: lib.latextools

Tools for handling LaTeX.

8.49.1 1 Class

`class IPython.lib.latextools.LaTeXTool(**kwargs: Any)`

Базовые классы: `SingletonConfigurable`

An object to store configuration of the LaTeX tool.

backends

Preferred backend to draw LaTeX math equations. Backends in the list are checked one by one and the first usable one is used. Note that `matplotlib` backend is usable only for inline style equations. To draw display style equations, `dvipng` backend must be specified.

packages

A list of packages to use for `dvipng` backend. „breqn“ will be automatically appended when `use_breqn=True`.

preamble

Additional preamble to use when generating LaTeX source for `dvipng` backend.

use_breqn

Use `breqn.sty` to automatically break long equations. This configuration takes effect only for `dvipng` backend.

8.49.2 6 Functions

`IPython.lib.latextools.latex_to_png(s, encode=False, backend=None, wrap=False, color='Black', scale=1.0)`

Render a LaTeX string to PNG.

Параметры

- `s` (*str*) – The raw string containing valid inline LaTeX.
- `encode` (*bool*, *optional*) – Should the PNG data base64 encoded to make it JSON’able.
- `backend` (*{matplotlib, dvipng}*) – Backend for producing PNG data.
- `wrap` (*bool*) – If true, Automatically wrap `s` as a LaTeX equation.
- `color` (*string*) – Foreground color name among dvipsnames, e.g. „Maroon“ or on hex RGB format, e.g. „#AA20FA“.
- `scale` (*float*) – Scale factor for the resulting PNG.
- `used`. (*None is returned when the backend cannot be*) –

`IPython.lib.latextools.latex_to_png_mpl(s, wrap, color='Black', scale=1.0)`

`IPython.lib.latextools.latex_to_png_dvipng(s, wrap, color='Black', scale=1.0)`

`IPython.lib.latextools.kpsewhich(filename)`

Invoke `kpsewhich` command with an argument `filename`.

`IPython.lib.latextools.genelatem(body, wrap)`

Generate LaTeX document for dvipng backend.

`IPython.lib.latextools.latex_to_html(s, alt='image')`

Render LaTeX to HTML with embedded PNG data using data URIs.

Параметры

- `s` (*str*) – The raw string containing valid inline LaTeX.
- `alt` (*str*) – The alt text to use for the HTML.

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

8.50 Module: `lib.lexers`

Defines a variety of Pygments lexers for highlighting IPython code.

This includes:

IPythonLexer, IPython3Lexer

Lexers for pure IPython (python + magic/shell commands)

IPythonPartialTracebackLexer, IPythonTracebackLexer

Supports 2.x and 3.x via keyword `python3`. The partial traceback lexer reads everything but the Python code appearing in a traceback. The full lexer combines the partial lexer with an IPython lexer.

IPythonConsoleLexer

A lexer for IPython console sessions, with support for tracebacks.

IPyLexer

A friendly lexer which examines the first line of text and from it, decides whether to use an IPython lexer or an IPython console lexer. This is probably the only lexer that needs to be explicitly added to Pygments.

8.50.1 4 Classes

```
class IPython.lib.lexers.IPythonPartialTracebackLexer(*args, **kwargs)
```

Базовые классы: `RegexLexer`

Partial lexer for IPython tracebacks.

Handles all the non-python output.

`name = 'IPython Partial Traceback'`

Name of the lexer

```
tokens = {'root': [(r'^(\\^C)?(-+\\n)', <function bygroups.<locals>.callback>), (r'^(
File)(.*) (, line )(\\d+\\n)', <function bygroups.<locals>.callback>),
(r'(?u)(^\\d\\W\\w*)(\\s*)(Traceback.*?\\n)', <function
bygroups.<locals>.callback>), (r'(.*) ( in )(.*)\\(\\.(.*\\)\\n)', <function
bygroups.<locals>.callback>), (r'(\\s*)(\\d+)(.*?\\n)', <function
bygroups.<locals>.callback>), (r'(->?\\s*)(\\d+)(.*?\\n)', <function
bygroups.<locals>.callback>), (r'(?u)(^\\d\\W\\w*)(:.*?\\n)', <function
bygroups.<locals>.callback>), (r'.*\\n', Token.Other)]}
```

At all time there is a stack of states. Initially, the stack contains a single state „root“. The top of the stack is called «the current state».

Dict of `{'state': [(regex, tokentype, new_state), ...], ...}`

`new_state` can be omitted to signify no state transition. If `new_state` is a string, it is pushed on the stack. This ensure the new current state is `new_state`. If `new_state` is a tuple of strings, all of those strings are pushed on the stack and the current state will be the last element of the list. `new_state` can also be combined(`'state1', 'state2', ...`) to signify a new, anonymous state combined from the rules of two or more existing ones. Furthermore, it can be „`#pop`“ to signify going back one step in the state stack, or „`#push`“ to push the current state on the stack again. Note that if you push while in a combined state, the combined state itself is pushed, and not only the state in which the rule is defined.

The tuple can also be replaced with `include('state')`, in which case the rules from the state named by the string are included in the current one.

```
class IPython.lib.lexers.IPythonTracebackLexer(**options)
```

Базовые классы: `DelegatingLexer`

IPython traceback lexer.

For doctests, the tracebacks can be snipped as much as desired with the exception to the lines that designate a traceback. For non-syntax error tracebacks, this is the line of hyphens. For syntax error tracebacks, this is the line which lists the File and line number.

```
__init__(**options)
```

A subclass of `DelegatingLexer` which delegates to the appropriate to either `IPyLexer`, `IPythonPartialTracebackLexer`.

`aliases = ['ipythontb']`

Shortcuts for the lexer

`name = 'IPython Traceback'`

Name of the lexer

```
class IPython.lib.lexers.IPythonConsoleLexer(**options)
```

Базовые классы: `Lexer`

An IPython console lexer for IPython code-blocks and doctests, such as:

```
.. code-block:: ipythonconsole

    In [1]: a = 'foo'

In [2]:     a
Out[2]: 'foo'

In [3]: p     rint(a)
foo
```

Support is also provided for IPython exceptions:

```
.. code-block:: ipythonconsole

    In [1]: raise Exception
    Traceback (most recent call last):
    ...
Exce      ptio      n
```

`__init__(**options)`

Initialize the IPython console lexer.

Параметры

- `python3` (*bool*) – If `True`, then the console inputs are parsed using a Python 3 lexer. Otherwise, they are parsed using a Python 2 lexer.
- `in1_regex` (*RegexObject*) – The compiled regular expression used to detect the start of inputs. Although the IPython configuration setting may have a trailing whitespace, do not include it in the regex. If `None`, then the default input prompt is assumed.
- `in2_regex` (*RegexObject*) – The compiled regular expression used to detect the continuation of inputs. Although the IPython configuration setting may have a trailing whitespace, do not include it in the regex. If `None`, then the default input prompt is assumed.
- `out_regex` (*RegexObject*) – The compiled regular expression used to detect outputs. If `None`, then the default output prompt is assumed.

`aliases = ['ipythonconsole']`

Shortcuts for the lexer

`buffered_tokens()`

Generator of unprocessed tokens after doing insertions and before changing to a new state.

`get_mci(line)`

Parses the line and returns a 3-tuple: (mode, code, insertion).

`mode` is the next mode (or state) of the lexer, and is always equal to „input“, „output“, or „tb“.

`code` is a portion of the line that should be added to the buffer corresponding to the next mode and eventually lexed by another lexer. For example, `code` could be Python code if `mode` were „input“.

`insertion` is a 3-tuple (index, token, text) representing an unprocessed «token» that will be inserted into the stream of tokens that are created from the buffer once we change modes. This is usually the input or output prompt.

In general, the next mode depends on current mode and on the contents of `line`.

`get_tokens_unprocessed(text)`

Return an iterable of (index, tokentype, value) pairs where «index» is the starting position of the token within the input text.

In subclasses, implement this method as a generator to maximize effectiveness.

`ipytb_start = re.compile('^(\\^C)?(-+\\n)|^(File)(.*)(, line)(\\d+\\n)')`

The regex to determine when a traceback starts.

`mimetypes = ['text/x-ipython-console']`

MIME types

`name = 'IPython console session'`

Name of the lexer

`class IPython.lib.lexers.IPyLexer(**options)`

Базовые классы: `Lexer`

Primary lexer for all IPython-like code.

This is a simple helper lexer. If the first line of the text begins with «In [[0-9]+]:», then the entire text is parsed with an IPython console lexer. If not, then the entire text is parsed with an IPython lexer.

The goal is to reduce the number of lexers that are registered with Pygments.

`__init__(**options)`

Create a new IPyLexer instance which dispatch to either an IPythonCONsoleLexer (if In prompts are present) or and IPythonLexer (if In prompts are not present).

`aliases = ['ipy']`

Shortcuts for the lexer

`get_tokens_unprocessed(text)`

Return an iterable of (index, tokentype, value) pairs where «index» is the starting position of the token within the input text.

In subclasses, implement this method as a generator to maximize effectiveness.

`name = 'IPy session'`

Name of the lexer

8.50.2 1 Function

`IPython.lib.lexers.build_ipy_lexer(python3)`

Builds IPython lexers depending on the value of `python3`.

The lexer inherits from an appropriate Python lexer and then adds information about IPython specific keywords (i.e. magic commands, shell commands, etc.)

Параметры

`python3 (bool)` – If True, then build an IPython lexer from a Python 3 lexer.

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

8.51 Module: `lib.pretty`

Python advanced pretty printer. This pretty printer is intended to replace the old `pprint` python module which does not allow developers to provide their own pretty print callbacks.

This module is based on ruby's `prettyprint.rb` library by Tanaka Akira.

8.51.1 Example Usage

To directly print the representation of an object use `pprint`:

```
from pretty import pprint
pprint(complex_object)
```

To get a string of the output use `pretty`:

```
from pretty import pretty
string = pretty(complex_object)
```

8.51.2 Extending

The pretty library allows developers to add pretty printing rules for their own objects. This process is straightforward. All you have to do is to add a `_repr_pretty_` method to your object and call the methods on the pretty printer passed:

```
class MyObject(object):

    def _repr_pretty_(self, p, cycle):
        ...
```

Here's an example for a class with a simple constructor:

```
class MySimpleObject:

    def __init__(self, a, b, *, c=None):
        self.a = a
        self.b = b
        self.c = c

    def _repr_pretty_(self, p, cycle):
        ctor = CallExpression.factory(self.__class__.__name__)
        if self.c is None:
            p.pretty(ctor(a, b))
```

(continues on next page)

(продолжение с предыдущей страницы)

```

else:
    p.pretty(ctor(a, b, c=c))

```

Here is an example implementation of a `_repr_pretty_` method for a list subclass:

```

class MyList(list):

    def _repr_pretty_(self, p, cycle):
        if cycle:
            p.text('MyList(...)')
        else:
            with p.group(8, 'MyList([', '])'):
                for idx, item in enumerate(self):
                    if idx:
                        p.text(',')
                        p.breakable()
                    p.pretty(item)

```

The `cycle` parameter is `True` if pretty detected a cycle. You *have* to react to that or the result is an infinite loop. `p.text()` just adds non breaking text to the output, `p.breakable()` either adds a whitespace or breaks here. If you pass it an argument it's used instead of the default space. `p.pretty` prettyprints another object using the pretty print method.

The first parameter to the `group` function specifies the extra indentation of the next line. In this example the next item will either be on the same line (if the items are short enough) or aligned with the right edge of the opening bracket of `MyList`.


If you just want to indent something you can use the `group` function without open / close parameters. You can also use this code:

```

with p.indent(2):
    ...

```

Inheritance diagram:

**copyright**

2007 by Armin Ronacher. Portions (c) 2009 by Robert Kern.

license

BSD License.

8.51.3 10 Classes

```
class IPython.lib.pretty.PrettyPrinter(output, max_width=79, newline='\n',
                                       max_seq_length=1000)
```

Базовые классы: `_PrettyPrinterBase`

Baseclass for the `RepresentationPrinter` prettyprinter that is used to generate pretty reprs of objects. Contrary to the `RepresentationPrinter` this printer knows nothing about the default pprinters or the `_repr_pretty_` callback method.

```
__init__(output, max_width=79, newline='\n', max_seq_length=1000)
```

```
begin_group(indent=0, open='')
```

Begin a group. The first parameter specifies the indentation for the next line (usually the width of the opening text), the second the opening text. All parameters are optional.

```
break_()
```

Explicitly insert a newline into the output, maintaining correct indentation.

```
breakable(sep=' ')
```

Add a breakable separator to the output. This does not mean that it will automatically break here. If no breaking on this position takes place the `sep` is inserted which default to one space.

```
end_group(dedent=0, close='')
```

End a group. See `begin_group` for more details.

```
flush()
```

Flush data that is left in the buffer.

```
text(obj)
```

Add literal text to the output.

```
class IPython.lib.pretty.RepresentationPrinter(output, verbose=False, max_width=79,
                                              newline='\n', singleton_pprinters=None,
                                              type_pprinters=None, deferred_pprinters=None,
                                              max_seq_length=1000)
```

Базовые классы: *PrettyPrinter*

Special pretty printer that has a `pretty` method that calls the pretty printer for a python object.

This class stores processing data on `self` so you must *never* use this class in a threaded environment. Always lock it or reinstantiate it.

Instances also have a verbose flag callbacks can access to control their output. For example the default instance repr prints all attributes and methods that are not prefixed by an underscore if the printer is in verbose mode.

```
__init__(output, verbose=False, max_width=79, newline='\n', singleton_pprinters=None,
        type_pprinters=None, deferred_pprinters=None, max_seq_length=1000)
```

```
pretty(obj)
```

Pretty print the given object.

```
class IPython.lib.pretty.Printable
```

Базовые классы: *object*

```
class IPython.lib.pretty.Text
```

Базовые классы: *Printable*

```
__init__()
```

```
class IPython.lib.pretty.Breakable(seq, width, pretty)
```

Базовые классы: *Printable*

```
__init__(seq, width, pretty)
```

```
class IPython.lib.pretty.Group(depth)
```

Базовые классы: *Printable*

```
__init__(depth)
```

```
class IPython.lib.pretty.GroupQueue(*groups)
```

Базовые классы: *object*

```
__init__(*groups)
```

```
class IPython.lib.pretty.RawText(value)
```

Базовые классы: `object`

Object such that `p.pretty(RawText(value))` is the same as `p.text(value)`.

An example usage of this would be to show a list as binary numbers, using `p.pretty([RawText(bin(i)) for i in integers])`.

```
__init__(value)
```

```
class IPython.lib.pretty.CallExpression(_ CallExpression__ name, *args, **kwargs)
```

Базовые классы: `object`

Object which emits a line-wrapped call expression in the form `__name__(*args, **kwargs)`

```
__init__( _ CallExpression__ name, *args, **kwargs)
```

```
class IPython.lib.pretty.RawStringLiteral(value)
```

Базовые классы: `object`

Wrapper that shows a string with a `r` prefix

```
__init__(value)
```

8.51.4 4 Functions

```
IPython.lib.pretty.pretty(obj, verbose=False, max_width=79, newline='\n', max_seq_length=1000)
```

Pretty print the object's representation.

```
IPython.lib.pretty.pprint(obj, verbose=False, max_width=79, newline='\n', max_seq_length=1000)
```

Like `pretty` but print to `stdout`.

```
IPython.lib.pretty.for_type(typ, func)
```

Add a pretty printer for a given type.

```
IPython.lib.pretty.for_type_by_name(type_module, type_name, func)
```

Add a pretty printer for a type specified by the module and name of a type rather than the type object itself.

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

8.52 Module: paths

Find files and directories which IPython uses.

8.52.1 5 Functions

`IPython.paths.get_ipython_dir()` → `str`

Get the IPython directory for this platform and user.

This uses the logic in `get_home_dir` to find the home directory and then adds `.ipython` to the end of the path.

`IPython.paths.get_ipython_cache_dir()` → `str`

Get the cache directory it is created if it does not exist.

`IPython.paths.get_ipython_package_dir()` → `str`

Get the base directory where IPython itself is installed.

`IPython.paths.get_ipython_module_path(module_str)`

Find the path to an IPython module in this version of IPython.

This will always find the version of the module that is in this importable IPython package. This will always return the path to the `.py` version of the module.

`IPython.paths.locate_profile(profile='default')`

Find the path to the folder associated with a given profile.

I.e. find `$IPYTHONDIR/profile_whatever`.

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

8.53 Module: terminal.debugger

8.53.1 1 Class

`class IPython.terminal.debugger.TerminalPdb(*args, pt_session_options=None, **kwargs)`

Базовые классы: `Pdb`

Standalone IPython debugger.

`__init__(*args, pt_session_options=None, **kwargs)`

Create a new IPython debugger.

Параметры

- `completekey` (*default None*) – Passed to `pdb.Pdb`.
- `stdin` (*default None*) – Passed to `pdb.Pdb`.
- `stdout` (*default None*) – Passed to `pdb.Pdb`.
- `context` (*int*) – Number of lines of source code context to show when displaying stacktrace information.
- `**kwargs` – Passed to `pdb.Pdb`.

Заметки

The possibilities are python version dependent, see the python docs for more info.

`cmdloop(intro=None)`

Repeatedly issue a prompt, accept input, parse an initial prefix off the received input, and dispatch to action methods, passing them the remainder of the line as argument.

override the same methods from `cmd.Cmd` to provide prompt toolkit replacement.

`do_interact(arg)`

`interact`

Start an interactive interpreter whose global namespace contains all the (global and local) names found in the current scope.

`pt_init(pt_session_options=None)`

Initialize the prompt session and the prompt loop and store them in `self.pt_app` and `self.pt_loop`.

Additional keyword arguments for the `PromptSession` class can be specified in `pt_session_options`.

8.53.2 1 Function

`IPython.terminal.debugger.set_trace(frame=None)`

Start debugging from `frame`.

If `frame` is not specified, debugging starts from caller's frame.

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

8.54 Module: terminal.embed

An embedded IPython shell.

8.54.1 3 Classes

```
class IPython.terminal.embed.KillEmbedded
```

Базовые классы: *Exception*

```
class IPython.terminal.embed.EmbeddedMagics(**kwargs: Any)
```

Базовые классы: *Magics*

```
exit_raise(parameter_s='')
```

%exit_raise Make the current embedded kernel exit and raise an exception.

This function sets an internal flag so that an embedded IPython will raise a `IPython.terminal.embed.KillEmbedded` Exception on exit, and then exit the current I. This is useful to permanently exit a loop that creates an IPython embed instance.

```
kill_embedded(parameter_s='')
```

```
%kill_embedded [-i] [-x] [-y]
```

%kill_embedded : deactivate for good the current embedded IPython

This function (after asking for confirmation) sets an internal flag so that an embedded IPython will never activate again for the given call location. This is useful to permanently disable a shell that is being called inside a loop: once you've figured out what you needed from it, you may then kill it and the program will then continue to run without the interactive shell interfering again.

Kill Instance Option:

If for some reasons you need to kill the location where the instance is created and not called, for example if you create a single instance in one place and debug in many locations, you can use the `--instance` option to kill this specific instance. Like for the `call location` killing an «instance» should work even if it is recreated within a loop.

Примечание: This was the default behavior before IPython 5.2

options:

<code>-i, --instance</code>	Kill instance instead of call location
<code>-x, --exit</code>	Also exit the current session
<code>-y, --yes</code>	Do not ask confirmation

```
class IPython.terminal.embed.InteractiveShellEmbed(**kwargs: Any)
```

Базовые классы: *TerminalInteractiveShell*

```
__init__(**kw)
```

Create a configurable given a config object.

Параметры

- `config` (*Config*) – If this is empty, default values are used. If `config` is a `Config` instance, it will be used to configure the instance.
- `parent` (*Configurable instance, optional*) – The parent `Configurable` instance of this object.

Заметки

Subclasses of `Configurable` must call the `__init__()` method of `Configurable` *before* doing anything else and using `super()`:

```
class MyConfigurable(Configurable):
    def __init__(self, config=None):
        super(MyConfigurable, self).__init__(config=config)
        # Then any other code you need to finish initialization.
```

This ensures that instances will be configured properly.

`init_sys_modules()`

Explicitly overwrite `IPython.core.interactiveshell` to do nothing.

`mainloop(local_ns=None, module=None, stack_depth=0, compile_flags=None)`

Embeds IPython into a running python program.

Параметры

- `local_ns` – Working local namespace (a dict) and module (a module or similar object). If given as `None`, they are automatically taken from the scope where the shell was called, so that program variables become visible.
- `module` – Working local namespace (a dict) and module (a module or similar object). If given as `None`, they are automatically taken from the scope where the shell was called, so that program variables become visible.
- `stack_depth` (*int*) – How many levels in the stack to go to looking for namespaces (when `local_ns` or `module` is `None`). This allows an intermediate caller to make sure that this function gets the namespace from the intended level in the stack. By default (0) it will get its locals and globals from the immediate caller.
- `compile_flags` – A bit field identifying the `__future__` features that are enabled, as passed to the builtin `compile()` function. If given as `None`, they are automatically taken from the scope where the shell was called.

`term_title`

Automatically set the terminal title

8.54.2 1 Function

`IPython.terminal.embed.embed(*, header='', compile_flags=None, **kwargs)`

Call this to embed IPython at the current point in your program.

The first invocation of this will create a `terminal.embed.InteractiveShellEmbed` instance and then call it. Consecutive calls just call the already created instance.

If you don't want the kernel to initialize the namespace from the scope of the surrounding function, and/or you want to load full IPython configuration, you probably want `IPython.start_ipython()` instead.

Here is a simple example:

```
from IPython import embed
a = 10
b = 20
embed(header='First time')
c = 30
d = 40
embed()
```

Параметры

- `header` (*str*) – Optional header string to print at startup.
- `compile_flags` – Passed to the `compile_flags` parameter of `terminal.embed.InteractiveShellEmbed.mainloop()`, which is called when the `terminal.embed.InteractiveShellEmbed` instance is called.
- `**kwargs` (*various, optional*) – Any other kwargs will be passed to the `terminal.embed.InteractiveShellEmbed` constructor. Full customization can be done by passing a traitlets `Config` in as the `config` argument (see *Running IPython from Python* and *Terminal IPython options*).

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

8.55 Module: `terminal.interactiveshell`

IPython terminal interface using `prompt_toolkit`

8.55.1 2 Classes

```
class IPython.terminal.interactiveshell.PtkHistoryAdapter(shell)
```

Базовые классы: `History`

Prompt toolkit has it's own way of handling history, Where it assumes it can Push/pull from history.

```
__init__(shell)
```

```
append_string(string)
```

Add string to the history.

`load_history_strings()`

This should be a generator that yields `str` instances.

It should yield the most recent items first, because they are the most important. (The history can already be used, even when it's only partially loaded.)

`store_string(string: str) → None`

Store the string in persistent storage.

`class IPython.terminal.interactiveshell.TerminalInteractiveShell(**kwargs: Any)`

Базовые классы: *InteractiveShell*

`__init__(*args, **kwargs) → None`

Create a configurable given a config config.

Параметры

- `config (Config)` – If this is empty, default values are used. If config is a `Config` instance, it will be used to configure the instance.
- `parent (Configurable instance, optional)` – The parent `Configurable` instance of this object.

Заметки

Subclasses of `Configurable` must call the `__init__()` method of `Configurable` *before* doing anything else and using `super()`:

```
class MyConfigurable(Configurable):
    def __init__(self, config=None):
        super(MyConfigurable, self).__init__(config=config)
        # Then any other code you need to finish initialization.
```

This ensures that instances will be configured properly.

`auto_match`

Automatically add/delete closing bracket or quote when opening bracket or quote is entered/deleted. Brackets: `()`, `[]`, `{}` Quotes: `„`, `»`

`auto_rewrite_input(cmd)`

Overridden from the parent class to use fancy rewriting prompt

`autoformatter`

Autoformatter to reformat Terminal code. Can be `'black'`, `'yapf'` or `None`

`autosuggestions_provider`

Specifies from which source automatic suggestions are provided. Can be set to `'NavigableAutoSuggestFromHistory'` (up and down swap suggestions), `'AutoSuggestFromHistory'`, or `None` to disable automatic suggestions. Default is `'NavigableAutoSuggestFromHistory'`.

`confirm_exit`

Set to confirm when you try to exit IPython with an EOF (Control-D in Unix, Control-Z/Enter in Windows). By typing `„exit“` or `„quit“`, you can force a direct exit without any confirmation.

`property debugger_cls`

Version of debugger where `KeyboardInterrupt` exits the debugger altogether.

debugger_history_file

File in which to store and read history

display_completions

Options for displaying tab completions, „column“, „multicolumn“, and „readlinelike“. These options are for `prompt_toolkit`, see `prompt_toolkit` documentation for more information.

editing_mode

Shortcut style to use at the prompt. „vi“ or „emacs“.

editor

Set the editor used by IPython (default to `$EDITOR/vi/notepad`).

emacs_bindings_in_vi_insert_mode

Add shortcuts from „emacs“ insert mode to „vi“ insert mode.

enable_history_search

Allows to enable/disable the prompt toolkit history search

extra_open_editor_shortcuts

Enable vi (v) or Emacs (C-X C-E) shortcuts to open an external editor. This is in addition to the F2 binding, which is always enabled.

handle_return

Provide an alternative handler to be called when the user presses Return. This is an advanced option intended for debugging, which may be changed or removed in later releases.

highlight_matching_brackets

Highlight matching brackets.

highlighting_style

The name or class of a Pygments style to use for syntax highlighting. To see available styles, run `pygmentize -L styles`.

highlighting_style_overrides

Override highlighting format for specific tokens

modal_cursor

beam in vi insert mode, block in nav mode, underscore in replace mode.

Type

Cursor shape changes depending on vi mode

mouse_support

Enable mouse support in the prompt (Note: prevents selecting text with the mouse)

prompt_includes_vi_mode

Display the current vi mode (when using vi editing mode).

prompts_class

Class used to generate Prompt token for `prompt_toolkit`

shortcuts

Add, disable or modifying shortcuts.

Each entry on the list should be a dictionary with `command` key identifying the target function executed by the shortcut and at least one of the following:

- `match_keys`: list of keys used to match an existing shortcut,

- `match_filter`: shortcut filter used to match an existing shortcut,
- `new_keys`: list of keys to set,
- `new_filter`: a new shortcut filter to set

The filters have to be composed of pre-defined verbs and joined by one of the following conjunctions: `&` (and), `|` (or), `~` (not). The pre-defined verbs are:

- `always`
- `never`
- `has_line_below`
- `has_line_above`
- `has_selection`
- `has_suggestion`
- `vi_mode`
- `vi_insert_mode`
- `emacs_insert_mode`
- `emacs_like_insert_mode`
- `has_completions`
- `insert_mode`
- `default_buffer_focused`
- `search_buffer_focused`
- `ebivim`
- `supports_suspend`
- `is_windows_os`
- `auto_match`
- `focused_insert`
- `not_inside_unclosed_string`
- `readline_like_completions`
- `preceded_by_paired_double_quotes`
- `preceded_by_paired_single_quotes`
- `preceded_by_raw_str_prefix`
- `preceded_by_two_double_quotes`
- `preceded_by_two_single_quotes`
- `followed_by_closing_paren_or_end`
- `preceded_by_opening_round_paren`
- `preceded_by_opening_bracket`
- `preceded_by_opening_brace`
- `preceded_by_double_quote`

- `preceded_by_single_quote`
- `followed_by_closing_round_paren`
- `followed_by_closing_bracket`
- `followed_by_closing_brace`
- `followed_by_double_quote`
- `followed_by_single_quote`
- `navigable_suggestions`
- `cursor_in_leading_ws`

To disable a shortcut set `new_keys` to an empty list. To add a shortcut add key `create` with value `True`.

When modifying/disabling shortcuts, `match_keys`/`match_filter` can be omitted if the provided specification uniquely identifies a shortcut to be modified/disabled. When modifying a shortcut `new_filter` or `new_keys` can be omitted which will result in reuse of the existing filter/keys.

Only shortcuts defined in IPython (and not default prompt-toolkit shortcuts) can be modified or disabled. The full list of shortcuts, command identifiers and filters is available under [IPython shortcuts](#).

`simple_prompt`

Use `raw_input` for the REPL, without completion and prompt colors.

Useful when controlling IPython as a subprocess, and piping STDIN/OUT/ERR. Known usage are: IPython own testing machinery, and emacs inferior-shell integration through elpy.

This mode default to `True` if the `IPY_TEST_SIMPLE_PROMPT` environment variable is set, or the current terminal is not a tty.

`space_for_menu`

Number of line at the bottom of the screen to reserve for the tab completion menu, search history, ...etc, the height of these menus will at most this value. Increase it is you prefer long and skinny menus, decrease for short and wide.

`switch_doctest_mode(mode)`

Switch prompts to classic for `%doctest_mode`

`system(cmd)`

Call the given `cmd` in a subprocess using `os.system` on Windows or `subprocess.call` using the system shell on other platforms.

Параметры

`cmd` (*str*) – Command to execute.

`term_title`

Automatically set the terminal title

`term_title_format`

{`cwd`}.

Type

Customize the terminal title format. This is a python format string. Available substitutions are

`timeoutlen`

The time in milliseconds that is waited for a mapped key sequence to complete.

`true_color`

Use 24bit colors instead of 256 colors in prompt highlighting. If your terminal supports true color, the following command should print `TRUECOLOR` in orange:

```
printf "\x1b[38;2;255;100;0mTRUECOLOR\x1b[0m\n"
```

`ttimeoutlen`

The time in milliseconds that is waited for a key code to complete.

8.55.2 3 Functions

`IPython.terminal.interactiveshell.get_default_editor()`

`IPython.terminal.interactiveshell.black_reformat_handler(text_before_cursor)`

We do not need to protect against error, this is taken care at a higher level where any reformat error is ignored. Indeed we may call reformatting on incomplete code.

`IPython.terminal.interactiveshell.yapf_reformat_handler(text_before_cursor)`

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

8.56 Module: `terminal.ipapp`

The `Application` object for the command line `ipython` program.

8.56.1 3 Classes

`class IPython.terminal.ipapp.IAppCrashHandler(app)`

Базовые классы: `CrashHandler`

`sys.excepthook` for IPython itself, leaves a detailed report on disk.

`__init__(app)`

Create a new crash handler

Параметры

- `app` (*Application*) – A running *Application* instance, which will be queried at crash time for internal information.

- `contact_name` (*str*) – A string with the name of the person to contact.
- `contact_email` (*str*) – A string with the email address of the contact.
- `bug_tracker` (*str*) – A string with the URL for your project’s bug tracker.
- `show_crash_traceback` (*bool*) – If false, don’t print the crash traceback on stderr, only generate the on-disk report
- `call_pdb` – Whether to call pdb on crash

These instances contain some non-argument attributes which allow for further customization of the crash handler's behavior. Please see the source for further details.

`make_report(traceback)`

Return a string containing a crash report.

`class IPython.terminal.ipapp.LocateIPythonApp(**kwargs: Any)`

Базовые классы: *BaseIPythonApplication*

`start()`

Start the app mainloop.

Override in subclasses.

`class IPython.terminal.ipapp.TerminalIPythonApp(**kwargs: Any)`

Базовые классы: *BaseIPythonApplication*, *InteractiveShellApp*

`crash_handler_class`

alias of *IPAppCrashHandler*

`display_banner`

Whether to display a banner upon starting IPython.

`force_interact`

If a command or file is given via the command-line, e.g. „ipython foo.py“, start an interactive shell after executing the file or command.

`init_banner()`

optionally display the banner

`init_shell()`

initialize the InteractiveShell instance

`initialize(argv=None)`

Do actions after construct, but before starting the app.

`interactive_shell_class`

Class to use to instantiate the TerminalInteractiveShell object. Useful for custom Frontends

`quick`

Start IPython quickly by skipping the loading of config files.

`start()`

Start the app mainloop.

Override in subclasses.

8.56.2 1 Function

```
IPython.terminal.ipapp.load_default_config(ipython_dir=None)
```

Load the default config file from the default `ipython_dir`.

This is useful for embedded shells.

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

8.57 Module: terminal.magics

Extra magics for terminal use.

8.57.1 1 Class

```
class IPython.terminal.magics.TerminalMagics(**kwargs: Any)
```

Базовые классы: *Magics*

```
__init__(shell)
```

Create a configurable given a config config.

Параметры

- `config` (*Config*) – If this is empty, default values are used. If config is a `Config` instance, it will be used to configure the instance.
- `parent` (*Configurable instance, optional*) – The parent `Configurable` instance of this object.

Заметки

Subclasses of `Configurable` must call the `__init__()` method of `Configurable` *before* doing anything else and using `super()`:

```
class MyConfigurable(Configurable):
    def __init__(self, config=None):
        super(MyConfigurable, self).__init__(config=config)
        # Then any other code you need to finish initialization.
```

This ensures that instances will be configured properly.

```
autoindent(parameter_s='')
```

Toggle autoindent on/off (deprecated)

```
cpaste(parameter_s='')
```

Paste & execute a pre-formatted code block from clipboard.

You must terminate the block with „-“ (two minus-signs) or Ctrl-D alone on the line. You can also provide your own sentinel with „%paste -s %%%“ („%%“ is the new sentinel for this operation).

The block is dedented prior to execution to enable execution of method definitions. „>“ and „+“ characters at the beginning of a line are ignored, to allow pasting directly from e-mails, diff files and doctests (the „...“ continuation prompt is also stripped). The executed block is also assigned to variable named „pasted_block“ for later editing with „%edit pasted_block“.

You can also pass a variable name as an argument, e.g. „%cpaste foo“. This assigns the pasted block to variable „foo“ as string, without dedenting or executing it (preceding >>> and + is still stripped)

„%cpaste -r“ re-executes the block previously entered by cpaste. „%cpaste -q“ suppresses any additional output messages.

Do not be alarmed by garbled output on Windows (it’s a readline bug). Just press enter and type – (and press enter again) and the block will be what was just pasted.

Shell escapes are not supported (yet).

См.также:

paste

automatically pull code from clipboard.

Примеры

```
In [8]: %cpaste
Pasting code; enter '--' alone on the line to stop.
:>>> a = ["world!", "Hello"]
:>>> print(" ".join(sorted(a)))
:--
Hello world!
```

::

```
In [8]: %cpaste Pasting code; enter „-“ alone on the line to stop. :>>> %alias_magic t timeit
:>>> %t -n1 pass :- Created %t as an alias for %timeit. Created %%t as an alias for %%timeit.
354 ns ± 224 ns per loop (mean ± std. dev. of 7 runs, 1 loop each)
```

```
paste(parameter_s='')
```

Paste & execute a pre-formatted code block from clipboard.

The text is pulled directly from the clipboard without user intervention and printed back on the screen before execution (unless the -q flag is given to force quiet mode).

The block is dedented prior to execution to enable execution of method definitions. „>“ and „+“ characters at the beginning of a line are ignored, to allow pasting directly from e-mails, diff files and doctests (the „...“ continuation prompt is also stripped). The executed block is also assigned to variable named „pasted_block“ for later editing with „%edit pasted_block“.

You can also pass a variable name as an argument, e.g. „%paste foo“. This assigns the pasted block to variable „foo“ as string, without executing it (preceding >>> and + is still stripped).

Options:

-r: re-executes the block previously entered by cpaste.

-q: quiet mode: do not echo the pasted text back to the terminal.

IPython statements (magics, shell escapes) are not supported (yet).

См.также:

cpaste

manually paste code into terminal until you mark its end.

`rerun_pasted(name='pasted_block')`

Rerun a previously pasted command.

`store_or_execute(block, name, store_history=False)`

Execute a block, or store it in a variable, per the user's request.

8.57.2 1 Function

`IPython.terminal.magics.get_pasted_lines(sentinel, l_input=<function input>, quiet=False)`

Yield pasted lines until the user enters the given sentinel value.

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

8.58 Module: terminal.prompts

Terminal input and output prompts.

8.58.1 3 Classes

`class IPython.terminal.prompts.Prompts(shell)`

Базовые классы: *object*

`__init__(shell)`

`class IPython.terminal.prompts.ClassicPrompts(shell)`

Базовые классы: *Prompts*

```
class IPython.terminal.prompts.RichPromptDisplayHook(**kwargs: Any)
```

Базовые классы: `DisplayHook`

Subclass of base display hook using coloured prompt

```
write_format_data(format_dict, md_dict=None) → None
```

Write the format data dict to the frontend.

This default version of this method simply writes the plain text representation of the object to `sys.stdout`. Subclasses should override this method to send the entire `format_dict` to the frontends.

Параметры

- `format_dict` (*dict*) – The format dict for the object passed to `sys.displayhook`.
- `md_dict` (*dict* (*optional*)) – The metadata dict to be associated with the display data.

```
write_output_prompt()
```

Write the output prompt.

The default implementation simply writes the prompt to `sys.stdout`.

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

8.59 Module: `terminal.shortcuts`

Module to define and register Terminal IPython shortcuts with `prompt_toolkit`

8.59.1 3 Classes

```
class IPython.terminal.shortcuts.BaseBinding(command:
    Callable[[prompt_toolkit.key_binding.key_processor.KeyPressEvent],
    Any], keys: List[str])
```

Базовые классы: `object`

```
class IPython.terminal.shortcuts.RuntimeBinding(command:
    Callable[[prompt_toolkit.key_binding.key_processor.KeyPressEvent],
    Any], keys: List[str], filter:
    prompt_toolkit.filters.base.Condition)
```

Базовые классы: `BaseBinding`

```
class IPython.terminal.shortcuts.Binding(command:
    Callable[[prompt_toolkit.key_binding.key_processor.KeyPressEvent],
    Any], keys: List[str], condition: Optional[str] = None)
```

Базовые классы: [BaseBinding](#)

8.59.2 17 Functions

```
IPython.terminal.shortcuts.create_identfier(handler: Callable)
```

```
IPython.terminal.shortcuts.add_binding(bindings: KeyBindings, binding: Binding)
```

```
IPython.terminal.shortcuts.create_ipython_shortcuts(shell, skip=None) → KeyBindings
```

Set up the prompt_toolkit keyboard shortcuts for IPython.

Параметры

- `shell` ([InteractiveShell](#)) – The current IPython shell Instance
- `skip` (*List* [[Binding](#)]) – Bindings to skip.

Результат

the keybinding instance for prompt toolkit.

Тип результата

KeyBindings

```
IPython.terminal.shortcuts.reformat_and_execute(event)
```

Reformat code and execute it

```
IPython.terminal.shortcuts.reformat_text_before_cursor(buffer, document, shell)
```

```
IPython.terminal.shortcuts.handle_return_or_newline_or_execute(event)
```

```
IPython.terminal.shortcuts.newline_or_execute_outer(shell)
```

```
IPython.terminal.shortcuts.previous_history_or_previous_completion(event)
```

Control-P in vi edit mode on readline is history next, unlike default prompt toolkit.

If completer is open this still select previous completion.

```
IPython.terminal.shortcuts.next_history_or_next_completion(event)
```

Control-N in vi edit mode on readline is history previous, unlike default prompt toolkit.

If completer is open this still select next completion.

```
IPython.terminal.shortcuts.dismiss_completion(event)
```

Dismiss completion

```
IPython.terminal.shortcuts.reset_buffer(event)
```

Reset buffer

```
IPython.terminal.shortcuts.reset_search_buffer(event)
```

Reset search buffer

```
IPython.terminal.shortcuts.suspend_to_bg(event)
```

Suspend to background

`IPython.terminal.shortcuts.quit(event)`

Quit application with `SIGQUIT` if supported or `sys.exit` otherwise.

On platforms that support `SIGQUIT`, send `SIGQUIT` to the current process. On other platforms, just exit the process with a message.

`IPython.terminal.shortcuts.indent_buffer(event)`

Indent buffer

`IPython.terminal.shortcuts.newline_autoindent(event)`

Insert a newline after the cursor indented appropriately.

Fancier version of former `newline_with_copy_margin` which should compute the correct indentation of the inserted line. That is to say, indent by 4 extra space after a function definition, class definition, context manager... And dedent by 4 space after `pass`, `return`, `raise`

`IPython.terminal.shortcuts.open_input_in_editor(event)`

Open code from input in external editor

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

8.60 Module: `terminal.shortcuts.auto_match`

Utilities function for keybinding with prompt toolkit.

This will be bound to specific key press and filter modes, like whether we are in edit mode, and whether the completer is open.

8.60.1 12 Functions

`IPython.terminal.shortcuts.auto_match.parenthesis(event: KeyPressEvent)`

Auto-close parenthesis

`IPython.terminal.shortcuts.auto_match.brackets(event: KeyPressEvent)`

Auto-close brackets

`IPython.terminal.shortcuts.auto_match.braces(event: KeyPressEvent)`

Auto-close braces

`IPython.terminal.shortcuts.auto_match.double_quote(event: KeyPressEvent)`

Auto-close double quotes

`IPython.terminal.shortcuts.auto_match.single_quote(event: KeyPressEvent)`

Auto-close single quotes

`IPython.terminal.shortcuts.auto_match.docstring_double_quotes(event: KeyPressEvent)`

Auto-close docstring (double quotes)

`IPython.terminal.shortcuts.auto_match.docstring_single_quotes(event: KeyPressEvent)`

Auto-close docstring (single quotes)

`IPython.terminal.shortcuts.auto_match.raw_string_parenthesis(event: KeyPressEvent)`

Auto-close parenthesis in raw strings

`IPython.terminal.shortcuts.auto_match.raw_string_bracket(event: KeyPressEvent)`

Auto-close bracker in raw strings

`IPython.terminal.shortcuts.auto_match.raw_string_braces(event: KeyPressEvent)`

Auto-close braces in raw strings

`IPython.terminal.shortcuts.auto_match.skip_over(event: KeyPressEvent)`

Skip over automatically added parenthesis/quote.

(rather than adding another parenthesis/quote)

`IPython.terminal.shortcuts.auto_match.delete_pair(event: KeyPressEvent)`

Delete auto-closed parenthesis

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

8.61 Module: `terminal.shortcuts.auto_suggest`

8.61.1 2 Classes

`class IPython.terminal.shortcuts.auto_suggest.AppendAutoSuggestionInAnyLine(style: str = 'class:auto-suggestion')`

Базовые классы: `Processor`

Append the auto suggestion to lines other than the last (appending to the last line is natively supported by the prompt toolkit).

`__init__(style: str = 'class:auto-suggestion') → None`

`apply_transformation(ti: TransformationInput) → Transformation`

Apply transformation. Returns a `Transformation` instance.

Параметры

`transformation_input` – `TransformationInput` object.

`class IPython.terminal.shortcuts.auto_suggest.NavigableAutoSuggestFromHistory`

Базовые классы: `AutoSuggestFromHistory`

A subclass of `AutoSuggestFromHistory` that allow navigation to next/previous suggestion from history. To do so it remembers the current position, but its state needs to be carefully cleared on the right events.

`__init__()`

`get_suggestion(buffer: Buffer, document: Document) → Optional[Suggestion]`

Return None or a `Suggestion` instance.

We receive both `Buffer` and `Document`. The reason is that auto suggestions are retrieved asynchronously. (Like completions.) The buffer text could be changed in the meantime, but `document` contains the buffer document like it was at the start of the auto suggestion call. So, from here, don't access `buffer.text`, but use `document.text` instead.

Параметры

- `buffer` – The `Buffer` instance.
- `document` – The `Document` instance.

8.61.2 14 Functions

`IPython.terminal.shortcuts.auto_suggest.accept_or_jump_to_end(event: KeyPressEvent)`

Apply autosuggestion or jump to end of line.

`IPython.terminal.shortcuts.auto_suggest.accept(event: KeyPressEvent)`

Accept autosuggestion

`IPython.terminal.shortcuts.auto_suggest.discard(event: KeyPressEvent)`

Discard autosuggestion

`IPython.terminal.shortcuts.auto_suggest.accept_word(event: KeyPressEvent)`

Fill partial autosuggestion by word

`IPython.terminal.shortcuts.auto_suggest.accept_character(event: KeyPressEvent)`

Fill partial autosuggestion by character

`IPython.terminal.shortcuts.auto_suggest.accept_and_keep_cursor(event: KeyPressEvent)`

Accept autosuggestion and keep cursor in place

`IPython.terminal.shortcuts.auto_suggest.accept_and_move_cursor_left(event: KeyPressEvent)`

Accept autosuggestion and move cursor left in place

`IPython.terminal.shortcuts.auto_suggest.backspace_and_resume_hint(event: KeyPressEvent)`

Resume autosuggestions after deleting last character

`IPython.terminal.shortcuts.auto_suggest.resume_hinting(event: KeyPressEvent)`

Resume autosuggestions

`IPython.terminal.shortcuts.auto_suggest.up_and_update_hint(event: KeyPressEvent)`

Go up and update hint

`IPython.terminal.shortcuts.auto_suggest.down_and_update_hint(event: KeyPressEvent)`

Go down and update hint

```
IPython.terminal.shortcuts.auto_suggest.accept_token(event: KeyPressEvent)
```

Fill partial autosuggestion by token

```
IPython.terminal.shortcuts.auto_suggest.swap_autosuggestion_up(event: KeyPressEvent)
```

Get next autosuggestion from history.

```
IPython.terminal.shortcuts.auto_suggest.swap_autosuggestion_down(event: KeyPressEvent)
```

Get previous autosuggestion from history.

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

8.62 Module: `terminal.shortcuts.filters`

Filters restricting scope of IPython Terminal shortcuts.

8.62.1 13 Functions

```
IPython.terminal.shortcuts.filters.has_focus(value: Union[str, Buffer, UIControl, Container, MagicContainer])
```

Wrapper around `has_focus` adding a nice `__name__` to tester function

```
IPython.terminal.shortcuts.filters.ebivim() → bool
```

Turn any callable into a Filter. The callable is supposed to not take any arguments.

This can be used as a decorator:

```
@Condition
def feature_is_active(): # `feature_is_active` becomes a Filter.
    return True
```

Параметры

`func` – Callable which takes no inputs and returns a boolean.

```
IPython.terminal.shortcuts.filters.supports_suspend() → bool
```

Turn any callable into a Filter. The callable is supposed to not take any arguments.

This can be used as a decorator:

```
@Condition
def feature_is_active(): # `feature_is_active` becomes a Filter.
    return True
```

Параметры

`func` – Callable which takes no inputs and returns a boolean.

`IPython.terminal.shortcuts.filters.auto_match()` → `bool`

Turn any callable into a Filter. The callable is supposed to not take any arguments.

This can be used as a decorator:

```
@Condition
def feature_is_active(): # `feature_is_active` becomes a Filter.
    return True
```

Параметры

`func` – Callable which takes no inputs and returns a boolean.

`IPython.terminal.shortcuts.filters.all_quotes_paired(quote, buf)`

`IPython.terminal.shortcuts.filters.preceding_text(pattern: Union[str, Callable])`

`IPython.terminal.shortcuts.filters.following_text(pattern)`

`IPython.terminal.shortcuts.filters.not_inside_unclosed_string()` → `bool`

Turn any callable into a Filter. The callable is supposed to not take any arguments.

This can be used as a decorator:

```
@Condition
def feature_is_active(): # `feature_is_active` becomes a Filter.
    return True
```

Параметры

`func` – Callable which takes no inputs and returns a boolean.

`IPython.terminal.shortcuts.filters.navigable_suggestions()` → `bool`

Turn any callable into a Filter. The callable is supposed to not take any arguments.

This can be used as a decorator:

```
@Condition
def feature_is_active(): # `feature_is_active` becomes a Filter.
    return True
```

Параметры

`func` – Callable which takes no inputs and returns a boolean.

`IPython.terminal.shortcuts.filters.readline_like_completions()` → `bool`

Turn any callable into a Filter. The callable is supposed to not take any arguments.

This can be used as a decorator:

```
@Condition
def feature_is_active(): # `feature_is_active` becomes a Filter.
    return True
```

Параметры

`func` – Callable which takes no inputs and returns a boolean.

`IPython.terminal.shortcuts.filters.is_windows_os()` → `bool`

Turn any callable into a Filter. The callable is supposed to not take any arguments.

This can be used as a decorator:

```
@Condition
def feature_is_active(): # `feature_is_active` becomes a Filter.
    return True
```

Параметры

`func` – Callable which takes no inputs and returns a boolean.

`IPython.terminal.shortcuts.filters.eval_node(node: Optional[AST])`

`IPython.terminal.shortcuts.filters.filter_from_string(code: str)`

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

8.63 Module: `testing.ipunittest`

Experimental code for cleaner support of IPython syntax with unittest.

In IPython up until 0.10, we've used very hacked up nose machinery for running tests with IPython special syntax, and this has proved to be extremely slow. This module provides decorators to try a different approach, stemming from a conversation Brian and I (FP) had about this problem Sept/09.

The goal is to be able to easily write simple functions that can be seen by unittest as tests, and ultimately for these to support doctests with full IPython syntax. Nose already offers this based on naming conventions and our hackish plugins, but we are seeking to move away from nose dependencies if possible.

This module follows a different approach, based on decorators.

- A decorator called `@ipdoctest` can mark any function as having a docstring that should be viewed as a doctest, but after syntax conversion.

8.63.1 Authors

- Fernando Perez <Fernando.Perez@berkeley.edu>

8.63.2 2 Classes

```
class IPython.testing.ipunittest.IPython2PythonConverter
```

Базовые классы: `object`

Convert IPython „syntax“ to valid Python.

Eventually this code may grow to be the full IPython syntax conversion implementation, but for now it only does prompt conversion.

```
__init__()
```

```
class IPython.testing.ipunittest.Doc2UnitTester(verbose=False)
```

Базовые классы: `object`

Class whose instances act as a decorator for docstring testing.

In practice we're only likely to need one instance ever, made below (though no attempt is made at turning it into a singleton, there is no need for that).

```
__init__(verbose=False)
```

New decorator.

Параметры

`verbose (boolean, optional (False))` – Passed to the doctest finder and runner to control verbosity.

8.63.3 2 Functions

```
IPython.testing.ipunittest.count_failures(runner)
```

Count number of failures in a doctest runner.

Code modeled after the `summarize()` method in doctest.

```
IPython.testing.ipunittest.ipdocstring(func)
```

Change the function docstring via `ip2py`.

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

8.64 Module: `testing.skipdoctest`

Decorators marks that a doctest should be skipped.

The `IPython.testing.decorators` module triggers various extra imports, including `numpy` and `sympy` if they're present. Since this decorator is used in core parts of IPython, it's in a separate module so that running IPython doesn't trigger those imports.

8.64.1 1 Function

`IPython.testing.skipdoctest.skip_doctest(f)`

Decorator - mark a function or method for skipping its doctest.

This decorator allows you to mark a function whose docstring you wish to omit from testing, while preserving the docstring for introspection, `help`, etc.

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

8.65 Module: `utils.PyColorize`

Class and program to colorize python source code for ANSI terminals.

Based on an HTML code highlighter by Jurgen Hermann found at: <http://aspn.activestate.com/ASPN/Cookbook/Python/Recipe/52298>

Modifications by Fernando Perez (fperez@colorado.edu).

Information on the original HTML highlighter follows:

MoinMoin - Python Source Parser

Title: Colorize Python source using the built-in tokenizer

Submitter: Jurgen Hermann Last Updated:2001/04/06

Version no:1.2

Description:

This code is part of MoinMoin (<http://moin.sourceforge.net/>) and converts Python source code to HTML markup, rendering comments, keywords, operators, numeric and string literals in different colors.

It shows how to use the built-in keyword, token and tokenize modules to scan Python source code and re-emit it with no changes to its original formatting (which is the hard part).

8.65.1 1 Class

```
class IPython.utils.PyColorize.Parser(**kwargs: Any)
```

Базовые классы: `Colorable`

Format colored Python source.

```
__init__(color_table=None, out=<_io.TextIOWrapper name='<stdout>' mode='w'
        encoding='utf-8'>, parent=None, style=None)
```

Create a parser with a specified color table and output channel.

Call `format()` to process code.

```
format2(raw, out=None)
```

Parse and send the colored source.

If `out` and `scheme` are not specified, the defaults (given to constructor) are used.

`out` should be a file-type object. Optionally, `out` can be given as the string „str“ and the parser will automatically return the output in a string.

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

8.66 Module: `utils.capture`

IO capturing utilities.

8.66.1 3 Classes

```
class IPython.utils.capture.RichOutput(data=None, metadata=None, transient=None,
                                       update=False)
```

Базовые классы: `object`

```
__init__(data=None, metadata=None, transient=None, update=False)
```

```
class IPython.utils.capture.CapturedIO(stdout, stderr, outputs=None)
```

Базовые классы: `object`

Simple object for containing captured stdout/err and rich display StringIO objects

Each instance `c` has three attributes:

- `c.stdout` : standard output as a string
- `c.stderr` : standard error as a string

- `c.outputs`: a list of rich display outputs

Additionally, there's a `c.show()` method which will print all of the above in the same order, and can be invoked simply via `c()`.

```
__init__(stdout, stderr, outputs=None)
```

property `outputs`

A list of the captured rich display outputs, if any.

If you have a `CapturedIO` object `c`, these can be displayed in IPython using:

```
from IPython.display import display
for o in c.outputs:
    display(o)
```

`show()`

write my output to `sys.stdout/err` as appropriate

property `stderr`

Captured standard error

property `stdout`

Captured standard output

```
class IPython.utils.capture.capture_output(stdout=True, stderr=True, display=True)
```

Базовые классы: `object`

context manager for capturing `stdout/err`

```
__init__(stdout=True, stderr=True, display=True)
```

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

8.67 Module: `utils.colorable`

Color managing related utilities

8.67.1 1 Class

```
class IPython.utils.colorable.Colorable(**kwargs: Any)
```

Базовые классы: `Configurable`

A subclass of configurable for all the classes that have a `default_scheme`

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

8.68 Module: `utils.coloransi`

Tools for coloring text in ANSI terminals.

8.68.1 5 Classes

```
class IPython.utils.coloransi.TermColors
```

Базовые классы: `object`

Color escape sequences.

This class defines the escape sequences for all the standard (ANSI?) colors in terminals. Also defines a `NoColor` escape which is just the null string, suitable for defining „dummy“ color schemes in terminals which get confused by color escapes.

This class should be used as a mixin for building color schemes.

```
class IPython.utils.coloransi.InputTermColors
```

Базовые классы: `object`

Color escape sequences for input prompts.

This class is similar to `TermColors`, but the escapes are wrapped in `001` and `002` so that readline can properly know the length of each line and can wrap lines accordingly. Use this class for any colored text which needs to be used in input prompts, such as in calls to `raw_input()`.

This class defines the escape sequences for all the standard (ANSI?) colors in terminals. Also defines a `NoColor` escape which is just the null string, suitable for defining „dummy“ color schemes in terminals which get confused by color escapes.

This class should be used as a mixin for building color schemes.

```
class IPython.utils.coloransi.NoColors
```

Базовые классы: `object`

This defines all the same names as the colour classes, but maps them to empty strings, so it can easily be substituted to turn off colours.

```
class IPython.utils.coloransi.ColorScheme(_ColorScheme__scheme_name_, colordict=None,
                                          **colormap)
```

Базовые классы: `object`

Generic color scheme class. Just a name and a Struct.

```
__init__(_ColorScheme__scheme_name_, colordict=None, **colormap)
```

```
copy(name=None)
```

Return a full copy of the object, optionally renaming it.

```
class IPython.utils.coloransi.ColorSchemeTable(scheme_list=None, default_scheme='')
```

Базовые классы: `dict`

General class to handle tables of color schemes.

It's basically a dict of color schemes with a couple of shorthand attributes and some convenient methods.

active_scheme_name -> obvious active_colors -> actual color table of the active scheme

```
__init__(scheme_list=None, default_scheme='')
```

Create a table of color schemes.

The table can be created empty and manually filled or it can be created with a list of valid color schemes AND the specification for the default active scheme.

```
add_scheme(new_scheme)
```

Add a new color scheme to the table.

```
copy()
```

Return full copy of object

```
set_active_scheme(scheme, case_sensitive=0)
```

Set the currently active scheme.

Names are by default compared in a case-insensitive way, but this can be changed by setting the parameter case_sensitive to true.

8.68.2 1 Function

```
IPython.utils.coloransi.make_color_table(in_class)
```

Build a set of color attributes in a class.

Helper function for building the `TermColors` and `:class`InputTermColors``.

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

8.69 Module: `utils.contexts`

Miscellaneous context managers.

8.69.1 1 Class

`class IPython.utils.contexts.preserve_keys(dictionary, *keys)`

Базовые классы: `object`

Preserve a set of keys in a dictionary.

Upon entering the context manager the current values of the keys will be saved. Upon exiting, the dictionary will be updated to restore the original value of the preserved keys. Preserved keys which did not exist when entering the context manager will be deleted.

Примеры

```
>>> d = {'a': 1, 'b': 2, 'c': 3}
>>> with preserve_keys(d, 'b', 'c', 'd'):
...     del d['a']
...     del d['b']      # will be reset to 2
...     d['c'] = None   # will be reset to 3
...     d['d'] = 4      # will be deleted
...     d['e'] = 5
...     print(sorted(d.items()))
...
[('c', None), ('d', 4), ('e', 5)]
>>> print(sorted(d.items()))
[('b', 2), ('c', 3), ('e', 5)]
```

`__init__(dictionary, *keys)`

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

8.70 Module: `utils.data`

Utilities for working with data structures like lists, dicts and tuples.

8.70.1 2 Functions

`IPython.utils.data.uniq_stable(elems) → list`

Return from an iterable, a list of all the unique elements in the input, but maintaining the order in which they first appear.

Note: All elements in the input must be hashable for this routine to work, as it internally uses a set for efficiency reasons.

`IPython.utils.data.chop(seq, size)`

Chop a sequence into chunks of the given size.

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

8.71 Module: `utils.decorators`

Decorators that don't go anywhere else.

This module contains misc. decorators that don't really go with another module in `IPython.utils`. Before putting something here please see if it should go into another topical module in `IPython.utils`.

8.71.1 3 Functions

`IPython.utils.decorators.flag_calls(func)`

Wrap a function to detect and flag when it gets called.

This is a decorator which takes a function and wraps it in a function with a „called“ attribute. `wrapper.called` is initialized to `False`.

The `wrapper.called` attribute is set to `False` right before each call to the wrapped function, so if the call fails it remains `False`. After the call completes, `wrapper.called` is set to `True` and the output is returned.

Testing for truth in `wrapper.called` allows you to determine if a call to `func()` was attempted and succeeded.

`IPython.utils.decorators.undoc(func)`

Mark a function or class as undocumented.

This is found by inspecting the AST, so for now it must be used directly as `@undoc`, not as e.g. `@decorators.undoc`

`IPython.utils.decorators.sphinx_options(show_inheritance: bool = True, show_inherited_members: bool = False, exclude_inherited_from: Sequence[str] = ())`

Set sphinx options

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

8.72 Module: `utils.dir2`

A fancy version of Python's builtin `dir()` function.

8.72.1 3 Functions

`IPython.utils.dir2.safe_hasattr(obj, attr)`

In recent versions of Python, `hasattr()` only catches `AttributeError`. This catches all errors.

`IPython.utils.dir2.dir2(obj) → list of strings`

Extended version of the Python builtin `dir()`, which does a few extra checks.

This version is guaranteed to return only a list of true strings, whereas `dir()` returns anything that objects inject into themselves, even if they are later not really valid for attribute access (many extension libraries have such bugs).

`IPython.utils.dir2.get_real_method(obj, name)`

Like `getattr`, but with a few extra sanity checks:

- If `obj` is a class, ignore everything except class methods
- Check if `obj` is a proxy that claims to have all attributes
- Catch attribute access failing with any exception
- Check that the attribute is a callable object

Returns the method or `None`.

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

8.73 Module: `utils.encoding`

Utilities for dealing with text encodings

8.73.1 2 Functions

`IPython.utils.encoding.get_stream_enc(stream, default=None)`

Return the given stream's encoding or a default.

There are cases where `sys.std*` might not actually be a stream, so check for the encoding attribute prior to returning it, and return a default if it doesn't exist or evaluates as False. `default` is None if not provided.

`IPython.utils.encoding.getdefaultencoding(prefer_stream=True)`

Return IPython's guess for the default encoding for bytes as text.

If `prefer_stream` is True (default), asks for `stdin.encoding` first, to match the calling Terminal, but that is often None for subprocesses.

Then fall back on `locale.getpreferredencoding()`, which should be a sensible platform default (that respects LANG environment), and finally to `sys.getdefaultencoding()` which is the most conservative option, and usually UTF8 as of Python 3.

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

8.74 Module: `utils.frame`

Utilities for working with stack frames.

8.74.1 4 Functions

`IPython.utils.frame.extract_vars(*names, **kw)`

Extract a set of variables by name from another frame.

Параметры

- `*names` (*str*) – One or more variable names which will be extracted from the caller’s frame.
- `**kw` (*integer, optional*) – How many frames in the stack to walk when looking for your variables. The default is 0, which will use the frame where the call was made.

Примеры

```
In [2]: def func(x):
...:     y = 1
...:     print(sorted(extract_vars('x','y').items()))
...:

In [3]: func('hello')
[('x', 'hello'), ('y', 1)]
```

`IPython.utils.frame.extract_vars_above(*names)`

Extract a set of variables by name from another frame.

Similar to `extractVars()`, but with a specified depth of 1, so that names are extracted exactly from above the caller.

This is simply a convenience function so that the very common case (for us) of skipping exactly 1 frame doesn’t have to construct a special dict for keyword passing.

`IPython.utils.frame.debugx(expr, pre_msg='')`

Print the value of an expression from the caller’s frame.

Takes an expression, evaluates it in the caller’s frame and prints both the given expression and the resulting value (as well as a debug mark indicating the name of the calling function. The input must be of a form suitable for `eval()`).

An optional message can be passed, which will be prepended to the printed `expr->value` pair.

`IPython.utils.frame.extract_module_locals(depth=0)`

Returns (module, locals) of the function `depth` frames away from the caller

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

8.75 Module: `utils.generics`

Generic functions for extending IPython.

8.75.1 2 Functions

`IPython.utils.generics.inspect_object(obj)`

Called when you do `obj?`

`IPython.utils.generics.complete_object(obj, prev_completions)`

Custom completer dispatching for python objects.

Параметры

- `obj` (*object*) – The object to complete.
- `prev_completions` (*list*) – List of attributes discovered so far.
- `to` (*This should return the list of attributes in obj. If you only wish*) –
- `normally` (*add to the attributes already discovered*) –
- `return` –
- `prev_completions. (own_attrs +)` –

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

8.76 Module: `utils.importstring`

A simple utility to import something by its string name.

8.76.1 1 Function

`IPython.utils.importstring.import_item(name)`

Import and return `bar` given the string `foo.bar`.

Calling `bar = import_item("foo.bar")` is the functional equivalent of executing the code `from foo import bar`.

Параметры

- `name` (*string*) – The fully qualified name of the module/package being imported.

Результат**mod** – The module that was imported.**Тип результата**

module object

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

8.77 Module: `utils.io`

IO related utilities.

8.77.1 1 Class

```
class IPython.utils.io.Tee(file_or_name, mode='w', channel='stdout')
```

Базовые классы: `object`

A class to duplicate an output stream to stdout/err.

This works in a manner very similar to the Unix „tee“ command.

When the object is closed or deleted, it closes the original file given to it for duplication.

```
__init__(file_or_name, mode='w', channel='stdout')
```

Construct a new Tee object.

Параметры

- `file_or_name` (*filename or open filehandle (writable)*) – File that will be duplicated
- `mode` (*optional, valid mode for open()*) – If a filename was give, open with this mode.
- `channel` (*str, one of ['stdout', 'stderr']*) –

```
close()
```

Close the file and restore the channel.

```
flush()
```

Flush both channels.

```
write(data)
```

Write data to both channels.

8.77.2 2 Functions

`IPython.utils.io.ask_yes_no(prompt, default=None, interrupt=None)`

Asks a question and returns a boolean (y/n) answer.

If default is given (one of „y“,“n“), it is used if the user input is empty. If interrupt is given (one of „y“,“n“), it is used if the user presses Ctrl-C. Otherwise the question is repeated until an answer is given.

An EOF is treated as the default answer. If there is no default, an exception is raised to prevent infinite loops.

Valid answers are: y/yes/n/no (match is not case sensitive).

`IPython.utils.io.temp_pyfile(src, ext='.py')`

Make a temporary python file, return filename and filehandle.

Параметры

- `src` (*string or list of strings (no need for ending newlines if list)*) – Source code to be written to the file.
- `ext` (*optional, string*) – Extension for the generated file.

Результат

It is the caller’s responsibility to close the open file and unlink it.

Тип результата

(filename, open filehandle)

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

8.78 Module: `utils.ipstruct`

A dict subclass that supports attribute style access.

Authors:

- Fernando Perez (original)
- Brian Granger (refactoring to a dict subclass)

8.78.1 1 Class

`class IPython.utils.ipstruct.Struct(*args, **kw)`

Базовые классы: `dict`

A dict subclass with attribute style access.

This dict subclass has a a few extra features:

- Attribute style access.
- Protection of class members (like keys, items) when using attribute style access.
- The ability to restrict assignment to only existing keys.
- Intelligent merging.
- Overloaded operators.

`__init__(*args, **kw)`

Initialize with a dictionary, another Struct, or data.

Параметры

- `*args` (`dict`, `Struct`) – Initialize with one dict or Struct
- `**kw` (`dict`) – Initialize with key, value pairs.

Примеры

```
>>> s = Struct(a=10,b=30)
>>> s.a
10
>>> s.b
30
>>> s2 = Struct(s,c=30)
>>> sorted(s2.keys())
['a', 'b', 'c']
```

`allow_new_attr(allow=True)`

Set whether new attributes can be created in this Struct.

This can be used to catch typos by verifying that the attribute user tries to change already exists in this Struct.

`copy()`

Return a copy as a Struct.

Примеры

```
>>> s = Struct(a=10,b=30)
>>> s2 = s.copy()
>>> type(s2) is Struct
True
```

`hasattr(key)`

`hasattr` function available as a method.

Implemented like `has_key`.

Примеры

```
>>> s = Struct(a=10)
>>> s.hasattr('a')
True
>>> s.hasattr('b')
False
>>> s.hasattr('get')
False
```

`merge(__loc_data__=None, __Struct__conflict_solve=None, **kw)`

Merge two Structs with customizable conflict resolution.

This is similar to `update()`, but much more flexible. First, a dict is made from `data+key=value` pairs. When merging this dict with the Struct `S`, the optional dictionary „conflict“ is used to decide what to do.

If conflict is not given, the default behavior is to preserve any keys with their current value (the opposite of the `update()` method’s behavior).

Параметры

- `__loc_data__` (*dict*, *Struct*) – The data to merge into self
- `__conflict_solve` (*dict*) – The conflict policy dict. The keys are binary functions used to resolve the conflict and the values are lists of strings naming the keys the conflict resolution function applies to. Instead of a list of strings a space separated string can be used, like „a b c“.
- `**kw` (*dict*) – Additional key, value pairs to merge in

Заметки

The `__conflict_solve` dict is a dictionary of binary functions which will be used to solve key conflicts. Here is an example:

```
__conflict_solve = dict(
    func1=['a', 'b', 'c'],
    func2=['d', 'e']
)
```

In this case, the function `func1()` will be used to resolve keys „a“, „b“ and „c“ and the function `func2()` will be used for keys „d“ and „e“. This could also be written as:

```
__conflict_solve = dict(func1='a b c', func2='d e')
```

These functions will be called for each key they apply to with the form:

```
func1(self['a'], other['a'])
```

The return value is used as the final merged value.

As a convenience, `merge()` provides five (the most commonly needed) pre-defined policies: `preserve`, `update`, `add`, `add_flip` and `add_s`. The easiest explanation is their implementation:

```
preserve = lambda old,new: old
update   = lambda old,new: new
add      = lambda old,new: old + new
add_flip = lambda old,new: new + old # note change of order!
add_s    = lambda old,new: old + ' ' + new # only for str!
```

You can use those four words (as strings) as keys instead of defining them as functions, and the merge method will substitute the appropriate functions for you.

For more complicated conflict resolution policies, you still need to construct your own functions.

Примеры

This show the default policy:

```
>>> s = Struct(a=10,b=30)
>>> s2 = Struct(a=20,c=40)
>>> s.merge(s2)
>>> sorted(s.items())
[('a', 10), ('b', 30), ('c', 40)]
```

Now, show how to specify a conflict dict:

```
>>> s = Struct(a=10,b=30)
>>> s2 = Struct(a=20,b=40)
>>> conflict = {'update': 'a', 'add': 'b'}
>>> s.merge(s2, conflict)
>>> sorted(s.items())
[('a', 20), ('b', 70)]
```

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

8.79 Module: `utils.module_paths`

Utility functions for finding modules

Utility functions for finding modules on `sys.path`.

8.79.1 1 Function

`IPython.utils.module_paths.find_mod(module_name)`

Find module `module_name` on `sys.path`, and return the path to module `module_name`.

- If `module_name` refers to a module directory, then return path to `__init__` file. - If `module_name` is a directory without an `__init__` file, return `None`.
- If module is missing or does not have a `.py` or `.pyw` extension, return `None`. - Note that we are not interested in running bytecode.
- Otherwise, return the full path of the module.

Параметры

`module_name` (*str*) –

Результат

`module_path` – Path to module `module_name`, its `__init__.py`, or `None`, depending on above conditions.

Тип результата

str

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

8.80 Module: `utils.openpy`

Tools to open `.py` files as Unicode, using the encoding specified within the file, as per PEP 263.

Much of the code is taken from the `tokenize` module in Python 3.2.

8.80.1 4 Functions

`IPython.utils.openpy.source_to_unicode(txt, errors='replace', skip_encoding_cookie=True)`

Converts a bytes string with python source code to unicode.

Unicode strings are passed through unchanged. Byte strings are checked for the python source file encoding cookie to determine encoding. `txt` can be either a bytes buffer or a string containing the source code.

`IPython.utils.openpy.strip_encoding_cookie(filelike)`

Generator to pull lines from a text-mode file, skipping the encoding cookie if it is found in the first two lines.

`IPython.utils.openpy.read_py_file(filename, skip_encoding_cookie=True)`

Read a Python file, using the encoding declared inside the file.

Параметры

- `filename` (*str*) – The path to the file to read.
- `skip_encoding_cookie` (*bool*) – If True (the default), and the encoding declaration is found in the first two lines, that line will be excluded from the output.

Тип результата

A unicode string containing the contents of the file.

`IPython.utils.openpy.read_py_url(url, errors='replace', skip_encoding_cookie=True)`

Read a Python file from a URL, using the encoding declared inside the file.

Параметры

- `url` (*str*) – The URL from which to fetch the file.
- `errors` (*str*) – How to handle decoding errors in the file. Options are the same as for `bytes.decode()`, but here „replace“ is the default.
- `skip_encoding_cookie` (*bool*) – If True (the default), and the encoding declaration is found in the first two lines, that line will be excluded from the output.

Тип результата

A unicode string containing the contents of the file.

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

8.81 Module: `utils.path`

Utilities for path handling.

8.81.1 1 Class

`class IPython.utils.path.HomeDirError`

Базовые классы: `Exception`

8.81.2 15 Functions

`IPython.utils.path.get_long_path_name(path)`

Expand a path into its long form.

On Windows this expands any `~` in the paths. On other platforms, it is a null operation.

`IPython.utils.path.compress_user(path)`

Reverse of `os.path.expanduser()`

`IPython.utils.path.get_py_filename(name)`

Return a valid python filename in the current directory.

If the given name is not a file, it adds „py“ and searches again. Raises `IOError` with an informative message if the file isn't found.

`IPython.utils.path.filefind(filename: str, path_dirs=None) → str`

Find a file by looking through a sequence of paths.

This iterates through a sequence of paths looking for a file and returns the full, absolute path of the first occurrence of the file. If no set of path dirs is given, the filename is tested as is, after running through `expandvars()` and `expanduser()`. Thus a simple call:

```
filefind('myfile.txt')
```

will find the file in the current working dir, but:

```
filefind('~'/myfile.txt')
```

Will find the file in the users home directory. This function does not automatically try any paths, such as the cwd or the user's home directory.

Параметры

- `filename` (*str*) – The filename to look for.
- `path_dirs` (*str, None or sequence of str*) – The sequence of paths to look for the file in. If `None`, the filename need to be absolute or be in the cwd. If a string, the string is put into a sequence and the searched. If a sequence, walk through each element and join with `filename`, calling `expandvars()` and `expanduser()` before testing for existence.

Результат

`path` – returns absolute path to file.

Тип результата

str

Исключение`IOError` –`IPython.utils.path.get_home_dir(require_writable=False) → str`

Return the „home“ directory, as a unicode string.

Uses `os.path.expanduser(„~“)`, and checks for writability.

See `stdlib` docs for how this is determined. For Python <3.8, `$HOME` is first priority on *ALL* platforms. For Python ≥3.8 on Windows, `%HOME%` is no longer considered.

Параметры`require_writable (bool [default: False]) –`**if True:**

guarantees the return value is a writable directory, otherwise raises `HomeDirError`

if False:

The path is resolved, but it is not guaranteed to exist or be writable.

`IPython.utils.path.get_xdg_dir()`

Return the `XdG_CONFIG_HOME`, if it is defined and exists, else `None`.

This is only for non-OS X posix (Linux, Unix, etc.) systems.

`IPython.utils.path.get_xdg_cache_dir()`

Return the `XdG_CACHE_HOME`, if it is defined and exists, else `None`.

This is only for non-OS X posix (Linux, Unix, etc.) systems.

`IPython.utils.path.expand_path(s)`

Expand `$VARS` and `~`names in a string, like a shell

Examples

In [2]: `os.environ[„FOO“]=„test“`

In [3]: `expand_path(„variable FOO is $FOO“)` Out[3]: „variable FOO is test“

`IPython.utils.path.unescape_glob(string)`

Unescape glob pattern in `string`.

`IPython.utils.path.shellglob(args)`

Do glob expansion for each element in `args` and return a flattened list.

Unmatched glob pattern will remain as-is in the returned list.

`IPython.utils.path.target_outdated(target, deps)`

Determine whether a target is out of date.

`target_outdated(target, deps) -> 1/0`

`deps`: list of filenames which **MUST** exist. `target`: single filename which may or may not exist.

If target doesn't exist or is older than any file listed in `deps`, return `true`, otherwise return `false`.

`IPython.utils.path.target_update(target, deps, cmd)`

Update a target with a given command given a list of dependencies.

`target_update(target, deps, cmd) ->` runs `cmd` if target is outdated.

This is just a wrapper around `target_outdated()` which calls the given command if target is outdated.

`IPython.utils.path.link(src, dst)`

Hard links `src` to `dst`, returning 0 or `errno`.

Note that the special `errno` `ENOLINK` will be returned if `os.link` isn't supported by the operating system.

`IPython.utils.path.link_or_copy(src, dst)`

Attempts to hardlink `src` to `dst`, copying if the link fails.

Attempts to maintain the semantics of `shutil.copy`.

Because `os.link` does not overwrite files, a unique temporary file will be used if the target already exists, then that file will be moved into place.

`IPython.utils.path.ensure_dir_exists(path, mode=493)`

ensure that a directory exists

If it doesn't exist, try to create it and protect against a race condition if another process is doing the same.

The default permissions are 755, which differ from `os.makedirs` default of 777.

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

8.82 Module: `utils.process`

Utilities for working with external processes.

8.82.1 1 Class

`class IPython.utils.process.FindCmdError`

Базовые классы: `Exception`

8.82.2 2 Functions

`IPython.utils.process.find_cmd(cmd)`

Find absolute path to executable `cmd` in a cross platform manner.

This function tries to determine the full path to a command line program using `which` on Unix/Linux/OS X and `win32api` on Windows. Most of the time it will use the version that is first on the users `PATH`.

Warning, don't use this to find IPython command line programs as there is a risk you will find the wrong one. Instead find those using the following code and looking for the application itself:

```
import sys
argv = [sys.executable, '-m', 'IPython']
```

Параметры

`cmd` (*str*) – The command line program to look for.

`IPython.utils.process.abbrev_cwd()`

Return abbreviated version of cwd, e.g. d:mydir

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

8.83 Module: `utils.sentinel`

Sentinel class for constants with useful reprs

8.83.1 1 Class

```
class IPython.utils.sentinel.Sentinel(name, module, docstring=None)
```

Базовые классы: `object`

```
__init__(name, module, docstring=None)
```

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

8.84 Module: `utils.shimmodule`

A shim module for deprecated imports

8.84.1 3 Classes

```
class IPython.utils.shimmodule.ShimWarning
```

Базовые классы: `Warning`

A warning to show when a module has moved, and a shim is in its place.

```
class IPython.utils.shimmodule.ShimImporter(src, mirror)
```

Базовые классы: `MetaPathFinder`

Import hook for a shim.

This ensures that submodule imports return the real target module, not a clone that will confuse `is` and `isinstance` checks.

```
__init__(src, mirror)
```

```
class IPython.utils.shimmodule.ShimModule(*args, **kwargs)
```

Базовые классы: `module`

```
__init__(*args, **kwargs)
```

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

8.85 Module: `utils.strdispatch`

String dispatch class to match regexps and dispatch commands.

8.85.1 1 Class

```
class IPython.utils.strdispatch.StrDispatch
```

Базовые классы: `object`

Dispatch (lookup) a set of strings / regexps for match.

Example:

```
>>> dis = StrDispatch()
>>> dis.add_s('hei',34, priority = 4)
>>> dis.add_s('hei',123, priority = 2)
>>> dis.add_re('h.i', 686)
>>> print(list(dis.flat_matches('hei')))
[123, 34, 686]
```

`__init__()`

`add_re(regex, obj, priority=0)`

Adds a target regexp for dispatching

`add_s(s, obj, priority=0)`

Adds a target „string“ for dispatching

`dispatch(key)`

Get a seq of Commandchain objects that match key

`flat_matches(key)`

Yield all „value“ targets, without priority

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

8.86 Module: `utils.sysinfo`

Utilities for getting information about IPython and the system it's running in.

8.86.1 5 Functions

`IPython.utils.sysinfo.pkg_commit_hash(pkg_path)`

Get short form of commit hash given directory `pkg_path`

We get the commit hash from (in order of preference):

- `IPython.utils._sysinfo.commit`
- git output, if we are in a git repository

If these fail, we return a not-found placeholder tuple

Параметры

`pkg_path` (*str*) – directory containing package only used for getting commit from active repo

Результат

- `hash_from` (*str*) – Where we got the hash from - description
- `hash_str` (*str*) – short form of hash

`IPython.utils.sysinfo.pkg_info(pkg_path)`

Return dict describing the context of this package

Параметры

`pkg_path` (*str*) – path containing `__init__.py` for package

Результат

`context` – with named parameters of interest

Тип результата

`dict`

`IPython.utils.sysinfo.get_sys_info()`

Return useful information about IPython and the system, as a dict.

`IPython.utils.sysinfo.sys_info()`

Return useful information about IPython and the system, as a string.

Примеры

```
In [2]: print(sys_info())
{'commit_hash': '144fdae',          # random
 'commit_source': 'repository',
 'ipython_path': '/home/fperez/usr/lib/python2.6/site-packages/IPython',
 'ipython_version': '0.11.dev',
 'os_name': 'posix',
 'platform': 'Linux-2.6.35-22-generic-i686-with-Ubuntu-10.10-maverick',
 'sys_executable': '/usr/bin/python',
 'sys_platform': 'linux2',
 'sys_version': '2.6.6 (r266:84292, Sep 15 2010, 15:52:39) \n[GCC 4.4.5]'}
```

`IPython.utils.sysinfo.num_cpus()`

DEPRECATED

Return the effective number of CPUs in the system as an integer.

This cross-platform function makes an attempt at finding the total number of available CPUs in the system, as returned by various underlying system and python calls.

If it can't find a sensible answer, it returns 1 (though an error *may* make it return a large positive number that's actually incorrect).

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

8.87 Module: `utils.syspathcontext`

Context managers for adding things to `sys.path` temporarily.

Authors:

- Brian Granger

8.87.1 2 Classes

```
class IPython.utils.syspathcontext.appended_to_syspath(dir)
```

Базовые классы: `object`

Deprecated since IPython 8.1, no replacements.

A context for appending a directory to `sys.path` for a second.

```
__init__(dir)
```

```
class IPython.utils.syspathcontext.prepended_to_syspath(dir)
```

Базовые классы: `object`

A context for prepending a directory to `sys.path` for a second.

```
__init__(dir)
```

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

8.88 Module: `utils.tempdir`

This module contains classes - `NamedFileInTemporaryDirectory`, `TemporaryWorkingDirectory`.

These classes add extra features such as creating a named file in temporary directory and creating a context manager for the working directory which is also temporary.

8.88.1 2 Classes

```
class IPython.utils.tempdir.NamedFileInTemporaryDirectory(filename, mode='w+b', bufsize=-1,
                                                         add_to_syspath=False, **kws)
```

Базовые классы: `object`

```
__init__(filename, mode='w+b', bufsize=-1, add_to_syspath=False, **kws)
```

Open a file named `filename` in a temporary directory.

This context manager is preferred over `NamedTemporaryFile` in `stdlib tempfile` when one needs to reopen the file.

Arguments `mode` and `bufsize` are passed to `open`. Rest of the arguments are passed to `TemporaryDirectory`.

```
class IPython.utils.tempdir.TemporaryWorkingDirectory(suffix=None, prefix=None, dir=None,
                                                      ignore_cleanup_errors=False)
```

Базовые классы: `TemporaryDirectory`

Creates a temporary directory and sets the `cwd` to that directory. Automatically reverts to previous `cwd` upon cleanup. Usage example:

```
with TemporaryWorkingDirectory() as tmpdir:
    ...
```

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

8.89 Module: `utils.terminal`

Utilities for working with terminals.

Authors:

- Brian E. Granger
- Fernando Perez
- Alexander Belchenko (e-mail: bialix AT ukr.net)

8.89.1 5 Functions

`IPython.utils.terminal.toggle_set_term_title(val)`

Control whether `set_term_title` is active or not.

`set_term_title()` allows writing to the console titlebar. In embedded widgets this can cause problems, so this call can be used to toggle it on or off as needed.

The default state of the module is for the function to be disabled.

Параметры

`val (bool)` – If True, `set_term_title()` actually writes to the terminal (using the appropriate platform-specific module). If False, it is a no-op.

`IPython.utils.terminal.set_term_title(title)`

Set terminal title using the necessary platform-dependent calls.

`IPython.utils.terminal.restore_term_title()`

Restore, if possible, terminal title to the original state

`IPython.utils.terminal.freeze_term_title()`

`IPython.utils.terminal.get_terminal_size(defaultx=80, defaulty=25)`

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.


Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

8.90 Module: `utils.text`

Utilities for working with strings and text.

Inheritance diagram:



8.90.1 5 Classes

`class IPython.utils.text.LSString`

Базовые классы: `str`

String derivative with a special access attributes.

These are normal strings, but with the special attributes:

`.l` (or `.list`) : value as list (split on newlines). `.n` (or `.nlstr`): original value (the string itself). `.s` (or `.spstr`): value as whitespace-separated string. `.p` (or `.paths`): list of path objects (requires `path.py` package)

Any values which require transformations are computed only once and cached.

Such strings are very useful to efficiently interact with the shell, which typically only understands whitespace-separated options for commands.

`class IPython.utils.text.SList(iterable=(), /)`

Базовые классы: `list`

List derivative with a special access attributes.

These are normal lists, but with the special attributes:

- `.l` (or `.list`) : value as list (the list itself).
- `.n` (or `.nlstr`): value as a string, joined on newlines.
- `.s` (or `.spstr`): value as a string, joined on spaces.
- `.p` (or `.paths`): list of path objects (requires `path.py` package)

Any values which require transformations are computed only once and cached.

`fields(*fields)`

Collect whitespace-separated fields from string list

Allows quick awk-like usage of string lists.

Example data (in var `a`, created by `„a = !ls -l“`):

```
-rwxrwxrwx  1 ville None      18 Dec 14  2006 ChangeLog
drwxrwxrwx+ 6 ville None       0 Oct 24 18:05 IPython
```

- `a.fields(0)` is `['-rwxrwxrwx', 'drwxrwxrwx+']`
- `a.fields(1,0)` is `['1 -rwxrwxrwx', '6 drwxrwxrwx+']` (note the joining by space).
- `a.fields(-1)` is `['ChangeLog', 'IPython']`

`IndexErrors` are ignored.

Without args, `fields()` just `split()`“s the strings.

`grep(pattern, prune=False, field=None)`

Return all strings matching „pattern“ (a regex or callable)

This is case-insensitive. If `prune` is true, return all items NOT matching the pattern.

If `field` is specified, the match must occur in the specified whitespace-separated field.

Examples:

```
a.grep( lambda x: x.startswith('C') )
a.grep('Cha.*log', prune=1)
a.grep('chm', field=-1)
```

`sort(field=None, nums=False)`
 sort by specified fields (see `fields()`)

Example:

```
a.sort(1, nums = True)
```

Sorts a by second field, in numerical order (so that 21 > 3)

`class IPython.utils.text.EvalFormatter`

Базовые классы: `Formatter`

A String Formatter that allows evaluation of simple expressions.

Note that this version interprets a `:` as specifying a format string (as per standard string formatting), so if slicing is required, you must explicitly create a slice.

This is to be used in templating cases, such as the parallel batch script templates, where simple arithmetic on arguments is useful.

Примеры

```
In [1]: f = EvalFormatter()
In [2]: f.format('{n//4}', n=8)
Out[2]: '2'

In [3]: f.format("{greeting[slice(2,4)]}", greeting="Hello")
Out[3]: 'll'
```

`class IPython.utils.text.FullEvalFormatter`

Базовые классы: `Formatter`

A String Formatter that allows evaluation of simple expressions.

Any time a format key is not found in the kwargs, it will be tried as an expression in the kwargs namespace.

Note that this version allows slicing using `[1:2]`, so you cannot specify a format string. Use `EvalFormatter` to permit format strings.

Примеры

```
In [1]: f = FullEvalFormatter()
In [2]: f.format('{n//4}', n=8)
Out[2]: '2'

In [3]: f.format('{list(range(5))[2:4]}')
Out[3]: '[2, 3]'

In [4]: f.format('{3*2}')
Out[4]: '6'
```

class IPython.utils.text.DollarFormatter

Базовые классы: *FullEvalFormatter*

Formatter allowing Itpl style \$foo replacement, for names and attribute access only. Standard {foo} replacement also works, and allows full evaluation of its arguments.

Примеры

```
In [1]: f = DollarFormatter()
In [2]: f.format('{n//4}', n=8)
Out[2]: '2'

In [3]: f.format('23 * 76 is $result', result=23*76)
Out[3]: '23 * 76 is 1748'

In [4]: f.format('$a or {b}', a=1, b=2)
Out[4]: '1 or 2'
```

8.90.2 12 Functions

IPython.utils.text.indent(*instr*, *nspaces=4*, *ntabs=0*, *flatten=False*)

Indent a string a given number of spaces or tabstops.

indent(str,nspaces=4,ntabs=0) -> indent str by ntabs+nspaces.

Параметры

- *instr* (*basestring*) – The string to be indented.
- *nspaces* (*int* (*default: 4*)) – The number of spaces to be indented.
- *ntabs* (*int* (*default: 0*)) – The number of tabs to be indented.
- *flatten* (*bool* (*default: False*)) – Whether to scrub existing indentation. If True, all lines will be aligned to the same indentation. If False, existing indentation will be strictly increased.

Результат

str|unicode

Тип результата

string indented by ntabs and nspaces.

IPython.utils.text.list_strings(*arg*)

Always return a list of strings, given a string or list of strings as input.

Примеры

```
In [7]: list_strings('A single string')
Out[7]: ['A single string']

In [8]: list_strings(['A single string in a list'])
Out[8]: ['A single string in a list']

In [9]: list_strings(['A','list','of','strings'])
Out[9]: ['A', 'list', 'of', 'strings']
```

`IPython.utils.text.marquee(txt='', width=78, mark='*')`
 Return the input string centered in a „marquee“.

Примеры

```
In [16]: marquee('A test',40)
Out[16]: '***** A test *****'

In [17]: marquee('A test',40,'-')
Out[17]: '----- A test -----'

In [18]: marquee('A test',40,' ')
Out[18]: '          A test          '
```

`IPython.utils.text.num_ini_spaces(strng)`
 Return the number of initial spaces in a string

`IPython.utils.text.format_screen(strng)`
 Format a string for screen printing.

This removes some latex-type format codes.

`IPython.utils.text.dedent(text)`
 Equivalent of `textwrap.dedent` that ignores unindented first line.
 This means it will still dedent strings like: „“foo is a bar „“
 For use in `wrap_paragraphs`.

`IPython.utils.text.wrap_paragraphs(text, ncols=80)`
 Wrap multiple paragraphs to fit a specified width.
 This is equivalent to `textwrap.wrap`, but with support for multiple paragraphs, as separated by empty lines.

Тип результата

list of complete paragraphs, wrapped to fill `ncols` columns.

`IPython.utils.text.strip_email_quotes(text)`
 Strip leading email quotation characters („>“).

Removes any combination of leading „>“ interspersed with whitespace that appears *identically* in all lines of the input text.

Параметры

`text (str)` –

Примеры

Simple uses:

```
In [2]: strip_email_quotes('> > text')
Out[2]: 'text'

In [3]: strip_email_quotes('> > text\n> > more')
Out[3]: 'text\nmore'
```

Note how only the common prefix that appears in all lines is stripped:

```
In [4]: strip_email_quotes('> > text\n> > more\n> more...')
Out[4]: '> text\n> more\nmore...'
```

So if any line has no quote marks („>“), then none are stripped from any of them

```
In [5]: strip_email_quotes('> > text\n> > more\nlast different')
Out[5]: '> > text\n> > more\nlast different'
```

`IPython.utils.text.strip_ansi(source)`

Remove ansi escape codes from text.

Параметры

`source` (*str*) – Source to remove the ansi from

`IPython.utils.text.compute_item_matrix(items, row_first=False, empty=None, *args, **kwargs)`

Returns a nested list, and info to columnize items

Параметры

- `items` – list of strings to columnize
- `row_first` ((*default False*)) – Whether to compute columns for a row-first matrix instead of column-first (default).
- `empty` ((*default None*)) – default value to fill list if needed
- `separator_size` (*int* (*default=2*)) – How much characters will be used as a separation between each columns.
- `displaywidth` (*int* (*default=80*)) – The width of the area onto which the columns should enter

Результат

- `strings_matrix` – nested list of string, the outer most list contains as many list as rows, the innermost lists have each as many element as columns. If the total number of elements in `items` does not equal the product of rows*columns, the last element of some lists are filled with `None`.

- `dict_info` – some info to make columnize easier:

num_columns

number of columns

max_rows

maximum number of rows (final number may be less)

column_widths

list of with of each columns

optimal_separator_width
best separator width between columns

Примеры

```
In [1]: l = ['aaa', 'b', 'cc', 'd', 'eeee', 'f', 'g', 'h', 'i', 'j', 'k', 'l']
In [2]: list, info = compute_item_matrix(l, displaywidth=12)
In [3]: list
Out[3]: [['aaa', 'f', 'k'], ['b', 'g', 'l'], ['cc', 'h', None], ['d', 'i', None], [
↪ 'eeee', 'j', None]]
In [4]: ideal = {'num_columns': 3, 'column_widths': [5, 1, 1], 'optimal_separator_
↪ width': 2, 'max_rows': 5}
In [5]: all((info[k] == ideal[k] for k in ideal.keys()))
Out[5]: True
```

IPython.utils.text.columnize(*items*, *row_first=False*, *separator=' '*, *displaywidth=80*, *spread=False*)
Transform a list of strings into a single string with columns.

Параметры

- *items* (*sequence of strings*) – The strings to process.
- *row_first* ((*default False*)) – Whether to compute columns for a row-first matrix instead of column-first (default).
- *separator* (*str*, *optional [default is two spaces]*) – The string that separates columns.
- *displaywidth* (*int*, *optional [default is 80]*) – Width of the display in number of characters.

Тип результата

The formatted string.

IPython.utils.text.get_text_list(*list_*, *last_sep=' and '*, *sep=', '*, *wrap_item_with=''*)
Return a string with a natural enumeration of items

```
>>> get_text_list(['a', 'b', 'c', 'd'])
'a, b, c and d'
>>> get_text_list(['a', 'b', 'c'], ' or ')
'a, b or c'
>>> get_text_list(['a', 'b', 'c'], ', ')
'a, b, c'
>>> get_text_list(['a', 'b'], ' or ')
'a or b'
>>> get_text_list(['a'])
'a'
>>> get_text_list([])
''
>>> get_text_list(['a', 'b'], wrap_item_with="`)")
'`a` and `b`'
>>> get_text_list(['a', 'b', 'c', 'd'], " = ", sep=" + ")
'a + b + c = d'
```

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

8.91 Module: `utils.timing`

Utilities for timing code execution.

8.91.1 7 Functions

`IPython.utils.timing.clocku()` → floating point number

Return the *USER* CPU time in seconds since the start of the process. This is done via a call to `resource.getrusage`, so it avoids the wraparound problems in `time.clock()`.

`IPython.utils.timing.clocks()` → floating point number

Return the *SYSTEM* CPU time in seconds since the start of the process. This is done via a call to `resource.getrusage`, so it avoids the wraparound problems in `time.clock()`.

`IPython.utils.timing.clock()` → floating point number

Return the *TOTAL USER+SYSTEM* CPU time in seconds since the start of the process. This is done via a call to `resource.getrusage`, so it avoids the wraparound problems in `time.clock()`.

`IPython.utils.timing.clock2()`

Similar to `clock()`, but return a tuple of user/system times.

`IPython.utils.timing.timings_out(reps, func, *args, **kw)`

Execute a function `reps` times, return a tuple with the elapsed total CPU time in seconds, the time per call and the function's output.

Under Unix, the return value is the sum of user+system time consumed by the process, computed via the `resource` module. This prevents problems related to the wraparound effect which the `time.clock()` function has.

Under Windows the return value is in wall clock seconds. See the documentation for the `time` module for more details.

`IPython.utils.timing.timings(reps, func, *args, **kw)`

Execute a function `reps` times, return a tuple with the elapsed total CPU time in seconds and the time per call. These are just the first two values in `timings_out()`.

`IPython.utils.timing.timing(func, *args, **kw)` → `t_total`

Execute a function once, return the elapsed total CPU time in seconds. This is just the first value in `timings_out()`.

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

8.92 Module: `utils.tokenutil`

Token-related utilities

8.92.1 3 Functions

`IPython.utils.tokenutil.generate_tokens(readline)`

wrap `generate_tokens` to catch EOF errors

`IPython.utils.tokenutil.line_at_cursor(cell, cursor_pos=0)`

Return the line in a cell at a given cursor position

Used for calling line-based APIs that don't support multi-line input, yet.

Параметры

- `cell` (*str*) – multiline block of text
- `cursor_pos` (*integer*) – the cursor position

Результат

(`line`, `offset`) – The line with the current cursor, and the character offset of the start of the line.

Тип результата

(string, integer)

`IPython.utils.tokenutil.token_at_cursor(cell, cursor_pos=0)`

Get the token at a given cursor

Used for introspection.

Function calls are prioritized, so the token for the callable will be returned if the cursor is anywhere inside the call.

Параметры

- `cell` (*unicode*) – A block of Python code
- `cursor_pos` (*int*) – The location of the cursor in the block where the token should be found

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

8.93 Module: `utils.tz`

Timezone utilities

Just UTC-awareness right now

8.93.1 1 Class

`class IPython.utils.tz.tzUTC`

Базовые классы: `tzinfo`

`tzinfo` object for UTC (zero offset)

`dst(d)`

datetime -> DST offset as timedelta positive east of UTC.

`utcoffset(d)`

datetime -> timedelta showing offset from UTC, negative values indicating West of UTC

8.93.2 1 Function

`IPython.utils.tz.utc_aware(unknown)`

decorator for adding UTC `tzinfo` to datetime's `utcoffset` methods

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

8.94 Module: `utils.ulinecache`

This module has been deprecated since IPython 6.0.

Wrapper around `linecache` which decodes files to unicode according to PEP 263.

8.94.1 1 Function

`IPython.utils.ulinecache.getlines(filename, module_globals=None)`

Get the lines for a Python source file from the cache. Update the cache if it doesn't contain an entry for this file already.

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

8.95 Module: `utils.wildcard`

Support for wildcard pattern matching in object inspection.

8.95.1 Authors

- Jörgen Stenarson <jorgen.stenarson@bostream.nu>
- Thomas Kluyver

8.95.2 6 Functions

`IPython.utils.wildcard.create_typedict(dont_include_in_type2typestr=['lambda'])`

Return dictionaries mapping lower case typename (e.g. „tuple“) to type objects from the `types` package, and vice versa.

`IPython.utils.wildcard.is_type(obj, typestr_or_type)`

`is_type(obj, typestr_or_type)` verifies if `obj` is of a certain type. It can take strings or actual python types for the second argument, i.e. „tuple“ <-> `TupleType`. „all“ matches all types.

TODO: Should be extended for choosing more than one type.

`IPython.utils.wildcard.show_hidden(str, show_all=False)`

Return true for strings starting with single `_` if `show_all` is true.

`IPython.utils.wildcard.dict_dir(obj)`

Produce a dictionary of an object's attributes. Builds on `dir2` by checking that a `getattr()` call actually succeeds.

`IPython.utils.wildcard.filter_ns(ns, name_pattern='*', type_pattern='all', ignore_case=True, show_all=True)`

Filter a namespace dictionary by name pattern and item type.

`IPython.utils.wildcard.list_namespace(namespace, type_pattern, filter, ignore_case=False, show_all=False)`

Return dictionary of all objects in a namespace dictionary that match `type_pattern` and `filter`.

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

Директива IPython Sphinx

Примечание: The IPython Sphinx Directive is in „beta“ and currently under active development. Improvements to the code or documentation are welcome!

The *ipython* directive is a stateful shell that can be used in reStructured text files.

It knows about standard ipython prompts, and extracts the input and output lines. These prompts will be renumbered starting at 1. The inputs will be fed to an embedded ipython interpreter and the outputs from that interpreter will be inserted as well. For example, code blocks like the following:

```
.. ipython::

    In [136]: x = 2

    In [137]: x**3
    Out[137]: 8
```

will be rendered as

```
In [1]: x = 2

In [2]: x**3
Out[2]: 8
```

Примечание: This tutorial should be read side-by-side with the Sphinx source for this document because otherwise you will see only the rendered output and not the code that generated it. Excepting the example above, we will not in general be showing the literal ReST in this document that generates the rendered output.

9.1 Директивы и параметры

The IPython directive takes a number of options detailed here.

```
.. ipython::
    Create an IPython directive.

:doctest:
    Run a doctest on IPython code blocks in rst.

:python:
    Used to indicate that the relevant code block does not have IPython prompts.

:okexcept:
    Allow the code block to raise an exception.

:okwarning:
    Allow the code block to emit an warning.

:suppress:
    Silence any warnings or expected errors.

:verbatim:
    A noop that allows for any text to be syntax highlighted as valid IPython code.

:savefig: OUTFILE [IMAGE_OPTIONS]
    Save output from matplotlib to outfile.
```

It's important to note that all of these options can be used for the entire directive block or they can decorate individual lines of code as explained in *Псевдодекораторы*.

9.2 Сохранение сеанса Python в блоках директив IPython

The state from previous sessions is stored, and standard error is trapped. At doc build time, ipython's output and std err will be inserted, and prompts will be renumbered. So the prompt below should be renumbered in the rendered docs, and pick up where the block above left off.

```
In [3]: z = x*3    # x is recalled from previous block

In [4]: z
Out[4]: 6

In [5]: print(z)
6

In [6]: q = z[]    # this is a syntax error -- we trap ipy exceptions
-----
File "<ipython console>", line 1
  q = z[]    # this is a syntax error -- we trap ipy exceptions
      ^
SyntaxError: invalid syntax
```


9.3 Добавление тестов документации в вашу директиву IPython

The embedded interpreter supports some limited markup. For example, you can put comments in your ipython sessions, which are reported verbatim. There are some handy «pseudo-decorators» that let you doctest the output. The inputs are fed to an embedded ipython session and the outputs from the ipython session are inserted into your doc. If the output in your doc and in the ipython session don't match on a doctest assertion, an error will occur.

```
In [7]: x = 'hello world'

# this will raise an error if the ipython output is different
In [8]: x.upper()
Out[8]: 'HELLO WORLD'

# some readline features cannot be supported, so we allow
# "verbatim" blocks, which are dumped in verbatim except prompts
# are continuously numbered
In [9]: x.st<TAB>
x.startswith x.strip
```

For more information on @doctest decorator, please refer to the end of this page in Pseudo-Decorators section.

9.4 Многострочный ввод

Multi-line input is supported.

```
In [10]: url = 'http://ichart.finance.yahoo.com/table.csv?s=CROX\
....: &d=9&e=22&f=2009&g=d&a=1&br=8&c=2006&ignore=.csv'
....:

In [11]: print(url.split('&'))
['http://ichart.finance.yahoo.com/table.csv?s=CROX', 'd=9', 'e=22',
```

9.5 Выходные данные директивы по тестированию

The IPython Sphinx Directive makes it possible to test the outputs that you provide with your code. To do this, decorate the contents in your directive block with one of the options listed above.

If an IPython doctest decorator is found, it will take these steps when your documentation is built:

1. Run the *input* lines in your IPython directive block against the current Python kernel (remember that the session persists across IPython directive blocks);
2. Compare the *output* of this with the output text that you've put in the IPython directive block (what comes after Out [NN]);
3. If there is a difference, the directive will raise an error and your documentation build will fail.

You can do doctest on multi-line output as well. Just be careful when using non-deterministic inputs like random numbers in the ipython directive, because your inputs are run through a live interpreter, so if

you are doctesting random output you will get an error. Here we «seed» the random number generator for deterministic output, and we suppress the seed line so it doesn't show up in the rendered output

```
In [12]: import numpy.random

In [13]: numpy.random.rand(10,2)
Out[13]:
array([[0.64524308, 0.59943846],
       [0.47102322, 0.8715456 ],
       [0.29370834, 0.74776844],
       [0.99539577, 0.1313423 ],
       [0.16250302, 0.21103583],
       [0.81626524, 0.1312433 ],
       [0.67338089, 0.72302393],
       [0.7566368 , 0.07033696],
       [0.22591016, 0.77731835],
       [0.0072729 , 0.34273127]])
```

For more information on `@suppress` and `@doctest` decorators, please refer to the end of this file in Pseudo-Decorators section.

Another demonstration of multi-line input and output

```
In [14]: print(x)
jdjh

In [15]: for i in range(10):
.....:     print(i)
.....:
.....:
0
1
2
3
4
5
6
7
8
9
```

Most of the «pseudo-decorators» can be used as options to ipython mode. For example, to setup matplotlib pylab but suppress the output, you can do. When using the matplotlib `use` directive, it should occur before any import of pylab. This will not show up in the rendered docs, but the commands will be executed in the embedded interpreter and subsequent line numbers will be incremented to reflect the inputs:

```
.. ipython::
   :suppress:

In [144]: from matplotlib.pylab import *

In [145]: ion()
```

Likewise, you can set `:doctest:` or `:verbatim:` to apply these settings to the entire block. For example,

```

In [16]: cd mpl/examples/
/home/jdhunter/mpl/examples

In [17]: pwd
Out[17]: '/home/jdhunter/mpl/examples'

In [18]: cd mpl/examples/<TAB>
mpl/examples/animation/      mpl/examples/misc/
mpl/examples/api/            mpl/examples/mplot3d/
mpl/examples/axes_grid/      mpl/examples/pylab_examples/
mpl/examples/event_handling/  mpl/examples/widgets

In [19]: cd mpl/examples/widgets/
/home/msierig/mpl/examples/widgets

In [20]: !wc *
  2   12   77 README.txt
40   97  884 buttons.py
26   90  712 check_buttons.py
19   52  416 cursor.py
180 404 4882 menu.py
16   45  337 multicursor.py
36  106  916 radio_buttons.py
48  226 2082 rectangle_selector.py
43  118 1063 slider_demo.py
40  124 1088 span_selector.py
450 1274 12457 total

```

You can create one or more pyplot plots and insert them with the `@savefig` decorator.



For more information on `@savefig` decorator, please refer to the end of this page in Pseudo-Decorators section.

```

In [21]: plot([1,2,3]);

# use a semicolon to suppress the output
In [22]: hist(np.random.randn(10000), 100);

```




In a subsequent session, we can update the current figure with some text, and then resave

```
In [23]: ylabel('number')
Out[23]: Text(38.09722222222214, 0.5, 'number')

In [24]: title('normal distribution')
Out[24]: Text(0.5, 1.0, 'normal distribution')

In [25]: grid(True)
```



You can also have function definitions included in the source.

```
In [26]: def square(x):
...:     """
...:     An overcomplicated square function as an example.
...:     """
...:     if x < 0:
...:         x = abs(x)
...:     y = x * x
...:     return y
...:
```

Then call it from a subsequent section.

```
In [27]: square(3)
Out[27]: 9

In [28]: square(-2)
Out[28]: 4
```

9.5.1 Написание чистого кода Python

Pure python code is supported by the optional argument `python`. In this pure python syntax you do not include the output from the python interpreter. The following markup:

```
.. ipython:: python

    foo = 'bar'
    print(foo)
    foo = 2
    foo**2
```

Renders as

```
In [29]: foo = 'bar'


In [30]: print(foo)
bar

In [31]: foo = 2

In [32]: foo**2
Out[32]: 4
```

We can even plot from python, using the `savefig` decorator, as well as, suppress output with a semicolon

```
In [33]: plot([1,2,3]);
```



For more information on `@savefig` decorator, please refer to the end of this page in Pseudo-Decorators section.

Similarly, std err is inserted

```
In [34]: foo = 'bar'

In [35]: foo()
[0;36m Cell [0;32mIn[35], line 1[0;36m[0m
[0;31m     foo()[0m
[0m         ^[0m
[0;31mSyntaxError[0m[0;31m:[0m closing parenthesis ')' does not match opening
↪parenthesis '['
```

9.6 Обработка комментариев

Comments are handled and state is preserved

```
# comments are handled
In [36]: print(foo)
bar
```

If you don't see the next code block then the options work.

9.7 Разделение инструкций Python по строкам

Multi-line input is handled.

```
In [37]: line = 'Multi\
....:         line &\
....:         support &\
....:         works'
....:

In [38]: print(line.split('&'))
['Multi         line ', '         support ', '         works']
```

Functions definitions are correctly parsed

```
In [39]: def square(x):
....:     """
....:     An overcomplicated square function as an example.
....:     """
....:     if x < 0:
....:         x = abs(x)
....:     y = x * x
....:     return y
....:
```

And persist across sessions

```
In [40]: print(square(3))
9

In [41]: print(square(-2))
4
```

Pretty much anything you can do with the ipython code, you can do with a simple python script. Obviously, though it doesn't make sense to use the doctest option.

9.8 Псевдодекораторы

Here are the supported decorators, and any optional arguments they take. Some of the decorators can be used as options to the entire block (eg `verbatim` and `suppress`), and some only apply to the line just below them (eg `savefig`).

`@suppress`

execute the ipython input block, but suppress the input and output block from the rendered output. Also, can be applied to the entire `.. ipython` block as a directive option with `:suppress:`.

`@verbatim`

insert the input and output block in verbatim, but auto-increment the line numbers. Internally, the interpreter will be fed an empty string, so it is a no-op that keeps line numbering consistent. Also, can be applied to the entire `.. ipython` block as a directive option with `:verbatim:`.

`@savefig` OUTFILE [IMAGE_OPTIONS]

save the figure to the static directory and insert it into the document, possibly binding it into a minipage and/or putting code/figure label/references to associate the code and the figure. Takes args to pass to the image directive (*scale*, *width*, etc can be kwargs); see [image options](#) for details.

`@doctest`

Compare the pasted in output in the ipython block with the output generated at doc build time, and raise errors if they don't match. Also, can be applied to the entire `.. ipython` block as a directive option with `:doctest:`.

9.9 Параметры конфигурации

`ipython_savefig_dir`

The directory in which to save the figures. This is relative to the Sphinx source directory. The default is `html_static_path`.

`ipython_rgxin`

The compiled regular expression to denote the start of IPython input lines. The default is `re.compile('In [(d+)] :s?(.*)s*')`. You shouldn't need to change this.

`ipython_rgxout`

The compiled regular expression to denote the start of IPython output lines. The default is `re.compile('Out [(d+)] :s?(.*)s*')`. You shouldn't need to change this.

`ipython_promptin`

The string to represent the IPython input prompt in the generated ReST. The default is `'In [%d] : '`. This expects that the line numbers are used in the prompt.

`ipython_promptout`

The string to represent the IPython prompt in the generated ReST. The default is `'Out [%d] : '`. This expects that the line numbers are used in the prompt.

9.10 Автоматически создаваемая документация

Sphinx directive to support embedded IPython code.

IPython provides an extension for [Sphinx](#) to highlight and run code.

This directive allows pasting of entire interactive IPython sessions, prompts and all, and their code will actually get re-executed at doc build time, with all prompts renumbered sequentially. It also allows you to input code as a pure python input by giving the argument `python` to the directive. The output looks like an interactive ipython section.

Here is an example of how the IPython directive can **run** python code, at build time.

```
In [1]: 1+1
Out[1]: 2

In [2]: import datetime
...: datetime.date.fromisoformat('2022-02-22')
...:
Out[2]: datetime.date(2022, 2, 22)
```

It supports IPython construct that plain Python does not understand (like magics):

```
In [3]: import time

In [4]: %pdoc time.sleep
[0;31mClass docstring:[0m
    sleep(seconds)

    Delay execution for a given number of seconds. The argument may be
    a floating point number for subsecond precision.
[0;31mCall docstring:[0m
    Call self as a function.
```

This will also support top-level `async` when using IPython 7.0+

```
In [5]: import asyncio
...: print('before')
...: await asyncio.sleep(1)
...: print('after')
...:
before
after
```

The namespace will persist across multiple code chunks, Let's define a variable:

```
In [6]: who = "World"
```

And now say hello:

```
In [7]: print('Hello,', who)
Hello, World
```

If the current section raises an exception, you can add the `:okexcept:` flag to the current block, otherwise the build will fail.

```
In [8]: 1/0
[0;31m-----[0m
[0;31mZeroDivisionError[0m          Traceback (most recent call last)
Cell [0;32mIn[8], line 1[0m
[0;32m----> 1[0m [38;5;241;43m1[39;49m[38;5;241;43m/[39;49m[38;5;241;43m0[39;49m

[0;31mZeroDivisionError[0m: division by zero
```

9.10.1 IPython Sphinx directive module

To enable this directive, simply list it in your Sphinx `conf.py` file (making sure the directory where you placed it is visible to sphinx, as is needed for all Sphinx directives). For example, to enable syntax highlighting and the IPython directive:

```
extensions = ['IPython.sphinxext.ipython_console_highlighting',
              'IPython.sphinxext.ipython_directive']
```

The IPython directive outputs code-blocks with the language „ipython“. So if you do not have the syntax highlighting extension enabled as well, then all rendered code-blocks will be uncolored. By default this directive assumes that your prompts are unchanged IPython ones, but this can be customized. The configurable options that can be placed in `conf.py` are:

ipython_savefig_dir:

The directory in which to save the figures. This is relative to the Sphinx source directory. The default is `html_static_path`.

ipython_rgxin:

The compiled regular expression to denote the start of IPython input lines. The default is `re.compile('In \[(\d+)\]:\s?(.*)\s*')`. You shouldn't need to change this.

ipython_warning_is_error: [default to True]

Fail the build if something unexpected happen, for example if a block raise an exception but does not have the `:okexcept:` flag. The exact behavior of what is considered strict, may change between the sphinx directive version.

ipython_rgxout:

The compiled regular expression to denote the start of IPython output lines. The default is `re.compile('Out \[(\d+)\]:\s?(.*)\s*')`. You shouldn't need to change this.

ipython_promptin:

The string to represent the IPython input prompt in the generated ReST. The default is `'In [%d]: '`. This expects that the line numbers are used in the prompt.

ipython_promptout:

The string to represent the IPython prompt in the generated ReST. The default is `'Out [%d]: '`. This expects that the line numbers are used in the prompt.

ipython_mplbackend:

The string which specifies if the embedded Sphinx shell should import Matplotlib and set the backend. The value specifies a backend that is passed to `matplotlib.use()` before any lines in `ipython_execlines` are executed. If not specified in `conf.py`, then the default value of „agg“ is used. To use the IPython directive without matplotlib as a dependency, set the value to `None`. It may end up that matplotlib is still imported if the user specifies so in `ipython_execlines` or makes use of the `@savefig` pseudo decorator.

ipython_execlines:

A list of strings to be exec'd in the embedded Sphinx shell. Typical usage is to make certain packages always available. Set this to an empty list if you wish to have no imports always available. If specified in `conf.py` as `None`, then it has the effect of making no imports available. If omitted from `conf.py` altogether, then the default value of `[„import numpy as np“, „import matplotlib.pyplot as plt“]` is used.

ipython_holdcount

When the `@suppress` pseudo-decorator is used, the execution count can be incremented or not. The default behavior is to hold the execution count, corresponding to a value of `True`. Set this to `False` to increment the execution count after each suppressed command.

As an example, to use the IPython directive when `matplotlib` is not available, one sets the backend to `None`:

```
ipython_mplbackend = None
```

An example usage of the directive is:

```
.. ipython::

    In [1]: x = 1

    In [2]: y = x**2

    In [3]: print(y)
```

See http://matplotlib.org/sampledoc/ipython_directive.html for additional documentation.

9.10.2 Pseudo-Decorators

Note: Only one decorator is supported per input. If more than one decorator is specified, then only the last one is used.

In addition to the Pseudo-Decorators/options described at the above link, several enhancements have been made. The directive will emit a message to the console at build-time if code-execution resulted in an exception or warning. You can suppress these on a per-block basis by specifying the `:okexcept:` or `:okwarning:` options:

```
.. ipython::
    :okexcept:
    :okwarning:

    In [1]: 1/0
    In [2]: # raise warning.
```

9.10.3 To Do

- Turn the ad-hoc `test()` function into a real test suite.
- Break up ipython-specific functionality from matplotlib stuff into better separated code.

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

10.1 История

10.1.1 Происхождение

IPython был основан в 2001 году Фернандо Пересом, когда он был аспирантом Университета Колорадо в Боулдере. IPython, каким мы его знаем сегодня, вырос из следующих трех проектов:

- ipython Фернандо Переса. Фернандо начал использовать Python, а ipython появился как

результат его стремления к таким вещам, как подсказки в стиле Mathematica, доступ к предыдущему выводу (опять же, как синтаксис `% Mathematica`) и гибкая система настройки (что-то лучше, чем `PYTHONSTARTUP`). * IPP Янко Хаузера. Очень хорошо организовано, отличное удобство использования. Была старая справочная система. IPP использовался в качестве кода «контейнера» в который добавили функциональность из ipython и LazyPython. * LazyPython от Натана Грея. Простой, но очень мощный. Быстрый синтаксис (автоматические скобки, автоматические кавычки) и подробные/цветные трассировки все они были взяты отсюда.

Вот как Фернандо описывает раннюю историю IPython:

Когда я узнал об IPP и LazyPython, я попытался соединить все три в единую систему. Я подумал, что это могло бы обеспечить очень хорошую рабочую среду, как для регулярного программирования, так и для научных вычислений: функции, подобные bash, числовые методы IDL/Matlab, Mathematica-тип оперативная история и отличный самоанализ объекта и вспомогательных средств. Я думаю, что оно сработалось достаточно хорошо, хотя было намного больше работы, чем я изначально планировал.

Предупреждение: This documentation covers a development version of IPython. The development version may differ significantly from the latest stable release.

Важно: This documentation covers IPython versions 6.0 and higher. Beginning with version 6.0, IPython stopped supporting compatibility with Python versions lower than 3.3 including all versions of Python 2.7.

If you are looking for an IPython version compatible with Python 2.7, please use the IPython 5.x LTS release and refer to its documentation (LTS is the long term support release).

10.2 Licenses and Copyright

10.2.1 Licenses

IPython source code and examples are licensed under the terms of the new or revised BSD license, as follows:

```
Copyright (c) 2011, IPython Development Team
```

```
All rights reserved.
```

```
Redistribution and use in source and binary forms, with or without  
modification, are permitted provided that the following conditions are  
met:
```

```
Redistributions of source code must retain the above copyright notice,  
this list of conditions and the following disclaimer.
```

```
Redistributions in binary form must reproduce the above copyright notice,  
this list of conditions and the following disclaimer in the documentation  
and/or other materials provided with the distribution.
```

```
Neither the name of the IPython Development Team nor the names of its  
contributors may be used to endorse or promote products derived from this  
software without specific prior written permission.
```

```
THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS  
IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO,  
THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR  
PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR  
CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,  
EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,  
PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
```

(continues on next page)

(продолжение с предыдущей страницы)

PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

IPython documentation, examples and other materials are licensed under the terms of the Attribution 4.0 International (CC BY 4.0) license, as follows:

Creative Commons Attribution 4.0 International Public License

By exercising the Licensed Rights (defined below), You accept and agree to be bound by the terms and conditions of this Creative Commons Attribution 4.0 International Public License ("Public License"). To the extent this Public License may be interpreted as a contract, You are granted the Licensed Rights in consideration of Your acceptance of these terms and conditions, and the Licensor grants You such rights in consideration of benefits the Licensor receives from making the Licensed Material available under these terms and conditions.

Section 1 -- Definitions.

- a. Adapted Material means material subject to Copyright and Similar Rights that is derived from or based upon the Licensed Material and in which the Licensed Material is translated, altered, arranged, transformed, or otherwise modified in a manner requiring permission under the Copyright and Similar Rights held by the Licensor. For purposes of this Public License, where the Licensed Material is a musical work, performance, or sound recording, Adapted Material is always produced where the Licensed Material is synched in timed relation with a moving image.
- b. Adapter's License means the license You apply to Your Copyright and Similar Rights in Your contributions to Adapted Material in accordance with the terms and conditions of this Public License.
- c. Copyright and Similar Rights means copyright and/or similar rights closely related to copyright including, without limitation, performance, broadcast, sound recording, and Sui Generis Database Rights, without regard to how the rights are labeled or categorized. For purposes of this Public License, the rights specified in Section 2(b)(1)-(2) are not Copyright and Similar Rights.
- d. Effective Technological Measures means those measures that, in the absence of proper authority, may not be circumvented under laws fulfilling obligations under Article 11 of the WIPO Copyright Treaty adopted on December 20, 1996, and/or similar international agreements.
- e. Exceptions and Limitations means fair use, fair dealing, and/or any other exception or limitation to Copyright and Similar Rights

(continues on next page)

(продолжение с предыдущей страницы)

that applies to Your use of the Licensed Material.

- f. Licensed Material means the artistic **or** literary work, database, **or** other material to which the Licensor applied this Public License.
- g. Licensed Rights means the rights granted to You subject to the terms **and** conditions of this Public License, which are limited to **all** Copyright **and** Similar Rights that apply to Your use of the Licensed Material **and** that the Licensor has authority to license.
- h. Licensor means the individual(s) **or** entity(ies) granting rights under this Public License.
- i. Share means to provide material to the public by **any** means **or** process that requires permission under the Licensed Rights, such **as** reproduction, public display, public performance, distribution, dissemination, communication, **or** importation, **and** to make material available to the public including **in** ways that members of the public may access the material **from a** place **and** at a time individually chosen by them.
- j. Sui Generis Database Rights means rights other than copyright resulting **from Directive 96/9/EC** of the European Parliament **and** of the Council of **11 March 1996** on the legal protection of databases, **as amended and/or** succeeded, **as well as** other essentially equivalent rights anywhere **in** the world.
- k. You means the individual **or** entity exercising the Licensed Rights under this Public License. Your has a corresponding meaning.

Section 2 -- Scope.

a. License grant.

1. Subject to the terms **and** conditions of this Public License, the Licensor hereby grants You a worldwide, royalty-free, non-sublicensable, non-exclusive, irrevocable license to exercise the Licensed Rights **in** the Licensed Material to:
 - a. reproduce **and** Share the Licensed Material, **in** whole **or** **in** part; **and**
 - b. produce, reproduce, **and** Share Adapted Material.
2. Exceptions **and** Limitations. For the avoidance of doubt, where Exceptions **and** Limitations apply to Your use, this Public License does **not** apply, **and** You do **not** need to comply **with** its terms **and** conditions.
3. Term. The term of this Public License **is** specified **in** Section

(continues on next page)

(продолжение с предыдущей страницы)

6(a).

4. Media and formats; technical modifications allowed. The Licensor authorizes You to exercise the Licensed Rights in all media and formats whether now known or hereafter created, and to make technical modifications necessary to do so. The Licensor waives and/or agrees not to assert any right or authority to forbid You from making technical modifications necessary to exercise the Licensed Rights, including technical modifications necessary to circumvent Effective Technological Measures. For purposes of this Public License, simply making modifications authorized by this Section 2(a)(4) never produces Adapted Material.

5. Downstream recipients.

- a. Offer from the Licensor -- Licensed Material. Every recipient of the Licensed Material automatically receives an offer from the Licensor to exercise the Licensed Rights under the terms and conditions of this Public License.
- b. No downstream restrictions. You may not offer or impose any additional or different terms or conditions on, or apply any Effective Technological Measures to, the Licensed Material if doing so restricts exercise of the Licensed Rights by any recipient of the Licensed Material.

6. No endorsement. Nothing in this Public License constitutes or may be construed as permission to assert or imply that You are, or that Your use of the Licensed Material is, connected with, or sponsored, endorsed, or granted official status by, the Licensor or others designated to receive attribution as provided in Section 3(a)(1)(A)(i).

b. Other rights.

- 1. Moral rights, such as the right of integrity, are not licensed under this Public License, nor are publicity, privacy, and/or other similar personality rights; however, to the extent possible, the Licensor waives and/or agrees not to assert any such rights held by the Licensor to the limited extent necessary to allow You to exercise the Licensed Rights, but not otherwise.
- 2. Patent and trademark rights are not licensed under this Public License.
- 3. To the extent possible, the Licensor waives any right to collect royalties from You for the exercise of the Licensed Rights, whether directly or through a collecting society

(continues on next page)

(продолжение с предыдущей страницы)

under **any** voluntary **or** waivable statutory **or** compulsory licensing scheme. In **all** other cases the Licensor expressly reserves **any** right to collect such royalties.

Section 3 -- License Conditions.

Your exercise of the Licensed Rights **is** expressly made subject to the following conditions.

a. Attribution.

1. If You Share the Licensed Material (including **in** modified form), You must:
 - a. retain the following **if** it **is** supplied by the Licensor **with** the Licensed Material:
 - i. identification of the creator(s) of the Licensed Material **and** **any** others designated to receive attribution, **in** **any** reasonable manner requested by the Licensor (including by pseudonym **if** designated);
 - ii. a copyright notice;
 - iii. a notice that refers to this Public License;
 - iv. a notice that refers to the disclaimer of warranties;
 - v. a URI **or** hyperlink to the Licensed Material to the extent reasonably practicable;
 - b. indicate **if** You modified the Licensed Material **and** retain an indication of **any** previous modifications; **and**
 - c. indicate the Licensed Material **is** licensed under this Public License, **and** include the text of, **or** the URI **or** hyperlink to, this Public License.
2. You may satisfy the conditions **in** Section 3(a)(1) **in** **any** reasonable manner based on the medium, means, **and** context **in** which You Share the Licensed Material. For example, it may be reasonable to satisfy the conditions by providing a URI **or** hyperlink to a resource that includes the required information.
3. If requested by the Licensor, You must remove **any** of the information required by Section 3(a)(1)(A) to the extent reasonably practicable.

(continues on next page)

(продолжение с предыдущей страницы)

4. If You Share Adapted Material You produce, the Adapter's License You apply must **not** prevent recipients of the Adapted Material **from complying with** this Public License.

Section 4 -- Sui Generis Database Rights.

Where the Licensed Rights include Sui Generis Database Rights that apply to Your use of the Licensed Material:

- a. **for** the avoidance of doubt, Section 2(a)(1) grants You the right to extract, reuse, reproduce, **and Share all or** a substantial portion of the contents of the database;
- b. **if** You include **all or** a substantial portion of the database contents **in** a database **in** which You have Sui Generis Database Rights, then the database **in** which You have Sui Generis Database Rights (but **not** its individual contents) **is** Adapted Material; **and**
- c. You must comply **with** the conditions **in** Section 3(a) **if** You Share **all or** a substantial portion of the contents of the database.

For the avoidance of doubt, this Section 4 supplements **and** does **not** replace Your obligations under this Public License where the Licensed Rights include other Copyright **and** Similar Rights.

Section 5 -- Disclaimer of Warranties **and** Limitation of Liability.

- a. UNLESS OTHERWISE SEPARATELY UNDERTAKEN BY THE LICENSOR, TO THE EXTENT POSSIBLE, THE LICENSOR OFFERS THE LICENSED MATERIAL AS-IS AND AS-AVAILABLE, AND MAKES NO REPRESENTATIONS OR WARRANTIES OF ANY KIND CONCERNING THE LICENSED MATERIAL, WHETHER EXPRESS, IMPLIED, STATUTORY, OR OTHER. THIS INCLUDES, WITHOUT LIMITATION, WARRANTIES OF TITLE, MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, NON-INFRINGEMENT, ABSENCE OF LATENT OR OTHER DEFECTS, ACCURACY, OR THE PRESENCE OR ABSENCE OF ERRORS, WHETHER OR NOT KNOWN OR DISCOVERABLE. WHERE DISCLAIMERS OF WARRANTIES ARE NOT ALLOWED IN FULL OR IN PART, THIS DISCLAIMER MAY NOT APPLY TO YOU.
- b. TO THE EXTENT POSSIBLE, IN NO EVENT WILL THE LICENSOR BE LIABLE TO YOU ON ANY LEGAL THEORY (INCLUDING, WITHOUT LIMITATION, NEGLIGENCE) OR OTHERWISE FOR ANY DIRECT, SPECIAL, INDIRECT, INCIDENTAL, CONSEQUENTIAL, PUNITIVE, EXEMPLARY, OR OTHER LOSSES, COSTS, EXPENSES, OR DAMAGES ARISING OUT OF THIS PUBLIC LICENSE OR USE OF THE LICENSED MATERIAL, EVEN IF THE LICENSOR HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH LOSSES, COSTS, EXPENSES, OR DAMAGES. WHERE A LIMITATION OF LIABILITY IS NOT ALLOWED IN FULL OR IN PART, THIS LIMITATION MAY NOT APPLY TO YOU.
- c. The disclaimer of warranties **and** limitation of liability provided above shall be interpreted **in** a manner that, to the extent

(continues on next page)

(продолжение с предыдущей страницы)

possible, most closely approximates an absolute disclaimer and waiver of all liability.

Section 6 -- Term and Termination.

- a. This Public License applies for the term of the Copyright and Similar Rights licensed here. However, if You fail to comply with this Public License, then Your rights under this Public License terminate automatically.
- b. Where Your right to use the Licensed Material has terminated under Section 6(a), it reinstates:
 1. automatically as of the date the violation is cured, provided it is cured within 30 days of Your discovery of the violation; or
 2. upon express reinstatement by the Licensor.

For the avoidance of doubt, this Section 6(b) does not affect any right the Licensor may have to seek remedies for Your violations of this Public License.

- c. For the avoidance of doubt, the Licensor may also offer the Licensed Material under separate terms or conditions or stop distributing the Licensed Material at any time; however, doing so will not terminate this Public License.
- d. Sections 1, 5, 6, 7, and 8 survive termination of this Public License.

Section 7 -- Other Terms and Conditions.

- a. The Licensor shall not be bound by any additional or different terms or conditions communicated by You unless expressly agreed.
- b. Any arrangements, understandings, or agreements regarding the Licensed Material not stated herein are separate from and independent of the terms and conditions of this Public License.

Section 8 -- Interpretation.

- a. For the avoidance of doubt, this Public License does not, and shall not be interpreted to, reduce, limit, restrict, or impose conditions on any use of the Licensed Material that could lawfully be made without permission under this Public License.
- b. To the extent possible, if any provision of this Public License is deemed unenforceable, it shall be automatically reformed to the

(continues on next page)

(продолжение с предыдущей страницы)

minimum extent necessary to make it enforceable. If the provision cannot be reformed, it shall be severed from this Public License without affecting the enforceability of the remaining terms and conditions.

- c. No term or condition of this Public License will be waived and no failure to comply consented to unless expressly agreed to by the Licensor.
- d. Nothing in this Public License constitutes or may be interpreted as a limitation upon, or waiver of, any privileges and immunities that apply to the Licensor or You, including from the legal processes of any jurisdiction or authority.

10.2.2 About the IPython Development Team

Fernando Perez began IPython in 2001 based on code from Janko Hauser <jhauser-AT-zscout.de> and Nathaniel Gray <n8gray-AT-caltech.edu>. Fernando is still the project lead.

The IPython Development Team is the set of all contributors to the IPython project. This includes all of the IPython subprojects. See the release notes for a list of people who have contributed to each release.

10.2.3 Our Copyright Policy

IPython uses a shared copyright model. Each contributor maintains copyright over their contributions to IPython. But, it is important to note that these contributions are typically only changes (diffs/commits) to the repositories. Thus, the IPython source code, in its entirety is not the copyright of any single person or institution. Instead, it is the collective copyright of the entire IPython Development Team. If individual contributors want to maintain a record of what changes/contributions they have specific copyright on, they should indicate their copyright in the commit message of the change, when they commit the change to one of the IPython repositories.

Any new code contributed to IPython must be licensed under the BSD license or a similar (MIT) open source license.

10.2.4 Miscellaneous

Some files (DPyGetOpt.py, for example) may be licensed under different conditions. Ultimately each file indicates clearly the conditions under which its author/authors have decided to publish the code.

Versions of IPython up to and including 0.6.3 were released under the GNU Lesser General Public License (LGPL), available at <http://www.gnu.org/copyleft/lesser.html>.

Online versions of the Creative Commons licenses can be found at:

- <http://creativecommons.org/licenses/by/4.0/>
- <http://creativecommons.org/licenses/by/4.0/legalcode.txt>

C

IPython.core.alias, 560
IPython.core.application, 562
IPython.core.async_helpers, 564
IPython.core.autocall, 565
IPython.core.builtin_trap, 566
IPython.core.compilerop, 567
IPython.core.completer, 569
IPython.core.completerlib, 584
IPython.core.crashhandler, 585
IPython.core.debugger, 586
IPython.core.error, 591
IPython.core.events, 593
IPython.core.excolors, 594
IPython.core.extensions, 595
IPython.core.formatters, 597
IPython.core.getipython, 604
IPython.core.guarded_eval, 604
IPython.core.history, 606
IPython.core.historyapp, 612
IPython.core.hooks, 613
IPython.core.inputsplitter, 614
IPython.core.inputtransformer, 618
IPython.core.inputtransformer2, 621
IPython.core.interactiveshell, 625
IPython.core.logger, 643
IPython.core.macro, 644
IPython.core.magic, 645
IPython.core.magic_arguments, 650
IPython.core.oinspect, 654
IPython.core.page, 658
IPython.core.payload, 659
IPython.core.payloadpage, 660
IPython.core.prefilter, 660
IPython.core.profileapp, 667
IPython.core.profiledir, 668
IPython.core.prompts, 669
IPython.core.pylabtools, 670
IPython.core.shellapp, 672

IPython.core.splitinput, 674
IPython.core.ultratb, 675

d

IPython.display, 682

e

IPython.extensions.autoreload, 520
IPython.extensions.storemagic, 522

i

IPython, 558

|

IPython.lib.backgroundjobs, 700
IPython.lib.clipboard, 703
IPython.lib.deepreload, 704
IPython.lib.demo, 706
IPython.lib.editorhooks, 712
IPython.lib.guisupport, 713
IPython.lib.latextools, 715
IPython.lib.lexers, 716
IPython.lib.pretty, 720

p

IPython.paths, 725

s

IPython.sphinxext.ipython_directive, 797

t

IPython.terminal.debugger, 725
IPython.terminal.embed, 727
IPython.terminal.interactiveshell, 729
IPython.terminal.ipapp, 734
IPython.terminal.magics, 736
IPython.terminal.prompts, 738
IPython.terminal.shortcuts, 739
IPython.terminal.shortcuts.auto_match, 741

`IPython.terminal.shortcuts.auto_suggest`, 742
`IPython.terminal.shortcuts.filters`, 744
`IPython.testing.ipunittest`, 746
`IPython.testing.skipdoctest`, 748

U

`IPython.utils.capture`, 749
`IPython.utils.colorable`, 750
`IPython.utils.coloransi`, 751
`IPython.utils.contexts`, 753
`IPython.utils.data`, 754
`IPython.utils.decorators`, 754
`IPython.utils.dir2`, 755
`IPython.utils.encoding`, 756
`IPython.utils.frame`, 756
`IPython.utils.generics`, 758
`IPython.utils.importstring`, 758
`IPython.utils.io`, 759
`IPython.utils.ipstruct`, 760
`IPython.utils.module_paths`, 764
`IPython.utils.openpy`, 764
`IPython.utils.path`, 766
`IPython.utils.process`, 768
`IPython.utils.PyColorize`, 748
`IPython.utils.sentinel`, 769
`IPython.utils.shimmodule`, 770
`IPython.utils.strdispatch`, 770
`IPython.utils.sysinfo`, 771
`IPython.utils.syspathcontext`, 773
`IPython.utils.tempdir`, 773
`IPython.utils.terminal`, 774
`IPython.utils.text`, 775
`IPython.utils.timing`, 782
`IPython.utils.tokenutil`, 783
`IPython.utils.tz`, 784
`IPython.utils.ulinecache`, 785
`IPython.utils.wildcard`, 785

СИМВОЛЫ

`:doctest:` (*directive option*)
 `ipython` (*директива*), 788
`:okexcept:` (*directive option*)
 `ipython` (*директива*), 788
`:okwarning:` (*directive option*)
 `ipython` (*директива*), 788
`:python:` (*directive option*)
 `ipython` (*директива*), 788
`:savefig:` (*directive option*)
 `ipython` (*директива*), 788
`:suppress:` (*directive option*)
 `ipython` (*директива*), 788
`:verbatim:` (*directive option*)
 `ipython` (*директива*), 788

модуль

`IPython`, 558
`IPython.core.alias`, 560
`IPython.core.application`, 562
`IPython.core.async_helpers`, 564
`IPython.core.autocall`, 565
`IPython.core.builtin_trap`, 566
`IPython.core.compilerop`, 567
`IPython.core.completer`, 569
`IPython.core.completerlib`, 584
`IPython.core.crashhandler`, 585
`IPython.core.debugger`, 586
`IPython.core.error`, 591
`IPython.core.events`, 593
`IPython.core.excolors`, 594
`IPython.core.extensions`, 595
`IPython.core.formatters`, 597
`IPython.core.getipython`, 604
`IPython.core.guarded_eval`, 604
`IPython.core.history`, 606
`IPython.core.historyapp`, 612
`IPython.core.hooks`, 613
`IPython.core.inputsplitter`, 614
`IPython.core.inputtransformer`, 618

`IPython.core.inputtransformer2`, 621
`IPython.core.interactiveshell`, 625
`IPython.core.logger`, 643
`IPython.core.macro`, 644
`IPython.core.magic`, 645
`IPython.core.magic_arguments`, 650
`IPython.core.oinspect`, 654
`IPython.core.page`, 658
`IPython.core.payload`, 659
`IPython.core.payloadpage`, 660
`IPython.core.prefilter`, 660
`IPython.core.profileapp`, 667
`IPython.core.profiledir`, 668
`IPython.core.prompts`, 669
`IPython.core.pylabtools`, 670
`IPython.core.shellapp`, 672
`IPython.core.splitinput`, 674
`IPython.core.ultratb`, 675
`IPython.display`, 682
`IPython.extensions.autoreload`, 520
`IPython.extensions.storemagic`, 522
`IPython.lib.backgroundjobs`, 700
`IPython.lib.clipboard`, 703
`IPython.lib.deepreload`, 704
`IPython.lib.demo`, 706
`IPython.lib.editorhooks`, 712
`IPython.lib.guisupport`, 713
`IPython.lib.latextools`, 715
`IPython.lib.lexers`, 716
`IPython.lib.pretty`, 720
`IPython.paths`, 725
`IPython.sphinxext.ipython_directive`, 797
`IPython.terminal.debugger`, 725
`IPython.terminal.embed`, 727
`IPython.terminal.interactiveshell`, 729
`IPython.terminal.ipapp`, 734
`IPython.terminal.magics`, 736
`IPython.terminal.prompts`, 738
`IPython.terminal.shortcuts`, 739

IPython.terminal.shortcuts.auto_match, 741	<code>--init__()</code> (метод <i>IPython.core.builtin_trap.BuiltinTrap</i>), 566
IPython.terminal.shortcuts.auto_suggest, 742	<code>--init__()</code> (метод <i>IPython.core.compilerop.CachingCompiler</i>), 567
IPython.terminal.shortcuts.filters, 744	<code>--init__()</code> (метод <i>IPython.core.completer.Completer</i>), 573
IPython.testing.ipunittest, 746	<code>--init__()</code> (метод <i>IPython.core.completer.Completion</i>), 572
IPython.testing.skipdoctest, 748	<code>--init__()</code> (метод <i>IPython.core.completer.CompletionSplitter</i>), 573
IPython.utils.capture, 749	<code>--init__()</code> (метод <i>IPython.core.completer.IPCompleter</i>), 575
IPython.utils.colorable, 750	<code>--init__()</code> (метод <i>IPython.core.completer.SimpleCompletion</i>), 572
IPython.utils.coloransi, 751	<code>--init__()</code> (метод <i>IPython.core.crashhandler.CrashHandler</i>), 585
IPython.utils.contexts, 753	<code>--init__()</code> (метод <i>IPython.core.debugger.Pdb</i>), 588
IPython.utils.data, 754	<code>--init__()</code> (метод <i>IPython.core.events.EventManager</i>), 593
IPython.utils.decorators, 754	<code>--init__()</code> (метод <i>IPython.core.extensions.ExtensionManager</i>), 596
IPython.utils.dir2, 755	<code>--init__()</code> (метод <i>IPython.core.history.HistoryAccessor</i>), 606
IPython.utils.encoding, 756	<code>--init__()</code> (метод <i>IPython.core.history.HistoryManager</i>), 608
IPython.utils.frame, 756	<code>--init__()</code> (метод <i>IPython.core.history.HistorySavingThread</i>), 610
IPython.utils.generics, 758	<code>--init__()</code> (метод <i>IPython.core.hooks.CommandChainDispatcher</i>), 613
IPython.utils.importstring, 758	<code>--init__()</code> (метод <i>IPython.core.inputsplitter.IPythonInputSplitter</i>), 616
IPython.utils.io, 759	<code>--init__()</code> (метод <i>IPython.core.inputsplitter.InMultilineStatement</i>), 614
IPython.utils.ipstruct, 760	<code>--init__()</code> (метод <i>IPython.core.inputsplitter.IncompleteString</i>), 614
IPython.utils.module_paths, 764	<code>--init__()</code> (метод <i>IPython.core.inputsplitter.InputSplitter</i>), 615
IPython.utils.openpy, 764	<code>--init__()</code> (метод <i>IPython.core.inputtransformer.CoroutineInputTr</i>), 619
IPython.utils.path, 766	<code>--init__()</code> (метод <i>IPython.core.inputtransformer.StatelessInputTra</i>), 619
IPython.utils.process, 768	<code>--init__()</code> (метод <i>IPython.core.inputtransformer.TokenInputTransf</i>), 619
IPython.utils.PyColorize, 748	<code>--init__()</code> (метод <i>IPython.core.inputtransformer.assemble__python</i>), 619
IPython.utils.sentinel, 769	<code>--init__()</code> (метод <i>IPython.core.inputtransformer2.HelpEnd</i>), 623
IPython.utils.shimmodule, 770	<code>--init__()</code> (метод <i>IPython.core.inputtransformer2.MaybeAsyncCom</i>), 623
IPython.utils.strdispatch, 770	<code>--init__()</code> (метод <i>IPython.core.inputtransformer2.MaybeAsyncCom</i>), 623
IPython.utils.sysinfo, 771	<code>--init__()</code> (метод <i>IPython.core.inputtransformer2.PromptStripper</i>), 621
IPython.utils.syspathcontext, 773	
IPython.utils.tempdir, 773	
IPython.utils.terminal, 774	
IPython.utils.text, 775	
IPython.utils.timing, 782	
IPython.utils.tokenutil, 783	
IPython.utils.tz, 784	
IPython.utils.ulinecache, 785	
IPython.utils.wildcard, 785	
переменная окружения	
EDITOR, 96, 515	
HOME, 364	
INPUTRC, 367	
IPYTHON_DIR, 252, 546	
IPYTHONDIR, 252, 364, 441, 546	
PATH, 4	
PYTHONSTARTUP, 372, 801	
<code>--init__()</code> (метод <i>IPython.core.alias.Alias</i>), 560	
<code>--init__()</code> (метод <i>IPython.core.alias.AliasManager</i>), 560	
<code>--init__()</code> (метод <i>IPython.core.application.BaseIPythonApplication</i>), 562	
<code>--init__()</code> (метод <i>IPython.core.autocall.IPyAutocall</i>), 565	

`--init__()` (метод `IPython.core.inputtransformer2.TokenTransformer(Base)`), `IPython.display.Audio`), 684
622 `--init__()` (метод `IPython.display.Code`), 685
`--init__()` (метод `IPython.core.inputtransformer2.Transformers(Magic)`), `IPython.display.DisplayHandle`),
623 685
`--init__()` (метод `IPython.core.interactiveshell.ExecutionInfo`), `(метод IPython.display.DisplayObject)`,
625 685
`--init__()` (метод `IPython.core.interactiveshell.ExecutionResult`), `(метод IPython.display.FileLink)`, 686
625 `--init__()` (метод `IPython.display.FileLinks`), 686
`--init__()` (метод `IPython.core.interactiveshell.InteractiveShell`), `(метод IPython.display.GeoJSON)`, 687
625 `--init__()` (метод `IPython.display.HTML`), 688
`--init__()` (метод `IPython.core.logger.Logger`), `--init__()` (метод `IPython.display.IFrame`), 688
643 `--init__()` (метод `IPython.display.Image`), 689
`--init__()` (метод `IPython.core.macro.Macro`), `--init__()` (метод `IPython.display.JSON`), 690
644 `--init__()` (метод `IPython.display.Javascript`),
`--init__()` (метод `IPython.core.magic.MagicAlias`), 690
648 `--init__()` (метод `IPython.display.ProgressBar`),
`--init__()` (метод `IPython.core.magic.Magics`), 691
647 `--init__()` (метод `IPython.display.ScribdDocument`),
`--init__()` (метод `IPython.core.magic.MagicsManager`), 692
645 `--init__()` (метод `IPython.display.Video`), 692
`--init__()` (метод `IPython.core.magic_arguments.ArgMethodWrapper`), `(метод IPython.display.VimeoVideo)`,
652 693
`--init__()` (метод `IPython.core.magic_arguments.MagicArgument(Base)`), `IPython.display.YouTubeVideo`),
652 693
`--init__()` (метод `IPython.core.magic_arguments.kwds`), `--init__()` (метод `IPython.lib.backgroundjobs.BackgroundJobBase`),
653 702
`--init__()` (метод `IPython.core.magic_arguments.magic_arguments`), `(метод IPython.lib.backgroundjobs.BackgroundJobExpr)`,
652 703
`--init__()` (метод `IPython.core.oinspect.Inspector`), `--init__()` (метод `IPython.lib.backgroundjobs.BackgroundJobFunc`),
654 703
`--init__()` (метод `IPython.core.prefilter.PrefilterChecker`), `--init__()` (метод `IPython.lib.backgroundjobs.BackgroundJobManager`),
664 701
`--init__()` (метод `IPython.core.prefilter.PrefilterHandler`), `--init__()` (метод `IPython.lib.demo.Demo`), 709
665 `--init__()` (метод `IPython.lib.lexers.IPyLexer`),
`--init__()` (метод `IPython.core.prefilter.PrefilterManager`), 719
661 `--init__()` (метод `IPython.lib.lexers.IPythonConsoleLexer`),
`--init__()` (метод `IPython.core.prefilter.PrefilterTransformer`), 718
663 `--init__()` (метод `IPython.lib.lexers.IPythonTracebackLexer`),
`--init__()` (метод `IPython.core.prompts.LazyEvaluate`), 717
670 `--init__()` (метод `IPython.lib.pretty.Breakable`),
`--init__()` (метод `IPython.core.splitinput.LineInfo`), 723
674 `--init__()` (метод `IPython.lib.pretty.CallExpression`),
`--init__()` (метод `IPython.core.ultratb.ColorTB`), 724
680 `--init__()` (метод `IPython.lib.pretty.Group`), 723
`--init__()` (метод `IPython.core.ultratb.FormattedTB`), `--init__()` (метод `IPython.lib.pretty.GroupQueue`),
680 723
`--init__()` (метод `IPython.core.ultratb.FrameInfo`), `--init__()` (метод `IPython.lib.pretty.PrettyPrinter`),
679 722
`--init__()` (метод `IPython.core.ultratb.SyntaxTB`), `--init__()` (метод `IPython.lib.pretty.RawStringLiteral`),
681 724
`--init__()` (метод `IPython.core.ultratb.TBTools`), `--init__()` (метод `IPython.lib.pretty.RawText`),
677 724
`--init__()` (метод `IPython.core.ultratb.VerboseTB`), `--init__()` (метод `IPython.lib.pretty.RepresentationPrinter`),
679 723

add_to_parser() (метод *IPython.core.inputtransformer*), 620
IPython.core.magic_arguments.ArgMethodWrapper, 652
 assemble_python_lines (класс в *IPython.core.inputtransformer*), 619
 add_to_parser() (метод *assign_from_magic()* (в модуле *IPython.core.magic_arguments.argument_group*), *IPython.core.inputtransformer*), 620
 653 *assign_from_system()* (в модуле *IPython.core.inputtransformer*), 620
 again() (метод *IPython.lib.demo.Demo*), 709
 alias *AssignmentChecker* (класс в *IPython.core.prefilter*), 664
 magic command, 399
 Alias (класс в *IPython.core.alias*), 560
 alias_magic
 magic command, 400
 AliasError (класс в *IPython.core.alias*), 560
 aliases (амбузм *IPython.lib.lexers.IPyLexer*), 719
 aliases (амбузм *IPython.lib.lexers.IPythonConsoleLexer*), 718
 aliases (амбузм *IPython.lib.lexers.IPythonTracebackLexer*), 717
 AliasManager (класс в *IPython.core.alias*), 560
 all_completions() (метод *IPython.core.completer.IPCompleter*), 575
 all_ns_refs (*IPython.core.interactiveshell.InteractiveShell* (класс в *IPython.display*), 682
 property), 626
 all_quotes_paired() (в модуле *IPython.terminal.shortcuts.filters*), 745
 allow_new_attr() (метод *IPython.utils.ipstruct.Struct*), 761
 append_string() (метод *IPython.terminal.interactiveshell.PtkHistoryAdapter*), 729
 AppendAutoSuggestionInAnyLine (класс в *IPython.terminal.shortcuts.auto_suggest*), 742
 appended_to_syspath (класс в *IPython.utils.syspathcontext*), 773
 apply_transformation() (метод *IPython.terminal.shortcuts.auto_suggest.AppendAutoSuggestionInAnyLine*), 742
 arg_err() (метод *IPython.core.magic.Magics*), 648
 ArgDecorator (класс в *IPython.core.magic_arguments*), 652
 ArgMethodWrapper (класс в *IPython.core.magic_arguments*), 652
 argument (класс в *IPython.core.magic_arguments*), 652
 argument_group (класс в *IPython.core.magic_arguments*), 653
 as_hook() (в модуле *IPython.core.page*), 658
 ask_yes_no() (в модуле *IPython.utils.io*), 760
 assemble_continued_line() (в модуле *IPython.core.inputtransformer2*), 624
 assemble_logical_lines() (в модуле *IPython.core.inputtransformer*), 620
 assign_from_magic() (в модуле *IPython.core.magic_arguments.argument_group*), 620
 assign_from_system() (в модуле *IPython.core.inputtransformer*), 620
 AssignmentChecker (класс в *IPython.core.prefilter*), 664
 ast_node_interactivity (амбузм *IPython.core.interactiveshell.InteractiveShell*), 626
 ast_parse() (метод *IPython.core.compilerop.CachingCompiler*), 567
 ast_transformers (амбузм *IPython.core.interactiveshell.InteractiveShell*), 626
 atexit_operations() (метод *IPython.core.interactiveshell.InteractiveShell*), 626
 attr_matches() (метод *IPython.core.completer.Completer*), 573
 Audio (класс в *IPython.display*), 682
 auto_close_dict_keys (амбузм *IPython.core.completer.Completer*), 573
 auto_create (амбузм *IPython.core.application.BaseIPythonApplication*), 562
 auto_magic (амбузм *IPython.core.magic.MagicsManager*), 645
 auto_match (амбузм *IPython.terminal.interactiveshell.TerminalInteractiveShell*), 730
 auto_match() (в модуле *IPython.terminal.shortcuts.filters*), 745
 auto_rewrite_input() (метод *IPython.terminal.interactiveshell.TerminalInteractiveShell*), 730
 auto_status() (метод *IPython.core.magic.MagicsManager*), 645
 autoawait
 magic command, 401
 autoawait (амбузм *IPython.core.interactiveshell.InteractiveShell*), 627
 autocall
 magic command, 401
 autocall (амбузм *IPython.core.interactiveshell.InteractiveShell*), 627

- 627
AutocallChecker (класс в *IPython.core.prefilter*), 665
AutoFormattedTB (класс в *IPython.core.ultratb*), 680
autoformatter (ампубум *IPython.terminal.interactiveshell.TerminalInteractiveShell*), 730
AutoHandler (класс в *IPython.core.prefilter*), 666
autoindent (ампубум *IPython.core.interactiveshell.InteractiveShell*), 627
autoindent() (метод *IPython.terminal.magics.TerminalMagics*), 736
automagic
magic command, 402
automagic (ампубум *IPython.core.interactiveshell.InteractiveShell*), 627
AutoMagicChecker (класс в *IPython.core.prefilter*), 665
autoreload
magic command, 520
autosuggestions_provider (ампубум *IPython.terminal.interactiveshell.TerminalInteractiveShell*), 730
- ## B
- back() (метод *IPython.lib.demo.Demo*), 709
back_latex_name_matcher() (в модуле *IPython.core.completer*), 583
back_latex_name_matches() (в модуле *IPython.core.completer*), 583
back_unicode_name_matcher() (в модуле *IPython.core.completer*), 582
back_unicode_name_matches() (в модуле *IPython.core.completer*), 583
backends (ампубум *IPython.lib.latextools.LaTeXTool*), 715
BackgroundJobBase (класс в *IPython.lib.backgroundjobs*), 702
BackgroundJobExpr (класс в *IPython.lib.backgroundjobs*), 703
BackgroundJobFunc (класс в *IPython.lib.backgroundjobs*), 703
BackgroundJobManager (класс в *IPython.lib.backgroundjobs*), 701
backslash_combining_completions (ампубум *IPython.core.completer.Completer*), 574
backspace_and_resume_hint() (в модуле *IPython.terminal.shortcuts.auto_suggest*), 743
backup (ампубум *IPython.core.historyapp.HistoryTrim*), 612
banner (ампубум *MyKernel*), 540
banner1 (ампубум *IPython.core.interactiveshell.InteractiveShell*), 627
banner2 (ампубум *IPython.core.interactiveshell.InteractiveShell*), 627
BaseBinding (класс в *IPython.terminal.shortcuts*), 739
BaseFormatter (класс в *IPython.core.formatters*), 599
BaseIPythonApplication (класс в *IPython.core.application*), 562
bash
cell magic, 432
BdbQuit_excepthook() (в модуле *IPython.core.debugger*), 591
BdbQuit_IPython_excepthook() (в модуле *IPython.core.debugger*), 591
begin_group() (метод *IPython.lib.pretty.PrettyPrinter*), 722
Binding (класс в *IPython.terminal.shortcuts*), 739
black_reformat_handler() (в модуле *IPython.terminal.interactiveshell*), 734
bookmark
magic command, 402
braces() (в модуле *IPython.terminal.shortcuts.auto_match*), 741
brackets() (в модуле *IPython.terminal.shortcuts.auto_match*), 741
break_() (метод *IPython.lib.pretty.PrettyPrinter*), 722
break_anywhere() (метод *IPython.core.debugger.Pdb*), 588
Breakable (класс в *IPython.lib.pretty*), 723
breakable() (метод *IPython.lib.pretty.PrettyPrinter*), 722
buffered_tokens() (метод *IPython.lib.lexers.IPythonConsoleLexer*), 718
build_ipy_lexer() (в модуле *IPython.lib.lexers*), 719
BuiltinTrap (класс в *IPython.core.builtin_trap*), 566
Bunch (класс в *IPython.core.magic*), 645
- ## C
- cache() (метод *IPython.core.compilerop.CachingCompiler*), 567
cache_size (ампубум *IPython.core.interactiveshell.InteractiveShell*), 627

CachingCompiler (класс в `IPython.core.compilerop`), 567
 call_pdb (`IPython.core.interactiveshell.InteractiveShell`.`check_complete`() (метод `IPython.core.inputsplitter.InputSplitter`),
 property), 627 `IPython.core.inputsplitter.InputSplitter`,
 CallExpression (класс в `IPython.lib.pretty`), 724 615
 capture check_complete() (метод
 cell magic, 432 `IPython.core.inputtransformer2.TransformerManager`),
 capture_output (класс в `IPython.utils.capture`), 750 623
 CapturedIO (класс в `IPython.utils.capture`), 749 check_complete() (метод
 cast() (в модуле `IPython.core.completer`), 579 `IPython.core.interactiveshell.InteractiveShell`),
 catch_corrupt_db() (в модуле 627
`IPython.core.history`), 611 check_linecache_ipython() (в модуле
 catch_format_error() (в модуле `IPython.core.compilerop`), 568
`IPython.core.formatters`), 603 checkers (`IPython.core.prefilter.PrefilterManager`
 cd property), 662
 magic command, 402 chop() (в модуле `IPython.utils.data`), 754
 cd_completer() (в модуле classic_prompt() (в модуле
`IPython.core.completerlib`), 584 `IPython.core.inputtransformer`), 620
 cell magic ClassicPrompts (класс в
 bash, 432 `IPython.terminal.prompts`), 738
 capture, 432 clear_err_state() (метод
 html, 433 `IPython.core.ultratb.SyntaxTB`), 681
 javascript, 433 clear_main_mod_cache() (метод
 js, 433 `IPython.core.interactiveshell.InteractiveShell`),
 latex, 433 627
 markdown, 433 clear_output() (в модуле `IPython.display`), 694
 perl, 433 ClearDemo (класс в `IPython.lib.demo`), 711
 pypy, 433 ClearIPDemo (класс в `IPython.lib.demo`), 711
 python, 433 ClearMixin (класс в `IPython.lib.demo`), 711
 python2, 433 clipboard_get() (в модуле `IPython.core.hooks`),
 python3, 434 614
 ruby, 434 ClipboardEmpty (класс в `IPython.lib.clipboard`), 703
 script, 434 clock() (в модуле `IPython.utils.timing`), 782
 sh, 434 clock2() (в модуле `IPython.utils.timing`), 782
 svg, 435 clocks() (в модуле `IPython.utils.timing`), 782
 writefile, 435 clocku() (в модуле `IPython.utils.timing`), 782
 cell_magic() (в модуле close() (метод `IPython.utils.io.Tee`), 759
`IPython.core.inputtransformer2`), 624 close_log() (метод `IPython.core.logger.Logger`),
 cellmagic() (в модуле 643
`IPython.core.inputtransformer`), 620 cmdloop() (метод `IPython.core.debugger.InterruptiblePdb`),
 check() (метод `IPython.core.prefilter.AssignmentChecker`), 591 cmdloop() (метод `IPython.terminal.debugger.TerminalPdb`),
 664 Code (класс в `IPython.display`), 684
 check() (метод `IPython.core.prefilter.AutocallChecker`), 726 code_name() (в модуле `IPython.core.compilerop`),
 665 568
 check() (метод `IPython.core.prefilter.AutoMagicChecker`), code_to_run (атрибут
 665 `IPython.core.shellapp.InteractiveShellApp`),
 check() (метод `IPython.core.prefilter.EmacsChecker`), 672
 664 color_info (атрибут
 check() (метод `IPython.core.prefilter.IPyAutocallChecker`), `IPython.core.interactiveshell.InteractiveShell`),
 664 628
 check() (метод `IPython.core.prefilter.MacroChecker`), `IPython.core.interactiveshell.InteractiveShell`,
 664 628
 check() (метод `IPython.core.prefilter.PrefilterChecker`), `IPython.core.ultratb.TBTools`), 677
 664

- Colorable (класс в *IPython.utils.colorable*), 751
 colors
 magic command, 403
 colors (атрибут *IPython.core.interactiveshell.InteractiveShell*), 628
 ColorScheme (класс в *IPython.utils.coloransi*), 751
 ColorSchemeTable (класс в *IPython.utils.coloransi*), 752
 ColorTB (класс в *IPython.core.ultratb*), 680
 columnize() (в модуле *IPython.utils.text*), 781
 command line option
 --ipython-dir, 441
 CommandChainDispatcher (класс в *IPython.core.hooks*), 613
 compiler_flags (*IPython.core.compilerop.CachingCompiler* property), 567
 complete() (метод *IPython.core.completer.Completer*), 574
 complete() (метод *IPython.core.completer.IPCompleter*), 575
 complete() (метод *IPython.core.interactiveshell.InteractiveShell*), 628
 complete_object() (в модуле *IPython.utils.generics*), 758
 Completer (класс в *IPython.core.completer*), 573
 Completion (класс в *IPython.core.completer*), 571
 completion_matcher() (в модуле *IPython.core.completer*), 580
 CompletionContext (класс в *IPython.core.completer*), 572
 completions (атрибут *IPython.core.completer.SimpleMatcherResult*), 572
 completions() (метод *IPython.core.completer.IPCompleter*), 576
 completions_sorting_key() (в модуле *IPython.core.completer*), 580
 CompletionSplitter (класс в *IPython.core.completer*), 573
 compress_dhist() (в модуле *IPython.core.magic*), 649
 compress_user() (в модуле *IPython.core.completer*), 580
 compress_user() (в модуле *IPython.utils.path*), 766
 compute_item_matrix() (в модуле *IPython.utils.text*), 780
 conda
 magic command, 403
 config
 magic command, 403
 configure_inline_support() (в модуле *IPython.core.pylabtools*), 671
 confirm_exit (атрибут *IPython.terminal.interactiveshell.TerminalInteractiveShell*), 730
 connection_options (атрибут *IPython.core.history.HistoryAccessor*), 606
 construct_parser() (в модуле *IPython.core.magic_arguments*), 653
 continuation_prompt_tokens() (метод *MyPrompts*), 513
 copy() (метод *IPython.utils.coloransi.ColorScheme*), 752
 copy() (метод *IPython.utils.coloransi.ColorSchemeTable*), 752
 copy() (метод *IPython.utils.ipstruct.Struct*), 761
 copy_config_file() (метод *IPython.core.profiledir.ProfileDir*), 668
 copy_config_files (атрибут *IPython.core.application.BaseIPythonApplication*), 562
 CoroutineInputTransformer (класс в *IPython.core.inputtransformer*), 619
 count_failures() (в модуле *IPython.testing.ipunittest*), 747
 count_lines_in_py_file() (в модуле *IPython.core.ultratb*), 682
 cpaste() (метод *IPython.terminal.magics.TerminalMagics*), 737
 crash_handler_class (атрибут *IPython.terminal.ipapp.TerminalIPythonApp*), 735
 crash_handler_lite() (в модуле *IPython.core.crashhandler*), 586
 CrashHandler (класс в *IPython.core.crashhandler*), 585
 create_identifier() (в модуле *IPython.terminal.shortcuts*), 740
 create_ipython_shortcuts() (в модуле *IPython.terminal.shortcuts*), 740
 create_profile_dir() (метод класса *IPython.core.profiledir.ProfileDir*), 668
 create_profile_dir_by_name() (метод класса *IPython.core.profiledir.ProfileDir*), 668
 create_typestr2type_dicts() (в модуле *IPython.utils.wildcard*), 785
 crimson_editor() (в модуле *IPython.lib.editorhooks*), 713
 cursor_line (атрибут *IPython.core.completer.CompletionContext*), 572
 cursor_position (атрибут *IPython.core.completer.CompletionContext*), 572
 cursor_to_position() (в модуле *IPython.core.completer*), 582

`custom_completer_matcher()` (*метод* `IPython.core.completer.IPCompleter`), 576

D

`db_cache_size` (*амбузм* `IPython.core.history.HistoryManager`), 608

`db_log_output` (*амбузм* `IPython.core.history.HistoryManager`), 609

`deactivate()` (*метод* `IPython.core.builtin_trap.BuiltinTrap`), 566

`debug` *magic command*, 404

`debug` (*амбузм* `IPython.core.completer.Completer`), 574

`debugger()` (*метод* `IPython.core.interactiveshell.InteractiveShell`), 628

`debugger()` (*метод* `IPython.core.ultratb.VerboseTB`), 679

`debugger_cls` (*амбузм* `IPython.core.interactiveshell.InteractiveShell`), 629

`debugger_cls` (`IPython.terminal.interactiveshell.TerminalInteractiveShell` *property*), 730

`debugger_history_file` (*амбузм* `IPython.terminal.interactiveshell.TerminalInteractiveShell`), 730

`debugx()` (*в модуле* `IPython.utils.frame`), 757

`decorate_fn_with_doc()` (*в модуле* `IPython.core.debugger`), 591

`dedent()` (*в модуле* `IPython.utils.text`), 779

`deep_import_hook()` (*в модуле* `IPython.lib.deepreload`), 705

`deep_reload_hook()` (*в модуле* `IPython.lib.deepreload`), 705

`default_aliases()` (*в модуле* `IPython.core.alias`), 561

`default_option()` (*метод* `IPython.core.magic.Magics`), 648

`defaults` (*класс в* `IPython.core.magic_arguments`), 652

`define_alias()` (*метод* `IPython.core.alias.AliasManager`), 561

`define_macro()` (*метод* `IPython.core.interactiveshell.InteractiveShell`), 629

`del_var()` (*метод* `IPython.core.interactiveshell.InteractiveShell`), 629

`delete_pair()` (*в модуле* `IPython.terminal.shortcuts.auto_match`), 742

`delims` (`IPython.core.completer.CompletionSplitter` *property*), 573

`Demo` (*класс в* `IPython.lib.demo`), 709

`DemoError` (*класс в* `IPython.lib.demo`), 709

`dhist` *magic command*, 404

`dict_dir()` (*в модуле* `IPython.utils.wildcard`), 785

`dict_key_matcher()` (*метод* `IPython.core.completer.IPCompleter`), 576

`dict_key_matches()` (*метод* `IPython.core.completer.IPCompleter`), 576

`dict_keys_only` (*амбузм* `IPython.core.completer.IPCompleter`), 576

`dir2()` (*в модуле* `IPython.utils.dir2`), 755

`dirs` *magic command*, 405

`disable_failing_post_execute` (*амбузм* `IPython.core.interactiveshell.InteractiveShell`), 629

`disable_matchers` (*амбузм* `IPython.core.completer.IPCompleter`), 577

`disable()` (*в модуле* `IPython.terminal.shortcuts.auto_suggest`), 743

`distutils_completion()` (*в модуле* `IPython.terminal.shortcuts`), 740

`dispatch()` (*метод* `IPython.utils.strdispatch.StrDispatch`), 771

`dispatch_custom_completer()` (*метод* `IPython.core.completer.IPCompleter`), 577

`display()` (*метод* `IPython.display.DisplayHandle`), 685

`display()` (*в модуле* `IPython.display`), 694

`display_banner` (*амбузм* `IPython.terminal.ipapp.TerminalIPythonApp`), 735

`display_completions` (*амбузм* `IPython.terminal.interactiveshell.TerminalInteractiveShell`), 731

`display_html()` (*в модуле* `IPython.display`), 696

`display_javascript()` (*в модуле* `IPython.display`), 696

`display_jpeg()` (*в модуле* `IPython.display`), 697

`display_json()` (*в модуле* `IPython.display`), 697

`display_latex()` (*в модуле* `IPython.display`), 697

`display_markdown()` (*в модуле* `IPython.display`), 697

`display_page` (*амбузм* `IPython.core.interactiveshell.InteractiveShell`),

- 629
- `display_page()` (в модуле *IPython.core.page*), 658
- `display_pdf()` (в модуле *IPython.display*), 698
- `display_png()` (в модуле *IPython.display*), 698
- `display_pretty()` (в модуле *IPython.display*), 698
- `display_svg()` (в модуле *IPython.display*), 698
- `DisplayFormatter` (класс в *IPython.core.formatters*), 597
- `DisplayHandle` (класс в *IPython.display*), 685
- `DisplayObject` (класс в *IPython.display*), 685
- `do_complete()` (метод *MyBetterKernel*), 542
- `do_context()` (метод *IPython.core.debugger.Pdb*), 588
- `do_d()` (метод *IPython.core.debugger.Pdb*), 588
- `do_debug()` (метод *IPython.core.debugger.Pdb*), 588
- `do_down()` (метод *IPython.core.debugger.Pdb*), 588
- `do_execute()` (метод *MyKernel*), 540
- `do_history()` (метод *MyBetterKernel*), 542
- `do_inspect()` (метод *MyBetterKernel*), 542
- `do_interact()` (метод *IPython.terminal.debugger.TerminalPdb*), 726
- `do_is_complete()` (метод *MyBetterKernel*), 542
- `do_l()` (метод *IPython.core.debugger.Pdb*), 588
- `do_list()` (метод *IPython.core.debugger.Pdb*), 588
- `do_ll()` (метод *IPython.core.debugger.Pdb*), 589
- `do_longlist()` (метод *IPython.core.debugger.Pdb*), 589
- `do_one_token_transform()` (метод *IPython.core.inputtransformer2.TransformerManager*), 623
- `do_pdef()` (метод *IPython.core.debugger.Pdb*), 589
- `do_pdoc()` (метод *IPython.core.debugger.Pdb*), 589
- `do_pfile()` (метод *IPython.core.debugger.Pdb*), 589
- `do_pinfo()` (метод *IPython.core.debugger.Pdb*), 589
- `do_pinfo2()` (метод *IPython.core.debugger.Pdb*), 589
- `do_psource()` (метод *IPython.core.debugger.Pdb*), 589
- `do_q()` (метод *IPython.core.debugger.Pdb*), 589
- `do_quit()` (метод *IPython.core.debugger.Pdb*), 589
- `do_shutdown()` (метод *MyBetterKernel*), 542
- `do_skip_hidden()` (метод *IPython.core.debugger.Pdb*), 589
- `do_skip_predicates()` (метод *IPython.core.debugger.Pdb*), 589
- `do_u()` (метод *IPython.core.debugger.Pdb*), 590
- `do_up()` (метод *IPython.core.debugger.Pdb*), 590
- `do_w()` (метод *IPython.core.debugger.Pdb*), 590
- `do_where()` (метод *IPython.core.debugger.Pdb*), 590
- `Doc2UnitTester` (класс в *IPython.testing.ipunittest*), 747
- `docstring_double_quotes()` (в модуле *IPython.terminal.shortcuts.auto_match*), 741
- `docstring_single_quotes()` (в модуле *IPython.terminal.shortcuts.auto_match*), 742
- `doctest_mode` magic command, 405
- `DollarFormatter` (класс в *IPython.utils.text*), 777
- `double_quote()` (в модуле *IPython.terminal.shortcuts.auto_match*), 741
- `down_and_update_hint()` (в модуле *IPython.terminal.shortcuts.auto_suggest*), 743
- `drop_by_id()` (метод *IPython.core.interactiveshell.InteractiveShell*), 629
- `dst()` (метод *IPython.utils.tz.tzUTC*), 784
- ## E
- `ebivim()` (в модуле *IPython.terminal.shortcuts.filters*), 744
- `edit` magic command, 405
- `edit()` (метод *IPython.lib.demos.Demo*), 709
- `editing_mode` (атрибут *IPython.terminal.interactiveshell.TerminalInteractiveShell*), 731
- `EDITOR`, 96, 515
- `editor` (атрибут *IPython.terminal.interactiveshell.TerminalInteractiveShell*), 731
- `editor()` (в модуле *IPython.core.hooks*), 613
- `emacs()` (в модуле *IPython.lib.editorhooks*), 713
- `emacs_bindings_in_vi_insert_mode` (атрибут *IPython.terminal.interactiveshell.TerminalInteractiveShell*), 731
- `EmacsChecker` (класс в *IPython.core.prefilter*), 664
- `EmacsHandler` (класс в *IPython.core.prefilter*), 666
- `embed()` (в модуле *IPython*), 558
- `embed()` (в модуле *IPython.terminal.embed*), 728
- `embed_kernel()` (в модуле *IPython*), 558
- `EmbeddedMagics` (класс в *IPython.terminal.embed*), 727
- `enable_history_search` (атрибут *IPython.terminal.interactiveshell.TerminalInteractiveShell*), 731
- `enable_html_pager` (атрибут *IPython.core.interactiveshell.InteractiveShell*), 629
- `enable_matplotlib()` (метод *IPython.core.interactiveshell.InteractiveShell*), 629

629
 enable_pylab() (метод `IPython.core.shellapp.InteractiveShellApp`),
 `IPython.core.interactiveshell.InteractiveShell`), 672
 630
 exec_files (атрибут `IPython.core.shellapp.InteractiveShellApp`),
 606 672
 end_group() (метод `IPython.lib.pretty.PrettyPrinter`), 723
 end_session() (метод `IPython.core.history.HistoryManager`),
 609
 ends_in_comment_or_string() (в модуле `IPython.core.inputtransformer`), 620
 ensure_dir_exists() (в модуле `IPython.utils.path`), 768
 ensure_fromlist() (в модуле `IPython.lib.deepreload`), 705
 env
 magic command, 407
 eqrepr() (в модуле `IPython.core.ultratb`), 682
 error() (метод `IPython.core.magic_arguments.MagicArgumentManager`),
 652
 escaped_commands() (в модуле `IPython.core.inputtransformer`), 620
 EscapedCommand (класс в `IPython.core.inputtransformer2`), 622
 ev() (метод `IPython.core.interactiveshell.InteractiveShell`),
 630
 eval_node() (в модуле `IPython.core.guarded_eval`),
 605
 eval_node() (в модуле `IPython.terminal.shortcuts.filters`), 746
 EvalFormatter (класс в `IPython.utils.text`), 777
 evaluation (атрибут `IPython.core.completer.Completer`), 574
 evaluation (атрибут `IPython.core.guarded_eval.EvaluationContext`),
 604
 EvaluationContext (класс в `IPython.core.guarded_eval`), 604
 EventManager (класс в `IPython.core.events`), 593
 ex() (метод `IPython.core.interactiveshell.InteractiveShell`),
 630
 excepthook() (метод `IPython.core.application.BaseIPythonApplication`),
 562
 excepthook() (метод `IPython.core.interactiveshell.InteractiveShell`),
 630
 exception_colors() (в модуле `IPython.core.excolors`), 595
 exclude_regexp (атрибут `IPython.core.prefilter.AutocallChecker`),
 665
 exec_files (атрибут `IPython.core.shellapp.InteractiveShellApp`),
 672
 exec_lines (атрибут `IPython.core.shellapp.InteractiveShellApp`),
 672
 exec_PYTHONSTARTUP (атрибут `IPython.core.shellapp.InteractiveShellApp`),
 672
 ExecutionInfo (класс в `IPython.core.interactiveshell`), 625
 ExecutionResult (класс в `IPython.core.interactiveshell`), 625
 exit_raise() (метод `IPython.terminal.embed.EmbeddedMagics`),
 727
 ExitAutocall (класс в `IPython.core.autocall`), 565
 expand_path() (в модуле `IPython.utils.path`), 767
 expand_user() (в модуле `IPython.core.completer`),
 580
 ExtensionManager (класс в `IPython.core.extensions`), 595
 extensions (атрибут `IPython.core.shellapp.InteractiveShellApp`),
 672
 extra_config_file (атрибут `IPython.core.application.BaseIPythonApplication`),
 563
 extra_extensions (атрибут `IPython.core.shellapp.InteractiveShellApp`),
 672
 extra_open_editor_shortcuts (атрибут `IPython.terminal.interactiveshell.TerminalInteractiveShell`),
 731
 extract_hist_ranges() (в модуле `IPython.core.history`), 611
 extract_input_lines() (метод `IPython.core.interactiveshell.InteractiveShell`),
 630
 extract_module_locals() (в модуле `IPython.utils.frame`), 757
 extract_vars() (в модуле `IPython.utils.frame`),
 757
 extract_vars_above() (в модуле `IPython.utils.frame`), 757
 F
 fields() (метод `IPython.utils.text.SList`), 776
 figsize() (в модуле `IPython.core.pylabtools`), 670
 file_matcher() (метод `IPython.core.completer.IPCompleter`),
 577
 file_matches() (метод `IPython.core.completer.IPCompleter`),
 577

- 577
- `file_to_run` (ампубум `IPython.core.shellapp.InteractiveShellApp`), 673
- `filefind()` (в модуле `IPython.utils.path`), 766
- `FileLink` (класс в `IPython.display`), 686
- `FileLinks` (класс в `IPython.display`), 686
- `filter_from_string()` (в модуле `IPython.terminal.shortcuts.filters`), 746
- `filter_ns()` (в модуле `IPython.utils.wildcard`), 786
- `find()` (метод класса `IPython.core.inputtransformer2.EscapedCommand`), 622
- `find()` (метод класса `IPython.core.inputtransformer2.HelpEnd`), 623
- `find()` (метод класса `IPython.core.inputtransformer2.MagicAssign`), 622
- `find()` (метод класса `IPython.core.inputtransformer2.SystemAssign`), 622
- `find()` (метод класса `IPython.core.inputtransformer2.TokenTransformBase`), 622
- `find_cell_magic()` (метод `IPython.core.interactiveshell.InteractiveShell`), 631
- `find_cmd()` (в модуле `IPython.utils.process`), 768
- `find_end_of_continued_line()` (в модуле `IPython.core.inputtransformer2`), 624
- `find_file()` (в модуле `IPython.core.oinspect`), 657
- `find_gui_and_backend()` (в модуле `IPython.core.pylabtools`), 671
- `find_handler()` (метод `IPython.core.prefilter.PrefilterManager`), 662
- `find_last_indent()` (в модуле `IPython.core.inputtransformer2`), 624
- `find_line_magic()` (метод `IPython.core.interactiveshell.InteractiveShell`), 631
- `find_magic()` (метод `IPython.core.interactiveshell.InteractiveShell`), 631
- `find_mod()` (в модуле `IPython.utils.module_paths`), 764
- `find_next_indent()` (в модуле `IPython.core.inputsplitter`), 617
- `find_profile_dir()` (метод класса `IPython.core.profiledir.ProfileDir`), 669
- `find_profile_dir_by_name()` (метод класса `IPython.core.profiledir.ProfileDir`), 669
- `find_source_lines()` (в модуле `IPython.core.oinspect`), 657
- `find_user_code()` (метод `IPython.core.interactiveshell.InteractiveShell`), 631
- `FindCmdError` (класс в `IPython.utils.process`), 768
- `flag_calls()` (в модуле `IPython.utils.decorators`), 754
- `flat_matches()` (метод `IPython.utils.strdispatch.StrDispatch`), 771
- `fload()` (метод `IPython.lib.demo.Demo`), 710
- `flush()` (метод `IPython.lib.backgroundjobs.BackgroundJobManager`), 701
- `flush()` (метод `IPython.lib.pretty.PrettyPrinter`), 723
- `flush()` (метод `IPython.utils.io.Tee`), 759
- `following_text()` (в модуле `IPython.terminal.shortcuts.filters`), 745
- `for_type()` (метод `IPython.core.formatters.BaseFormatter`), 599
- `for_type()` (в модуле `IPython.lib.pretty`), 724
- `for_type_by_name()` (метод `IPython.core.formatters.BaseFormatter`), 599
- `for_type_by_name()` (в модуле `IPython.lib.pretty`), 724
- `force` (ампубум `IPython.core.historyapp.HistoryClear`), 612
- `force_interact` (ампубум `IPython.terminal.ipapp.TerminalIPythonApp`), 735
- `format()` (метод `IPython.core.formatters.DisplayFormatter`), 597
- `format2()` (метод `IPython.utils.PyColorize.Parser`), 749
- `format_code_name()` (метод `IPython.core.compilerop.CachingCompiler`), 567
- `format_display_data()` (в модуле `IPython.core.formatters`), 603
- `format_exception_as_a_whole()` (метод `IPython.core.ultratb.VerboseTB`), 679
- `format_latex()` (метод `IPython.core.magic.Magics`), 648
- `format_mime()` (метод `IPython.core.oinspect.Inspector`), 654
- `format_record()` (метод `IPython.core.ultratb.VerboseTB`), 679
- `format_screen()` (в модуле `IPython.utils.text`), 779
- `format_stack_entry()` (метод `IPython.core.debugger.Pdb`), 590
- `format_types` (`IPython.core.formatters.DisplayFormatter` property), 598
- `FormattedTB` (класс в `IPython.core.ultratb`), 679

- FormatterABC (класс в *IPython.core.formatters*), 598
 FormatterWarning (класс в *IPython.core.formatters*), 598
 FrameInfo (класс в *IPython.core.ultratb*), 678
 freeze_term_title() (в модуле *IPython.utils.terminal*), 775
 full_text (атрибут *IPython.core.completer.CompletionContext*), 572
 FullEvalFormatter (класс в *IPython.utils.text*), 777
 function_name_regex (атрибут *IPython.core.prefilter.AutocallChecker*), 665
 fwd_unicode_match() (метод *IPython.core.completer.IPCompleter*), 577
 fwd_unicode_matcher() (метод *IPython.core.completer.IPCompleter*), 577
- ## G
- genelatex() (в модуле *IPython.lib.latextools*), 715
 generate_tokens() (в модуле *IPython.utils.tokenutil*), 783
 GeoJSON (класс в *IPython.display*), 687
 get() (метод *IPython.core.oinspect.OInfo*), 654
 get_all_entries() (в модуле *IPython.core.completer*), 581
 get_alias() (метод *IPython.core.alias.AliasManager*), 561
 get_app_qt4() (в модуле *IPython.lib.guisupport*), 714
 get_app_wx() (в модуле *IPython.lib.guisupport*), 714
 get_asyncio_loop() (в модуле *IPython.core.async_helpers*), 564
 get_code_name() (метод *IPython.core.compilerop.CachingCompiler*), 568
 get_default_editor() (в модуле *IPython.terminal.interactiveshell*), 734
 get_encoding() (в модуле *IPython.core.oinspect*), 656
 get_exception_only() (метод *IPython.core.interactiveshell.InteractiveShell*), 631
 get_exception_only() (метод *IPython.core.ultratb.ListTB*), 678
 get_handler_by_esc() (метод *IPython.core.prefilter.PrefilterManager*), 662
 get_handler_by_name() (метод *IPython.core.prefilter.PrefilterManager*), 662
 get_home_dir() (в модуле *IPython.utils.path*), 767
 get_input_encoding() (в модуле *IPython.core.inputsplitter*), 618
 get_ipython() (метод *IPython.core.interactiveshell.InteractiveShell*), 632
 get_ipython() (в модуле *IPython.core.getipython*), 604
 get_ipython_cache_dir() (в модуле *IPython.paths*), 725
 get_ipython_dir() (в модуле *IPython.paths*), 725
 get_ipython_module_path() (в модуле *IPython.paths*), 725
 get_ipython_package_dir() (в модуле *IPython.paths*), 725
 get_last_session_id() (метод *IPython.core.history.HistoryAccessor*), 606
 get_line_number_of_frame() (в модуле *IPython.core.ultratb*), 682
 get_local_scope() (метод *IPython.core.interactiveshell.InteractiveShell*), 632
 get_long_path_name() (в модуле *IPython.utils.path*), 766
 get_mci() (метод *IPython.lib.lexers.IPythonConsoleLexer*), 718
 get_pager_cmd() (в модуле *IPython.core.page*), 659
 get_pager_start() (в модуле *IPython.core.page*), 659
 get_parent() (в модуле *IPython.lib.deepreload*), 705
 get_pasted_lines() (в модуле *IPython.terminal.magics*), 738
 get_path_links() (статический метод *IPython.core.interactiveshell.InteractiveShell*), 632
 get_py_filename() (в модуле *IPython.utils.path*), 766
 get_range() (метод *IPython.core.history.HistoryAccessor*), 606
 get_range() (метод *IPython.core.history.HistoryManager*), 609
 get_range_by_str() (метод *IPython.core.history.HistoryAccessor*), 607
 get_real_method() (в модуле *IPython.utils.dir2*), 755
 get_root_modules() (в модуле *IPython.core.completerlib*), 584
 get_session_info() (метод

IPython.core.history.HistoryAccessor),
 607
 get_session_info() (метод *IPython.core.history.HistoryManager*),
 609
 get_stream_enc() (в модуле *IPython.utils.encoding*), 756
 get_suggestion() (метод *IPython.terminal.shortcuts.auto_suggest.NavigableAutoSuggestFromHistory*),
 743
 get_sys_info() (в модуле *IPython.utils.sysinfo*),
 772
 get_tail() (метод *IPython.core.history.HistoryAccessor*),
 607
 get_tail() (метод *IPython.core.history.HistoryManager*),
 609
 get_terminal_size() (в модуле *IPython.utils.terminal*), 775
 get_text_list() (в модуле *IPython.utils.text*), 781
 get_tokens_unprocessed() (метод *IPython.lib.lexers.IPyLexer*), 719
 get_tokens_unprocessed() (метод *IPython.lib.lexers.IPythonConsoleLexer*),
 719
 get_xdg_cache_dir() (в модуле *IPython.utils.path*), 767
 get_xdg_dir() (в модуле *IPython.utils.path*), 767
 getdefaultencoding() (в модуле *IPython.utils.encoding*), 756
 getdoc() (в модуле *IPython.core.oinspect*), 656
 getfigs() (в модуле *IPython.core.pylabtools*), 670
 getlines() (в модуле *IPython.utils.ulinecache*), 785
 getoutput() (метод *IPython.core.interactiveshell.InteractiveShell*),
 632
 getsource() (в модуле *IPython.core.oinspect*), 657
 global_matches() (метод *IPython.core.completer.Completer*), 574
 globals (атрибут *IPython.core.guarded_eval.EvaluationContext*),
 604
 gnuclient() (в модуле *IPython.lib.editorhooks*), 713
 greedy (атрибут *IPython.core.completer.Completer*),
 574
 grep() (метод *IPython.utils.text.SList*), 776
 Group (класс в *IPython.lib.pretty*), 723
 GroupQueue (класс в *IPython.lib.pretty*), 723
 guarded_eval() (в модуле *IPython.core.guarded_eval*), 605
 GuardRejection (класс в *IPython.core.guarded_eval*), 605
 gui
 magic command, 407
 gui (атрибут *IPython.core.shellapp.InteractiveShellApp*),
 673
 H
 handle() (метод *IPython.core.prefilter.AutoHandler*),
 666
 handle() (метод *IPython.core.prefilter.EmacsHandler*),
 666
 handle() (метод *IPython.core.prefilter.MacroHandler*),
 666
 handle() (метод *IPython.core.prefilter.MagicHandler*),
 666
 handle() (метод *IPython.core.prefilter.PrefilterHandler*),
 666
 handle_return (атрибут *IPython.terminal.interactiveshell.TerminalInteractiveShell*),
 731
 handle_return_or_newline_or_execute() (в модуле *IPython.terminal.shortcuts*), 740
 handlers (*IPython.core.prefilter.PrefilterManager* property), 662
 has_any_completions() (в модуле *IPython.core.completer*), 580
 has_comment() (в модуле *IPython.core.inputtransformer*), 620
 has_focus() (в модуле *IPython.terminal.shortcuts.filters*), 744
 has_open_quotes() (в модуле *IPython.core.completer*), 580
 has_sunken_brackets() (в модуле *IPython.core.inputtransformer2*), 624
 hasattr() (метод *IPython.utils.ipstruct.Struct*),
 761
 help_end() (в модуле *IPython.core.inputtransformer*), 620
 HelpEnd (класс в *IPython.core.inputtransformer2*),
 622
 hidden_frames() (метод *IPython.core.debugger.Pdb*), 590
 hide_initial_ns (атрибут *IPython.core.shellapp.InteractiveShellApp*),
 673
 highlight() (метод *IPython.lib.demos.Demo*), 710
 highlight_matching_brackets (атрибут *IPython.terminal.interactiveshell.TerminalInteractiveShell*),
 731
 highlighting_style (атрибут *IPython.terminal.interactiveshell.TerminalInteractiveShell*),
 731
 highlighting_style_overrides (атрибут *IPython.terminal.interactiveshell.TerminalInteractiveShell*),
 731
 hist_file (атрибут *IPython.core.history.HistoryAccessor*),
 608
 history
 magic command, 408

history_length	(ампубум	735	
	IPython.core.interactiveshell.InteractiveShell),	init_checkers()	(метод
632		IPython.core.prefilter.PrefilterManager),	
history_load_length	(ампубум	662	
	IPython.core.interactiveshell.InteractiveShell),	init_code()	(метод
632		IPython.core.shellapp.InteractiveShellApp),	
HistoryAccessor (класс в IPython.core.history),		673	
606		init_completer()	(метод
HistoryAccessorBase (класс в		IPython.core.interactiveshell.InteractiveShell),	
IPython.core.history),	606	632	
HistoryApp (класс в IPython.core.historyapp),	612	init_config_files()	(метод
HistoryClear (класс в IPython.core.historyapp),		IPython.core.application.BaseIPythonApplication),	
612		563	
HistoryManager (класс в IPython.core.history),	608	init_config_files()	(метод
HistorySavingThread (класс в		IPython.core.profileapp.ProfileCreate),	
IPython.core.history),	610	667	
HistoryTrim (класс в IPython.core.historyapp),	612	init_crash_handler()	(метод
HOME, 364		IPython.core.application.BaseIPythonApplication),	
HomeDirError (класс в IPython.utils.path),	766	563	
html		init_db() (метод IPython.core.history.HistoryAccessor),	
cell magic, 433		608	
HTML (класс в IPython.display),	688	init_environment()	(метод
HTMLFormatter (класс в IPython.core.formatters),		IPython.core.interactiveshell.InteractiveShell),	
601		632	
		init_extensions()	(метод
		IPython.core.shellapp.InteractiveShellApp),	
		673	
idle() (в модуле IPython.lib.editorhooks),	713	init_gui_pylab()	(метод
IFrame (класс в IPython.display),	688	IPython.core.shellapp.InteractiveShellApp),	
ignore_cwd	(ампубум	673	
	IPython.core.shellapp.InteractiveShellApp),	init_handlers()	(метод
673		IPython.core.prefilter.PrefilterManager),	
Image (класс в IPython.display),	689	662	
implementation (ампубум MyKernel),	540	init_history()	(метод
implementation_version (ампубум MyKernel),		IPython.core.interactiveshell.InteractiveShell),	
540		632	
import_item() (в		init_logstart()	(метод
IPython.utils.importstring),	758	IPython.core.interactiveshell.InteractiveShell),	
import_pylab() (в модуле IPython.core.pylabtools),		633	
671		init_path()	(метод
import_submodule() (в		IPython.core.shellapp.InteractiveShellApp),	
IPython.lib.deepreload),	705	673	
in_prompt_tokens() (метод MyPrompts),	513	init_profile_dir()	(метод
in_subscript	(ампубум	IPython.core.application.BaseIPythonApplication),	
	IPython.core.guarded_eval.EvaluationContext),	563	
604		init_shell()	(метод
IncompleteString (класс в		IPython.terminal.ipapp.TerminalIPythonApp),	
IPython.core.inputsplitter),	614	735	
indent() (в модуле IPython.utils.text),	778	init_sys_modules()	(метод
indent_buffer() (в		IPython.terminal.embed.InteractiveShellEmbed),	
IPython.terminal.shortcuts),	741	728	
info() (метод IPython.core.oinspect.Inspector),		init_user_ns()	(метод
655		IPython.core.interactiveshell.InteractiveShell),	
init_banner() (метод		633	
IPython.terminal.ipapp.TerminalIPythonApp),			

`init_virtualenv()` (метод `ipy_prompt()` (в модуле `IPython.core.interactiveshell.InteractiveShell`), `IPython.core.inputtransformer`), 620
 633 `IPyAutocall` (класс в `IPython.core.autocall`), 565
`initialize()` (метод `IPyAutocallChecker` (класс в `IPython.core.application.BaseIPythonApplication`), `IPython.core.prefilter`), 664
 563 `IPyLexer` (класс в `IPython.lib.lexers`), 719
`initialize()` (метод `ipytb_start` (атрибут `IPython.terminal.ipapp.TerminalIPythonApp`), `IPython.lib.lexers.IPythonConsoleLexer`),
 735 719
`InMultilineStatement` (класс в `IPython` `IPython.core.inputsplitter`), 614 модуль, 558
`input_splitter` (`IPython.core.interactiveshell.InteractiveShell` (дупликата), 788
`property`), 633 `:doctest:` (directive option), 788
`input_transformers_post` (атрибут `IPython.core.interactiveshell.InteractiveShell`),
 633 `:okexcept:` (directive option), 788
`INPUTRC`, 367 `:okwarning:` (directive option), 788
`InputRejected` (класс в `IPython.core.error`), 592 `:python:` (directive option), 788
`InputSplitter` (класс в `IPython.core.inputsplitter`),
 614 `:savefig:` (directive option), 788
`InputTermColors` (класс в `IPython.utils.coloransi`),
 751 `:suppress:` (directive option), 788
`InputTransformer` (класс в `IPython.core.inputtransformer`), 618 `:verbatim:` (directive option), 788
`inspect_object()` (в модуле `IPython.core.alias`
`IPython.utils.generics`), 758 модуль, 560
`Inspector` (класс в `IPython.core.oinspect`), 654 `IPython.core.application`
`inspector_class` (атрибут `IPython.core.interactiveshell.InteractiveShell`),
 633 модуль, 562
`install_editor()` (в модуле `IPython.core.async_helpers`
`IPython.lib.editorhooks`), 712 модуль, 564
`install_payload_page()` (в модуле `IPython.core.autocall`
`IPython.core.payloadpage`), 660 модуль, 565
`interactive_shell_class` (атрибут `IPython.core.builtin_trap`
`IPython.terminal.ipapp.TerminalIPythonApp`), 735 модуль, 566
`InteractiveShell` (класс в `IPython.core.compilerop`
`IPython.core.interactiveshell`), 625 модуль, 567
`InteractiveShellABC` (класс в `IPython.core.completer`
`IPython.core.interactiveshell`), 642 модуль, 569
`InteractiveShellApp` (класс в `IPython.core.completerlib`
`IPython.core.shellapp`), 672 модуль, 584
`InteractiveShellEmbed` (класс в `IPython.core.crashhandler`
`IPython.terminal.embed`), 727 модуль, 585
`InterruptiblePdb` (класс в `IPython.core.debugger`),
 590 модуль, 586
`InvalidAliasError` (класс в `IPython.core.error`),
 560 модуль, 591
`IPAppCrashHandler` (класс в `IPython.core.events`
`IPython.terminal.ipapp`), 734 модуль, 593
`IPCompleter` (класс в `IPython.core.excolors`
`IPython.core.completer`), 575 модуль, 594
`ipdocstring()` (в модуле `IPython.core.extensions`
`IPython.testing.ipunittest`), 747 модуль, 595
`IPython.core.alias` модуль, 560
`IPython.core.application` модуль, 562
`IPython.core.async_helpers` модуль, 564
`IPython.core.autocall` модуль, 565
`IPython.core.builtin_trap` модуль, 566
`IPython.core.compilerop` модуль, 567
`IPython.core.completer` модуль, 569
`IPython.core.completerlib` модуль, 584
`IPython.core.crashhandler` модуль, 585
`IPython.core.debugger` модуль, 586
`IPython.core.error` модуль, 591
`IPython.core.events` модуль, 593
`IPython.core.excolors` модуль, 594
`IPython.core.extensions` модуль, 595
`IPython.core.formatters` модуль, 597
`IPython.core.getipython` модуль, 604
`IPython.core.guarded_eval` модуль, 604
`IPython.core.history`

модуль, 606
IPython.core.historyapp
модуль, 612
IPython.core.hooks
модуль, 613
IPython.core.inputsplitter
модуль, 614
IPython.core.inputtransformer
модуль, 618
IPython.core.inputtransformer2
модуль, 621
IPython.core.interactiveshell
модуль, 625
IPython.core.logger
модуль, 643
IPython.core.macro
модуль, 644
IPython.core.magic
модуль, 645
IPython.core.magic_arguments
модуль, 650
IPython.core.oinspect
модуль, 654
IPython.core.page
модуль, 658
IPython.core.payload
модуль, 659
IPython.core.payloadpage
модуль, 660
IPython.core.prefilter
модуль, 660
IPython.core.profileapp
модуль, 667
IPython.core.profiledir
модуль, 668
IPython.core.prompts
модуль, 669
IPython.core.pylabtools
модуль, 670
IPython.core.shellapp
модуль, 672
IPython.core.splitinput
модуль, 674
IPython.core.ultratb
модуль, 675
IPython.display
модуль, 682
IPython.extensions.autoreload
модуль, 520
IPython.extensions.storemagic
модуль, 522
IPython.lib.backgroundjobs
модуль, 700
IPython.lib.clipboard
модуль, 703
IPython.lib.deepreload
модуль, 704
IPython.lib.demo
модуль, 706
IPython.lib.editorhooks
модуль, 712
IPython.lib.guisupport
модуль, 713
IPython.lib.latextools
модуль, 715
IPython.lib.lexers
модуль, 716
IPython.lib.pretty
модуль, 720
IPython.paths
модуль, 725
IPython.sphinxext.ipynon_directive
модуль, 797
IPython.terminal.debugger
модуль, 725
IPython.terminal.embed
модуль, 727
IPython.terminal.interactiveshell
модуль, 729
IPython.terminal.ipapp
модуль, 734
IPython.terminal.magics
модуль, 736
IPython.terminal.prompts
модуль, 738
IPython.terminal.shortcuts
модуль, 739
IPython.terminal.shortcuts.auto_match
модуль, 741
IPython.terminal.shortcuts.auto_suggest
модуль, 742
IPython.terminal.shortcuts.filters
модуль, 744
IPython.testing.ipunittest
модуль, 746
IPython.testing.skipdoctest
модуль, 748
IPython.utils.capture
модуль, 749
IPython.utils.colorable
модуль, 750
IPython.utils.coloransi
модуль, 751
IPython.utils.contexts
модуль, 753
IPython.utils.data
модуль, 754
IPython.utils.decorators

- модуль, 754
 - IPython.utils.dir2
 - модуль, 755
 - IPython.utils.encoding
 - модуль, 756
 - IPython.utils.frame
 - модуль, 756
 - IPython.utils.generics
 - модуль, 758
 - IPython.utils.importstring
 - модуль, 758
 - IPython.utils.io
 - модуль, 759
 - IPython.utils.ipstruct
 - модуль, 760
 - IPython.utils.module_paths
 - модуль, 764
 - IPython.utils.openpy
 - модуль, 764
 - IPython.utils.path
 - модуль, 766
 - IPython.utils.process
 - модуль, 768
 - IPython.utils.PyColorize
 - модуль, 748
 - IPython.utils.sentinel
 - модуль, 769
 - IPython.utils.shimmodule
 - модуль, 770
 - IPython.utils.strdispatch
 - модуль, 770
 - IPython.utils.sysinfo
 - модуль, 771
 - IPython.utils.syspathcontext
 - модуль, 773
 - IPython.utils.tempdir
 - модуль, 773
 - IPython.utils.terminal
 - модуль, 774
 - IPython.utils.text
 - модуль, 775
 - IPython.utils.timing
 - модуль, 782
 - IPython.utils.tokenutil
 - модуль, 783
 - IPython.utils.tz
 - модуль, 784
 - IPython.utils.ulinecache
 - модуль, 785
 - IPython.utils.wildcard
 - модуль, 785
 - IPython2PythonConverter (класс в *IPython.testing.ipunittest*), 747
 - IPYTHON_DIR, 252, 364, 546
 - ipython_dir (атрибут *IPython.core.application.BaseIPythonApplication*), 563
 - ipython_dir (атрибут *IPython.core.profileapp.ProfileList*), 667
 - IPythonConsoleLexer (класс в *IPython.lib.lexers*), 717
 - IPythonCoreError (класс в *IPython.core.error*), 592
 - IPythonDemo (класс в *IPython.lib.demo*), 710
 - IPYTHONDIR, 252, 364, 546
 - IPythonDisplayFormatter (класс в *IPython.core.formatters*), 602
 - IPythonInputSplitter (класс в *IPython.core.inputsplitters*), 616
 - IPythonLineDemo (класс в *IPython.lib.demo*), 711
 - IPythonPartialTracebackLexer (класс в *IPython.lib.lexers*), 717
 - IPythonTracebackLexer (класс в *IPython.lib.lexers*), 717
 - is_alias() (метод *IPython.core.alias.AliasManager*), 561
 - is_event_loop_running_qt4() (в модуле *IPython.lib.guisupport*), 714
 - is_event_loop_running_wx() (в модуле *IPython.lib.guisupport*), 714
 - is_importable() (в модуле *IPython.core.completerlib*), 584
 - is_integer_string() (в модуле *IPython.core.interactiveshell*), 643
 - is_possible_submodule() (в модуле *IPython.core.completerlib*), 584
 - is_shadowed() (в модуле *IPython.core.prefilter*), 666
 - is_simple_callable() (в модуле *IPython.core.oinspect*), 657
 - is_type() (в модуле *IPython.utils.wildcard*), 785
 - is_windows_os() (в модуле *IPython.terminal.shortcuts.filters*), 746
- J
- javascript
 - cell magic, 433
 - Javascript (класс в *IPython.display*), 690
 - JavascriptFormatter (класс в *IPython.core.formatters*), 602
 - jed() (в модуле *IPython.lib.editorhooks*), 712
 - jedi_compute_type_timeout (атрибут *IPython.core.completer.Completer*), 574
 - JPEGFormatter (класс в *IPython.core.formatters*), 602
 - js
 - cell magic, 433
 - JSON (класс в *IPython.display*), 690

- JSONFormatter (класс в *IPython.core.formatters*), 602
- jump() (метод *IPython.lib.demos.Demo*), 710
- ## K
- kate() (в модуле *IPython.lib.editorhooks*), 713
- keep (ампулум *IPython.core.historyapp.HistoryClear*), 612
- keep (ампулум *IPython.core.historyapp.HistoryTrim*), 612
- kill_embedded() (метод *IPython.terminal.embed.EmbeddedMagics*), 727
- killbgscripts
magic command, 409
- KillEmbedded (класс в *IPython.terminal.embed*), 727
- komodo() (в модуле *IPython.lib.editorhooks*), 712
- kpsewhich() (в модуле *IPython.lib.latextools*), 715
- kwds (класс в *IPython.core.magic_arguments*), 653
- ## L
- language (ампулум *MyKernel*), 540
- language_info (ампулум *MyKernel*), 540
- language_version (ампулум *MyKernel*), 540
- last_blank() (в модуле *IPython.core.inputsplitter*), 617
- last_execution_result (ампулум *IPython.core.interactiveshell.InteractiveShell*), 633
- last_execution_succeeded (ампулум *IPython.core.interactiveshell.InteractiveShell*), 633
- last_two_blanks() (в модуле *IPython.core.inputsplitter*), 617
- latex
cell magic, 433
- Latex (класс в *IPython.display*), 691
- latex_matches() (метод *IPython.core.completer.IPCompleter*), 577
- latex_name_matcher() (метод *IPython.core.completer.IPCompleter*), 577
- latex_to_html() (в модуле *IPython.lib.latextools*), 716
- latex_to_png() (в модуле *IPython.lib.latextools*), 715
- latex_to_png_dvipng() (в модуле *IPython.lib.latextools*), 715
- latex_to_png_mpl() (в модуле *IPython.lib.latextools*), 715
- LatexFormatter (класс в *IPython.core.formatters*), 602
- LaTeXTool (класс в *IPython.lib.latextools*), 715
- lazy_magics (ампулум *IPython.core.magic.MagicsManager*), 645
- LazyEvaluate (класс в *IPython.core.prompts*), 670
- leading_empty_lines() (в модуле *IPython.core.inputtransformer2*), 624
- leading_indent() (в модуле *IPython.core.inputtransformer*), 620
- leading_indent() (в модуле *IPython.core.inputtransformer2*), 624
- limit_to_all__ (ампулум *IPython.core.completer.IPCompleter*), 577
- line_at_cursor() (в модуле *IPython.utils.tokenutil*), 783
- LineDemo (класс в *IPython.lib.demos*), 710
- LineInfo (класс в *IPython.core.splitinput*), 674
- link() (в модуле *IPython.utils.path*), 767
- link_or_copy() (в модуле *IPython.utils.path*), 768
- list_bundled_profiles() (в модуле *IPython.core.profileapp*), 668
- list_namespace() (в модуле *IPython.utils.wildcard*), 786
- list_profiles_in() (в модуле *IPython.core.profileapp*), 668
- list_strings() (в модуле *IPython.utils.text*), 778
- ListTB (класс в *IPython.core.ultratb*), 678
- load
magic command, 409
- load_config_file() (метод *IPython.core.application.BaseIPythonApplication*), 563
- load_default_config() (в модуле *IPython.terminal.ipapp*), 736
- load_ext
magic command, 410
- load_extension() (метод *IPython.core.extensions.ExtensionManager*), 596
- load_history_strings() (метод *IPython.terminal.interactiveshell.PtkHistoryAdapter*), 729
- load_next() (в модуле *IPython.lib.deepreload*), 705
- load_subconfig() (метод *IPython.core.application.ProfileAwareConfigLoader*), 562
- loadpy
magic command, 410
- locals (ампулум *IPython.core.guarded_eval.EvaluationContext*), 605
- locate_profile() (в модуле *IPython.paths*), 725
- LocateIPythonApp (класс в *IPython.terminal.ipapp*), 735

`location` (*атрибут* `IPython.core.profiledir.ProfileDir`), 669
`log()` (*метод* `IPython.core.logger.Logger`), 643
`log_write()` (*метод* `IPython.core.logger.Logger`), 643
`logappend` (*атрибут* `IPython.core.interactiveshell.InteractiveShell`), 633
`logfile` (*атрибут* `IPython.core.interactiveshell.InteractiveShell`), 633
`Logger` (*класс* в `IPython.core.logger`), 643
`logoff`
 magic command, 410
`logon`
 magic command, 410
`logstart`
 magic command, 410
`logstart` (*атрибут* `IPython.core.interactiveshell.InteractiveShell`), 633
`logstart()` (*метод* `IPython.core.logger.Logger`), 643
`logstate`
 magic command, 411
`logstate()` (*метод* `IPython.core.logger.Logger`), 644
`logstop`
 magic command, 411
`logstop()` (*метод* `IPython.core.logger.Logger`), 644
`lookup()` (*метод* `IPython.core.formatters.BaseFormatter`), 600
`lookup_by_type()` (*метод* `IPython.core.formatters.BaseFormatter`), 600
`loop_runner` (*атрибут* `IPython.core.interactiveshell.InteractiveShell`), 633
`lsmagic`
 magic command, 411
`lsmagic()` (*метод* `IPython.core.magic.MagicsManager`), 646
`lsmagic_docs()` (*метод* `IPython.core.magic.MagicsManager`), 646
`LSString` (*класс* в `IPython.utils.text`), 776

M

`macro`
 magic command, 411
`Macro` (*класс* в `IPython.core.magic`), 644
`MacroChecker` (*класс* в `IPython.core.prefilter`), 664
`MacroHandler` (*класс* в `IPython.core.prefilter`), 666
`magic`
 magic command, 412
`magic command`
 alias, 399
 alias_magic, 400
 autoawait, 401
 autocall, 401
 automagic, 402
 autoreload, 520
 bookmark, 402
 cd, 402
 clears, 403
 conda, 403
 config, 403
 debug, 404
 dhist, 404
 dirs, 405
 doctest_mode, 405
 edit, 405
 env, 407
 envs, 407
 history, 408
 killbgscripts, 409
 load, 409
 load_ext, 410
 loadpy, 410
 logoff, 410
 logon, 410
 logstart, 410
 logstate, 411
 logstop, 411
 lsmagic, 411
 macro, 411
 magic, 412
 matplotlib, 412
 notebook, 413
 page, 413
 pastebin, 414
 pdb, 414
 pdef, 414
 pdoc, 414
 pfile, 414
 pinfo, 415
 pinfo2, 415
 pip, 415
 popd, 415
 pprint, 415
 precision, 415
 prun, 416
 psearch, 417
 psource, 418
 pushd, 418
 pwd, 419
 pycat, 419
 pylab, 419
 quickref, 420
 recall, 420

- rehashx, 420
- reload_ext, 420
- rerun, 420
- reset, 421
- reset_selective, 422
- run, 423
- save, 425
- sc, 425
- set_env, 427
- sx, 427
- system, 428
- tb, 428
- time, 428
- timeit, 429
- unalias, 430
- unload_ext, 430
- who, 430
- who_ls, 431
- whos, 431
- xdel, 432
- xmode, 432
- magic() (метод *IPython.core.interactiveshell.InteractiveShell*), 633
- magic_arguments (класс в *IPython.core.magic_arguments*), 652
- magic_color_matcher() (метод *IPython.core.completer.IPCompleter*), 578
- magic_color_matches() (метод *IPython.core.completer.IPCompleter*), 578
- magic_config_matcher() (метод *IPython.core.completer.IPCompleter*), 578
- magic_config_matches() (метод *IPython.core.completer.IPCompleter*), 578
- magic_matcher() (метод *IPython.core.completer.IPCompleter*), 578
- magic_matches() (метод *IPython.core.completer.IPCompleter*), 578
- magic_run_completer() (в модуле *IPython.core.completerlib*), 584
- MagicAlias (класс в *IPython.core.magic*), 648
- MagicArgumentParser (класс в *IPython.core.magic_arguments*), 652
- MagicAssign (класс в *IPython.core.inputtransformer2*), 622
- MagicHandler (класс в *IPython.core.prefilter*), 666
- Magics (класс в *IPython.core.magic*), 647
- magics_class() (в модуле *IPython.core.magic*), 649
- MagicsManager (класс в *IPython.core.magic*), 645
- mainloop() (метод *IPython.terminal.embed.InteractiveShellEmbed*), 728
- make_arrow() (в модуле *IPython.core.debugger*), 591
- make_color_table() (в модуле *IPython.utils.coloransi*), 752
- make_report() (метод *IPython.core.crashhandler.CrashHandler*), 586
- make_report() (метод *IPython.terminal.ipapp.IPAppCrashHandler*), 735
- make_tokens_by_line() (в модуле *IPython.core.inputtransformer2*), 624
- markdown
 - cell magic, 433
- Markdown (класс в *IPython.display*), 691
- MarkdownFormatter (класс в *IPython.core.formatters*), 601
- marquee() (метод *IPython.lib.demo.ClearMixin*), 711
- marquee() (метод *IPython.lib.demo.Demo*), 710
- marquee() (в модуле *IPython.utils.text*), 779
- match_dict_keys() (в модуле *IPython.core.completer*), 581
- matcher_api_version (атрибут *IPython.core.completer.MatcherAPIv2*), 573
- MatcherAPIv2 (класс в *IPython.core.completer*), 573
- matchers (*IPython.core.completer.IPCompleter* property), 578
- mate() (в модуле *IPython.lib.editorhooks*), 713
- Math (класс в *IPython.display*), 691
- matplotlib
 - magic command, 412
- matplotlib (атрибут *IPython.core.shellapp.InteractiveShellApp*), 673
- max_seq_length (атрибут *IPython.core.formatters.PlainTextFormatter*), 601
- MaybeAsyncCommandCompiler (класс в *IPython.core.inputtransformer2*), 623
- MaybeAsyncCompile (класс в *IPython.core.inputtransformer2*), 623
- merge() (метод *IPython.utils.ipstruct.Struct*), 762
- merge_completions (атрибут *IPython.core.completer.IPCompleter*), 578
- MimeBundleFormatter (класс в *IPython.core.formatters*), 603
- mimetypes (атрибут *IPython.lib.lexers.IPythonConsoleLexer*), 719

mktempfile() (метод [IPython.core.interactiveshell.InteractiveShell](#)), 610
 modal_cursor (атрибут [IPython.terminal.interactiveshell.TerminalInteractiveShell](#)), 731
 module_completer() (в модуле [IPython.core.completerlib](#)), 584
 module_completion() (в модуле [IPython.core.completerlib](#)), 584
 module_list() (в модуле [IPython.core.completerlib](#)), 584
 module_to_run (атрибут [IPython.core.shellapp.InteractiveShellApp](#)), 673
 mouse_support (атрибут [IPython.terminal.interactiveshell.TerminalInteractiveShell](#)), 731
 mpl_runner() (в модуле [IPython.core.pylabtools](#)), 671
 MyBetterKernel (встроенный класс), 542
 MyKernel (встроенный класс), 540
 MyObject (встроенный класс), 525
 MyPrompts (встроенный класс), 513

N

name (атрибут [IPython.lib.lexers.IPyLexer](#)), 719
 name (атрибут [IPython.lib.lexers.IPythonConsoleLexer](#)), 719
 name (атрибут [IPython.lib.lexers.IPythonPartialTracebackLexer](#)), 717
 name (атрибут [IPython.lib.lexers.IPythonTracebackLexer](#)), 717
 name_session() (метод [IPython.core.history.HistoryManager](#)), 610
 NamedFileInTemporaryDirectory (класс в [IPython.utils.tempdir](#)), 774
 navigable_suggestions() (в модуле [IPython.terminal.shortcuts.filters](#)), 745
 NavigableAutoSuggestFromHistory (класс в [IPython.terminal.shortcuts.auto_suggest](#)), 742
 needs_local_scope() (в модуле [IPython.core.magic](#)), 649
 new() (метод [IPython.lib.backgroundjobs.BackgroundJobManager](#)), 701
 new_do_restart() (метод [IPython.core.debugger.Pdb](#)), 590
 new_main_mod() (метод [IPython.core.interactiveshell.InteractiveShell](#)), 634
 new_session() (метод [IPython.core.history.HistoryManager](#)), 610

O

object_info() (в модуле [IPython.core.oinspect](#)), 656
 object_inspect() (метод [IPython.core.interactiveshell.InteractiveShell](#)), 634
 object_inspect_mime() (метод [IPython.core.interactiveshell.InteractiveShell](#)), 634
 object_inspect_text() (метод [IPython.core.interactiveshell.InteractiveShell](#)), 634
 ofind() (метод [IPython.core.splitinput.LineInfo](#)), 674
 OInfo (класс в [IPython.core.oinspect](#)), 654
 omit_names (атрибут [IPython.core.completer.IPCompleter](#)), 578
 on_off() (в модуле [IPython.core.magic](#)), 649
 only_when_enabled() (в модуле [IPython.core.history](#)), 611
 open_input_in_editor() (в модуле [IPython.terminal.shortcuts](#)), 741
 ostream ([IPython.core.ultratb.TBTools](#) property), 677
 osx_clipboard_get() (в модуле [IPython.lib.clipboard](#)), 704
 out_prompt_tokens() (метод [MyPrompts](#)), 513

`output_can_be_silenced()` (в модуле `IPython.core.magic`), 649
`outputs` (`IPython.utils.capture.CapturedIO` property), 750
`overwrite` (`ампубум` `IPython.core.application.BaseIPythonApplication`), 563
P
`packages` (`ампубум` `IPython.lib.latextools.LaTeXTool`), 715
`page`
 magic command, 413
`page()` (в модуле `IPython.core.page`), 658
`page()` (в модуле `IPython.core.payloadpage`), 660
`page_dumb()` (в модуле `IPython.core.page`), 658
`page_file()` (в модуле `IPython.core.page`), 658
`page_more()` (в модуле `IPython.core.page`), 659
`pager_page()` (в модуле `IPython.core.page`), 658
`parallel` (`ампубум` `IPython.core.profileapp.ProfileCreate`), 667
`parenthesis()` (в модуле `IPython.terminal.shortcuts.auto_match`), 741
`parse_argstring()` (метод `IPython.core.magic_arguments.MagicArguments`), 652
`parse_argstring()` (в модуле `IPython.core.magic_arguments`), 653
`parse_command_line()` (метод `IPython.core.profileapp.ProfileCreate`), 667
`parse_command_line()` (метод `IPython.core.profileapp.ProfileLocate`), 667
`parse_options()` (метод `IPython.core.magic.Magics`), 648
`Parser` (класс в `IPython.utils.PyColorize`), 749
`partial_tokens()` (в модуле `IPython.core.inputsplitter`), 617
`paste()` (метод `IPython.terminal.magics.TerminalMagics`), 737
`pastebin`
 magic command, 414
`PATH`, 4
`PayloadManager` (класс в `IPython.core.payload`), 659
`pdb`
 magic command, 414
`pdb` (`ампубум` `IPython.core.interactiveshell.InteractiveShell`), 634
`Pdb` (класс в `IPython.core.debugger`), 588
`pdef`
 magic command, 414
`pdef()` (метод `IPython.core.oinspect.Inspector`), 655
`PDFFormatter` (класс в `IPython.core.formatters`), 602
`pdoc`
 magic command, 414
`pdoc()` (метод `IPython.core.oinspect.Inspector`), 655
`perl`
 cell magic, 433
`pfile`
 magic command, 414
`pfile()` (метод `IPython.core.oinspect.Inspector`), 655
`pinfo`
 magic command, 415
`pinfo()` (метод `IPython.core.oinspect.Inspector`), 655
`pinfo2`
 magic command, 415
`pip`
 magic command, 415
`pkg_commit_hash()` (в модуле `IPython.utils.sysinfo`), 771
`pkg_info()` (в модуле `IPython.utils.sysinfo`), 772
`PlainTextFormatter` (класс в `IPython.core.formatters`), 600
`PNGFormatter` (класс в `IPython.core.formatters`), 601
`pop()` (метод `IPython.core.formatters.BaseFormatter`), 600
`popd`
 magic command, 415
`position_to_cursor()` (в модуле `IPython.core.completer`), 582
`post_cmd()` (метод `IPython.lib.demo.Demo`), 710
`post_execute()` (в модуле `IPython.core.events`), 594
`post_run_cell()` (в модуле `IPython.core.events`), 594
`pprint`
 magic command, 415
`pprint()` (в модуле `IPython.lib.pretty`), 724
`pre_cmd()` (метод `IPython.lib.demo.ClearMixin`), 711
`pre_cmd()` (метод `IPython.lib.demo.Demo`), 710
`pre_execute()` (в модуле `IPython.core.events`), 594
`pre_prompt_hook()` (в модуле `IPython.core.hooks`), 613
`pre_run_cell()` (в модуле `IPython.core.events`), 594
`preamble` (`ампубум` `IPython.lib.latextools.LaTeXTool`), 715
`preceding_text()` (в модуле

- IPython.terminal.shortcuts.filters*), 745
- precision
 magic command, 415
- precmd() (метод *IPython.core.debugger.Pdb*), 590
- prefilter_line() (метод *IPython.core.prefilter.PrefilterManager*), 662
- prefilter_line_info() (метод *IPython.core.prefilter.PrefilterManager*), 662
- prefilter_lines() (метод *IPython.core.prefilter.PrefilterManager*), 662
- PrefilterChecker (класс в *IPython.core.prefilter*), 664
- PrefilterError (класс в *IPython.core.prefilter*), 661
- PrefilterHandler (класс в *IPython.core.prefilter*), 665
- PrefilterManager (класс в *IPython.core.prefilter*), 661
- PrefilterTransformer (класс в *IPython.core.prefilter*), 663
- prepare_user_module() (метод *IPython.core.interactiveshell.InteractiveShell*), 634
- prepending_to_syspath (класс в *IPython.utils.syspathcontext*), 773
- preserve_keys (класс в *IPython.utils.contexts*), 753
- Pretty (класс в *IPython.display*), 691
- pretty() (метод *IPython.lib.pretty.RepresentationPrinter*), 723
- pretty() (в модуле *IPython.lib.pretty*), 724
- PrettyPrinter (класс в *IPython.lib.pretty*), 722
- previous_history_or_previous_completion() (в модуле *IPython.terminal.shortcuts*), 740
- print_figure() (в модуле *IPython.core.pylabtools*), 670
- print_list_lines() (метод *IPython.core.debugger.Pdb*), 590
- Printable (класс в *IPython.lib.pretty*), 723
- profile (атрибут *IPython.core.application.BaseIPythonApplication*), 563
- profile_completions (атрибут *IPython.core.completer.IPCompleter*), 578
- ProfileApp (класс в *IPython.core.profileapp*), 667
- ProfileAwareConfigLoader (класс в *IPython.core.application*), 562
- ProfileCreate (класс в *IPython.core.profileapp*), 667
- ProfileDir (класс в *IPython.core.profiledir*), 668
- ProfileDirError (класс в *IPython.core.profiledir*), 668
- ProfileList (класс в *IPython.core.profileapp*), 667
- ProfileLocate (класс в *IPython.core.profileapp*), 667
- profiler_output_dir (атрибут *IPython.core.completer.IPCompleter*), 578
- ProgressBar (класс в *IPython.display*), 691
- prompt_includes_vi_mode (атрибут *IPython.terminal.interactiveshell.TerminalInteractiveShell*), 731
- Prompts (класс в *IPython.terminal.prompts*), 738
- prompts_class (атрибут *IPython.terminal.interactiveshell.TerminalInteractiveShell*), 731
- PromptStripper (класс в *IPython.core.inputtransformer2*), 621
- protect_filename() (в модуле *IPython.core.completer*), 580
- provisionalcompleter() (в модуле *IPython.core.completer*), 579
- ProvisionalCompleterWarning (класс в *IPython.core.completer*), 571
- ProvisionalWarning (класс в *IPython.core.interactiveshell*), 625
- prun
 magic command, 416
- psearch
 magic command, 417
- psearch() (метод *IPython.core.oinspect.Inspector*), 656
- psource
 magic command, 418
- psource() (метод *IPython.core.oinspect.Inspector*), 656
- pt_init() (метод *IPython.terminal.debugger.TerminalPdb*), 726
- PtkHistoryAdapter (класс в *IPython.terminal.interactiveshell*), 729
- publish_display_data() (в модуле *IPython.display*), 698
- push() (метод *IPython.core.inputsplitter.InputSplitter*), 616
- push() (метод *IPython.core.inputsplitter.IPythonInputSplitter*), 619
- push() (метод *IPython.core.inputtransformer.CoroutineInputTransformer*), 618
- push() (метод *IPython.core.inputtransformer.InputTransformer*), 619
- push() (метод *IPython.core.inputtransformer.StatelessInputTransformer*), 619
- push() (метод *IPython.core.inputtransformer.TokenInputTransformer*), 619
- push() (метод *IPython.core.interactiveshell.InteractiveShell*), 635

[push_accepts_more\(\)](#) (метод `IPython.core.inputsplitter.InputSplitter`), 615
[push_accepts_more\(\)](#) (метод `IPython.core.inputsplitter.IPythonInputSplitter`), 616
[pushd](#)
 magic command, 418
[pwd](#)
 magic command, 419
[pycat](#)
 magic command, 419
[pylab](#)
 magic command, 419
[pylab](#) (ампубум `IPython.core.shellapp.InteractiveShellApp`), 673
[pylab_import_all](#) (ампубум `IPython.core.shellapp.InteractiveShellApp`), 673
[pylight\(\)](#) (в модуле `IPython.core.oinspect`), 656
[pypy](#)
 cell magic, 433
[python](#)
 cell magic, 433
[python2](#)
 cell magic, 433
[python3](#)
 cell magic, 434
[python_config_loader_class](#) (ампубум `IPython.core.application.BaseIPythonApplication`), 563
[python_func_kw_matcher\(\)](#) (метод `IPython.core.completer.IPCompleter`), 578
[python_func_kw_matches\(\)](#) (метод `IPython.core.completer.IPCompleter`), 579
[python_matches\(\)](#) (метод `IPython.core.completer.IPCompleter`), 579
[PythonOpsChecker](#) (класс в `IPython.core.prefilter`), 665
[PYTHONSTARTUP](#), 372, 801
Q
[quick](#) (ампубум `IPython.terminal.ipapp.TerminalIPythonApp`), 735
[quick_completer\(\)](#) (в модуле `IPython.core.completerlib`), 584
[quickref](#)
 magic command, 420
[quit\(\)](#) (в модуле `IPython.terminal.shortcuts`), 740
R
[raise_error\(\)](#) (метод `IPython.core.interactiveshell.ExecutionResult`), 625
[raw_reset\(\)](#) (метод `IPython.core.inputsplitter.IPythonInputSplitter`), 617
[raw_string_braces\(\)](#) (в модуле `IPython.terminal.shortcuts.auto_match`), 742
[raw_string_bracket\(\)](#) (в модуле `IPython.terminal.shortcuts.auto_match`), 742
[raw_string_parenthesis\(\)](#) (в модуле `IPython.terminal.shortcuts.auto_match`), 742
[RawStringLiteral](#) (класс в `IPython.lib.pretty`), 724
[RawText](#) (класс в `IPython.lib.pretty`), 723
[re_mark\(\)](#) (в модуле `IPython.lib.demo`), 712
[read_py_file\(\)](#) (в модуле `IPython.utils.openpy`), 765
[read_py_url\(\)](#) (в модуле `IPython.utils.openpy`), 765
[readline_like_completions\(\)](#) (в модуле `IPython.terminal.shortcuts.filters`), 745
[real_name\(\)](#) (в модуле `IPython.core.magic_arguments`), 653
[recall](#)
 magic command, 420
[record_magic\(\)](#) (в модуле `IPython.core.magic`), 649
[rectify_completions\(\)](#) (в модуле `IPython.core.completer`), 581
[reformat_and_execute\(\)](#) (в модуле `IPython.terminal.shortcuts`), 740
[reformat_text_before_cursor\(\)](#) (в модуле `IPython.terminal.shortcuts`), 740
[register\(\)](#) (метод `IPython.core.events.EventManager`), 593
[register\(\)](#) (метод `IPython.core.magic.MagicsManager`), 646
[register\(\)](#) (в модуле `IPython.terminal.pt_inputhooks`), 535
[register_alias\(\)](#) (метод `IPython.core.magic.MagicsManager`), 646
[register_checker\(\)](#) (метод `IPython.core.prefilter.PrefilterManager`), 662
[register_function\(\)](#) (метод `IPython.core.magic.MagicsManager`), 646
[register_handler\(\)](#) (метод `IPython.core.prefilter.PrefilterManager`), 662

[register_lazy\(\)](#) (*метод* [IPython.core.magic.MagicsManager](#)), 647
[register_magic_function\(\)](#) (*метод* [IPython.core.interactiveshell.InteractiveShell](#)), 635
[register_post_execute\(\)](#) (*метод* [IPython.core.interactiveshell.InteractiveShell](#)), 635
[register_transformer\(\)](#) (*метод* [IPython.core.prefilter.PrefilterManager](#)), 662
[rehashx](#)
 magic command, 420
[reload\(\)](#) (*метод* [IPython.display.Audio](#)), 684
[reload\(\)](#) (*метод* [IPython.display.DisplayObject](#)), 686
[reload\(\)](#) (*метод* [IPython.display.Image](#)), 690
[reload\(\)](#) (*метод* [IPython.display.Video](#)), 693
[reload\(\)](#) (*метод* [IPython.lib.demos.Demo](#)), 710
[reload\(\)](#) (*метод* [IPython.lib.demos.LineDemo](#)), 711
[reload\(\)](#) (*в модуле* [IPython.lib.deepreload](#)), 705
[reload_ext](#)
 magic command, 420
[reload_extension\(\)](#) (*метод* [IPython.core.extensions.ExtensionManager](#)), 596
[remove\(\)](#) (*метод* [IPython.lib.backgroundjobs.BackgroundJobManager](#)), 702
[remove_builtin\(\)](#) (*метод* [IPython.core.builtin_trap.BuiltinTrap](#)), 566
[remove_comments\(\)](#) (*в модуле* [IPython.core.inputsplitters](#)), 618
[replace_import_hook\(\)](#) (*в модуле* [IPython.lib.deepreload](#)), 705
[RepresentationPrinter](#) (*класс* *в* [IPython.lib.pretty](#)), 723
[reraise_ipython_extension_failures](#) (*атрибут* [IPython.core.shellapp.InteractiveShellApp](#)), 673
[rerun](#)
 magic command, 420
[rerun_pasted\(\)](#) (*метод* [IPython.terminal.magics.TerminalMagics](#)), 738
[reset](#)
 magic command, 421
[reset\(\)](#) (*метод* [IPython.core.history.HistoryManager](#)), 610
[reset\(\)](#) (*метод* [IPython.core.inputsplitters.InputSplitter](#)), 616
[reset\(\)](#) (*метод* [IPython.core.inputsplitters.IPythonInputSplitter](#)), 617
[reset\(\)](#) (*метод* [IPython.core.inputtransformer.CoroutineInputTransformer](#)), 619
[reset\(\)](#) (*метод* [IPython.core.inputtransformer.InputTransformer](#)), 618
[reset\(\)](#) (*метод* [IPython.core.inputtransformer.StatelessInputTransformer](#)), 619
[reset\(\)](#) (*метод* [IPython.core.inputtransformer.TokenInputTransformer](#)), 619
[reset\(\)](#) (*метод* [IPython.core.interactiveshell.InteractiveShell](#)), 635
[reset\(\)](#) (*метод* [IPython.lib.demos.Demo](#)), 710
[reset_buffer\(\)](#) (*в модуле* [IPython.terminal.shortcuts](#)), 740
[reset_compiler_flags\(\)](#) (*метод* [IPython.core.compilerop.CachingCompiler](#)), 568
[reset_completer\(\)](#) (*в модуле* [IPython.core.completerlib](#)), 584
[reset_search_buffer\(\)](#) (*в модуле* [IPython.terminal.shortcuts](#)), 740
[reset_selective](#)
 magic command, 422
[reset_selective\(\)](#) (*метод* [IPython.core.interactiveshell.InteractiveShell](#)), 636
[restore_sys_module_state\(\)](#) (*метод* [IPython.core.interactiveshell.InteractiveShell](#)), 636
[restore_term_title\(\)](#) (*в модуле* [IPython.utils.terminal](#)), 775
[result\(\)](#) (*метод* [IPython.lib.backgroundjobs.BackgroundJobManager](#)), 702
[resume_hinting\(\)](#) (*в модуле* [IPython.terminal.shortcuts.auto_suggest](#)), 743
[retina_figure\(\)](#) (*в модуле* [IPython.core.pylabtools](#)), 670
[retrieve_alias\(\)](#) (*метод* [IPython.core.alias.AliasManager](#)), 561
[rewrite_prompt_tokens\(\)](#) (*метод* [MyPrompts](#)), 513
[RichOutput](#) (*класс* *в* [IPython.utils.capture](#)), 749
[RichPromptDisplayHook](#) (*класс* *в* [IPython.terminal.prompts](#)), 738
[ruby](#)
 cell magic, 434
[run](#)
 magic command, 423
[run\(\)](#) (*метод* [IPython.core.history.HistorySavingThread](#)), 611
[run\(\)](#) (*метод* [IPython.lib.backgroundjobs.BackgroundJobBase](#)), 702
[run_in_parallel_nodes\(\)](#) (*метод* [IPython.core.interactiveshell.InteractiveShell](#)), 617

[636](#)
[run_cell\(\)](#) (*метод* [IPython.core.interactiveshell.InteractiveShell](#)), [752](#)
[636](#) [IPython.core.interactiveshell.InteractiveShell](#)),
[run_cell\(\)](#) (*метод* [IPython.lib.demos.Demo](#)), [710](#) [639](#)
[run_cell\(\)](#) (*метод* [IPython.lib.demos.IPythonDemo](#)), [set_colors\(\)](#) (*метод* [IPython.core.debugger.Pdb](#)),
[710](#) [590](#)
[run_cell_async\(\)](#) (*метод* [set_colors\(\)](#) (*метод* [IPython.core.ultratb.TBTools](#)), [677](#)
[637](#) [set_completer_frame\(\)](#) (*метод* [IPython.core.interactiveshell.InteractiveShell](#)),
[run_cell_magic\(\)](#) (*метод* [IPython.core.interactiveshell.InteractiveShell](#)), [639](#)
[637](#) [set_custom_completer\(\)](#) (*метод* [IPython.core.interactiveshell.InteractiveShell](#)),
[run_code\(\)](#) (*метод* [IPython.core.interactiveshell.InteractiveShell](#)), [639](#)
[637](#) [639](#)
[run_line_magic\(\)](#) (*метод* [set_custom_exc\(\)](#) (*метод* [IPython.core.interactiveshell.InteractiveShell](#)), [639](#)
[638](#) [639](#)
[runcode\(\)](#) (*метод* [IPython.core.interactiveshell.InteractiveShell](#)), [638](#)
[638](#) [magic command](#), [427](#)
[RuntimeBinding](#) (*класс* [set_hook\(\)](#) (*метод* [IPython.core.interactiveshell.InteractiveShell](#)), [640](#)
[IPython.terminal.shortcuts](#)), [739](#)
[set_ip\(\)](#) (*метод* [IPython.core.autocall.IPyAutocall](#)), [565](#)
S
[safe_execfile\(\)](#) (*метод* [set_matplotlib_close\(\)](#) (*в* *модуле* [IPython.core.interactiveshell.InteractiveShell](#)), [IPython.display](#)), [699](#)
[638](#) [set_matplotlib_formats\(\)](#) (*в* *модуле* [IPython.display](#)), [699](#)
[safe_execfile_ipy\(\)](#) (*метод* [set_mode\(\)](#) (*метод* [IPython.core.ultratb.FormattedTB](#)), [680](#)
[638](#) [680](#)
[safe_hasattr\(\)](#) (*в* *модуле* [IPython.utils.dir2](#)), [755](#) [set_next_input\(\)](#) (*метод* [IPython.core.interactiveshell.InteractiveShell](#)), [640](#)
[safe_run_module\(\)](#) (*метод* [set_term_title\(\)](#) (*в* *модуле* [IPython.utils.terminal](#)), [775](#)
[639](#) [set_trace\(\)](#) (*метод* [IPython.core.debugger.Pdb](#)), [590](#)
[save](#) [magic command](#), [425](#)
[save_sys_module_state\(\)](#) (*метод* [set_trace\(\)](#) (*в* *модуле* [IPython.core.debugger](#)), [591](#)
[639](#) [set_trace\(\)](#) (*в* *модуле* [IPython.terminal.debugger](#)), [726](#)
sc [magic command](#), [425](#)
scite() (*в* *модуле* [IPython.lib.editorhooks](#)), [712](#)
ScribdDocument (*класс* *в* [IPython.display](#)), [691](#)
script [cell magic](#), [434](#)
[search\(\)](#) (*метод* [IPython.core.history.HistoryAccessor](#)), [608](#)
[seek\(\)](#) (*метод* [IPython.lib.demos.Demo](#)), [710](#)
[select_figure_formats\(\)](#) (*в* *модуле* [IPython.core.pylabtools](#)), [671](#)
Sentinel (*класс* *в* [IPython.utils.sentinel](#)), [769](#)
SeparateUnicode (*класс* *в* [IPython.core.interactiveshell](#)), [625](#)
[set_active_scheme\(\)](#) (*метод* [should_run_async\(\)](#) (*метод* [IPython.core.interactiveshell.InteractiveShell](#)), [731](#)
[IPython.utils.coloransi.ColorSchemeTable](#)), [731](#)

640
 show() (метод *IPython.lib.demo.Demo*), 710
 show() (метод *IPython.utils.capture.CapturedIO*), 750
 show_all() (метод *IPython.lib.demo.Demo*), 710
 show_exception_only() (метод *IPython.core.ultratb.ListTB*), 678
 show_hidden() (в модуле *IPython.utils.wildcard*), 785
 show_in_pager() (в модуле *IPython.core.hooks*), 613
 show_linewise_tokens() (в модуле *IPython.core.inputtransformer2*), 624
 show_rewritten_input (атрибут *IPython.core.interactiveshell.InteractiveShell*), 640
 show_usage() (метод *IPython.core.interactiveshell.InteractiveShell*), 640
 show_usage_error() (метод *IPython.core.interactiveshell.InteractiveShell*), 641
 showindentationerror() (метод *IPython.core.interactiveshell.InteractiveShell*), 641
 showsyntaxerror() (метод *IPython.core.interactiveshell.InteractiveShell*), 641
 showtraceback() (метод *IPython.core.interactiveshell.InteractiveShell*), 641
 simple_prompt (атрибут *IPython.terminal.interactiveshell.TerminalInteractiveShell*), 733
 SimpleCompletion (класс в *IPython.core.completer*), 572
 SimpleMatcherResult (класс в *IPython.core.completer*), 572
 single_quote() (в модуле *IPython.terminal.shortcuts.auto_match*), 741
 skip_doctest() (в модуле *IPython.testing.skipdoctest*), 748
 skip_over() (в модуле *IPython.terminal.shortcuts.auto_match*), 742
 slide() (в модуле *IPython.lib.demo*), 712
 SList (класс в *IPython.utils.text*), 776
 soft_define_alias() (метод *IPython.core.alias.AliasManager*), 561
 sort() (метод *IPython.utils.text.SList*), 777
 sort_checkers() (метод *IPython.core.prefilter.PrefilterManager*), 663
 sort_transformers() (метод *IPython.core.prefilter.PrefilterManager*), 663
 source_reset() (метод *IPython.core.inputsplitter.InputSplitter*), 616
 source_reset() (метод *IPython.core.inputsplitter.IPythonInputSplitter*), 617
 source_to_unicode() (в модуле *IPython.utils.openpy*), 765
 space_for_menu (атрибут *IPython.terminal.interactiveshell.TerminalInteractiveShell*), 733
 SpaceInInput (класс в *IPython.core.interactiveshell*), 625
 sphinx_options() (в модуле *IPython.utils.decorators*), 755
 sphinxify() (в модуле *IPython.core.interactiveshell*), 643
 sphinxify_docstring (атрибут *IPython.core.interactiveshell.InteractiveShell*), 641
 split_line() (метод *IPython.core.completer.CompletionSplitter*), 573
 split_user_input() (в модуле *IPython.core.splitinput*), 675
 stage_default_config_file() (метод *IPython.core.application.BaseIPythonApplication*), 563
 stage_default_config_file() (метод *IPython.core.profileapp.ProfileCreate*), 667
 start() (метод *IPython.core.historyapp.HistoryApp*), 612
 start() (метод *IPython.core.historyapp.HistoryClear*), 612
 start() (метод *IPython.core.historyapp.HistoryTrim*), 612
 start() (метод *IPython.core.profileapp.ProfileApp*), 667
 start() (метод *IPython.core.profileapp.ProfileList*), 667
 start() (метод *IPython.core.profileapp.ProfileLocate*), 667
 start() (метод *IPython.terminal.ipapp.LocateIPythonApp*), 735
 start() (метод *IPython.terminal.ipapp.TerminalIPythonApp*), 735
 start_event_loop_qt4() (в модуле *IPython.lib.guisupport*), 714
 start_event_loop_wx() (в модуле *IPython.lib.guisupport*), 714

start_ipython() (в модуле *IPython*), 559
start_kernel() (в модуле *IPython*), 559
StatelessInputTransformer (класс в *IPython.core.inputtransformer*), 619
status() (метод *IPython.lib.backgroundjobs.BackgroundJobs*), 702
stb2text() (метод *IPython.core.ultratb.FormattedTB*), 680
stb2text() (метод *IPython.core.ultratb.SyntaxTB*), 681
stb2text() (метод *IPython.core.ultratb.TBTools*), 677
stderr (*IPython.utils.capture.CapturedIO* property), 750
StdinNotImplementedError (класс в *IPython.core.error*), 592
stdout (*IPython.utils.capture.CapturedIO* property), 750
stop() (метод *IPython.core.history.HistorySavingThread*), 611
stop_here() (метод *IPython.core.debugger.Pdb*), 590
store() (метод *IPython.extensions.storemagic.StoreMagic*), 522
store_inputs() (метод *IPython.core.history.HistoryManager*), 610
store_or_execute() (метод *IPython.terminal.magics.TerminalMagics*), 738
store_output() (метод *IPython.core.history.HistoryManager*), 610
store_string() (метод *IPython.terminal.interactiveshell.PtkHistoryAdapter*), 730
StrDispatch (класс в *IPython.utils.strdispatch*), 770
strip_ansi() (в модуле *IPython.utils.text*), 780
strip_email_quotes() (в модуле *IPython.utils.text*), 779
strip_encoding_cookie() (в модуле *IPython.utils.openpy*), 765
strip_indentation() (в модуле *IPython.core.debugger*), 591
Struct (класс в *IPython.utils.ipstruct*), 761
structured_traceback() (метод *IPython.core.ultratb.AutoFormattedTB*), 680
structured_traceback() (метод *IPython.core.ultratb.FormattedTB*), 680
structured_traceback() (метод *IPython.core.ultratb.ListTB*), 678
structured_traceback() (метод *IPython.core.ultratb.SyntaxTB*), 681
structured_traceback() (метод *IPython.core.ultratb.TBTools*), 677
structured_traceback() (метод *IPython.core.ultratb.VerboseTB*), 679
suspend() (в модуле *IPython.terminal.shortcuts.filters*), 744
suppress_competing_matchers (атрибут *IPython.core.completer.IPCompleter*), 579
suspend_to_bg() (в модуле *IPython.terminal.shortcuts*), 740
svg
 cell magic, 435
SVG (класс в *IPython.display*), 691
SVGFormatter (класс в *IPython.core.formatters*), 601
swap_autosuggestion_down() (в модуле *IPython.terminal.shortcuts.auto_suggest*), 744
swap_autosuggestion_up() (в модуле *IPython.terminal.shortcuts.auto_suggest*), 744
switch_doctest_mode() (метод *IPython.terminal.interactiveshell.TerminalInteractiveShell*), 733
switch_log() (метод *IPython.core.logger.Logger*), 644
sx
 magic command, 427
synchronize_with_editor() (в модуле *IPython.core.hooks*), 613
SyntaxTB (класс в *IPython.core.ultratb*), 681
sys_info() (в модуле *IPython.utils.sysinfo*), 772
system
 magic command, 428
system() (метод *IPython.core.interactiveshell.InteractiveShell*), 641
system() (метод *IPython.terminal.interactiveshell.TerminalInteractiveShell*), 733
system_piped() (метод *IPython.core.interactiveshell.InteractiveShell*), 641
system_raw() (метод *IPython.core.interactiveshell.InteractiveShell*), 641
SystemAssign (класс в *IPython.core.inputtransformer2*), 622
T
target_outdated() (в модуле *IPython.utils.path*), 767
target_update() (в модуле *IPython.utils.path*), 767
tb
 magic command, 428

TBTools (класс в <i>IPython.core.ultratb</i>), 677	<i>IPython.core.inputtransformer2.EscapedCommand</i>), 622
Tee (класс в <i>IPython.utils.io</i>), 759	
temp_pyfile() (в модуле <i>IPython.utils.io</i>), 760	transform() (метод
TemporaryWorkingDirectory (класс в <i>IPython.utils.tempdir</i>), 774	<i>IPython.core.inputtransformer2.HelpEnd</i>), 623
term_title (атрибут <i>transform()</i> (метод <i>IPython.terminal.embed.InteractiveShellEmbed</i>), 728	<i>IPython.core.inputtransformer2.MagicAssign</i>), 622
term_title (атрибут <i>transform()</i> (метод <i>IPython.terminal.interactiveshell.TerminalInteractiveShell</i>), 733	<i>IPython.core.inputtransformer2.SystemAssign</i>), 622
term_title_format (атрибут <i>transform()</i> (метод <i>IPython.terminal.interactiveshell.TerminalInteractiveShell</i>), 733	<i>IPython.core.inputtransformer2.TokenTransformBase</i>), 622
TermColors (класс в <i>IPython.utils.coloransi</i>), 751	transform() (метод
TerminalInteractiveShell (класс в <i>IPython.terminal.interactiveshell</i>), 730	<i>IPython.core.prefilter.PrefilterTransformer</i>), 663
TerminalIPythonApp (класс в <i>IPython.terminal.ipapp</i>), 735	transform_ast() (метод <i>IPython.core.interactiveshell.InteractiveShell</i>), 641
TerminalMagics (класс в <i>IPython.terminal.magics</i>), 736	transform_cell() (метод <i>IPython.core.inputsplitter.IPythonInputSplitter</i>), 617
TerminalPdb (класс в <i>IPython.terminal.debugger</i>), 725	transform_cell() (метод <i>IPython.core.inputtransformer2.TransformerManager</i>), 623
Text (класс в <i>IPython.lib.pretty</i>), 723	transform_cell() (метод <i>IPython.core.interactiveshell.InteractiveShell</i>), 642
text() (метод <i>IPython.core.ultratb.TBTools</i>), 677	transform_line() (метод <i>IPython.core.prefilter.PrefilterManager</i>), 663
text() (метод <i>IPython.lib.pretty.PrettyPrinter</i>), 723	TransformerManager (класс в <i>IPython.core.inputtransformer2</i>), 623
text_repr() (в модуле <i>IPython.core.ultratb</i>), 682	transforms (IPython.core.prefilter.PrefilterManager property), 663
TextDisplayObject (класс в <i>IPython.display</i>), 692	transforms (IPython.core.inputsplitter.IPythonInputSplitter property), 617
time	transforms_in_use (IPython.core.inputsplitter.IPythonInputSplitter property), 617
magic command, 428	trigger() (метод <i>IPython.core.events.EventManager</i>), 593
timeit	true_color (атрибут <i>IPython.terminal.interactiveshell.TerminalInteractiveShell</i>), 734
magic command, 429	
timeoutlen (атрибут <i>transform()</i> (метод <i>IPython.terminal.interactiveshell.TerminalInteractiveShell</i>), 733	try_import() (в модуле <i>IPython.core.completerlib</i>), 584
timing() (в модуле <i>IPython.utils.timing</i>), 782	TryNext (класс в <i>IPython.core.error</i>), 592
timings() (в модуле <i>IPython.utils.timing</i>), 782	ttimeoutlen (атрибут <i>IPython.terminal.interactiveshell.TerminalInteractiveShell</i>), 734
timings_out() (в модуле <i>IPython.utils.timing</i>), 782	
tkinter_clipboard_get() (в модуле <i>IPython.lib.clipboard</i>), 704	
toggle_set_term_title() (в модуле <i>IPython.utils.terminal</i>), 775	
token (атрибут <i>IPython.core.completer.CompletionContext</i>), 572	
token_at_cursor() (в модуле <i>IPython.utils.tokenutil</i>), 783	
TokenInputTransformer (класс в <i>IPython.core.inputtransformer</i>), 619	
tokens (атрибут <i>IPython.lib.lexers.IPythonPartialTracebackLexer</i>), 717	
TokenTransformBase (класс в <i>IPython.core.inputtransformer2</i>), 621	
transform() (метод	

U

unalias

magic command, 430

undoc() (в модуле *IPython.utils.decorators*), 754unescape_glob() (в модуле *IPython.utils.path*), 767unicode_name_matcher() (метод *IPython.core.completer.IPCompleter*), 579unicode_name_matches() (статический метод *IPython.core.completer.IPCompleter*), 579unicode_names (*IPython.core.completer.IPCompleter* property), 579uniq_stable() (в модуле *IPython.utils.data*), 754

unload_ext

magic command, 430

unload_extension() (метод *IPython.core.extensions.ExtensionManager*), 596unregister() (метод *IPython.core.events.EventManager*), 593unregister_checker() (метод *IPython.core.prefilter.PrefilterManager*), 663unregister_handler() (метод *IPython.core.prefilter.PrefilterManager*), 663unregister_transformer() (метод *IPython.core.prefilter.PrefilterManager*), 663up_and_update_hint() (в модуле *IPython.terminal.shortcuts.auto_suggest*), 743update() (метод *IPython.display.DisplayHandle*), 685update_display() (в модуле *IPython.display*), 700UsageError (класс в *IPython.core.error*), 592use_breqn (ампубум *IPython.lib.latextools.LaTeXTool*), 715use_jedi (ампубум *IPython.core.completer.Completer*), 575user_expressions() (метод *IPython.core.interactiveshell.InteractiveShell*), 642utc_aware() (в модуле *IPython.utils.tz*), 784utcoffset() (метод *IPython.utils.tz.tzUTC*), 784

V

validate() (метод *IPython.core.alias.Alias*), 560validate_type() (в модуле *IPython.core.magic*), 649var_expand() (метод *IPython.core.interactiveshell.InteractiveShell*), 642verbose_crash (ампубум *IPython.core.application.BaseIPythonApplication*), 564VerboseTB (класс в *IPython.core.ultratb*), 679Video (класс в *IPython.display*), 692VimeoVideo (класс в *IPython.display*), 693

W

warn_venv (ампубум *IPython.core.interactiveshell.InteractiveShell*), 642wayland_clipboard_get() (в модуле *IPython.lib.clipboard*), 704

who

magic command, 430

who_ls magic command, 431

whos magic command, 431

win32_clipboard_get() (в модуле *IPython.lib.clipboard*), 704wrap() (метод класса *IPython.core.inputtransformer.InputTransformer*), 618wrap_paragraphs() (в модуле *IPython.utils.text*), 779write() (метод *IPython.utils.io.Tee*), 759write_format_data() (метод *IPython.terminal.prompts.RichPromptDisplayHook*), 739write_output_prompt() (метод *IPython.terminal.prompts.RichPromptDisplayHook*), 739write_payload() (метод *IPython.core.payload.PayloadManager*), 659

writefile cell magic, 435

writeout_cache() (метод *IPython.core.history.HistoryAccessor*), 608writeout_cache() (метод *IPython.core.history.HistoryManager*), 610

X

xdel

magic command, 432

xmode

magic command, 432

xmode (ампубум *IPython.core.interactiveshell.InteractiveShell*), 642

Y

`yapf_reformat_handler()` (в модуле `IPython.terminal.interactiveshell`), [734](#)

`YouTubeVideo` (класс в `IPython.display`), [693](#)

Z

`ZMQExitAutocall` (класс в `IPython.core.autocall`), [565](#)